

UNCLASSIFIED

AD NUMBER	
AD004338	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	restricted
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Distribution authorized to DoD only; Test and Evaluation; FEB 1953. Other requests shall be referred to U.S. Naval Proving Ground, Dahlgren, VA. Pre-dates formal DoD distribution statements. Treat as DoD only.
AUTHORITY	
E.O. 10501, 5 Nov 1953; USNSWC ltr, 26 Apr 1976	

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AD 4338

*Reproduced
by the*

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



CLASSIFICATION CHANGED
TO ~~UNCLASSIFIED~~
FROM ~~RESTRICTED~~

change
Classification cancelled in accordance with
Executive Order 10601 issued 6 November 1953

Handley & Genshagen

Document Service Center
Armed Services Tech. Info Agency

UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

AD No. 4338
ASTIA FILE COPY

RESTRI
SECURITY INFO

U. S. NAVAL PROVING GROUND
DAHLGREN, VIRGINIA

REPORT NO. 1093

BOMBS AND ASSOCIATED COMPONENTS

3rd Partial Report

TESTS OF FIRE BOMB MK 77 MOD 0
MODIFIED TO 75 GALLON CAPACITY

FINAL Report

Copy No. _____

Task

Assignment NP6-Re3c-321-1-53

Classification RESTRICTED
SECURITY INFORMATION

RECEIVED

NOV 28 AM 9 19

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

PART A

SYNOPSIS

1. This is the final report on catapult and arrested landing and Douglas bomb ejector tests of the Mk 77 Mod O Fire Bomb modified to 75 gallon capacity. The purpose of this test was to determine the maximum accelerations in the fore and aft and side directions this bomb will withstand without causing deformation that would be detrimental to the operation of the bomb and to determine whether the bomb will withstand the forces applied by Douglas bomb ejector without deformation that would be detrimental to the operation of the bomb.

2. The Mk 77 Mod O Fire Bomb modified to 75 gallon capacity withstood 15.1 g's acceleration in the fore and aft direction and 9.7 g's sideways without deformation. This bomb satisfactorily withstood the Douglas bomb ejector forces with only minor deformation.

3. It is concluded that:

a. The Mk 77 Mod O Fire Bomb modified to 75 gallon capacity will withstand an acceleration of 15.1 g's in the fore and aft direction and 9.7 g's sideways without suffering deformation which would be detrimental to the operation of the bomb.

b. The modified Mk 77 Mod O Fire Bomb is suitable for use with the Douglas bomb ejector.

c. The modified Mk 77 Mod O Fire Bomb should be suitable for most operational catapult take-offs and arrested landings although it does not meet the general acceleration requirements for all externally carried aircraft stores as listed in reference (c).

4. It is recommended that a seal be developed for closing the end bulkheads which is more effective than the shaft seal used on the samples tested.

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

TABLE OF CONTENTS

	<u>Page</u>
SYNOPSIS	1
TABLE OF CONTENTS.	2
AUTHORITY.	3
REFERENCES	3
BACKGROUND	3
OBJECT OF TEST	3
PERIOD OF TEST	3
DESCRIPTION OF ITEMS UNDER TEST.	4
DESCRIPTION OF TEST EQUIPMENT.	4
PROCEDURE.	4
RESULTS AND DISCUSSION	5
CONCLUSIONS.	6
RECOMMENDATIONS.	6
DISPOSITION OF MATERIAL.	6
APPENDIX A - TABULATED TEST DATA	TABLE I
APPENDIX B - NPG PHOTOGRAPH.	FIGURE 1
APPENDIX C - DISTRIBUTION.	1-2 (Incl)

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

PART B

INTRODUCTION

1. AUTHORITY:

These tests were authorized by reference (a) and conducted in accordance with reference (b).

2. REFERENCES:

- a. BUORD Conf ltr NP9-Re3c-BEK:mp Ser 42777 of 29 Jul 1952
- b. BUORD Rest ltr Re3c-RMN;gg F41-6 of 25 Nov 1952
- c. BUORD Rest ltr NP9-Re3c-LME:edb of 31 Aug 1951

3. BACKGROUND:

A requirement exists for a Fire Bomb, suitable for suspension on the Aero 14A bomb rack. The Mk 77 Mod O Fire Bomb has been modified to 75 gallon capacity for this purpose. Reference (b) was written to accomplish testing of this modified fire bomb.

4. OBJECT OF TEST:

The object of this test was to determine the maximum accelerations which this modified bomb will withstand in the fore and aft and side directions without causing deformation which would be detrimental to the operation of the bomb. It was further desired to determine whether the bomb will withstand the forces applied by the Douglas bomb ejector without deformation that would be detrimental to the operation of the bomb.

5. PERIOD OF TEST:

- | | |
|--------------------------------------|-------------------------------------|
| a. Date of Project Letter | 25 November 1952 |
| b. Dates Necessary Material Received | 4 December 1952
16 December 1952 |
| c. Date Commenced Test | 9 December 1952 |
| d. Date Test Completed | 18 December 1952 |

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod 0 Modified to 75 gallon Capacity

PART C

DETAILS OF TEST

6. DESCRIPTION OF ITEMS UNDER TEST:

The Mk 77 Mod 0 Fire Bomb was modified to 75 gallons capacity by shortening the center section to 23 inches. The front and rear sections were then welded to the center section. This eliminated the circumferential gasketed seams and eliminated reliance on the longitudinal tie-rod through the center of the bomb for holding the three (3) sections together and providing sealing pressure. The resulting welded bomb derives its strength from its continuous, stressed skin construction. The modified bomb is approximately 90 inches long and remains 19 inches in diameter. The bombs were water filled for the catapult and arrested landing and Douglas bomb ejector tests. Inert M23 igniters and arming wires were installed for the catapult and arrested landing tests.

7. DESCRIPTION OF TEST EQUIPMENT:

a. The acceleration tests were conducted on the Catapult and Arrested Landing Facility of the Laboratory Services Division of the Aviation Ordnance Department. This consists of a car traveling on a track launched by a catapult Type P, Mk 6 Mod 0, and stopped by an arresting gear unit Mk 4.

b. The bomb ejector test was conducted on the Douglas Bomb Ejector Facility. This consists of a Douglas bomb ejector mounted on the bomb ejector tower. A Mk 1 Mod 2 Bomb Ejector Cartridge was used with the modified Mk 77 Mod 0 Fire Bomb.

8. PROCEDURE:

a. Acceleration Tests:

The modified Mk 77 Mod 0 Fire Bombs were filled with water and two (2) inert M23 igniters and arming wires installed. The bombs were mounted on the catapult car and sway braced to simulate operational use. The bomb was accelerated with the nose forward for fore and aft loading and with the longitudinal axis perpendicular to the motion of the car for side loading. Appendix (A) lists the complete schedule of accelerations to which the fire bombs were subjected.

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

b. Douglas Bomb Ejector Test:

The Douglas bomb ejector was mounted on the bomb ejector tower. The modified Mk 77 Mod O Fire Bomb was filled with water and hoisted into position and latched on the bomb ejector with the nose down. A 35mm Mitchell motion picture camera was set up so that photographs could be made of the fire bomb in the interval between the firing of the ejector and the impact of the bomb with the ground. A Mk 1 Mod 2 Bomb Ejector Cartridge was loaded in the ejector and the ejector was fired after starting camera operation to observe the complete fall of the bomb.

9. RESULTS AND DISCUSSION:

All accelerations listed are the equivalent values for this fire bomb filled with napalm mixture.

a. There was a slight water spray from the filling caps of the modified Mk 77 Mod O Fire Bomb at 15.1 g's when the bomb was catapulted with the nose forward. The fire bomb was considered satisfactory for this acceleration, which was the maximum attainable, in the fore and aft direction.

b. There was a slight water leakage from the seal between the through rod and the end bulkheads after the modified Mk 77 Mod O Fire Bomb was catapulted at 9.7 g's sideways. The bomb was still considered satisfactory.

c. The welded seam between the forward and center sections of the modified Mk 77 Mod O Fire Bomb split when the bomb was catapulted at 11.4 g's sideways.

d. In all accelerations of the modified Mk 77 Mod O Fire Bomb in both the fore and aft and side directions, no arming or displacement of the igniters or displacement of the arming wires occurred.

e. The modified Mk 77 Mod O Fire Bomb was no more than superficially damaged by the bomb ejector foot. This superficial damage is shown in Figure 1.

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

PART D

CONCLUSIONS

10. It is concluded that:

a. The Mk 77 Mod O Fire Bomb modified to 75 gallon capacity will withstand an acceleration of 15.1 g's in the fore and aft direction and 9.7 g's sideways without suffering deformation which would be detrimental to the operation of the bomb.

b. The modified Mk 77 Mod O Fire Bomb is suitable for use with the Douglas bomb ejector.

c. The modified Mk 77 Mod O Fire Bomb should be suitable for most operational catapult take-offs and arrested landings although it does not meet the general acceleration requirements for all externally carried aircraft stores as listed in reference (c).

PART E

RECOMMENDATIONS

11. It is recommended that a seal be developed for closing the end bulkheads which is more effective than the shaft seal used on the unmodified Mk 77 Mod O Fire Bomb and the samples tested. Presumably this bulkhead could be made solid since the need for the central through rod does not exist. It should be noted that the advantageous nesting ratio of the Mk 77 Mod O Fire Bomb has been lost.

PART F

DISPOSITION OF MATERIAL

12. The two (2) damaged fire bombs were returned to the Ammunition Division of the Armament Department for disposal as scrap. Instructions are requested for the disposition of the third, undamaged fire bomb.

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod 0 Modified to 75 gallon Capacity

The tests upon which this report is based were conducted by:

L. P. MITCHELL, Lieutenant, USNR
Laboratory Services Officer
Aviation Ordnance Department

This report was prepared by:

L. P. MITCHELL, Lieutenant, USNR
Laboratory Services Officer
Aviation Ordnance Department

This report was reviewed by:

J. C. TALLEY, Director of Research
Aviation Ordnance Department
J. D. WATSON, Lieutenant Commander, USN
Assistant Aviation Ordnance Officer
Aviation Ordnance Department
F. A. NUSOM, Captain, USN
Aviation Ordnance Officer
Aviation Ordnance Department
C. C. BRAMBLE, Director of Research, Ordnance Group

APPROVED: J. F. BYRNE
Captain, USN
Commander, Naval Proving Ground



E. A. RUCKNER
Captain, USN
Ordnance Officer
By direction

RESTRICTED

NPG REPORT NO. 1093

U. S. NAVAL PROVING GROUND
DAHLGREN, VIRGINIA

Fifty-third Partial Report
on
Bombs and Associated Components

Final Report
on
Tests of Fire Bomb Mk 77 Mod 0
Modified to 75 gallon Capacity

Project No.: NPG-Re3c-321-1-53
No. of Pages: 7

Date:

FEB 26 1953

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

TABLE I

Tabulated Test Data

Acceleration Tests of Fire Bomb Mk 77 Mod O
Modified to 75 gallon Capacity

<u>Date</u>	<u>Direction</u>	<u>Acceleration in g's*</u>	<u>Results</u>
12-9-52	Fore & Aft	6.1	No Change
12-9-52	Fore & Aft	7.6	No Change
12-9-52	Fore & Aft	9.0	No Change
12-9-52	Fore & Aft	10.4	Slight water spray from filling caps. O.K.
12-9-52	Fore & Aft	11.9	Some water spray from filling caps. O.K.
12-18-52	Side	3.0	No Change
12-18-52	Side	4.5	No Change
12-18-52	Side	6.1	No Change
12-18-52	Side	7.6	Water leak from thru rod seals. O.K.
12-18-52	Side	9.0	Welded seam split at bottom.

* These accelerations may be multiplied by 1.27 to give equivalent values for the bomb filled with napalm mixture.

RESTRICTED
SECURITY INFORMATION

APPENDIX A

NP9-52121

Mk 77 Mod 0

10 December 1952

fire bomb modified to 75 gallon capacity after firing from Douglas bomb ejector. Note lack of deformation of all parts.

Figure 1

RESTRICTED
SECURITY INFORMATION



RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod 0 Modified to 75 gallon Capacity

DISTRIBUTION

Bureau of Ordnance	
Ad3	1
Re3	1
Re3c	6
Chief of Ordnance	
Department of the Army	
Attn: ORDTX-AR	1
Commanding General	
Aberdeen Proving Ground, Aberdeen, Maryland	
Attn: Technical Information Section	
Development and Proof Services	1
Commander, Operational Development Force	
U. S. Atlantic Fleet, U. S. Naval Base,	
Norfolk 11, Virginia	1
Navy Research Section	
Library of Congress	
Washington 25, D. C.	
(Via BUORD, Re3c)	2
Naval Gun Factory	
Attn: Aircraft Armament Section	1
Bureau of Aeronautics	
Attn: Armament Section	2
NATC, Patuxent River, Maryland	1
NAOTS, Chincoteague, Virginia	1
Air Material Command Liaison Officer	
Wing 3 Headquarters, Aberdeen Proving Ground	
Aberdeen, Maryland	2
Naval Liaison Officer	
USAFPGC, Eglin Field, Florida	1
NOTS, Inyokern, Calif.	1

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod 0 Modified to 75 gallon Capacity

DISTRIBUTION (Continued)

NOTS, Inyokern, California Attn: Aviation Ordnance and Test Department	1
Naval Air Development Center Johnsville, Pennsylvania	1
U. S. Air Force AIC Engineering Field Office Room 1833, Main Navy Building Navy Dept., Washington, D. C.	2
Commanding General Air Force Armament Center Attn: Technical Library Eglin Air Force Base, Florida	1
Commanding Officer Picatinny Arsenal, Dover, New Jersey Attn: Technical Division	1
Local:	
OVL	1
OVX	1
File	1

Best Available Copy

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod 0 Modified to 75 gallon Capacity

DISTRIBUTION

Bureau of Ordnance	
Ad3	1
Re3	1
Re3c	6
Chief of Ordnance	
Department of the Army	
Attn: ORDTX-AR	1
Commanding General	
Aberdeen Proving Ground, Aberdeen, Maryland	
Attn: Technical Information Section	
Development and Proof Services	1
Commander, Operational Development Force	
U. S. Atlantic Fleet, U. S. Naval Base,	
Norfolk 11, Virginia	1
Navy Research Section	
Library of Congress	
Washington 25, D. C.	
(Via BUORD, Re3c)	2
Naval Gun Factory	
Attn: Aircraft Armament Section	1
Bureau of Aeronautics	
Attn: Armament Section	2
NATC, Patuxent River, Maryland	1
NAOTS, Chincoteague, Virginia	1
Air Material Command Liaison Officer	
Wing 3 Headquarters, Aberdeen Proving Ground	
Aberdeen, Maryland	2
Naval Liaison Officer	
USAFPGC, Eglin Field, Florida	1
NOTS, Inyokern, Calif.	1

RESTRICTED
SECURITY INFORMATION

RESTRICTED

NPG REPORT NO. 1093

Tests of Fire Bomb Mk 77 Mod O Modified to 75 gallon Capacity

DISTRIBUTION (Continued)

NOTS, Inyokern, California	
Attn: Aviation Ordnance and Test Department	1
Naval Air Development Center	
Johnsville, Pennsylvania	1
U. S. Air Force	
AMC Engineering Field Office	
Room 1833, Main Navy Building	
Navy Dept., Washington, D. C.	2
Commanding General	
Air Force Armament Center	
Attn: Technical Library	
Eglin Air Force Base, Florida	1
Commanding Officer	
Picatinny Arsenal, Dover, New Jersey	
Attn: Technical Division	1
Local:	
OVL	1
OVX	1
File	1