

UNCLASSIFIED

AD NUMBER	
AD007128	
CLASSIFICATION CHANGES	
TO:	UNCLASSIFIED
FROM:	CONFIDENTIAL
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited.	
FROM: Distribution authorized to DoD only; Administrative/Operational Use; 20 MAY 1953. Other requests shall be referred to National Aeronautics and Space Administration, Washington, DC.	
AUTHORITY	
NASA dtd 29 Sep 1960; NASA TR Server website	

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD **7128**

*Reproduced
by the*

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



DECLASSIFIED
PER AUTHORITY
TAB 260-4-5
DATED 1 DEC. '60

UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

SECURITY INFORMATION
CONFIDENTIAL

Copy 73
RM E52J20

NACA RM E52J20

NACA

RESEARCH MEMORANDUM

PRELIMINARY EVALUATION OF TURBINE PERFORMANCE WITH
VARIABLE-AREA TURBINE NOZZLES IN A TURBOJET ENGINE

By Carl E. Campbell and Henry J. Welna

Lewis Flight Propulsion Laboratory
Cleveland, Ohio

CLASSIFIED DOCUMENT

This material contains information affecting the National Defense of the United States within the meaning of the espionage laws, Title 18, U.S.C., Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS

WASHINGTON

May 20, 1953

CONFIDENTIAL

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUMPRELIMINARY EVALUATION OF TURBINE PERFORMANCE WITH VARIABLE-
AREA TURBINE NOZZLES IN A TURBOJET ENGINE

By Carl E. Campbell and Henry J. Welna

SUMMARY

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles used in this investigation were primarily a test device for compressor research purposes and were not necessarily of optimum aerodynamic design. The results of this investigation are indicative of effects of turbine-nozzle-area variation on turbine performance within the operating range allowed by the engine. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At a given corrected turbine speed and turbine pressure ratio, changing the turbine nozzle area from 1.30 to 1.67 square feet lowered the turbine efficiency 3 or 4 percent. The effect of increasing the turbine nozzle area from 1.15 to 1.67 square feet (decreasing the turning angle about $7\frac{1}{2}^\circ$) would be to lower the turbine efficiency about 5 or 6 percent.

INTRODUCTION

Analyses such as that given in reference 1 indicate the performance and operational advantages to be gained by utilization of variable-area turbine nozzles in turbojet engines. When combined with a proper speed control, the variable turbine nozzle can greatly increase the thrust capability of supersonic turbojet engines because of increased flexibility in matching of the compressor and turbine over a wide range of flight conditions. Furthermore, potential improvements in specific fuel consumption, particularly at thrust values below rated thrust, are possible for engines equipped with both variable-area turbine nozzles and variable-area exhaust nozzles (reference 1). In both these analyses, it was assumed that turbine efficiency was not affected by changes in the area or angle of the turbine nozzles. However, aside from analytical treatment of the problem, there exists at the present time a lack of

experimental data on the performance of variable-area turbine nozzles operating as integral components of full-scale turbojet engines. Complexity and mechanical reliability have been the main deterrent factors in obtaining experimental data and in the utilization of variable turbine nozzles in present turbojet engine designs.

During a study of the surge characteristics of a turbojet engine fitted with variable-area first-stage turbine nozzles in the NACA Lewis altitude wind tunnel, it was possible to obtain some preliminary data on the effect of these nozzles on the performance of the two-stage turbine. The effect of the variable-area turbine nozzles on the efficiency and gas flow characteristics of the turbine are presented herein. The variable-area turbine nozzles investigated in this study were intended primarily to provide a variable compressor pressure ratio independent of engine speed and turbine-inlet temperature for compressor research purposes; therefore, the aerodynamic design of the nozzles was not necessarily optimum. Furthermore, the turbine rotors and the second-stage stator were designed for fixed-area first-stage nozzles. The experimental results obtained in this investigation, therefore, do not represent the best turbine performance obtainable with variable-area turbine nozzles, but serve instead as a preliminary indicator of general performance and mechanical problems.

Corrected turbine gas flow and turbine efficiency are presented as functions of corrected turbine speed and turbine pressure ratio to show the effects of turbine nozzle area and nozzle angle on turbine performance. The turbine efficiency obtained with the original fixed turbine nozzles is compared with the turbine efficiency obtained with the variable turbine nozzles at a position corresponding to approximately the same throat area and turning angle. All turbine performance data obtained with the variable turbine nozzles are presented in numerical form in table I.

INSTALLATION AND INSTRUMENTATION

Engine

The engine was mounted on a wing section which extended across the 20-foot-diameter test section of the altitude wind tunnel (fig. 1). Dry refrigerated air was supplied to the engine from the tunnel make-up air system through a duct connected to the engine inlet. Manually controlled butterfly valves in this duct were used to adjust the total pressure of the refrigerated air at the engine inlet to correspond to the desired flight condition, while the static pressure in the tunnel test section was maintained to correspond to the desired altitude. A slip joint with a frictionless seal in the duct permitted the measurement of thrust and installation drag with the tunnel scales.

The engine used in this investigation was a J40-WE-6, which had a sea-level rating of 7500 pounds of jet thrust at an engine speed of 7260 rpm and a turbine-inlet temperature of 1425° F. At this rating, the compressor pressure ratio was about 5.0 and the engine air flow was 140 pounds per second. A cross-section of the engine is presented in figure 2 showing the main components of the engine which included an eleven-stage axial-flow compressor, a single-annulus basket-type combustor, a two-stage turbine, and a clamshell-type variable-area exhaust nozzle. The engine was equipped with an electronic control that varied engine fuel flow and exhaust-nozzle area to maintain a schedule of turbine-outlet temperature and engine speed.

The original J40-WE-6 engine was modified before the investigation reported herein by replacing the compressor-outlet straightening-vane assembly with a two-element mixer-vane assembly, by using a slightly modified combustor basket, and by replacing the first-stage fixed turbine nozzles with a variable turbine-nozzle diaphragm. The original control was also modified to permit independent control of engine speed and exhaust-nozzle area.

Turbine

Both first- and second-stage turbine disks were solid steel and had an outer diameter of 21.90 inches. The first-stage rotor disk had 62 high-temperature-alloy blades fitted into its outer rim (fig. 3(a)) and the second stage contained 32 blades of the same material (fig. 3(b)). All turbine rotor blades were 5.50 inches in length; the turbine tip diameter was thus 32.90 inches and the hub-tip radius ratio was 0.666. The radial tip clearance for the turbine rotors was 5/32 inch.

The first-stage or variable turbine-nozzle diaphragm consisted of 56 high-temperature-alloy vanes which could be rotated between an inner and outer shroud (figs. 4(a) and 4(b)). All vanes were rotated simultaneously by an actuating mechanism similar to the one shown schematically in figure 5. The single actuating shaft extending through the engine outer skin was actuated by an externally mounted worm-gear drive. Changing the turbine-nozzle vane angle varied the nozzle throat area and also the angle that the fluid is turned in passing through the nozzles. Mid-vane cross sections of two adjacent turbine nozzle vanes are shown in the open and closed positions in figure 6. The solid-line section shows the vanes in the open position corresponding to a geometric throat area of 1.67 square feet and a turning angle at the throat of approximately 54.5°. The dashed-line section corresponds to the closed position with a throat area of 1.15 square feet and turning angle of about 62°. The original fixed turbine nozzles, for which the turbine rotors and second-stage nozzles were designed, corresponded closely to the variable turbine-nozzle setting that provided a throat area of 1.30 square feet and a turning angle of about 59°.

The second-stage or interstage stator consisted of 60 high-temperature-alloy vanes welded to an inner and outer shroud with a fixed nozzle-throat area of approximately 1.81 square feet. The annular passage through the turbine from first-stage nozzles to turbine outlet had approximately constant inner and outer diameters; the unblocked annular area was about 3.4 square feet.

Instrumentation

Stations at which instrumentation was installed within the engine for measuring pressures and temperatures are shown in figure 2. The number of total and static pressure tubes, static pressure orifices, and thermocouples installed at each measuring station is shown in tabular form in this figure. Schematic sketches of the instrumentation at the cowl inlet (station 1), compressor outlet (station 4), turbine inlet (station 5), and turbine outlet (station 6) are shown in figure 7. Fuel flow was measured by calibrated rotameters and engine speed was measured by a stroboscopic tachometer.

Procedure

Data were obtained at altitudes of 15,000, 30,000, 40,000, and 44,000 feet at various flight Mach numbers from 0.14 to 0.62. Extensive performance data were obtained at an altitude of 30,000 feet and a flight Mach number of 0.62. At this flight condition, the variable turbine nozzles were set at five different positions and at each nozzle position the engine was operated at six different speeds from 3630 to 7260 rpm (rated speed). At each turbine-nozzle setting and engine speed, the exhaust nozzle was varied from the wide-open position to full closed, or until limiting turbine temperature was approached, to extend the range of turbine pressure ratio and corrected turbine speed. The ranges of turbine pressure ratio, corrected turbine speed, turbine nozzle area, and engine speed covered at this flight condition are shown in the following table:

Engine speed, rpm	3630 to 7260
Measured turbine-nozzle-throat area, sq ft	1.15 to 1.67
Turbine pressure ratio	1.57 to 3.00
Corrected turbine speed, rpm	2663 to 4407

The symbols and methods of calculation used to determine the turbine performance are given in the appendix.

RESULTS AND DISCUSSION

Inasmuch as the primary object is to show the effect of turbine nozzle area on turbine performance, curves are shown only for an altitude of 30,000 feet and a flight Mach number of 0.62 where the most extensive investigation was made. Data obtained at all of the flight conditions investigated are presented in numerical form in table I.

Corrected Turbine Gas Flow

The variation of corrected turbine gas flow with corrected turbine speed for all five turbine nozzle areas is shown in figure 8 for an altitude of 30,000 feet and a flight Mach number of 0.62. Although turbine pressure ratio is not a direct function of corrected turbine speed, lines of constant turbine pressure ratio have been superimposed to indicate approximately the general increase in turbine pressure ratio with increased corrected turbine speed at each turbine nozzle area. For each of the five nozzle areas, the corrected gas flow increased with corrected turbine speed to a maximum value and was unaffected by further increases in corrected turbine speed or turbine pressure ratio. Failure of the corrected gas flow to increase at high corrected turbine speeds (and high turbine pressure ratios) is attributed to choking of the flow at some station within the turbine. The turbine pressure ratio for choking varied from about 2.6 at a turbine nozzle area of 1.15 square feet to about 2.2 at an area of 1.67 square feet. However, these values of turbine pressure ratio at the transition point between choked and unchoked flow are very approximate because of the data inaccuracy in the low range of turbine pressure ratios.

The maximum corrected turbine gas flow (choked conditions) obtained at each nozzle area is shown in figure 9. This curve is also a measure of effective turbine-nozzle throat area inasmuch as corrected turbine gas flow is directly proportional to effective area when the nozzles are choked. Over the range of actual turbine nozzle areas from 1.15 to 1.67 square feet, the effective turbine nozzle area varied from 1.13 to 1.25 square feet for an effective area range of approximately 10 percent. It is apparent that the effective and measured areas are nearly equal at small area settings of the nozzles but the effective area is considerably smaller than the measured area at large area settings. This indicates a reduction in nozzle flow coefficient (defined as the ratio of effective area to measured area) from about 0.98 to 0.75 as the nozzles are opened. This large reduction in indicated flow coefficient may be caused by choking at some station within the turbine other than the inlet nozzles. However, inasmuch as interstage pressures and temperatures were not measured, the location of the choking station within the turbine could not be determined with certainty.

Turbine Efficiency

The turbine efficiencies obtained with all five turbine nozzle areas at an altitude of 30,000 feet and a flight Mach number of 0.62 are shown in figure 10 as a function of corrected turbine speed. The maximum turbine efficiency obtained was 0.87 with the smallest turbine nozzle area and a high corrected turbine speed. The minimum turbine efficiency was about 0.70 with the largest nozzle area and a low corrected turbine speed. In general, turbine efficiency increased with corrected turbine speed for all turbine nozzle areas and was lowered by increasing the turbine nozzle area (decreasing the nozzle turning angle) at a given corrected turbine speed. These general effects, however, are not clearly separated in figure 10 because the effects of turbine pressure ratio have not been accounted for.

In figures 11(a) and (b) to 15(a) and (b), operating lines of turbine pressure ratio and turbine efficiency are shown as functions of corrected turbine speed for each engine speed and turbine nozzle area. Although turbine efficiency is not a direct function of engine speed, lines of constant engine speed have been faired for the turbine efficiency data for the purpose of obtaining cross plots. The cross plots of turbine efficiency against corrected turbine speed for constant values of turbine pressure ratio obtained from parts (a) and (b) of figures 11 to 15 are shown in parts (c) of these figures. At a constant turbine pressure ratio, turbine efficiency increased with increased corrected turbine speed. This trend occurred at all values of constant turbine pressure ratio for which cross plots could be obtained at each turbine nozzle area. The maximum range of corrected turbine speed obtainable at a constant turbine pressure ratio was about 200 rpm and the average increase in turbine efficiency for this increase in corrected turbine speed was about 4 percent. However, the rate of increase in turbine efficiency with increased corrected turbine speed was greater at the lower values of constant turbine pressure ratio. At a given corrected turbine speed, turbine efficiency increased with reduced turbine pressure ratio, but the corrected turbine speed could be maintained constant only for a very small range of turbine pressure ratios.

The effect of changing turbine nozzle area and turning angle on turbine efficiency at a given corrected turbine speed and turbine pressure ratio is shown in figure 16. The symbols, which represent cross-plotted data points rather than actual data points, have been included to indicate the accuracy of the cross-plotted data as well as for distinguishing between turbine nozzle areas. In all cases where a comparison could be made at the same turbine pressure ratio and corrected turbine speed, the turbine efficiency was lowered by increasing the turbine nozzle area. Changing the turbine nozzle area from 1.30 to 1.67 square feet at constant values of corrected turbine speed and turbine pressure ratio

lowered the turbine efficiency by 3 or 4 percent. It is probable that the reduction in turbine efficiency over the complete range of turbine nozzle areas (decreasing the turning angle about $7\frac{1}{2}^\circ$) would not be more than about 5 or 6 percent in the region of high corrected turbine speeds and turbine pressure ratios.

A comparison of turbine efficiencies obtained with the original fixed turbine nozzles and with the variable turbine nozzles at a corresponding area setting and at the same flight conditions and engine speed is shown in figure 17. The slightly lower turbine efficiency of about 1 percent (which is less than the data accuracy spread) obtained with the variable turbine nozzles indicates that the leakage losses with the variable nozzles were very small.

Mechanical Reliability

The variable-area turbine-nozzle diaphragm was installed in the engine during approximately 240 hours of engine operation and only minor mechanical difficulties were encountered during this period. Although the turbine nozzle area was not varied frequently during the part of the engine investigation reported herein, a great many changes in nozzle area were made during other parts of the investigation. The nozzles were at low physical loading conditions most of the time because most of the investigation was conducted at high altitudes, but inasmuch as a large part of the total operating time was at military speed and temperature, it is felt that these tests were a good indication of variable turbine nozzle life. Calibrations of turbine-nozzle-throat dimensions versus indicated nozzle setting showed good reproducibility of turbine nozzle areas.

CONCLUDING REMARKS

The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. It was possible to achieve a variation in corrected turbine gas flow or effective turbine nozzle area of about 10 percent by use of these variable turbine nozzles. At a given corrected turbine speed and turbine pressure ratio, changing the turbine nozzle area from 1.30 to 1.67 square feet lowered the turbine efficiency by 3 or 4 percent. The effect of increasing the turbine nozzle area from 1.15 to 1.67 square feet (decreasing the turning angle about $7\frac{1}{2}^\circ$) would probably lower the turbine efficiency about 5 or 6 percent.

Lewis Flight Propulsion Laboratory
National Advisory Committee for Aeronautics
Cleveland, Ohio

APPENDIX - CALCULATIONS

Symbols

The following symbols are used in this report:

A	cross-sectional area, sq ft
g	acceleration due to gravity, 32.2 ft/sec ²
H	enthalpy of air or gas mixture, Btu/lb
N	engine speed, rpm
P	total pressure, lb/sq ft absolute
P	static pressure, lb/sq ft absolute
R	gas constant, 53.4 ft-lb/lb-°R
T	total temperature, °R
T _i	indicated temperature, °R
V	velocity, ft/sec
W _a	air flow, lb/sec
W _f	fuel flow, lb/hr
W _g	gas flow, lb/sec
α	thermocouple impact recovery factor, 0.85
γ	ratio of specific heats for gases
δ	pressure correction factor, P/2116 (total pressure divided by NACA standard sea-level pressure)
η	adiabatic efficiency
θ	temperature correction factor, $\gamma T / (1.4)(519)$, (product of γ and total temperature divided by product of γ and temperature for air at NACA standard sea-level conditions)
ρ	density, slugs/cu ft

Corrected parameters:

$N/\sqrt{\theta_5}$ corrected turbine speed, rpm
 T_5/θ_2 corrected turbine-inlet temperature, °R
 $\frac{W_g \sqrt{\theta_5}}{\delta_5 (r_5/1.4)}$ corrected turbine-inlet gas flow, lb/sec
 $\Delta H_t/\theta_5$ corrected turbine enthalpy drop, Btu/lb

Subscripts:

a air
 g gas mixture
 t turbine
 1 cowl inlet
 2 compressor inlet
 4 compressor outlet
 5 turbine inlet
 6 turbine outlet

Methods of Calculation

Total temperatures were calculated from thermocouple indicated temperatures with the equation

$$T = \frac{T_i \left(\frac{P}{p} \right)^{\frac{\gamma-1}{\gamma}}}{1 + \alpha \left[\left(\frac{P}{p} \right)^{\frac{\gamma-1}{\gamma}} - 1 \right]} \quad (1)$$

Air flow. - Air flow was determined from pressure and temperature measurements at the cowl inlet (station 1) by use of the equation

$$W_{a,1} = \rho_1 A_1 V_1 = A_1 \sqrt{\frac{2g}{R}} \left(\frac{P_1}{\sqrt{T_1}} \right) \sqrt{\left(\frac{\gamma_1}{\gamma_1 - 1} \right) \left(\frac{P_1}{P_1} \right)^{\frac{\gamma_1 - 1}{\gamma_1}} \left[\left(\frac{P_1}{P_1} \right)^{\frac{\gamma_1 - 1}{\gamma_1}} - 1 \right]} \quad (2)$$

Gas flow. - Gas flow was calculated from fuel-flow measurements and cowl-inlet air flow as follows:

$$W_g = W_{a,1} + W_f/3600 \quad (3)$$

Turbine-inlet temperature. - Turbine-inlet temperature was determined from the enthalpy and fuel-air ratio at the turbine inlet by use of temperature-enthalpy tables. Turbine-inlet enthalpy was calculated from the following equation which assumes that the turbine enthalpy drop equals the compressor enthalpy rise:

$$H_{g,5} = H_{g,6} + \frac{W_{a,1}}{W_g} (H_{a,4} - H_{a,2}) \quad (4)$$

Turbine efficiency. - The turbine adiabatic efficiency was determined from the following equation:

$$\eta_t = \frac{1 - \frac{T_6}{T_5}}{1 - \left(\frac{P_6}{P_5} \right)^{\frac{\gamma_t - 1}{\gamma_t}}} \quad (5)$$

where γ_t is the average value of γ between stations 5 and 6.

REFERENCES

1. Silvern, David H., and Slivka, William R.: Analytical Investigation of Turbines with Adjustable Stator Blades and Effect of These Turbines on Jet-Engine Performance. NACA RM E50E05, 1950.

2618



TABLE I. - VARIABLE-AREA TURBINE PERFORMANCE

Run	Altitude (ft)	M ₀	P ₀ (lb sq ft)	Turbine nozzle area (sq ft)	N (rpm)	W _r (lb hr)	P ₂ (lb sq ft)	T ₂ (°R)	T ₄ (°R)	P ₅ (lb sq ft)	T ₅ (°R)	P ₆ (lb sq ft)	T ₆ (°R)	W _{a,1} (lb sec)	W _{g,5} (lb sec)	η _t	P ₅ /P ₆	N √P ₅ (rpm)	ΔH ₅ P ₅ (Btu lb)	T ₅ P ₅ (°R)	W _{g,5} √P ₅ P ₅ (lb sec)	W _r W _{a,1} (3600) (lb)	T ₅ T ₆
1	15,000	0.424	1185	1.15	7260	3140	1340	499	855	6421	1563	2210	1191	95.40	96.38	0.8637	2.905	4281	30.2	1640	56.36	0.0103	1.262
2		.464	1189	1.15	7260	3525	1379	495	888	6825	1660	2370	1239	95.46	96.56	.8773	2.795	4163	29.7	1745	56.53	.0115	1.253
3		.480	1189	1.15	7260	3955	1379	494	871	6794	1720	2479	1362	95.72	96.93	.8733	2.740	4095	29.2	1809	56.42	.0126	1.245
4		.467	1188	1.15	7260	4340	1379	494	880	6964	1850	2659	1493	95.46	96.79	.8849	2.619	3956	27.9	1941	57.15	.0140	1.231
5		.459	1189	1.15	6897	2855	1385	495	824	5979	1410	2016	1116	93.23	94.02	.8407	2.965	4268	30.4	1479	55.86	.0085	1.263
6		.455	1191	1.15	6897	3515	1372	491	837	6240	1560	2254	1251	92.67	93.45	.8613	2.768	4071	28.9	1649	56.34	.0105	1.263
7		.457	1200	1.15	6897	3765	1394	490	839	6384	1600	2376	1294	93.54	94.59	.8601	2.564	4022	28.2	1694	56.39	.0112	1.236
8		.453	1195	1.15	6897	4195	1375	490	849	6531	1704	2547	1386	92.98	94.15	.8731	2.514	3800	27.6	1805	56.76	.0125	1.218
9		.460	1198	1.15	6897	4610	1385	496	862	6710	1810	2669	1486	93.04	94.32	.8731	2.514	3800	28.5	1895	57.15	.0138	1.218
10		.464	1198	1.15	6897	5025	1377	492	871	6818	1900	2822	1576	93.84	95.11	.8852	2.438	3586	27.5	1473	55.95	.0088	1.236
11		.456	1191	1.15	6353	2335	1377	492	871	6818	1900	2822	1576	93.84	95.11	.8852	2.438	3586	27.5	1473	55.95	.0088	1.236
12		.456	1191	1.15	6353	2590	1375	491	881	6964	1950	2970	1668	94.11	95.43	.8952	2.383	3352	25.1	1647	56.45	.0100	1.224
13		.456	1192	1.15	6353	3000	1375	491	881	7118	2000	3120	1760	94.11	95.43	.8952	2.383	3352	25.1	1647	56.45	.0100	1.224
14		.457	1187	1.15	6353	3250	1377	490	802	6621	1555	2235	1280	82.72	83.82	.8252	2.638	3836	27.0	1570	56.72	.0109	1.215
15		.457	1187	1.15	6353	3615	1361	491	809	6739	1650	2359	1369	81.88	82.88	.8383	2.514	3757	25.9	1744	56.86	.0123	1.205
16		.469	1183	1.15	5808	1800	1375	488	676	4364	1150	1669	966	73.73	74.23	.8986	2.635	3951	21.6	1225	54.25	.0068	1.190
17		.471	1186	1.15	5808	2115	1361	487	736	4482	1210	1742	1082	73.40	73.96	.8986	2.635	3951	21.6	1225	54.25	.0068	1.190
18		.472	1176	1.15	5808	2455	1370	486	743	4546	1420	1891	1191	70.28	70.96	.8986	2.635	3951	21.6	1225	54.25	.0068	1.190
19		.460	1186	1.15	5808	2795	1371	480	743	4546	1420	1891	1191	70.28	70.96	.8986	2.635	3951	21.6	1225	54.25	.0068	1.190
20		.455	1188	1.15	5808	3015	1369	488	763	4585	1630	2142	1386	68.71	69.55	.8640	2.262	3439	23.1	1355	53.75	.0097	1.192
21		.475	1176	1.15	4719	1095	1372	488	650	2869	1050	1314	898	52.10	52.40	.7534	2.103	3352	22.1	1736	58.26	.0122	1.176
22		.485	1182	1.15	4719	1229	1368	486	651	2982	1085	1420	938	52.17	52.51	.7853	2.103	3352	22.1	1736	58.26	.0122	1.176
23		.472	1182	1.15	4719	1365	1371	487	657	3005	1165	1502	1005	50.80	51.16	.8053	2.003	3193	18.7	1144	55.51	.0068	1.169
24		.474	1186	1.15	4719	1511	1377	487	663	3146	1290	1626	1124	49.19	49.65	.8424	1.935	3111	18.7	1241	54.72	.0075	1.159
25		.467	1180	1.15	3630	785	1370	485	580	2032	940	1217	860	36.17	37.03	.7258	1.670	2512	12.3	1005	52.51	.0059	1.148
26		.472	1177	1.15	3630	879	1371	485	584	2089	990	1283	902	36.20	36.47	.7795	1.563	2574	12.1	1123	51.42	.0074	1.098
27		.482	1192	1.15	3630	965	1397	485	588	2183	1055	1384	961	36.20	36.47	.7795	1.563	2574	12.1	1123	51.42	.0074	1.098
28		.480	1193	1.15	3630	1050	1379	483	612	2194	1480	1524	1180	36.96	37.90	.8394	2.769	4392	28.9	1591	60.30	.0097	1.244
29		.463	1183	1.30	7260	3785	1369	493	836	6559	1743	2558	1430	96.18	97.43	.8782	2.486	4070	28.7	1349	61.02	.0110	1.236
30		.459	1192	1.30	7260	4495	1377	489	844	6559	1743	2558	1430	96.18	97.43	.8782	2.486	4070	28.7	1349	61.02	.0110	1.236
31		.464	1187	1.30	6897	3005	1376	495	803	5553	1430	2027	1153	92.54	93.37	.8348	2.739	4339	28.0	1560	60.21	.0130	1.219
32		.463	1187	1.30	6897	3495	1374	495	815	5767	1540	2238	1258	92.42	93.39	.8477	2.576	4096	27.2	1615	60.39	.0105	1.224
33		.462	1190	1.30	6897	3855	1377	494	823	5935	1627	2373	1332	92.73	93.80	.8745	2.501	3991	26.5	1710	60.54	.0115	1.221
34		.463	1184	1.30	6897	4450	1371	496	831	6190	1748	2562	1446	92.11	93.35	.8803	2.392	3860	25.4	1830	60.74	.0134	1.209
35		.464	1186	1.30	6353	2400	1375	493	764	6353	1827	2673	1583	86.00	86.67	.8030	2.653	4041	25.9	1397	60.49	.0076	1.259
36		.464	1185	1.30	6353	2890	1374	492	775	5113	1433	2051	1180	85.39	86.19	.8348	2.493	3901	25.6	1512	60.47	.0094	1.244
37		.462	1188	1.30	6353	3390	1374	491	785	5316	1563	2256	1301	84.45	85.39	.8490	2.356	3746	24.7	1652	60.47	.0094	1.244
38		.463	1188	1.30	6353	3885	1375	490	794	5501	1680	2465	1412	83.61	84.69	.8548	2.268	3522	23.7	1779	60.47	.0112	1.231
39		.460	1188	1.30	6353	4390	1374	489	799	5616	1800	2673	1531	82.61	83.83	.8494	2.182	3310	22.6	1910	60.47	.0129	1.190
40		.464	1187	1.30	5808	1865	1374	491	724	4144	1230	1665	1007	75.77	75.79	.8332	2.488	3829	24.7	1510	60.85	.0146	1.176
41		.464	1187	1.30	5808	2230	1374	487	727	4310	1323	1823	1103	75.17	75.79	.8160	2.364	3702	23.5	1409	60.41	.0068	1.199
42		.463	1185	1.30	5808	2500	1372	488	733	4361	1410	1933	1194	73.53	74.22	.8004	2.256	3594	22.6	1502	60.48	.0094	1.181
43		.467	1184	1.30	5808	2890	1374	488	743	4477	1540	2073	1310	72.34	73.14	.8332	2.159	3449	21.9	1640	60.91	.0111	1.176
44		.459	1188	1.30	5808	3295	1372	487	753	4570	1673	2195	1437	70.28	71.20	.8394	2.082	3319	20.9	1782	60.73	.0130	1.164
45		.467	1185	1.30	4719	1175	1375	486	644	2798	1083	1410	933	52.36	52.71	.8123	1.984	3302	18.6	1156	58.23	.0062	1.161
46		.464	1185	1.30	4719	1295	1375	485	643	2798	1083	1410	933	52.36	52.71	.8123	1.984	3302	18.6	1156	58.23	.0062	1.161
47		.464	1185	1.30	4719	1455	1374	482	646	2941	1243	1576	1080	52.06	52.49	.8563	1.866	3096	17.6	1342	59.33	.0068	1.161
48		.471	1184	1.30	4719	1530	1378	481	653	3004	1293	1630	1137	51.21	51.87	.8112	1.842	3041	17.4	1393	58.29	.0090	1.151
49		.466	1184	1.30	4719	1740	1374	480	653	3004	1293	1630	1137	51.21	51.87	.8112	1.842	3041	17.4	1393	58.29	.0090	1.151
50		.470	1183	1.30	3630	814	1375	484	573	1967	955	1282	868	37.71	37.94	.8178	1.534	2699	12.2	1023	55.81	.0060	1.100
51		.467	1185	1.30	3630	1022	1375	483	582	2086	1108	1192	1009	36.36	36.64	.8386	1.750	2574	11.5	1191	54.97	.0078	1.098
52		.463	1190	1.67	7260	3840	1378	485	813	5797	1573	2574	1348	94.20	95.32	.8386	1.750	2574	11.5	1191	54.97	.0078	1.098
53		.460	1180	1.67	7260	4040	1364	487	827	5820	1643	2700	1480	94.40	96.60	.8386	1.750	2574	11.5	1191	54.97	.0078	1.098
54		.457	1186	1.67	7260	4310	1373	491	824	5856	1680	1920	1364	95.40	96.60	.8386	1.750	2574	11.5	1191	54.97	.0078	1.098
55		.457	1183	1.67																			

2618



TABLE I. - VARIABLE-AREA TURBINE PERFORMANCE - Continued

Run	Altitude (ft)	M ₀	P ₀ (lb sq ft)	Turbine nozzle area (sq ft)	N (rpm)	W _r (lb hr)	P ₂ (lb sq ft)	T ₂ (°R)	T ₄ (°R)	P ₅ (lb sq ft)	T ₅ (°R)	P ₆ (lb sq ft)	T ₆ (°R)	W _{a,1} (lb sec)	W _{a,5} (lb sec)	η _t	P ₆ /P ₆	N √P ₆ (rpm)	Δh _t P ₅ (Btu lb)	T ₅ P ₅ (°R)	W _{a,5} √P ₆ (lb sec)	W _r (lb hr)	T ₅ T ₆
57	15,000	0.453	1188	1.67	7260	5030	1368	487	830	6210	1830	2307	1525	95.40	96.80	0.7661	2.692	3978	24.9	1949	63.72	0.0146	1.200
58		.455	1183	1.67	6897	3370	1362	504	807	5374	1507	1951	1355	90.85	91.79	0.7473	2.855	4135	26.3	1552	62.92	0.0103	1.220
59		.460	1186	1.67	6897	3765	1371	497	805	5571	1580	1951	1355	92.05	93.10	0.7473	2.855	4048	26.8	1650	63.14	0.0114	1.214
60		.464	1186	1.67	6897	4065	1375	500	813	5677	1650	2123	1370	91.99	93.12	0.7696	2.674	3964	25.1	1713	63.45	0.0123	1.204
61		.467	1186	1.67	6897	4480	1377	496	817	5876	1730	2205	1448	92.48	93.72	0.7487	2.665	3881	24.4	1811	63.24	0.0135	1.195
62		.460	1181	1.67	6897	4890	1365	499	827	5983	1825	2361	1536	91.45	92.81	0.7689	2.588	3785	23.8	1898	63.21	0.0148	1.188
63		.464	1186	1.67	6853	2695	1374	499	762	4766	1570	1853	1366	85.43	86.18	0.7729	2.563	3983	24.8	1425	63.03	0.0088	1.206
64		.464	1191	1.67	6853	3160	1381	497	769	5016	1473	2054	1230	85.33	86.21	0.7668	2.478	3850	24.3	1538	62.51	0.0103	1.198
65		.457	1183	1.67	6853	3645	1365	496	777	5134	1600	2190	1349	84.49	85.50	0.8054	2.344	3707	22.8	1675	63.34	0.0120	1.186
66		.459	1186	1.67	6853	4075	1370	496	789	5313	1703	2377	1442	83.50	84.63	0.8377	2.235	3601	22.8	1783	62.69	0.0136	1.181
67		.462	1187	1.67	6853	4450	1374	498	792	5428	1793	2466	1537	82.84	84.08	0.8123	2.483	3516	21.5	1868	62.68	0.0149	1.167
68		.462	1181	1.67	5808	2090	1366	473	674	4092	1215	1690	1023	77.08	77.66	0.7488	2.421	3854	21.6	1332	62.36	0.0075	1.188
69		.462	1182	1.67	5808	2500	1368	487	722	4204	1377	1806	1168	75.38	76.07	0.7480	2.328	3632	21.9	1467	63.53	0.0092	1.179
70		.459	1190	1.67	5808	2965	1375	486	735	4360	1520	2002	1301	74.55	75.37	0.7944	2.178	3470	21.1	1622	64.02	0.0110	1.168
71		.460	1188	1.67	5808	3230	1373	483	734	4430	1600	2136	1375	73.30	74.20	0.8320	2.072	3389	20.4	1720	63.66	0.0122	1.164
72		----	1184	1.67	5808	3595	1375	484	676	4504	1600	2298	1463	73.30	74.20	0.8320	2.072	3389	20.4	1720	63.66	0.0122	1.164
73		.471	1181	1.67	4719	1250	1375	510	660	2624	1145	1329	996	49.15	49.50	0.7664	1.974	3221	17.2	1164	59.97	0.0071	1.148
74		.467	1185	1.67	4719	1445	1367	501	657	2761	1197	1428	1045	50.73	51.13	0.7844	1.933	3152	17.0	1240	60.36	0.0079	1.145
75		.464	1186	1.67	4719	1595	1377	499	658	2792	1255	1528	1163	49.10	49.54	0.8037	1.827	3084	16.6	1305	59.35	0.0090	1.135
76		.460	1186	1.67	4719	1705	1374	502	664	2841	1323	1624	1173	48.84	49.31	0.8296	1.749	3010	16.3	1368	59.68	0.0097	1.128
77		.472	1184	1.67	4719	1910	1379	493	662	2903	1400	1733	1246	51.51	52.04	0.8772	1.675	2929	15.8	1474	63.52	0.0103	1.124
78		.467	1186	1.67	3630	892	1377	486	574	1967	983	1222	900	37.69	37.94	0.6918	1.610	2661	11.3	1049	56.71	0.0066	1.082
79		.460	1185	1.67	3630	972	1368	483	572	1997	1023	1274	944	37.53	37.80	0.6961	1.568	2612	10.4	1100	56.76	0.0072	1.084
80		.459	1186	1.67	3630	1060	1370	488	579	2027	1103	1342	1017	36.72	37.01	0.7415	1.510	2521	10.4	1175	56.98	0.0060	1.085
81	30,000	0.452	605	1.15	7260	1379	791	459	809	3229	1460	1843	1268	57.07	57.62	0.8541	2.995	4392	30.8	1672	56.39	0.0096	1.267
82		.619	616	1.15	7260	2255	797	473	837	3892	1615	1856	1283	56.49	57.12	0.8693	2.870	4216	30.0	1770	56.13	0.0111	1.259
83		.607	621	1.15	7260	2480	796	471	844	3997	1693	1940	1360	56.50	57.19	0.8635	2.776	4105	29.1	1867	56.08	0.0122	1.245
84		.621	614	1.15	7260	2810	797	465	845	4135	1803	1541	1467	56.66	57.44	0.8562	2.683	4007	27.7	2010	56.33	0.0138	1.229
85		----	620	1.15	7260	3020	797	463	844	4202	1803	1599	1518	56.66	57.44	0.8562	2.683	4007	27.7	2010	56.33	0.0138	1.229
86		.621	626	1.15	6897	1710	812	475	801	3593	1393	1198	1099	57.00	57.48	0.8410	2.999	4289	30.2	1521	56.49	0.0083	1.268
87		.619	619	1.15	6897	1905	803	475	810	3748	1477	1260	1177	56.33	56.86	0.8379	2.904	4175	29.7	1613	56.64	0.0094	1.255
88		.611	622	1.15	6897	2115	800	471	816	3748	1573	1342	1265	56.25	56.84	0.8454	2.793	4055	28.7	1735	57.11	0.0104	1.243
89		.610	620	1.15	6897	2390	797	469	826	3988	1710	1467	1393	55.90	56.59	0.8497	2.650	3901	27.5	1895	57.37	0.0124	1.228
90		.618	615	1.15	6897	2635	795	466	832	4045	1857	1601	1541	55.57	56.59	0.8519	2.527	3794	25.8	2067	57.42	0.0147	1.205
91		.628	615	1.15	6853	1223	802	475	782	3111	1270	1047	1000	51.17	51.34	0.8413	2.971	4125	29.6	1387	55.70	0.0072	1.270
92		.619	619	1.15	6853	1445	801	479	770	3149	1337	1096	1070	50.87	51.51	0.8067	2.810	3983	28.1	1449	56.26	0.0079	1.250
93		.624	618	1.15	6853	1567	804	477	772	3226	1370	1148	1107	51.07	51.51	0.8191	2.673	4029	27.5	1491	55.85	0.0085	1.238
94		.616	618	1.15	6853	1688	798	479	779	3258	1430	1197	1161	50.49	50.96	0.8182	2.722	3902	27.2	1550	56.02	0.0093	1.232
95		.623	617	1.15	6853	1786	802	479	781	3302	1455	1232	1194	50.69	51.19	0.7938	2.680	3874	26.8	1577	56.08	0.0098	1.219
96		.624	615	1.15	5808	997	799	477	720	2600	1150	921	915	46.04	46.32	0.8319	2.823	3951	27.3	1251	56.78	0.0060	1.257
97		.611	624	1.15	5808	1169	802	476	724	2650	1240	993	1006	46.14	46.46	0.8162	2.669	3816	25.9	1352	58.20	0.0070	1.233
98		.616	622	1.15	5808	1333	805	474	730	2723	1315	1062	1082	46.16	46.53	0.8033	2.564	3711	25.3	1439	58.54	0.0080	1.215
99		.616	621	1.15	5808	1498	802	475	737	2754	1400	1116	1164	45.72	46.14	0.8130	2.468	3605	24.3	1529	59.34	0.0091	1.203
100		.622	616	1.15	5808	1614	800	474	745	2779	1477	1155	1233	45.47	45.92	0.8130	2.406	3518	24.2	1616	59.23	0.0099	1.198
101		.627	621	1.15	4719	641	809	476	638	1701	963	750	803	32.34	32.52	0.7947	2.268	3493	21.4	1050	55.56	0.0055	1.192
102		.621	621	1.15	4719	709	805	476	636	1738	1015	786	853	31.16	31.35	0.8130	2.211	3407	20.8	1120	53.86	0.0063	1.190
103		.624	618	1.15	4719	773	804	473	643	1764	1070	820	905	31.03	31.24	0.8180	2.151	3323	20.3	1173	54.38	0.0079	1.182
104		.613	622	1.15	4719	867	801	471	647	1805	1157	869	987	30.60	30.84	0.8216	2.046	3204	19.8	1276	54.70	0.0079	1.172
105		.622	619	1.15	4719	964	804	471	654	1864	1230	911	1055	29.90	30.17	0.8197	2.017	3113	19.6	1357	53.53	0.0090	1.166
106		.614	618	1.15	3630	526	797	470	562	1147	800	668	711	23.75	23.90	0.7939	1.717	2937	14.4	884	55.00	0.0062	1.125
107		.619	620	1.15	3630	562	802	468	557	1154	823	694	741	23.95	24.11	0.7528	1.663	2859	12.8	913	55.94	0.0065	1.111
108		.625	620	1.15	3630	579	807	469	565	1154	823	694	741	23.95	24.11	0.7528	1.663	2859	12.8	913	55.94	0.0065	1.111
109		.619	617	1.15	3630	605	803	466	564	1206	907	729	820	23.19	23.36	0.7371	1.654	2767	12.8	1006	54.55	0.0072	1.106
110		.616	612	1.15	3630	626	791	466	593	1259	917	747											



TABLE I. - VARIABLE-AREA TURBINE PERFORMANCE - Continued

Run	Altitude (ft)	M ₀	P ₀ (lb sq ft)	T ₂ (°R)	T ₄ (°R)	P ₅ (lb sq ft)	T ₅ (°R)	P ₆ (lb sq ft)	T ₆ (°R)	W _{a,1} (lb sec)	W _{g,5} (lb sec)	η _t	P ₅ /t ₆	N √t ₆ (rpm)	Δh _t θ ₅ (Btu lb)	T ₅ θ ₂ (°R)	W _{g,5} √t ₆ θ ₅ (lb sec)	W _r W _{a,1} (3600)	T ₅ T ₆
113	30,000	0.618	614	462	809	3806	1610	1382	1301	57.02	57.68	0.8006	2.754	4221	28.4	1810	57.86	0.0116	1.238
114		.614	614	459	812	3888	1673	1445	1365	57.02	57.74	.8308	2.691	4149	27.4	1890	57.92	.0126	1.226
115		.614	614	458	815	3960	1733	1509	1422	56.99	57.76	.8341	2.624	4081	26.9	1962	57.93	.0135	1.219
116		.616	612	463	815	3434	1367	1292	1086	56.33	56.72	-----	-----	4330	29.6	1532	58.33	.0087	1.259
117		.626	617	462	785	3575	1480	1294	1196	56.68	57.22	.8264	2.767	4173	28.2	1664	58.73	.0099	1.237
118		.621	617	462	795	3722	1590	1404	1294	56.86	57.50	.8433	2.651	4034	27.4	1787	58.58	.0113	1.229
119		.611	614	469	809	3796	1713	1492	1412	55.98	56.70	.8391	2.544	3899	26.2	1932	58.92	.0129	1.213
120		.616	615	460	834	3680	1860	1595	1544	54.71	55.53	.8361	2.433	3753	25.7	2016	58.97	.0151	1.205
121		.634	605	460	813	3974	1847	1621	1540	55.33	56.77	.8360	2.452	3763	25.0	2083	58.67	.0150	1.199
122		.624	612	462	736	3048	1177	1074	912	52.79	53.17	.9154	2.838	4278	30.3	1333	56.33	.0072	1.291
123		.614	608	460	740	3099	1277	1121	1019	51.99	52.41	.8487	2.784	4117	28.1	1440	57.01	.0081	1.253
124		.619	612	460	746	3208	1355	1204	1099	52.43	52.90	.8296	2.664	4066	27.0	1528	57.36	.0090	1.233
125		.634	607	461	753	3307	1440	1274	1183	52.37	52.90	.8106	2.596	3893	26.3	1621	57.54	.0101	1.217
126		.628	615	460	758	3401	1530	1366	1267	52.70	53.28	.8217	2.490	3784	25.2	1723	58.21	.0110	1.208
127		.624	612	460	686	2542	1080	932	860	46.77	47.06	.8477	2.727	4070	27.0	1218	57.13	.0061	1.256
128		-----	-----	457	859	2589	-----	966	901	-----	-----	-----	2.680	-----	-----	-----	-----	-----	-----
129		.621	606	457	895	2634	1200	1014	971	45.87	46.22	.8424	2.597	3877	25.8	1363	57.27	.0075	1.236
130		.614	610	460	701	2663	1243	1054	1019	45.77	46.14	.8210	2.527	3811	24.9	1402	57.57	.0081	1.220
131		.633	612	460	705	2766	1280	1102	1061	46.38	46.78	.7885	2.510	3762	24.2	1444	57.14	.0086	1.206
132		.624	608	459	614	1695	940	746	609	32.40	32.59	.7536	2.272	3535	20.1	1082	55.17	.0060	1.181
133		.624	609	458	613	1684	950	760	830	32.87	33.07	.7510	2.216	3516	19.9	1075	56.84	.0080	1.174
134		.629	609	456	612	1693	973	782	809	32.85	33.05	.7656	2.165	3475	19.4	1107	57.05	.0062	1.172
135		.630	607	459	619	1731	1043	818	893	33.27	33.49	.7765	2.115	3364	19.2	1179	58.60	.0067	1.168
136		.630	609	458	622	1786	1123	909	971	33.00	33.25	.7727	2.050	3328	17.9	1271	58.66	.0077	1.158
137		.624	605	457	830	-----	-----	790	708	33.75	33.91	.7560	1.696	2956	13.8	891	55.35	.0066	1.116
138		.623	607	459	546	1128	800	688	713	23.79	23.96	-----	-----	2939	13.7	904	56.05	.0065	1.122
139		.624	607	459	546	1149	810	685	726	23.51	23.67	.7704	1.677	2920	13.5	915	54.73	.0069	1.116
140		.624	610	460	549	1174	855	710	773	23.05	23.23	.7366	1.653	2847	12.8	964	54.07	.0076	1.106
141		.626	608	460	552	1204	905	736	822	22.72	22.90	.7203	1.636	2770	12.1	1021	53.54	.0081	1.101
142		.626	610	453	778	3497	1473	1258	1185	57.49	58.05	.8380	2.780	4400	28.7	1690	60.40	.0098	1.243
143		.616	611	454	778	3538	1593	1356	1293	57.27	57.92	.8436	2.683	4243	27.7	1821	60.41	.0114	1.232
144		.622	607	454	794	3759	1703	1449	1393	56.97	57.70	.8521	2.594	4113	27.0	1943	60.40	.0129	1.223
145		.625	605	455	806	3886	1810	1557	1498	56.90	57.73	.8476	2.496	4006	26.1	2060	60.39	.0145	1.208
146		.590	622	457	821	3963	1890	1627	1582	56.68	57.58	.8308	2.436	3922	25.1	2147	60.44	.0159	1.195
147		.613	611	459	765	3358	1403	1241	1127	56.23	56.73	.8616	2.690	4279	28.5	1585	60.23	.0089	1.245
148		.613	615	460	775	3480	1493	1294	1210	56.83	57.40	.8378	2.689	4155	27.6	1684	60.42	.0100	1.234
149		.619	621	460	785	3631	1610	1420	1321	57.03	57.69	.8439	2.557	4010	26.7	1816	60.71	.0116	1.219
150		.613	621	461	796	3785	1743	1547	1447	56.94	57.71	.8477	2.447	3866	25.5	1963	60.71	.0135	1.205
151		.618	620	459	804	3933	1853	1657	1559	56.81	57.68	.8253	2.374	3759	24.1	2094	60.34	.0153	1.189
152		.621	618	462	731	3033	1285	1110	1034	53.48	53.89	.8318	2.732	4104	27.1	1440	60.14	.0077	1.243
153		.621	620	462	738	3106	1367	1191	1115	53.05	53.54	.8273	2.608	3988	26.4	1537	60.23	.0088	1.226
154		.626	617	463	746	3222	1463	1284	1291	53.01	53.54	.8247	2.509	3864	25.5	1640	60.24	.0102	1.212
155		.628	605	463	753	3241	1543	1358	1291	51.89	52.47	.8044	2.422	3768	24.3	1730	60.42	.0126	1.190
156		.627	615	463	759	3387	1643	1450	1381	52.53	53.19	.8251	2.336	3662	23.6	1842	60.58	.0135	1.186
157		.607	613	460	685	2432	1340	935	907	46.15	46.45	.8534	2.633	3986	26.4	1275	59.59	.0065	1.246
158		.607	607	462	705	2639	1347	1112	1126	45.71	46.12	.8068	2.373	3671	23.6	1514	60.63	.0090	1.196
159		.621	613	462	712	2717	1443	1190	1228	45.62	46.09	.7732	2.283	3554	22.1	1622	61.09	.0103	1.175
160		.616	608	462	720	2443	1567	1247	1335	45.18	45.70	.8115	2.200	3420	21.5	1761	62.65	.0115	1.174
161		.619	619	462	724	2646	1643	1315	1416	45.75	46.33	.7799	2.164	3348	20.6	1847	62.81	.0126	1.160
162		.634	615	461	613	1657	764	644	590	33.97	34.16	-----	-----	2169	-----	-----	-----	.0057	-----
163		.634	614	461	615	1687	1043	810	690	32.99	33.21	.8078	2.083	3564	19.3	1174	59.63	.0067	1.172
164		.640	610	460	619	1728	1070	846	921	33.06	33.30	.7883	2.043	3523	18.8	1207	59.18	.0071	1.162
165		.640	612	461	631	1764	1070	846	921	32.21	32.47	-----	-----	3121	-----	-----	-----	.0082	-----
166		.623	612	465	634	1771	1223	920	1072	31.56	31.84	.7719	1.925	2946	17.1	1364	59.30	.0089	1.141
167		.616	612	461	544	1102	795	672	717	24.92	25.07	.7599	1.640	2946	12.5	895	59.87	.0062	1.109

TABLE I. - VARIABLE-AREA TURBINE PERFORMANCE - Continued

Run	Altitude (ft)	M ₀	P ₀ (lb sq ft)	Turbine nozzle area (sq ft)	N (rpm)	W _t (lb hr)	P ₂ (lb sq ft)	T ₂ (°R)	T ₄ (°R)	P ₅ (lb sq ft)	T ₅ (°R)	P ₆ (lb sq ft)	T ₆ (°R)	W _{a,1} (lb sec)	W _{a,5} (lb sec)	η _t	P ₅ /P ₆	1/ √g ₅ (rpm)	Δh _t g ₅ (Btu lb)	T ₅ g ₅ (°R)	W _{a,5} √g ₅ (lb sec)	W _t W _{a,1} (3600)	η _s W _t
169	30,000	0.621	610	1.30	3630	635	791	460	546	1146	863	705	778	23.44	23.62	0.7811	1.626	2834	12.8	974	56.60	0.0075	1.109
170		.636	610	1.30	3630	698	801	460	550	1186	920	743	835	23.33	23.52	.7836	1.596	2748	12.8	1038	56.31	.0083	1.102
171		.599	623	1.37	7260	2130	794	468	798	3488	1527	1277	1234	56.95	57.54	.8398	2.731	4327	28.0	1693	61.22	.0104	1.237
172		.619	608	1.37	7260	2315	787	469	809	3488	1607	1354	1304	56.44	57.08	.8355	2.559	4118	27.8	1779	61.14	.0114	1.232
173		.609	618	1.37	7260	2615	794	469	816	3678	1700	1437	1394	56.75	57.48	.8615	2.496	4042	26.0	1862	61.42	.0128	1.220
174		.616	604	1.37	7260	2780	780	468	820	3599	1767	1492	1456	56.75	56.52	.8615	2.496	4042	26.0	1862	61.42	.0128	1.220
175		.619	622	1.37	7260	3015	781	469	824	3794	1840	1559	1529	56.57	56.41	.8653	2.434	3969	25.4	2037	60.93	.0151	1.203
176		.619	616	1.37	6897	1890	797	467	769	3351	1430	1266	1169	56.49	57.02	.8653	2.434	3969	25.4	2037	60.93	.0151	1.203
177		.621	607	1.37	6897	2350	787	467	788	3493	1604	1368	1319	56.68	56.33	.8482	2.517	4019	26.1	1589	61.35	.0093	1.203
178		.628	604	1.37	6897	2590	788	467	795	3606	1685	1471	1398	56.67	56.39	.8418	2.451	3928	25.3	1782	61.40	.0117	1.216
179		.629	610	1.37	6897	2875	796	466	801	3726	1777	1568	1484	56.27	57.07	.8513	2.376	3832	24.7	1978	61.63	.0142	1.205
180		.618	620	1.37	6897	3295	802	466	811	3903	1897	1697	1602	56.39	57.31	.8433	2.300	3718	24.1	2111	61.61	.0162	1.197
181		.622	612	1.37	6353	1535	---	466	730	2946	1300	1104	1059	52.44	52.87	.8091	2.570	3973	25.4	1625	61.12	.0081	1.184
182		.622	605	1.37	6353	1695	---	468	741	3017	1377	1174	1135	51.70	52.17	.8091	2.570	3973	25.4	1625	61.12	.0081	1.184
183		.629	605	1.37	6353	1890	---	467	747	3114	1463	1255	1217	51.91	52.44	.8013	2.481	3864	24.8	1625	61.05	.0101	1.213
184		.634	605	1.37	6353	2080	---	467	751	3186	1533	1326	1280	52.09	52.67	.8176	2.403	3782	24.0	1703	61.44	.0111	1.202
185		.627	612	1.37	6353	2215	---	466	750	3255	1570	1371	1322	52.43	53.05	.7976	2.374	3739	23.6	1747	61.36	.0117	1.188
186		.624	605	1.37	5808	1136	---	464	686	2459	1153	953	943	46.09	46.41	.8050	2.580	3948	24.4	1290	60.30	.0068	1.223
187		.629	603	1.37	5808	1305	---	466	695	2524	1255	1027	1038	45.92	46.28	.8102	2.458	3796	23.8	1397	61.25	.0079	1.209
188		.625	605	1.37	5808	1479	---	464	704	2660	1323	1095	1111	46.31	46.76	.7718	2.311	3702	22.7	1472	60.75	.0090	1.191
189		.634	609	1.37	5808	1602	---	463	709	2702	1440	1185	1224	45.69	46.17	.7796	2.280	3559	22.1	1544	57.95	.0096	1.178
190		.630	605	1.37	5808	1720	---	463	719	2715	1505	1244	1284	45.69	46.17	.7796	2.280	3559	22.1	1544	57.95	.0096	1.178
191		.619	608	1.37	4719	717	787	463	614	1615	987	753	841	33.07	33.27	.7796	2.145	3425	19.8	1164	61.47	.0105	1.176
192		.625	609	1.37	4719	743	793	463	614	1628	1003	768	857	33.31	33.52	.7796	2.145	3425	19.8	1164	61.47	.0105	1.176
193		.647	605	1.37	4719	851	801	464	619	1692	1067	829	920	33.24	33.48	.7796	2.145	3425	19.8	1164	61.47	.0105	1.176
194		.626	603	1.37	4719	917	785	465	625	1698	1150	862	995	32.14	32.39	.8072	1.970	3212	18.4	1292	60.86	.0071	1.160
195		.650	603	1.37	4719	1050	801	462	627	1790	1200	930	1083	32.09	32.38	.8094	1.925	3150	18.4	1349	59.07	.0091	1.156
196		.626	596	1.37	3630	588	776	462	546	1083	820	658	738	23.71	23.87	.7704	1.646	2854	12.8	922	58.93	.0069	1.108
197		.616	605	1.37	3630	617	781	463	548	1110	850	677	767	23.46	23.63	.7597	1.601	2752	12.1	953	57.96	.0073	1.108
198		.625	597	1.37	3630	655	777	463	551	1138	917	711	834	22.93	23.11	.7436	1.591	2713	12.1	1028	57.58	.0079	1.100
199		.633	610	1.37	3630	673	798	462	553	1179	945	741	857	23.29	23.58	.7752	1.591	2713	12.1	1028	57.58	.0079	1.100
200		.625	608	1.37	7260	2245	791	456	783	3468	1530	1287	1239	57.23	58.14	.8435	2.695	4324	27.7	1741	62.26	.0080	1.103
201		.616	612	1.67	7260	2375	793	459	787	3526	1590	1357	1302	57.23	57.69	.8339	2.637	4266	26.7	1787	62.26	.0115	1.235
202		.623	610	1.67	7260	2500	793	459	790	3574	1650	1384	1359	57.35	58.04	.8339	2.637	4266	26.7	1787	62.26	.0115	1.235
203		.627	608	1.67	7260	2625	792	458	792	3622	1650	1430	1359	57.39	58.12	.8416	2.583	4175	26.1	1868	62.80	.0121	1.214
204		.621	610	1.67	7260	2785	791	458	798	3682	1720	1471	1427	57.16	57.93	.8280	2.503	4097	25.4	1947	62.25	.0135	1.205
205		.623	607	1.67	7260	2980	789	458	806	3744	1810	1553	1507	56.81	57.67	.8536	2.411	4000	25.2	2042	62.64	.0151	1.201
206		.623	608	1.67	6897	1995	790	460	758	---	1443	1238	1178	56.40	56.95	.8167	2.554	4086	25.6	1628	62.53	.0098	1.225
207		.623	608	1.67	6897	2270	790	460	766	3407	1548	1334	1277	56.38	57.01	.8167	2.554	4086	25.6	1628	62.53	.0098	1.225
208		.624	608	1.67	6897	2560	790	459	773	3523	1643	1441	1370	56.50	57.21	.8187	2.445	3974	24.6	1857	62.70	.0126	1.199
209		.619	614	1.37	6897	2845	795	458	780	3630	1730	1533	1448	56.75	57.54	.8395	2.368	3882	24.0	1958	62.85	.0139	1.195
210		.625	608	1.67	6897	3015	791	459	787	3724	1793	1601	1506	56.28	57.12	.8449	2.326	3817	23.9	2026	62.07	.0149	1.191
211		.621	610	1.67	6353	1625	791	459	721	2943	1270	1132	1031	52.86	53.31	.8353	2.600	4128	26.3	1435	60.95	.0085	1.232
212		.625	610	1.67	6353	1880	794	462	733	3045	1428	1234	1185	52.84	53.16	.8112	2.468	3907	24.6	1605	62.55	.0099	1.205
213		.621	608	1.67	6353	2100	788	459	736	3130	1500	1315	1257	52.28	52.86	.8088	2.580	3820	23.9	1695	62.08	.0112	1.193
214		.625	608	1.67	6353	2220	791	459	739	3172	1543	1357	1296	52.42	53.04	.8198	2.538	3768	23.6	1744	62.41	.0118	1.191
215		.621	609	1.67	6353	2410	789	459	745	3263	1620	1426	1365	52.16	52.83	.8306	2.288	3685	22.9	1831	62.04	.0128	1.187
216		.625	609	1.67	5808	1209	794	462	681	2432	1150	971	939	46.70	47.04	.8335	2.505	3954	24.6	1293	61.67	.0072	1.225
217		.625	609	1.67	5808	1301	792	461	684	2476	1200	1009	987	46.56	46.92	.8267	2.454	3878	24.0	1351	61.84	.0078	1.216
218		.624	609	1.67	5808	1427	792	461	686	2532	1267	1061	1057	46.45	46.85	.8024	2.386	3779	23.2	1427	62.14	.0085	1.219
219		.624	610	1.67	5808	1550	794	460	690	2577	1330	1152	1123	46.22	46.95	.7833	2.317	3693	23.2	1500	62.76	.0093	1.199
220		.622	610	1.67	5808	1681	792	460	695	2629	1390	1157	1179	46.22	46.95	.7855	2.272	3617	22.7	1568	62.70	.0101	1.179
221		.622	605	1.67	4719	790	792	457	607	1632	995	773	850	33.51	33.73	.7842	2.110	3442	19.0	1130	61.08	.0065	1.171
222		.627	605	1.67	4719	800	798	457	608	1602	1010	777	866	33.35	33.57	.7922	2.062	3415	18.7	1147	62.43	.0067	1.166
223		.628	601	1.67	4719	850	784	457	610	1607	1043	797	900	33.15	33.39	.7870	2.016	3364	18.2	1185	62.92	.0071	1.15






Figure 1. - Installation of turbojet engine in altitude wind tunnel.




NACA
CD-2732

Figure 2. - Top view of turbojet-engine installation showing stations at which instrumentation was installed



(a) First-stage turbine rotor.


Figure 3. - Photographs of turbine rotors.



(b) Second-stage turbine rotor.


Figure 3. - Concluded. Photographs of turbine rotors.

2618



(a) Open.

Figure 4. - Photographs of variable-area turbine nozzles.



(b) Closed.

Figure 4. - Concluded. Photographs of variable-area turbine nozzles.






Figure 5. - Schematic sketch of variable-area turbine-nozzle actuating mechanism.



(a) Mid-vane cross-sections of two adjacent vanes ($2\frac{1}{2}$ times actual size).


(b) Side view of vane (actual size).

Figure 6. - Sketches of variable-area turbine-nozzle vanes in open and closed positions.



(a) Station 1, cowl inlet. Diameter, 34 inches; location, 6 inches downstream of cowl-inlet flange.

(b) Station 4, compressor outlet. Passage height, $3\frac{1}{8}$ inches; location, $\frac{1}{2}$ inch downstream of trailing edge of fixed vanes.



(c) Station 5, turbine inlet. Passage height, $6\frac{3}{4}$ inches; location, $1\frac{3}{4}$ inches upstream of leading edge of first-stage turbine-nozzle diaphragm.

(d) Station 6, turbine outlet. Passage height, $5\frac{5}{8}$ inches; location, $3\frac{3}{8}$ inches downstream of trailing edge of turbine rotor.

Figure 7. - Location of instrumentation (view looking downstream).




Figure 8. - Effect of turbine-nozzle area and corrected turbine speed on corrected turbine gas flow. Altitude, 30,000 feet; flight Mach number, 0.62.




Figure 9. - Variation of maximum corrected turbine gas flow or effective turbine-nozzle area with measured turbine-nozzle area. Altitude 30,000 feet; flight Mach number, 0.62.







Figure 10. - Effect of turbine-nozzle area and corrected turbine speed on turbine efficiency. Altitude, 30,000 feet; flight Mach number, 0.62.



(a) Variation of turbine pressure ratio with corrected turbine speed at constant engine speeds.




(b) Variation of turbine efficiency with corrected turbine speed at constant engine speeds.




(c) Cross plots showing variation of turbine efficiency with corrected turbine speed at constant values of turbine pressure ratio.


Figure 11. - Effect of various parameters on turbine pressure ratio and turbine efficiency. Altitude, 30,000 feet; flight Mach number, 0.62; turbine nozzle area, 1.15 square feet.



(a) Variation of turbine pressure ratio with corrected turbine speed at constant engine speeds.




(b) Variation of turbine efficiency with corrected turbine speed at constant engine speeds.




(c) Cross plots showing variation of turbine efficiency with corrected turbine speed at constant values of turbine pressure ratio.


Figure 12. - Effect of various parameters on turbine pressure ratio and turbine efficiency. Altitude, 30,000 feet; flight Mach number, 0.62; turbine nozzle area, 1.20 square feet.



(a) Variation of turbine pressure ratio with corrected turbine speed at constant engine speeds.



(b) Variation of turbine efficiency with corrected turbine speed at constant engine speeds.



(c) Cross plots showing variation of turbine efficiency with corrected turbine speed at constant values of turbine pressure ratio.

Figure 13. - Effect of various parameters on turbine pressure ratio and turbine efficiency. Altitude, 30,000 feet; flight Mach number, 0.62; turbine nozzle area, 1.30 square feet.







Figure 14. - Effect of various parameters on turbine pressure ratio and turbine efficiency. Altitude, 30,000 feet; flight Mach number, 0.62; turbine nozzle area, 1.37 square feet.



(a) Variation of turbine pressure ratio with corrected turbine speed at constant engine speeds.



(b) Variation of turbine efficiency with corrected turbine speed at constant engine speeds.



(c) Cross plots showing variation of turbine efficiency with corrected turbine speed at constant values of turbine pressure ratio.

Figure 15. - Effect of various parameters on turbine pressure ratio and turbine efficiency. Altitude, 30,000 feet; flight Mach number, 0.62; turbine nozzle area, 1.87 square feet.




Figure 16. - Effect of turbine-nozzle area and corrected turbine speed on turbine efficiency at constant values of turbine pressure ratio. Altitude, 30,000 feet; flight Mach number, 0.62.




Figure 17. - Comparison of efficiencies obtained with fixed turbine nozzles and with variable-area turbine nozzles for an actual turbine-nozzle area of 1.30 square feet. Altitude, 30,000 feet; flight Mach number, 0.62; engine speed, 7260 rpm.

NACA RM E52J20

National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

CONFIDENTIAL

SECURITY INFORMATION

1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
- I. Campbell, Carl E.
- II. Welna, Henry J.
- III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20

National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

CONFIDENTIAL

SECURITY INFORMATION

1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
- I. Campbell, Carl E.
- II. Welna, Henry J.
- III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20

National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

CONFIDENTIAL

SECURITY INFORMATION

1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
- I. Campbell, Carl E.
- II. Welna, Henry J.
- III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20

National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

CONFIDENTIAL

SECURITY INFORMATION

1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
- I. Campbell, Carl E.
- II. Welna, Henry J.
- III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20
National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

- CONFIDENTIAL
SECURITY INFORMATION
1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
I. Campbell, Carl E.
II. Welna, Henry J.
III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20
National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

NACA RM E52J20
National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

- CONFIDENTIAL
SECURITY INFORMATION
1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
I. Campbell, Carl E.
II. Welna, Henry J.
III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20
National Advisory Committee for Aeronautics.
PRELIMINARY EVALUATION OF TURBINE
PERFORMANCE WITH VARIABLE-AREA TURBINE
NOZZLES IN A TURBOJET ENGINE. Carl E.
Campbell and Henry J. Welna. May 1953. 33p.
diags., photos., tab. (NACA RM E52J20)

CONFIDENTIAL

The performance of a two-stage turbine with variable-area first-stage turbine nozzles was determined in the NACA Lewis altitude wind tunnel over a range of simulated altitudes from 15,000 to 44,000 feet and engine speeds from 50 to 100 percent of rated speed. The variable-area turbine nozzles were found to be mechanically reliable and to have negligible leakage losses. Increasing the turbine-nozzle-throat area from 1.15 to 1.67 square feet increased the corrected turbine gas flow or effective turbine nozzle area about 10 percent. At

Copies obtainable from NACA, Washington (over)

- CONFIDENTIAL
SECURITY INFORMATION
1. Engines, Turbojet (3.1.3)
2. Turbines, Axial-Flow (3.7.1.1)
I. Campbell, Carl E.
II. Welna, Henry J.
III. NACA RM E52J20



CONFIDENTIAL

NACA RM E52J20

a given corrected turbine speed and turbine pressure ratio, changing the turbine nozzle area from 1.30 to 1.67 square feet lowered the turbine efficiency 3 or 4 percent. The effect of increasing the turbine nozzle area from 1.15 to 1.67 square feet (decreasing the turning angle about $7-1/2^\circ$) would be to lower the turbine efficiency about 5 or 6 percent.

CONFIDENTIAL
SECURITY INFORMATION

NACA RM E52J20

a given corrected turbine speed and turbine pressure ratio, changing the turbine nozzle area from 1.30 to 1.67 square feet lowered the turbine efficiency 3 or 4 percent. The effect of increasing the turbine nozzle area from 1.15 to 1.67 square feet (decreasing the turning angle about $7-1/2^\circ$) would be to lower the turbine efficiency about 5 or 6 percent.

CONFIDENTIAL
SECURITY INFORMATION

Copies obtainable from NACA, Washington



CONFIDENTIAL

NACA RM E52J20

a given corrected turbine speed and turbine pressure ratio, changing the turbine nozzle area from 1.30 to 1.67 square feet lowered the turbine efficiency 3 or 4 percent. The effect of increasing the turbine nozzle area from 1.15 to 1.67 square feet (decreasing the turning angle about $7-1/2^\circ$) would be to lower the turbine efficiency about 5 or 6 percent.

CONFIDENTIAL
SECURITY INFORMATION

NACA RM E52J20

a given corrected turbine speed and turbine pressure ratio, changing the turbine nozzle area from 1.30 to 1.67 square feet lowered the turbine efficiency 3 or 4 percent. The effect of increasing the turbine nozzle area from 1.15 to 1.67 square feet (decreasing the turning angle about $7-1/2^\circ$) would be to lower the turbine efficiency about 5 or 6 percent.



CONFIDENTIAL

CONFIDENTIAL
SECURITY INFORMATION

Copies obtainable from NACA, Washington



CONFIDENTIAL

Copies obtainable from NACA, Washington



CONFIDENTIAL