

UNCLASSIFIED

AD NUMBER	
AD012951	
CLASSIFICATION CHANGES	
TO:	UNCLASSIFIED
FROM:	CONFIDENTIAL
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited.	
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; MAY 1953. Other requests shall be referred to Naval Proving Ground, Dahlgren, VA.	
AUTHORITY	
14 may 1976, usnswc; 14 may 1976, usnswc	

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AD

12951

CLASSIFICATION CHANGED

TO: UNCLASSIFIED

FROM: CONFIDENTIAL

AUTHORITY:

UNCLASSIFIED

CONFIDENTIAL

SECURITY INFORMATION

AD NO. 12-951
ASTIA FILE COPY

U. S. NAVAL PROVING GROUND
DAHLGREN, VIRGINIA

REPORT NO. 1134

EFFECT OF SOIL BARRIERS
ON
SHAPED CHARGE PENETRATION

FINAL Report

Copy No. 8

Task


Assignment AQ-4E, Marine Corps

Classification CONFIDENTIAL
SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

Effect of Soil Barriers on Shaped Charge Penetration
-----PART ASYNOPSIS

1. This test was conducted to determine the effect of dry and wet soil barriers (sand, loam, and clay) on shaped charge jet penetration. The 5" Rocket Head Mk 25, Composition B loaded, was used as the jet producer. After the jet passed through the soil barrier, it impinged upon a plate of armor steel. The residual penetration of the steel was measured in each case.

2. a. The minimum residual penetrations for the various soil barriers tested are as follows:

<u>Soil</u>	<u>Condition</u>	<u>Barrier</u>	<u>Minimum Residual Penetration</u>
Sand, loam, or clay	dry	4'	2"
Sand, loam, or clay	wet	4'	1"
Sand, loam, or clay	dry or wet	*3-1/2'	2"
Sand or loam	dry	3'	3"
Sand, loam, or clay	wet	3'	2-1/2"
Sand, loam, or clay	dry	2'	4"
Sand or loam	dry	2'	5-1/2"
Sand, loam, or clay	wet	2'	4"

* Interpolated from test results.

b. Varying soil had little effect on the amount of shaped charge penetration. Clay and wet soil barriers offered slightly more resistance to the shaped charge jet thereby reducing the amount of armor penetration.

Effect of Soil Barriers on Shaped Charge Penetration
-----TABLE OF CONTENTS

	<u>Page</u>
SYNOPSIS.	1
TABLE OF CONTENTS	2
AUTHORITY	3
REFERENCES.	3
BACKGROUND	3
OBJECT OF TEST.	3
PERIOD OF TEST.	3
REPRESENTATIVES PRESENT	4
DESCRIPTION OF ITEMS UNDER TEST	4
PROCEDURE	4
RESULTS AND DISCUSSION.	5
CONCLUSIONS	5
APPENDIX A - FIELD TEST SET UP.	FIGURE 1
APPENDIX B - PLATE AND SLUGS AFTER FIRING, PHOTOGRAPHS.	FIGURES 2-3 (Incl)
APPENDIX C - PLOTS, PENETRATION VERSUS DEPTHS	FIGURES 9-10 (Incl)
APPENDIX D - FIELD DATA	TABLES I-II (Incl)
APPENDIX E - DISTRIBUTION	1-2 (Incl)

Effect of Soil Barriers on Shaped Charge Penetration
-----PART BINTRODUCTION

1. AUTHORITY:

This test was authorized by reference (a).

2. REFERENCES:

- a. BUCRD Conf ltr S7c-1 Re2c-JSM:rjb Ser 48219 of
25 November 1952
- b. NAVORD Conf Report 2487 of 27 June 1952

3. BACKGROUND:

a. Shaped charges as anti-tank mines were developed during World War II. The Office of Naval Research is pursuing the use and application of these charges by investigating the effects of soil on various types of charges.

b. Reference (b) reported the effect of soil barriers on 1.563 and 3.25 diameter shaped charges. Reference (a) requested that tests be conducted with the 5" Rocket Head Mk 25 shaped charges for the Office of Naval Research and Headquarters, Marine Corps. The Naval Ordnance Test Station is conducting similar tests with different shaped charges.

4. OBJECT OF TEST:

This test was conducted to determine the effect of dry and wet soil barriers (sand, loam, and clay) on shaped charge jet penetration. The 5" Rocket Head Mk 25, Composition B loaded, was used as the jet producer.

5. PERIOD OF TEST:

- | | |
|-------------------------------------|------------------|
| a. Date Project Letter | 25 November 1952 |
| b. Date Necessary Material Received | 1 December 1952 |
| c. Date Commenced Test | 26 January 1953 |
| d. Test Completed | 3 April 1953 |

CONFIDENTIAL

NPG REPORT NO. 1134

Effect of Soil Barriers on Shaped Charge Penetration

6. REPRESENTATIVES PRESENT:

This test was witnessed in part by LCDR R. G. Gibson and LT J. E. Peterson representing the Office of Naval Research.

PART C

DETAILS OF TEST

7. DESCRIPTION OF ITEMS UNDER TEST:

a. 5" Rocket Head Mk 25 Mod 1, loaded with 16.0 lbs. of Composition B, Head Lot No. 71, Ammunition Lot RHCZ-6-HA-52, assembled with Mk 149 nose fuze modified for static detonation, and total assembled weight of 51.3±0.6 lbs. This head contains a copper cone.

b. 4-1/4" thick Class B armor plate.

c. Soil Barriers	% Water			Average
	Sample #1	#2	#3	
(1) Dry Sand -	0.08	0.10	0.09	0.09
(2) Dry Loam -	2.80	2.43	2.35	2.53
(3) Dry Clay -	2.05	1.69	1.91	1.88
(4) Wet Sand -	18.54	18.09	20.06	18.89
(5) Wet Loam -	32.37	29.94	27.92	30.08
(6) Wet Clay -	23.57	31.74	26.50	27.27

8. PROCEDURE:

The test set up is shown in Figure 1. After a 12" diameter hole was dug for the desired soil depth the rocket head was lowered base-down into the hole. The hole was then filled with loose soil. Either one (1) or two (2) thicknesses of 4-1/4" plate was placed over the expected jet exit on 12" high wooden blocks. During the filling of the hole with soil, a water hose saturated the soil if a wet soil condition was desired. The dry soil used was dried on a heated plate one (1) week before the test. Jet penetration was measured by a thin wire prober. The recorded penetrations are not the maximum since some jet material usually remained in the plate.

CONFIDENTIAL
SECURITY INFORMATION

Effect of Soil Barriers on Shaped Charge Penetration

9. RESULTS AND DISCUSSION:

The detailed field data are listed in Tables I and II. The plate penetrations are shown in Figures 2 to 7, inclusive. Typical jet slugs are shown in Figure 8. The average penetrations for dry and wet soils were plotted and are shown in Figures 9 and 10. The averaged data are summarized as follows:

Soil Type	Plate Penetration (Inches)					
	2' Soil		3' Soil		4' Soil	
	dry	wet	dry	wet	dry	wet
Sand	5-5/8	4-5/16	3-1/8	2-3/4	2-11/16	1-7/8
Loam	6-1/4	4-7/8	3-3/4	3-1/4	2-11/16	1-5/16
Clay	4-1/4	4-9/16	2-3/8	2-5/8	3-1/16	1-5/8

At the 2' and 3' soil barrier depths, the loam soil appeared to offer the least resistance to the shaped charge jet. A wet soil condition generally can be expected to reduce the plate thickness penetrated. At 4' barrier depths, the variation of soil did not result in any significant plate penetration differences.

PART DCONCLUSIONS

10. a. The minimum residual penetrations for the various soil barriers tested are as follows:

<u>Soil</u>	<u>Condition</u>	<u>Barrier</u>	<u>Minimum Residual Penetration</u>
Sand, loam, or clay	dry	4'	2"
Sand, loam, or clay	wet	4'	1"
Sand, loam, or clay	dry or wet	*3-1/2'	2"
Sand or loam	dry	3'	3"
Sand, loam or clay	wet	3'	2-1/2"
Sand, loam or clay	dry	2'	4"
Sand or loam	dry	2'	5-1/2"
Sand, loam, or clay	wet	2'	4"

* Interpolated from test results.

CONFIDENTIAL

NPG REPORT NO. 1134

Effect of Soil Barriers on Shaped Charge Penetration

b. Varying soil had little effect on the amount of shaped charge penetration. Clay and wet soil barriers offered slightly more resistance to the shaped charge jet thereby reducing the amount of armor penetration.

The tests upon which this report is based were conducted by:

LT A. N. HUGHES, Fragmentation Firing Officer
Fragmentation Division
Terminal Ballistics Department

This report was prepared by:

V. PHILIPCHUK, Fragmentation Battery Officer
Fragmentation Division
Terminal Ballistics Department

This report was reviewed by:

W. B. ROBERTSON, Lieutenant Commander, USN
Terminal Ballistics Officer
Terminal Ballistics Department
C. C. BRAMBLE, Director of Research, Ordnance Group

APPROVED: J. F. BYRNE
Captain, USN
Commander, Naval Proving Ground


E. A. RUCKNER
Captain, USN
Ordnance Officer
By direction

CONFIDENTIAL
SECURITY INFORMATION

CONFIDENTIAL

NPG REPORT NO. 1134

U. S. NAVAL PROVING GROUND
DAHLGREN, VIRGINIA


Final Report
on
Effect of Soil Barriers on Shaped Charge Penetration

Project: AC-4E, Marine Corps
Copy No.: 8
No. of Pages: 6

Date: MAY 29 1953

CONFIDENTIAL
SECURITY INFORMATION

SOIL BARRIER TEST



FIELD TEST SET UP

CONFIDENTIAL.
Security Information

FIGURE 1

APPENDIX A

04 09 06

05

04

03

02

00

08

1

06


NP9-63033

18 February 1953

CONFIDENTIAL
SECURITY INFORMATION

5" Rocket Head Mk 25-1 shaped charge impacts on armor plate after penetrating dry soil barriers.

FIGURE 3




MP9-63034

19 February 1953

CONFIDENTIAL
SECURITY INFORMATION

5" Rocket Head Nr 25-1 shaped charge impacts on armor plate after penetrating dry soil barriers.

FIGURE 4




WP-63035

26 January 1953

CONFIDENTIAL
SECURITY INFORMATION

5" Rocket Head Mk 25-1 shaped charge impacts on armor plate after penetrating wet soil -
barriers.

Plating 5



NP9-63036

28 January 1953

CONFIDENTIAL
SECURITY INFORMATION

5" Rocket Head Mk 25-1 shaped charge impacts on armor plate after penetrating wet soil barriers.

FIGURE 6



803
809


1P9-63037

20 January 1963

CONFIDENTIAL
SECURITY INFORMATION

50 Rocket Head 1K 25-1 shaped charge impact on armor plate after penetration of soil barriers.

Figure 1




179-13038

19 February 1953

CONFIDENTIAL
SECURITY INFORMATION

Sample copper jet slug recovered after crash, the only one of its kind.
5th rocket heads 1 k 15 and 1.

Page 6






Figure 9

Appendix C




Figure 10

Appendix C

Effect of Soil Barriers on Shaped Charge Penetration
-----TABLE I

Shaped Charge: 5" Rocket Head Mk 25-1

Soil Condition: Dry

<u>Rd. No.</u>	<u>Soil Barrier (feet)</u>	<u>Soil</u>	<u>Penetration (inches)</u>
1	3	clay	1-3/4
2	3	"	1-3/4
3	4	"	2-9/16
4	4	"	2-1/2
5	3	"	2-1/4
6	2	"	4-3/4
7	2	"	4-1/8
8	3	"	4-1/4 +
9	3	"	1-7/8
10	4	sand	2-7/8
11	3	"	2-1/4
12	2	"	6-1/16
13	2	"	5-3/16
14	3	"	4-1/4 +
15	3	"	*1-1/8
16	3	"	2-13/16
17	3	"	3-1/4
18	3	loam	4-1/4 +
19	3	"	* 13/16
20	3	"	3-9/16
21	3	"	2-5/8
22	2	"	6-15/16
23	2	"	5-1/2
24	3	"	4-1/4 +
25	4	"	2-11/16
26	4	sand	2-1/2
27	4	loam	*1-1/2
28	4	clay	3-5/8
29	4	"	3-5/8

+ indicates complete penetration of a 4-1/4" plate.

* penetration was greater than amount shown, part of cone stuck in plate. These values were not used in averaging.

Effect of Soil Barriers on Shaped Charge Penetration
-----TABLE II

Shaped Charge: 5" Rocket Head Mk 25-1

Soil Condition: wet

<u>Rd. No.</u>	<u>Soil Barrier (feet)</u>	<u>Soil</u>	<u>Penetration (inches)</u>
1	4	sand	1-7/8
2	3	"	4-1/16
3	3	"	3-1/16
4	2	"	4-5/16
5	3	"	9/16
6	4	clay	2-3/16
7	4	loam	2-5/16
8	3	sand	2-9/16
9	3	"	3-3/8
10	3	clay	1-7/8
11	3	"	1-1/2
12	3	loam	2-3/4
13	3	"	3-1/4
14	2	clay	4-5/8
15	4	loam	3/4
16	3	"	4
17	3	"	3-1/16
18	4	"	7/8
19	2	"	4
20	4	clay	1
21	2	"	4-1/2
22	3	"	3-1/4
23	3	"	2-3/4
24	2	loam	5-3/4