




PROPERTY OF RIL
TECHNICAL LIBRARY

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

WOODS HOLE OCEANOGRAPHIC INSTITUTION

Woods Hole, Massachusetts

In citing this manuscript in a bibliography
the reference should be followed by the
phrase: UNPUBLISHED MANUSCRIPT

Reference No. 54-25

MARINE METEOROLOGY

WHOI Airplane Turbulence and Flux
Measurements, O'Neill, Nebraska

August 21-28, 1953

By

Andrew F. Bunker

Technical Report No. 29
Submitted to the Office of Naval Research
Under Contract N6onr-27702(NR-082-021)

April 1954

APPROVED FOR DISTRIBUTION



Director

WEOI AIRPLANE TURBULENCE AND FLUX MEASUREMENTS

O'NEILL, NEBRASKA, AUGUST 21 - 28, 1953

I. INTRODUCTION

The primary purpose of this report is to distribute data obtained over the plains of Nebraska to other participants of the Great Plains Turbulence Field Program at O'Neill. Little discussion or analysis of the data can be given until more data, such as the wind profiles obtained by other groups, are reduced and made available. A complete analysis will be contained in the final report of the Air Force Program.

The field program in which the marine meteorology group at Woods Hole was invited to participate was conceived and organized by members of the Geophysics Research Directorate of the Air Force Cambridge Research Center. They and their contract organizations interested in the study of atmospheric turbulence set up their equipment in an east-west line across a flat field near O'Neill, Nebraska. The site was chosen for its extreme flatness and the predominance of southerly winds during the summer months. Figure 1 is a photograph which shows the observing line and the flatness of the surrounding land. The ground stations were operated from August 1, 1953 to September 8, 1953. Woods Hole personnel operated only between August 21 and August 28. During this interval 56 horizontal runs were made between 40 ft. and 7000 ft. above the ground.

II. THE AIRPLANE TECHNIQUE OF MEASURING SHEARING STRESSES, ROOT-MEAN-SQUARE TURBULENCE VELOCITY COMPONENTS AND HEAT FLUXES

Only brief mention will be made here of the airplane method of measuring stresses and velocity components since the technique was described in WHOI Ref. No. 53-52. (About 20 copies of this report to the Office of Naval Research are still available.) It is planned to submit a revised copy of the report to a meteorological journal in the near future.

The method may be summarized as follows: All of the many qualifications, limitations, and difficulties of the system will be passed over in this statement. When an airplane flies through a turbulent atmosphere the angle of attack continually changes thereby modifying the lift of the airplane. If instruments are mounted in the airplane to measure the vertical accelerations of the airplane, the airspeed, and the attitude of the airplane, then the vertical velocity of any gust may be computed by placing the observed values in the following equation.

$$w_1 = 4.98 \frac{\Delta n}{\rho V_t} - \frac{8.9 \times 10^3 \Delta V_t}{\rho \bar{V}_t^2} - \Delta \alpha_{att} V_t + \sum 1.1 \Delta n t_1 - w_0 \quad (1)$$

Here w_1 is the vertical component of the gust in cm/sec, Δn the observed vertical acceleration of the airplane, ρ the density of the air, V_t the true air speed, ΔV_t the deviation of the true airspeed from a line of regression upon time, $\Delta \alpha_{att}$ the change in attitude of the airplane, t_1 the time interval of the measurement, and w_0 the initial vertical velocity of the airplane. The coefficients in the equation depend on the mass of the airplane, its wing area and other considerations. Values of w' are obtained from the series of w_1 's

by eliminating any mean value of $\bar{w}_1$ and finding deviations from a line of regression of w_1 upon time. This step is necessary to eliminate the effect of any mean acceleration of the airplane, but it also eliminates the contribution of large eddies of the same size as the length of the observing run (1.5 km) to the shearing stress and root-mean-square velocity calculations.

The horizontal component of the gust velocity is obtained from the airspeed and the line of regression of the airspeed. Once the w_1 and u_1 values are obtained they may be combined to form the shearing stress, $-\bar{\rho} \overline{w'u'}$, and the root-mean-square velocities, $\sqrt{\overline{w'^2}}$, and $\sqrt{\overline{u'^2}}$. A thermocouple was mounted on the airplane so that deviations of the temperature could be combined with the w 's to form $cp \bar{\rho} \overline{w'T'}$, the heat flux.

Probable errors due to reading, calibrating, airplane deformation, instrumental inaccuracies, and symmetry assumptions are small. The errors arising from these causes based on 150 observational points amount to only ± 0.07 dynes cm^{-2} for the shearing stress, ± 1.7 cm sec^{-1} for $\sqrt{\overline{w'^2}}$, and ± 0.8 cm sec^{-1} for $\sqrt{\overline{u'^2}}$. These values are not, however, the total errors of the determinations. Phugoid motion (a vertical oscillation of the airplane of about 20 seconds period) can add up to ± 20 cm sec^{-1} to the root-mean-square velocities for an extreme case. In all cases presented here the oscillation was damped so that it is believed that this error does not exceed ± 5 cm sec^{-1} .

On August 25, 1953, the PBV flew past a tower on which Dr. Soumi had his sonic anemometer operating so a direct comparison of the two methods of determining $\sqrt{\overline{w'^2}}$ was made. The values obtained from the sonic anemometer mounted at 12 m were 72 and 68 cm sec^{-1} for the first and second run respectively. The PBV values were 58 and 60 cm sec^{-1} . The PBV value is based on a line of regression against time as described while the sonic

anemometer is based on a mean value constant with time. When the PBY data is reduced in a comparable way 76 and 77 cm sec⁻¹ are obtained for $\sqrt{w'^2}$.

The agreement between the values obtained by such widely differing methods of measurements proves that the airplane method is reliable to at least 10% accuracy and probably better. A frequency diagram (Figure 2) of the vertical velocities obtained by the two methods is presented to show that the distributions are nearly the same.

III. EQUIPMENT MOUNTED IN PBY AIRCRAFT

The accelerations of the airplane were measured by a Statham electric accelerometer mounted near the center of gravity of the airplane. The output of this strain gauge bridge was recorded by one channel of a nine channel CEC oscillograph. For the air speed, the dynamic and static pressures of two pitot static tubes, one mounted on each wing, were connected to a single Statham differential pressure gauge to give an average value over the wing-spread of the air speed. To record the attitude of the airplane a potentiometer circuit of an automatic pilot control was connected to the oscillograph. A reading of the attitude was made available to the pilot to enable him to keep the airplane at constant attitude. The thermopile was biased by two mercury cells and the resulting signal recorded on the oscillograph. The airplane's altimeter, airspeed indicator and flux gate compass were used for supplementary observations.

An airplane psychograph was mounted on the side of the nose turret to give dry- and wet-bulb temperatures of the air. Rod thermistors are used in a bridge circuit as the sensing elements. The output of the bridge is recorded on an L and N Speedomax self-balancing potentiometer.

IV. FLIGHT PROCEDURE

A standard flight pattern was developed that would meet the requirements of (1) safety with regard to both ground personnel and other sounding aircraft, (2) non-interference with ground observations, and non-interference of ground equipment with air observations, and (3) an extended horizontal upwind course over terrain comparable to that upwind of the ground stations. A course that met these requirements was an upwind course of 2-3 miles extent with an end point 200 or 300 yds east and north of the eastern end of the observing line. A left turn was made at this point and the airplane climbed to the starting point of the course for another run. During the horizontal runs all the equipment was operating. The psychrograph was operated alone during the 200 ft per minute climbs to the next run level.

Two exceptions to the above flight pattern were made on August 25, when comparison tests were run with the sonic anemometer of the University of Wisconsin. For this test two passes were made past the instrument mounted at 40 ft on a tower. Actually, the flight was made higher than the instrument although it was intended to be at the same level. The passes were made upwind as usual and the instruments were operating both prior to arrival at the tower and for a minute or so after its passage.

No winds were measured by drift meter since so many wind observations were made by the ground stations.

V. PRESENTATION OF REDUCED DATA

Both the graphical and tabular forms are used in the presentation of the reduced data. Certain quantities that are related have been plotted on the same height diagram to clarify their relationship and allow the reader to

get a complete picture of the variation of the quantities throughout the layer. The data is also tabulated for easy reference and extraction of exact values.

a) Psychrograph Data

Values of the potential dry-bulb temperature and the mixing ratio are collected in Table I. Not every value of the temperature and mixing ratio is given in the table. Rather, only enough significant levels are tabulated to show the variation with height and through the inversions. It will be noted that all available values have been plotted in the diagrams. The heights given in the table are heights in meters above the ground surface.

b) Turbulence and Flux Data

From the series of w_i , u_i and T_i obtained, the following quantities have been determined and entered in Table II. First, after an identifying run number and the height of the run above the ground, is the computed value of the shearing stress. It is found from the defining equation $\tau = -\rho \overline{w'u'}$ and the series of w_i and u_i values. In the next two columns are the values of $\sqrt{\overline{w'^2}}$ and $\sqrt{\overline{u'^2}}$. Next is the correlation coefficient between the w 's and the u 's. In the next column is the heat flux computed from $cp \overline{\rho w'T'}$. In the next column is the root-mean-square deviation of the dry-bulb temperature. In the last column a reliability indicator is entered. This key is based entirely on the change in attitude. If the attitude changed by less than $\pm 1^\circ$ the run is labelled, R, for reliable. If the attitude changed more than $\pm 1^\circ$, a U is entered indicating an unreliable run.

The data contained in Tables I and II have been plotted against height in seven diagrams, Figures 3 - 9. On the left is the potential dry-bulb

Psychograph Data O'Neill, Nebraska

TABLE I

<u>A</u>			<u>B</u>			<u>C</u>		
Aug. 21, 1953 1112 to 1140 CST			Aug. 22, 1953 1450 to 1540 CST			Aug. 24, 1953 1547 to 1649 CST		
Height m	Θd °C	w gm/kg	Height m	Θd °C	w gm/kg	Height m	Θd °C	w gm/kg
195	304.7	9.9	35	307.2	7.8	35	312.1	11.3
240	305.4	9.8	65	307.2	7.8	70	312.3	10.5
320	305.0	9.2	100	307.3	7.7	135	311.6	10.7
500	304.9	9.0	165	307.3	7.4	165	312.1	11.0
640	303.6	9.4	285	307.8	7.5	360	311.2	10.8
770	303.9	9.1	480	308.2	7.2	525	312.1	10.8
960	304.1	8.9	700	307.6	7.4	675	312.0	10.5
1110	304.2	8.5	900	307.5	7.2	845	311.7	10.7
1260	304.2	8.4	1020	307.6	7.3	1155	311.6	10.3
			1110	307.4	7.4	1310	312.2	10.2
			1260	307.4	7.2	1565	311.9	10.2
			1495	307.0	7.3	1805	311.4	10.1
						1950	311.5	10.0
						2070	311.6	9.9
						2130	312.2	8.8
						2215	314.5	6.7
<u>D</u>			<u>E</u>			<u>F</u>		
Aug. 25, 1953 1050 to 1150 CST			Aug. 25, 1953 1600 to 1630 CST			Aug. 27, 1953 1110 to 1211 CST		
Height m	Θd °C	w gm/kg	Height m	Θd* °C	w gm/kg	Height m	Θd °C	w gm/kg
35	307.4	Wick believed to be dry	180	312.6	Dry wick	35	308.2	13.3
65	307.2		360	312.6		65	308.0	13.5
100	307.0		490	312.5		100	308.5	13.5
130	307.0		660	312.5		130	308.1	13.5
165	307.3		825	312.5		165	308.1	13.4
210	307.1		1000	312.8		330	308.6	13.3
360	307.5					490	308.5	13.2
490	308.7					660	308.5	13.1
660	312.0					820	309.0	12.9
825	311.9					990	309.0	12.6
990	312.3					1140	309.0	12.0
						1170	311.2	10.3
						1200	309.5	11.8
						1260	311.6	10.0
						1365	311.5	9.6
						1540	312.9	8.5
						1670	312.1	8.3

*Temperature below
180 m off scale of
psychograph

Psychograph Data C'Neill, Nebraska

TABLE I
(continued)

G

Aug. 28, 1953
1043 to 1145 CST

Height m	Θd °C	w gm/kg
35	308.3	17.1
100	307.8	16.0
130	307.6	15.9
180	307.8	16.0
330	307.8	15.7
530	308.2	15.1
660	308.0	14.7
850	308.0	14.1
990	308.5	13.7
1140	312.4	12.0
1300	312.4	11.5
1500	313.4	11.9
1660	314.1	10.6

TABLE II

Turbulence and Flux Data

A

August 21, 1953					1012 to 1140 CST				
Run No.	Altitude feet	Stress dynes cm ⁻²	$\sqrt{w'^2}$ cm sec ⁻¹	$\sqrt{u'^2}$ cm sec ⁻¹	r	Heat Flux cal cm ⁻² sec ⁻¹	$\sqrt{T'^2}$ °C	Reliability	
379	500	0.04	68	51	-0.01	0.0010	0.12	R	
380	1000	1.4	86	49	-0.29	0.0005	0.09	R	
381	2000	1.0	66	65	-0.22	0.0007	0.08	R	
383	3000	-0.11	39	33	+0.06	0.0002	0.06	R	
384	3500	0.26	52	35	-0.13	-0.0004	0.09	R	

B

August 22, 1953					1450 to 1540 CST				
Run No.	Altitude feet	Stress dynes cm ⁻²	$\sqrt{w'^2}$ cm sec ⁻¹	$\sqrt{u'^2}$ cm sec ⁻¹	r	Heat Flux cal cm ⁻² sec ⁻¹	$\sqrt{T'^2}$ °C	Reliability	
386	100	0.74	61	98	-0.11	0.0007	0.16	U	
388	200	0.51	89	44	-0.14	0.002	0.18	U	
389	500	-1.3	62	65	+0.29	-0.002	0.13	U	
390	1000	1.16	97	86	-0.13	+0.002	0.15	R	
392	2000	0.96	67	79	-0.16	0*	0*	R	
393	3000	-3.05	82	71	+0.48	0*	0*	U	
394	4000	-0.64	70	58	+0.14	0*	0*	U	
395	5000	-0.99	76	66	+0.18	0*	0*	U	

* not measured

C

August 21, 1953					1547 to 1649 CST				
Run No.	Altitude feet	Stress dynes cm ⁻²	$\sqrt{w'^2}$ cm sec ⁻¹	$\sqrt{u'^2}$ cm sec ⁻¹	r	Heat Flux cal cm ⁻² sec ⁻¹	$\sqrt{T'^2}$ °C	Reliability	
398	100	-0.02	84	121	+0.002	+0.0017	0.17	U	
399	200	1.2	89	97	-0.13	+0.0019	0.18	U	
400	500	0.55	97	88	-0.06	+0.0017	0.13	R	
401	1000	-1.3	56	48	0.44	+0.0004	0.054	R	
402	2000	-0.13	63	45	-0.04	*	*	R	
403	3400	1.9	120	99	-0.14	*	*	R	
404	4000	-0.001	79	45	-0.0003	*	*	R	
405	5000	2.05	57	60	-0.64	*	*	R	
406	6000	-0.41	52	39	+0.18	*	*	R	

* not measured

TABLE II (continued)

Turbulence and Flux Data

D

August 25, 1953		1045 to 1115 CST				
Run No.	Altitude feet	Stress dynes cm ⁻²	$\sqrt{w'^2}$ cm sec ⁻¹	$\sqrt{u'^2}$ cm sec ⁻¹	r	Heat Flux cal cm ⁻² sec ⁻¹
410	100	3.11	77	109	-0.34	0.004
411	200	+3.32	92	73	-0.45	0.004
412	500	2.17	96	81	-0.25	0.001
413	1000	1.99	123	68	-0.22	0.003
414	2000	-0.16	19	15	-0.49	0.0002
415	3000	0.02	6	5	-0.57	*
416	1900 to 2100	-1.0	84	78	+0.14	-0.001
						0.93
						Reliability
						R
						U
						R
						R
						R
						U

-10-

E

August 25, 1953		1600 to 1650 CST				
Run No.	Altitude feet	Stress dynes cm ⁻²	$\sqrt{w'^2}$ cm sec ⁻¹	$\sqrt{u'^2}$ cm sec ⁻¹	r	Heat Flux cal cm ⁻² sec ⁻¹
418	3000	-0.78	85	65	+0.13	*
419	2000	-1.27	50	44	+0.53	*
420	1000	-0.09	37	33	+0.06	*
421	500	-0.20	58	45	+0.07	0.0006
422	200	1.82	70	70	-0.34	-0.0007
423	100	1.03	73	87	-0.15	0
424	40	1.9	58	103	-0.30	-0.0003
425	40	2.2	60	125	-0.41	0.0009
						0.055
						0.093
						0.08
						0.086
						0.140
						Reliability
						R
						R
						R
						R
						R
						U
						U

* not measured

TABLE II (continued)

Turbulence and Flux Data August 27, 1953 1110 to 1140 CST									
Run No.	Altitude feet	Stress dynes cm ⁻²	$\sqrt{w'^2}$ cm sec ⁻¹	$\sqrt{u'^2}$ cm sec ⁻¹	r	Heat Flux cal cm ⁻² sec ⁻¹	$\sqrt{T'^2}$ °C	Reliability	
429	100	-1.04	65	111	0.131	0.0015	0.25	R	
430	200	+0.42	66	77	-0.08	0.0003	0.13	R	
431	400-480	-0.59	58	54	+0.43	0.0010	0.13	R	
432	900	-2.29	93	45	+0.50	0.0003	0.08	R	
433	1900	+0.13	54	59	-0.04	0.0020	0.10	R	
434	3000	-0.02	85	38	0.001	-0.0030	0.20	R	
435	3700	-0.56	44	38	0.31	0.0023	0.30	R	
436	4000	+0.34	58	36	-0.15	-0.0072	0.63	R	
437	5000	+0.18	30	18	-0.29	0.0006	0.06	R	
439	4000	-0.49	58	55	0.14	0.0003	0.26	R	
August 28, 1953 1043 to 1136 CST									
441	100	+0.8	67	70	-0.17	0.0023	0.27	R	
442	200	+3.3	121	67	-0.37	0.0050	0.26	R	
443	500	+0.4	56	51	-0.14	0.0005	0.11	R	
444	1000	-1.18	109	48	0.204	0.0044	0.21	R	
445	2160	-4.13	104	79	0.512	0.0022	0.17	R	
446	3000	-0.63	51	40	0.281	-0.00006	0.24	R	
447	3400	-1.08	41	54	0.444	0.0010	0.62	R	
448	4000	-1.68	47	45	0.721	0.0003	0.10	R	
449	5000	0.14	24	15	-0.34	-		R	

temperature. All values measured are plotted here instead of the few significant ones in Table I. The range in temperature observed on any horizontal run is indicated by a line with an "x" at either end. If there was an appreciable change in altitude the line is drawn sloping to indicate the altitude change. Similarly, the mixing ratios are plotted both as points and range lines. The shearing stress and the heat flux have been plotted with a common zero line. Different symbols and scales reduce confusion of elements. On the right, $\sqrt{w'^2}$ and $\sqrt{u'^2}$ are also plotted with a common zero line and different symbols. The only other entry on the diagram is a horizontal line drawn to delineate the inversion at the top of the ground layer. This inversion was not reached in all soundings.

Only very limited discussion can be made of the data until wind profiles are available. Many of the height variations of the stress values seem most peculiar and can only be interpreted later in conjunction with the measured winds. It is hoped that such huge swings as the stress took on the 22nd, 27th, and 28th will be explained by the winds. It is of interest to note that on only one day did the stress have a large, positive value near the ground and decrease more or less linearly to zero near the ground layer inversion. This distribution of stress values corresponds to the variation expected if the air under the inversion reacted as though it were a liquid confined in an open channel, an assumption frequently made in dealing with the atmosphere. This observation that open channel-like flow occurred when the inversion was relatively low may give a clue as to the role of the inversion height in defining a single flow pattern or stratification of the air into several distinct flow regions.

Values of $-\overline{\rho w'u'}$ taken in or near an inversion should not be interpreted as a stress or flux of momentum. This is true since the airplane frequently passes from one air layer to the other. Thus correlation between w' and u' may be computed that have little or no relation to the actual shear. Similarly, heat fluxes computed may be dependent more on the number of times the airplane crosses the boundary than on the flow of heat.

The variation of the values of $\sqrt{w'^2}$ and $\sqrt{u'^2}$ may be commented upon briefly. One point of interest is that the $\sqrt{u'^2}$ is invariably greater than the $\sqrt{w'^2}$ at the 30 m level, but at either the 60 or 100 m level the $\sqrt{w'^2}$ becomes the larger. Above the 100 m level the values of both $\sqrt{w'^2}$ and $\sqrt{u'^2}$ are remarkably constant up to the vicinity of the inversion where they decrease rapidly to a small value. When values of the coefficient of turbulent mass exchange are computed it may be possible to determine the relation of the $\sqrt{w'^2}$ to the coefficient without relying on an unobservable mixing length.

No spectrum analyses have been run upon the present series of data. The limitations of the system are such that only a rather narrow spectral band could be investigated. The smallest averages of significance may be defined as either 10 or 20 m eddies while the largest are of the order 1000 m. Spectral analysis within these limits may be carried out with assurance of significance.

Acknowledgements

The author wishes to acknowledge the large part that Kenneth McCasland played in the success of the enterprise. He not only designed and constructed the control circuits for the recording system, but skillfully ran the oscillograph and its associated instruments during the observational runs.

All of the shearing stress and root-mean-square velocity computations were made by Miss Martha Walsh.



FIG. 1


28

—x—x— UNIV. OF WISC. SONIC ANEMOMETER ON 12 M TOWER $\sqrt{W'^2} = 68 \text{ CM SEC}^{-1}$

○—○— WHOI CALIBRATED PBY AIRCRAFT 15-23 M $\sqrt{W'^2} = 60 \text{ CM SEC}^{-1}$


24

FREQUENCY OF OCCURRENCE, %



AUG 25 1953 - 1645 HRS CST - O'NEILL, NEBRASKA

FIG. 2



• HEAT FLUX, CAL/CM²/SEC

AUG 21 1953 - 1012 CST

FIG. 3




FIG. 4

AUG 22 1953 - 1450 CST






FIG. 5




AUG 25 1953 - 1100 CST

FIG. 6




AUG 25 1953 - 1600 CST

FIG. 7



AUG 27 1953 - 1110 CST

FIG. 8



AUG 28 1953 -- 1043 CST

FIG. 9

Legends for Figures

- Figure 1. The flatness of the Nebraska plains can be judged from this photograph of the observing line at O'Neill.
- Figure 2. The frequency distribution of the turbulent vertical velocities as measured by the sonic anemometer and the airplane are compared. The distributions are very similar.
- Figure 3. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 21, 1953, 1012 to 1140 CST.
- Figure 4. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 22, 1953, 1450 to 1540 CST.
- Figure 5. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 24, 1953, 1547 to 1649 CST.
- Figure 6. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 25, 1953, 1045 to 1145 CST.
- Figure 7. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 25, 1953, 1600 to 1650 CST.

Legends for Figures
-continued-

Figure 8. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 27, 1953, 1110 to 1140 CST.

Figure 9. Observations of stress, root-mean-square velocities, heat flux, potential temperature, and mixing ratio obtained over O'Neill, Aug. 28, 1953, 1043 to 1136 CST.

Technical Report Distribution List
ONR Project NR-082-021

24 August 1953

- 1 -

<u>Addressee</u>	<u>Copies</u>
Geophysics Branch, Code 416, Office of Naval Research Washington 25, D. C.	2
Director, Naval Research Laboratory, Attention: Technical Information Officer, Washington 25, D. C.	6
Officer-in-Charge, Office of Naval Research London Branch Office, Navy No. 100, Fleet Post Office, New York, New York	2
Office of Naval Research Branch Office, 346 Broadway, New York 13, New York	1
Office of Naval Research Branch Office, 150 Causeway Street, Boston, Massachusetts	1
Office of Naval Research Branch Office, Tenth Floor, The John Crerar Library Building, 86 East Randolph Street, Chicago, Illinois	1
Office of Naval Research Branch Office, 1030 East Green Street, Pasadena 1, California	1
Office of Naval Research Branch Office, 1000 Geary Street, San Francisco, California	1
Office of Technical Services, Department of Commerce, Washington 25, D. C.	1
Armed Services Technical Information Center, Documents Service Center, Knott Building, Dayton 2, Ohio	5
Assistant Secretary of Defense for Research and Develop- ment, Attn: Committee on Geophysics and Geography, Pentagon Building, Washington 25, D. C.	1
Department of Aerology, U. S. Naval Post Graduate School, Monterey, California	1
Aerology Branch, Bureau of Aeronautics (Ma-5), Navy Department, Washington 25, D. C.	1
Mechanics Division, Naval Research Laboratory, Anacostia Station, Washington 20, D. C., Attention: J. E. Dinger, Code 3820	1

Technical Report Distribution List
ONR Project NR-082-021

24 August 1953

- 2 -

<u>Addressee</u>	<u>Copies</u>
Radio Division I, Code 3420, Naval Research Laboratory, Anacostia Station, Washington 20, D. C.	1
Meteorology Section, Navy Electronics Laboratory, San Diego 52, California, Attention: L. J. Anderson	1
Library, Naval Ordnance Laboratory, White Oak, Silver Spring 19, Maryland	1
Bureau of Ships, Navy Department, Washington 25, D. C., Attention: Code 851 (Special Devices Center)	1
Bureau of Ships, Navy Department, Washington 25, D. C., Attention: Code 327 (Technical Library)	2
Chief of Naval Operations, Navy Department, Washington 25, D. C., Attention: Op-533D	2
Oceanographic Division, U. S. Navy Hydrographic Office, Suitland, Maryland	1
Library, Naval Ordnance Test Station, Inyokern, China Lake, California	1
Project Arowa, U. S. Naval Air Station, Building R-48, Norfolk, Virginia	2
The Chief, Armed Forces Special Weapons Project, P. O. Box 2610, Washington, D. C.	1
Office of the Chief Signal Officer, Engineering and Technical Service, Washington 25, D. C., Attn: SIGGGM	1
Meteorological Branch, Evans Signal Laboratory, Belmar, New Jersey	1
Headquarters Quartermaster Research and Development Command. Quartermaster Research and Development Center, U. S. Army, Natick, Massachusetts. Attention: Environmental Protection Division	1
Office of the Chief, Chemical Corps, Research and Engineering Division, Research Branch, Army Chemical Center, Maryland	2

Technical Report Distribution List
ONR Project NR-082-021

24 August 1953

- 3 -

<u>Addressee</u>	<u>Copies</u>
Commanding Officer, Air Force Cambridge Research Center, 230 Albany Street, Cambridge, Massachusetts, Attention: ERHS-1	1
Headquarters, Air Weather Service, Andrews Air Force Base, Washington 20, D. C., Attention: Director Scientific Services	2
Commanding General, Air Materiel Command, Wright Field, Dayton, Ohio, Attention: MCREEO	1
Commanding General, Air Force Cambridge Research Center, 230 Albany Street, Cambridge, Massachusetts, Attention: CRHSL	1
Commanding General, Air Research and Development Command, P. O. Box 1395, Baltimore 3, Maryland	1
Department of Meteorology, Massachusetts Institute of Technology, Cambridge, Massachusetts, Attention: H. G. Houghton	1
Department of Meteorology, University of Chicago, Chicago 37, Illinois, Attention: H. R. Byers	1
Institute for Advanced Study, Princeton, New Jersey, Attention: J. von Neumann	1
Scripps Institution of Oceanography, La Jolla, California, Attention: R. Revelle	1
General Electric Research Laboratory, Schenectady, New York, Attention: I. Langmuir	1
St. Louis University, 3621 Olive Street, St. Louis 8, Missouri, Attention: J. B. Macelwane, S. J.	1
Department of Meteorology, University of California at Los Angeles, Los Angeles, California, Attention: M. Neiburger	1
Department of Engineering, University of California at Los Angeles, Los Angeles, California, Attention: L. M. K. Boelter	

24 August 1953

- 4 -

<u>Addressee</u>	<u>Copies</u>
Department of Meteorology, Florida State University, Tallahassee, Florida, Attention: W. A. Baum	1
Woods Hole Oceanographic Institution, Woods Hole, Massachusetts, Attention: C. Iselin	1
The Johns Hopkins University, Department of Civil Engi- neering, Baltimore, Maryland, Attention: R. Long	1
The Johns Hopkins University, Department of Physics, Homewood Campus, Baltimore, Maryland, Attention: G. Plass	1
New Mexico Institute of Mining and Technology, Research and Development Division, Socorro, New Mexico, Attention: E. Workman	1
University of Chicago, Department of Meteorology, Chicago 37, Illinois, Attention: H. Riehl	1
Woods Hole Oceanographic Institution, Woods Hole, Massachusetts, Attention: A. Woodcock	1
General Electric Research Laboratory, Schenectady, New York, Attention: V. Schaefer	1
Geophysical Institute, University of Alaska, College, Alaska, Attention: C. T. Elvey	1
Blue Hill Meteorological Observatory, Harvard University, Milton 86, Massachusetts, Attention: C. Brooks	1
Laboratory of Climatology, Johns Hopkins University, Seabrook, New Jersey	1
Department of Meteorology, New York University, New York 53, New York, Attention: B. Haurwitz	1
Texas A and M, Department of Oceanography, College Station, Texas, Attention: J. Freeman, Jr.	1
Massachusetts Institute of Technology, Department of Meteorology, 77 Massachusetts Avenue, Cambridge 39, Massachusetts, Attention: T. F. Malone	1

24 August 1953

- 5 -

<u>Addressee</u>	<u>Copies</u>
Rutgers University, College of Agriculture, Department of Meteorology, New Brunswick, New Jersey	1
National Advisory Committee of Aeronautics, 1500 New Hampshire Avenue, N. W., Washington 25, D. C.	2
U. S. Weather Bureau, 24th and M Streets, N. W., Washington 25, D. C., Attention: Scientific Services Division	2
Air Coordinating Committee, Subcommittee on Aviation Meteorology, Room 2D889-A, The Pentagon, Washington, D. C.	1
American Meteorological Society, 3 Joy Street, Boston 8, Massachusetts, Attention: The Executive Secretary	1
Research Professor of Aerological Engineering, College of Engineering, Department of Electrical Engineering, University of Florida, Gainesville, Florida	1
The Hydrographer, U. S. Navy Hydrographic Office, Washington 25, D. C.	8

ADDITIONAL DISTRIBUTION LIST

<u>Addressee</u>	<u>Copies</u>
Brookhaven National Laboratory, Upton, L. I., New York, Attention: Meteorology Group	1
Chemical Corps, Biological Laboratories, Technical Library, Camp Detrick, Frederick, Maryland	2
Dr. August Raspet, Engineering and Industrial Research Station, Mississippi State College, State College, Mississippi	2
Dr. E. W. Hewson, Diffusion Project, Round Hill, South Dartmouth, Massachusetts	1
Dr. Hunter Rouse, Director, Iowa Institute of Hydraulic Research, State University of Iowa, Iowa City, Iowa	1

Technical Report Distribution List
ONR Project NR-082 -021

24 August 1953

- 6 -

<u>Addressee</u>	<u>Copies</u>
Head, Department of Physics, University of New Mexico, Albuquerque, New Mexico	1
Mr. Wendell A. Mordy, Hawaiian Pineapple Research Institute, Honolulu, Hawaii	1
Dr. E. G. Bowen, Chief, Division of Radiophysics, Commonwealth Scientific Industrial Research Organization, University Grounds, Chippendale, N. S. W., Australia	1
Professor Max A. Woodbury, Department of Statistics, Wharton School, University of Pennsylvania, Philadelphia 4, Pennsylvania	1
Pennsylvania State College, School of Mineral Industries, State College, Pennsylvania, Attention: H. Panosfky	1
University of Wisconsin, Department of Meteorology, Madison, Wisconsin, Attention: V. Suomi	1