

UNCLASSIFIED

AD NUMBER	
AD070852	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; May 1955. Other requests shall be referred to Naval Proving Ground, Dahlgren, VA.
AUTHORITY	
31 May 1967 per DoDD 5200.10; Naval Surface Weapons Center ltr dtd 20 Jan 1976	

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD _____

*Reproduced
by the*

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS
DOD DIR 5200.10

UNCLASSIFIED

Best Available Copy

20050216191

AD 70852

Armed Services Technical Information Agency

Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO

Best Available Copy

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE OR USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

CONFIDENTIAL

**NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE
NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING
OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794.
THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN
ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.**

CONFIDENTIAL

NPG Report No. 1365

SECURITY CLASSIFICATION
reviewed by
SOLID PROPELLANT INFORMATION AGENCY
NO CHANGE RECOMMENDED

HEAT INPUT CALCULATED FROM
BORE SURFACE TEMPERATURES IN GUNS

FC

RECEIVED



**U. S. NAVAL PROVING GROUND
DAHLGREN, VIRGINIA**

SECURITY CLASSIFICATION
reviewed by
SOLID PROPELLANT INFORMATION AGENCY
NO CHANGE RECOMMENDED

Copy No. 62

CONFIDENTIAL

SEP 29 1955

Date 5 May 1955

Best Available Copy

55 AA

39713

CONFIDENTIAL

U. S. Naval Proving Ground
Dahlgren, Virginia

Heat Input Calculated from
Bore Surface Temperature in Guns
by

J. Nanigian
Armament Department

NPG REPORT NO. 1365

Foundational Research
Project NPG-M-11016-9

5 May 1955

APPROVED: J. F. BYRNE
Captain, USN
Commander, Naval Proving Ground



E. A. RUCKNER
Captain, USN
Ordnance Officer
By direction

CONFIDENTIAL

55 AA

39712

CONTENTS

	<u>Page</u>
Abstract	ii
Foreword	iii
Introduction	1
Description of Material.	2
Description of Test Equipment.	2
Procedure.	5
Results and Discussion	7
References	9
Appendix:	
A. Distribution	

Figures:

1. Bore Temperature and Heat Input Curves at the Origin of Rifling (3"/70 Type E Mod 0 Gun)
2. Bore Temperature and Heat Input Curves at 3000 from the Breech Face (40mm Mark A Mod 1 Gun)
3. Reproduction of Bore Surface Temperature Oscillograms (40mm Mark A Mod 1 Gun)

Tables:

1. Chemical and Physical Characteristics of Powders used in the 3"/70 Type E Mod 0 Gun
2. Chemical and Physical Characteristics of SPDN-8541

ABSTRACT

Heat transfer curves calculated from bore surface temperature time curves are presented. Bore surface temperatures were recorded on the 3"/70 Type E Mod O Gun at the origin of rifling region and the 40mm Mark A Mod 1 Gun at 30° from the breech face. Typical "hot" and "cool" powders were used on the 3"/70 gun firings and typical solid and liquid propellants were used on the 40mm gun firings.

The results indicate that the total heat transferred to the 3"/70 barrel at the origin of rifling region is approximately proportional to the calculated flame temperatures of the two powders. Both powders were fired under similar firing conditions at service velocities. The total heat transferred to the 40mm barrel at 30° from the breech face for the liquid propellant rounds is about 80% of the total heat input transferred for the solid propellant rounds. However, in this instance, the firing conditions were not identical since the muzzle velocity for the solid propellant rounds was 2800 fps and only 2500 fps for the liquid propellant rounds.

FOREWORD

This is the fourth partial report on Foundational Research Project NPG-M-11016-9, "Investigation of Heat Input to Guns by Strain Gauge Methods and Bore Surface Temperature Measurements", and the twenty-fifth partial report under the Foundational Research Program of the Naval Proving Ground authorized by reference (a).

The firings on the 3"/70 Type E Mod 0 Gun reported in this test were conducted during October thru November 1953. The firings on the 4.0mm gun were conducted during September 1954. The computations were done during the period from December 1954 to January 1955 on the Aiken Relay Calculator located at the Naval Proving Ground.

The author wishes to acknowledge the assistance and cooperation of Messrs. J. H. Walker and M. Macchia in carrying out the work involving the use of the Aiken Relay Calculator. Also, the author is indebted to Mr. R. I. Rossbacher for his assistance with the mathematics involved in the heat transfer calculations.

This report was reviewed by:

W. F. VOSE, Commander, USN, Main Battery Officer
Armament Department
H. S. OVERMAN, Director of Research
Armament Department
D. R. MARZETTA, Commander, USN, Armament Officer
N. A. M. RIFFOLT, Director of Research

INTRODUCTION

Much time and effort have been spent on the problem of determining the heat transfer to a gun barrel during firing. The factors of gun erosion, thermal stresses, optimum firing rates and barrel coolants depend upon the heat transfer to the barrel. Until recently, the heat input to the barrel has been estimated by the following conventional methods: (1) external thermocouples applied to the barrel, (2) embedded thermocouples and (3) external strain gauges installed on the barrel to record the thermal strain.

Each of these methods has its disadvantages, and it has long been recognized that the ideal method for measuring the heat transfer to the barrel consisted of measuring the temperature history of the bore surface. The rigid requirements for such a thermocouple have prevented the recording of these measurements on large caliber guns until recently (references (b) and (c)).

With the advent of a thermocouple capable of recording the bore surface temperature histories of large caliber guns accurately and consistently, the problem of calculating the heat transfer and the rate of heat transfer has been simplified. Similar bore surface thermocouples have been recently constructed for use on small caliber guns by the Naval Proving Ground.

The object of this report is to present heat transfer data calculated from typical bore surface temperature measurements on the 3"/70 Type E Mod 0 and the 40mm Mark A Mod 1 Guns. Bore surface temperature measurements were taken on the 3"/70 gun at the origin of rifling, using both "hot" and "cool" powders. Bore surface temperatures were recorded on the 40mm gun at 30°0 from the breech face, using both solid and liquid propellants.

DESCRIPTION OF MATERIAL

3"/70 Type E Mod O Gun Powders:

Two different powders were used in these firings: SPDN-10114, a "hot" powder with a calculated flame temperature of 2481°K, and EX 6586, a "cool" powder with a calculated flame temperature of 2065°K. The chemical and physical characteristics of these powders are contained in Table 1. Both powders were fired under identical conditions using a 15.0 pound projectile at a muzzle velocity of approximately 3400 fps.

40mm Mark A Mod 1 Gun Propellants:

Both solid and liquid propellants were used in these firings. The solid propellant consisted of 305.3 gms of SPDN-8541 with a calculated flame temperature of 2380°K. The chemical and physical characteristics of this powder are contained in Table 2. The liquid propellant consisted of 180 gms of 67% hydrazine, 23% hydrazine nitrate and 10% water, with 5% free volume. Mark 2 projectiles, whose weights were adjusted to 902 gms, were fired with both types of propellants. The muzzle velocities on the solid and liquid propellant rounds were about 2800 fps and 2500 fps respectively. The maximum breech pressures on the solid and liquid propellant rounds were about 45,000 psi and 50,000 psi respectively. (Bore surface temperatures were taken on this gun incidental to other tests.)

DESCRIPTION OF TEST EQUIPMENT

3"/70 Type E Mod O Gun:

The bore surface thermocouple used on this gun is described in detail in references (b) and (c). Briefly, the thermocouple consists of a strip of nickel foil, approximately 1/8" wide and 0.0002 thick, which is sandwiched between the flat surfaces of a split steel cylinder. Two thin sheets of mica (3-6 microns thickness) are used for insulation between the two elements.

TABLE 1

Chemical Characteristics (Per Cent Composition)						
Powder Index	Nitrocellulose	Dinitrotoluene	Diphenylamine	Centralite	Dibutylphthalate	Total Volatiles
						Ash
SPDN-10114	82.33	11.35	.99	--	3.40	1.86
						.07
EX 6586	20.33					
		Nitroglycerin	Piorite			
		8.90	60.74	2.09	7.94	.20
						.04

Physical Characteristics

Powder Index	Diameter (D) (in.)	Diameter of Per. (d) (in.)	Web (in.)			Length (L) (in.)	Web Var.	L/D	D/d	Form	No. of Perf.	No. of Grs./lb.	S.G.	Calc. Flame Temp. °K	Nominal Flame Temp. °K
			Inner	Outer	Avg.									°K	
SPDN-10114	.254	.023	--	.049	.046	.606	--	2.4	11.0	Cyl.	7	637	1.6	2481	2500
EX 6586	.1425	.0132	.0248	.0266	.0257	.3500	7.0	2.45	10.8	Cyl.	7	3326	1.58	2065	2100

TABLE 2
CHEMICAL AND PHYSICAL CHARACTERISTICS OF SPDN-8541

Chemical Composition
(Per Cent Composition)

Nitrocellulose	Diphenylamine	Dinitrotoluene	Dibutylphthalate	Potassium	
				Sulfate	Alcohol Water
81.33	1.08	10.41	5.21	.91	.58 .48

<u>Physical Characteristics</u>						
Diam. of Perf.	Average Web	Length of Grain	No. of Perf.	No. of grs./lb.	Ratio of Specific Heats	Calculated Flame Temp.
"1195	"0132	"0200	7	6523	1.2609	2380°K
		"2707				300,200 ft./lb./lb.

The two metals comprising the thermocouple may be made of any thermoelectric combination, although it is best to use for the split cylindrical sections the same material as the metal wall whose temperature is to be recorded. The assembly containing the split cylinder, mica and nickel foil is then threaded into an appropriate steel housing. Set screws and a press-fit ring are used to keep the unit together tightly. The end surface of the assembly is ground flat and polished perpendicular to the crack. A number of thermoelectric junctions are thus formed on the exposed surface.

40mm Mark A Mod 1 Gun:

The bore surface thermocouples used on this gun embodied a slight modification of the design described above. The two semicylindrical steel sections (comprising the steel element) were made in the form of a tapered wedge which was press-fitted into a steel housing containing an appropriate hole. The larger diameter of the wedge was exposed to the bore. This modification allowed for the construction of thermocouples to fit into a small hole drilled to the bore of the barrel. A total of 15 rounds were fired in the 40mm gun using this bore surface thermocouple with the thermal junction remaining in excellent condition throughout the test. The end surface of the thermocouple was recessed .0005 from the bore wall on these firings.

PROCEDURE

3"/70 Type E Mod 0 Gun:

The two representative bore surface temperature time curves chosen for analysis appeared in reference (c) as rounds 2 and 5 for the "hot" and "cool" powders respectively. The test procedure was outlined in that reference. Also, pressure curves and additional bore surface temperature curves using these two powders are contained in reference (c). The thermocouple was installed at the location 34 inches from the breech face which corresponds to the origin of rifling region on this barrel.

40mm Mark A Mod 1 Gun:

Firings were conducted using the 40mm Mark A Mod 1 gun barrel mounted in the 6-pounder mount Mark 7 Mod 1. The bore surface thermocouple was installed at the location 30" from the breech face. (The origin of rifling is 12" from the breech face.) The bore surface temperature curves for the solid and liquid propellants are typical for these propellants when firing in a "dry" barrel. When the barrel was lubricated prior to firing, the recorded bore temperatures were about 25% lower in magnitude and also had a slower rise time. Since the barrel is normally cleaned and greased at the end of each day's firing, the temperature records for the "warming" or first round of each day's firings were not used.

Heat Transfer Calculations:

It is assumed that the cylindrical divergence and the longitudinal flow of heat may be neglected during the firing of a single round. Also, it is assumed that the barrel may be represented by a semi-infinite medium. Since the bore surface temperature varies with time, it can be shown (reference (d)) that the temperature increment at any point in the medium is given by the equation:

$$\Delta T = \frac{x}{2\sqrt{\pi h}} \int_0^t \frac{\phi(\beta)}{(t-\beta)^{3/2}} e^{-\frac{x^2}{4h(t-\beta)}} d\beta \quad (1)$$

where

β = time variable of integration

$\phi(\beta)$ = instantaneous bore surface temperature

x = distance from bore surface

h = thermal diffusivity

Since the heat input per unit area of the bore is given by $Q = \int_0^{\infty} C_p \rho \Delta T dx$, one finds by performing the integration over x , with the above expression for ΔT that:

$$Q(t) = \frac{k}{\sqrt{\pi h}} \int_0^t \frac{\phi(\beta)}{\sqrt{(t-\beta)}} d\beta \quad (2)$$

with k the thermal conductivity. (It is assumed that the thermocouple is recording the temperature at the bore surface so that $\phi(\beta)$ is known.) The rate of heat transfer then is

$$q(t) = \frac{k}{\sqrt{\pi h}} \int_0^t \frac{d\phi(\beta)}{d\beta} \frac{d\beta}{\sqrt{(t-\beta)}} \quad (3)$$

It must be remembered that the heat transfer calculations are taken as valid only up to the instant of projectile exit from the barrel.

The method of computing the actual values consisted of fitting parabolas to each set of three consecutive data points along the whole range of data points and then computing $Q(t)$ and $q(t)$ over each parabola. The intervals of time were adjusted so that no appreciable change in the calculated values resulted from any further subdivisions.

RESULTS AND DISCUSSION

3"/70 Type E Mod O Gun:

The bore surface temperature-time curves and the calculated heat transfer curves are contained in Figure 1. The total heat inputs at the instant of projectile exit are 31 cal./sq.cm. and 24 cal./sq.cm. for the "hot" and "cool" powders respectively. Thermal conductivity and




FIGURE 1
BORE TEMPERATURE AND HEAT INPUT CURVES
AT THE ORIGIN OF RIFLING

3770 TYPE E MOD O GUN

NP9-67447

diffusivity were assumed constant in these calculations. The paragraph Thermal Conductivity and Diffusivity below contains a discussion of the effects of temperature on these properties and the resulting effects on the heat transfer calculations. It is interesting to note that over one-half of the total heat input occurs during the first two milliseconds after projectile passage for both types of powders.

40mm Mark A Mod 1 Gun:

The bore surface temperature-time curves and the calculated heat transfer curves are shown in Figure 2. Each of these temperature-time curves represents the average of three rounds. The variation in the recorded temperatures for each set of three rounds with each type of propellant was not more than 10°C. These rounds are representative of the 15 rounds fired in this test, excluding the warming rounds. Four of the six original temperature oscillograms are reproduced in Figure 3. Note the extremely rapid response of the thermocouple at the instant of projectile passage on the solid propellant rounds, Figure 3. During the firing of the liquid propellant rounds, some temperature rise was indicated by the thermocouple prior to projectile passage. This is attributed to leakage of propellant past the sealing band of the projectile causing combustion in front of the projectile. (Pressure gauges installed at this location showed a rise in pressure prior to projectile passage also.) This temperature rise prior to projectile passage was neglected in the calculations of heat transfer on the liquid propellant rounds.

The total heat inputs at the instant of projectile exit from the barrel are 6.2 cal./sq.cm. and 5.1 cal./sq.cm. for the solid and liquid propellant rounds respectively. Because of the different muzzle velocities, the projectile exit times were slightly different for the two types of propellants as noted on the curves in Figure 2. Over one-half the total heat input occurs during the first 0.5 millisecond after projectile passage for both types of propellants.





FIGURE 2

BORE TEMPERATURE AND HEAT INPUT CURVES AT 30.0 FROM THE BREECH FACE

40MM MARK A MOD 1 GUN




Timing Marks: 1000 cps
Location of Thermocouple: 30V0 from Breech Face
September 1954

CORE SURFACE TEMPERATURE
OSCILLOGRAMS

NP9-67547
CONFIDENTIAL

40MM Mark A Mod 1 Gun

Figure 3



Timing Marks: 1000 cps
Location of Thermocouple: 30V0 from Breech Face
September 1954

BORE SURFACE TEMPERATURE
OSCILLOGRAMS

NP9-67547
CONFIDENTIAL

40MM Mark A Mod 1 Gun

Figure 3

Thermal Conductivity and Diffusivity:

The values for thermal conductivity and diffusivity used for the calculations in this report were 0.11 cal./sec.cm.² °C/cm. and 0.096 cm.²/sec. respectively. It was assumed that both of these properties were independent of temperature to simplify the calculations. Tests have been conducted in England and this country which show that these properties decrease in value by about 30% for steels in the temperature range above 800°C. Using these figures, the heat transfer values would be reduced by about 15%. Since the bore surface temperature curve for the "hot" powder used in the 3"/70 gun was well above 800°C during the time interval to projectile exit, the total heat input would be 26 cal./sq.cm. using these values. Also, since the bore surface temperature curve for the "cool" 3"/70 powder was about 800°C or higher for most of the time interval to projectile exit, the same values for these properties may be used with little loss in accuracy. This would then yield a total heat input of 21 cal./sq.cm. for the "cool" powder. These values for the total heat inputs for these two powders are very closely proportional to their respective calculated flame temperatures.

The bore surface temperatures recorded on the 40mm gun were relatively low and the heat transfer data would not change appreciably with the slight changes in the thermal properties over this temperature range.

REFERENCES

- (a) BUORD ltr Reb-1:LHT:mmt NP9 of 14 July 1952
- (b) NPG Conf Report No. 1130 "A Thermocouple to Record Transient Temperatures at the Bore Surface of Guns" of 15 July 1953
- (c) NPG Conf Report No. 1296 "Bore Surface Temperatures in the 3"/70 Type E Mod O Gun Using Hot and Cool Powders" of 4 October 1954
- (d) "Mathematical Theory of the Conduction of Heat in Solids" by H. S. Carslaw, 1945

APPENDIX A

DISTRIBUTION

Bureau of Ordnance:

Ad3	1
Ad8	4
Re2	1
Re2a	1
Re2d	1
Re5e	1

Commanding General
Aberdeen Proving Ground
Aberdeen, Maryland
Attn: Technical Information Section
Development and Proof Services 2

Commander, Operational Development Force
U. S. Atlantic Fleet, U. S. Naval Base
Norfolk 11, Virginia 1

Chief of Ordnance
Department of the Army
Washington 25, D. C.
Attn: ORDTU 1

Chief of Ordnance
Department of the Army
Washington 25, D. C.
Attn: ORDTA 2

Allegany Ballistics Laboratory
P. O. Box 210
Cumberland, Maryland 1

Armor Research Foundation of
Illinois Institute of Technology
Technology Center
Chicago 16, Illinois
Attn: Propulsion and Structures
Research; Department M 1

DISTRIBUTION (Continued)

Atlantic Research Corporation 812 North Fairfax Street Alexandria, Virginia	1
Arthur D. Little, Inc. 30 Memorial Drive Cambridge 42, Massachusetts Attn: W. C. Lothrop	1
Bureau of Mines 4800 Forbes Street Pittsburgh 13, Pennsylvania Attn: Explosives and Physical Sciences Division	1
Catholic University of America 7th St. and Michigan Ave., N. E. Washington 17, D. C. Attn: F. O. Rice	1
Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTX-AR	1
Commander, U. S. Naval Ordnance Test Station Inyokern, China Lake, California Attn: Technical Library Branch	2
Commander, U. S. Naval Air Missile Test Center Point Mugu, California Attn: Technical Library	1
Commander, U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland Attn: Library	2
Commanding General Frankford Arsenal Bridge and Tacony Streets Philadelphia 27, Pennsylvania Attn: Pitman-Dunn Laboratory	1

DISTRIBUTION (Continued)

Commanding General Wright Air Development Center Wright-Patterson AFB, Ohio Attn: WCEGH-2 WCLPN-2 WCRRC	1 1 1
Commanding General Aberdeen Proving Ground Aberdeen, Maryland Attn: Ballistic Research Laboratories ORDGC-BLI	2
Commanding General Redstone Arsenal Huntsville, Alabama Attn: Technical Library	2
Commanding Officer Office of Ordnance Research Box CM Duke Station Durham, North Carolina	3
Commanding Officer Picatinny Arsenal Dover, New Jersey Attn: Library	2
Commanding Officer Indiana Arsenal Charlestown, Indiana	1
Commanding Officer Radford Ordnance Works Radford, Virginia	1
Commanding Officer Sunflower Ordnance Works Lawrence, Kansas	1

DISTRIBUTION (Continued)

Commanding Officer
U. S. Naval Powder Factory
Indian Head, Maryland
Attn: Research and Development Department 2

Commanding Officer
Office of Naval Research
Branch Office
86 E. Randolph Street
Chicago 1, Illinois
Attn: LTJG M. C. Laug 1

Commanding Officer
Office of Naval Research
1030 E. Green Street
Pasadena 1, California 1

Commanding Officer
Badger Ordnance Works
Baraboo, Wisconsin
Attn: R. R. Buell 1

Department of the Air Force
Hq. USAF, DCS/D
Washington 25, D. C.
Attn: AFDRD-AR 1
AFDRD-AN, Maj H. R. Schmidt 1

E. I. du Pont de Nemours and Company
10th and Market Streets
Wilmington, Delaware
Attn: W. F. Jackson 1

Hercules Experimental Station
Wilmington, Delaware
Attn: A. M. Ball 1

Director
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena 3, California 1

DISTRIBUTION (Continued)

Midwest Research Institute 4049 Pennsylvania Kansas City, Missouri Attn: Technical Director	1
University of Michigan Engineering Research Institute Ann Arbor, Michigan Attn: J. C. Brier	1
Naval Ordnance Research School of Chemistry University of Minnesota Minneapolis 14, Minnesota Attn: B. L. Crawford, Jr.	1
Rohm and Haas Company Redstone Arsenal Research Division Huntsville, Alabama Attn: Technical Director	1
Solid Propellant Information Agency Applied Physics Laboratory The Johns Hopkins University Silver Spring, Maryland Attn: P. K. Reily, Jr.	8
Western Cartridge Company East Alton, Illinois	1
Olin Mathieson Chemical Corporation East Alton, Illinois Attn: R. A. Cooley	1
Olin Mathieson Chemical Corporation New Haven, Connecticut Attn: R. L. Womer	1

DISTRIBUTION (Continued)

Southwest Research Institute
8500 Culebra Road
San Antonio, Texas
Attn: Dr. J. H. Wiegand

1

British Joint Services Mission
Technical Services
1800 K Street, N. W.
Washington, D. C.
Attn: C. G. Lawson
Via: BUORD (Ad8)

4

Canadian Joint Staff
2001 Connecticut Ave., N. W.
Washington 6, D. C.
Attn: Defense Research Member
Via: BUORD (Ad8)

4

Local:

OR
OMBR
OM-1
OMIR
OML
OMIV
File

1
1
1
1
1
1
1