

UNCLASSIFIED

AD NUMBER

AD075314

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

**Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 20 JUN 1955.
Other requests shall be referred to Naval Ordnance Laboratory, White Oak MD 20993.**

AUTHORITY

USNOL ltr, 29 Aug 1974

THIS PAGE IS UNCLASSIFIED

AD 75314

Armed Services Technical Information Agency

**Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO**

This document is the property of the United States Government. It is furnished for the duration of the contract and shall be returned when no longer required, or upon recall by ASTIA to the following address:
Armed Services Technical Information Agency, Document Service Center,
Knott Building, Dayton 2, Ohio.

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

UNCLASSIFIED

AD No. 75314

ASTIA

5th copy

NAVORD REPORT 4022

FC

THE LAMINAR BOUNDARY LAYER ON A ROTATING CYLINDER IN CROSSFLOW

20 JUNE 1955



U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

Aeroballistic Research Report 288

THE LAMINAR BOUNDARY LAYER ON A ROTATING CYLINDER IN CROSSFLOW

Prepared by:

E. Krahn

ABSTRACT: A rotating cylinder in a stream produces a circulation which is regarded as the cause of the Magnus force. The problem is to find the dependence of the circulation on the rotational speed of the cylinder. This question is treated in the present report for a stationary flow about a circular cylinder with the axis perpendicular to the direction of the stream under the assumption that the flow in the boundary layer is laminar. Two approximate methods are used for the calculation of the boundary layer. One is due to Burgers and the other is an adaptation of the Polhausen method. In the case of only one stagnation line on the surface of the cylinder the boundary layer is evaluated numerically, the profiles and the shearing stress computed.

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, SILVER SPRING, MARYLAND

20 June 1955

This report contains information concerning the laminar boundary layer on a rotating cylinder and the circulation in the potential flow around the cylinder. It is a step in the calculation of the Magnus force.

This work has been carried out at the Naval Ordnance Laboratory under Task NOL - A3d - 453 - 1 - 55.

The results are distributed to outside research agencies for information and for use in the study of spinning bodies of revolution.

JOHN T. HAYWARD
Captain, USN
Commander

H. H. KURZWEG, Chief
Aeroballistic Research Department
By direction

NAVORD Report 4022

CONTENTS

1.	Introduction	page 1
2.	Burgers' method	1
3.	Notations	1,2
4.	The potential flow	2
5.	Velocity in the boundary layer according to Burgers' method	3
6.	Determination of the circulation	5
7.	The momentum equation	6, 7
8.	The velocity profile	7
9.	The differential equation of the form parameter	8,9,10
10.	Investigation of the singularities and the solution in the case of one stagnation point	11,12,13
11.	Discussion of other cases	14

ILLUSTRATIONS

Figure 1.	Notations	page 1
Figure 2.	Path of integration in the X,Y plane	11
Figure 3.	Singularities of Y'	12
Figure 4.	A saddle point	13
Figure 5.	A solution in the X,Y plane in the case of one stagnation point	16
Figure 6.	Velocity profiles	17
Figure 7.	The form parameter K	18
Figure 8.	The shearing stress	19
Figure 9.	Integral curves for negative X	14


THE LAMINAR BOUNDARY LAYER ON A ROTATING CYLINDER IN CROSSFLOW

1. An infinite cylinder is rotating in a stream perpendicular to the axis and a stationary flow has developed. The fluid is supposed to be incompressible but viscous. The Reynolds number is assumed small enough to insure a laminar boundary layer. The question is, how does the circulation in the surrounding flow depend on the speed of the rotation? The answer will be sought by the calculation of the boundary layer. This will be carried out by two different methods independently. First by an approximate method due to J. M. Burgers and then by the solution of the momentum equation.

2. J. M. Burgers [1] calculated the flow around a non-rotating cylinder by a method which has not been much used later. He got a separation of the flow at an angle of 120° from the stagnation point, a result which does not agree with the experiments nor with other calculations. This is due to the fact that he took the pressure distribution of the surrounding potential flow as given in the case of a stream attached to the cylinder on the whole surface. Hiemenz [2] carried out the calculation of the same flow by a different method by using a velocity distribution of the potential flow taken from experiments and got a separation at 83° . Applying the method of Blasius one gets the same result, which coincides with the experimental data.

Recalculating Burgers' result with the pressure distribution used by Hiemenz one gets the point of separation at 88° , which does not differ so very much from the exact result. It is therefore of interest to use this method in the calculation of the boundary layer on the rotating cylinder, so much the more as it is easier to apply than other methods.

3. Notations.



- x, y - Cartesian coordinates
- r, φ - polar coordinates
- a - radius of the cylinder
- l - length of the cylinder
- U_0 - velocity of the surface of the cylinder
- U_∞ - velocity of the potential flow at infinity
- U - velocity of the potential flow near the surface of the cylinder

Fig. 1

u - velocity component of the flow in the boundary layer in the direction parallel to the surface of the cylinder.

v - velocity component of the flow in the boundary layer in the r -direction

ω - vorticity

NAVORD Report 4022

ϕ, ψ - potential and stream function of the potential flow

v_x, v_y - velocity components in the boundary layer parallel to the x- and the y-axis.

γ - angle between the radius to the stagnation point and the negative x - axis

ρ - density

μ - viscosity

τ - shearing stress

ν - kinematic viscosity

Re - Reynolds' number

Γ - circulation

δ - thickness of the boundary layer

η - distance from the cylinder in radial direction

K - form parameter

$$X = \frac{U}{U_0}$$

$$Y = \frac{KU}{10U_0}$$

$$c = \frac{4U_\infty}{U_0}$$

ξ - parameter

$$t = \frac{\eta}{\delta}$$

P - power

4. The stationary potential flow around the cylinder is given by

$$\phi = -U_\infty \left(r + \frac{a^2}{r} \right) \cos \varphi + \frac{\Gamma}{2\pi} \cdot \varphi$$

$$\psi = U_\infty \left(r - \frac{a^2}{r} \right) \sin \varphi + \frac{\Gamma}{2\pi} \log \frac{r}{a}$$

$$u = U_\infty \left(1 + \frac{a^2}{r^2} \right) \cos \varphi + \frac{\Gamma}{2\pi} \cdot \frac{1}{r}$$

NAVORD Report 4022

If the circulation Γ does not exceed $4\pi U_\infty a$ then there are one or two stagnation points on the circle (stagnation lines on the cylinder) and Γ can be written as

$$\Gamma = 4\pi U_\infty a \sin \gamma.$$

From now on, this expression for Γ (which is a restriction on the amount of circulation) will be used.

For the flow near the surface of the cylinder one can take $r = a$ and has then

$$U = 2U_\infty (\sin \varphi + \sin \gamma)$$

$$\phi = 2U_\infty a (\varphi \sin \gamma - \cos \varphi).$$

These expressions will be further used for U and ϕ .

5. Burgers' method consists in starting from the equation of the vorticity in a stationary flow

$$(1) \quad v_x \frac{\partial \omega}{\partial x} + v_y \frac{\partial \omega}{\partial y} = \nu \left(\frac{\partial^2 \omega}{\partial x^2} + \frac{\partial^2 \omega}{\partial y^2} \right)$$

and substituting for the velocity components in the boundary layer those of the potential flow outside the boundary layer, i.e.

$$v_x = \frac{\partial \psi}{\partial y} \quad v_y = -\frac{\partial \psi}{\partial x} \quad ,$$

where ψ is the stream function of the potential flow. Transforming (1) from the variables x, y to the variables ϕ, ψ he gets

$$\frac{\partial \omega}{\partial \phi} = \nu \left(\frac{\partial^2 \omega}{\partial \phi^2} + \frac{\partial^2 \omega}{\partial \psi^2} \right).$$

In conformity with usual boundary layer simplifications $\frac{\partial^2 \omega}{\partial \psi^2}$ is dropped as small compared with $\frac{\partial^2 \omega}{\partial \phi^2}$ and

$$(2) \quad \frac{\partial \omega}{\partial \phi} = \nu \frac{\partial^2 \omega}{\partial \phi^2}$$

results. A solution of (2) is

$$\omega = \frac{1}{\sqrt{\phi - \xi}} \cdot e^{-\frac{\psi^2}{4\nu(\phi - \xi)}}$$

where ξ is an arbitrary parameter.

As (2) is a linear equation, then with an arbitrary function $A(\xi)$

$$\omega = -\frac{1}{2} \int_{\phi_1}^{\phi} \frac{A(\xi)}{\sqrt{\pi\nu(\phi-\xi)}} \cdot e^{-\frac{\psi^2}{4\nu(\phi-\xi)}} d\xi$$

is also a solution. ϕ_1 is the value of ϕ at the forward stagnation point.

To get the velocity component u in the boundary layer in the direction tangential to the circle (surface of the cylinder) $\frac{\partial v}{\partial \varphi}$ is neglected compared with $\frac{\partial u}{\partial \tau}$ in

$$\omega = \frac{1}{2} \left(\frac{\partial v}{\partial \varphi} - \frac{\partial u}{\partial \tau} \right)$$

as v , the velocity component in the radial direction, is zero at the surface and small inside the boundary layer. Then

$$\omega = -\frac{1}{2} \frac{\partial u}{\partial \tau} = -\frac{1}{2} \frac{\partial u}{\partial \psi} \cdot u.$$

The application of this method to the problem at hand requires now the determination of the constants and the function $A(\xi)$.

For $\psi = 0$ there must be $u = U_0$ and for sufficiently large ψ there must be $u = U$.
Writing

$$u = U_0 + \frac{1}{u} \int_{\phi_1}^{\phi} A(\xi) \left\{ \int_0^{\psi} \frac{e^{-\frac{\psi^2}{4\nu(\phi-\xi)}}}{\sqrt{\pi\nu(\phi-\xi)}} d\psi \right\} d\xi$$

and taking into account

$$\int_0^{\infty} \frac{e^{-\frac{\psi^2}{4\nu(\phi-\xi)}}}{\sqrt{\pi\nu(\phi-\xi)}} d\psi = 1,$$

the condition for $A(\xi)$ becomes

$$u = U_0 + \frac{1}{u} \int_{\phi_1}^{\phi} A(\xi) d\xi.$$

Thus

$$A(\phi) = (2u - U_0) \frac{du}{d\phi}$$

and

$$(3) \quad u = U_0 + \frac{1}{u} \int_{\phi_1}^{\phi} (2u - U_0) \frac{du}{d\xi} \left\{ \int_0^{\psi} \frac{e^{-\frac{\psi^2}{4\nu(\phi-\xi)}}}{\sqrt{\pi\nu(\phi-\xi)}} d\psi \right\} d\xi.$$

Here ϕ and ψ of the potential flow are regarded as coordinates in the boundary layer, where ψ is not the stream function of the viscous flow.

U is regarded as a function of ϕ only. This corresponds to the assumption of a pressure in the boundary layer, which depends on ϕ only and not on r .

Velocity profiles can be easily computed by (3), but one should remember that (3) is an approximate expression only, representing u correctly at the surface of the cylinder and at the outer limit of the boundary layer.

6. To determine the circulation about the cylinder from (3) small values of ψ will be considered and higher than first order terms in ψ will be neglected. Then

$$\int_0^\psi \frac{e^{-\frac{\psi^2}{4\nu(\phi-\xi)}}}{\sqrt{\pi\nu(\phi-\xi)}} d\psi = \frac{\psi}{\sqrt{\pi\nu(\phi-\xi)}}.$$

Making the substitution

$$r = a + \eta$$

and retaining linear terms only in η

$$\psi = 2 U_\infty \eta (\sin \phi + \sin \gamma) = U \eta.$$

(3) becomes thus

$$u = U_0 + \frac{\eta}{U} \int_{\phi_1}^{\phi} (2U - U_0) \frac{dU}{d\xi} \cdot \frac{U}{\sqrt{\pi\nu(\phi-\xi)}} d\xi.$$

The integral must be equal to zero for $U=0$ to give a finite value to u . That is the case at the forward stagnation point where $\phi = \phi_1$. At the rear stagnation point it gives a condition for U_0 . Inserting the values of U and ϕ

$$\int_{-\gamma}^{\pi+\gamma} \frac{(\sin \phi + \sin \gamma - \frac{U_0}{4U_\infty}) \cos \phi (\sin \phi + \sin \gamma)}{\sqrt{(\pi+\gamma)\sin \gamma - \cos(\pi+\gamma) - \phi \sin \gamma + \cos \phi}} d\phi = 0$$

or

$$(4) \quad \frac{U_0}{4U_\infty} = \int_{-\gamma}^{\pi+\gamma} \frac{(\sin \phi + \sin \gamma)^2 \cos \phi}{\sqrt{\cos \phi + \cos \gamma + (\pi+\gamma-\phi) \sin \gamma}} d\phi : \int_{-\gamma}^{\pi+\gamma} \frac{(\sin \phi + \sin \gamma) \cos \phi}{\sqrt{\cos \phi + \cos \gamma + (\pi+\gamma-\phi) \sin \gamma}} d\phi.$$

The denominator of each integral is zero at $\phi = \pi + \gamma$, nevertheless the integrals converge. This can be seen if ϵ is introduced by the substitution

$$\phi = \pi + \gamma - \epsilon$$

and the integrals calculated from $\pi + \gamma - \epsilon$ to $\pi + \gamma$. They become then

$$-\cos^3 \gamma \sqrt{\frac{2}{\cos \gamma}} \cdot \frac{\epsilon^2}{2} \quad \text{and} \quad -\cos^2 \gamma \sqrt{\frac{2}{\cos \gamma}} \cdot \epsilon$$

respectively. This proves the statement.

The integrals in (4) were evaluated numerically, except in the case $\gamma = 0$ where an exact integration is possible, and the following values were found

γ	0	$\frac{\pi}{6}$	$\frac{\pi}{3}$	$\frac{\pi}{2}$
$\frac{U_0}{U_\infty}$	1.6	2.5	3.2	3.6

These results need some explanation.

If the cylinder does not rotate then the separation occurs on both sides, let us call them the upper and the lower sides, symmetrically. If the cylinder rotates in such a way that on the upper side the rotation is in the direction of the flow, then on this side the point of separation will be farther from the forward stagnation point than in the case of the non-rotating cylinder, and on the lower side it will be nearer.

The result for $\gamma = 0$ means that in case of a speed ratio 1.6 the flow will be attached to the cylinder on the upper half, whereas on the lower side it separates and therefore the velocity distribution assumed for U does not apply here.

Similarly in case of $\gamma = \frac{\pi}{6}$ and $\gamma = \frac{\pi}{3}$, where the calculation is valid on the upper part from stagnation point to stagnation point.

One cannot expect from these results that they are precise, because in deriving (4) too many terms were neglected. One should not be surprised if the figures are erroneous by 10 or 20 per cent. Nevertheless they are of the same order as the experimental results and show that e.g. in the case of $\gamma = \frac{\pi}{2}$ the circulation in the boundary layer decreases from its value at the surface of the cylinder to about half its amount in the potential flow, for at the surface

$$\Gamma = 2\pi a U_0 = 7.2\pi a U_\infty$$

whereas in the potential flow

$$\Gamma = 4\pi a U_\infty.$$

7. To get more reliable results a different method will be applied. The boundary layer equation shall be taken in the form

$$(5) \quad u \frac{\partial u}{\partial \varphi} + v \frac{\partial u}{\partial r} = U \frac{dU}{d\varphi} + \nu \frac{\partial^2 u}{\partial r^2}.$$

Here the centrifugal term is omitted. This is justifiable as long as the thickness of the boundary layer is small compared with the radius of the cylinder.

The other equation is the continuity equation

$$(6) \quad \frac{1}{a} \frac{\partial u}{\partial \varphi} + \frac{\partial v}{\partial r} = 0.$$

The boundary conditions are

$$(7) \quad \begin{array}{lll} \text{for } r=a: & u = u_0 & v = 0 \\ \text{for } r=a+\delta: & u = U & \frac{\partial u}{\partial r} = 0 \end{array} \quad \frac{\partial^2 u}{\partial r^2} = 0,$$

where δ is the boundary layer thickness.

Further the variable

$$\eta = r - a$$

will be used.

Eliminating v from (5) and (6) and integrating over the thickness of the boundary layer the momentum equation results

$$(8) \quad 2 \int_0^\delta u \frac{\partial u}{\partial \varphi} d\eta - U \int_0^\delta \frac{\partial u}{\partial \varphi} d\eta = U \frac{dU}{d\varphi} \cdot \delta - a v \frac{\partial u}{\partial \eta} \Big|_{\eta=0}.$$

8. The solution will be sought in the form

$$u = \sum_{k=0}^4 a_k t^k,$$

where the a_k are functions of φ and $t = \frac{\eta}{\delta}$.

By the 5 boundary conditions (7) the 5 functions a_k are determined and the solution is

$$(9) \quad u = U_0 + (2t - 2t^3 + t^4)(U - U_0) + \frac{1}{6}(t - 3t^2 + 3t^3 - t^4)KU,$$

where

$$(10) \quad K = \frac{\delta^2}{a v} \cdot \frac{dU}{d\varphi}.$$

Only the boundary layer thickness δ will be used, as the displacement thickness

$$\int_0^\delta \left(1 - \frac{u}{U}\right) d\eta$$

does not seem reasonable in the present case. It could be replaced perhaps by

$$\int_0^\delta \frac{u - U}{U_0 - U} d\eta \quad \text{or} \quad \int_0^\delta \frac{u - U}{U_0} d\eta.$$

9. Substituting (9) in (8) one gets the following equation

$$\begin{aligned}
 & 2\delta \left\{ \frac{7}{10} u_0 \frac{du}{d\varphi} + \frac{1}{120} u_0 \frac{d(Ku)}{d\varphi} + \frac{367}{630} (u - u_0) \frac{du}{d\varphi} + \frac{71}{15120} (u - u_0) \frac{d(Ku)}{d\varphi} + \right. \\
 & \quad \left. + \frac{71}{15120} Ku \frac{du}{d\varphi} + \frac{1}{9072} Ku \frac{d(Ku)}{d\varphi} \right\} + \\
 (11) \quad & + 2 \frac{d\delta}{d\varphi} \left\{ -\frac{3}{10} u_0 (u - u_0) + \frac{1}{120} u_0 Ku - \frac{263}{1260} (u - u_0)^2 + \frac{71}{15120} (u - u_0) Ku + \right. \\
 & \quad \left. + \frac{1}{18144} (Ku)^2 \right\} - \\
 & - u \delta \left\{ \frac{7}{10} \frac{du}{d\varphi} + \frac{1}{120} \frac{d(Ku)}{d\varphi} \right\} + \frac{d\delta}{d\varphi} \left\{ \frac{3}{10} u (u - u_0) - \frac{1}{120} u \cdot Ku \right\} = \\
 & = \delta u \frac{du}{d\varphi} - av \left\{ \frac{2}{\delta} (u - u_0) + \frac{1}{6\delta} Ku \right\}.
 \end{aligned}$$

Eliminating av by

$$av = \frac{\delta^2}{K} \cdot \frac{du}{d\varphi}$$

the last term in (11) becomes

$$-\frac{2\delta}{Ku} u (u - u_0) \frac{du}{d\varphi} - \frac{\delta}{6} u \frac{du}{d\varphi}.$$

Further the following notations will be used

$$(11a) \quad \frac{u}{u_0} = X \quad \frac{Ku}{10u_0} = Y.$$

After division by $\delta U_0 \frac{dU}{d\varphi}$ the equation (11) becomes

$$\begin{aligned} & 2 \left\{ \frac{7}{10} + \frac{1}{12} \frac{dY}{dX} + \frac{367}{630} (X-1) + \frac{71}{1512} (X-1) \frac{dY}{dX} + \frac{71}{1512} Y + \frac{100}{9072} Y \frac{dY}{dX} \right\} + \\ & + \frac{2}{\delta} \frac{d\delta}{dX} \left\{ -\frac{3}{10} (X-1) + \frac{1}{12} Y - \frac{263}{1260} (X-1)^2 + \frac{71}{1512} (X-1) Y + \frac{100}{18144} Y^2 \right\} - \\ & - X \left\{ \frac{7}{10} + \frac{1}{12} \frac{dY}{dX} \right\} + \frac{1}{\delta} \frac{d\delta}{dX} \left\{ \frac{3}{10} X(X-1) - \frac{1}{12} X Y \right\} = \\ & = X - \frac{1}{5} \frac{X(X-1)}{Y} - \frac{1}{6} X. \end{aligned}$$

Now $\frac{1}{\delta} \frac{d\delta}{dX}$ has to be expressed by X, Y and known functions.

As

$$Y = \frac{\delta^2}{10av} \cdot \frac{U}{U_0} \cdot \frac{dU}{d\varphi}$$

then

$$\frac{dY}{dX} = \frac{2\delta}{10av} \cdot \frac{d\delta}{dX} \cdot \frac{U}{U_0} \cdot \frac{dU}{d\varphi} + \frac{\delta^2}{10avU_0} \left[\left(\frac{dU}{d\varphi} \right)^2 + U \frac{d^2U}{d\varphi^2} \right] : \frac{dU}{U_0 d\varphi}$$

and

$$\frac{1}{Y} \cdot \frac{dY}{dX} = \frac{2}{\delta} \cdot \frac{d\delta}{dX} + \frac{1}{X} + \frac{U_0 \frac{d^2U}{d\varphi^2}}{\left(\frac{dU}{d\varphi} \right)^2}.$$

Using

$$U = 2 U_\infty (\sin \varphi + \sin \gamma)$$

one gets

$$\frac{U_0 \frac{d^2U}{d\varphi^2}}{\left(\frac{dU}{d\varphi} \right)^2} = - \frac{U_0}{2 U_\infty} \cdot \frac{\sin \varphi}{1 - \sin^2 \varphi}.$$

Introducing a constant c by

$$4 U_{\infty} = c U_0$$

and expressing $\sin \varphi$ by

$$\sin \varphi = \frac{U}{2 U_{\infty}} - \sin \gamma = \frac{U_0}{2 U_{\infty}} X - \sin \gamma = \frac{2}{c} X - \sin \gamma$$

there is

$$\frac{U_0 \frac{d^2 U}{d \varphi^2}}{\left(\frac{dU}{d\varphi}\right)^2} = \frac{4X - 2c \sin \gamma}{4X^2 - 4Xc \sin \gamma - c^2 \cos^2 \gamma}$$

Thus,

$$\begin{aligned} \frac{2}{\delta} \frac{d\delta}{dX} &= \frac{1}{Y} \cdot \frac{dY}{dX} - \frac{1}{X} - \frac{4X - 2c \sin \gamma}{4X^2 - 4Xc \sin \gamma - c^2 \cos^2 \gamma} \\ &= \frac{1}{Y} \frac{dY}{dX} - \frac{2X^2 - 1.5Xc \sin \gamma - 0.25c^2 \cos^2 \gamma}{X(X^2 - Xc \sin \gamma - 0.25c^2 \cos^2 \gamma)} \end{aligned}$$

Further Y' is written for $\frac{dY}{dX}$ and the momentum equation becomes after multiplication by $\frac{Y}{2}$,

$$\begin{aligned} Y' \left\{ \frac{100}{9072} Y^2 + \frac{71}{1512} (X-1)Y + \frac{1}{12} Y - \frac{3}{20} (X-1) + \frac{1}{24} Y - \frac{263}{2520} (X-1)^2 + \frac{71}{3024} (X-1)Y + \right. \\ \left. + \frac{100}{36288} Y^2 - \frac{1}{24} XY + \frac{3}{40} X(X-1) - \frac{1}{48} XY \right\} + \\ + \frac{1}{10} Y + \frac{307}{630} (X-1)Y + \frac{71}{1512} Y^2 - \frac{7}{20} XY - \frac{5}{12} XY + \frac{1}{10} X(X-1) - \\ - \frac{Y(2X^2 - 1.5Xc \sin \gamma - 0.25c^2 \cos^2 \gamma)}{2X(X^2 - Xc \sin \gamma - 0.25c^2 \cos^2 \gamma)} \left\{ -\frac{2}{10} (X-1) + \frac{1}{12} Y - \frac{263}{1260} (X-1)^2 + \frac{71}{1512} (X-1)Y + \frac{100}{18144} Y^2 + \frac{3}{20} X(X-1) - \frac{1}{24} XY \right\} = 0. \end{aligned}$$

This equation is now multiplied by 72.576 and solved with respect to Y'

$$Y' = \{ Y(2X^2 - 1.5Xc \sin \gamma - 0.25c^2 \cos^2 \gamma)(0.2Y^2 + 0.192XY + 1.32Y - 2.1312X^2 - 1.1808X + 3.312) + \\ (12) \quad + X(X^2 - Xc \sin \gamma - 0.25c^2 \cos^2 \gamma)(-3.408Y^2 + 13.3632XY - 8.5248Y + 7.2576X - 7.2576X^2) \} : \\ : \{ X(X - 0.5c \sin \gamma + 0.5c)(X - 0.5c \sin \gamma - 0.5)(Y - 1.2X + 1.2)(Y + 1.776X + 2.76) \} .$$

10. X varies on the upper side of the cylinder from zero at the stagnation point to $0.5c(1 + \sin \gamma)$ at $\varphi = \frac{\pi}{2}$ and decreases then to zero at the rear stagnation point. On the lower side X decreases from zero at the forward stagnation point to $0.5c(-1 + \sin \gamma)$ at $\varphi = -\frac{\pi}{2}$ and increases again to zero at the rear stagnation point.

As Y is the product of a positive quantity with $U \frac{dU}{d\varphi}$ then it is zero at the forward stagnation point, assumes positive values for increasing φ and decreases to zero at $\varphi = \frac{\pi}{2}$, then it is negative for larger values of φ and becomes zero again at the rear stagnation point. On the lower side of the cylinder Y is zero at the forward stagnation point, assumes further negative values until $\varphi = -\frac{\pi}{2}$, where it is zero again, then becomes positive and decreases to zero at the rear stagnation point.




Fig.2

values of X and Y to $(0.5c(\sin \gamma - 1), 0)$ and returns through positive values of Y to $(0, 0)$.


Thus the solution (Fig.2) of the differential equation must start from $(0, 0)$, proceed through positive values of X and Y to $(0.5c(1 + \sin \gamma), 0)$ and return through negative values of Y to $(0, 0)$. The solution for the lower part of the cylinder starts from $(0, 0)$, proceeds through negative

The question is whether for a given γ there is a solution satisfying these conditions for every given value of c or only for certain values of c or for none.

One should expect a solution for only one value of c because a circulation in the flow should be produced uniquely by a certain spin of the cylinder.

To find an answer to the question the singularities of the differential equation have to be investigated.

Y' becomes infinite on five straight lines given by the factors in the denominator of (12). (Fig.3.)



Suppose $0.5c(1 + \sin \gamma) > 1$. The solution starting from $(0,0)$ has to cross the line $Y = 1.2(X - 1)$ between $X = 1$ and $X = 0.5c(1 + \sin \gamma)$ and proceed then to $(0.5c(1 + \sin \gamma), 0)$.

Fig.3

On the line $Y = 1.2(X - 1)$ there is a singular point between 1 and $0.5c(1 + \sin \gamma)$ where the numerator in (12) is zero. This can be shown by substituting in the numerator $Y = 1.2(X - 1)$. It then becomes

$$(X - 1) [(-1.93536X^2 - 0.48384X + 2.4192)(2X^2 - 1.5Xc \sin \gamma - 0.25c^2 \cos^2 \gamma) + X(3.87072X - 5.32224)(X^2 - Xc \sin \gamma - 0.25c^2 \cos^2 \gamma)].$$

The expression in the square brackets is equal to

$$-1.45152(1 - c \sin \gamma - 0.25c^2 \cos^2 \gamma)$$

for $X = 1$. The expression is positive, as according to the assumption

$$1 - 0.5c \sin \gamma < 0.5c$$

and the expression in question can be written

$$-1.45152[(1 - 0.5c \sin \gamma)^2 - (0.5c)^2].$$

For $X = 0.5c(1 + \sin \gamma)$ the expression becomes

$$0.25c^2(1 + \sin \gamma)(2.4192 - 0.48384X - 1.93536X^2)$$

and this is negative for $X > 1$.

Thus the numerator in (12) is zero somewhere between $X = 1$ and $X = 0.5c(1 + \sin \gamma)$. The point, let us call it P, on the line $Y = 1.2(X - 1)$ where the numerator is zero is a saddle point (Fig.4.) The derivative Y' is positive to the right of P above the line and to the left below the line, it is negative to the left of P above the line and to the right below the line. There are two integral curves which pass through the point P. Only one of them can possibly be the solution of the problem, that which passes through the point P from the left above the line to the right below the line. This curve has to pass through $(0,0)$ to be a solution. This is




Fig. 4

the origin. If such values do not exist then the conclusion is that

$$c = \frac{2}{1 + \sin \gamma}$$

It may be mentioned that in the case $0.5c(1 + \sin \gamma) > 1$ there are two more singular points on the line $Y = 1.2(X - 1)$. One is a spiral point at $X = 1$ and the other a saddle point between $X = 0$ and $X = 1$.

For $\gamma = \pi/2$, $c = 1$ an integral curve was computed numerically. A saddle point is in this case at $(0.5, -0.6)$ and the curve passing through this point passed through $(0,0)$ and $(1,0)$. The solution is shown in Fig. 5.

From the found solution the boundary layer profiles were computed and are shown in Fig. 6.

In Fig. 7 the values of the form parameter K are plotted against the angle φ and in Fig. 8 the shearing stress τ times $\frac{\sqrt{Re}}{8\sqrt{2} \varrho u_{\infty}^2}$ against φ .

As

$$\tau = \mu \frac{\partial u}{\partial \eta} \Big|_{\eta=0}$$

then from (9), (10) and (11a) with $Re = \frac{U_{\infty} 2a}{\nu}$ follows

$$\frac{\tau \sqrt{Re}}{16\sqrt{2} \cdot \frac{1}{2} \varrho u_{\infty}^2} = \left[2(X-1) + \frac{1}{6} KX \right] \left(\frac{dX}{d\varphi} / K \right)^{\frac{1}{2}}$$

This is a dimensionless quantity.

Numerical integration gives

$$\frac{\sqrt{Re}}{8\sqrt{2} \varrho u_{\infty}^2} \int_0^{2\pi} \tau d\varphi = -1.00$$

and thus the shearing stress on the surface of the cylinder is

$$\int_0^{2\pi} \tau a d\varphi = -a \ell \cdot 11.3 \rho U_{\infty}^2 Re^{-\frac{1}{2}}$$

and the power P necessary to rotate the cylinder so that $U_0 = 4U_{\infty}$ is

$$P = 45.2 a \ell \rho U_{\infty}^3 Re^{-\frac{1}{2}}.$$

11. The computation suggests that there exist integral curves for $0.5c(1+\sin \gamma) = 1$ only. This equation gives the connection between the spin of the cylinder and the circulation, but it will be valid for the upper side of the cylinder only giving the stagnation points and therewith the region of attached flow on the upper side of the cylinder in dependence on the velocity of rotation of the cylinder.

What happens on the lower side of the cylinder?

If $U_0 = 0$ then there is separation on the upper as well as on the lower side of the cylinder between 80° and 90° from the stagnation point. If U_0 has a positive value the point of separation on the upper side will be moved farther from the forward stagnation point and the separation point on the lower side will be nearer to the forward stagnation point than in the case $U_0 = 0$, because on the lower side the wall is moving in a direction opposite to the flow.

Thus there will be a wake on the lower side, the limits of which are a point between $\varphi = -\gamma$ and $\varphi = -\frac{\pi}{2}$ and the rear stagnation point $\varphi = \pi + \gamma$.

This has to be taken into account in solving (12) for negative values of X . The solution is limited by the line $Y = 1.2(X - 1)$. As long as $|Y| < 1.2|X - 1|$ a family of integral curves exist which pass through $(0,0)$ and $0.5c(\sin \gamma - 1)$. But for larger values of $|Y|$ there are curves starting from $(0,0)$ which cross the line $Y = 1.2(X - 1)$ and remain on the lower side of it (Fig.9). These do not reach the point $0.5c(\sin \gamma - 1)$ and correspond to a separated flow. To calculate such a flow the pressure distribution from the forward stagnation point to the point of separation must be known. Of course one can get an approximate solution taking on the lower side of the cylinder as well $U = 2U_{\infty}(\sin \varphi + \sin \gamma)$ as if the flow was attached.




Fig. 9

For the calculation of the Magnus force the pressure in the wake must be known.

NAVORD Report 4022

LIST OF REFERENCES

- [1.] J. M. Burgers, Verslag van de Gewone vergaderingen der
Wisen-Naturkundige Afdeeling 29(1921) p.952.
- [2.] S. Goldstein, Modern Developments of Fluid Dynamics, p.152.




FIG. 5 SOLUTION IN THE CASE OF ONE STAGNATION POINT




FIG. 6 VELOCITY PROFILES




FIG. 7 THE FORM PARAMETER K




FIG. 8 THE SHEARING STRESS

Aeroballistic Research Department
External Distribution List for Applied Math. (X3)

<u>No. of Copies</u>		<u>No. of Copies</u>	
	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C.		Air Targets Division Directorate of Intelligence Headquarters, USAF Washington 25, D. C.
1	Attn: Rea	1	Attn: Chief, Physical Vulnerability Br.
1	Attn: Rexe	1	Attn: AFDRD-RE
3	Attn: Re9a		
	Chief, Bureau of Aeronautics Department of the Navy Washington 25, D. C.		Commanding General Hdqts, Wright Air Development Center Wright-Patterson Air Force Base Dayton, Ohio
1	Attn: AER-TD-414	1	Attn: WCSO
1	Attn: RS-7	7	Attn: WCAPD
	Commander U.S. Naval Ordnance Test Station Inyokern P.O. China Lake, California	2	Attn: WCRR
2	Attn: Technical Library		Physics Branch Division of Research U. S. Atomic Energy Commission Washington 25, D. C.
1	Attn: Code 5003	1	
	Commander U.S. Naval Air Missile Test Center Point Mugu, California		Director Maxwell Air Force Base, Alabama Attn: Air University Library
2	Attn: Technical Library	1	
	Superintendent U.S. Naval Postgraduate School Monterey, California		The Artillery School Antiaircraft and Guided Missiles Br. Fort Bliss, Texas
1	Attn: Librarian	2	Attn: Research and Analysis Sec.
	Commanding Officer and Director David Taylor Model Basin Washington 7, D. C.	1	Attn: Pres. Army Field Forces, Board #4
1	Attn: Hydrodynamics Laboratory		Ballistic Research Laboratories Aberdeen Proving Ground Aberdeen, Maryland
	Chief of Naval Research Navy Research Section Library of Congress Washington 25, D. C.	2	Attn: D.S. Dederick
2			National Bureau of Standards Washington 25, D. C.
	Office of Naval Research Washington 25, D. C.	1	Attn: Nat'l Applied Math. Lab.
1	Attn: Code 432	1	Attn: W. Ramberg
1	Attn: Code 438	1	Attn: Librarian(Ord. Dev. Div.)
1	Attn: Code 463		National Bureau of Standards Corona Laboratories (Ord. Dev. Div.) Corona, California
	Director Naval Research Laboratory Washington 25, D. C.	1	Attn: Dr. Harold Thomas
1	Attn: Code 2021		National Bureau of Standards Building 3U, UCLA Campus 405 Hilgard Avenue Los Angeles 24, California
1	Attn: Code 3800	1	Attn: Librarian
	Research and Development Board Library Branch Pentagon, 3D1041 Washington 25, D. C.		University of California Berkeley 4, California
1		1	Attn: G. J. Maslach
	Chief, AFSWP P.O. Box 2610 Washington, D. C.	1	Attn: Dr. S.A. Schaaf
1	Attn: Technical Library		VIA: InsMat
			California Institute of Technology Pasadena 4, California
		2	Attn: Librarians(Guggenheim Aero Lab)
		1	Attn: Prof. M.S. Plesset
			VIA: BuAero Rep.

No. of
Copies

1 University of Illinois
202 E. R. L.
Urbana, Illinois
Attn: Prof. A.H. Taub
VIA: InsMat

1 Director
Fluid Dynamics and Applied Math.
University of Maryland
College Park, Maryland
VIA: InsMat

1 University of Michigan
Engineering Research Institute
Ypsilanti, Michigan
Attn: J.W. Carr, III

1 Willow Run Research Center
Willow Run Airport
University of Michigan
Ypsilanti, Michigan
Attn: L.R. Biasell
VIA: InsMat

1 University of Minnesota
Rosemount, Minnesota
Attn: J. Leonard Frame
VIA: Ass't InsMat

1 Dept. of Aero. Engr.
The Ohio State University
Columbus, Ohio
Attn: G.L. Von Eschen
VIA: Ass't InsMat

1 Polytechnic Institute of Brooklyn
99 Livingston Street
Brooklyn 2, New York
Attn: Dr. Antonio Ferri
VIA: ONR

1 University of Wisconsin
Naval Research Laboratory
422 Farm Place
Madison 6, Wisconsin
VIA: InsMat

1 Princeton University
Forrestal Research Center Library
Project Squid
Princeton, New Jersey
Attn: M. H. Smith

1 Armour Research Foundation
35 West 33rd Street
Chicago 16, Illinois
Attn: Engr. Mech. Div.

1 Applied Physics Laboratory
The Johns Hopkins University
8621 Georgia Avenue
Silver Spring, Maryland
Attn: Arthur G. Norris
VIA: NIO

No. of
Copies

1 Defense Research Laboratory
University of Texas
Box 1, University Station
Austin, Texas
Attn: InsMat

2 Eastman Kodak Company
50 West Main Street
Rochester 4, New York
Attn: Dr. H. Trotter, Jr.
VIA: NIO

1 General Electric Company
Bldg. #1, Campbell Avenue Plant
Schenectady, New York
Attn: Joseph C. Hoffman
VIA: InsMach.

1 The Rand Corporation
1500 Fourth Street
Santa Monica, California
Attn: Librarian
VIA: InsMat

1 Douglas Aircraft Company, Inc.
3000 Ocean Park Boulevard
Santa Monica, California
Attn: E.F. Burton
VIA: BuAero Rep.

2 North American Aviation, Inc.
12214 Lakewood Boulevard
Downey, California
Attn: Aerophysics Library
VIA: BuAero Rep.

5 National Advisory Committee for Aero
1724 F Street Northwest
Washington 25, D. C.
Attn: E.B. Jackson

2 Ames Aeronautical Laboratory
Moffett Field, California
Attn: Dr. A. C. Charter

1 Langley Aeronautical Laboratory
Langley Field, Virginia
Attn: Theoretical Aerodynamics Div.
1 Attn: Dr. A. Busemann
1 Attn: J. Stack

1 NACA Lewis Flight Propulsion Lab.
Cleveland Hopkins Airport
Cleveland, 11, Ohio
Attn: Dr. John C. Evvard

1 Harvard University
21 Vanserg Building
Cambridge 38, Massachusetts
Attn: Prof. G. Birkhoff

1 Johns Hopkins University
Charles and 34th Streets
Baltimore 18, Maryland
Attn: Dr. F. H. Clauser

No. of
Copies

1	New York University 45 Fourth Avenue New York 3, New York Attn: Dr. R. Courant
1	California Institute of Technology Pasadena 4, California Attn: Dr. Hans W. Liepmann
1	University of Toronto Institute of Aerophysics Toronto 5, Ontario Attn: Dr. G.N. Patterson VIA: BuOrd (Ad8)
1	Hughes Aircraft Company Missile Aerodynamics Department Culver City, California Attn: Dr. Allen E. Puckett
1	Institute for Advanced Study Professor John von Neumann Princeton, New Jersey
1	University of Michigan Willow Run Research Center Ypsilanti, Michigan
1	INTERNATIONAL BUSINESS MACHINES CORPORATION ENDICOTT, NEW YORK ATTN. MR. M. G. JOHNSON, LIBRARIAN
1	DIGITAL COMPUTER LABORATORY UNIVERSITY OF ILLINOIS CHAMPAIGNE, ILLINOIS ATTN. PROFESSOR J. P. NASH
1	U. S. NAVAL PROVING GROUND DAHLGREN, VIRGINIA ATTN. RALPH A. NIEMANN

Aeroballistic Research Department
External Distribution List for Applied Math. (X3a)

<u>No. of Copies</u>		
8	Office of Naval Research Branch Office, Navy 100 Fleet Post Office New York, New York	1 WESTINGHOUSE ELECTRIC CORPORATION PITTSBURGH 30, PENNA. ATTN. VIVIAN STERNBERG, LIBRARIAN
1	Commanding General Aberdeen Proving Ground Aberdeen, Maryland Attn: C.L. Poor	1 CORNELL UNIVERSITY ITHACA, NEW YORK ATTN. DR. N. ROTT
1	Attn: Dr. B.L. Hicks	
1	National Bureau of Standards Washington 25, D. C. Attn: G.B. Schubauer	1 UNIVERSITY OF MARYLAND INST. OF FLUID DYNAMICS AND APPLIED MATHEMATICS COLLEGE PARK, MD. ATTN. DR. S. PAI
1	Ames Aeronautical Laboratory Moffett Field, California Attn: W.G. Vincenti	
1	Brown University Providence 12, Rhode Island Attn: Prof. Wm. Prager VIA: Ass't InsMat	
1	University of California Observatory 21 Berkeley 4, California Attn: Leland E. Cunningham VIA: InsMat	
1	Cornell University Ithaca, New York Attn: W.R. Sears VIA: ONR	
1	Indiana University Bloomington, Indiana Attn: T.Y. Thomas VIA: Ass't InsMat	
1	Massachusetts Institute of Technology 77 Massachusetts Avenue Cambridge 39, Massachusetts Attn: Prof. Eric Reissner VIA: InsMat	
1	Stanford University Stanford, California Attn: R.J. Langle VIA: Ass't InsMat	
1	Case Institute of Technology Cleveland, Ohio Attn: Prof. G. Kuerti VIA: ONR	