

UNCLASSIFIED

AD NUMBER	
AD085783	
CLASSIFICATION CHANGES	
TO:	UNCLASSIFIED
FROM:	CONFIDENTIAL
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited.	
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; DEC 1954. Other requests shall be referred to Army Armament Research and Development Command, Picatinny Arsenal, NJ.	
AUTHORITY	
ARRADCOM ltr 19 Nov 1979 ; ARRADCOM ltr 19 Nov 1979	

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE,
DISTRIBUTION UNLIMITED.

E X C L U D E D

**FROM GENERAL CLASSIFICATION SCHEDULE
IN ACCORDANCE WITH
INFORMATION SECURITY PROGRAM REGULATION**

DATED - JULY 1972

**DOD 5000.1R & EXECUTIVE ORDER 11652
(EXECUTIVE ORDER 10501 AMENDED)**

BY

**Defense Documentation Center
Defense Supply Agency
Cameron Station
Alexandria, Virginia 22314**

DEC 1972

85 783

1

UNCLASSIFIED

AD 85 783

CLASSIFICATION CHANGED

TO: UNCLASSIFIED-

FROM: CONFIDENTIAL-

AUTHORITY:

ARRADCom 1+r

19 NOV 79



UNCLASSIFIED

CONFIDENTIAL
A 85783

Armed Services Technical Information Agency

Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO

This document is the property of the United States Government. It is furnished for the duration of the contract and shall be returned when no longer required, or upon recall by ASTIA to the following address: Armed Services Technical Information Agency, Document Service Center, Knott Building, Dayton 2, Ohio.

NOTICE WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

UNCLASSIFIED

CONFIDENTIAL

FRANKFORD ARSENAL

TEST REPORT

REPORT NO. T54-13-1

FC



EXAMINATION AND EVALUATION OF FOREIGN FIRE CONTROL INSTRUMENTS

GERMAN PERISCOPE TYPE PVE 8B-1

by P. R. Yoder, Jr.

Ord. Proj. TRL-1055D
DA Proj. 513-01-006

Fire Control Instrument Group

FRANKFORD ARSENAL
PHILADELPHIA, PA.

28 Dec 1954

CONFIDENTIAL

55AA

6030

FEB 23 1955

AD No. 85783
ASTIA FILED

REPORT NO. T54-13-1

NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE
NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING
OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794.
THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN
ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

CONFIDENTIAL

Ground Weapons Division
Research and Development Department
Fire Control Instrument Group
Frankford Arsenal
Philadelphia 37, Pa.

Test Report T54-13-1
28 December 1954
Ord. Proj. TR1-1055D
DA Proj. 513-01-066
F.C. Proj. 412-7
X.O. 8986-05

EXAMINATION AND EVALUATION OF FOREIGN FIRE CONTROL INSTRUMENTS

GERMAN PERISCOPE TYPE PVE 8B-1

Prepared by P. R. Yoder, Jr.
P. R. Yoder, Jr.
Physicist

Reviewed by F. B. Patrick
F. B. Patrick
Chief, Optical Design Br.

Approved by W. T. Abell
W. T. Abell
Chief, Ground Weapons Div.

W. S. Carlson
W. S. Carlson
Chief, RAD Department

PRYoder, Jr/ms/6213
15 December 1954

55 A A 6030

CONFIDENTIAL

CONFIDENTIAL

ABSTRACT

The purpose of this test was to examine and evaluate the German Periscope, Type PVE 8B-1.

The important optical and mechanical features of this periscope were listed. The approximately 43° field of view could be adjusted through 360° in azimuth, and from -30° to $+135^{\circ}$ in elevation. The magnification provided was about 1.8 power. The image quality was not so good as expected.

The reticle, which was projected into the field of view, could be moved horizontally and/or vertically by a complex mechanism involving handmade three-dimensional cams.

CONFIDENTIAL

BACKGROUND

A German Periscope, Type PVE 8B-1, which is believed to have been used during World War II for observation and gun sighting from an aircraft, was obtained through the courtesy of the National Bureau of Standards, Washington, D. C., for examination and evaluation. This report summarizes the important optical and mechanical features of the instrument.

DISCUSSION

The instrument (see Figures 1 and 2) is essentially a periscopic type of sight with a movable head prism to permit the line of sight to be rotated through 360° in azimuth, and depressed or elevated from -30° to $+135^{\circ}$ referenced to the horizontal, at any azimuth setting. Movement of the line of sight in azimuth and elevation is accomplished through linkages to an external control unit. Observations are made through a spherical glass dome of excellent optical quality containing the head prism mechanism.

The optical system (see Figures 3 and 4) provides a true field of view of approximately 43° at a magnification of approximately 1.8 power and with a clear eye distance of about 1.0 inches. The eyepiece design used is a "wide-angle" type, characteristic of instruments having a large apparent field of view.

The reticle of this instrument is illuminated by an incandescent lamp and is viewed through an auxiliary microscope system superimposed upon the target through a beam-combining ocular prism assembly. The reticle pattern is a pair of crossed lines with a circle at the center (see Item 1 of Figure 7). A neutral density optical filter is provided, which may be inserted into the field of view by moving a filter control lever.

The optical image quality of the instrument examined was not so good as expected for this type optical system. The image definition was good only within about 6° of the center of the field of view. It could not be determined positively whether this condition was inherent in the optical design or caused by some hidden defect (or mis-alignment) within the system.

Details of the mounting of the optical components and the complex mechanism used to move the reticle horizontally and vertically are illustrated in Figures 5, 6, and 7. The reticle mechanism permits ballistic data to be fed into the instrument by positioning the control knob (see Item 3 of Figure 1). The three-dimensional cams are of particular interest since they appear to have been handmade to close tolerances.

DISTRIBUTION:

20 - Commanding Officer Frankford Arsenal Philadelphia 37, Pa. Attn: Chief, FCIG (1)	1 - Office, Chief of Ordnance Washington 25, D. C. Attn: ORDTT
Deputy Chief, FCIG (1)	1 - Commanding Officer Detroit Arsenal Center Line, Michigan Attn: ORDMX-ECCF
Chief, FRE (1)	
Chief, FGE (1)	1 - Commanding General Aberdeen Proving Ground Maryland Attn: D & PS, Bldg. 313
Chief, FSE (1)	
Chief, FFE (1)	1 - Commanding General Air Materiel Command Wright Patterson AF Base Dayton, Ohio
FRE (8)	
FRA (1)	
FRL (1)	
FRG, W. T. Abell (1)	2 - Armed Services Technical Information Agency Document Service Center Knott Bldg. Dayton 2, Ohio Attn: DSC-SA
FRG, F. B. Patrick (1)	
ER, Library (1)	
EW, Dr. Smith (1)	
1 - Office, Chief of Ordnance Washington 25, D. C. Attn: ORDTR	
23- Office, Chief of Ordnance Washington 25, D. C. THRU: ORDTR to ORDGU-IN	

Confidential




Figure 1. Front View of Periscope

- | | |
|-----------------|--------------------------|
| 1. Dome | 4. Eyepiece |
| 2. Dessicators | 5. Rheostat |
| 3. Control Knob | 6. Electrical Connection |

Confidential

Confidential




Figure 2. Side View of Periscope

- | | |
|-------------------|-----------------------------|
| 1. Dome | 4. Eyepiece |
| 2. Dessicators | 5. Sockets for Azimuth and |
| 3. Filter Control | Elevation Control Linkages. |

Confidential

Confidential




Figure 3. Schematic View of Optical System

Confidential

Confidential




Figure 4. Exploded View of Optical System

- | | |
|------------------------|----------------------------------|
| 1. Head Prism | 6. Filter Assembly |
| 2. Objective Assembly | 7. Ocular Prism Assembly |
| 3. First Erector Lens | 8. Eyepiece |
| 4. Dove Prism Assembly | 9. Microscope Objective Assembly |
| 5. Second Erector Lens | 10. Prism |

Reticle not shown

Confidential

Confidential




Figure 5. Exploded View (Front)

- | | |
|----------------------------------|-----------------------|
| 1. Dome | 8. Prism |
| 2. Head Prism | 9. Housing |
| 3. Objective Assembly | 10. Dove Prism |
| 4. Gear Housing | 11. Filter Control |
| 5. Linkages | 12. Rheostat |
| 6. Reticle Mechanism | 13. Eyepiece Assembly |
| 7. Microscope Objective Assembly | |

Confidential

Confidential




Figure 6. Exploded View (Rear)

- | | |
|-----------------------|---------------------------|
| 1. Dome | 8. Three Dimensional Cams |
| 2. Head Prism | 9. Housing |
| 3. Objective Assembly | 10. Dove Prism |
| 4. Gear Housing | 11. Filter |
| 5. Linkages | 12. Erector Lens |
| 6. Reticle Mechanism | 13. Ocular Prism Assembly |
| 7. Reticle | 14. Eyepiece Assembly |

Confidential

Confidential




Figure 7. View of Reticle Mechanism

1. Reticle

2. Three Dimensional Cams

3. Cam Followers

Confidential