

UNCLASSIFIED

AD NUMBER
AD115333
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to DoD only; Specific authority; 31 Jul 1968. Other requests shall be referred to Naval Ordnance Systems Command, Washington, DC.
AUTHORITY
USNOL ltr, 29 Aug 1974

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD NUMBER	
AD115333	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO: Distribution authorized to DoD only; Specific authority; 31 Jul 1968. Other requests shall be referred to Naval Ordnance Systems Command, Washington, DC.	
FROM: Controlling DoD Organization. Naval Ordnance Systems Command, Washington, DC.	
AUTHORITY	
31 Jul 1968, DoDD 5200.10; Pre-dates formal DoD distribution statements. Treated as DoD only	

THIS PAGE IS UNCLASSIFIED

~~CONFIDENTIAL~~

AD 115333

Armed Services Technical Information Agency

Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO

This document is the property of the United States Government. It is furnished for the duration of the contract and shall be returned when no longer required, or upon recall by ASTIA to the following address: Armed Services Technical Information Agency, Document Service Center, Knott Building, Dayton 2, Ohio.

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

~~CONFIDENTIAL~~

UNCLASSIFIED

AD _____

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

**DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS
DOD DIR 5200-10**



UNCLASSIFIED

Best Available Copy

**NOTICE: THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE
NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING
OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 and 794.
THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN
ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.**

CONFIDENTIAL

NAVORD REPORT

4345

115333

FC

A HYPERVELOCITY GUN USING A SHOCK-COMPRESSED
STEAM-HEATED PROPELLANT

30 JULY 1956



U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

CONFIDENTIAL

CONFIDENTIAL
NAVORD Report 4345

Aeroballistic Research Report 351

A HYPERVELOCITY GUN USING A SHOCK-COMPRESSED
STEAM-HEATED PROPELLANT

Prepared by:

A. E. Seigel and Z. I. Slawsky

ABSTRACT: This report describes a new type of hypervelocity gas gun for launching models of hypersonic missiles. The basic principle of this launcher (called the NOL Shock Gun) is the advantageous use of a chemical reaction (oxygen plus hydrogen added to helium) to produce a low molecular weight high temperature propellant gas and a shock to further compress and heat the hot steam-helium mixture. As described in the report the NOL Hypervelocity Gun is modified by the elongation of the gun chamber and the addition of the shock producing chamber in back of it. The paper contains theoretical analysis of the expected performance of this gun and discusses the use of the same principle for shock tubes where extreme high velocity is desired.

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

1
CONFIDENTIAL

561 61312

20050204040

CONFIDENTIAL

NAVORD Report 4345

30 July 1956

This report contains a description of a new type of hypervelocity missile launcher, a theoretical analysis of its performance and an outline of the method of converting the NOI Hypervelocity Gun to the new type. This conception of a new hypervelocity gun resulted from the need of devising means of launching models of Fleet Ballistic Missiles at speeds which are equal to those of the actual missile.

Although this gun was actually conceived and developed during the past year, it is in a sense the end product of over six years of research in the field of interior ballistics. The authors wish therefore to acknowledge their appreciation for the support received during this period to the Armaments Branch of the Office of Naval Research and Re5-a of the Bureau of Ordnance for supporting the initial stages of hypervelocity gun research, to Re3-1 of the Bureau of Ordnance for assistance in the construction of the steam-helium hypervelocity gun, and finally to the Special Projects Office of the Bureau of Ordnance for the high priority backing which made it possible to design and fire this gun in six months.

The authors also wish to acknowledge their debt to Dr. Hermann Kurzweg, Associate Technical Director for Aeroballistic Research for his enthusiastic support of a scheme in the stages where its final results were still in question.

WILLIAM W. WILBOURNE
Captain, USN
Commander

H. H. KURZWEG, Associate Technical
Director for Aeroballistic Research
By direction

11
CONFIDENTIAL

04-040602032

CONFIDENTIAL
NAVORD Report 4345

CONTENTS

	Page
Introduction	1
The Basic Principle of High Speed Guns	1
The Shock Gun Principle.	2
Summary and Conclusion	5
References	7
Appendix I	8
Appendix II.	12

ILLUSTRATIONS

Figure 1	40-mm Gun Performance.	15
Figure 2	Schematic of Shock Gun Parts and Assembly.	16
Figure 3	Shock Gun Method of Operation.	17
Figure 4	Pressure of Gas After Passage of Reflected Shock.	18
Figure 5	Sound Velocity of Gas After Passage of Reflected Shock.	19
Figure 6	Density Ratio of Gas After Passage of Reflected Shock.	20
Figure 7	Necessary Ratio of Gun Chamber Length to Shock Chamber Length.	21
Figure 8	40-mm Shock Gun Performance.	22
Figure 9	The % Dissociation of Water in the Reacted Mixture.	23

CONFIDENTIAL
NAVORD Report 4345

LIST OF SYMBOLS

a	Sound velocity of gas
$\bar{C}_v$	Average specific heat per unit weight if no dissociation
D	Dissociation energy of water, per mole of water, divided by the molecular weight of mixture
D_1	Gun chamber diameter
D_0	Shock chamber diameter
e	Internal energy of gas per unit weight
M	Mach number of gas
n	Exponent in isentropic relation for maximum dissociated gas
N	Number of moles of constituents in dissociated gas
N_0	Number of moles of constituents in undissociated gas
P	Pressure of gas
R	Gas constant of gas per unit weight
s	Entropy of gas per unit weight
S_1	Denotes shock which is initially propagated into gun chamber
S_2	Denotes shock which is reflected at the end of the gun chamber and travels back toward the shock chamber
T	Temperature of gas
u	Velocity of gas
v	Specific volume of gas
X_{gc}/X_{sc}	Ratio of gun chamber length to shock chamber length
γ	Specific heat ratio of gas (here equal to 1.5)
ϵ	Equal to $N - N_0$

CONFIDENTIAL
NAVORD Report 4345

ρ Density of gas
 σ Riemann function, defined in Appendix I

SUBSCRIPTS

o Denotes initial state of gas in shock chamber after chemical reaction
1 Denotes initial state of gas in gun chamber after chemical reaction
2 Denotes state of gas between contact surface and shock S_1
3 Denotes state of stationary gas behind shock S_3
s Denotes state of gas in the shock chamber just before the change in area section
g Denotes the state of gas in the gun chamber just after the change in area section
A Denotes state of gas in shock chamber before chemical reaction
B Denotes state of gas in gun chamber before chemical reaction

BARRED QUANTITIES

A bar over a quantity in Appendix I denotes that it is dimensionless

^v
CONFIDENTIAL

A HYPERVELOCITY GUN USING A SHOCK-COMPRESSED
STEAM-HEATED PROPELLANT

INTRODUCTION

1. The quest for high-speed model launchers dates back at least a dozen years. The first successful high velocity launcher for small caliber projectiles was developed by the New Mexico School of Mines, and since then this type of gun has been improved by Dr. Charters of the Ames Aeronautical Laboratory of NACA and a similar one built by the Universal Winding Company for the Ballistics Research Laboratory, Aberdeen Proving Ground.
2. More recently the Naval Ordnance Laboratory has developed the "NOL Hypervelocity Gun", the 40-mm size of which is capable of launching models at speeds almost as high as those reached by the small caliber guns. This gun is described in references (a) and (e). Figure 1 illustrates the performance of this gun. There exists also an NOL Hypervelocity Gun in the caliber 0.50 size.

THE BASIC PRINCIPLE OF HIGH SPEED GUNS

3. The basic principle of all high-speed gas guns is the use of a low acoustic impedance gas, the idea being to get the required pressure in the chamber with the smallest weight of propellant gas per unit volume. There are two main methods for obtaining a low molecular weight, high temperature gas, i.e., one with a low acoustic impedance. One of these has already been amply discussed in the literature. It depends upon the use of a single stroke piston to compress and adiabatically heat the light gas. The other is the method used here at NOL in its Hypervelocity Gun. Chemical energy is used to heat helium without adding too much of the heavy components which supply the chemical energy. More specifically, oxygen and hydrogen are added to the helium in the ratio of 1:3:8 by molar volume. The hydrogen-oxygen reaction furnishes the necessary energy,* (see references (a) and (e)).

*It is to be noted that the helium can be supplanted in part or in total by hydrogen, yielding slightly higher projectile velocities and lower mixture temperatures. However, in this case the danger of hydrogen embrittlement and explosion must be recognized.

CONFIDENTIAL
NAVORD Report 4345

4. The NOL Hypervelocity Gun has a muzzle velocity capability which is less than an equivalent gun system using the compression principle. This is due to the fact that the amount of chemical energy that can be used is limited, whereas the temperature that can be obtained by the alternate method depends only on the compression ratio. The advantage of the NOL Hypervelocity Gun lies in the simplicity of its construction with the practicability of making large guns using the same principle. The compression ratio required by the other type of gun makes the chamber impractically large for guns above the 20-mm size.

5. The following scheme, the "shock gun" scheme, has been conceived by the authors in order to achieve even lower acoustic impedance and hence higher muzzle velocity without resorting to moving pistons or very large compression ratios.

THE SHOCK GUN PRINCIPLE

6. The basic principle in the shock-compressed steam-helium ("shock gun") method is the advantageous use of the chemical reaction as already used in the NOL Hypervelocity Gun together with the advantages of heating by compression. The first carries with it the penalty of increase in molecular weight due to the combustion products. The second does not require any such contamination but it does require large initial volumes. In the "shock gun" a hot gas is raised in pressure and temperature still further by means of a compression. The compression is effected by the use of a shock rather than a mechanical piston. The obvious advantage of this procedure is that one does not have any moving parts in the chamber of the gun. Consideration was given to the possibility of compressing the steam-helium mixture with a piston, but it was rejected in favor of the method to be described below.

7. The fabrication of the "shock gun" from an existing gun and an adapter is schematically illustrated in Figure 2. The uppermost sketch is a schematic of the existing caliber 0.50 gun (one of the NOL Hypervelocity Guns) with its 30-mm chamber. Immediately below it is a sketch of an adapter containing a 30-mm diameter chamber and a 70-mm diameter chamber. The latter chamber will be referred to as the shock-producing chamber or shock chamber for short and the first as part of the gun chamber. Below this in the same figure is a sketch of the assembled "shock gun". As can be seen in the assembly sketch the gun chamber is sealed from the gun barrel by a diaphragm identical to the ones used in the caliber 0.50 NOL Hypervelocity Gun. (This type of diaphragm developed at NOL,

reference (a), upon rupture simply folds, and no pieces of the diaphragm are sent downstream.) The shock chamber is sealed from the gun chamber by another diaphragm identical to those used in the 40-mm NOL Hypervelocity Gun. In fact the breech plug, although somewhat shorter is essentially the same as that used in the 40-mm NOL Hypervelocity Gun.

8. The conceived method of operation is illustrated in Figure 3. Diagram A shows the "shock gun", the gun chamber of which is loaded with oxygen-hydrogen-helium mixture (the same mixture as used in the NOL Hypervelocity Gun) to a pressure P_2 of about 850 psi. The shock chamber is loaded with the same mixture to a pressure P_A of 8000 psi. The mixture in the gun chamber is now ignited. The reaction will raise the pressure to approximately 7500 psi and a temperature of approximately 2700°K. Since the diaphragms are designed to take much higher pressure, this will result in what is known in gun terminology as a "hangfire" in the gun chamber. Diagram B indicates the new state. After a short time delay of approximately 1 to 2 milliseconds, the mixture in the shock chamber is ignited raising the pressure in it to an estimated 45,000 psi and a temperature approximately the same as in the gun chamber (see Diagram C). The pressure in the shock chamber is now sufficient to rupture the chamber diaphragm and to fold it so that it is out of the way of the flow (see Diagram D). A shock S_1 as is shown in D is propagated into the gun chamber by the gas expanding from the shock chamber. The shock will be reflected at the end of the gun chamber as is indicated in E, further raising the pressure and temperature to values P_3 and T_3 . The strength of the reflected shock will, of course, depend on the rupture process of the gun diaphragm which divides the gun chamber from the missile. For the calculations presented below, reflection has been assumed to be complete. The effect of incomplete reflection will be discussed later.

9. Figure 4 is a graphical presentation of the pressure ratio P_3/P_0 as a function of the initial pressure ratio P_0/P_1 across the diaphragm separating the shock chamber from the gun chamber. As is shown in the figure, curves have been calculated for a series of shock chamber to gun chamber diameter ratios. Appendix I describes the method used for these calculations. The curve appropriate to the gun under discussion is one slightly above that labeled $D_0/D_1 = 2$. Since the initial pressure ratio is approximately 6 for the conditions described above, a 20% gain in pressure over that in the shock chamber is expected. This would make the pressure that the missile first feels approximately 55,000 psi. Figure 5 is a graphical presentation of the resulting sound speed ratio, a_3/a_0 as a

CONFIDENTIAL
NAVORD Report 4345

function of the initial pressure ratios. Again, separate curves are calculated for the various ratios of shock chamber to gun chamber diameters. The curve corresponding to the gun under discussion is again one slightly above that labeled 2. Notice that for a pressure ratio of six the expected sound speed will be somewhat more than 1.4 times the sound speed already in the steam-helium mixture. Since the sound speed in the steam-helium mixture is approximately 7000 ft/sec it is expected that after shock reflection the sound speed will be approximately 10,000 ft/sec.

10. Figure 6 is a graphical presentation of the density ρ_1 before any shock has been propagated through the gun chamber divided by the density ρ_2 after shock reflection as a function of the initial pressure ratio. Again for an initial pressure ratio of six the increase in density will be approximately $3\frac{1}{2}$ times the initial density. This means that the effective gun chamber length will be 0.275 times its initial length. This loss in effective chamber volume is the price paid for the increase in the sound speed by the method of shock heating and compression. The length of gun chamber required is determined by the methods outlined in reference (c).

11. The necessary length of gun chamber relative to the length of shock chamber is determined by the condition that the reflected shock S_2 reach the contact surface at the same time as the first reflected rarefaction disturbance (dashed line A-B in Appendix I). This length ratio is plotted as a function of P_0/P_1 in Figure 7.

12. Figure 8 contains four calculated performance curves giving the muzzle velocity as a function of the in-gun-weight of projectile. These curves are calculated on the basis of a 40-mm, 4-meter long gun barrel with initial pressure experienced by the projectile of 40,000 psi. (See references (b) and (c) for method of calculation.) The curves correspond to different sound speeds. Conversion to a caliber 0.50 gun, 50 inches long is straightforward. The corresponding missile weight must be in the ratio of the diameters raised to the third power. Thus 40 grams in this gun corresponds to 1.25 grams in the caliber 0.50. Increase in initial pressure can also be taken into account by the condition that the muzzle velocity will be the same as long as $\frac{PAL}{M}$ is kept the same. P

is the initial pressure behind the projectile, A the area, L the length of travel, and M the mass of the projectile. Thus 55,000 psi corresponds to a mass of $40 \times 40/55$ or approximately 30 grams. According to these calculations therefore it is expected that a nylon sphere (1.25 grams--equivalent to 40

CONFIDENTIAL
NAVORD Report 4345

grams in the 40-mm gun) will be launched at somewhere between 15,000 and 16,000 ft/sec. The formulae used in calculating Figures 4 through 7 are presented in Appendix I. In these calculations the final state of the steam-helium mixture has been assumed to follow ideal gas laws without dissociation of the water molecule. The effect of dissociation is discussed in Appendix II. It is shown there that the muzzle velocity is not appreciably affected by the occurrence of dissociation. For this reason it was thought not worthwhile to carry through more exact calculation of the projectile motion with the dissociation taken into account.

SUMMARY AND CONCLUSION

13. It is our opinion that there are several factors which make this gun scheme attractive.

(a) Because the reaction in the gun chamber is contained, it will go to completion, and the resulting pressure and temperature will be higher than that attained in the NOL Hypervelocity Gun.

(b) Since the diaphragm separating the shock chamber from the gun chamber will have 7500 psi on the downstream side (gun chamber side), rupture should not take place until the pressure in the shock chamber exceeds 20,000 psi (diaphragm used here ruptures at 12,500 psi). Since the higher the pressure prior to rupture the more complete is the combustion, better performance should be obtained from the shock chamber too.

(c) Since the shock is used to further heat and compress an already hot mixture of steam and helium, the volume ratio required (initial volume to final volume) to reach a temperature of 5000°K is less than four. Because of this the shock chamber and gun chamber will not be impractically large: for example, a 200 caliber 40-mm gun would require a gun chamber 4 meters long and a shock chamber about 1 meter long, an overall length of 13 meters or approximately 40 feet. This is not much longer than the caliber 0.50 New Mexico School of Mines type of gun.

(d) In the calculations, complete reflection of the shock was assumed. If the diaphragm separating the gun barrel from the gun chamber, ruptures as the shock hits it, the reflection will not be complete. An estimate of the effect of incomplete reflection on the muzzle velocity can be made as follows: the limiting case will be one with no reflection at all. It is then not too difficult to calculate the approximate projectile motion when accelerated by a gas at pressure P_2 and with a velocity U_2 (contact surface velocity). It turns out that

CONFIDENTIAL
NAVORD Report 4345

the loss in pressure and temperature due to the fact that the flow is not brought to rest is nearly compensated for by the fact that the propelling gas is already in motion.

14. The application of this principle, that is the multi-stage compression chamber using a steam-helium mixture to shock tube drivers, is obvious. Although the idea of the use of a series of compression chambers in a shock tube each having higher pressure than the previous one is not new, the use of a hot steam-helium mixture initially in each of the compression chambers is. The difference in the expected performance between this scheme and the previous ones is large. Quantitative evaluation will appear in a future publication.

15. Finally it is to be noticed that although the shock gun scheme uses two stages it is possible to introduce a third and a fourth stage thus raising the temperature. However, in the opinion of the authors there are several practical arguments which make the introduction of other stages not particularly attractive. Larger chambers will be necessary, and the higher temperature will aggravate the erosion problem and the heat loss due to radiation.

CONFIDENTIAL
NAVORD Report 4345


REFERENCES

- (a) Dawson, V., Shepard, B. M., and Thurston, P. A., "Recent Results on the Capabilities of 40-mm Hypervelocity Launchers", Paper presented at the First Symposium on Ballistic Missiles at Ramo-Wooldridge Corp., Los Angeles, Calif., Jun 1950
- (b) Seigel, A. E., "The Effect of the Optimum Chambrage on the Muzzle Velocity of Guns with a Qualitative Description of the Fundamental Phenomena Occurring During Gun Firing", NAVORD Report 2691, Oct 1952
- (c) Seigel, A. E., "The Influence of Chamber Diameter on the Muzzle Velocity of a Gun with an Effectively Infinite Length Chamber", NAVORD Report 3635, Jan 1954
- (d) Lukasiewicz, J., "Shock Tube Theory and Applications", National Aeronautical Establishment, Canada, Report No. 15
- (e) Slawsky, Z. I., "Some Fundamental Theoretical and Experimental Studies in the Development of Hypervelocity Guns", Paper presented at Picatinny Arsenal, May 1956

APPENDIX I


EQUATIONS USED TO CALCULATE PRESSURE RATIO (P_3/P_0) AND
SOUND VELOCITY RATIO (a_3/a_0) AFTER PASSAGE OF REFLECTED SHOCK

1. The history of the gases in the shock chamber and the gun chamber after each has been ignited may be obtained from conventional chambered shock tube theory (for example, see report by J. Lukasiewicz, reference (d)). The states of the gases after ignition are depicted in the sketch below,



where P_0 is the pressure of the gas in the shock chamber and P_1 is the relatively lower pressure of the gas in the gun chamber. Both gases have equal sound velocities, since the same proportion of the constituents of the gaseous mixture before ignition are in each of the chambers.* Thus, $a_0 = a_1$.

2. The difference in pressure, $P_0 - P_1$, is sufficient to rupture the diaphragm separating the gun chamber from the




* The mixture before and hence after ignition are at different pressures, but the effect of pressure on the adiabatic flame temperature and sound velocity is assumed negligible.

shock chamber; the gas from the shock chamber rushes into the gun chamber pushing the gas in the gun chamber at a velocity U_2 ; this pushing causes a shock to be sent ahead into the gas in the gun chamber at a greater velocity S_1 . This shock increases the pressure and sound velocity of the gas it passes through to values denoted by P_2 and a_2 respectively.

3. When the shock reaches the end of the gun chamber it is reflected and travels back toward the shock chamber with velocity S_2 raising the pressure and sound velocity of the gas it travels through to P_3 and a_3 .

4. The travel-time diagram is sketched below:



5. The equations describing the changes which take place are summarized below in a dimensionless form. The quantities are made dimensionless by the following transformations:

$$\bar{u} = \frac{U}{\frac{2}{\gamma-1} a_0}$$

$$\bar{\sigma} = \frac{\sigma}{\frac{2}{\gamma-1} a_0}$$

$$\bar{a} = \frac{a}{\frac{2}{\gamma-1} a_0}$$

$$\bar{p} = p/p_0$$

where σ is the Riemann function equal to a perfect gas

$$\bar{\sigma} = \frac{2\bar{a}}{\gamma-1}$$

$$\bar{p} = \bar{\sigma}^{2\gamma/(\gamma-1)}$$

$$\int_0^p \left(\frac{dp}{\rho a} \right)_s$$

For

(1)

CONFIDENTIAL
NAVORD Report 4345

The suffix "s" is used to denote the state of the gas in the shock chamber just before the change of area section; the suffix "g" is used to denote the state of the gas in the gun chamber immediately after the change of area section.

Shock Chamber Equations

$$\bar{u}_s + \bar{\sigma}_s = 1 \quad (\text{rarefaction equation}) \quad (2)$$

Change of Area Section Equations

$$\frac{2}{\gamma-1} \bar{u}_s^2 + \bar{\sigma}_s^2 = \frac{2}{\gamma-1} \bar{u}_g^2 + \bar{\sigma}_g^2 \quad (\text{energy equation}) \quad (3)$$

$$\frac{\pi}{4} D_0^2 (\bar{\sigma}_s)^{\frac{2}{\gamma-1}} \bar{u}_s = \frac{\pi}{4} D_1^2 (\bar{\sigma}_g)^{\frac{2}{\gamma-1}} \bar{u}_g \quad (\text{continuity equation}) \quad (4)$$

6. The maximum velocity attainable in the throat state "r" is sonic; at this time

$$\bar{u}_g = \bar{u}_g^* = \bar{a}_g^* = \bar{\sigma}_g^* \left(\frac{\gamma-1}{2} \right) \quad (5)$$

where the asterisk indicates the sonic conditions. When the sonic condition occurs equation (5) is used with equations (3) and (4).

Equation Relating Gas in State "g" With the Gas Behind Shock

$$\bar{u}_g + \bar{\sigma}_g = \bar{u}_2 + \bar{\sigma}_2 \quad (\text{rarefaction equation}) \quad (6)$$

Equations for States Across Shocks

$$\bar{u}_2 = \frac{u_2}{\frac{2}{\gamma-1} a_0} = \frac{u_2}{\frac{2}{\gamma-1} a_1} = \frac{P_2/P_1 - 1}{\sqrt{\frac{2\gamma}{\gamma-1} \left[\frac{\gamma+1}{\gamma-1} \cdot \frac{P_2}{P_1} + 1 \right]}} \quad (7)$$

$$\frac{a_2}{a_0} = \frac{a_2}{a_1} = \sqrt{\frac{\frac{\gamma+1}{\gamma-1} + P_2/P_1}{\frac{\gamma+1}{\gamma-1} + P_1/P_2}} \quad (8)$$

$$P_3/P_2 = \frac{(\frac{\gamma+1}{\gamma-1} + 2)(P_2/P_1) - 1}{P_2/P_1 + \frac{\gamma+1}{\gamma-1}} \quad (9)$$

$$\frac{a_2}{a_0} = \left[\frac{P_3/P_2 (\frac{\gamma+1}{\gamma-1} + P_3/P_2)}{(\frac{\gamma+1}{\gamma-1}) P_3/P_2 + 1} \right]^{1/2} \quad (10)$$

7. From equations (1) through (10), the desired quantities P_3/P_0 , and a_3/a_0 can be obtained as a function of P_0/P_1 . In the present instance the computations were done with an automatic computing machine, an IBM 650 computer, by the Applied Mathematics Division, Aeroballistic Research Department of NOL. The ratio ρ_1/ρ_3 was calculated from the relation:

$$\frac{\rho_1}{\rho_3} = \frac{T_3 P_1}{T_1 P_1} = \frac{T_3 P_1}{T_0 P_1} = \left(\frac{a_2}{a_0} \right)^2 \frac{P_1}{P_3}$$

APPENDIX II

EFFECT OF DISSOCIATION OF WATER IN THE MIXTURE
ON THE PROJECTILE VELOCITY

1. In the calculation of projectile velocity the gas mixture was assumed to consist of undissociated products of the reaction (i.e., $2H_2O + H_2 + 8H_2$ with a $\gamma = 1.5$). Actually, of course the water will dissociate as the temperature rises. This is shown in Figure 9 where the percent of dissociation of the water for the mixture is plotted as a function of pressure for constant temperatures. (These curves were calculated on the assumption that the water dissociates into H_2 , O_2 and OH .)

2. To determine the effects of the dissociation on the shock gun performance a limiting case of maximum dissociation was examined in which most of the energy imparted to the gas above $4000^\circ K$ goes toward dissociating the water, while a negligible amount goes toward raising its temperature.* Thus, from the expression for internal energy per unit weight of the gas with dissociation

$$e = \left(1 + \frac{\epsilon}{N_0}\right) \bar{c}_v T + \frac{2\epsilon}{N_0} D \quad ** \quad (1)$$

the change in internal energy becomes

$$de = (\bar{c}_v T + 2D) \frac{d\epsilon}{N_0} \quad (2)$$

where the dT term has been neglected by our assumption of a limiting case of maximum dissociation.

3. From the equation of state of the dissociating gas

$$pv = \frac{N}{N_0} RT = \left(1 + \frac{\epsilon}{N_0}\right) RT \quad (3)$$

* A more exact calculation is possible but was not attempted because it was thought not worthwhile.

** See list of symbols

and from the Gibbs relation

$$Tds = de + pdv \quad (4)$$

the isentropic relation is obtained as

$$pv^n = \text{constant} \quad (5)$$

with

$$n = 1 + \frac{RT}{2D + C_v T}$$

and in which T has been taken as effectively constant in the derivation in accord with our limiting case assumption. The exponent " n " in equation (5), which can be interpreted as an effective ratio of specific heat, has a value for the mixture at 4000°K of approximately 1.07.

4. From (5) the sound velocity is obtained as

$$a = \sqrt{npv} \quad (6)$$

Further, from the above equations the relations between variables across a normal shock may be easily obtained. It is found that the ratios of p, ρ, a, u , and M across a normal shock are the same function of initial Mach number in this limiting case as for the classic case of an ideal gas.

5. If the conditions of the gas are calculated after the reflected shock passes through it, the pressure is found to rise from 22,500 psi to 44,500 psi and the sound velocity from 8540 ft/sec to 8730 ft/sec. These values are compared to those obtained with the undissociated $\gamma = 1.5$ gas in the table below.

Comparison of State of Gas After Passage of Reflected Shock in Limiting Cases

	Undissociated Gas $\gamma = 1.5$	Maximum Dissociated Gas $\gamma = 1.07$
P_3 , psi	55,500	44,500
a_3 , ft/sec	10,025	8,730
T_3 , °K	5,525	4,000
% Dissociation	0	55%

6. With the conditions in state "3" taken as initial conditions the projectile velocity can be calculated for the

CONFIDENTIAL
NAVORD Report 4345

maximum dissociated gas case. For this calculation the gas is taken to expand from state "3" with an effective " γ " of 1.07 until reassociation is complete (i.e., $\epsilon = 0$), after which the gas expands with a γ of 1.50. For the example cited in the text (40 gram projectile in a 40-mm gun), the calculated projectile velocities are compared below.


Comparison of Projectile Velocities in Limiting Cases

	Undissociated Gas $\gamma = 1.5$	Maximum Dissociated Gas in State "3", Reassociation During Expansion
Projectile Velocity ft/sec	15,800	15,000

Thus in the extreme case of maximum dissociation the projectile velocity is slightly decreased.

7. Actually from Figure 9 and a knowledge of the specific heats it may be readily shown that the assumption of no dissociation is more nearly correct. Thus, it was calculated that instead of 5500°K, the value of T_3 , obtained for the undissociated case, the temperature would drop to about 5000°K.

8. Therefore, because (a) dissociation has little effect on the performance of the shock gun, (b) the gas is more nearly undissociated, and (c) the calculation is considerably simplified, the piston motion was computed with the assumption that no dissociation occurs.



THE NOL HYPERVELOCITY GUN
FIG.1 40 MM GUN PERFORMANCE




FIG. 2




FIG. 3




FIG. 4 PRESSURE OF GAS AFTER PASSAGE OF REFLECTED SHOCK




FIG.5 SOUND VELOCITY OF GAS AFTER PASSAGE OF REFLECTED SHOCK

CONFIDENTIAL
NAVORD REPORT 4345




FIG. 6 DENSITY RATIO OF GAS AFTER PASSAGE OF REFLECTED SHOCK





FIG. 7 NECESSARY RATIO OF GUN CHAMBER LENGTH TO SHOCK CHAMBER LENGTH



M, PROJECTILE MASS (GRAMS)
FIG. 8 40 MM SHOCK GUN PERFORMANCE




FIG. 9 % DISSOCIATION OF WATER IN THE REACTED MIXTURE

Aeroballistic Research Department
External Distribution List for Development (X1)

<u>No. of Copies</u>		<u>No. of Copies</u>	
	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C.		Commander, WADC Wright-Patterson AF Base Ohio
1	Attn: Ad3	5	Attn: WCOSI-3
1	Attn: Ado	3	Attn: WCRRD
1	Attn: Ree	1	Attn: WCLGH-3
1	Attn: ReU1-b		
1	Attn: ReW4-d	1	Director
1	Attn: ReS1-e		Air University Library
1	Attn: ReO-3		Maxwell AF Base, Alabama
	Chief, PuAer Washington 25, D. C.		Director
3	Attn: TD-414		Aberdeen Proving Ground, Md.
	Commander, U. S. NOTS Inyokern, China Lake, Calif.	1	Attn: Technical Info. Br.
1	Attn: Technical Library	1	Attn: Ballistics Res. Lab.
1	Attn: Code 503	1	Attn: Mr. D. C. Vest
	Commander, NAMTC Point Mugu, California		Commanding General Redstone Arsenal Huntsville, Alabama
2	Attn: Technical Library	1	Attn: Aero. Lab, GMDD
	Superintendent U. S. Naval Postgraduate School Monterey, California	5	ASTIA
1	Attn: Tech. Rpts Section		Document Service Center Knott Building Dayton 2, Ohio
	Director, NRL Washington 25, D. C.		NACA
1	Attn: Code 2021		High Speed Flight Station Box 273 Edwards Air Force Base, Calif.
	Officer in Charge, NPG Dahlgren, Virginia	1	Attn: Mr. W. C. Williams
1	Attn: Technical Library		NACA
	Office, Chief of Ordnance Department of the Army Washington 25, D. C.		Ames Aeronautical Laboratory Moffett Field, California
1	Attn: ORDTU	1	Attn: Librarian
	Office of the Assistant Secretary of Defense (R and D) Room 3 E 1065, The Pentagon Washington 25, D. C.	1	Attn: Mr. H. Allen
1	Attn: Technical Library	1	Attn: Mr. A. J. Eggers, Jr.
	Chief, AFSWP Washington 25, D. C.	1	Attn: Dr. A. Charters
1	Attn: Document Library Br.		NACA
			Langley Aeronautical Lab. Langley Field, Virginia
		1	Attn: Librarian
		1	Attn: Mr. C. H. McLellan
		1	Attn: Comp. Res. Div.
		1	Attn: Adolf Busemann
		1	Attn: John J. Stack

No. of
Copies

No. of
Copies

1	NACA Lewis Flight Propulsion Lab. 21000 Brookpark Road Cleveland 11, Ohio Attn: Librarian	1	The Ohio State University Research Foundation Nineteenth Avenue Columbus 10, Ohio Attn: Security Officer Via: ONR
1	NACA 1512 H Street, N. W. Washington 25, D. C. Commanding Officer, DOPPL Washington 25, D. C. Attn: Lib., Rm 211, Bldg 92	1	CIT Pasadena 4, California Attn: Aeronautics Dept.
1	Office of Naval Research Room 2709, T-3 Building Washington 25, D. C. Attn: Head, Mechanics Br.	2	Attn: Jet Propulsion Lab. Via: ONR
1	Attn: Mr. C. Burns	1	University of Minnesota Minneapolis 14, Minnesota Attn: Mechanical Eng. Dept. Via: ONR
1	Attn: Dr. I. Esterman	1	BAR Aerojet-General Corporation 6352 N. Irwindale Ave. Azusa, California
1	Director of Intelligence Headquarters, USAF Washington 25, D. C. Attn: APOIN-3B	1	RAND Corp. 1700 Main St. Santa Monica, California Attn: Lib., USAF Project RAND Via: InsMat
1	Director, DTMB Aerodynamics Laboratory Washington 7, D. C. Attn: Library	1	Douglas Aircraft Co., Inc. Santa Monica Division 3000 Ocean Park Blvd. Santa Monica, California Attn: Chief Engineer Via: InsMat
1	The University of Texas P. O. Box 8029 Austin 12, Texas Attn: Defense Res. Lab. Via: ONR	1	CONVAIR Corp. A Div. of Gen. Dynamics Corp. Daingerfield, Texas Via: InsMat
1	University of Michigan Willow Run Research Center Willow Run Airport Ypsilanti, Michigan Attn: Librarian Via: ONR	1	United Aircraft Corporation 400 Main Street East Hartford 8, Connecticut Attn: Chief Librarian Via: InsMat
2	APL/JHU 8021 Georgia Avenue Silver Spring, Maryland Attn: Tech. Hpts. Group Via: InsOrd		

No. of
Copies

No. of
Copies

1	Guggenheim Aeronautical Lab. California Inst. of Technology Pasadena 4, California Attn: Aeronautics Lib. Via: ONR	1	Commander AF Office of Scientific Research Washington 25, D. C.
1	Cornell Aeronautical Lab., Inc. P. O. Box 235, 4455 Genessee St. Buffalo 21, New York Attn: Librarian	1	Commander Western Development Division Headquarters ARDC Box 262 Inglewood, California
1	Attn: Mr. A. Hertzberg Via: InsMat		
1	Lewis Flight Propulsion Lab. 21000 Brookpark Road Cleveland 11, Ohio Attn: Chief, Supersonic Propulsion Div. Via: InsMat		
2	Armour Research Foundation 10 West 35th Street Chicago 16, Illinois Attn: Dept. M Via: InsMat		
1	Hughes Aircraft Corp. Culver City, California Attn: Assistant Director GMRD Div. Via: InsMat		
1	McDonnell Aircraft Corporation P. O. Box 516 St. Louis 3, Missouri Via: InsMat		
1	General Electric Company 2900 Campbell Avenue Schenectady 5, New York Attn: Library Guided Missiles Dept. Via: InsMat		
2	Eastman Kodak Company Navy Ordnance Division 50 West Main Street Rochester 14, New York Attn: Mr. W. B. Forman Via: InsOrd		