

UNCLASSIFIED

AD 261 670

*Reproduced
by the*


**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

261670

AFCRL 507

LUNAR TRAJECTORY STUDIES


A. Petty
I. Jurkevich
M. Fairize
T. Coffin

General Electric Company
Missile and Space Vehicle Department
Space Sciences Laboratory
Philadelphia, Pa.

Final Report

Contract No. AF 19(604)-5863

JUNE 1961



ELECTRONICS RESEARCH DIRECTORATE
AIR FORCE CAMBRIDGE RESEARCH LABORATORIES
OFFICE OF AEROSPACE RESEARCH
UNITED STATES AIR FORCE
Bedford, Mass.

Requests for additional copies by Agencies of the Department of Defense, their contractors, and other Government agencies should be directed to the:

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA

Department of Defense contractors must be established for ASTIA services or have their 'need-to-know' certified by the cognizant military agency of their project or contract.

All other persons and organizations should apply to the:

U.S. DEPARTMENT OF COMMERCE
OFFICE OF TECHNICAL SERVICES
WASHINGTON 25, D. C.

AFCRL 507

LUNAR TRAJECTORY STUDIES

A. Petty
I. Jurkevich
M. Fabrize
T. Coffin

General Electric Company
Missile and Space Vehicle Department
Space Sciences Laboratory
Philadelphia, Pa.

Contract No. AF 19(604)-5863

JUNE 1961

ELECTRONICS RESEARCH DIRECTORATE
AIR FORCE CAMBRIDGE RESEARCH LABORATORIES
OFFICE OF AEROSPACE RESEARCH
UNITED STATES AIR FORCE
Bedford, Mass.

ABSTRACT

This report presents a description of several related IBM-7090 Fortran computer programs designed to provide a fast, accurate, and systematic procedure for determining initial conditions to the differential equations of motion from tracking data, lunar and interplanetary trajectories in n-body space, and satellite ephemeris compilations.

The theory and analytical formulation for each program is given in detail. Instruction in program usage is given with individual check problems provided to facilitate operational proficiency.

To verify the formulations the following examples were used:

1. Initial Condition Determinations - (Data for the asteroid Leuschnerina 1935 used in form of a check problem).
2. Trajectory Computation - Lunik III Data (included in interim report).
3. Ephemeris Computation - (Data for the asteroids Pallas and Vesta used in form of a check problem).

In addition to the above work, this report also contains a study of Lunar Trajectories. The types of trajectories considered are:

1. Error Analysis of Hyperbolic Impact Trajectories.
2. Lifetime of an Artificial Lunar Satellite.
3. Lunar Circumnavigation and Earth Return.

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
ABSTRACT	i
TABLE OF CONTENTS	ii
I. INTRODUCTION	1
II. INITIAL CONDITION DETERMINATIONS - (GENERAL COMMENTS)	4
A. Introduction	4
B. Determination of Initial Conditions from Two Position Vectors	5
C. Determination of Initial Conditions from Three Angular Positions	7
D. Determination of Initial Conditions from Six Radar Range Measurements	11
III. INITIAL CONDITION DETERMINATIONS (COMPUTER ROUTINES)	14
A. Determination of Initial Conditions from Three Angular Positions	14
B. Determination of Initial Conditions from Two Position Vectors	29
C. Determination of Initial Conditions from Six Radar Range Measurements	37
IV. AUXILIARY COMPUTATIONS AND CONVERSION SUB-ROUTINES	44
A. Basic Requirements	45
B. Computation of Rectangular Geocentric Site Coordinates	47
C. Reduction of Rectangular Coordinates X, Y, Z of Date to Equinox of 1950.0	50
D. Reduction of (X, Y, Z) 1950.0 to Those of Date	51

TABLE OF CONTENTS (CONT.)

<u>Section</u>	<u>Page</u>
E. Conversion of Azimuth and Elevation to Right Ascension and Declination	53
F. Reduction of α and δ from Equinox of Date to Reference Equinox	54
G. Ephemeris Computation	57
H. Reduction of Sidereal Time Regulated by a Moving Equinox to Sidereal Time Regulated by a Stationary Equinox	61
I. Schematics of Typical Computations	64
V. ERROR ANALYSIS OF HYPERBOLIC LUNAR IMPACT TRAJECTORIES	69
VI. LIFETIME OF AN ARTIFICIAL LUNAR SATELLITE ..	86
VII. LUNAR CIRCUMNAVIGATION AND EARTH RETURN ..	90
VIII. EPHEMERIS COMPUTATION - PALLAS AND VESTA ..	99
REFERENCES	102
APPENDICES	
A MODIFICATION OF LUNAR TRAJECTORY COMPUTER PROGRAM TO N-BODY COMPUTER PROGRAM	A-1
A. Computer Input	A-3
B. N-Body Trajectory Program (Operational Directory)	A-3
C. Computer Output	A-7
D. Operating Notes for N-Body Trajectory Program ...	A-8
E. Description of Binary Table Tapes	A-9
F. Description of Modified DBC FORTRAN Input Routine	A-11
G. Julian Date and Calendar Date vs. Table Day	A-17
H. Listing of N-Body Program	A-33

TABLE OF CONTENTS (CONT.)

<u>Section</u>	<u>Page</u>
APPENDICES (Cont.)	
B. OPERATIONAL DIRECTORIES, LISTINGS, CHECK PROBLEMS FOR SECTIONS II, III AND IV	B-1
A. Two Position Vector Program	B-1
B. Three Angular Positions Program	B-10
C. Conversion of Coordinates from Equinox to Equinox	B-19
D. Conversion of Right Ascension and Declination from Equinox to Equinox	B-24
E. Computation of Rectangular Geocentric Site Coordinates and Conversion of Azimuth and Elevation to Right Ascension and Declination	B-29
F. Ephemeris Computation Program	B-35

I. INTRODUCTION

This report, which represents the final report on contract AF 19(604)-5863, is intended to cover only that work performed between July 1960 and June 1961. All work prior to this period has been given in an interim report.* All remarks made in the interim report concerning restrictions and assumptions pertaining to uncertainties in the physical constants employed and the resulting effects on the accuracy of the computations are applicable to this report.

A computer program designed to compute the trajectories of a body in the combined gravitational field of the Earth, Sun, and Moon, using true ephemerides of the positions of these bodies, has been operational for some time. It is described in the interim report.* This program has been extended to include the major planets and is known as the "n-body interplanetary trajectory program" ($n = 9$). The formulation of the equations of motion and the numerical integration techniques used are discussed in detail in the interim report. The main features and operational procedures are, however, included in Appendix A of this report.

Such a program is of great value in the computation of theoretical trajectories and orbits in which assumed sets of initial conditions are employed. However, employment of tracking data obtained from various radar and/or optical equipments located at a specific geographical location on the earth will require a great deal of additional hand computation before a "suitable set of initial conditions may be derived." This additional computation may assume several forms of which orbit determination, coordinate transformations,

* AFCRL - TN - 60 - 1132 Scientific Report No. 1 (AF 19(604)-5863 Lunar Trajectory Studies and An Application to Lunik III Trajectory Prediction - Petty, A. F., Jurkevick, I.; July 1960.

equinox to equinox reductions, and compilation of ephemeris tracking data are prominent.

These hand computations are tedious and time consuming. If a sizable number are required the impracticality of manual computation becomes increasingly evident. To circumvent this problem, computer subroutines have been developed. These routines, used in conjunction with the "n-body interplanetary trajectory program", provide a high degree of flexibility in solving diverse orbital and trajectory problems.

An objective of this report is to present each program's analytical development and to illustrate its use in augmenting the inherent capability of the "n-body interplanetary trajectory program." Machine listings, together with programming instructions, are given for those with more than cursory interest. (See Appendix B)

Verification of the accuracy of these computer programs and routines was established by recomputing the orbits and trajectories of well known astronomical objects (asteroids). In no case were theoretical orbits or trajectories employed to test the programs.

In particular, extensive use has been made of the data for the asteroid Leuschnerina 1935 in developing the initial condition determination programs, both for the two position vector case and for the three angular position case. Also a recomputation of the orbits of the asteroids Pallas and Vesta were used to verify the ephemeris prediction accuracy of the "n-body interplanetary trajectory program." Residuals obtained by comparing computed values against tabular values as given by the American Ephemeris and Nautical Almanac is indicative of the accuracy achievable.

The computer program development mentioned above represents one of the two major aspects of this contract. The other is the employment of these programs in the study of several classes of Lunar Trajectories. The first of these, a circumlunar flight which passes at a distance of 7,000 km from the Moon (Lunik III) was described in detail in the interim report. Here, tracking data released through the Russian news agency TASS was employed to obtain a set of initial conditions to the differential equations of motion. A second circumlunar flight initiating from the Atlantic Missile Range (AMR) was also studied in some detail and the results are included in this report. Such constraints as range safety limits, launch time, and booster limitations were considered as well as the usual two point boundary value constraints. The effect of some of these constraints is indicated.

A major effort was given to the determination of initial condition error sensitivities for "Hyperbolic Lunar Impact Trajectories." Nominal impact trajectories were established on three separate dates and error tubes obtained. No attempt was made to artificially constrain the nominal trajectory to a normal impact. In all cases the center of the apparent lunar disc was taken as the nominal trajectories impact location.

The final study involving the life time of a lunar satellite over extended period of time (25 days) indicates the perturbative effects of the earth and sun on the orbital elements. The instantaneous perturbations of the elements as a function of time are presented for the first ten (10) days of the orbit. An interesting development arising from this study is the fact that for identical initial conditions the life time of the satellite in an Earth, Moon, Sun field exceeds 25 days (we did not ascertain the limit) while in an Earth-Moon field, the vehicle impacts the Moon after some 9 days.

This report contains the results of all of the above mentioned studies with the exception of the Lunik III trajectory. Also, a few additional special cases are included in Section VIII of this report to illustrate certain statements in the text.

II. INITIAL CONDITION DETERMINATIONS (GENERAL CONSIDERATIONS)

GENERAL COMMENTS

In the development of the following computer programs two branches of Astronomy have been used. These are spherical Astronomy and Celestial Mechanics. The former is concerned with the details of establishing precise and practical coordinate systems from which observational or tracking data can be readily employed in the theoretical equations developed in the latter. An attempt has been made in this report to follow the standard developments found in the Astronomical texts. Familiarity with these standard conventions is assumed. However, for each routine or program, all parameters are defined in terms of the units used and the direction in which they are measured. Appropriate references are given to the Astronomical literature throughout the discussions.

A. INTRODUCTION

Once a set of initial conditions becomes known, the differential equations of motion on the n-body problem may be numerically integrated. Such a set comprises the vehicle's position and velocity vector at an instant of time relative to a particular coordinate system. It may be determined at the end of thrust or at subsequent times.

This section's objective is to indicate methods for determining this set of initial conditions from observational or tracking data. Concern here is with single tracking stations whose tracking equipment cannot instantaneously measure or provide vehicle position and velocity vector. Tracking situations considered are:

- (a) Vehicle position vector is measured or known at two instances of time.

(b) Vehicle angular position is measured or known at three instances of time. (no distance information available)

(c) Distance to the vehicle is measured or known at six instances of time. (no angular information is available)

It is to be noted that in all these tracking situations, six pieces of information are obtained. This is a necessary and sufficient condition to establish the required initial conditions.

Situation (a) corresponds to a radar recording the vehicle's range and angular coordinates. Situation (b) corresponds to an optical or infrared telescope recording of only the angular positions of the vehicle. Situation (c) corresponds to a radar recording of only the range to the vehicle.

In all cases it has been assumed that the time of each measurement is accurately known as well as the geographical position of the tracking station on the Earth's surface.

B. DETERMINATION OF THE INITIAL CONDITIONS FROM TWO POSITION VECTORS

Following Laplace, the position vector at any time t may be expressed in terms of the position and velocity vector at some time t_0 by

$$\vec{r}(t) = f \vec{r}_0 + g \dot{\vec{r}}_0 \quad (1)$$

where $\vec{r}_0 = \vec{r}(t_0)$, $\dot{\vec{r}}_0 = \dot{\vec{r}}(t_0)$

and
$$f = 1 - \frac{1}{2} \mu \tau^2 + \frac{1}{2} \mu \sigma \tau^3 + \frac{\mu}{24} (3\omega - 2\mu - 15\sigma^2) \tau^4 - \frac{\mu \sigma}{8} (3\omega - 2\mu - 7\sigma^2) \tau^5 + \dots$$

$$g = \tau - \frac{1}{6} \mu \tau^3 + \frac{1}{4} \mu \sigma \tau^4 + \frac{\mu}{120} (9\omega - 8\mu - 45\sigma^2) \tau^5 + \dots$$

$$\mu = \frac{MG}{|\vec{r}_0|^3}, \quad \sigma = \frac{\vec{r}_0 \cdot \dot{\vec{r}}_0}{|\vec{r}_0|^2}, \quad \omega = \frac{|\dot{\vec{r}}_0|^2}{|\vec{r}_0|^2}, \quad \tau = (t - t_0)$$

and where G is the gravitational constant and M is the mass of the Earth.

Note that f and g are scalar functions of the position and velocity at time t_0 and the time interval between measurements τ . If the conditions at t_0 are known, the entire trajectory is specified by equation (1).

The three scalar equations associated with (1) are:

$$\begin{aligned} X &= f X_0 + g \dot{X}_0 \\ Y &= f Y_0 + g \dot{Y}_0 \\ Z &= f Z_0 + g \dot{Z}_0 \end{aligned} \tag{2}$$

Now if observations are made at time t and t_0 , so that X , Y , Z , and X_0 , Y_0 , Z_0 can be computed, the velocity components $\dot{X}_0$, $\dot{Y}_0$, $\dot{Z}_0$ may be expressed in terms of the scalar function f and g as

$$\begin{aligned} \dot{X}_0 &= \frac{1}{g} (X - f X_0) \\ \dot{Y}_0 &= \frac{1}{g} (Y - f Y_0) \\ \dot{Z}_0 &= \frac{1}{g} (Z - f Z_0) \end{aligned} \tag{3}$$

Since f and g are themselves functions of the velocity $\dot{\vec{r}}_0$, the velocity components are given only implicitly by (3). To determine the velocity components, f and g are initially approximated by the first and second terms in the series which defines them. Specifically, f and g are initially approximated by $1 - \frac{1}{2} \mu \tau^2$ and $\tau - \frac{1}{6} \mu \tau^3$ respectively.

Equation (3) is then solved, giving first approximations to $\dot{X}_O, \dot{Y}_O, \dot{Z}_O$. These values are used to recompute the f and g series, which in turn are used in (3) to recompute better approximations to $\dot{X}_O, \dot{Y}_O, \dot{Z}_O$. This procedure is repeated until successive iterations result in velocity components that differ by less than some prescribed tolerance.

C. DETERMINATION OF THE INITIAL CONDITIONS FROM THREE ANGULAR POSITIONS

(Distance Information Not Available)

Again following Laplace, but employing the entire development, computation of the initial conditions from angular observations alone is possible. Generally, the Laplacian method consists of writing two equations in two unknowns. One, the geometrical equation, can be expressed as

$$r^2 = \rho^2 + R^2 - 2(\vec{P} \cdot \vec{R}) \rho \quad (4)$$

and the other, the dynamical equation, as

$$\rho \left[\vec{P} \times \dot{\vec{P}} \cdot \ddot{\vec{P}} \right] = \left[\vec{P} \times \dot{\vec{P}} \cdot \ddot{\vec{R}} \right] + \left[\vec{P} \times \dot{\vec{P}} \cdot \ddot{\vec{R}} \right] / r^3 \quad (5)$$

in which $\vec{\rho}$ is the radius vector between the observing station and vehicle, and $\vec{r}$, the geocentric distance of the object at time t. These are the unknown quantities. The quantity $\vec{R}$ is the geocentric radius vector of the observing station and is assumed to be known. The quantity $\vec{P}$ is a unit vector directed along the line from the observing station to the vehicle. Its components are the direction cosines of the observations and together with the components of $\dot{\vec{P}}_O$ and $\ddot{\vec{P}}_O$, enable evaluation of the triple scalar products in the dynamical equations.

For computational facility various schemes have been advocated. The methods differ only in the quantities taken as the independent variables. Thus, the straight or original Laplacian method directly uses the magnitudes of $\vec{\rho}$ and $\vec{r}$.

Leuschner's modification uses $\rho \cos \delta$ and $|\vec{r}|$ as the variables, and Stumpff employs $|\vec{r}|$ and one of the components of $\vec{r}$ as the principal variables. The quantity $\rho \cos \delta$ is known as the curtate distance, and δ represents the declination.

We have chosen to program Stumpff's method. This method derives its principal advantage from the use of the ratios of the direction cosines and the reduction of all the determinants from the third to second order. In the original Laplacian formulation, all the formulas were expressed in terms of third order determinants which correspond to the triple scalar product. The following formulation of Stumpff's Method has been employed. (See Herget - "Computation of Orbits")

Let

$$U = \frac{y + Y}{x + X} = \tan \alpha, \quad V = \frac{z + Z}{x + X} = \sec \alpha \tan \delta, \quad P = Y - UX,$$

$$Q = Z - VX \tag{6}$$

where the small x, y, z are components of the vehicle and the large X, Y, Z are the components of the tracking site both referred to the same geocentric equatorial coordinate system. The latter are known quantities since we assume the geographic coordinates of the tracking station on the Earth's surface are known. The quantities α (the right ascension) and δ (the declination) are the measured observables. Three sets $\alpha_1 \delta_1, \alpha_2 \delta_2, \alpha_3 \delta_3$ of these observables are recorded and are the fundamental six pieces of information required for the trajectory determination.

Cross multiplying the equations for U and V , introducing P and Q , and differentiating twice, obtains

$$\begin{aligned} y &= Ux - P & z &= Vx - Q \\ \dot{y} &= \dot{U}x + U\dot{x} - \dot{P} & \dot{z} &= \dot{V}x - V\dot{x} - \dot{Q} \\ \ddot{y} &= \ddot{U}x + 2\dot{U}\dot{x} + U\ddot{x} - \ddot{P} & \ddot{z} &= \ddot{V}x - 2\dot{V}\dot{x} + V\ddot{x} - \ddot{Q} \end{aligned} \tag{7}$$

Substituting the dynamical conditions for each component of $\ddot{\vec{r}} = \frac{\vec{r}}{r^3}$ into the two bottom equations of (7) obtains

$$\frac{1}{2} \ddot{U}_x + \dot{U}_x = \frac{1}{2} \ddot{P} + \frac{P}{2r^3} \quad (8)$$

$$\frac{1}{2} \ddot{V}_x + \dot{V}_x = \frac{1}{2} \ddot{Q} + \frac{Q}{2r^3}$$

Let

$$D = \frac{1}{2} \ddot{U} \dot{V} - \frac{1}{2} \ddot{V} \dot{U}$$

obtaining

$$D_x = \frac{1}{2} (\ddot{P} \dot{V} - \ddot{Q} \dot{U}) + (P \dot{V} - Q \dot{U}) / 2r^3 \quad (9)$$

$$D_x = \frac{1}{4} (\ddot{Q} \ddot{U} - \ddot{P} \ddot{V}) + (\ddot{U} Q - \ddot{V} P) / 4r^3$$

$$r^2 = x^2 + y^2 + z^2 = (1 + U^2 + V^2)X^2 - 2(UP + VQ)X + (P^2 + Q^2)$$

In equation (9) the only unknowns are x , $\dot{x}$, and r which can be obtained by a simple iteration between the equations. The approximate numerical values of the coefficients at time t_0 , the time of the middle observation, may be obtained from the observations by writing a Taylor's series for the first and third observations as

$$\begin{aligned} W_1 &= W_0 + \dot{W}_0 T_1 + \frac{1}{2} \ddot{W}_0 T_1^2 + \dots \\ W_3 &= W_0 + \dot{W}_0 T_3 + \frac{1}{2} \ddot{W}_0 T_3^2 + \dots \end{aligned} \quad (10)$$

which may be written in the form

$$(W_1 - W_0) T_1 = \dot{W}_0 + \frac{1}{2} \ddot{W}_0 T_1 = (W, 1)$$

$$(W_3 - W_0) T_3 = \dot{W}_0 + \frac{1}{2} \ddot{W}_0 T_3 = (W, 3)$$

and then

$$\dot{W}_0 (T_3 - T_1) = T_3 (W, 1) - T_1 (W, 3)$$

$$\frac{1}{2} \ddot{W}_0 (T_3 - T_1) = (W, 3) - (W, 1)$$

where W denotes U , V , P or Q and $T_1 = (t_1 - t_0)$, $T_3 = (t_3 - t_0)$. Thus, all coefficients can be determined from the observations, and equations in (9) solved. With the solutions from (9), (7) may be employed to obtain the other components of the vehicle's position and velocity vectors at time t_0 . Initial conditions are thus obtained.

The value of D is the controlling factor of the entire solution. This corresponds to the coefficient of ρ in the left-hand member of (5). If extremely small, it indicates the time interval between measurements is too small to make the solution very determinate. Also, it is easy to see that difficulties will arise in employing this method when observations exist in the neighborhood of 6^h or 18^h right ascension, due to the large, or even meaningless, values obtained for the derivatives of U . Methods for circumventing this problem are currently being considered e.g., rotating the coordinate system by a fixed amount, though this will probably only shift the problem to the V 's for observations near the celestial pole.

Employing more than three observations will aid in alleviating this problem. This, however, is an entirely different computation involving differential correction procedures and will not be discussed here.

D. DETERMINATION OF INITIAL CONDITIONS FROM SIX RADAR RANGE MEASUREMENTS


(Angular Information not available)

Initially, it appears that the initial conditions could be obtained from six radar measurements employing a line of reasoning similar to that used for two range vectors.

The observing site, the vehicle, and the dynamical center are connected by

$$\vec{\rho} = \vec{r} - \vec{R} \quad (11)$$

as shown in the following sketch



From the law of cosines

$$r_n^2 = R_n^2 + \rho_n^2 + 2\vec{R}_n \cdot \vec{\rho}_n \quad (12)$$

Recall now that in Laplace's method

$$\vec{r}_n = f_n \vec{r}_o + g_n \dot{\vec{r}}_o \quad (13)$$

From (13) it follows directly that

$$r_n^2 = f_n^2 r_o^2 + 2f_n g_n \vec{r}_o \cdot \dot{\vec{r}}_o + g_n^2 \dot{r}_o^2 = (f_n^2 + 2f_n g_n \sigma + g_n^2 \omega) r_o^2, \quad (14)$$

where σ and ω are defined as for the case of two range vectors. The same holds for the f_n and g_n series.

It is further convenient to express $2 \vec{\rho}_n \cdot \vec{R}_n$ as

$$2 (\vec{r}_n - \vec{R}_n) \cdot (\vec{R}_n) = 2 \vec{r}_n \cdot \vec{R}_n - 2 R_n^2 \quad (15)$$

Employing now (4) and (5), in (2) obtains

$$C_n = \rho_n^2 - R_n^2 = (f_n^2 + 2 f_n g_n \sigma + g_n^2 \omega) r_o^2 - 2 f_n X_n x_o - 2 f_n Y_n y_o - 2 f_n Z_n z_o \\ - 2 g_n X_n \dot{x}_o - 2 g_n Y_n \dot{y}_o - 2 g_n Z_n \dot{z}_o \quad (16)$$

In the above, X_n, Y_n, Z_n are the rectangular components of the vector $\vec{R}_n$ at the corresponding time τ_n at which the range ρ_n is measured.

Using obvious definitions, it is convenient to write equations (16) as follows:

$$a_{n1} r_o^2 + a_{n2} x_o + a_{n3} y_o + a_{n4} z_o + a_{n5} \dot{x}_o + a_{n6} \dot{y}_o + a_{n7} \dot{z}_o = C_n \quad (17)$$

$$n = 1, 2, 3, \dots, 6$$

A few remarks are pertinent with respect to this set. The unknown quantities are $x_o, y_o, z_o, \dot{x}_o, \dot{y}_o, \dot{z}_o$, and r_o although the latter is given by $r_o^2 = x_o^2 + y_o^2 + z_o^2$. The coefficients a_{ni} are not really known, although, an approximation to these is available by taking first terms in the f and g series.

It is apparent that if r_o is included among the unknowns seven measurements instead of six are needed. On the other hand, a better approximation of f_n and g_n can be obtained by taking two terms in these series. This is, however, equivalent to estimating r_o . If this is the adopted procedure, only six measurements are required.

The computational scheme is then:

The input data are the six values of measured range; an estimate of r_o ; X_o , Y_o , Z_o ; sidereal time; six values of time at which the measurements are taken; and the rotation rate of the Earth.

From the above the coefficients a_{ni} are estimated and set (17) is solved. This results in quantities

$$r_o = (x_o^2 + y_o^2 + z_o^2)^{1/2}$$

$$v_o = (\dot{x}_o^2 + \dot{y}_o^2 + \dot{z}_o^2)^{1/2}$$

From these, better estimate of μ , σ and ω are obtained entering the f_n and g_n series. Using these, the whole procedure is repeated until the desired precision is obtained.

III. INITIAL CONDITION DETERMINATIONS (COMPUTER ROUTINES)

Section II presented the motivation behind the need for tracking sub-routines. Summarizing, the purpose of tracking subroutines is to yield initial conditions required to initiate numerical integration of the differential equations of the n-body problem.

Basic ideas and computational formulas involved in the three chosen routines were outlined in Section II. In the present section, detailed step-by-step procedures, as programmed for the computer are given. In all three cases, however, discussion is more extensive than that prepared for computer use, reflecting the programs evolution. The entire development will be included since many procedures, though not employed in final computational programs, can be of interest to the user willing to effect personal modifications.

It should be noted that one of the three tracking schemes considered in this report proves unsuitable for numerical computations. Reasons for failure of the routine employing six ranges, measured from a single tracking station, will be discussed later.

The first tracking scheme to be described employs the vehicle's three measured angular positions.

A. DETERMINATION OF THE INITIAL CONDITIONS FROM THREE ANGULAR POSITIONS

This tracking method's purpose is to compute the components of the vehicle's position and velocity at some time t from measurements of its right ascension and declination at three instants of time. It is assumed that if the measured quantities are azimuth and elevation, they are transformed

into the corresponding right ascension and declination by methods outlined in Section IV. It is further assumed that these methods are employed to prepare all measured data and auxiliary quantities for computations.

It must be emphasized that all tracking methods described in this report yield preliminary values of initial conditions. The significance is that a minimum of data is used to effect the computation. Consequently, no provisions are made to accept redundant data to obtain a better estimate of the desired quantities. Standard differential correction procedures can be used, eg. maximum likelihood estimation, or the conventional least squares method once the initial preliminary trajectory is obtained. Their inclusion in this report is omitted as they were not considered a part of the study.


Initial estimates are based on a two body problem where the vehicle moves in the immediate neighborhood of some dominant mass. The latter will, in most cases, be the Earth.

It can be seen from Figure 1 that an astronomer usually considers the distances Observer $\rightarrow$ Vehicle and Observer $\rightarrow$ Center of Force positive. For purposes of this report it was found more convenient to measure distance Center of Force $\rightarrow$ Observer as positive. Distance $\vec{r}$ is in both cases measured positively from the center of the force.


The new definition of the sign of $\vec{r}$ will result in expressions slightly different from those in the previous section. For this reason, the development of Stumpff's method is repeated. The choice of this particular method was discussed in Section II.

1. Determination of the Initial Conditions from Three Angular Positions

From Figure 1b, it can be seen that the observer's position,



(a) Astronomical convention



(b) Convention employed in the report

Figure 1. Relation Between the Observer, Vehicle and Center of Force

the vehicle's geocentric position, and position of the center of force are related by

$$\begin{aligned}\vec{r} &= \vec{\rho} + \vec{R} \\ \therefore \vec{\rho} &= \vec{r} - \vec{R}\end{aligned}\tag{1}$$

In appropriate rectangular components this is:

$$\begin{aligned}\xi &= \rho \cos \delta \cos \alpha = x - X \\ \eta &= \rho \cos \delta \sin \alpha = y - Y \\ \zeta &= \rho \sin \delta = z - Z\end{aligned}\tag{2}$$

Employing the latter expressions define

$$\begin{aligned}U &\equiv \tan \alpha = \frac{y - Y}{x - X} \\ V &\equiv \sec \alpha \tan \delta = \frac{z - Z}{x - X}\end{aligned}\tag{3}$$

These equations yield in an obvious manner

$$\begin{aligned}Ux - UX &= y - Y \\ Vx - VX &= z - Z\end{aligned}\tag{4}$$

or

$$\begin{aligned}Y - UX &= y - Ux \equiv P \\ Z - VX &= z - Vx \equiv Q\end{aligned}\tag{5}$$

The last equations can be rewritten as

$$\begin{aligned} y &= P + Ux \\ z &= Q + Vx \end{aligned} \quad (6)$$

In the above, it must be noted, α and δ are measured in the coordinate system fixed at the observer's site. The components of $\bar{R}$ can always be found as soon as the location of the tracking station and the time of measurement are known. Both α , δ and X , Y , Z must be referred to the same coordinate system. It is recommended that some standard coordinate system be adopted, e. g., that referenced to the mean equinox of 1950.0.

Differentiating equations (6) obtains

$$\begin{aligned} \dot{y} &= \dot{U}x + U\dot{x} + \dot{P} & \dot{z} &= \dot{V}x + V\dot{x} + \dot{Q} \\ \ddot{y} &= \ddot{U}x + 2\dot{U}\dot{x} + U\ddot{x} + \ddot{P} & \ddot{z} &= \ddot{V}x + 2\dot{V}\dot{x} + V\ddot{x} + \ddot{Q} \end{aligned} \quad (7)$$

Note the equations of motion of the vehicle in the gravitational field of the dominant mass are given by

$$\ddot{x} = -\frac{x}{r^3}, \quad \ddot{y} = -\frac{y}{r^3}, \quad \ddot{z} = -\frac{z}{r^3} \quad (8)$$

In these equations, units are chosen in such a way that the constant k appearing normally in (8) is equal to unity.

Employing equations (8) in (7) it follows that

$$\begin{aligned} \frac{1}{2} \ddot{U}x + \dot{U}\dot{x} &= -\frac{1}{2} \ddot{P} - \frac{P}{2r^3} \\ \frac{1}{2} \ddot{V}x + \dot{V}\dot{x} &= -\frac{1}{2} \ddot{Q} - \frac{Q}{2r^3} \end{aligned} \quad (9)$$

Solution of system (9) for x and $\dot{x}$ yields

$$x = \frac{\begin{vmatrix} -\frac{1}{2} \ddot{P} - \frac{P}{2r^3} \dot{U} \\ -\frac{1}{2} \ddot{Q} - \frac{Q}{2r^3} \dot{V} \end{vmatrix}}{\begin{vmatrix} \frac{1}{2} \ddot{U} & \dot{U} \\ \frac{1}{2} \ddot{V} & \dot{V} \end{vmatrix}} = \frac{-\left(\frac{1}{2} \ddot{P} \dot{V} - \frac{1}{2} \ddot{Q} \dot{U}\right) - \left(\frac{P \dot{V} - Q \dot{U}}{2r^3}\right)}{\frac{1}{2} \ddot{U} \dot{V} - \frac{1}{2} \ddot{V} \dot{U}} \quad (10)$$

Define the following quantities

$$\begin{aligned} D &\equiv \frac{1}{2} \ddot{U} \dot{V} - \frac{1}{2} \ddot{V} \dot{U} \\ A &\equiv -\left(\frac{1}{2} \ddot{P} \dot{V} - \frac{1}{2} \ddot{Q} \dot{U}\right) \\ B &\equiv -\left(P \dot{V} - Q \dot{U}\right) \end{aligned} \quad (11)$$

By virtue of equation (11), x can be rewritten as

$$x = \frac{A}{D} + \frac{B}{2D} \cdot \frac{1}{r^3}$$

Similarly

$$\begin{aligned} D\dot{x} &= \begin{vmatrix} \frac{1}{2} \ddot{U} & -\frac{1}{2} \ddot{P} - \frac{P}{2r^3} \\ \frac{1}{2} \ddot{V} & -\frac{1}{2} \ddot{Q} - \frac{Q}{2r^3} \end{vmatrix} \\ D\dot{x} &= -\left(\frac{1}{2} \ddot{U} \cdot \frac{1}{2} \ddot{Q} - \frac{1}{2} \ddot{P} \cdot \frac{1}{2} \ddot{V}\right) - \frac{\left(\frac{1}{2} Q \ddot{U} - \frac{1}{2} P \ddot{V}\right)}{2r^3} \end{aligned} \quad (12)$$

Defining quantities

$$G \equiv - \left(\frac{1}{4} \ddot{U} \ddot{Q} - \frac{1}{4} \ddot{P} \ddot{V} \right)$$

$$H \equiv - \left(\frac{1}{2} Q \ddot{U} - \frac{1}{2} P \ddot{V} \right)$$

$\dot{x}$ can be written as

$$\dot{x} = \frac{G}{D} + \frac{H}{2D} \cdot \frac{1}{r^3}$$

Finally r can be expressed in terms of x using equations (4).

Thus

$$\begin{aligned} r^2 &= x^2 + y^2 + z^2 = x^2 + (P + Ux)^2 + (Q + Vx)^2 \\ r^2 &= \left(1 + U^2 + V^2 \right) x^2 + 2 (PU + QV) x + \left(P^2 + Q^2 \right) \end{aligned} \quad (13)$$

Defining

$$C = 1 + U^2 + V^2$$

$$E = 2 (PU + QV)$$

$$F = P^2 + Q^2$$

r can be expressed as

$$r^2 = Cx^2 + Ex + F$$

Equations (10), (12), and (13) represent a system of simultaneous equations in x , $\dot{x}$, and r . Now, x and r are solved by (10) and (12), employing any convenient numerical procedure. Once r is available, $\dot{x}$ follows from (12). Other components of the position and velocity follow from equations (6) and (7).

The development of Stumpff's method will be concluded by giving, without proof, two infinite series frequently occurring in orbit determinations of the type considered in this report.

These are the f and g series of the Laplacian method of orbit computation. The simple idea behind these series is as follows. Suppose that position $\vec{r}_0$ and velocity $\dot{\vec{r}}_0$ of the vehicle are known at some time t_0 . The motion of the vehicle in the neighborhood of this point can then be expressed as

$$\vec{r} = \vec{r}_0 + \tau \dot{\vec{r}}_0 + \tau^2/2! \ddot{\vec{r}}_0 + \dots \quad (14)$$

and

$$\ddot{\vec{r}} = - \frac{\vec{r}}{r^3}$$

Successive differentiation of the last equation permits elimination of higher order derivatives in (14). It can be shown that as a result of this procedure equation (14) assumes the following form

$$\vec{r} = f \vec{r}_0 + g \dot{\vec{r}}_0 \quad (15)$$

where

$$\begin{aligned}
 f = 1 - \frac{1}{2} \mu \tau^2 + \frac{1}{2} \mu \sigma \tau^3 + \frac{\mu \left(3\omega - 2\mu - 15\sigma^2 \right)}{24} \tau^4 \\
 - \frac{\mu \sigma \left(3\omega - 2\mu - 7\sigma^2 \right)}{8} \tau^5 + \frac{\mu}{720} \left[\left(630\omega - 420\mu - 945\sigma^2 \right) \sigma^2 \right. \\
 \left. - \left(22\mu^2 - 66\mu\omega + 45\omega^2 \right) \right] \tau^6 + \dots
 \end{aligned} \tag{16}$$

$$\begin{aligned}
 g = \tau - \frac{1}{6} \mu \tau^3 + \frac{\mu \sigma}{4} \tau^4 + \frac{\mu \left(9\omega - 8\mu - 45\sigma^2 \right)}{120} \tau^5 \\
 - \frac{\mu \sigma \left(6\omega - 5\mu - 14\sigma^2 \right)}{24} \tau^6 + \dots
 \end{aligned} \tag{17}$$

$$\mu = \frac{\bar{r}_o \cdot \bar{r}_o}{r_o^5} = \frac{1}{r_o^3} \quad \sigma = \frac{\bar{r}_o \cdot \dot{\bar{r}}_o}{r_o^2} \quad \omega = \frac{\dot{\bar{r}}_o \cdot \ddot{\bar{r}}_o}{r_o^2}$$

Terms higher than τ^6 become too complicated for practical purposes. Note that $\tau = t - t_o$ is expressed in the appropriate units of time.

Use of f and g series is subject to the usual limitations of convergence. If any doubt exists concerning the latter, it is better to use the closed form of the series in question. The appropriate expressions can be found in Reference (1) pp. 48 or 75.

It is unlikely that in problems considered in this report the need for closed forms will ever appear.

The procedure written for the computer is based on the above development and it is summarized in a step by step form below:

Measured Data and Site Coordinates

Time and Date	Right Ascension	Declination	Rectangular Components of Site		
			X	Y	Z
t_1	a_1	δ_1	X_1	Y_1	Z_1
t_0	a_0	δ_0	X_0	Y_0	Z_0
t_3	a_3	δ_3	X_3	Y_3	Z_3

In the above, units of distance and time should be taken in accordance with the rules outlined in Section IV. The procedures of this chapter also determine the site coordinates.

2. Computer Program

The computation then proceeds as follows:

I. Compute

$$\text{TAN } a_i \equiv U_i$$

$$\text{SEC } a_i$$

$$P_i = Y_i - U_i X_i$$

$$\text{TAN } \delta_i$$

$$Q_i = Z_i - V_i X_i$$

$$\text{SEC } a_i \text{ TAN } \delta_i \equiv V_i$$

$$i = 1, 0, 3$$

II. Compute

$$\tau_1 = k (t_1 - t_o)$$

$$\tau_3 = k (t_3 - t_o)$$

$$\tau_3 - \tau_1$$

The value of k is the reciprocal of the time unit employed for the particular problem.

In any modification of the Laplacian method of preliminary orbit determination, it is desirable that intervals $t_1 - t_o$ and $t_3 - t_o$ be nearly equal. It can be shown that, under these conditions, errors in numerical derivatives and accelerations of U , P , V , Q are of the second order.

III. Compute the following quantities

$$(U, 1) = \frac{U_1 - U_o}{\tau_1}$$

$$(U, 3) = \frac{U_3 - U_o}{\tau_3}$$

$$(V, 1) = \frac{V_1 - V_o}{\tau_1}$$

$$(V, 3) = \frac{V_3 - V_o}{\tau_3}$$

$$(P, 1) = \frac{P_1 - P_o}{\tau_1}$$

$$(P, 3) = \frac{P_3 - P_o}{\tau_3}$$

$$(Q, 1) = \frac{Q_1 - Q_o}{\tau_1}$$

$$(Q, 3) = \frac{Q_3 - Q_o}{\tau_3}$$

IV. Compute

$$\dot{U}_o = \frac{\tau_3 (U, 1) - \tau_1 (U, 3)}{\tau_3 - \tau_1}, \quad \dot{P}_o = \frac{\tau_3 (P, 1) - \tau_1 (P, 3)}{\tau_3 - \tau_1}$$

$$\dot{V}_o = \frac{\tau_3 (V, 1) - \tau_1 (V, 3)}{\tau_3 - \tau_1}, \quad \dot{Q}_o = \frac{\tau_3 (Q, 1) - \tau_1 (Q, 3)}{\tau_3 - \tau_1}$$

V. Compute quantities

$$\frac{1}{2} \ddot{U}_o = \frac{(U, 3) - (U, 1)}{\tau_3 - \tau_1}, \quad \frac{1}{2} \ddot{P}_o = \frac{(P, 3) - (P, 1)}{\tau_3 - \tau_1}$$

$$\frac{1}{2} \ddot{V}_o = \frac{(V, 3) - (V, 1)}{\tau_3 - \tau_1}, \quad \frac{1}{2} \ddot{Q}_o = \frac{(Q, 3) - (Q, 1)}{\tau_3 - \tau_1}$$

VI. Compute the quantities

$$(a) \quad D = \frac{1}{2} \ddot{U}_o \dot{V}_o - \frac{1}{2} \ddot{V}_o \dot{U}_o$$

$$(e) \quad E = 2 \left(P_o U_o + Q_o V_o \right)$$

$$(b) \quad A = - \left(\frac{1}{2} \ddot{P}_o \dot{V}_o - \frac{1}{2} \ddot{Q}_o \dot{U}_o \right)$$

$$(f) \quad F = P_o^2 + Q_o^2$$

$$(c) \quad B = - \left(P_o \dot{V}_o - Q_o \dot{U}_o \right)$$

$$(g) \quad G = - \left(\frac{1}{2} \ddot{Q}_o \frac{1}{2} \ddot{U}_o - \frac{1}{2} \ddot{P}_o \frac{1}{2} \ddot{V}_o \right)$$

$$(d) \quad C = 1 + U_o^2 + V_o^2$$

$$(h) \quad H = - \left(\frac{1}{2} Q_o \ddot{U}_o - \frac{1}{2} P_o \ddot{V}_o \right)$$

VII. Form the following equations

$$(a) \quad x = \frac{A}{D} + \frac{B}{2D} \cdot \frac{1}{r^3}$$

$$(b) \quad r^2 = C x^2 + E x + F$$

$$(c) \quad \dot{x} = \frac{G}{D} + \frac{H}{2D} \cdot \frac{1}{r^3}$$

VIII. Solve (a) and (b) of step VII simultaneously for x and r .
Designate desired solutions by x_o and r_o .

For the case of vehicles moving in the Earth's vicinity $r_o > 1$ in units of the Earth equatorial radius. Generally, equations (a) and (b) may result in three values of r . One is the desired one, the second represents the position of the center of force, and the third is entirely spurious.

IX. Using the value of r_o obtained in step VIII compute $\dot{x}_o$ from equation VII. (c)

$$\dot{x}_o = \frac{G}{D} + \frac{H}{2D} \cdot \frac{1}{r_o^3}$$

X. Compute

$$y_o = P_o + U_o x_o$$

$$\dot{y}_o = \dot{U}_o x_o + U_o \dot{x}_o + \dot{P}_o$$

$$z_o = Q_o + V_o x_o$$

$$\dot{z}_o = \ddot{V}_o x_o + V_o \dot{x}_o + \dot{Q}_o$$

If the intervals of time between measurements are equal, the computed values of

$$x_o, y_o, z_o$$

$$\dot{x}_o, \dot{y}_o, \dot{z}_o$$

refer to the time of middle measurement.

These values, expressed in suitable units, are then employed as the initial conditions in the n-body Trajectory Program. If redundant data are available, preliminary values are used to initiate a differential correction program.

The following computation has not been programmed. It is included so that, if desired, it can be employed as a check on the quality of computation.

For times t_1 and t_3 compute values of f and g . In employing these values

$$x_1 = f_1 x_o + g_1 \dot{x}_o$$

$$y_1 = f_1 y_o + g_1 \dot{y}_o$$

$$z_1 = f_1 z_o + g_1 \dot{z}_o$$

and

$$x_3 = f_3 x_0 + g_3 \dot{x}_0$$

$$y_3 = f_3 y_0 + g_3 \dot{y}_0$$

$$z_3 = f_3 z_0 + g_3 \dot{z}_0$$

Since positions of the observer at times t_1 and t_3 are known, it is possible to compute

$$x_1 - X_1$$

$$y_1 - Y_1$$

$$z_1 - Z_1$$

$$x_3 - X_3$$

$$y_3 - Y_3$$

$$z_3 - Z_3$$

Using these compute a_1 , δ_1 and a_3 , δ_3 from

$$\text{TAN } a_1 = \frac{y_1 - Y_1}{x_1 - X_1} ; \text{SEC } a_1 \text{ TAN } \delta_1 = \frac{z_1 - Z_1}{x_1 - X_1}$$

and similar expressions at $t = t_3$.

The computed values of $a_1, \delta_1, a_3, \delta_3$ should be in reasonable agreement with the observed ones. Failure to achieve agreement may be due to:

- (a) Error in computation
- (b) Too long or too short a time interval
- (c) Original observations too inaccurate

etc.

This concludes the discussion of the first tracking method.

B. DETERMINATION OF INITIAL CONDITIONS FROM TWO POSITION VECTORS

This section describes a procedure for determining velocity components of vehicle movement in the Earth's gravitational field from measurements of the distance and two associated angles at two different times.

In analysis, the technique offers a fast and accurate computer solution to establishing the complete initial conditions at some time t .

Laplace's method shows that position $\vec{r}$, at any time t , of an object traveling in a Keplerian orbit, can be expressed as a function of the position $\vec{r}_0$ and velocity $\dot{\vec{r}}_0$ at some time t_0 , according to

$$\vec{r} = f \vec{r}_0 + g \dot{\vec{r}}_0 \quad (A)$$

where f and g are scalar functions of the position and velocity at time t_0 and the time interval $t - t_0$. Since $\vec{r}$ and $\dot{\vec{r}}_0$ are specified if two range and two

angular coordinates are observed at time t and t_0 , the velocity $\vec{r}_0$ may be determined from (A), if f and g are known. Fortunately, for time intervals between observations of practical interest, functions f and g are represented by rapidly converging infinite series whose first dominant terms are functions of position $\vec{r}_0$ and the time interval $t-t_0$, but not of the velocity $\vec{r}_0$. Thus, good first approximations of f and g are known, though the initial velocity is unknown.

The method described in this section is based on the above facts. The initial velocity $\vec{r}_0$ is evaluated from Equation (A) after f and g have been approximated. This first approximation in velocity is used to recompute f and g , giving a better estimate of velocity. The procedure is repeated until desired precision is obtained. It is apparent the computation is iterative in which good initial estimates of the initial velocity components are not required. In fact, because of the very nature of the f and g series, the first approximations are quite satisfactory.

1. Determination of Equatorial Position Coordinates From Range, Azimuth and Elevation

Figure 2 shows the position of the observed object in the coordinate system fixed at the radar site. Let $\hat{\xi}$, $\hat{\eta}$, $\hat{\zeta}$ be the unit vectors along the respective axes, A-azimuth and E-elevation. Then the vector $\vec{\rho}$ from the observing station to the object is given by

$$\vec{\rho} = \rho \left[\cos E \cos A \hat{\zeta} + \cos E \sin A \hat{\eta} + \sin E \hat{\xi} \right] \quad (18)$$

Figure 3 shows that the position vector of the observing station is given by

$$\vec{R} = R \left[\cos \phi' \cos \Theta \hat{i}_x + \cos \phi' \sin \Theta \hat{i}_y + \sin \phi' \hat{i}_z \right] \quad (19)$$

where $\hat{i}_x, \hat{i}_y, \hat{i}_z$ are the unit vectors in the inertial geocentric cartesian coordinate system and ϕ' and θ are the geocentric latitude and local sidereal time (expressed in angular measure) of the site, respectively. The latter quantities are computed according to the rules given in the chapter on conversion routines.

Rotation of the x, y, z coordinate system through an angle θ about the z axis, and through an angle ϕ' about the y' axis, results in the following expression.

$$\begin{pmatrix} \hat{\xi} \\ \hat{\eta} \\ \hat{\zeta} \end{pmatrix} = \begin{pmatrix} \cos \phi' & 0 & \sin \phi' \\ 0 & 1 & 0 \\ -\sin \phi' & 0 & \cos \phi' \end{pmatrix} \begin{pmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} \hat{i}_x \\ \hat{i}_y \\ \hat{i}_z \end{pmatrix}$$

Let

$$\cos \phi' \cos \theta = L$$

$$\cos \phi' \sin \theta = M$$

$$\sin \phi' = N$$

then the unit vectors are related by:

$$\hat{\xi} = L\hat{i}_x + M\hat{i}_y + N\hat{i}_z$$

$$\hat{\eta} = -\frac{M}{\sqrt{L^2 + M^2}}\hat{i}_x + \frac{L}{\sqrt{L^2 + M^2}}\hat{i}_y$$

(20)

$$\hat{\zeta} = - \frac{NL}{\sqrt{L^2 + M^2}} \hat{i}_x - \frac{NM}{\sqrt{L^2 + M^2}} \hat{i}_y + \sqrt{L^2 + M^2} \hat{i}_z \quad (20)$$

Using (20) in (18):

$$\begin{aligned} \vec{\rho} = \rho & \left[\left(L \sin E - \frac{M}{\sqrt{L^2 + M^2}} \cos E \sin A - \frac{NL}{\sqrt{L^2 + M^2}} \cos E \cos A \right) \hat{i}_x \right. \\ & + \left(M \sin E + \frac{L}{\sqrt{L^2 + M^2}} \cos E \sin A - \frac{NM}{\sqrt{L^2 + M^2}} \cos E \cos A \right) \hat{i}_y \\ & \left. + \left(N \sin E + \sqrt{L^2 + M^2} \cos E \cos A \right) \hat{i}_z \right] \end{aligned}$$

From Figure 1b.

$$\vec{r} = \vec{\rho} + \vec{R} = x \hat{i}_x + y \hat{i}_y + z \hat{i}_z$$

Thus, previous expressions yield

$$\begin{aligned} x &= RL + \rho \left(L \sin E - \frac{M}{\sqrt{L^2 + M^2}} \cos E \sin A - \frac{NL}{\sqrt{L^2 + M^2}} \cos E \cos A \right) \\ y &= RM + \rho \left(M \sin E + \frac{L}{\sqrt{L^2 + M^2}} \cos E \sin A - \frac{NM}{\sqrt{L^2 + M^2}} \cos E \cos A \right) \\ z &= RN + \rho \left(N \sin E + \sqrt{L^2 + M^2} \cos E \cos A \right) \end{aligned}$$

To obtain the geocentric rectangular coordinates of the object referred to the equinox of date, range, azimuth, elevation, geocentric site latitude and sidereal time are needed.

If the computation is to proceed with respect to some other equinox, x , y , and z must be transformed according to the rules given elsewhere in this report.

This need, however, will be ignored for the present.

2. Determination of the Initial Conditions from Range, Azimuth and Elevation Measurements

Since motions in the Earth's immediate vicinity, over relatively short spans of time, are being considered, it is permissible to consider the object's path as a Keplerian Orbit. The latter is completely specified by six independent quantities, e.g., six orbital elements, six angular sightings of the position, three position and three velocity components at any time, etc.

In this problem, the tracking instrument supplies the range and angular data. Thus, two such observations at different times are sufficient to specify the orbit. However, since the n -body Trajectory Program requires position and velocity components as inputs, the above measurements must be made to yield velocity components at some time t as well.

From the previous section, two observations yield x , y , z at two different times.

Following Laplace, the position vector $\vec{r}$ at time t is expressed as:

$$\vec{r}(t) = f \vec{r}_0 + g \dot{\vec{r}}_0 \quad (21)$$

Development of this result was discussed in Scientific Report No. 1, and is found in references (1) and (2).

In expression (21): $\vec{r}_0 = \vec{r} \left(t_0 \right)$, $\dot{\vec{r}}_0 = \dot{\vec{r}} \left(t_0 \right)$

$$f = 1 - \frac{1}{2} \mu \tau^2 + \frac{1}{2} \mu \sigma \tau^3 + \frac{\mu (3\omega - 2\mu - 15\sigma^2)}{24} \tau^4 - \frac{\mu \sigma (3\omega - 2\mu - 7\sigma^2)}{8} \tau^5$$

$$+ \frac{\mu}{720} \left[(630\omega - 420\mu - 945\sigma^2) \sigma^2 - (22\mu^2 - 66\mu\omega + 45\omega^2) \right] \tau^6 + \dots$$

(22)

$$g = \tau - \frac{1}{6} \mu \tau^3 + \frac{\mu \sigma}{4} \tau^4 + \frac{\mu (9\omega - 8\mu - 45\sigma^2)}{120} \tau^5 - \frac{\mu \sigma (6\omega - 5\mu - 14\sigma^2)}{24} \tau^6 + \dots$$

(23)

where

$$\mu = \frac{1}{r_0^3}; \quad \sigma = \frac{\vec{r}_0 \cdot \dot{\vec{r}}_0}{r_0^2}; \quad \omega = \frac{\dot{\vec{r}}_0 \cdot \dot{\vec{r}}_0}{r_0^2}$$

and

$$\tau = k (t - t_0)$$

Depending on the object, it is convenient to express distances in astronomical units and time in 58.13244 days, or distance in Earth radii and time in units of 806.9275 seconds.

The procedure used was outlined in Section II and repetition is unnecessary.

3. Computer Program

A step-by-step outline of the computer solution is given below. Note that, in the final computer program, azimuth and elevation are not directly used but are first transformed to right ascension and declination referred to a suitable equinox.

I. Input data:

$$\rho_o, X_o, Y_o, Z_o, A_o, E_o, t_o$$

$$\rho_1, X_1, Y_1, Z_1, A_1, E_1, t_1$$

$\alpha_o, \delta_o, \alpha_1, \delta_1$ are obtained from A_o, E_o, A_1, E_1

II. Compute

$$x_o = X_o + \rho_o \cos \delta_o \cos \alpha_o$$

$$x_1 = X_1 + \rho_1 \cos \delta_1 \cos \alpha_1$$

$$y_o = Y_o + \rho_o \cos \delta_o \sin \alpha_o$$

$$y_1 = Y_1 + \rho_1 \cos \delta_1 \sin \alpha_1$$

$$z_o = Z_o + \rho_o \sin \delta_o$$

$$z_1 = Z_1 + \rho_1 \sin \delta_1$$

III. Compute

$$r_o = (x_o^2 + y_o^2 + z_o^2)^{1/2}$$

$$\mu = \frac{1}{r_o^3}$$

IV. Compute

$$f = 1 - \frac{1}{2} \mu \tau^2$$

$$g = \tau - \frac{1}{6} \mu \tau^3$$

V. Compute

$$\dot{x}_0 = \frac{1}{g} (x - fx_0)$$

$$\dot{y}_0 = \frac{1}{g} (y - fy_0)$$

$$\dot{z}_0 = \frac{1}{g} (z - fz_0)$$

VI. Compute

$$\dot{\vec{r}}_0 \cdot \dot{\vec{r}}_0 = \dot{x}_0^2 + \dot{y}_0^2 + \dot{z}_0^2$$

$$\vec{r}_0 \cdot \dot{\vec{r}}_0 = x_0 \dot{x}_0 + y_0 \dot{y}_0 + z_0 \dot{z}_0$$

$$\sigma = \frac{\dot{\vec{r}}_0 \cdot \vec{r}_0}{r_0^2} ; \quad \omega = \frac{\dot{\vec{r}}_0 \cdot \dot{\vec{r}}_0}{r_0^2}$$

VII. Compute f and g using complete equations (22) and (23).

VIII. Return to Step V. and compute new $\dot{x}_0$, $\dot{y}_0$, $\dot{z}_0$. Repeat the entire procedure.

IX. Compare velocity components computed at each step with the corresponding velocity components obtained in the previous step.

When differences reach a value of less than $\epsilon = 4 \times 10^{-8}$ in appropriate units, the iteration procedure is terminated.

4. Evaluation of the Method

The evaluation of the computational method is summarized in Figure 4 and 5.

A time interval between observations of about one minute, it appears, results in the minimum error. When smaller intervals are used, round off errors become significant. For larger time intervals the f and g series become inaccurate. Figure 4 indicates that for a time interval between observations of five minutes the percentage velocity error for the lunar trajectory is .05 per cent corresponding to 12 mph error. Increasing the time interval to ten minutes, yields a velocity error of .5 per cent, or 120 mph. These results indicate the initial velocity may be precisely established, using a reasonable number of terms in the f and g series. Because of its large eccentricity, the lunar trajectory is a relatively worse case.

Figure 5 shows that, for a five minute interval, seven iterations are required to reach the solution for the lunar orbit. If the interval is increased to ten minutes, the velocity is established after eleven iterations.

Precision achievable by this technique is more than sufficient to establish preliminary initial conditions.

C. DETERMINATION OF THE INITIAL CONDITIONS FROM SIX RADAR RANGE MEASUREMENTS

This study's third tracking scheme attempted to utilize only range

measurements. Underlying ideas, and the derivation of appropriate expressions, can be found in Section II. For present purposes it is sufficient to recall that the method involves a solution of six equations, linear in unknowns x_0 , y_0 , z_0 , $\dot{x}_0$, $\dot{y}_0$, $\dot{z}_0$ in which, at least initially, the coefficients are only approximations to the true ones. Furthermore, if the time intervals between observations are equal, the coefficients' numerical values are not far from unity. If the intervals are made deliberately unequal, some coefficients will be considerably larger or smaller than unity, but in a manner that they are basically multiples of each other.

The latter observations have the following unfortunate consequence.

There are many methods available for solving simultaneous linear equations. However, all methods, with one exception, involve many successive subtractions of quantities of nearly the same order of magnitude. This leads to the loss of significant figures which often makes the results meaningless.

Though the equations of the problem fell in the above category, an attempt was made to solve them by (a) inverting the matrix and (b) by successive elimination of the unknowns where division by the leading coefficient was employed. This was done for equally and unequally spaced time intervals.

In either case, a point in the solution was reached where the original seven significant figures were reduced to one or two. Use of double precision in the computer arithmetic was to no avail. Generally, after the first try the values of x_0 , y_0 , z_0 , $\dot{x}_0$, $\dot{y}_0$, $\dot{z}_0$ were larger by one or two orders of magnitude than those desired. No iteration was carried out because the structure of the equations indicated futility of further computation.

The one exceptional method hinted at above was the solution of simultaneous equations by the iteration method described in Reference (1).


This method is free from the loss of significant figures due to the subtractions of nearly equal quantities. Unfortunately the iterative process converges only when each equation contains, compared to others, a large coefficient, and this coefficient must be associated with different unknowns in each equation. This implies that the dominant coefficients are arranged along the principal diagonal of the coefficient matrix. Generally, such an arrangement cannot be expected in the physical problem considered. A theorem given in Reference (3) states that, for the method to be applicable in each equation of the system, the absolute value of the largest coefficient must be greater than the sum of the absolute values of all the remaining coefficients in that equation.

Simulated problems constructed for testing the over-all method do not satisfy the above condition. Finally, it was found that the result of the first iteration is quite sensitive to the initial estimate of r_0 . It appears that the problem is poorly conditioned. This difficulty cannot be attributed to unfavorable geometrical arrangement of the orbit and the observer, because in all other methods the selected example gave excellent agreement with the known values of $x_0, y_0, z_0, \dot{x}_0, \dot{y}_0, \dot{z}_0$. The basic problem is apparently contained in the fact that the coefficients of the starting system of equations are not really known, and the approximations used for these are insufficient.

The conclusion drawn is that the determination of the vehicle's position and velocity components, from range measurements at a single station, is not practical as formulated in the previous section.

Before abandoning this investigation an attempt was made to reformulate the problem. In the previous scheme, the solution starts with a guess of r_0 . The difficulty of finding a reasonably close initial value of geocentric distance is obvious. However, instead of starting with r_0 , the angle between some reference (vertical), and the direction of the antenna to the body at some time t , could be estimated.

The geometry is then:



Using ϕ which is now supposed estimated, r is computed from

$$r^2 = R^2 + \rho^2 - 2 \rho R \cos (\pi - \phi)$$

$$r^2 = R^2 + \rho^2 + 2 \rho R \cos \phi$$

It is felt that ϕ can be estimated better than r . If this is allowed, it also follows that the right ascension and declination α, δ can be estimated. This in turn leads to values of topocentric coordinates ξ, η, ζ and then to geocentric position components x, y, z . The above follows from the well known relations

$$\xi = \rho \cos \delta \cos \alpha = x - X \quad (24)$$

$$\eta = \rho \cos \delta \sin \alpha = y - Y \quad (25)$$

$$\zeta = \rho \sin \delta = z - Z \quad (26)$$

Furthermore:

$$r = \sqrt{x^2 + y^2 + z^2} \quad (27)$$

Finally since ϕ is supposed known and thereby r , angle β can be computed from

$$r R \cos \beta = x X + y Y + z Z \quad (28)$$

Note in the above equations that the unknown quantities are α , δ , x , y , and z .

These equations can now be used to obtain initial estimates of these parameters.

Thus, from (27):

$$x = \left(r^2 - y^2 - z^2 \right)^{1/2}$$

and using in (1), (2), (3) and (5):

$$\rho \cos \delta \cos \alpha = \sqrt{r^2 - y^2 - z^2} - X \quad (24')$$

$$\rho \cos \delta \sin \alpha = y - Y \quad (25')$$

$$\rho \sin \delta = z - Z \quad (26')$$

$$r R \cos \beta = \sqrt{r^2 - y^2 - z^2} X + y Y + z Z \quad (28')$$

Employing (25') and (26') in (24') and (28') one obtains

$$\rho \cos \alpha \cos \delta = \sqrt{r^2 - (\rho \cos \delta \sin \alpha + Y)^2 - (\rho \sin \delta + Z)^2} \quad (24'')$$

$$r R \cos \beta = X \sqrt{r^2 - (\rho \cos \delta \sin \alpha + Y)^2 - (\rho \sin \delta + Z)^2} \\ + (\rho \cos \delta \sin \alpha + Y) Y + (\rho \sin \delta + Z) Z \quad (28'')$$

Consider equation (24''). Following a lengthy algebraic reduction, this equation can be written as:

$$A_1 \cos^2 \delta + B_1 \cos \delta + C_1 = 0$$

where

$$\begin{aligned} A_1 &= [X \cos \alpha + Y \sin \alpha]^2 + Z^2 \\ B_1 &= 2 [X \cos \alpha + Y \sin \alpha] \left[\frac{R^2 + \rho^2 - r^2}{2 \rho} \right] \\ C_1 &= \left[\frac{R^2 + \rho^2 - r^2}{2 \rho} \right]^2 - Z^2 \end{aligned}$$

Similarly, equation (28'') can be reduced to

$$A \sin^2 \alpha + B \sin \alpha + C = 0$$

where

$$\begin{aligned} A &= \rho^2 (X^2 + Y^2) \cos^2 \delta \\ B &= 2 \rho Y \cos \delta \left[(X^2 + Y^2) - r R \cos \beta + Z (\rho \sin \delta + Z) \right] \\ C &= \rho \sin \delta + z \left[(\rho \sin \delta + Z)(X^2 + Y^2) - 2 r R Z \cos \beta + 2 Y^2 Z \right] \\ &\quad + r^2 R^2 \cos^2 \beta + Y^2 (X^2 + Y^2) - 2 r R Y^2 \cos \beta - X^2 r^2 \end{aligned}$$

Note that A_1 , B_1 , C_1 do not depend on δ , and A , B , C do not depend on α . Equations (24'') and (28'') are decoupled as far as α and δ are concerned. The two angular coordinates can be computed by successive approximations as follows. Assume, for instance, a value of α in (24'') and compute δ . Using this

δ in equation (28'') compute α . In principle, the assumed and computed values of α must be identical. Since the first try will not result in an identity, the value of α assumed in (24'') must be modified until α assumed $= \alpha$ computed is reduced to a small quantity consistent with the desired precision.

The fact that equations (24'') and (28'') yield a multiplicity of roots will be ignored, and the proper values of α and δ will be assumed to have been found. This being the case, equations (24), (25), and (26) yield the corresponding values of ξ , η , ζ or x , y , z . Equations (24), (25), (26), and (28) can also serve as a partial control because the trigonometric functions involved must numerically be less than unity. If this is not the case, the value of r could be modified and the whole computation repeated. Assuming that reasonable values of x_o , y_o , z_o have been obtained, the procedure would be as follows. Using x_o , y_o , z_o obtained above in equation (17), Section II, namely,

$$a_{n1} r_o^2 + a_{n2} x_o + a_{n3} y_o + a_{n4} z_o + a_{n5} \dot{x}_o + a_{n6} \dot{y}_o + a_{n7} \dot{z}_o = C_n \quad (29)$$

$$n = 1, 2, 3 \dots 6$$

a set of simultaneous equations in $\dot{x}_o$, $\dot{y}_o$, $\dot{z}_o$ as unknowns is obtained. Thus, using two additional measurements of ρ , $\dot{x}_o$, $\dot{y}_o$, $\dot{z}_o$ can be computed. This procedure may result in better values of the velocity components since subtractive processes have been considerably reduced. Should this step result in reasonable values of $\dot{x}_o$, $\dot{y}_o$, and $\dot{z}_o$, equation (29) could be used in its entirety, and x_o , y_o , z_o could be considered as unknowns wherever they occur explicitly. The f and g series would be computed using x_o , y_o , z_o , $\dot{x}_o$, $\dot{y}_o$, $\dot{z}_o$ obtained in the previous step.

The iteration, as described in Section II would be attempted only if the above scheme showed a reasonable success.

No computations based on this method have been attempted.

IV. AUXILIARY COMPUTATIONS AND CONVERSION SUB-ROUTINES

In the description of the n-body Trajectory Program, Interim Report #1, July 1960, it has been pointed out that the coordinate system used is referenced to the mean equinox of 1950.0. Thus, all basic information, i.e., planetary positions stored on magnetic tapes, is expressed in this frame of reference. Consequently, the components of the position and velocity vectors, which serve as the input to the trajectory program, must be consistent with the accepted coordinate system.

The initial conditions for the n-body Trajectory Program are usually derived from some tracking subroutine. Previously, it had been tacitly assumed that the observed quantities are given in the proper frame of reference, making the output usable in the trajectory program. In practice this assumption is not warranted. Observations will usually yield quantities referenced to the coordinate system, differing from 1950.0 by at least the precession effect. If these observations (measured with respect to the equinox of date) are used in a particular tracking subroutine, the resulting output will not be usable by the trajectory program. Thus, the output of the tracking computation, and the input to the n-body subroutine, must be matched by an appropriate transformation.

The purpose of this section is to describe such transformations and auxiliary computations provided with the n-body Trajectory Program.

Before discussing various detailed schemes, a number of general comments are necessary.

A. BASIC REQUIREMENTS

(a) Distances

Two systems of units are provided for all distance measurements. These are astronomical units (A. U.) and the equatorial Earth radii. The reason for this choice is that, in general, in all computations of the type considered in this report, it is convenient to keep magnitudes of distances near unity. Thus, for vehicles moving in the close vicinity of the Earth, the above condition obtains if the distances are expressed in terms of the Earth radius as a unit. Conversely the mean Earth-Sun distance is suitable in computations of the motion of probes to Venus, Mars, and other points in the solar system.

Both units have been provided to avoid limiting the program to lunar vehicles.

Thus, prior to computations, range measurements should first be converted to either astronomical units or Earth radii.

(b) Angles

All angular inputs employed by the conversion routines must be expressed in degrees and decimals of a degree. This particularly applies to right ascension α which is often expressed in time measure. Note the conversion factor is 15° /hour, $15'$ /minute, and $15''$ /second.

(c) Dates and Times

The dates and times of observation employed by the transformation subroutines occur in two forms.

- (1) The date and time of observation shall be expressed in terms of universal time, in days and decimals of a day of

the same month, for all observations, even if this entails introducing a fictitious number of days in a month.

Example: Suppose that two measurements were made:

1935 Aug. 30.0006 UT and
1935 Sept. 2.9067 UT

They must then be expressed as

1935 Aug. 30.0006 UT and
1935 Aug. 33.9067 UT

- (2) The date and time of observation to be also expressed in Julian Days (JD) and decimals of a Julian Day. Note that there are 365.25 days in a Julian year. An extensive table of Julian Day numbers is provided in Appendix A. Also, Julian Day numbers are tabulated in yearly issues of the Nautical Almanac and American Ephemeris.

Example: Days and times considered under (c) (1) expressed in JD are given by

JD 2428044.5006
JD 2428048.4067

(d) Geographic Coordinates of the Observation Site

In computations of the rectangular site coordinates, geographic coordinates of the tracking station are required. These shall be expressed as follows:

Geographic longitude of the site λ in degrees. The sign convention adopted is:

$\lambda > 0$ if East of Greenwich Meridian

$\lambda < 0$ if West of Greenwich Meridian

Geographic latitude of the site ϕ is taken as positive if North of the equator, and negative if South of the equator.

The altitude of the site above sea level $|h|$ is expressed in astronomical units or Earth equatorial radii.

Specific subroutines available in the program are considered below:

B. COMPUTATION OF RECTANGULAR GEOCENTRIC SITE COORDINATES

The geocentric components of the observer's position on the Earth's surface are required by all tracking subroutines. These components can be computed with respect to equinox of date, and then transformed into the coordinate system of 1950.0, or computed directly with respect to equinox of 1950.0. In both cases, the procedure programmed is as follows:

1. Reduction to Geocentric Latitude

For reasons which will not be discussed here (see Reference 4), it is necessary to reduce the observer's geodetic latitude to a geocentric one prior to computing the components of the observer's position vector. The appropriate expression utilized in the program is

$$\phi' = \phi + \frac{1}{3600} \left[-695''.6635 \sin 2\phi + 1''.1731 \sin 4\phi - 0''.0026 \sin 6\phi \right]$$

where ϕ' is the geocentric latitude.

2. Magnitude of the Geocentric Radius Vector of the Site

The geocentric radius vector R is determined from

$$R = h + a (.998320047 + .001683494 \cos 2\phi - .000003549 \cos 4\phi + .000000008 \cos 6\phi)$$

In the above, a = equatorial radius of the Earth and h is the altitude of the site above sea level. Note that R may be expressed either in astronomical units or equatorial Earth radii.

3. Computation of Sidereal Time

Since the Earth rotates about its axis, the components of R will be functions of time. The time involved is the "star time," generally called the sidereal time - a measure of the angle between the observer's meridian and the vernal equinox.

In the computer program, sidereal time is computed as follows:

(a) First Greenwich Mean Sidereal Time (GMST) at O^h Universal Time as measured by the mean equinox of date is given by

$$\text{GMST} = \frac{1}{3600} \left[23925^s.836 + 8,640,184^s.542 \frac{\text{JD} - 2415020.0}{36525} + 0^s.0929 \left(\frac{\text{JD} - 2415020.0}{36525} \right)^2 \right]$$

Only that part of the resulting value is taken which is less than 24 hours.

In the above, JD is the Julian date at midnight of the beginning of the day at which the GMST is desired, and 2415020.0 corresponds to the noon of January 0, 1900. Note that GMST is given in hours.

(b) The Local Sidereal Time is computed from

$$\text{LST} = \left\{ \text{GMST} + 24(\text{UT}) + \frac{9^s.8565}{3600} \left[24(\text{UT}) \right] + \frac{\lambda}{15} \right\} 15$$

in degrees

In the above, UT = universal time expressed in decimals of a day.

GMST computed in (a) differs from that tabulated in the Almanac by nutation terms.

4. Rectangular Components of the Observer

Once LST has been computed, the observer's position vector can be resolved in the coordinate system with respect to which LST is given.

Thus

$$X = R \cos \phi' \cos (\text{LST})$$

$$Y = R \cos \phi' \sin (\text{LST})$$

$$Z = R \sin \phi'$$

with respect to the mean equinox of date.

Note: If a close Earth satellite is used, X, Y, Z determine the observer's position with respect to the center of force. However, for the deep space probes, the center of force will most likely reside in the Sun. In this case, designate by $X_{\odot}$, $Y_{\odot}$, $Z_{\odot}$, the components of the Sun's position vector. These components are tabulated in the Almanacs. Quantities X, Y, Z, computed above are now small corrections for the parallax since observations are made from the surface of the Earth. The Sun's coordinates, with respect to the observation site, are given by

$$X'' = X_{\odot} + X$$

$$Y'' = Y_{\odot} + Y$$

$$Z'' = Z_{\odot} + Z$$

In astronomical practice, it must be mentioned, the Sun-to-Earth direction is taken positive. However, the Sun's coordinates tabulated in the

Almanacs are measured with respect to the Earth. This convention is not observed in this report. It is always assumed that the inertial origin rests at the center of force and all distances are measured positive from this center. Consequently, if tabulated values of the Sun's coordinates are used in formulas of this report, always reverse the algebraic sign of the tabulated value. If all computations are assumed to be carried out in the coordinate system of 1950.0, X, Y, and Z of date must be converted to the standard reference system.

C. REDUCTION OF RECTANGULAR COORDINATES X, Y, Z OF DATE TO EQUINOX OF 1950.0

Designate the rectangular components of a vector given with respect to equinox of date by X_D , Y_D , Z_D . The conversion of these to the coordinate system, fixed by the equinox of date, is effected by the following transformation:

$$\mathbf{X}_{1950} = \mathbf{A} \mathbf{X}_D$$

In this expression

$$\mathbf{X}_{1950} = \begin{pmatrix} X_{1950} \\ Y_{1950} \\ Z_{1950} \end{pmatrix} \quad \mathbf{X}_D = \begin{pmatrix} X_D \\ Y_D \\ Z_D \end{pmatrix}$$

$$\mathbf{A} = \begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{pmatrix}$$

where the elements of matrix a_{ij} are given by the following formulas

$$a_{11} = 1.00000000 - .00029696 (\Delta t)^2 - .00000014 (\Delta t)^3$$

$$a_{12} = -.02234941 \Delta t - .00000676 (\Delta t)^2 + .00000221 (\Delta t)^3$$

$$a_{13} = -.00971691 \Delta t + .00000206 (\Delta t)^2 + .00000098 (\Delta t)^3$$

$$a_{21} = .02234941 \Delta t + .00000676 (\Delta t)^2 - .00000221 (\Delta t)^3$$

$$a_{22} = 1.00000000 - .00024975 (\Delta t)^2 - .00000015 (\Delta t)^3$$

$$a_{23} = .00010858 (\Delta t)^2 - .00000003 (\Delta t)^3$$

$$a_{31} = .00971691 \Delta t - .00000206 (\Delta t)^2 - .00000098 (\Delta t)^3$$

$$a_{32} = -.00010858 (\Delta t)^2 - .00000003 (\Delta t)^3$$

$$a_{33} = 1.00000000 - .00004721 (\Delta t)^2 + .00000002 (\Delta t)^3$$

In the above expressions

$$\Delta t = \frac{2433281.5 - \text{JD}}{36525}$$

where JD 2433281.5 corresponds to the beginning of the Besselian year 1950 (namely 1950.0), and JD to the date and time at which X, Y, Z are given.

Thus, Δt is in effect a measure of Julian centuries taken from 1950.0.

Numerical constants in a_{ij} were taken from Reference 5.

D. REDUCTION OF (X, Y, Z) 1950.0 TO THOSE OF DATE

If matrix $A_{D \rightarrow 1950}$ is known, this transformation is effected by

$$X_D = A^{-1} X_{1950.0}$$

where A^{-1} is A reflected about the principal diagonal. However, it is simpler to recompute the transformation matrix. This is done simply by

inverting the sign in Δt . Thus, the new Δt becomes

$$\Delta t = \frac{JD - 2433281.5}{36525}$$

Using this in the series expressions for a_{ij} and interchanging subscripts 1950.0 and D the desired transformation is obtained.

Note: In the American Ephemeris and Nautical Almanac it is now customary to tabulate solar coordinates with respect to both the mean equinox of the beginning of a given year and the equinox of 1950.0. In older Almanacs, solar coordinates were tabulated only with respect to the mean equinox of the beginning of the year. Under the latter conditions in determining $X_{\odot}$, $Y_{\odot}$, $Z_{\odot}$ between equinoxes, JD will correspond to the beginning of the Besselian year of interest.

The solar coordinates at other than tabular points are obtained from published ephemerides by interpolation. There is no reason why the above reduction formulas could not be used for this purpose, provided $X_{\odot}$, $Y_{\odot}$, $Z_{\odot}$ are known for some date.

It is well known that the Sun is slightly ahead of the position given by theory from which the solar coordinates are computed. This discrepancy can be largely eliminated if the Sun's coordinates are interpolated for the time

$$t_{\text{Desired}} + 0^d .000282$$

It should be noted that the above transformations are valid for any vector and, consequently, equally applicable to transformations of the velocity components.

E. CONVERSION OF AZIMUTH AND ELEVATION TO RIGHT ASCENSION AND DECLINATION

Another important transformation is conversion of elevation-azimuth angular coordinates to right ascension and declination coordinates.

Conventional radars are not well adapted to equatorial mountings, and the angular output is of necessity given with respect to the local elevation-azimuth coordinate system.

Designate by	α - right ascension
	δ - declination
	E - elevation
	A - azimuth
	HA - hour angle

In the northern hemisphere, azimuth will always be measured from the north point clockwise through 360° .

The hour angle is measured West from the observer's meridian through 360° .

The right ascension is measured East from the first point of Aries through 360° . The declination is taken positive North of celestial equator and negative South of the latter.

Since computations of preliminary orbits from angular data are more convenient when the latter are given in the equatorial system, elevation and azimuth are converted by the following expressions.

1. Declination δ is computed from

$$\sin \delta = \sin \phi' \sin E + \cos \phi' \cos E \cos A$$

The algebraic sign of $\sin \delta$ gives the sign of δ .

2. The right ascension α is computed as follows:

First, the hour angle of the observed body is computed from

$$\sin HA = - \frac{\cos E \sin A}{\cos \delta}$$

$$\cos HA = \frac{\sin E \cos \phi' - \cos E \sin \phi' \cos A}{\cos \delta}$$

The above expressions determine both the hour angle and its quadrant.

The right ascension α of the observed object is determined from

$$\alpha = LST - HA$$

The result can be given in either time or angular measure. In this program α is always computed in degrees.

The Local Sidereal Time is taken from B, 3(b). Since the elevation and azimuth are measured with respect to the coordinate system as existing at the time of measurement, α and δ from the above expressions are referred to the equinox of date.

Often these quantities must be reduced to the standard equinox of 1950.0.

F. REDUCTION OF α AND δ FROM THE EQUINOX OF DATE TO THE REFERENCE EQUINOX

Let α and δ referred to the equinox of date be designated by α_D and δ_D . These are obtained by direct measurement or from computation D.

The reduction can be accomplished in two ways. One of these is described in Reference (4) p. 240. The other method is substantially simpler although it involves an iterative procedure.

Computation is arranged as follows:

Suppose that α_D and δ_D are given with respect to equinox of t_1 and values at t_2 are desired where $t_2 > t_1$.

1. Certain quantities m and n are computed for the middle of the interval involved. These are given by

$$m = \frac{1}{3600} \left[46''.09905 + 0''.0002790 \left(\frac{\text{JD} - 2433281.5}{365.25} \right) \right] \text{ degrees}$$

$$n = \frac{1}{3600} \left[20''.0426 - 0''.000085 \left(\frac{\text{JD} - 2433281.5}{365.25} \right) \right] \text{ degrees}$$

Note that $(\text{JD } 2433281.5)/365.25$ will correspond to $t = \frac{t_1 + t_2}{2}$

Using α_{t_1} and δ_{t_1} in expressions for the annual precession in right ascension and declination, results in

$$\frac{d\alpha}{dt} = m + n \sin \alpha_{t_1} \tan \delta_{t_1}$$

$$\frac{d\delta}{dt} = n \cos \alpha_{t_1}$$

The approximate values of α_{t_2} and δ_{t_2} are then given by

$$\alpha_{t_2} = \alpha_{t_1} + (t_2 - t_1) \frac{d\alpha}{dt}$$

$$\delta_{t_2} = \delta_{t_1} + (t_2 - t_1) \frac{d\delta}{dt}$$

The means between α_{t_2} , δ_{t_2} and α_{t_1} , δ_{t_1} are denoted by α' and δ'

2. Employing α' and δ' in

$$\left(\frac{d\alpha}{dt} \right)' = m + n \sin \alpha' \tan \delta'$$

$$\left(\frac{d\delta}{dt} \right)' = n \cos \alpha'$$

a better approximation is obtained for the effects of annual precession. Thus, more nearly correct values of α_{t_2} and δ_{t_2} are

given by

$$\alpha'_{t_2} = \alpha_{t_1} + (t_2 - t_1) \left(\frac{d\alpha}{dt} \right)'$$

$$\delta'_{t_2} = \delta_{t_1} + (t_2 - t_1) \left(\frac{d\delta}{dt} \right)'$$

This procedure can be repeated as many times as desired.

Generally, even when $(t_2 - t_1)$ is as large as 50 years, two iterations lead to an error of less than one second of time in α , and less than a second of arc in δ . This is entirely sufficient for preliminary computations.

If the epoch $t_2 < t_1$ the procedure is the same as above.

Note, however, that the approximations are given by

$$\alpha_{t_1} = \alpha_{t_2} - (t_1 - t_2) \frac{d\alpha}{dt}$$

$$\delta_{t_1} = \delta_{t_2} - (t_1 - t_2) \frac{d\delta}{dt}$$

Thus, depending on the interval $|t_2 - t_1|$ the reduction can proceed from any equinox to any other one.

G. EPHEMERIS COMPUTATION

The purpose of any tracking and orbit computation program is, not only to determine the orbit, but to predict the future positions of the body. These data, the so-called ephemeris, are needed to enable the observer to re-acquire the body if the tracking is intermittent.

Ephemeris information can best be given as angular data, and possibly range data with respect to a coordinate system fixed at the observer's site. The predicted positions can be given with respect to the equinox of date or the equinox of 1950.0.

The computational procedure is as follows:

1. The n-body program yields values of the vehicle's position x, y, z at a time t with respect to equinox of 1950.0. The units of distance can be astronomical units, Earth equatorial radii, or kilometers. Denote these components by $X_{t_i 1950}, Y_{t_i 1950}, Z_{t_i 1950}$

2. At assigned universal times t_i , rectangular coordinates of site X_{t_i} , Y_{t_i} , Z_{t_i} are computed by methods of section B. If the Sun's coordinates are desired, use the appropriate Almanac.

3. Reduce these to $X_{t_i 1950}$, $Y_{t_i 1950}$, $Z_{t_i 1950}$

4. The topocentric range ρ expressed in appropriate units is computed from

$$\rho_{t_i} = \left[\left(x_{t_i 1950} - X_{t_i 1950} \right)^2 + \left(y_{t_i 1950} - Y_{t_i 1950} \right)^2 + \left(z_{t_i 1950} - Z_{t_i 1950} \right)^2 \right]^{1/2}$$

5. The declination $\delta_{t_i 1950}$ at t_i is computed from

$$\sin \delta_{t_i 1950} = \frac{z_{t_i 1950} - Z_{t_i 1950}}{\rho_{t_i}}$$

The algebraic sign of $z_{t_i 1950} - Z_{t_i 1950}$ determines the sign of δ .

The right ascension $a_{t_i 1950}$ is determined from expressions

$$\cos a_{t_i 1950} = \frac{x_{t_i 1950} - X_{t_i 1950}}{\rho_{t_i} \cos \delta_{t_i 1950}}$$

$$\sin a_{t_i 1950} = \frac{y_{t_i 1950} - Y_{t_i 1950}}{\rho_{t_i} \cos \delta_{t_i 1950}}$$

6. If desired, $a_{t_i 1950}$ and $\delta_{t_i 1950}$ are reduced to the equinox of date by method outlined in section F.

Thus, computations indicated in 1 through 6 result in

$$\rho_{t_i}, \quad a_{t_i \text{ 1950}}, \quad \delta_{t_i \text{ 1950}} \quad \text{or} \quad a_{t_i} \quad \text{and} \quad \delta_{t_i}$$

If the observing instrument is a radar, more appropriate angular quantities are azimuth and elevation. These are obtained as follows.

7. Compute the Local Sidereal Time (LST) as measured by the equinox of date or equinox of 1950.0 using methods of Section B. 3.

8. Using $a_{t_i \text{ 1950}}$ or a_{t_i} from G. 6 the Local Hour Angle (LHA) of the body is computed from

$$(\text{LHA})_{t_i} = (\text{LST})_{t_i} - a_{t_i}$$

It must be observed that LST and a used in the above must be referred to the same equinox.

9. Elevation at time t_i is obtained from

$$\sin E_{t_i} = \sin \phi' \sin \delta_{t_i} + \cos \phi' \cos \delta_{t_i} \cos (\text{LHA})_{t_i}$$

where ϕ' has been defined in B.1. The algebraic sign of $\sin E_{t_i}$ determines the sign of E_{t_i} .

10. Azimuth is determined uniquely from expressions

$$\sin A_{t_i} = \frac{-\sin (\text{LHA})_{t_i} \cos \delta_{t_i}}{\cos E_{t_i}}$$

and

$$\cos A_{t_i} = \frac{\sin \delta_{t_i} - \sin \phi' \sin E_{t_i}}{\cos \phi' \cos E_{t_i}}$$

A careful distinction must be made between $A_{t_i 1950.0}$, $E_{t_i 1950.0}$ and A_{t_i} , E_{t_i} . Indirectly, these values differ by effects of precession.

As a result of computations 6 through 10 azimuth and elevation are obtained referred to the horizon plane and zenith of date or that of 1950.0.

All computations discussed above are provided as separate sub-routines with the main n-body Trajectory Program. An attempt has been made to make these subroutines as independent as possible. In some cases, however, total separation is not practical. This is particularly true in converting α , δ to A , E . This subroutine utilizes the hour angle which in turn requires Local Sidereal Time. However, the computation of LST is tied up with the computation of the observer's coordinates on the Earth's surface. Thus, in cases where LST alone is required, some superfluous information may be produced.

Occasionally, in tracking routines, it is required to find the sidereal time measured by equinox at time t_2 if the sidereal time measured by equinox t_1 is known. This reduction can be accomplished by utilizing methods of B. 3(a), (b), but for a few dates the use of the 7090 subroutines may not be warranted. Under these conditions, a simpler procedure is available and, although it is not a part of this program, it will be described below.

H. REDUCTION OF SIDEREAL TIME REGULATED BY A MOVING EQUINOX TO SIDEREAL TIME REGULATED BY A STATIONARY EQUINOX

The relation between the sidereal time regulated by a stationary equinox and the mean solar time is given by

$$d \theta_s = 1.002737810 dt$$

The constant of proportionality is the ratio between the mean solar day and sidereal day. Its exact value varies depending upon the author. However, for most purposes the value given above is sufficiently accurate.

Integrating the above obtains

$$\theta_s = \theta_o + 1.002737810 (t - t_o) \quad (30)$$

where θ_o is the constant of integration. The sidereal time θ_s can be obtained from the Almanac or the formula given in Section B.

$$\text{GMST at } 0^h \text{ UT} = \frac{1}{3600} \left[23925^s.836 + 8640184^s.542 \Delta t + 0^s.0929 (\Delta t)^2 \right]$$

$$\text{where } \Delta t = \frac{\text{JD} - 2415020.0}{36525}$$

$$\text{and } \text{JD} = t_o$$

The Greenwich MST at any other universal time is then given by equation (1). It must be carefully noted that θ_s computed by (1) is measured by the stationary equinox of t_o .

To correct this time to GMST, regulated by the moving equinox, recall that the general precession of the first point of Aries amounts to $50''.2675/\text{year}$ as of 1950.0. Since the cosine of obliquity of the ecliptic for 1950.0 is $\cos E_{1950} = .91743695$, it follows that along a stationary equator precession is given by

$$\begin{aligned} 50''.2675 \cos \epsilon_{1950} &= 46''.117/\text{year} = 3''.074/\text{year} = \\ &= 0''.008417/\text{day} = 0^d.00000009742/\text{day}. \end{aligned}$$

In t years the equinox will precess along the equator by an amount

$$\Delta \Theta_s = 3''.0744841 t.$$

Sidereal time measured by the moving equinox is then given by

$$\text{GMST} = \Theta_o + 1.002737810 (t - t_o) \pm \Delta \Theta_s.$$

Positive sign is taken if $t > t_o$, negative one when $t < t_o$. In general then

$$\text{GMST} = \Theta_o + 1.002737810(t - t_o) + 3''.0744841(t - t_o). \quad (31)$$

To make the method clearer a numerical example is given.

Example:

Suppose that GMST at 0^h UT on Sept. 3, 1935, is equal to $22^h 44^m 48^s.38$. Let us compute the sidereal time on Sept. 3, 1950.

From Equation (1) it follows that

$$\begin{aligned} \text{GMST}_{1950} &= 22^h 44^m 48^s.38 + 1.002737810 (2433527.5 - 2428048.5) \\ &= 5494^d.9482431 \end{aligned}$$

Its fractional part gives

$$\text{GMST}_{1950} = 22^{\text{h}} 45^{\text{m}} 28^{\text{s}}.20$$

This is the GMST on Sept. 3, 1950, as measured by the stationary equinox of Sept. 3, 1935. However, to obtain GMST as measured by the equinox of Sept. 3, 1950, a correction for precession must be introduced. This correction is given by

$$\Delta \theta_s = 3^{\text{s}}.0744841 \times 15^{\text{y}}.0006845 = 46^{\text{s}}.12$$

Since the equinox of 1950 is in advance of equinox of 1935 by the above amount, there results

$$\text{GMST}_{\text{Sept. 3, 1950}} = 22^{\text{h}} 45^{\text{m}} 28^{\text{s}}.20 + 46^{\text{s}}.12 = 22^{\text{h}} 46^{\text{m}} 14^{\text{s}}.3$$

Converse Problem

Given equinox of Sept. 3, 1950, at which GMST at 0^h UT is 22^h 46^m 14^s.3, compute GMST on Sept. 3, 1935, as regulated by the stationary equinox of Sept. 3, 1950, and the moving equinox of Sept. 3, 1935.

$$\begin{aligned} \text{GMST on Sept. 3, 1935} &= 22^{\text{h}} 46^{\text{m}} 14^{\text{s}}.3 - .5494^{\text{d}}.0004610 \\ \text{measured by } \gamma \text{ 1950} & \end{aligned}$$

The fractional part of this number gives

$$\text{GMST} = .9483151 = 22^{\text{h}} 45^{\text{m}} 34^{\text{s}}.4$$

Since the equinox of Sept. 3, 1935, lags the equinox of Sept. 3, 1950 by an amount

$$\Delta \theta_s = 46^{\text{s}}.12$$

it follows

$$\text{GMST} = 22^{\text{h}} 44^{\text{m}} 48^{\text{s}}.30$$

as measured by the moving equinox of Sept. 3, 1935. It is also useful to note that $\Delta \Theta_s$ is the angle between the two equinoxes in question.

Thus, in equation (2) there exists a simple method of evaluating sidereal times as measured by any desired equinox, provided sidereal time is known at some instant of time.

The discussion of auxiliary subroutines will be concluded by giving several block diagrams of possible tracking computations involving situations frequently encountered in practice.

1. SCHEMATICS OF TYPICAL COMPUTATIONS

Problem 1

Consider a tracking station, whose geographic coordinates are ϕ' and λ that is capable of measuring angular positions of a close Earth satellite with respect to the geocentric equatorial coordinate system. The absolute minimum of information necessary to estimate the satellite's motion consists of α and δ measured at three different times. Assume α and δ are measured with respect to the equinox of date

The resulting computational scheme and the flow of information is shown in Figure 6. Its main features are as follows:

The first part of the computation can be carried out in two ways. The measured right ascension and declination, both with respect to equinox of date ($\alpha_{\text{MD}}, \delta_{\text{MD}}$), can be used directly in the three angle tracking routine to obtain a preliminary value of the vehicle position and velocity ($x_o, y_o, z_o, \dot{x}_o, \dot{y}_o, \dot{z}_o$) at some time t_o .

The n-body Trajectory Program cannot accept these values as initial conditions since they are referenced to the equinox of date. Thus x_0 , y_0 etc., must be converted to the epoch of 1950.0. Under these conditions the proper routing is obtained by placing S_1 at position 2, S_2 at 2.

Another way is to convert measured data to epoch of 1950.0. Under these conditions the output of the three-angle tracking routine is directly usable by the 7090 program. The proper connections are then $S_1(1)$, $S_2(1)$.

The output of the 7090 program is in the form of rectangular components of position and velocity of the vehicle at some future time t referenced to equinox of 1950.0.

Following this, two possibilities exist. One is to compute the predicted angular positions with respect to 1950.0. The second possibility is to compute all predicted positions with respect to the equinox of date. Figure 6 shows both alternatives.

The user can select the flow of computation as desired by rearranging the order of various subroutines.

However, it is strongly recommended that all computations be carried out in a coordinate system referenced to the equinox of 1950.0. Thus, all measured data as well as auxiliary quantities should be expressed in this frame of reference. This accomplishes two things. First, the method is in accord with the commonly accepted astronomical practice of referring data to a standard epoch. Secondly, comparison with computations of other investigators is possible without need for further transformations.

In some instances, of course, adherence to this recommendation may be awkward.

This is particularly true in the case of ephemerides prepared for radar stations in terms of elevation and azimuth.

Problem 2

Consider a situation which is in all respects identical with that of problem 1 with the exception that the measured angular data are expressed in terms of azimuth A and elevation E .

The block diagram of the computation is then arranged as in Figure 7.

From this figure it can be seen that problem 2 requires the addition of a subroutine converting measured azimuth and elevation to right ascension and declination of date.

The essential output of ephemeris computation in this problem consists of azimuth, elevation, and range ρ

Problem 3

A tracking situation is now considered in which an instrument, such as radar, measures range ρ and the associated angle which may be given as elevation and azimuth, or right ascension and declination.

Because a complete position vector is measured, it is merely necessary to compute velocity components at some time t which, in conjunction with the measured position components, can be used as initial conditions for the main program.

If the tracking instrument is equatorially mounted, the computation can be arranged as shown in Figure 8.

As in Problem 1, the first part of the computation can be carried out in the coordinate system of date, or that referenced to equinox 1950.0. In the first case, the measured A and E are first converted to α and δ of date. These are used to compute the components of the measured position vector at two different times from expressions

$$\xi = \rho \cos \delta \cos \alpha$$

$$\eta = \rho \cos \delta \sin \alpha$$

$$\zeta = \rho \sin \delta$$

These quantities used in

$$x = \xi + X$$

$$y = \eta + Y$$

$$z = \zeta + Z$$

yield the components of the geocentric position vector of the vehicle. These components are employed in the two-range vector iterative routine to produce the velocity components at one of the measured instants of time. Before using these in the n-body Trajectory Program, conversion to the equinox of 1950.0 must be effected. The computation then follows the same lines as in Problems 1 and 2.

Switches S_1 and S_2 are connected to positions 1 and 2 for the proper flow of information.

If the iteration routine is to produce $x_0, y_0, z_0, \dot{x}_0, \dot{y}_0, \dot{z}_0$ referenced to epoch 1950.0, S_1 is connected to position 2 and S_2 to position 1.

Problem 4

Though similar to Problem 3, this situation's tracking instrument is assumed to be mounted equatorially. The measured data therefore

consists of range ρ and the associated right ascension α and declination δ

The flow of information is very similar to that found in Figure 6 and shown in Figure 9.

Positions of switches S_1 and S_2 for proper flow of information are either $S_1(1)$ and $S_2(1)$ or $S_1(2)$ and $S_2(2)$, depending upon the referencing of the angular data to the equinox of date or 1950.0.

Diagrams similar to those given in Figures 6, 7, 8, and 9 can be constructed for any tracking subroutine. From these diagrams it is apparent that a substantial number of blocks contained in the conversion subroutines disappear if computations are consistently carried out in coordinates referenced to some standard equinox, e. g., 1950.0.

No block diagram is given for the case of 6 ranges. Operation of this routine in its present formulation was found unreliable.

Appendix B of this report consist of Operational Directories and FORTRAN Listings of programs discussed above, as well sample check problems for each subroutine.

V. ERROR ANALYSIS OF HYPERBOLIC LUNAR IMPACT TRAJECTORIES

A. INTRODUCTION

As a part of demonstrating the capabilities of the Lunar Trajectory Computer Program described earlier in this report a study was performed of tolerances in initial conditions involved in lunar flight impacting the Moon's surface.

For obvious reasons it was found impractical to consider all possible impact trajectories covering the velocity range from elliptical to hyperbolic ones. Likewise, there was no attempt to arrange trajectories by firing locations and dates. As a consequence of these considerations, it was decided to consider only trajectories of classes IS^{a+} or IS^{a-} in the sense of Egorov [10]. These classes of trajectories refer to impacts occurring on the ascending branches of trajectories. This in turn implies that the velocity with respect to the Earth is in the hyperbolic range. The actual value of the initial velocity is, in principle, immaterial for purposes of this demonstration. However, in general, higher velocity trajectories impose tighter tolerances on orientations of the initial position and velocity vectors.

The general character of this study can be summarized as follows:

- (a) A nominal hyperbolic trajectory is chosen.
- (b) It is a three dimensional trajectory. There are no restrictions commonly invoked in assuming that the vehicle moves in the Earth-Moon plane.
- (c) The vehicle moves in the field of the Sun, the Earth, and the Moon.
- (d) Three dates are considered. These correspond to the following phases of the Moon.

- | | |
|-------------------|-----------------|
| (1) First Quarter | (Nov. 7, 1959) |
| (2) Full Moon | (Nov. 15, 1959) |
| (3) Last Quarter | (Nov. 23, 1959) |

This arrangement of the study may at least qualitatively reveal effects of the changing geometrical configuration of the three main bodies.

B. NOMINAL TRAJECTORIES

Nominal trajectories for each phase of the moon at the above dates have been established empirically. An essential requirement that has been imposed on these trajectories is that the hit must occur at the center of the apparent disc of the Moon. Its angular coordinates as seen from the Earth have been taken from the Nautical Almanac.

The initial conditions for the differential equations of motion were determined experimentally in units of A. U. and A. U. /hour. Upon converting we find the burnout altitude $h \approx 388.5$ st. miles and the burnout velocity $V = 7.177$ st. miles/sec. We have succeeded in holding these values constant for the three dates indicated. Thus, the only difference in initial conditions between the three sets of runs occurs in the orientation of vectors $\bar{\rho}$ and $\bar{v}$. (See Figure 10).

The following procedure was followed in arriving at a nominal trajectory. As a first step, conditions have been taken which result in an impact for an idealized problem based on either two body approximations or previous computer runs. These initial conditions are used in the Lunar program to obtain a trajectory. This trajectory in most cases strikes the Moon, but not at the desired place. Following this the initial velocity is changed by a small increment, and the computation is repeated. After three runs are obtained, an estimate is made of the differential correction required to effect the desired impact. This correction is usually not sufficient; consequently,

the procedure described above is repeated several times until the strike occurs at the desired place. It was found that in all three phases of the moon the center of the apparent disc of the Moon could be hit in about 9 tries. The resulting error between the computed and observed angular coordinates is in the neighborhood of 1 second of arc.

C. SENSITIVITY OF THE IMPACT POINT TO ERRORS IN INITIAL CONDITIONS

In the description of the Lunar Trajectory Program it was indicated that the program accepts the components of the position and velocity vector $(x_o, y_o, z_o; \dot{x}_o, \dot{y}_o, \dot{z}_o)$ at some time t_o as the basic input. There are several disadvantages in using these inputs in the error analysis considered here. First of all, most measuring instruments work in a spherical coordinate system which is more natural. Thus, the above components are connected with the spherical coordinates by the usual transformation,

$$\begin{aligned} x &= \rho \cos \theta \cos \phi & \dot{x} &= v \cos \alpha \cos \beta \\ y &= \rho \sin \theta \cos \phi & \dot{y} &= v \cos \alpha \sin \beta \\ z &= \rho \sin \phi & \dot{z} &= v \sin \alpha \end{aligned} \quad (32)$$

Thus the original inputs are replaced by $\theta, \phi, \alpha, \beta, \rho, v$ at time t_o . In the equations above, ρ is the magnitude of the initial position vector, θ is the right ascension, and ϕ is the declination. Similarly, v is the magnitude of the initial velocity vector, and α , and β are the two corresponding angular coordinates. The coordinate system employed here is an equatorial one in the astronomical sense. The above relations underscore another difficulty. So far as the computation of the trajectory is concerned $x, y, z; \dot{x}, \dot{y}, \dot{z}$ are certainly independent quantities. However, as soon as the measuring instrument enters the scene we find that these quantities are related. Thus it is, for instance, impossible to change ρ without changing x, y, z simultaneously. A similar situation exists with regard to the angular coordinates.

In view of the above it has been decided to employ spherical coordinates in our study of impact point errors. From the practical point of view this implies that any uncertainty in one of the spherical components must be converted to uncertainty in the rectangular components before it can be used in the computer program.

It has been found that in dealing with high speed trajectories (e. g. hyperbolic), 8-place accuracy in input is sufficient to furnish accurate, perturbed trajectories. However, in elliptical trajectories, where the magnitude of the velocity is decreased, it has become apparent that the lunar program demands accuracy of input to 10 or more places in order to furnish output of sufficient numerical accuracy. This would be especially true when mid-course guidance parameters are to be generated.

Response of the impact point to errors in one of the independent variables is evaluated by holding other variables fixed and varying the remaining one over a range of values. The maximum allowable error is that which results in a "skimming" impact on the Moon. The amount of miss due to an error in the corresponding variable can be conveniently measured in terms of the distance S on the surface of the Moon between the nominal and the perturbed impact points. This distance is in effect computed from six measured quantities ρ , θ , ϕ , v , α , and β , which are assumed to be mutually independent. Thus,

$$S = S(\rho, \theta, \phi, v, \alpha, \beta). \quad (33)$$

Since the deviation from the nominal impact point is measured, S is equivalent to an incremental miss, which to the first order of approximation can be expressed as

$$S = \Delta M = \left(\frac{\partial S}{\partial \rho}\right) \Delta \rho + \left(\frac{\partial S}{\partial \theta}\right) \Delta \theta + \left(\frac{\partial S}{\partial \phi}\right) \Delta \phi + \left(\frac{\partial S}{\partial v}\right) \Delta v + \left(\frac{\partial S}{\partial \alpha}\right) \Delta \alpha + \left(\frac{\partial S}{\partial \beta}\right) \Delta \beta, \quad (34)$$

where $\Delta \rho$, $\Delta \theta$, etc. represent errors in the corresponding quantities.

It is then evident that a successive independent variation of one of the variables will result in relations $S = S(\rho)$, $S = S(\theta)$, etc., each of which can yield partial derivatives in equation (34). These derivatives will be termed "error or sensitivity" coefficients. It is obvious that relation (34) assumes that for small deviations the miss can be written as a linear combination of errors. Just where a particular error ceases to be small cannot be evaluated until S is obtained.

Prior to evaluation of S the range of errors in a particular variable should be decided on in order to result in a skimming impact. There must be a sufficient number of points within this range in order to obtain S . One approach is to repeat the same procedure as used in establishing the nominal trajectory. The final approach adopted in this work will be described later in the report.

For the present, however, the description of the computation as employed here will be continued.

The early approach was to hold all variables but one constant at values corresponding to those of the nominal trajectory and to vary the remaining one by small increments. Values of x , y , z , $\dot{x}$, $\dot{y}$, $\dot{z}$ corresponding to these increments were computed from equation (32) by employing an LGP-30 Computer subroutine. The resulting quantities are then fed to the Lunar Trajectory Program. The output of this computation are the following quantities:

x, y, z and r	of the vehicle from the Earth
$\dot{x}, \dot{y}, \dot{z}$, and v	of the vehicle with respect to the Earth
x, y, z , and r	of the vehicle from the Moon
x, y, z , and r	of the vehicle from the Sun
t -	Corresponding time

The units employed are astronomical units, astronomical units per hour, and hours. The nominal radius of the Moon (assumed spherical) was taken as $R_M = 1.1625090 \times 10^{-5}$ AU. The initial values of $\theta, \phi, \alpha, \beta$ are obtained from equation (32).

As indicated earlier the run is terminated by prescribing either a maximum running time or a minimum distance from the Moon's center. In neither case, however, are the coordinates of the impact point obtained directly. These points must be obtained by interpolation from the computed points that give the position of the vehicle from the Moon as a function of time. The first step is to obtain the time of impact. For purposes of this investigation, use is made of Everett's interpolation formula in the form

$$f + f_0 + p \delta_{1/2} + E_2 \delta_0^2 + F_2 \delta_1^2. \quad (35)$$

Various quantities in this relation are obtained according to the following scheme:

t	f	$\delta_{n/2}$	δ_n^2	$\delta_{n/2}^2$
t_{-1}	f_{-1}	$\delta_{-1/2} = f_0 - f_{-1}$ $\delta_{1/2} = f_1 - f_0$ $\delta_{3/2} = f_2 - f_1$		$\delta_{1/2}^3 = \delta_1^2 - \delta_0^2$
t_0	f_0		$\delta_0^2 = \delta_{1/2}^2 - \delta_{-1/2}^2$	
t_1	f_1		$\delta_1^2 = \delta_{3/2}^2 - \delta_{1/2}^2$	
t_2	f_2			

In the above t is the independent variable (time) and f can stand for r, x, y, z or any other dependent variable. Constants E_2 and F_2 are given by

$$E_2 = \frac{p(p-1)(p-2)}{6}, \quad F_2 = \frac{p(p-1)(p+1)}{6}$$

where p is the interpolation fraction such that $0 < p < 1$.

In determining the selenocentric coordinates of the impact point equation (4) was employed in the form

$$R_M^2 = \sum_{i=x,y,z} (X_{i0} + p \delta_{i1/2} + E_2(p) \delta_{i0}^2 + F_2(p) \delta_{i1}^2)^2 \quad (36)$$

A subroutine was written for the LGP-30 computer to obtain p from equation (36) by successive approximations using Newton's Method.

The above computation simultaneously yields values of x, y, z of the impact point.

At the time this study was begun, and largely by coincidence, several runs were terminated with only one point recorded after impact occurred. As (35) indicates, Everett's interpolation formula required two values of the argument on either side of the derived value of the function. To compensate for the lack of a sufficient number of tabular points, two additional subprograms were written for the LGP-30. A Newtonian formula was employed based on five points and differences on a horizontal line. Also a six point Lagrangian interpolation formula was tested. Both methods, however, were inadequate because of their failure to provide the necessary degree of precision. An accurate value, arrived at by using Everett's scheme could only be approached to four places with Lagrange and Newton methods.

Using this comparison as the basis, machine operators have been advised to terminate a run on a more comfortable maximum time, or on impact plus three or more points.

The value of miss distance follows then directly from

$$\cos \theta = \frac{\vec{R}_M \cdot \vec{R}_M}{R_M^2} = \frac{X_N X_I + Y_N Y_I + Z_N Z_I}{R_M^2} \quad (37)$$

and N, I denote nominal and impact respectively, Finally

$$S = R_M \theta \quad (3)$$

It must be realized that S, as computed here and used in subsequent work, contains no direction information.

S can now be plotted versus the variable in question, as, for instance, in Figure 11. Note that the discontinuity at the origin is the consequence of definition of S and the manner in which it is measured. The slope of such a relation represents $\frac{\partial S}{\partial \sigma_i}$ where σ_i is any of the independent variables.

The plot of $\frac{\partial S}{\partial \sigma_i}$ can be obtained by numerical differentiation of the $S(\sigma_i)$ relation. Caution must be exercised in putting too much trust in this result because in any process where numerical differentiation is involved there is a significant loss of accuracy. This is particularly true with regard to the first attempts where the number of points defining S was insufficient as, for instance, in Figure 12. In other cases where the distribution of points is more favorable $\frac{\partial S}{\partial \sigma_i}$ is considerably smoother, as shown in Figure 13. In either case, however, the linear trend of S or $\frac{\partial S}{\partial \sigma_i}$ extends only over a limited part of the lunar surface. Thereafter relation (3) ceases to be a good approximation.

The procedure just described was found somewhat wasteful of computing time. It was also found that it resulted in too many complete misses.

It was noticed, however, that the plot of the distance of closest approach r_p to the Moon's center versus error $\Delta \sigma_i$ resulted in a curve which could be represented remarkably well by a hyperbola of the form

$$\frac{(y - y_0)^2}{b^2} - \frac{(x - x_0)^2}{a^2} = 1.$$

An example of this is shown in Figure 14.

This situation was found to hold for all runs made in this investigation. It must be stated emphatically that there is no analytical justification for this and the use of this fact is predicated strictly on convenience.

The choice of hyperbola is not essential. It is conceivable that other curves could serve the same purpose. If it is agreed to use the above fact, the intersection of $r_p(\Delta\sigma_1)$ with R_M gives the maximum possible errors allowed, beyond which the Moon is missed entirely.

In addition, the bounding errors will indicate how $\Delta\sigma_1$ should be distributed to obtain $S(\sigma_1)$ with maximum efficiency. Uniform spacing is very important especially in the determination of the partial derivatives.

An item from the preceeding discussion deserving some elaboration is the determination of the fictitious distance of closest approach r_p . As in the case of the impact point, r_p cannot be obtained directly from the computer runs. To obtain this quantity the numerical minimum of r can be found by using various interpolation formulae. This procedure is not very accurate because the trajectory near the perilune is rather flat for the high velocity employed here. Secondly, the procedure is rather tedious.

It is possible to obtain r_p in a somewhat different manner by using computed tabular points. First it should be noted that regardless of velocity the trajectory which does not result in a capture is a hyperbola as far as the observer on the Moon is concerned.

The following equation can then be written:

$$r_p = a(e - 1), \quad (39)$$

where a is the real axis of the hyperbola and e its eccentricity.

Now at any three tabular points in the neighborhood of r_p ,

$$\begin{aligned} r_1 &= \frac{p}{1 + e \cos \theta_1} \\ r_2 &= \frac{p}{1 + e \cos (\theta_1 - \Delta \theta_1)} \\ r_3 &= \frac{p}{1 + e \cos (\theta_1 - \Delta \theta)} \end{aligned} \quad (40)$$

where $p = a(e^2 - 1)$ and θ is the true anomaly. Also,

$$\theta_1 - \theta_2 = \Delta \theta_1$$

$$\theta_2 - \theta_3 = \Delta \theta_2$$

$$\Delta \theta = \Delta \theta_1 + \Delta \theta_2.$$

The increments of the true anomaly are obtained from

$$\cos \Delta \theta_1 = \frac{\vec{r}_1 \cdot \vec{r}_2}{r_1 r_2} \text{ and } \cos \Delta \theta = \frac{\vec{r}_1 \cdot \vec{r}_3}{r_1 r_3}$$

Thus in equation (40), p , e , and θ , are unknown. The simultaneous solution of (40) yields

$$p = r_1 \frac{\frac{\sin \Delta \theta_1}{\sin \Delta \theta} (\cos \Delta \theta - 1) + (1 - \cos \Delta \theta_1)}{\frac{r_1}{r_2} - \cos \Delta \theta_1 + \frac{\sin \Delta \theta_1}{\sin \Delta \theta} \left(\cos \Delta \theta - \frac{r_1}{r_3} \right)}. \quad (41)$$

The quantity θ_1 is obtained from

$$\frac{p - r_2}{p - r_1} \left(\frac{r_1}{r_2} \right) = \cos \Delta \theta_1 + \tan \theta_1 \sin \Delta \theta_1. \quad (42)$$

The eccentricity follows from

$$e \cos \theta_1 = \frac{p}{r_1} - 1. \quad (43)$$

Finally, a is obtained from

$$a = \frac{p}{e^2 - 1} \quad (44)$$

All quantities necessary to obtain r_p from equation (39) are now available.

This computation was performed on the LGP-30 computer.

In the above a description was given of all the supplementary computations required to obtain the desired information from the main computer runs. These subroutines could very profitably be included in the main program in order to prevent the interruption of computation.

D. DISCUSSION OF RESULTS

As an example a discussion shall be given of the results obtained for the trajectory of Nov. 7, 1959.

The general character of incremental miss S as a function of $\Delta \rho$, $\Delta \theta$, $\Delta \phi$, Δv , $\Delta \alpha$, $\Delta \beta$, or ρ , θ , ϕ , v , α , β is shown in Figures 11, 15, 16, 17, 18, 19.

It is evident from these curves that for small errors (impacts not too close to the limb) S is a reasonably linear function of incremental errors. As the impact point moves closer toward the Moon's limb the curves break away from a linear variation. Values of errors for which the linear trend ceases to be a good approximation depend on a particular variable. This situation is shown much more clearly in plots of error coefficients. Two examples are given in Figures 12 and 13. The deviation from linearity can be either gradual or rather sharply defined.

Since this value of the error coefficient is only of significance in those cases where the curves of miss versus error are linear, the cases which fail to meet this qualification are not presented graphically.

A feature which is common to all plots of S is their asymmetry with respect to the nominal impact point. This is to be expected because the Moon is a moving target. It should be sufficiently clear that the larger the arrival angle the greater the asymmetry in S with respect to the desired impact point. It may be noted that in this investigation no attempt was made to achieve a normal impact. (Arrival angle is defined as the angle between the velocity vector and the local vertical.)

From the plots of S as they stand the total permissible spread of errors cannot be readily determined. By this we mean the maximum deviation in each variable from the nominal value that results in a skimming hit at each limit. This is accomplished best from the plot of the "distance of closest approach" as a function of a particular error. This also alleviates the problem of computing too many runs which fail to impact the moon. A typical example of such plot is shown in Figure 14. The range of errors for other variables has been estimated from similar plots given in Figures 20, 21, 22, 23. Similar estimates were made for the November 15 and November 23 trajectories.

The range of errors for the November 7 trajectory is as follows:

$$\begin{aligned} & -14.5 < \Delta \rho < 21.2 \\ & - .21 < \Delta \theta < .64 \\ & - .15 < \Delta \phi < .87 \\ & -79.0 < \Delta V < 101.0 \\ & - .202 < \Delta \alpha < .075 \end{aligned}$$

Values available for the November 15 case are

$$\begin{aligned} & - .18 < \Delta \rho < 22.0 \\ & .43 < \Delta \theta < .06 \\ & - .65 < \Delta \phi < .08 \\ & -10.0 < \Delta V < 82.0 \\ & - .03 < \Delta \alpha < .32 \\ & - .025 < \Delta \beta < .264 \end{aligned}$$

For the November trajectory, the available values are

$$\begin{aligned} & - 1.9 < \rho < 55 \\ & - .067 < \theta < 1.56 \\ & - .153 < \phi < .274 \\ & - 9.9 < V < 124 \\ & - .28 < \alpha < .41 \\ & - .35 < \beta < .002 \end{aligned}$$

Here $\Delta \rho$ is given in statute miles

ΔV in feet per second and
 $\Delta \alpha, \Delta \beta, \Delta \phi, \Delta \theta$ in degrees

The initial conditions used in the three cases are given in the following list.

	November 7	November 15	November 23
x_0	$-3.3000000 \times 10^{-5}$	$-3.3000000 \times 10^{-5}$	3.3000000×10^{-5}
y_0	$-3.3000000 \times 10^{-5}$	3.3000000×10^{-5}	3.3000000×10^{-5}
z_0	4.0500000×10^{-6}	4.0500000×10^{-6}	4.0500000×10^{-6}
r_0	4.6844449×10^{-5}	4.6844449×10^{-5}	4.6844449×10^{-5}
$\dot{x}_0$	7.9198756×10^{-5}	5.8280834×10^{-5}	$-1.2900149 \times 10^{-4}$
$\dot{y}_0$	$-2.6305573 \times 10^{-4}$	2.6288784×10^{-4}	2.4008342×10^{-4}
$\dot{z}_0$	$-4.3421102 \times 10^{-5}$	6.9638123×10^{-5}	5.5450141×10^{-5}
V	2.7812974×10^{-4}	2.7812971×10^{-4}	2.7812971×10^{-4}
θ	225°	135°	45°
ϕ	$4^\circ 57' 35''$	$4^\circ 57' 35''$	$4^\circ 57' 35''$
α	$-8^\circ.982$	$14^\circ.5$	$11^\circ.5$
β	$286^\circ.76$	$77^\circ.5$	$118^\circ.25$

Comparison of these three cases indicates that the geometrical arrangement of the three main bodies has a significant effect not only on the error range itself, but also on the error asymmetry. For instance, the tolerance in $\Delta\theta$ and $\Delta\phi$ in the November 15 case is very tight in the positive direction. Also the range in velocity became significantly smaller.

In none of the cases, however, do the tolerances become so small as to make the hit impractical for conditions specified above.

It is of interest to consider the effect of errors on the flight time of the vehicle. A few representative plots are shown in Figures 25, 26, 27, 28 and 29. It is evident from these that the variation in flight time is nearly linear with the magnitude of $\vec{\rho}$ and $\vec{v}$. The variation with angles, however, is sharply non-linear. It may also be noted that so far as the November 7 trajectory is concerned, errors $\Delta\theta$, $\Delta\phi$, and $\Delta\alpha\Delta\beta$ affect the flight time in

opposite directions. Thus negative $\Delta \theta$, $\Delta \phi$ tend to increase the time of flight while negative $\Delta \alpha$, $\Delta \beta$ tend to decrease it. As was to be expected V has the most serious effect on the flight time.

The entire previous discussion was concerned with errors in only one of the initial quantities: When errors in ρ , θ , ϕ , v , α , β are present simultaneously, the increment in miss is found by (34) provided that precision measures $\Delta \sigma_i$ are known. This expression will, however, result in an estimate that is generally too high. If the errors $\Delta \sigma_i$ are entirely independent, it is more reasonable to compute the miss from

(45)

$$\Delta M = \left[\frac{\partial S}{\partial \rho} \Delta \rho \right]^2 + \left[\frac{\partial S}{\partial \theta} \Delta \theta \right]^2 + \left[\frac{\partial S}{\partial \phi} \Delta \phi \right]^2 + \left[\frac{\partial S}{\partial V} \Delta V \right]^2 + \left[\frac{\partial S}{\partial \alpha} \Delta \alpha \right]^2 + \left[\frac{\partial S}{\partial \beta} \Delta \beta \right]^2^{1/2}$$

Conversely, if the miss is not to exceed some predetermined value, equation (45) can be used to specify the value of $\Delta \sigma_i$. In the converse problem a question arises whether the effects of various parameters are equal or not. This question can be settled by examining the plots of S . In general, however, the precision with which the parameters must be measured can be estimated from

(46)

$$\pm \frac{\Delta M^1}{6} = \frac{\partial S}{\partial \rho} \Delta \rho = n_1 \frac{\partial S}{\partial \theta} \Delta \theta = n_2 \frac{\partial S}{\partial \phi} \Delta \phi = n_3 \frac{\partial S}{\partial V} \Delta V = n_4 \frac{\partial S}{\partial \alpha} \Delta \alpha = n_5 \frac{\partial S}{\partial \beta} \Delta \beta,$$

where n_i are measures of the strength of the effect. Thus, as indicated above, $\Delta \theta$ affects S n_1 times as much as $\Delta \rho$, etc. The quantity ΔM^1 is the relative tolerance on ΔM .

Perhaps, if further study was to be carried out, another approach to the "total miss" portion of the error analysis could be tried. By varying the six spherical parameters separately, within the impact region, an error tube would be generated which would encompass the total allowable error. For

these trajectories, statistically speaking, the first moment, or mean error trajectory, could be computed. Using the mean as a measure of location, the second moment can be taken about it to obtain the variance, the square root of this quantity being the standard deviation. The standard deviation is merely a number, in the same units as the particular parameter in question, which measures the relative extent of the data concentrated about the mean and becomes larger as the data becomes more dispersed. With a large sample, an interval of two standard deviations will include about 95% of the trajectories. With this knowledge, the confidence limits on the allowable error can be computed.

However, it can be said without reservation that when the first moment of the error cone is computed it would not agree with the computed standard trajectory unless the arrival angle of the trajectory were normal. Immediately a problem becomes evident. By looking at Figure 30, a plot of longitude and latitude of the impact points, the allowable error is seen to be almost no better than the nominal trajectory itself for changes in the velocity angle $\Delta \alpha$. The implications of this become clear when it is realized that if a mean trajectory were to be computed from the data taken about a non-normally arriving nominal, the allowable error at the extremes would be fictitious. Under the same conditions, the tolerances probably would become so small that arrival at a predetermined point on the moon's surface would be impossible.

In light of the above discussion, certain desirable procedures can be ascertained which would be of value in predicting the likelihood of impact and the accuracy of impact about a desired point of the Moon based on the perturbations on the initial input.

Computing the impact points in terms of their latitude and longitude on the apparent disc gives not only an indication of the value of an error tube and the resulting measures of standard deviation, but also provides directional

information as well as a measure of the miss distance. This information would lead to optimization of computer runs on a factual rather than guess-work basis. It is also concluded that the accuracy of prediction within prescribed confidence limits is a direct function of the impact angle. In the November 7 trajectory, this angle was computed at 50° , for November 15, 66° , and for November 23, 65° . These angles are calculated by finding the direction cosines of a straight line approximation to the tangent line to the hyperbola at the point of impact. The direction cosines of the normal to the tangent plane are then computed. The products of the direction cosines are summed and this gives the cosine of the angle of impact.

This portion of the report shall be concluded with a brief discussion concerning the disturbing effects of the Sun on a vehicle moving in the Earth-Moon space.

For two of the three dates used in this study the computation of the standard trajectory was repeated with the Sun taken out of the program.

For a crude estimate it is sufficient to compare the distance of the vehicle from the Moon for equal flight times.

For the November 7 case, the distances differ by 5.3 miles after 20.250 hours (just before impact) while for the November 23 case, the difference is 4.8 miles at 20.969 hours, which is also just prior to impact. Thus the Sun's perturbation on the distance of the vehicle from the Moon is not a very significant one for the trajectories in question.

VI. LIFETIME OF AN ARTIFICIAL LUNAR SATELLITE

The principal objective of this phase of the Lunar Trajectory Study was to examine in a cursory way the life time of an artificial satellite placed in orbit around the moon. No attempt at an all inclusive analysis of this problem was intended or made.

Using the "n body computer program" in a restricted four body analysis, e.g., Earth, Moon, Sun and Vehicle; a near lunar orbit was run and some interesting results were obtained.

Fixing the altitude of the injection point at 135.827 st. miles above the moons surface a range of instantaneous injection velocities were introduced. The first orbit of each of the resulting orbits is shown in Figures 54 and 55. The range between escape and impact has been covered. Taking the case $V = 3.0 \times 10^{-5}$ A. U. /Hour the run was extended for 25 days. The projections of this orbit for the first revolution are given in Figures 56, 57, and 58. The osculating orbital elements for this revolution are

$$i = 34^{\circ}.36$$

$$\omega = 90^{\circ}.02$$

$$\Omega = 4^{\circ}.88$$

$$a = 1.458 \times 10^{-5} \text{ A. U.}$$

$$e = .1933$$

$$T = 14.^h 157$$

$$P \approx 2.^h 5$$

and a plot of the apolune, perilune distances as a function of orbital life time are given in Figures 59A and 59B. As may be seen in Figures 59A and 59B several interesting features appear. First we see that the lifetime of the orbit is a strong function of the number of major bodies carried in the computations.

In the Earth, Moon, Sun field the orbit exceeds 25 days (the limit has not been determined). But for the Earth, Moon field with the Solar effect removed, the lifetime is reduced to 220 hours, impact with the Moon terminating the run. A similar situation exists when the Earth's influence is removed with the lifetime reduced to only a few hours.

Secondly there exists a definite pattern showing both the effects of long and short period perturbations. The variation in the osculating orbital elements was derived from the rectangular components of the vehicles position and velocity at six hour intervals for the first 10 days of the orbit. This was done for both the Earth, Moon, Sun and Earth, Moon geometries with the results indicated in Figures 60, 61 and 62. These figures clearly show the rotation of the line of apsides as well as the long period effects in i and Ω . Also to be noted is the definite divergence between the two cases. The length of time of these runs precludes any obvious identification of secular terms except in T . Care should, however, be exercised here as a long period term can over a short interval of time look like a secular term. To show the true periodic variation in a , e , and ω requires that these elements be recomputed for time intervals of the order of one hour instead of the six hour interval employed in these figures.

If a lunar satellite is to be employed to determine the geometrical figure and internal density gradient of the Moon by perturbation analysis of the satellite's orbits, several factors are obvious. From Figure 59B we can see that the difference in perilunes during the mid portion of the orbit is 1.207×10^{-8} A. U. or some 1.12 statute miles. Similarly, for the apolunes we have a difference not exceeding 1.961×10^{-8} A. U. or 1.82 miles. Since this is as close an orbit as one cares to discuss, first perilune is 1.697×10^{-7} A. U. or 15.76 statute miles above the lunar surface, the perturbations shown are about the maximum that can be expected. Hence any tracking equipment must be able to resolve these perturbations with a high degree of accuracy. If this can be

done then an appropriate set of orbital elements can be computed for a known interval of time. Then a variation of parameters scheme can be introduced. As an example consider the planetary equations due to Lagrange in which we have

$$\begin{aligned}\dot{\Omega} &= \frac{1}{na^2 (1-e^2)^{1/2} \sin i} \frac{\partial R}{\partial i} \\ \dot{i} &= - \frac{1}{na^2 (1-e^2)^{1/2} \sin i} \frac{\partial R}{\partial \Omega} - \frac{\tan \frac{i}{2}}{na^2 (1-e^2)^{1/2}} \left[\frac{\partial P}{\partial \pi} - \frac{\partial R}{\partial \epsilon} \right] \\ \dot{\pi} &= \frac{\tan \frac{i}{2}}{na^2 (1-e^2)^{1/2}} \frac{\partial R}{\partial i} + \frac{(1-e^2)^{1/2}}{na^2} \frac{\partial R}{\partial e} \\ \dot{a} &= \frac{2}{na} \frac{\partial R}{\partial \epsilon} \\ \dot{e} &= - (1-e^2)^{1/2} \frac{1 - (1-e^2)^{1/2}}{na^2 e} \frac{\partial R}{\partial \epsilon} - \frac{(1-e^2)^{1/2}}{na^2 e} \frac{\partial R}{\partial \pi} \\ \dot{\epsilon} &= \frac{\tan i / 2}{na^2 (1-e^2)^{1/2}} \frac{\partial R}{\partial i} + (1-e)^{1/2} \frac{1 - (1-e^2)^{1/2}}{na^2 e} \frac{\partial R}{\partial e} - \frac{2}{na} \frac{\partial R}{\partial A}\end{aligned}$$

where $\sigma = -nT$, $\pi = \omega + \Omega$ and $\epsilon = \pi + \sigma$ and the other elements have the conventional meaning. The perturbing forces are contained in the disturbing function R .

If the left hand side of the above functions are known from the tracking data it is possible to compare these with values obtained from computations based on an assumed theoretical model. Comparisons can be made and in theory at least an improved theoretical model obtained. While it may be possible to arrive at a better figure for the moon in this way the likelihood of determining the density gradient is somewhat more uncertain since the force field is not a uniquely determined function of the density gradient.

VII. LUNAR CIRCUMNAVIGATION AND EARTH RETURN

In addition to the Lunik III trajectory* another Lunar Circumnavigation and Earth Return trajectory was analyzed from an entirely different point of view. In the Lunik III case we are primarily interested in the ability to reproduce the trajectory of the vehicle in Earth-Moon space from crude tracking data. In the case under present consideration we are concerned with the generation of such a trajectory subject to a number of additional constraints. These constraints are manifest in two ways, those associated with the ascent and those associated with the extraterrestrial portions of the flight. In the former such practical problems as booster capabilities, range safety limits, and the launch on time problem are eminent. These must be matched to the geometrical constraints imposed by the extraterrestrial portions of the flight.

An attempt has been made in this section to indicate the effects of these constraints on a Lunar Circumnavigation and Earth Return trajectory with particular emphasis on matching the ascent to the geometrical constraints. Consider the following as an initial set of constraints;

A. ASCENT TRAJECTORY

1. Launch Site: Cape Canaveral
2. Range Safety Limits: $85^{\circ} - 125^{\circ}$ in azimuth
3. Firing Azimuth Limits (Azimuth of the velocity vector at injection or burnout point) identical with range safety limits.
4. Flight path angle at injection limited to $0^{\circ} \leq \theta \leq 3^{\circ}$ (a booster characteristic)

B. CONDITIONS AT THE MOON

1. Distance of closest approach to Moon's surface $2000 \leq r_M \leq 3000$ miles

*Described in Scientific Report #1

2. Vehicle to pass in front of moon on outbound leg and slightly below Moon's orbital plane. (Necessary to achieve Earth return in Northern Hemisphere)
3. Transit Time $\approx 3.25^d$ for outbound leg (enabling vehicle to be in vicinity of Moon for longest possible time)

C. EARTH RETURN

1. Vehicle to return to the Earth in the Northern hemisphere and in a suitable recovery area.
2. Vehicle to return to the Earth in direction of the Earth's rotation (direct motion)
3. Vehicle to return at an altitude of from $200 \leq h \leq 300$ miles above the Earth's surface.

In arbitrarily specifying a set of constraints such as that listed above it is possible to overdefine the problem. A solution may not exist for a particular firing date. An indication of this exists in this case but an exhaustive study to definitely ascertain whether such a situation is the case or not has not been made.

To match the ascent and geometrical constraints it is first necessary to determine the orientation of the velocity vector at the time of injection. Thus, we must specify the time (t), the firing azimuth (A_z) and the flight path angle (θ) at the injection point. Since we have already placed a constraint on θ our free parameters become t and A_z . Initially then we wish to select values of t and A_z such that the orbital plane of our vehicle intersects the orbital plane of the moon some 3.25^d after injection.

To obtain preliminary values for A_z and t a method based on a two body approximation was tried. It was realized at the outset that the final values

for A_z and t could only be obtained from the n-body program by trial and error since a solution to the two point boundary value problem in n-body space does not exist in explicit form. However, it was hoped that the preliminary values would be sufficiently close to the final values for A_z and t to greatly reduce the convergence time. It is appropriate to mention at this point that we have selected a direct ascent trajectory, fully realizing that for extreme declinations of the Moon one may be forced to employ a coasting orbit.

The results of such an approximation give A_z as a function of t , launching site latitude (ϕ) and the coordinates of the Moon. For any specific case ϕ and the coordinates of the Moon enter as fixed parameters. For this problem we have taken the time as September 25, 1960, and the Moon's coordinates at the vehicles time of arrival (3.25^d later) as

$$\alpha_{\zeta} = 18^h 37^m 27.8^s$$

$$\delta_{\zeta} = -18^{\circ} 19' 51.5''$$

where α_{ζ} is the right ascension and δ_{ζ} is the declination of the Moon.

The injection point was taken as 1500 miles downrange at an azimuth value of 110° and altitude of 750000 ft over a spherical Earth.

A convenient relation between the firing azimuth and the launching time, can be obtained as follows:

Let (i_x, i_y, i_z) be unit vectors defining a geocentric equatorial coordinate System and $(\bar{\xi}, \bar{\zeta}, \bar{\eta})$ be a horizon-altitude system connected with the injection point. Then a unit vector $\bar{l}$ along the firing azimuth is given by

$$\bar{l} = \bar{\zeta} \cos A_z + \bar{\eta} \sin A_z.$$

Rotation into the (i_x, i_y, i_z) System gives

$$\begin{aligned}\bar{l} = & -(\cos A_z \sin \phi \cos a_L + \sin A_z \sin a_L) i_x \\ & + (\sin A_z \cos a_L - \cos A_z \sin \phi \sin a_L) i_y \\ & + (\cos \phi \cos A_z) i_z\end{aligned}$$

Unit vector normal to the plane of the orbit is given by $\bar{W} = \bar{r} \times \bar{l}$
where $\bar{r}$ is the unit vector defining the launching site.

From a dot product of W and a unit vector defining the Moon's direction at the encounter we obtain

$$\tan A_z = \frac{\sin(\alpha_L - \alpha_C)}{\sin \phi [\cos(\alpha_L - \alpha_C) - \tan \delta_C \cotg \phi]}$$

where a_L = Launching site right ascension
 a_C = right ascension of the Moon
 δ_C = declination of the Moon
 ϕ = launch site latitude

Since the n-body program employed in this search requires initial velocity components to be expressed in the geocentric equatorial system it was convenient to employ the following expressions:

$$\dot{x} = V_T \left[\sin \theta \cos \phi \cos a_L - \cos \theta (\cos A_z \sin \phi \cos a_L + \sin A_z \sin a_L) \right]$$

$$\dot{y} = V_T \left[\sin \theta \cos \phi \sin a_L + \cos \theta (\sin A_z \cos a_L - \cos A_z \sin \phi \sin a_L) \right]$$

$$\dot{z} = V_T \left[\sin \theta \sin \phi + \cos \theta \cos \phi \cos A_z \right]$$

where θ is the flight path angle, V_T is the total injection velocity, and ϕ is the latitude of the injection place.

Choosing now the launching site, injection point, lunar coordinates, and the trip time as specified earlier, we can plot the firing azimuth as a function of time on September 25, 1960. This plot is shown in Figure 63. (Only Eastward firings have been considered.) Note that the range in firing azimuth is quite restricted. There are two reasons for this. First of all firing on steep branches is impractical because any launching delays will require excessive re-adjustment of azimuth. Secondly most of the diagram lies outside the range safety limits of 85° to 125° .

From this point the procedure was rather straight forward. Three variables remained open to us. These were launching right ascension α_L , total velocity V_T , and the flight path angle θ . Trip time can hardly be considered a bonafide parameter.

The total velocity was fixed at a value which was found reasonable from previous studies. Then for values of $\theta = 1^\circ, 2^\circ, 3^\circ$ launching time was varied over the upper allowable part of the $A_z - t_L$ diagram. This is the region where the firing azimuth varies relatively slowly with launching time.

The resulting initial conditions $x_0, y_0, z_0, \dot{x}_0, \dot{y}_0, \dot{z}_0$ were employed in the n-body program. The bodies used were the Sun, Earth, Moon, and the vehicle. Note carefully that the Earth's oblateness was retained in the n-body program. Also, the initial conditions as used are based on a two body, approximation (no oblateness considered).

The very first runs indicated two problem areas. The first of these is that for the small range in θ one cannot use an arbitrary combination of A_z, t_L . In fact it appears that A_z, t_L diagram must include a grid of

constant θ lines to be really useful. The situation as it exists shows that we are firing almost at right angles to the initial radius vector. The line of apsides of the resulting orbit turns almost 90° away from the intended point of encounter. One can compensate for this effect by a large flight path angle. Yet in our case this variable is restricted to a narrow range. Thus the only way to correct this problem is to employ smaller values of a_L . In our case this forced us to employ a value for $A_z = 85^\circ$ which is practically the limit of the allowable range.

The second problem is the fact that first runs placed the vehicle far below the moon. Part of the rotation of the line of apsides described above, and the great dip of the trajectory below the Moon's orbital plane can be attributed to the effect of Earth oblateness.

To make the z component of the vehicle in the Moon's vicinity acceptable at all, it was found necessary to aim at a declination much different from that of the actual Moon. In our case the final value was in the neighborhood of -8° degrees as compared to -18° for the actual position of the target.

This experience indicates that the two body estimates of the launching conditions have an extremely limited value and should be modified. Since the declination of the target point must be watched so closely, this quantity became in our case an additional variable.

Our approach indicated finally that a reasonable circumnavigating trajectory results for the following conditions:

$$\begin{aligned} \alpha \zeta_T &= 279^\circ 22' 12'' \\ \delta \zeta_T &= -7^\circ 40'' \\ V_T &= 2.6200445 \times 10^{-4} \text{ AU/hr} \\ \theta &= 2^\circ \\ \delta L &= 19^\circ 13' 22'' \end{aligned}$$

$$\alpha_L = 124.00$$

Transit time to the Moon approximately 75 to 85 hours
and the total trip time between 7.5 to 8 days.

A limited error analysis of this trajectory was made over the following range of input parameters:

$$123.4 \leq \alpha_L \leq 124.00$$

$$-8^{\circ}19'52'' \leq \delta_{\zeta_T} \leq -7^{\circ}19'52''$$

$$2.6200226 \times 10^{-4} \leq V_T \leq 2.6200666 \times 10^{-4}$$

$$1^{\circ} \leq \theta \leq 3^{\circ}$$

One of these trajectories is shown in Figures 64, 65 and 66.

The resulting variation of distances of closest approach to the Moon and on return to the Earth are shown in Figures 67, 68, 69 and 70.

It can be seen that r_M and r_E as functions of δ_{ζ_T} reach a minimum in the vicinity of $-7^{\circ}40'$. However, these minimum values do not satisfy the original specification. Although the closest approach to the Moon is satisfactory and meets requirements, the value of r_E is entirely too large. At any rate δ_{ζ_T} can no longer be used to improve either distance.

The variation of these two distances with θ exhibits a similar trend. Thus r_E reaches a certain minimum which is contrary to specifications from the start. Not much improvement can be hoped for using this variable.

The next variable, the velocity V_T , causes changes in r_E and r_M in opposite directions. The point of intersection does not satisfy specifications. A limited hope of improving these two distances lies in the fact that slopes

of the two functions are quite different. Thus at the cost of a slight degradation of one distance, one may obtain a very substantial improvement in the other. No attempt was made to investigate this possibility.

Sensitivity of r_E and r_M to changes in the right ascension of the launching point α_L are shown in Figure 70. Its nature is exactly the same as that of the previous plot.

It appears then that for this trajectory we have reached near optimum conditions. Despite this fact the distance of closest approach on return to the Earth is entirely unsatisfactory. It must be noted that the above discussion ignored the question of transfer of angular momentum during scattering of the vehicle by the Moon. As pointed out by Egorov and Sedov in their papers, this is a parameter which is quite important in determining characteristics of the return leg of the trajectory. In fact specification B.2 is a direct consequence of this consideration.

Results of this study can be summarized as follows:

1. Initial conditions established on the basis of a two body problem were found highly unsatisfactory when used in a more realistic model of the Earth-Moon System. One of the causes appears to be the Earth oblateness and the restricted range available for flight path angles θ .
2. A "figure 8" trajectory was found which satisfies nearly all engineering restrictions at launch.

The distance of closest approach at the Moon is satisfactory.

The distance of closest approach to the Earth is unsatisfactory, being in the neighborhood of 10000 miles and occasionally even higher than this value. The return, however, does occur in the northern hemisphere in direct motion. The problem of proper recovery site was

not studied for obvious reasons.

The trip time achieved is satisfactory.

3. The limited error analysis indicates that the above trajectory is nearly optimum as far as the distances of closest approach are concerned. Thus, little hope exists for any further improvement.
4. It must be remarked that the above was a direct ascent trajectory. It is conceivable that employment of a coasting arc before final injection will result in better circumnavigation as well as recovery distances. Without question, the coasting arc will largely eliminate constraints associated with the launch on time problem and facilitate solution of the geometrical problem.

With regard to trajectories of this type Figure 71 shows the differences between considering a two body plus oblateness, three body, a four body, and a four body plus oblateness effect on close approaches to the Moon. Since the latter three cannot be handled analytically the only hope of getting a reasonable approximation for A_z as a function of t rests in modifying the two body method as outlined by an oblateness term. No attempt was made to do this on this contract.

VIII. EPHEMERIS COMPUTATION - PALLAS AND VESTA

One of the tasks which the n-body interplanetary trajectory computer program is capable of performing is the compilation of ephemerides. To test this facet of the program, it was decided to reproduce part of the orbit for two of the better observed asteroids the coordinates of which are tabulated in the American Ephemeris and Nautical Almanac. Observational inaccuracies in the ephemerides of artificial earth satellites together with atmospheric drag effects precluded their use. Furthermore, they would only serve as a check on the near earth accuracy of the program, the perturbative forces of the planets being of little or no consequence.

The ephemerides for Pallas and Vesta, as given in the almanac, are tabulated for each day and represent smoothed values for which the integrations were adjusted along the entire orbit. A discussion of the methods employed, intervals selected, etc. can be found in Vol. XI, Part IV of the Astronomical Papers. The smoothing technique employed greatly improves the accuracy of the ephemeris. Individual errors in the order of 5 seconds of arc between the computed and observed values of right ascension and declination is indicative of the accuracy of the observational data for which the ephemerides are compiled. Hence, only six decimal places are printed out in the Almanac. One unit in the last decimal place corresponding to 1×10^{-6} A. U. throughout.

Our purpose here is to select a small segment of observed data and to predict the future positions of the body. This represents the case most useful to artificial satellite ephemeris compilations in which the future position of the body is of interest. This will be compared with runs obtained by selecting data over a larger segment of the orbit indicating the improvement to be expected. The latter will indicate the need for a time history (past history of the satellite's position) of some extent if future position type ephemerides are to be accurately obtained.

For our computations we have used Pallas and Vesta in the combined force field of the Sun, Venus, Earth, Mars, Jupiter and Saturn. Selected data on these two asteroids is given in Table 1.

TABLE I

	Radius (Km)	Volume (cm^3)	Mass (grams)	Sidereal Period (days)	a (A. U.)	e	i (degrees)
Pallas	240	6×10^{22}	20×10^{22}	1684	2.767	.235	34.8
Vesta	190	30×10^{21}	10×10^{22}	1325	2.361	.088	7.1

It should be noted that they represent both extremes with regard to orbital eccentricity and inclination that is found among the brighter asteroids.

Selecting ten tabular geocentric positions from the almanac, a numerical differentiation scheme was employed to obtain the velocity vector at one of the tabular values and hence a complete set of initial conditions for the n-body trajectory program was obtained. The data represented a period of time of ten days. A run was made using these conditions. Then a linear differential correction scheme for each component of the velocity vector was applied to improve the original estimates of the velocity components. This was accomplished by employing the tabular position data at three day intervals but now extended over a period of sixty days. A set of normal equations were obtained the solution of which yielded the desired corrections. This entire procedure was again repeated at three day intervals but with the period extended to one hundred and fifty days for Vesta, and with six day intervals over one hundred and fifty days for Pallas.

The results of these computations are shown in Figure 72 for Pallas and 73 for Vesta. As may be seen, the ephemerides computed from the short time history soon indicate large errors. While the residuals are small over

the fitted portion of each orbit they soon build up to substantial errors further along in time. We can conclude that in compiling ephemerides of this type a long time history for the object under study is a prime requisite. This would allow the entire orbit to be fitted at one time a procedure used in astronomy. This does not necessarily mean that a great number of data points are required but rather that they be obtained at selected intervals over the entire orbit. Intervals in the order of 20 to 40 days are common in astronomical practice. In the case of Pallas and Vesta, whose periods are 4.6 and 3.6 years respectively, the 20 day interval necessitates the use of some 84 and 66 points respectively.

An additional effect that can be noticed in Figures 72 and 73 is a slight oscillation in the residuals. A satisfactory explanation of their cause has not as yet been determined. Generally speaking, the amplitudes of the oscillations are slightly less for Pallas than for Vesta.

References:

1. Paul Herget, "The Computation of Orbits," published privately by the author, 1948.
2. F.R. Moulton, "An Introduction to Celestial Mechanics," MacMillan Co., New York, 1914.
3. J.B. Scarborough, "Numerical Mathematical Analysis," The Johns Hopkins Press, 1955, p. 164.
4. W.M. Smart, "Textbook on Spherical Astronomy," Cambridge Univ. Press, 1956, p. 195.
5. "Planetary Coordinates for the Years 1960-1980," H. M. Nautical Almanac Office, London, 1958.

The reader interested in detailed aspects of practical astronomy can find a wealth of material in the following references:

6. Simon Newcomb, "A Compendium of Spherical Astronomy," Dover, 1960.
7. H.C. Plummer, "An Introductory Treatise on Dynamical Astronomy," Dover, 1960.
8. W. Chauvenet, "A Manual of Spherical and Practical Astronomy," Dover, 1960.
9. W.M. Smart, "Celestial Mechanics," Longmans, 1953.
10. Egorov, V.A., Certain Problems of Moon Flight Dynamics, USPEKHI FIZICHESKIKH NAUK, Vol. 63, 1957.




Figure 2. Topocentric Coordinate System




Figure 3. Geocentric and Topocentric Coordinate System




Figure 4. Percentage Error in Velocity as a Function of the Time Interval Between Positions




Figure 5. Number of Iterations Required to Reach a Solution
as a Function of the Time Interval




Figure 6. Schematic No. 1




Figure 6. Schematic No. 1




Figure 8. Schematic No. 3





Figure 9. Schematic No. 4



$$\rho = \overline{OO'}$$

O - CENTER OF THE EARTH

T.S. - TRACKING SITE

T.S. - O' = h = BURNOUT ALTITUDE

Figure 10. Coordinate System Used in Error Analysis

NOV. 7




Figure 11. Miss Distance as a Function of Error in Initial Position

NOV 7




Figure 12. Error Coefficient as a Function of Error in Initial Position




Figure 13. Error Coefficient as a Function of Error in Initial Velocity

NOV. 7




Figure 14. Distance of Closest Approach as a Function of Initial Position $|\rho|$

NOV. 7




Figure 15. Miss Distance as a Function of Error in Position Angle θ




Figure 16. Miss Distance as a Function of Error in Position Angle ψ

NOV. 7




Figure 17. Miss Distance as a Function of Error in Initial Velocity

NOV. 7




Figure 18. Miss Distance as a Function of Error in Velocity Angle α

NOV. 7




Figure 19. Miss Distance as a Function of Error in Velocity Angle β




Figure 20. Distance of Closest Approach as a Function of Position Angle ϕ

NOV. 7




Figure 21. Distance of Closest Approach as a Function of Position Angle θ

NOV. 7




Figure 22. Distance of Closest Approach as a Function of Initial Velocity V

NOV. 7




Figure 23. Distance of Closest Approach as Function of Velocity Angle α




Figure 24. Distance of Closest Approach as a Function of Error in Velocity Angle β

NOV. 7





Figure 25. Flight Time as a Function of Error in Initial Position $|\rho|$

NOV. 7

TIME (HOURS)



$\Delta\psi$ (DEGREES)

Figure 26. Error in Position Angle ψ

NOV. 7




Figure 27. Flight Time as a Function of Error in Initial Velocity

NOV. 7




Figure 28. Flight Time as a Function of Error in Velocity Angle α

NOV. 7




Figure 29. Flight Time as a Function of Error in Velocity Angle β




Figure 30. Latitude and Longitude of Error Trajectories Taken About the Nominal at the Surface of Moon

NOV 15




Figure 31. Miss Distance as a Function of Error in Burnout Altitude




Figure 32. Miss Distance as a Function of Error in θ




Figure 33. Miss Distance as a Function of Error in ψ

NOV 15




Figure 34. Miss Distance as a Function of Error in Initial Velocity

NOV. 15




Figure 35. Miss Distance as a Function of Error in Velocity Angle α

NOV. 15




Figure 36. Miss Distance as a Function of Error in Velocity Angle β




Figure 37. Distance of Closest Approach as a Function of Error in Burnout Altitude




Figure 38. Distance of Closest Approach as a Function of Position Angle θ




Figure 39. Distance of Closest Approach as a Function of Position Angle ψ




Figure 40. Distance of Closest Approach as a Function of Error in Initial Velocity




Figure 41. Distance of Closest Approach as a Function of Velocity Angle α




Figure 42. Distance of Closest Approach as a Function of Velocity Angle β

NOV 23




Figure 43. Miss Distance as a Function of Error in Burnout Altitude

NOV 23




Figure 44. Miss Distance as a Function of Error in θ

NOV 23

($\times 10^{-6}$ AU)




Figure 45. Miss Distance as a Function of Error in ψ

NOV 23




Figure 46. Miss Distance as a Function of Error in Initial Velocity




Figure 47. Miss Distance as a Function of Error in Velocity Angle β




Figure 48. Distance of Closest Approach as a Function of Error in Burnout Altitude




Figure 49. Distance of Closest Approach as a Function of Position Angle $\Delta\theta$.




Figure 50. Distance of Closest Approach as a Function of Position Angle ψ

NOV.23




Figure 51. Distance of Closest Approach as a Function of Error in Initial Velocity




Figure 52. Distance of Closest Approach as a Function of Velocity Angle α




Figure 53. Distance of Closest Approach as a Function of Velocity Angle β




Figure 54.




Figure 55.

(X,Y) PROJECTION OF LUNAR ORBIT




Figure 56.




Figure 57.

Y,Z PROJECTION OF LUNAR ORBIT




Figure 58.




Figure 59A.




Figure 59B.




Figure 60.




Figure 61.




Figure 62.




Figure 63.




Figure 64.




Figure 65.




Figure 66.




Figure 67. Distance of Closest Approach to the Moon and Earth as a Function




Figure 68.




Figure 69.




Figure 70.




Figure 71




Figure 72. ¹⁴ Pallas Ephemeris Residuals




Figure 73. Vesta Ephemeris Residuals

APPENDIX A

MODIFICATION OF THE LUNAR TRAJECTORY PROGRAM TO N-BODY COMPUTER PROGRAM

This report pointed out earlier that the original Lunar Trajectory Program had been extended to cover all major bodies of the Solar System ($n = 9$). The resulting equations of motion differ in no way from those given in the Scientific Report No. 1. Thus, the equation of motion of body m_i with respect to the body m_k is given by

$$\ddot{\vec{r}}_{ik} = -k^2 (m_k + m_i) \frac{\vec{r}_{ik}}{r_{ik}^3} + k^2 \sum_{\substack{j=1 \\ j \neq i \\ j \neq k}}^N \left[\frac{\vec{r}_{jk} - \vec{r}_{ik}}{r_{ij}^3} - \frac{\vec{r}_{jk}}{r_{jk}^3} \right]$$

The oblateness correction remains the same as in that Report. The change to include a greater number of bodies does not affect either the method of solution or the integration method employed. The heart of the extended program - the planetary tables - was described in the Scientific Report No. 1.

The physical data appropriate for the added bodies are given in Table I of this Appendix. It is to be noted that much of the data is included simply for interest and is not used in computations.

The present Appendix also includes the operational procedure for the "n-body interplanetary trajectory program" as written for the IBM 7090 computer. The information contained in this procedure is that required by an engineer and a machine operator to set up problems on the computer.

TABLE I - ASTRONOMICAL CONSTANTS

Body	Code Digit	Mass (1/solar mass units)	Mass (solar mass units)	Equatorial radius (visible) (10 ⁻⁴ A. U.)	Oblateness (Apparent)	Oblateness constant (2)	Equatorial rotational angular velocity (visible) (radian / hr)	Mean planetary distance (A. U.)	Mean daily motion(epoch Jan. 0, 1959) (degrees)	Inclination of orbit to ecliptic (epoch Jan. 0, 1959) (degrees)	Declination of North pole of planet (epoch Jan. 0, 1959) (degrees)
Earth	0	333,432	2.999112x10 ⁻⁶	.426636	.0034	1.6232x10 ⁻³	.762516	1.0	3,548.191	0	90.0
Sun	1	1.0	1.0	46.55	0.0	0.0	.01044	0	0	0	-
Moon	2	27,158,036.4	.3682151x10 ⁻⁷	.11625	**	.3761x10 ⁻³	.00958212	1.002571	47,414.690	5.15	-
Mercury	3	6,000,000	.16666667x10 ⁻⁶	.162	0.0	0.0	.00297604	.387094	14,732.420	7.00397	unknown
Venus	4	408,000	2.4509804x10 ⁻⁶	.414	0.0	0.0	unknown	.723332	5,767.670	3.39422	unknown
Mars	5	3,093,500	.3272584x10 ⁻⁶	.226	.0052	3.017x10 ⁻³	.255176	1.523691	1,886.519	1.84994	54.689
Jupiter	6	1,047,355	.954,78610x10 ⁻⁶	4.78	.062	2.2x10 ⁻²	.6384	5.202803	299.128	1.30542	64.551
Saturn	7	3,501.6	285.58373x10 ⁻⁶	4.04	.096	2.501x10 ⁻²	.3140	9.538841	120.455	2.48997	86.724
Uranus	8	22,869	43.727316x10 ⁻⁶	1.60	.06	-	.3809	19.181945	42.235	.77306	14.162
Neptune	9	19,314	51.775914x10 ⁻⁶	1.49	.02	7.4x10 ⁻³	.4010	30.057767	21.532	1.77383	41.488

*For some bodies this data is for the atmosphere of the body

**Tri-axial ellipsoid

In addition, a description is given of the binary table tapes used to obtain planetary positions and a flow diagram showing the general sequence of computations and logic of the program. Finally a complete listing of the n-body trajectory program is provided.

A. COMPUTER INPUT

This section lists the computer input required for the n-body program. This covers the computation of the trajectory from an initial velocity and position.

All decimal input is read on line by a modified DBC Fortran subroutine which accepts variable length fields. A copy of the write-up for this subroutine is incorporated in Section F of this Appendix. Note that the number of fields per card is arbitrary except that the first field of each Read statement must start a new card. Also note that the first field of each Read statement must be preceded by the character identifying the type of conversion. There are eight Read statements in the program and the quantities starting these statements will be designated as such.

B. N-BODY TRAJECTORY PROGRAM (Operational Directory)

Following is the list of the input quantities and then the input for a sample problem. All fields are floating point numbers except for starred fields which are integers. The units used are:

Mass - Solar mass units.

Time - hours (Table time is time in hours from the beginning of the input table tape. It is directly related to calendar time.)

Distance - Astronomical units.

Velocity - Astronomical units/hour.

Read Statement 1

Field 1 = k^2 (gravitational constant)

Field 2 = M_e (Mass of Earth)

Field 3 = R_e (Radius of Earth)

Field 4 = M_v (Mass of Vehicle)

Field 5 = J' (Constant used for oblateness = $J \cdot M_e \cdot R_e$)

Read Statement 2

Field 1 = D_{emax} (Maximum distance of vehicle from Earth)

Field 2 = D_{tmax} (Maximum distance of vehicle from Target)

Field 3 = D_{smax} (Maximum distance of vehicle from Sun)

Field 4 = T_{end} (Maximum trip time of run)

Field 5 = T_{start} (Starting trip time of run)

Read Statement 3

*Field 1 = 1 if initial scheme is Encke
0 if initial scheme is Cowell

*Field 2 = 0 if ΔT is determined by ϵ test
1 if 3 fixed ΔT 's are used

*Field 3 = 1 if switching computing scheme
0 if computing scheme is fixed

*Field 4 = M print output every M intervals

*Field 5 = 1 switch origins
0 do not switch origins

Read Statement 4 (used only if Field 2 of Read Statement 3 is a 0.)

Field 1 = ΔT_1 (Initial ΔT)

Field 2 = $\Delta T_{\max}$ (Maximum ΔT)

Field 3 = ϵ value to test minimum accuracy of integration

Read Statement 5 (used only if Field 2 of Read Statement 3 is a 1.)

Field 1 = ΔT_1 (ΔT to be used when the vehicle is within 3 radii of origin).

Field 2 = ΔT_2 (ΔT to be used when the vehicle is within 100 radii of origin).

Field 3 = ΔT_3 (ΔT to be used when the vehicle is further than 100 radii from origin).

Read Statement 6

*Field 1 = N (The number of bodies to be used other than the earth which is always included).

*Field 2 = Code (Code digit indicating the body used as the initial origin. The code is listed below).

*Field 3 = Code (Code digit of the target body).

Read Statement 7 (This statement is read once for each body to be used, except the earth. The number is obtained from Field 1 of Read Statement 6).

*Field 1 = Code (Code digit of a body to be used).

Field 2 = M_m (Mass of this body)

Field 3 = R_m (Radius of this body)

Read Statement 8

Field 1 = X (X distance of vehicle from origin)

Field 2 = Y (Y distance of vehicle from origin)

Field 3 = Z (Z distance of vehicle from origin)

Field 4 = X (X velocity WRT origin)

Field 5 = Y (Y velocity WRT origin)

Field 6 = Z (Z velocity WRT origin)

Code Digits of Bodies

0 = Earth

1 = Sun

2 = Moon

3 = Mercury

4 = Venus

5 = Mars

6 = Jupiter

7 = Saturn

8 = Uranus

9 = Neptune

SAMPLE TRAJECTORY

Description:

Cowell method only.

Earth is origin and remains as origin.

Other bodies included are -

Sun

Moon (target)

Initial Time is 6:00 A. M., January 5, 1960

Maximum Flight time is 30 days (720 hrs.)

Starting time of table tape is 0.00, January 1, 1960.

$$X = 4.82537 \times 10^{-5}$$

$$Y = -4.18 \times 10^{-5}$$

$$Z = 4.22 \times 10^{-6}$$

$$X = -1.44092 \times 10^{-4}$$

$$Y = 1.967513 \times 10^{-4}$$

$$Z = 9.23 \times 10^{-6}$$

The ΔT is to be determined by the program using an ϵ of 4.0×10^{-10} and an initial ΔT of 1 hr. and a maximum ΔT of 8 hrs.

Input Cards:

1. F5.1373647E-7, 2.99911226E-6, 4.263E-5, 0, -8.846148E-18*
2. F.5, .5, 1, 822.102*
3. X0, 0, 0, 1, 0*
4. F1, 8, 4E-10*
5. X2, 0, 2*
6. X1, F1.0, 4.646E-3*
7. X2, F3.68215133E-8, 1.1637E-5*
8. F4.82537E-5, -4.18E-5, 4.22E-6*
9. -1.44092E-4, -1.967513E-4, -9.23E-6*

C. COMPUTER OUTPUT

The following information for the n-body integration program is printed-out after every n integration steps, where n is an input-control parameter.

1. Flight time, hours from start of trajectory
2. Table time, hours from beginning of tape
3. Time increment of integration step, hours
4. Planetary code digit of body at the origin
5. Acceleration components of the vehicle with respect to the origin,
A. U. /hr²
6. Velocity components of the vehicle with respect to the origin, A. U. /hr
7. Position coordinates of the vehicle with respect to the origin, A. U.

8. Position coordinates of the vehicle with respect to the Earth, A. U.
9. Position coordinates of the vehicle with respect to the target, A. U.
10. Position coordinates of the vehicle with respect to the Sun, A. U.

D. OPERATING NOTES FOR THE N-BODY TRAJECTORY PROGRAM

1. Tapes Used

All tapes used in normal Fortran System. Tape B-6, Planet Position Tables Tape.

2. Sense Switches

Sense switch I is the only switch tested. In the down position, output will be printed on-line as well as on tape A-3. The sense switch may be repositioned at any time. Printing on line uses the Share No. 2 printer board.

3. Card Deck

Normal Fortran system deck set-up with input cases following. Operation is initiated by the Fortran system.

4. Stops

- a. All Fortran stops
- b. Stops of form HTR*. These are double precision subroutine stops caused by overflow. Experience has shown these to be due to machine error or input error.
- c. HPR 77777 - Error in two-body solution.

* To begin processing another case when machine has stopped, manually transfer to 171₃.

E. DESCRIPTION OF BINARY-TABLE TAPES

The binary-table tapes give the "table time" and position coordinates of the Sun, Mercury, Venus, Earth, Mars, Jupiter, Saturn, Uranus, Neptune, and the Moon at intervals of 12 hours. The positions are specified in terms of rectangular, geocentric equatorial coordinates referenced to the mean equator and equinox of 1950.0. Table Time is time in hours from the beginning of the tape; i. e., the first time on the tape is zero. Zero time may correspond to any given calendar time; however, it should be chosen to anticipate future requirements for the following reasons:

1. It is desirable to minimize the time used by the computer in searching the tape. This time is minimized if the starting time is near "table time" zero.
2. The writing of tapes should be kept to a minimum due to the relatively long time required to write a tape.

Table Time is directly related, and easily converted, to Calendar Time or Julian Time. Table Time was used because it provides certain advantages which Julian Time and Calendar Time do not provide. Calendar Time is awkward to use because the number of days per month and per year is not constant. While Julian Time does not present this problem, the numbers are of a large magnitude with respect to the units used in the program; i. e., hours. In order to reduce round-off error, it is necessary to measure the time with numbers of a smaller magnitude than those provided by Julian Time.

Zero time for the tape is January 1, 1960.0 Ephemeris Time, and the corresponding Julian day is 2436934.5. A table relating table day to Julian date and Calendar date may be found in Section G of this Appendix. The time of day for each listing is 0^h E. T., and therefore the Table Time in hours from the beginning of the tape for any given day may be found by multiplying

the table-day by 24 hours. The table in Section G covers the period from January 1, 1960.0 to December 31, 1964.0.

The binary tape is composed of one tape with the actual arrangement of the binary information as follows:

WORD	1	TIME
WORD	2	X for body 1
WORD	3	Y for body 1
WORD	4	Z for body 1
WORD	5	X for body 2
WORD	6	Y for body 2
WORD	7	Z for body 2
.	.	.
.	.	.
.	.	.
WORD	26	X for body 9
WORD	27	Y for body 9
WORD	28	Z for body 9
WORD	29	Time
WORD	30	X for body 1
WORD	31	Y for body 1
WORD	32	Z for body 1
WORD	33	X for body 2

etc.

This information is grouped by taking 60 sets of data totaling 1680 words (a set is composed of a time and all the associated positions) and writing one physical tape record, except for the first record which has only 5 sets of data, totaling 140 words.

F. DESCRIPTION OF MODIFIED DBC FORTRAN INPUT ROUTINE

This section describes a Fortran II BCD input-routine capable of accepting variable-length fields.

1. Replace the DBC subprogram and its control card with deck input 00-.
2. The lists for "READ" and "READ INPUT TAPE" remain the same. Since format statements are ignored these may be anything which permits legal compilation. (Exception: see Hollerith No. 6 below).
3.
 - a. Fields must be separated by commas.
 - b. Blanks are treated as zeros and blank cards are ignored.
 - c. The number of fields per card is completely arbitrary and may vary from run to run. The first field of each read statement must start a new card.
 - d. The last field of every card must be terminated by an asterisk.
 - e. The type of conversion is determined by the first character of a field. Omission of this character results in continuing the previous type conversion. (The first field for each read statement must contain a type conversion entry.)
 - f. Signs are optional.
4. Floating Point Conversion
 - a. Identifying character F
 - b. Powers of 10 may be represented by the exponent preceded by an E.
 - c. Decimal points are optional. When not included it is assumed to be following the least significant digit of the number.
 - d. Decimal points are illegal for exponents.

Examples:

F + 5.8E.1,
F58,
F.58E2,
F58.,
F580.E-1,

Acceptable formats of the
same number

5. Integer Conversion

- a. Identifying Character X.
- b. The converted number modulo 32767 is stored in the decrement.
- c. Decimal points should not be punched.

Examples:

X150,
X15-,
X--150,

Acceptable formats of the
same number

6. Hollerith Conversion (Used only to replace format statements)

- a. Format statements may be replaced (but not the concluding 7's) by the Hollerith characters if the associated "READ" statement has no list.
- b. Identifying Character H
- c. The number of BCD words and a comma must immediately follow the H with no blanks.
- d. Maximum number of BCD words 99.
- e. Column 1 of any continuation card follows column 72 of the previous card.

Examples:

H4, --- (312, 7H1TEST- = E12.4-)

7. Examples:

- a. The following is an example of a read statement, and cards that could be used. (Format 5 is ignored.)

READ 5, N, L, J. (A(I), I = 1, J), (B(M), M = 1, L)

Deck 1

Card 1 X5, 2, ---4, F3.24E-08, -8.2E.4, 1, F9.2*

Card 2 3.2, 5.8E + 4*

Deck 2

Card 1 X5, X2, X4, F.324E-7, 82---, 1.0*

Card 2 92E-1, 320E-02*

Card 3 58.E3*

Deck 3

Card 1 X-----5, -----2*

Card 2

Card 3 F.00324E-05, -.82E + 5, .1E1, 9.2*

Card 4 3.2*

Card 5 5800-*

Error Stops:

<u>Stop</u>	<u>Error</u>	<u>Action to be taken</u>
HPR-1, 1	Card does not end with *or number of BCD words undefined.	Correct card, ready reader, and start.

<u>Stop</u>	<u>Error</u>	<u>Action to be taken</u>
HPR-1, 2	No comma between fields.	Start to treat unidentified character as a comma.
HPR-1, 3	Field undefined.	Start to treat as floating point conversion.




Figure A-1b. Flow Chart of the N-Body Program

G. JULIAN DATE AND CALENDAR DATE VS. TABLE-DAY

Julian Day	Calendar Day (O ^h E. T.)	Table Day	Julian Day	Calendar Day (O ^h E. T.)	Table Day
2436934.5	JAN 1, 1960		2436993.5	FEB 29, 1960	59
2436935.5	JAN 2, 1960	1	2436994.5	MAR 1, 1960	60
2436936.5	JAN 3, 1960	2	2436995.5	MAR 2, 1960	61
2436937.5	JAN 4, 1960	3	2436996.5	MAR 3, 1960	62
2436938.5	JAN 5, 1960	4	2436997.5	MAR 4, 1960	63
2436939.5	JAN 6, 1960	5	2436998.5	MAR 5, 1960	64
2436940.5	JAN 7, 1960	6	2436999.5	MAR 6, 1960	65
2436941.5	JAN 8, 1960	7	2437000.5	MAR 7, 1960	66
2436942.5	JAN 9, 1960	8	2437001.5	MAR 8, 1960	67
2436943.5	JAN 10, 1960	9	2437002.5	MAR 9, 1960	68
2436944.5	JAN 11, 1960	10	2437003.5	MAR 10, 1960	69
2436945.5	JAN 12, 1960	11	2437004.5	MAR 11, 1960	70
2436946.5	JAN 13, 1960	12	2437005.5	MAR 12, 1960	71
2436947.5	JAN 14, 1960	13	2437006.5	MAR 13, 1960	72
2436948.5	JAN 15, 1960	14	2437007.5	MAR 14, 1960	73
2436949.5	JAN 16, 1960	15	2437008.5	MAR 15, 1960	74
2436950.5	JAN 17, 1960	16	2437009.5	MAR 16, 1960	75
2436951.5	JAN 18, 1960	17	2437010.5	MAR 17, 1960	76
2436952.5	JAN 19, 1960	18	2437011.5	MAR 18, 1960	77
2436953.5	JAN 20, 1960	19	2437012.5	MAR 19, 1960	78
2436954.5	JAN 21, 1960	20	2437013.5	MAR 20, 1960	79
2436955.5	JAN 22, 1960	21	2437014.5	MAR 21, 1960	80
2436956.5	JAN 23, 1960	22	2437015.5	MAR 22, 1960	81
2436957.5	JAN 24, 1960	23	2437016.5	MAR 23, 1960	82
2436958.5	JAN 25, 1960	24	2437017.5	MAR 24, 1960	83
2436959.5	JAN 26, 1960	25	2437018.5	MAR 25, 1960	84
2436960.5	JAN 27, 1960	26	2437019.5	MAR 26, 1960	85
2436961.5	JAN 28, 1960	27	2437020.5	MAR 27, 1960	86
2436962.5	JAN 29, 1960	28	2437021.5	MAR 28, 1960	87
2436963.5	JAN 30, 1960	29	2437022.5	MAR 29, 1960	88
2436964.5	JAN 31, 1960	30	2437023.5	MAR 30, 1960	89
2436965.5	FEB 1, 1960	31	2437024.5	MAR 31, 1960	90
2436966.5	FEB 2, 1960	32	2437025.5	APR 1, 1960	91
2436967.5	FEB 3, 1960	33	2437026.5	APR 2, 1960	92
2436968.5	FEB 4, 1960	34	2437027.5	APR 3, 1960	93
2436969.5	FEB 5, 1960	35	2437028.5	APR 4, 1960	94
2436970.5	FEB 6, 1960	36	2437029.5	APR 5, 1960	95
2436971.5	FEB 7, 1960	37	2437030.5	APR 6, 1960	96
2436972.5	FEB 8, 1960	38	2437031.5	APR 7, 1960	97
2436973.5	FEB 9, 1960	39	2437032.5	APR 8, 1960	98
2436974.5	FEB 10, 1960	40	2437033.5	APR 9, 1960	99
2436975.5	FEB 11, 1960	41	2437034.5	APR 10, 1960	100
2436976.5	FEB 12, 1960	42	2437035.5	APR 11, 1960	101
2436977.5	FEB 13, 1960	43	2437036.5	APR 12, 1960	102
2436978.5	FEB 14, 1960	44	2437037.5	APR 13, 1960	103
2436979.5	FEB 15, 1960	45	2437038.5	APR 14, 1960	104
2436980.5	FEB 16, 1960	46	2437039.5	APR 15, 1960	105
2436981.5	FEB 17, 1960	47	2437040.5	APR 16, 1960	106
2436982.5	FEB 18, 1960	48	2437041.5	APR 17, 1960	107
2436983.5	FEB 19, 1960	49	2437042.5	APR 18, 1960	108
2436984.5	FEB 20, 1960	50	2437043.5	APR 19, 1960	109
2436985.5	FEB 21, 1960	51	2437044.5	APR 20, 1960	110
2436986.5	FEB 22, 1960	52	2437045.5	APR 21, 1960	111
2436987.5	FEB 23, 1960	53	2437046.5	APR 22, 1960	112
2436988.5	FEB 24, 1960	54	2437047.5	APR 23, 1960	113
2436989.5	FEB 25, 1960	55	2437048.5	APR 24, 1960	114
2436990.5	FEB 26, 1960	56	2437049.5	APR 25, 1960	115
2436991.5	FEB 27, 1960	57	2437050.5	APR 26, 1960	116
2436992.5	FEB 28, 1960	58	2437051.5	APR 27, 1960	117

2437052.5	APR 28, 1960	118	2437111.5	JUN 26, 1960	177
2437053.5	APR 29, 1960	119	2437112.5	JUN 27, 1960	178
2437054.5	APR 30, 1960	120	2437113.5	JUN 28, 1960	179
2437055.5	MAY 1, 1960	121	2437114.5	JUN 29, 1960	180
2437056.5	MAY 2, 1960	122	2437115.5	JUN 30, 1960	181
2437057.5	MAY 3, 1960	123	2437116.5	JUL 1, 1960	182
2437058.5	MAY 4, 1960	124	2437117.5	JUL 2, 1960	183
2437059.5	MAY 5, 1960	125	2437118.5	JUL 3, 1960	184
2437060.5	MAY 6, 1960	126	2437119.5	JUL 4, 1960	185
2437061.5	MAY 7, 1960	127	2437120.5	JUL 5, 1960	186
2437062.5	MAY 8, 1960	128	2437121.5	JUL 6, 1960	187
2437063.5	MAY 9, 1960	129	2437122.5	JUL 7, 1960	188
2437064.5	MAY 10, 1960	130	2437123.5	JUL 8, 1960	189
2437065.5	MAY 11, 1960	131	2437124.5	JUL 9, 1960	190
2437066.5	MAY 12, 1960	132	2437125.5	JUL 10, 1960	191
2437067.5	MAY 13, 1960	133	2437126.5	JUL 11, 1960	192
2437068.5	MAY 14, 1960	134	2437127.5	JUL 12, 1960	193
2437069.5	MAY 15, 1960	135	2437128.5	JUL 13, 1960	194
2437070.5	MAY 16, 1960	136	2437129.5	JUL 14, 1960	195
2437071.5	MAY 17, 1960	137	2437130.5	JUL 15, 1960	196
2437072.5	MAY 18, 1960	138	2437131.5	JUL 16, 1960	197
2437073.5	MAY 19, 1960	139	2437132.5	JUL 17, 1960	198
2437074.5	MAY 20, 1960	140	2437133.5	JUL 18, 1960	199
2437075.5	MAY 21, 1960	141	2437134.5	JUL 19, 1960	200
2437076.5	MAY 22, 1960	142	2437135.5	JUL 20, 1960	201
2437077.5	MAY 23, 1960	143	2437136.5	JUL 21, 1960	202
2437078.5	MAY 24, 1960	144	2437137.5	JUL 22, 1960	203
2437079.5	MAY 25, 1960	145	2437138.5	JUL 23, 1960	204
2437080.5	MAY 26, 1960	146	2437139.5	JUL 24, 1960	205
2437081.5	MAY 27, 1960	147	2437140.5	JUL 25, 1960	206
2437082.5	MAY 28, 1960	148	2437141.5	JUL 26, 1960	207
2437083.5	MAY 29, 1960	149	2437142.5	JUL 27, 1960	208
2437084.5	MAY 30, 1960	150	2437143.5	JUL 28, 1960	209
2437085.5	MAY 31, 1960	151	2437144.5	JUL 29, 1960	210
2437086.5	JUN 1, 1960	152	2437145.5	JUL 30, 1960	211
2437087.5	JUN 2, 1960	153	2437146.5	JUL 31, 1960	212
2437088.5	JUN 3, 1960	154	2437147.5	AUG 1, 1960	213
2437089.5	JUN 4, 1960	155	2437148.5	AUG 2, 1960	214
2437090.5	JUN 5, 1960	156	2437149.5	AUG 3, 1960	215
2437091.5	JUN 6, 1960	157	2437150.5	AUG 4, 1960	216
2437092.5	JUN 7, 1960	158	2437151.5	AUG 5, 1960	217
2437093.5	JUN 8, 1960	159	2437152.5	AUG 6, 1960	218
2437094.5	JUN 9, 1960	160	2437153.5	AUG 7, 1960	219
2437095.5	JUN 10, 1960	161	2437154.5	AUG 8, 1960	220
2437096.5	JUN 11, 1960	162	2437155.5	AUG 9, 1960	221
2437097.5	JUN 12, 1960	163	2437156.5	AUG 10, 1960	222
2437098.5	JUN 13, 1960	164	2437157.5	AUG 11, 1960	223
2437099.5	JUN 14, 1960	165	2437158.5	AUG 12, 1960	224
2437100.5	JUN 15, 1960	166	2437159.5	AUG 13, 1960	225
2437101.5	JUN 16, 1960	167	2437160.5	AUG 14, 1960	226
2437102.5	JUN 17, 1960	168	2437161.5	AUG 15, 1960	227
2437103.5	JUN 18, 1960	169	2437162.5	AUG 16, 1960	228
2437104.5	JUN 19, 1960	170	2437163.5	AUG 17, 1960	229
2437105.5	JUN 20, 1960	171	2437164.5	AUG 18, 1960	230
2437106.5	JUN 21, 1960	172	2437165.5	AUG 19, 1960	231
2437107.5	JUN 22, 1960	173	2437166.5	AUG 20, 1960	232
2437108.5	JUN 23, 1960	174	2437167.5	AUG 21, 1960	233
2437109.5	JUN 24, 1960	175	2437168.5	AUG 22, 1960	234
2437110.5	JUN 25, 1960	176	2437169.5	AUG 23, 1960	235

2437170.5	AUG 24, 1960	236	2437229.5	OCT 22, 1960	295
2437171.5	AUG 25, 1960	237	2437230.5	OCT 23, 1960	296
2437172.5	AUG 26, 1960	238	2437231.5	OCT 24, 1960	297
2437173.5	AUG 27, 1960	239	2437232.5	OCT 25, 1960	298
2437174.5	AUG 28, 1960	240	2437233.5	OCT 26, 1960	299
2437175.5	AUG 29, 1960	241	2437234.5	OCT 27, 1960	300
2437176.5	AUG 30, 1960	242	2437235.5	OCT 28, 1960	301
2437177.5	AUG 31, 1960	243	2437236.5	OCT 29, 1960	302
2437178.5	SEP 1, 1960	244	2437237.5	OCT 30, 1960	303
2437179.5	SEP 2, 1960	245	2437238.5	OCT 31, 1960	304
2437180.5	SEP 3, 1960	246	2437239.5	NOV 1, 1960	305
2437181.5	SEP 4, 1960	247	2437240.5	NOV 2, 1960	306
2437182.5	SEP 5, 1960	248	2437241.5	NOV 3, 1960	307
2437183.5	SEP 6, 1960	249	2437242.5	NOV 4, 1960	308
2437184.5	SEP 7, 1960	250	2437243.5	NOV 5, 1960	309
2437185.5	SEP 8, 1960	251	2437244.5	NOV 6, 1960	310
2437186.5	SEP 9, 1960	252	2437245.5	NOV 7, 1960	311
2437187.5	SEP 10, 1960	253	2437246.5	NOV 8, 1960	312
2437188.5	SEP 11, 1960	254	2437247.5	NOV 9, 1960	313
2437189.5	SEP 12, 1960	255	2437248.5	NOV 10, 1960	314
2437190.5	SEP 13, 1960	256	2437249.5	NOV 11, 1960	315
2437191.5	SEP 14, 1960	257	2437250.5	NOV 12, 1960	316
2437192.5	SEP 15, 1960	258	2437251.5	NOV 13, 1960	317
2437193.5	SEP 16, 1960	259	2437252.5	NOV 14, 1960	318
2437194.5	SEP 17, 1960	260	2437253.5	NOV 15, 1960	319
2437195.5	SEP 18, 1960	261	2437254.5	NOV 16, 1960	320
2437196.5	SEP 19, 1960	262	2437255.5	NOV 17, 1960	321
2437197.5	SEP 20, 1960	263	2437256.5	NOV 18, 1960	322
2437198.5	SEP 21, 1960	264	2437257.5	NOV 19, 1960	323
2437199.5	SEP 22, 1960	265	2437258.5	NOV 20, 1960	324
2437200.5	SEP 23, 1960	266	2437259.5	NOV 21, 1960	325
2437201.5	SEP 24, 1960	267	2437260.5	NOV 22, 1960	326
2437202.5	SEP 25, 1960	268	2437261.5	NOV 23, 1960	327
2437203.5	SEP 26, 1960	269	2437262.5	NOV 24, 1960	328
2437204.5	SEP 27, 1960	270	2437263.5	NOV 25, 1960	329
2437205.5	SEP 28, 1960	271	2437264.5	NOV 26, 1960	330
2437206.5	SEP 29, 1960	272	2437265.5	NOV 27, 1960	331
2437207.5	SEP 30, 1960	273	2437266.5	NOV 28, 1960	332
2437208.5	OCT 1, 1960	274	2437267.5	NOV 29, 1960	333
2437209.5	OCT 2, 1960	275	2437268.5	NOV 30, 1960	334
2437210.5	OCT 3, 1960	276	2437269.5	DEC 1, 1960	335
2437211.5	OCT 4, 1960	277	2437270.5	DEC 2, 1960	336
2437212.5	OCT 5, 1960	278	2437271.5	DEC 3, 1960	337
2437213.5	OCT 6, 1960	279	2437272.5	DEC 4, 1960	338
2437214.5	OCT 7, 1960	280	2437273.5	DEC 5, 1960	339
2437215.5	OCT 8, 1960	281	2437274.5	DEC 6, 1960	340
2437216.5	OCT 9, 1960	282	2437275.5	DEC 7, 1960	341
2437217.5	OCT 10, 1960	283	2437276.5	DEC 8, 1960	342
2437218.5	OCT 11, 1960	284	2437277.5	DEC 9, 1960	343
2437219.5	OCT 12, 1960	285	2437278.5	DEC 10, 1960	344
2437220.5	OCT 13, 1960	286	2437279.5	DEC 11, 1960	345
2437221.5	OCT 14, 1960	287	2437280.5	DEC 12, 1960	346
2437222.5	OCT 15, 1960	288	2437281.5	DEC 13, 1960	347
2437223.5	OCT 16, 1960	289	2437282.5	DEC 14, 1960	348
2437224.5	OCT 17, 1960	290	2437283.5	DEC 15, 1960	349
2437225.5	OCT 18, 1960	291	2437284.5	DEC 16, 1960	350
2437226.5	OCT 19, 1960	292	2437285.5	DEC 17, 1960	351
2437227.5	OCT 20, 1960	293	2437286.5	DEC 18, 1960	352
2437228.5	OCT 21, 1960	294	2437287.5	DEC 19, 1960	353

2437288.5	DEC 20, 1960	354	2437347.5	FEB 17, 1961	413
2437289.5	DEC 21, 1960	355	2437348.5	FEB 18, 1961	414
2437290.5	DEC 22, 1960	356	2437349.5	FEB 19, 1961	415
2437291.5	DEC 23, 1960	357	2437350.5	FEB 20, 1961	416
2437292.5	DEC 24, 1960	358	2437351.5	FEB 21, 1961	417
2437293.5	DEC 25, 1960	359	2437352.5	FEB 22, 1961	418
2437294.5	DEC 26, 1960	360	2437353.5	FEB 23, 1961	419
2437295.5	DEC 27, 1960	361	2437354.5	FEB 24, 1961	420
2437296.5	DEC 28, 1960	362	2437355.5	FEB 25, 1961	421
2437297.5	DEC 29, 1960	363	2437356.5	FEB 26, 1961	422
2437298.5	DEC 30, 1960	364	2437357.5	FEB 27, 1961	423
2437299.5	DEC 31, 1960	365	2437358.5	FEB 28, 1961	424
2437300.5	JAN 1, 1961	366	2437359.5	MAR 1, 1961	425
2437301.5	JAN 2, 1961	367	2437360.5	MAR 2, 1961	426
2437302.5	JAN 3, 1961	368	2437361.5	MAR 3, 1961	427
2437303.5	JAN 4, 1961	369	2437362.5	MAR 4, 1961	428
2437304.5	JAN 5, 1961	370	2437363.5	MAR 5, 1961	429
2437305.5	JAN 6, 1961	371	2437364.5	MAR 6, 1961	430
2437306.5	JAN 7, 1961	372	2437365.5	MAR 7, 1961	431
2437307.5	JAN 8, 1961	373	2437366.5	MAR 8, 1961	432
2437308.5	JAN 9, 1961	374	2437367.5	MAR 9, 1961	433
2437309.5	JAN 10, 1961	375	2437368.5	MAR 10, 1961	434
2437310.5	JAN 11, 1961	376	2437369.5	MAR 11, 1961	435
2437311.5	JAN 12, 1961	377	2437370.5	MAR 12, 1961	436
2437312.5	JAN 13, 1961	378	2437371.5	MAR 13, 1961	437
2437313.5	JAN 14, 1961	379	2437372.5	MAR 14, 1961	438
2437314.5	JAN 15, 1961	380	2437373.5	MAR 15, 1961	439
2437315.5	JAN 16, 1961	381	2437374.5	MAR 15, 1961	440
2437316.5	JAN 17, 1961	382	2437375.5	MAR 17, 1961	441
2437317.5	JAN 18, 1961	383	2437376.5	MAR 18, 1961	442
2437318.5	JAN 19, 1961	384	2437377.5	MAR 19, 1961	443
2437319.5	JAN 20, 1961	385	2437378.5	MAR 20, 1961	444
2437320.5	JAN 21, 1961	386	2437379.5	MAR 21, 1961	445
2437321.5	JAN 22, 1961	387	2437380.5	MAR 22, 1961	446
2437322.5	JAN 23, 1961	388	2437381.5	MAR 23, 1961	447
2437323.5	JAN 24, 1961	389	2437382.5	MAR 24, 1961	448
2437324.5	JAN 25, 1961	390	2437383.5	MAR 25, 1961	449
2437325.5	JAN 26, 1961	391	2437384.5	MAR 26, 1961	450
2437326.5	JAN 27, 1961	392	2437385.5	MAR 27, 1961	451
2437327.5	JAN 28, 1961	393	2437386.5	MAR 28, 1961	452
2437328.5	JAN 29, 1961	394	2437387.5	MAR 29, 1961	453
2437329.5	JAN 30, 1961	395	2437388.5	MAR 30, 1961	454
2437330.5	JAN 31, 1961	396	2437389.5	MAR 31, 1961	455
2437331.5	FEB 1, 1961	397	2437390.5	APR 1, 1961	456
2437332.5	FEB 2, 1961	398	2437391.5	APR 2, 1961	457
2437333.5	FEB 3, 1961	399	2437392.5	APR 3, 1961	458
2437334.5	FEB 4, 1961	400	2437393.5	APR 4, 1961	459
2437335.5	FEB 5, 1961	401	2437394.5	APR 5, 1961	460
2437336.5	FEB 6, 1961	402	2437395.5	APR 6, 1961	461
2437337.5	FEB 7, 1961	403	2437396.5	APR 7, 1961	462
2437338.5	FEB 8, 1961	404	2437397.5	APR 8, 1961	463
2437339.5	FEB 9, 1961	405	2437398.5	APR 9, 1961	464
2437340.5	FEB 10, 1961	406	2437399.5	APR 10, 1961	465
2437341.5	FEB 11, 1961	407	2437400.5	APR 11, 1961	466
2437342.5	FEB 12, 1961	408	2437401.5	APR 12, 1961	467
2437343.5	FEB 13, 1961	409	2437402.5	APR 13, 1961	468
2437344.5	FEB 14, 1961	410	2437403.5	APR 14, 1961	469
2437345.5	FEB 15, 1961	411	2437404.5	APR 15, 1961	470
2437346.5	FEB 16, 1961	412	2437405.5	APR 16, 1961	471

2437406.5	APR 17, 1961	472	2437465.5	JUN 15, 1961	531
2437407.5	APR 18, 1961	473	2437466.5	JUN 16, 1961	532
2437408.5	APR 19, 1961	474	2437467.5	JUN 17, 1961	533
2437409.5	APR 20, 1961	475	2437468.5	JUN 18, 1961	534
2437410.5	APR 21, 1961	476	2437469.5	JUN 19, 1961	535
2437411.5	APR 22, 1961	477	2437470.5	JUN 20, 1961	536
2437412.5	APR 23, 1961	478	2437471.5	JUN 21, 1961	537
2437413.5	APR 24, 1961	479	2437472.5	JUN 22, 1961	538
2437414.5	APR 25, 1961	480	2437473.5	JUN 23, 1961	539
2437415.5	APR 26, 1961	481	2437474.5	JUN 24, 1961	540
2437416.5	APR 27, 1961	482	2437475.5	JUN 25, 1961	541
2437417.5	APR 28, 1961	483	2437476.5	JUN 26, 1961	542
2437418.5	APR 29, 1961	484	2437477.5	JUN 27, 1961	543
2437419.5	APR 30, 1961	485	2437478.5	JUN 28, 1961	544
2437420.5	MAY 1, 1961	486	2437479.5	JUN 29, 1961	545
2437421.5	MAY 2, 1961	487	2437480.5	JUN 30, 1961	546
2437422.5	MAY 3, 1961	488	2437481.5	JUL 1, 1961	547
2437423.5	MAY 4, 1961	489	2437482.5	JUL 2, 1961	548
2437424.5	MAY 5, 1961	490	2437483.5	JUL 3, 1961	549
2437425.5	MAY 6, 1961	491	2437484.5	JUL 4, 1961	550
2437426.5	MAY 7, 1961	492	2437485.5	JUL 5, 1961	551
2437427.5	MAY 8, 1961	493	2437486.5	JUL 6, 1961	552
2437428.5	MAY 9, 1961	494	2437487.5	JUL 7, 1961	553
2437429.5	MAY 10, 1961	495	2437488.5	JUL 8, 1961	554
2437430.5	MAY 11, 1961	496	2437489.5	JUL 9, 1961	555
2437431.5	MAY 12, 1961	497	2437490.5	JUL 10, 1961	556
2437432.5	MAY 13, 1961	498	2437491.5	JUL 11, 1961	557
2437433.5	MAY 14, 1961	499	2437492.5	JUL 12, 1961	558
2437434.5	MAY 15, 1961	500	2437493.5	JUL 13, 1961	559
2437435.5	MAY 16, 1961	501	2437494.5	JUL 14, 1961	560
2437436.5	MAY 17, 1961	502	2437495.5	JUL 15, 1961	561
2437437.5	MAY 18, 1961	503	2437496.5	JUL 16, 1961	562
2437438.5	MAY 19, 1961	504	2437497.5	JUL 17, 1961	563
2437439.5	MAY 20, 1961	505	2437498.5	JUL 18, 1961	564
2437440.5	MAY 21, 1961	506	2437499.5	JUL 19, 1961	565
2437441.5	MAY 22, 1961	507	2437500.5	JUL 20, 1961	566
2437442.5	MAY 23, 1961	508	2437501.5	JUL 21, 1961	567
2437443.5	MAY 24, 1961	509	2437502.5	JUL 22, 1961	568
2437444.5	MAY 25, 1961	510	2437503.5	JUL 23, 1961	569
2437445.5	MAY 26, 1961	511	2437504.5	JUL 24, 1961	570
2437446.5	MAY 27, 1961	512	2437505.5	JUL 25, 1961	571
2437447.5	MAY 28, 1961	513	2437506.5	JUL 26, 1961	572
2437448.5	MAY 29, 1961	514	2437507.5	JUL 27, 1961	573
2437449.5	MAY 30, 1961	515	2437508.5	JUL 28, 1961	574
2437450.5	MAY 31, 1961	516	2437509.5	JUL 29, 1961	575
2437451.5	JUN 1, 1961	517	2437510.5	JUL 30, 1961	576
2437452.5	JUN 2, 1961	518	2437511.5	JUL 31, 1961	577
2437453.5	JUN 3, 1961	519	2437512.5	AUG 1, 1961	578
2437454.5	JUN 4, 1961	520	2437513.5	AUG 2, 1961	579
2437455.5	JUN 5, 1961	521	2437514.5	AUG 3, 1961	580
2437456.5	JUN 6, 1961	522	2437515.5	AUG 4, 1961	581
2437457.5	JUN 7, 1961	523	2437516.5	AUG 5, 1961	582
2437458.5	JUN 8, 1961	524	2437517.5	AUG 6, 1961	583
2437459.5	JUN 9, 1961	525	2437518.5	AUG 7, 1961	584
2437460.5	JUN 10, 1961	526	2437519.5	AUG 8, 1961	585
2437461.5	JUN 11, 1961	527	2437520.5	AUG 9, 1961	586
2437462.5	JUN 12, 1961	528	2437521.5	AUG 10, 1961	587
2437463.5	JUN 13, 1961	529	2437522.5	AUG 11, 1961	588
2437464.5	JUN 14, 1961	530	2437523.5	AUG 12, 1961	589

2437524.5	AUG 13, 1961	590	2437583.5	OCT 11, 1961	649
2437525.5	AUG 14, 1961	591	2437584.5	OCT 12, 1961	650
2437526.5	AUG 15, 1961	592	2437585.5	OCT 13, 1961	651
2437527.5	AUG 16, 1961	593	2437586.5	OCT 14, 1961	652
2437528.5	AUG 17, 1961	594	2437587.5	OCT 15, 1961	653
2437529.5	AUG 18, 1961	595	2437588.5	OCT 16, 1961	654
2437530.5	AUG 19, 1961	596	2437589.5	OCT 17, 1961	655
2437531.5	AUG 20, 1961	597	2437590.5	OCT 18, 1961	656
2437532.5	AUG 21, 1961	598	2437591.5	OCT 19, 1961	657
2437533.5	AUG 22, 1961	599	2437592.5	OCT 20, 1961	658
2437534.5	AUG 23, 1961	600	2437593.5	OCT 21, 1961	659
2437535.5	AUG 24, 1961	601	2437594.5	OCT 22, 1961	660
2437536.5	AUG 25, 1961	602	2437595.5	OCT 23, 1961	661
2437537.5	AUG 26, 1961	603	2437596.5	OCT 24, 1961	662
2437538.5	AUG 27, 1961	604	2437597.5	OCT 25, 1961	663
2437539.5	AUG 28, 1961	605	2437598.5	OCT 26, 1961	664
2437540.5	AUG 29, 1961	606	2437599.5	OCT 27, 1961	665
2437541.5	AUG 30, 1961	607	2437600.5	OCT 28, 1961	666
2437542.5	AUG 31, 1961	608	2437601.5	OCT 29, 1961	667
2437543.5	SEP 1, 1961	609	2437602.5	OCT 30, 1961	668
2437544.5	SEP 2, 1961	610	2437603.5	OCT 31, 1961	669
2437545.5	SEP 3, 1961	611	2437604.5	NOV 1, 1961	670
2437546.5	SEP 4, 1961	612	2437605.5	NOV 2, 1961	671
2437547.5	SEP 5, 1961	613	2437606.5	NOV 3, 1961	672
2437548.5	SEP 6, 1961	614	2437607.5	NOV 4, 1961	673
2437549.5	SEP 7, 1961	615	2437608.5	NOV 5, 1961	674
2437550.5	SEP 8, 1961	616	2437609.5	NOV 6, 1961	675
2437551.5	SEP 9, 1961	617	2437610.5	NOV 7, 1961	676
2437552.5	SEP 10, 1961	618	2437611.5	NOV 8, 1961	677
2437553.5	SEP 11, 1961	619	2437612.5	NOV 9, 1961	678
2437554.5	SEP 12, 1961	620	2437613.5	NOV 10, 1961	679
2437555.5	SEP 13, 1961	621	2437614.5	NOV 11, 1961	680
2437556.5	SEP 14, 1961	622	2437615.5	NOV 12, 1961	681
2437557.5	SEP 15, 1961	623	2437616.5	NOV 13, 1961	682
2437558.5	SEP 16, 1961	624	2437617.5	NOV 14, 1961	683
2437559.5	SEP 17, 1961	625	2437618.5	NOV 15, 1961	684
2437560.5	SEP 18, 1961	626	2437619.5	NOV 16, 1961	685
2437561.5	SEP 19, 1961	627	2437620.5	NOV 17, 1961	686
2437562.5	SEP 20, 1961	628	2437621.5	NOV 18, 1961	687
2437563.5	SEP 21, 1961	629	2437622.5	NOV 19, 1961	688
2437564.5	SEP 22, 1961	630	2437623.5	NOV 20, 1961	689
2437565.5	SEP 23, 1961	631	2437624.5	NOV 21, 1961	690
2437566.5	SEP 24, 1961	632	2437625.5	NOV 22, 1961	691
2437567.5	SEP 25, 1961	633	2437626.5	NOV 23, 1961	692
2437568.5	SEP 26, 1961	634	2437627.5	NOV 24, 1961	693
2437569.5	SEP 27, 1961	635	2437628.5	NOV 25, 1961	694
2437570.5	SEP 28, 1961	636	2437629.5	NOV 26, 1961	695
2437571.5	SEP 29, 1961	637	2437630.5	NOV 27, 1961	696
2437572.5	SEP 30, 1961	638	2437631.5	NOV 28, 1961	697
2437573.5	OCT 1, 1961	639	2437632.5	NOV 29, 1961	698
2437574.5	OCT 2, 1961	640	2437633.5	NOV 30, 1961	699
2437575.5	OCT 3, 1961	641	2437634.5	DEC 1, 1961	700
2437576.5	OCT 4, 1961	642	2437635.5	DEC 2, 1961	701
2437577.5	OCT 5, 1961	643	2437636.5	DEC 3, 1961	702
2437578.5	OCT 6, 1961	644	2437637.5	DEC 4, 1961	703
2437579.5	OCT 7, 1961	645	2437638.5	DEC 5, 1961	704
2437580.5	OCT 8, 1961	646	2437639.5	DEC 6, 1961	705
2437581.5	OCT 9, 1961	647	2437640.5	DEC 7, 1961	706
2437582.5	OCT 10, 1961	648	2437641.5	DEC 8, 1961	707

2437642.5	DEC 9, 1961	708	2437701.5	FEB 6, 1962	767
2437643.5	DEC 10, 1961	709	2437702.5	FEB 7, 1962	768
2437644.5	DEC 11, 1961	710	2437703.5	FEB 8, 1962	769
2437645.5	DEC 12, 1961	711	2437704.5	FEB 9, 1962	770
2437646.5	DEC 13, 1961	712	2437705.5	FEB 10, 1962	771
2437647.5	DEC 14, 1961	713	2437706.5	FEB 11, 1962	772
2437648.5	DEC 15, 1961	714	2437707.5	FEB 12, 1962	773
2437649.5	DEC 16, 1961	715	2437708.5	FEB 13, 1962	774
2437650.5	DEC 17, 1961	716	2437709.5	FEB 14, 1962	775
2437651.5	DEC 18, 1961	717	2437710.5	FEB 15, 1962	776
2437652.5	DEC 19, 1961	718	2437711.5	FEB 16, 1962	777
2437653.5	DEC 20, 1961	719	2437712.5	FEB 17, 1962	778
2437654.5	DEC 21, 1961	720	2437713.5	FEB 18, 1962	779
2437655.5	DEC 22, 1961	721	2437714.5	FEB 19, 1962	780
2437656.5	DEC 23, 1961	722	2437715.5	FEB 20, 1962	781
2437657.5	DEC 24, 1961	723	2437716.5	FEB 21, 1962	782
2437658.5	DEC 25, 1961	724	2437717.5	FEB 22, 1962	783
2437659.5	DEC 26, 1961	725	2437718.5	FEB 23, 1962	784
2437660.5	DEC 27, 1961	726	2437719.5	FEB 24, 1962	785
2437661.5	DEC 28, 1961	727	2437720.5	FEB 25, 1962	786
2437662.5	DEC 29, 1961	728	2437721.5	FEB 26, 1962	787
2437663.5	DEC 30, 1961	729	2437722.5	FEB 27, 1962	788
2437664.5	DEC 31, 1961	730	2437723.5	FEB 28, 1962	789
2437665.5	JAN 1, 1962	731	2437724.5	MAR 1, 1962	790
2437666.5	JAN 2, 1962	732	2437725.5	MAR 2, 1962	791
2437667.5	JAN 3, 1962	733	2437726.5	MAR 3, 1962	792
2437668.5	JAN 4, 1962	734	2437727.5	MAR 4, 1962	793
2437669.5	JAN 5, 1962	735	2437728.5	MAR 5, 1962	794
2437670.5	JAN 6, 1962	736	2437729.5	MAR 6, 1962	795
2437671.5	JAN 7, 1962	737	2437730.5	MAR 7, 1962	796
2437672.5	JAN 8, 1962	738	2437731.5	MAR 8, 1962	797
2437673.5	JAN 9, 1962	739	2437732.5	MAR 9, 1962	798
2437674.5	JAN 10, 1962	740	2437733.5	MAR 10, 1962	799
2437675.5	JAN 11, 1962	741	2437734.5	MAR 11, 1962	800
2437676.5	JAN 12, 1962	742	2437735.5	MAR 12, 1962	801
2437677.5	JAN 13, 1962	743	2437736.5	MAR 13, 1962	802
2437678.5	JAN 14, 1962	744	2437737.5	MAR 14, 1962	803
2437679.5	JAN 15, 1962	745	2437738.5	MAR 15, 1962	804
2437680.5	JAN 16, 1962	746	2437739.5	MAR 16, 1962	805
2437681.5	JAN 17, 1962	747	2437740.5	MAR 17, 1962	806
2437682.5	JAN 18, 1962	748	2437741.5	MAR 18, 1962	807
2437683.5	JAN 19, 1962	749	2437742.5	MAR 19, 1962	808
2437684.5	JAN 20, 1962	750	2437743.5	MAR 20, 1962	809
2437685.5	JAN 21, 1962	751	2437744.5	MAR 21, 1962	810
2437686.5	JAN 22, 1962	752	2437745.5	MAR 22, 1962	811
2437687.5	JAN 23, 1962	753	2437746.5	MAR 23, 1962	812
2437688.5	JAN 24, 1962	754	2437747.5	MAR 24, 1962	813
2437689.5	JAN 25, 1962	755	2437748.5	MAR 25, 1962	814
2437690.5	JAN 26, 1962	756	2437749.5	MAR 26, 1962	815
2437691.5	JAN 27, 1962	757	2437750.5	MAR 27, 1962	816
2437692.5	JAN 28, 1962	758	2437751.5	MAR 28, 1962	817
2437693.5	JAN 29, 1962	759	2437752.5	MAR 29, 1962	818
2437694.5	JAN 30, 1962	760	2437753.5	MAR 30, 1962	819
2437695.5	JAN 31, 1962	761	2437754.5	MAR 31, 1962	820
2437696.5	FEB 1, 1962	762	2437755.5	APR 1, 1962	821
2437697.5	FEB 2, 1962	763	2437756.5	APR 2, 1962	822
2437698.5	FEB 3, 1962	764	2437757.5	APR 3, 1962	823
2437699.5	FEB 4, 1962	765	2437758.5	APR 4, 1962	824
2437700.5	FEB 5, 1962	766	2437759.5	APR 5, 1962	825

2437760.5	APR 6, 1962	826	2437819.5	JUN 4, 1962	885
2437761.5	APR 7, 1962	827	2437820.5	JUN 5, 1962	886
2437762.5	APR 8, 1962	828	2437821.5	JUN 6, 1962	887
2437763.5	APR 9, 1962	829	2437822.5	JUN 7, 1962	888
2437764.5	APR 10, 1962	830	2437823.5	JUN 8, 1962	889
2437765.5	APR 11, 1962	831	2437824.5	JUN 9, 1962	890
2437766.5	APR 12, 1962	832	2437825.5	JUN 10, 1962	891
2437767.5	APR 13, 1962	833	2437826.5	JUN 11, 1962	892
2437768.5	APR 14, 1962	834	2437827.5	JUN 12, 1962	893
2437769.5	APR 15, 1962	835	2437828.5	JUN 13, 1962	894
2437770.5	APR 16, 1962	836	2437829.5	JUN 14, 1962	895
2437771.5	APR 17, 1962	837	2437830.5	JUN 15, 1962	896
2437772.5	APR 18, 1962	838	2437831.5	JUN 16, 1962	897
2437773.5	APR 19, 1962	839	2437832.5	JUN 17, 1962	898
2437774.5	APR 20, 1962	840	2437833.5	JUN 18, 1962	899
2437775.5	APR 21, 1962	841	2437834.5	JUN 19, 1962	900
2437776.5	APR 22, 1962	842	2437835.5	JUN 20, 1962	901
2437777.5	APR 23, 1962	843	2437836.5	JUN 21, 1962	902
2437778.5	APR 24, 1962	844	2437837.5	JUN 22, 1962	903
2437779.5	APR 25, 1962	845	2437838.5	JUN 23, 1962	904
2437780.5	APR 26, 1962	846	2437839.5	JUN 24, 1962	905
2437781.5	APR 27, 1962	847	2437840.5	JUN 25, 1962	906
2437782.5	APR 28, 1962	848	2437841.5	JUN 26, 1962	907
2437783.5	APR 29, 1962	849	2437842.5	JUN 27, 1962	908
2437784.5	APR 30, 1962	850	2437843.5	JUN 28, 1962	909
2437785.5	MAY 1, 1962	851	2437844.5	JUN 29, 1962	910
2437786.5	MAY 2, 1962	852	2437845.5	JUN 30, 1962	911
2437787.5	MAY 3, 1962	853	2437846.5	JUL 1, 1962	912
2437788.5	MAY 4, 1962	854	2437847.5	JUL 2, 1962	913
2437789.5	MAY 5, 1962	855	2437848.5	JUL 3, 1962	914
2437790.5	MAY 6, 1962	856	2437849.5	JUL 4, 1962	915
2437791.5	MAY 7, 1962	857	2437850.5	JUL 5, 1962	916
2437792.5	MAY 8, 1962	858	2437851.5	JUL 6, 1962	917
2437793.5	MAY 9, 1962	859	2437852.5	JUL 7, 1962	918
2437794.5	MAY 10, 1962	860	2437853.5	JUL 8, 1962	919
2437795.5	MAY 11, 1962	861	2437854.5	JUL 9, 1962	920
2437796.5	MAY 12, 1962	862	2437855.5	JUL 10, 1962	921
2437797.5	MAY 13, 1962	863	2437856.5	JUL 11, 1962	922
2437798.5	MAY 14, 1962	864	2437857.5	JUL 12, 1962	923
2437799.5	MAY 15, 1962	865	2437858.5	JUL 13, 1962	924
2437800.5	MAY 16, 1962	866	2437859.5	JUL 14, 1962	925
2437801.5	MAY 17, 1962	867	2437860.5	JUL 15, 1962	926
2437802.5	MAY 18, 1962	868	2437861.5	JUL 16, 1962	927
2437803.5	MAY 19, 1962	869	2437862.5	JUL 17, 1962	928
2437804.5	MAY 20, 1962	870	2437863.5	JUL 18, 1962	929
2437805.5	MAY 21, 1962	871	2437864.5	JUL 19, 1962	930
2437806.5	MAY 22, 1962	872	2437865.5	JUL 20, 1962	931
2437807.5	MAY 23, 1962	873	2437866.5	JUL 21, 1962	932
2437808.5	MAY 24, 1962	874	2437867.5	JUL 22, 1962	933
2437809.5	MAY 25, 1962	875	2437868.5	JUL 23, 1962	934
2437810.5	MAY 26, 1962	876	2437869.5	JUL 24, 1962	935
2437811.5	MAY 27, 1962	877	2437870.5	JUL 25, 1962	936
2437812.5	MAY 28, 1962	878	2437871.5	JUL 26, 1962	937
2437813.5	MAY 29, 1962	879	2437872.5	JUL 27, 1962	938
2437814.5	MAY 30, 1962	880	2437873.5	JUL 28, 1962	939
2437815.5	MAY 31, 1962	881	2437874.5	JUL 29, 1962	940
2437816.5	JUN 1, 1962	882	2437875.5	JUL 30, 1962	941
2437817.5	JUN 2, 1962	883	2437876.5	JUL 31, 1962	942
2437818.5	JUN 3, 1962	884	2437877.5	AUG 1, 1962	943

2437878.5	AUG 2, 1962	944	2437937.5	SEP 30, 1962	1003
2437879.5	AUG 3, 1962	945	2437938.5	OCT 1, 1962	1004
2437880.5	AUG 4, 1962	946	2437939.5	OCT 2, 1962	1005
2437881.5	AUG 5, 1962	947	2437940.5	OCT 3, 1962	1006
2437882.5	AUG 6, 1962	948	2437941.5	OCT 4, 1962	1007
2437883.5	AUG 7, 1962	949	2437942.5	OCT 5, 1962	1008
2437884.5	AUG 8, 1962	950	2437943.5	OCT 6, 1962	1009
2437885.5	AUG 9, 1962	951	2437944.5	OCT 7, 1962	1010
2437886.5	AUG 10, 1962	952	2437945.5	OCT 8, 1962	1011
2437887.5	AUG 11, 1962	953	2437946.5	OCT 9, 1962	1012
2437888.5	AUG 12, 1962	954	2437947.5	OCT 10, 1962	1013
2437889.5	AUG 13, 1962	955	2437948.5	OCT 11, 1962	1014
2437890.5	AUG 14, 1962	956	2437949.5	OCT 12, 1962	1015
2437891.5	AUG 15, 1962	957	2437950.5	OCT 13, 1962	1016
2437892.5	AUG 16, 1962	958	2437951.5	OCT 14, 1962	1017
2437893.5	AUG 17, 1962	959	2437952.5	OCT 15, 1962	1018
2437894.5	AUG 18, 1962	960	2437953.5	OCT 16, 1962	1019
2437895.5	AUG 19, 1962	961	2437954.5	OCT 17, 1962	1020
2437896.5	AUG 20, 1962	962	2437955.5	OCT 18, 1962	1021
2437897.5	AUG 21, 1962	963	2437956.5	OCT 19, 1962	1022
2437898.5	AUG 22, 1962	964	2437957.5	OCT 20, 1962	1023
2437899.5	AUG 23, 1962	965	2437958.5	OCT 21, 1962	1024
2437900.5	AUG 24, 1962	966	2437959.5	OCT 22, 1962	1025
2437901.5	AUG 25, 1962	967	2437960.5	OCT 23, 1962	1026
2437902.5	AUG 26, 1962	968	2437961.5	OCT 24, 1962	1027
2437903.5	AUG 27, 1962	969	2437962.5	OCT 25, 1962	1028
2437904.5	AUG 28, 1962	970	2437963.5	OCT 26, 1962	1029
2437905.5	AUG 29, 1962	971	2437964.5	OCT 27, 1962	1030
2437906.5	AUG 30, 1962	972	2437965.5	OCT 28, 1962	1031
2437907.5	AUG 31, 1962	973	2437966.5	OCT 29, 1962	1032
2437908.5	SEP 1, 1962	974	2437967.5	OCT 30, 1962	1033
2437909.5	SEP 2, 1962	975	2437968.5	OCT 31, 1962	1034
2437910.5	SEP 3, 1962	976	2437969.5	NOV 1, 1962	1035
2437911.5	SEP 4, 1962	977	2437970.5	NOV 2, 1962	1036
2437912.5	SEP 5, 1962	978	2437971.5	NOV 3, 1962	1037
2437913.5	SEP 6, 1962	979	2437972.5	NOV 4, 1962	1038
2437914.5	SEP 7, 1962	980	2437973.5	NOV 5, 1962	1039
2437915.5	SEP 8, 1962	981	2437974.5	NOV 6, 1962	1040
2437916.5	SEP 9, 1962	982	2437975.5	NOV 7, 1962	1041
2437917.5	SEP 10, 1962	983	2437976.5	NOV 8, 1962	1042
2437918.5	SEP 11, 1962	984	2437977.5	NOV 9, 1962	1043
2437919.5	SEP 12, 1962	985	2437978.5	NOV 10, 1962	1044
2437920.5	SEP 13, 1962	986	2437979.5	NOV 11, 1962	1045
2437921.5	SEP 14, 1962	987	2437980.5	NOV 12, 1962	1046
2437922.5	SEP 15, 1962	988	2437981.5	NOV 13, 1962	1047
2437923.5	SEP 16, 1962	989	2437982.5	NOV 14, 1962	1048
2437924.5	SEP 17, 1962	990	2437983.5	NOV 15, 1962	1049
2437925.5	SEP 18, 1962	991	2437984.5	NOV 16, 1962	1050
2437926.5	SEP 19, 1962	992	2437985.5	NOV 17, 1962	1051
2437927.5	SEP 20, 1962	993	2437986.5	NOV 18, 1962	1052
2437928.5	SEP 21, 1962	994	2437987.5	NOV 19, 1962	1053
2437929.5	SEP 22, 1962	995	2437988.5	NOV 20, 1962	1054
2437930.5	SEP 23, 1962	996	2437989.5	NOV 21, 1962	1055
2437931.5	SEP 24, 1962	997	2437990.5	NOV 22, 1962	1056
2437932.5	SEP 25, 1962	998	2437991.5	NOV 23, 1962	1057
2437933.5	SEP 26, 1962	999	2437992.5	NOV 24, 1962	1058
2437934.5	SEP 27, 1962	1000	2437993.5	NOV 25, 1962	1059
2437935.5	SEP 28, 1962	1001	2437994.5	NOV 26, 1962	1060
2437936.5	SEP 29, 1962	1002	2437995.5	NOV 27, 1962	1061

2437996.5	NOV 28, 1962	1062	2438055.5	JAN 26, 1963	1121
2437997.5	NOV 29, 1962	1063	2438056.5	JAN 27, 1963	1122
2437998.5	NOV 30, 1962	1064	2438057.5	JAN 28, 1963	1123
2437999.5	DEC 1, 1962	1065	2438058.5	JAN 29, 1963	1124
2438000.5	DEC 2, 1962	1066	2438059.5	JAN 30, 1963	1125
2438001.5	DEC 3, 1962	1067	2438060.5	JAN 31, 1963	1126
2438002.5	DEC 4, 1962	1068	2438061.5	FEB 1, 1963	1127
2438003.5	DEC 5, 1962	1069	2438062.5	FEB 2, 1963	1128
2438004.5	DEC 6, 1962	1070	2438063.5	FEB 3, 1963	1129
2438005.5	DEC 7, 1962	1071	2438064.5	FEB 4, 1963	1130
2438006.5	DEC 8, 1962	1072	2438065.5	FEB 5, 1963	1131
2438007.5	DEC 9, 1962	1073	2438066.5	FEB 6, 1963	1132
2438008.5	DEC 10, 1962	1074	2438067.5	FEB 7, 1963	1133
2438009.5	DEC 11, 1962	1075	2438068.5	FEB 8, 1963	1134
2438010.5	DEC 12, 1962	1076	2438069.5	FEB 9, 1963	1135
2438011.5	DEC 13, 1962	1077	2438070.5	FEB 10, 1963	1136
2438012.5	DEC 14, 1962	1078	2438071.5	FEB 11, 1963	1137
2438013.5	DEC 15, 1962	1079	2438072.5	FEB 12, 1963	1138
2438014.5	DEC 16, 1962	1080	2438073.5	FEB 13, 1963	1139
2438015.5	DEC 17, 1962	1081	2438074.5	FEB 14, 1963	1140
2438016.5	DEC 18, 1962	1082	2438075.5	FEB 15, 1963	1141
2438017.5	DEC 19, 1962	1083	2438076.5	FEB 16, 1963	1142
2438018.5	DEC 20, 1962	1084	2438077.5	FEB 17, 1963	1143
2438019.5	DEC 21, 1962	1085	2438078.5	FEB 18, 1963	1144
2438020.5	DEC 22, 1962	1086	2438079.5	FEB 19, 1963	1145
2438021.5	DEC 23, 1962	1087	2438080.5	FEB 20, 1963	1146
2438022.5	DEC 24, 1962	1088	2438081.5	FEB 21, 1963	1147
2438023.5	DEC 25, 1962	1089	2438082.5	FEB 22, 1963	1148
2438024.5	DEC 26, 1962	1090	2438083.5	FEB 23, 1963	1149
2438025.5	DEC 27, 1962	1091	2438084.5	FEB 24, 1963	1150
2438026.5	DEC 28, 1962	1092	2438085.5	FEB 25, 1963	1151
2438027.5	DEC 29, 1962	1093	2438086.5	FEB 26, 1963	1152
2438028.5	DEC 30, 1962	1094	2438087.5	FEB 27, 1963	1153
2438029.5	DEC 31, 1962	1095	2438088.5	FEB 28, 1963	1154
2438030.5	JAN 1, 1963	1096	2438089.5	MAR 1, 1963	1155
2438031.5	JAN 2, 1963	1097	2438090.5	MAR 2, 1963	1156
2438032.5	JAN 3, 1963	1098	2438091.5	MAR 3, 1963	1157
2438033.5	JAN 4, 1963	1099	2438092.5	MAR 4, 1963	1158
2438034.5	JAN 5, 1963	1100	2438093.5	MAR 5, 1963	1159
2438035.5	JAN 6, 1963	1101	2438094.5	MAR 6, 1963	1160
2438036.5	JAN 7, 1963	1102	2438095.5	MAR 7, 1963	1161
2438037.5	JAN 8, 1963	1103	2438096.5	MAR 8, 1963	1162
2438038.5	JAN 9, 1963	1104	2438097.5	MAR 9, 1963	1163
2438039.5	JAN 10, 1963	1105	2438098.5	MAR 10, 1963	1164
2438040.5	JAN 11, 1963	1106	2438099.5	MAR 11, 1963	1165
2438041.5	JAN 12, 1963	1107	2438100.5	MAR 12, 1963	1166
2438042.5	JAN 13, 1963	1108	2438101.5	MAR 13, 1963	1167
2438043.5	JAN 14, 1963	1109	2438102.5	MAR 14, 1963	1168
2438044.5	JAN 15, 1963	1110	2438103.5	MAR 15, 1963	1169
2438045.5	JAN 16, 1963	1111	2438104.5	MAR 16, 1963	1170
2438046.5	JAN 17, 1963	1112	2438105.5	MAR 17, 1963	1171
2438047.5	JAN 18, 1963	1113	2438106.5	MAR 18, 1963	1172
2438048.5	JAN 19, 1963	1114	2438107.5	MAR 19, 1963	1173
2438049.5	JAN 20, 1963	1115	2438108.5	MAR 20, 1963	1174
2438050.5	JAN 21, 1963	1116	2438109.5	MAR 21, 1963	1175
2438051.5	JAN 22, 1963	1117	2438110.5	MAR 22, 1963	1176
2438052.5	JAN 23, 1963	1118	2438111.5	MAR 23, 1963	1177
2438053.5	JAN 24, 1963	1119	2438112.5	MAR 24, 1963	1178
2438054.5	JAN 25, 1963	1120	2438113.5	MAR 25, 1963	1179

2438114.5	MAR 26, 1963	1180	2438173.5	MAY 24, 1963	1239
2438115.5	MAR 27, 1963	1181	2438174.5	MAY 25, 1963	1240
2438116.5	MAR 28, 1963	1182	2438175.5	MAY 26, 1963	1241
2438117.5	MAR 29, 1963	1183	2438176.5	MAY 27, 1963	1242
2438118.5	MAR 30, 1963	1184	2438177.5	MAY 28, 1963	1243
2438119.5	MAR 31, 1963	1185	2438178.5	MAY 29, 1963	1244
2438120.5	APR 1, 1963	1186	2438179.5	MAY 30, 1963	1245
2438121.5	APR 2, 1963	1187	2438180.5	MAY 31, 1963	1246
2438122.5	APR 3, 1963	1188	2438181.5	JUN 1, 1963	1247
2438123.5	APR 4, 1963	1189	2438182.5	JUN 2, 1963	1248
2438124.5	APR 5, 1963	1190	2438183.5	JUN 3, 1963	1249
2438125.5	APR 6, 1963	1191	2438184.5	JUN 4, 1963	1250
2438126.5	APR 7, 1963	1192	2438185.5	JUN 5, 1963	1251
2438127.5	APR 8, 1963	1193	2438186.5	JUN 6, 1963	1252
2438128.5	APR 9, 1963	1194	2438187.5	JUN 7, 1963	1253
2438129.5	APR 10, 1963	1195	2438188.5	JUN 8, 1963	1254
2438130.5	APR 11, 1963	1196	2438189.5	JUN 9, 1963	1255
2438131.5	APR 12, 1963	1197	2438190.5	JUN 10, 1963	1256
2438132.5	APR 13, 1963	1198	2438191.5	JUN 11, 1963	1257
2438133.5	APR 14, 1963	1199	2438192.5	JUN 12, 1963	1258
2438134.5	APR 15, 1963	1200	2438193.5	JUN 13, 1963	1259
2438135.5	APR 16, 1963	1201	2438194.5	JUN 14, 1963	1260
2438136.5	APR 17, 1963	1202	2438195.5	JUN 15, 1963	1261
2438137.5	APR 18, 1963	1203	2438196.5	JUN 16, 1963	1262
2438138.5	APR 19, 1963	1204	2438197.5	JUN 17, 1963	1263
2438139.5	APR 20, 1963	1205	2438198.5	JUN 18, 1963	1264
2438140.5	APR 21, 1963	1206	2438199.5	JUN 19, 1963	1265
2438141.5	APR 22, 1963	1207	2438200.5	JUN 20, 1963	1266
2438142.5	APR 23, 1963	1208	2438201.5	JUN 21, 1963	1267
2438143.5	APR 24, 1963	1209	2438202.5	JUN 22, 1963	1268
2438144.5	APR 25, 1963	1210	2438203.5	JUN 23, 1963	1269
2438145.5	APR 26, 1963	1211	2438204.5	JUN 24, 1963	1270
2438146.5	APR 27, 1963	1212	2438205.5	JUN 25, 1963	1271
2438147.5	APR 28, 1963	1213	2438206.5	JUN 26, 1963	1272
2438148.5	APR 29, 1963	1214	2438207.5	JUN 27, 1963	1273
2438149.5	APR 30, 1963	1215	2438208.5	JUN 28, 1963	1274
2438150.5	MAY 1, 1963	1216	2438209.5	JUN 29, 1963	1275
2438151.5	MAY 2, 1963	1217	2438210.5	JUN 30, 1963	1276
2438152.5	MAY 3, 1963	1218	2438211.5	JUL 1, 1963	1277
2438153.5	MAY 4, 1963	1219	2438212.5	JUL 2, 1963	1278
2438154.5	MAY 5, 1963	1220	2438213.5	JUL 3, 1963	1279
2438155.5	MAY 6, 1963	1221	2438214.5	JUL 4, 1963	1280
2438156.5	MAY 7, 1963	1222	2438215.5	JUL 5, 1963	1281
2438157.5	MAY 8, 1963	1223	2438216.5	JUL 6, 1963	1282
2438158.5	MAY 9, 1963	1224	2438217.5	JUL 7, 1963	1283
2438159.5	MAY 10, 1963	1225	2438218.5	JUL 8, 1963	1284
2438160.5	MAY 11, 1963	1226	2438219.5	JUL 9, 1963	1285
2438161.5	MAY 12, 1963	1227	2438220.5	JUL 10, 1963	1286
2438162.5	MAY 13, 1963	1228	2438221.5	JUL 11, 1963	1287
2438163.5	MAY 14, 1963	1229	2438222.5	JUL 12, 1963	1288
2438164.5	MAY 15, 1963	1230	2438223.5	JUL 13, 1963	1289
2438165.5	MAY 16, 1963	1231	2438224.5	JUL 14, 1963	1290
2438166.5	MAY 17, 1963	1232	2438225.5	JUL 15, 1963	1291
2438167.5	MAY 18, 1963	1233	2438226.5	JUL 16, 1963	1292
2438168.5	MAY 19, 1963	1234	2438227.5	JUL 17, 1963	1293
2438169.5	MAY 20, 1963	1235	2438228.5	JUL 18, 1963	1294
2438170.5	MAY 21, 1963	1236	2438229.5	JUL 19, 1963	1295
2438171.5	MAY 22, 1963	1237	2438230.5	JUL 20, 1963	1296
2438172.5	MAY 23, 1963	1238	2438231.5	JUL 21, 1963	1297

2438232.5	JUL 22, 1963	1298	2438291.5	SEP 19, 1963	1357
2438233.5	JUL 23, 1963	1299	2438292.5	SEP 20, 1963	1358
2438234.5	JUL 24, 1963	1300	2438293.5	SEP 21, 1963	1359
2438235.5	JUL 25, 1963	1301	2438294.5	SEP 22, 1963	1360
2438236.5	JUL 26, 1963	1302	2438295.5	SEP 23, 1963	1361
2438237.5	JUL 27, 1963	1303	2438296.5	SEP 24, 1963	1362
2438238.5	JUL 28, 1963	1304	2438297.5	SEP 25, 1963	1363
2438239.5	JUL 29, 1963	1305	2438298.5	SEP 26, 1963	1364
2438240.5	JUL 30, 1963	1306	2438299.5	SEP 27, 1963	1365
2438241.5	JUL 31, 1963	1307	2438300.5	SEP 28, 1963	1366
2438242.5	AUG 1, 1963	1308	2438301.5	SEP 29, 1963	1367
2438243.5	AUG 2, 1963	1309	2438302.5	SEP 30, 1963	1368
2438244.5	AUG 3, 1963	1310	2438303.5	OCT 1, 1963	1369
2438245.5	AUG 4, 1963	1311	2438304.5	OCT 2, 1963	1370
2438246.5	AUG 5, 1963	1312	2438305.5	OCT 3, 1963	1371
2438247.5	AUG 6, 1963	1313	2438306.5	OCT 4, 1963	1372
2438248.5	AUG 7, 1963	1314	2438307.5	OCT 5, 1963	1373
2438249.5	AUG 8, 1963	1315	2438308.5	OCT 6, 1963	1374
2438250.5	AUG 9, 1963	1316	2438309.5	OCT 7, 1963	1375
2438251.5	AUG 10, 1963	1317	2438310.5	OCT 8, 1963	1376
2438252.5	AUG 11, 1963	1318	2438311.5	OCT 9, 1963	1377
2438253.5	AUG 12, 1963	1319	2438312.5	OCT 10, 1963	1378
2438254.5	AUG 13, 1963	1320	2438313.5	OCT 11, 1963	1379
2438255.5	AUG 14, 1963	1321	2438314.5	OCT 12, 1963	1380
2438256.5	AUG 15, 1963	1322	2438315.5	OCT 13, 1963	1381
2438257.5	AUG 16, 1963	1323	2438316.5	OCT 14, 1963	1382
2438258.5	AUG 17, 1963	1324	2438317.5	OCT 15, 1963	1383
2438259.5	AUG 18, 1963	1325	2438318.5	OCT 16, 1963	1384
2438260.5	AUG 19, 1963	1326	2438319.5	OCT 17, 1963	1385
2438261.5	AUG 20, 1963	1327	2438320.5	OCT 18, 1963	1386
2438262.5	AUG 21, 1963	1328	2438321.5	OCT 19, 1963	1387
2438263.5	AUG 22, 1963	1329	2438322.5	OCT 20, 1963	1388
2438264.5	AUG 23, 1963	1330	2438323.5	OCT 21, 1963	1389
2438265.5	AUG 24, 1963	1331	2438324.5	OCT 22, 1963	1390
2438266.5	AUG 25, 1963	1332	2438325.5	OCT 23, 1963	1391
2438267.5	AUG 26, 1963	1333	2438326.5	OCT 24, 1963	1392
2438268.5	AUG 27, 1963	1334	2438327.5	OCT 25, 1963	1393
2438269.5	AUG 28, 1963	1335	2438328.5	OCT 26, 1963	1394
2438270.5	AUG 29, 1963	1336	2438329.5	OCT 27, 1963	1395
2438271.5	AUG 30, 1963	1337	2438330.5	OCT 28, 1963	1396
2438272.5	AUG 31, 1963	1338	2438331.5	OCT 29, 1963	1397
2438273.5	SEP 1, 1963	1339	2438332.5	OCT 30, 1963	1398
2438274.5	SEP 2, 1963	1340	2438333.5	OCT 31, 1963	1399
2438275.5	SEP 3, 1963	1341	2438334.5	NOV 1, 1963	1400
2438276.5	SEP 4, 1963	1342	2438335.5	NOV 2, 1963	1401
2438277.5	SEP 5, 1963	1343	2438336.5	NOV 3, 1963	1402
2438278.5	SEP 6, 1963	1344	2438337.5	NOV 4, 1963	1403
2438279.5	SEP 7, 1963	1345	2438338.5	NOV 5, 1963	1404
2438280.5	SEP 8, 1963	1346	2438339.5	NOV 6, 1963	1405
2438281.5	SEP 9, 1963	1347	2438340.5	NOV 7, 1963	1406
2438282.5	SEP 10, 1963	1348	2438341.5	NOV 8, 1963	1407
2438283.5	SEP 11, 1963	1349	2438342.5	NOV 9, 1963	1408
2438284.5	SEP 12, 1963	1350	2438343.5	NOV 10, 1963	1409
2438285.5	SEP 13, 1963	1351	2438344.5	NOV 11, 1963	1410
2438286.5	SEP 14, 1963	1352	2438345.5	NOV 12, 1963	1411
2438287.5	SEP 15, 1963	1353	2438346.5	NOV 13, 1963	1412
2438288.5	SEP 16, 1963	1354	2438347.5	NOV 14, 1963	1413
2438289.5	SEP 17, 1963	1355	2438348.5	NOV 15, 1963	1414
2438290.5	SEP 18, 1963	1356	2438349.5	NOV 16, 1963	1415

2438350.5	NOV 17, 1963	1416	2438409.5	JAN 15, 1964	1475
2438351.5	NOV 18, 1963	1417	2438410.5	JAN 16, 1964	1476
2438352.5	NOV 19, 1963	1418	2438411.5	JAN 17, 1964	1477
2438353.5	NOV 20, 1963	1419	2438412.5	JAN 18, 1964	1478
2438354.5	NOV 21, 1963	1420	2438413.5	JAN 19, 1964	1479
2438355.5	NOV 22, 1963	1421	2438414.5	JAN 20, 1964	1480
2438356.5	NOV 23, 1963	1422	2438415.5	JAN 21, 1964	1481
2438357.5	NOV 24, 1963	1423	2438416.5	JAN 22, 1964	1482
2438358.5	NOV 25, 1963	1424	2438417.5	JAN 23, 1964	1483
2438359.5	NOV 26, 1963	1425	2438418.5	JAN 24, 1964	1484
2438360.5	NOV 27, 1963	1426	2438419.5	JAN 25, 1964	1485
2438361.5	NOV 28, 1963	1427	2438420.5	JAN 26, 1964	1486
2438362.5	NOV 29, 1963	1428	2438421.5	JAN 27, 1964	1487
2438363.5	NOV 30, 1963	1429	2438422.5	JAN 28, 1964	1488
2438364.5	DEC 1, 1963	1430	2438423.5	JAN 29, 1964	1489
2438365.5	DEC 2, 1963	1431	2438424.5	JAN 30, 1964	1490
2438366.5	DEC 3, 1963	1432	2438425.5	JAN 31, 1964	1491
2438367.5	DEC 4, 1963	1433	2438426.5	FEB 1, 1964	1492
2438368.5	DEC 5, 1963	1434	2438427.5	FEB 2, 1964	1493
2438369.5	DEC 6, 1963	1435	2438428.5	FEB 3, 1964	1494
2438370.5	DEC 7, 1963	1436	2438429.5	FEB 4, 1964	1495
2438371.5	DEC 8, 1963	1437	2438430.5	FEB 5, 1964	1496
2438372.5	DEC 9, 1963	1438	2438431.5	FEB 6, 1964	1497
2438373.5	DEC 10, 1963	1439	2438432.5	FEB 7, 1964	1498
2438374.5	DEC 11, 1963	1440	2438433.5	FEB 8, 1964	1499
2438375.5	DEC 12, 1963	1441	2438434.5	FEB 9, 1964	1500
2438376.5	DEC 13, 1963	1442	2438435.5	FEB 10, 1964	1501
2438377.5	DEC 14, 1963	1443	2438436.5	FEB 11, 1964	1502
2438378.5	DEC 15, 1963	1444	2438437.5	FEB 12, 1964	1503
2438379.5	DEC 16, 1963	1445	2438438.5	FEB 13, 1964	1504
2438380.5	DEC 17, 1963	1446	2438439.5	FEB 14, 1964	1505
2438381.5	DEC 18, 1963	1447	2438440.5	FEB 15, 1964	1506
2438382.5	DEC 19, 1963	1448	2438441.5	FEB 16, 1964	1507
2438383.5	DEC 20, 1963	1449	2438442.5	FEB 17, 1964	1508
2438384.5	DEC 21, 1963	1450	2438443.5	FEB 18, 1964	1509
2438385.5	DEC 22, 1963	1451	2438444.5	FEB 19, 1964	1510
2438386.5	DEC 23, 1963	1452	2438445.5	FEB 20, 1964	1511
2438387.5	DEC 24, 1963	1453	2438446.5	FEB 21, 1964	1512
2438388.5	DEC 25, 1963	1454	2438447.5	FEB 22, 1964	1513
2438389.5	DEC 26, 1963	1455	2438448.5	FEB 23, 1964	1514
2438390.5	DEC 27, 1963	1456	2438449.5	FEB 24, 1964	1515
2438391.5	DEC 28, 1963	1457	2438450.5	FEB 25, 1964	1516
2438392.5	DEC 29, 1963	1458	2438451.5	FEB 26, 1964	1517
2438393.5	DEC 30, 1963	1459	2438452.5	FEB 27, 1964	1518
2438394.5	DEC 31, 1963	1460	2438453.5	FEB 28, 1964	1519
2438395.5	JAN 1, 1964	1461	2438454.5	FEB 29, 1964	1520
2438396.5	JAN 2, 1964	1462	2438455.5	MAR 1, 1964	1521
2438397.5	JAN 3, 1964	1463	2438456.5	MAR 2, 1964	1522
2438398.5	JAN 4, 1964	1464	2438457.5	MAR 3, 1964	1523
2438399.5	JAN 5, 1964	1465	2438458.5	MAR 4, 1964	1524
2438400.5	JAN 6, 1964	1466	2438459.5	MAR 5, 1964	1525
2438401.5	JAN 7, 1964	1467	2438460.5	MAR 6, 1964	1526
2438402.5	JAN 8, 1964	1468	2438461.5	MAR 7, 1964	1527
2438403.5	JAN 9, 1964	1469	2438462.5	MAR 8, 1964	1528
2438404.5	JAN 10, 1964	1470	2438463.5	MAR 9, 1964	1529
2438405.5	JAN 11, 1964	1471	2438464.5	MAR 10, 1964	1530
2438406.5	JAN 12, 1964	1472	2438465.5	MAR 11, 1964	1531
2438407.5	JAN 13, 1964	1473	2438466.5	MAR 12, 1964	1532
2438408.5	JAN 14, 1964	1474	2438467.5	MAR 13, 1964	1533

2438468.5	MAR 14, 1964	1534	2438527.5	MAY 12, 1964	1593
2438469.5	MAR 15, 1964	1535	2438528.5	MAY 13, 1964	1594
2438470.5	MAR 16, 1964	1536	2438529.5	MAY 14, 1964	1595
2438471.5	MAR 17, 1964	1537	2438530.5	MAY 15, 1964	1596
2438472.5	MAR 18, 1964	1538	2438531.5	MAY 16, 1964	1597
2438473.5	MAR 19, 1964	1539	2438532.5	MAY 17, 1964	1598
2438474.5	MAR 20, 1964	1540	2438533.5	MAY 18, 1964	1599
2438475.5	MAR 21, 1964	1541	2438534.5	MAY 19, 1964	1600
2438476.5	MAR 22, 1964	1542	2438535.5	MAY 20, 1964	1601
2438477.5	MAR 23, 1964	1543	2438536.5	MAY 21, 1964	1602
2438478.5	MAR 24, 1964	1544	2438537.5	MAY 22, 1964	1603
2438479.5	MAR 25, 1964	1545	2438538.5	MAY 23, 1964	1604
2438480.5	MAR 26, 1964	1546	2438539.5	MAY 24, 1964	1605
2438481.5	MAR 27, 1964	1547	2438540.5	MAY 25, 1964	1606
2438482.5	MAR 28, 1964	1548	2438541.5	MAY 26, 1964	1607
2438483.5	MAR 29, 1964	1549	2438542.5	MAY 27, 1964	1608
2438484.5	MAR 30, 1964	1550	2438543.5	MAY 28, 1964	1609
2438485.5	MAR 31, 1964	1551	2438544.5	MAY 29, 1964	1610
2438486.5	APR 1, 1964	1552	2438545.5	MAY 30, 1964	1611
2438487.5	APR 2, 1964	1553	2438546.5	MAY 31, 1964	1612
2438488.5	APR 3, 1964	1554	2438547.5	JUN 1, 1964	1613
2438489.5	APR 4, 1964	1555	2438548.5	JUN 2, 1964	1614
2438490.5	APR 5, 1964	1556	2438549.5	JUN 3, 1964	1615
2438491.5	APR 6, 1964	1557	2438550.5	JUN 4, 1964	1616
2438492.5	APR 7, 1964	1558	2438551.5	JUN 5, 1964	1617
2438493.5	APR 8, 1964	1559	2438552.5	JUN 6, 1964	1618
2438494.5	APR 9, 1964	1560	2438553.5	JUN 7, 1964	1619
2438495.5	APR 10, 1964	1561	2438554.5	JUN 8, 1964	1620
2438496.5	APR 11, 1964	1562	2438555.5	JUN 9, 1964	1621
2438497.5	APR 12, 1964	1563	2438556.5	JUN 10, 1964	1622
2438498.5	APR 13, 1964	1564	2438557.5	JUN 11, 1964	1623
2438499.5	APR 14, 1964	1565	2438558.5	JUN 12, 1964	1624
2438500.5	APR 15, 1964	1566	2438559.5	JUN 13, 1964	1625
2438501.5	APR 16, 1964	1567	2438560.5	JUN 14, 1964	1626
2438502.5	APR 17, 1964	1568	2438561.5	JUN 15, 1964	1627
2438503.5	APR 18, 1964	1569	2438562.5	JUN 16, 1964	1628
2438504.5	APR 19, 1964	1570	2438563.5	JUN 17, 1964	1629
2438505.5	APR 20, 1964	1571	2438564.5	JUN 18, 1964	1630
2438506.5	APR 21, 1964	1572	2438565.5	JUN 19, 1964	1631
2438507.5	APR 22, 1964	1573	2438566.5	JUN 20, 1964	1632
2438508.5	APR 23, 1964	1574	2438567.5	JUN 21, 1964	1633
2438509.5	APR 24, 1964	1575	2438568.5	JUN 22, 1964	1634
2438510.5	APR 25, 1964	1576	2438569.5	JUN 23, 1964	1635
2438511.5	APR 26, 1964	1577	2438570.5	JUN 24, 1964	1636
2438512.5	APR 27, 1964	1578	2438571.5	JUN 25, 1964	1637
2438513.5	APR 28, 1964	1579	2438572.5	JUN 26, 1964	1638
2438514.5	APR 29, 1964	1580	2438573.5	JUN 27, 1964	1639
2438515.5	APR 30, 1964	1581	2438574.5	JUN 28, 1964	1640
2438516.5	MAY 1, 1964	1582	2438575.5	JUN 29, 1964	1641
2438517.5	MAY 2, 1964	1583	2438576.5	JUN 30, 1964	1642
2438518.5	MAY 3, 1964	1584	2438577.5	JUL 1, 1964	1643
2438519.5	MAY 4, 1964	1585	2438578.5	JUL 2, 1964	1644
2438520.5	MAY 5, 1964	1586	2438579.5	JUL 3, 1964	1645
2438521.5	MAY 6, 1964	1587	2438580.5	JUL 4, 1964	1646
2438522.5	MAY 7, 1964	1588	2438581.5	JUL 5, 1964	1647
2438523.5	MAY 8, 1964	1589	2438582.5	JUL 6, 1964	1648
2438524.5	MAY 9, 1964	1590	2438583.5	JUL 7, 1964	1649
2438525.5	MAY 10, 1964	1591	2438584.5	JUL 8, 1964	1650
2438526.5	MAY 11, 1964	1592	2438585.5	JUL 9, 1964	1651

2438586.5	JUL 10, 1964	1652	2438645.5	SEP 7, 1964	1711
2438587.5	JUL 11, 1964	1653	2438646.5	SEP 8, 1964	1712
2438588.5	JUL 12, 1964	1654	2438647.5	SEP 9, 1964	1713
2438589.5	JUL 13, 1964	1655	2438648.5	SEP 10, 1964	1714
2438590.5	JUL 14, 1964	1656	2438649.5	SEP 11, 1964	1715
2438591.5	JUL 15, 1964	1657	2438650.5	SEP 12, 1964	1716
2438592.5	JUL 16, 1964	1658	2438651.5	SEP 13, 1964	1717
2438593.5	JUL 17, 1964	1659	2438652.5	SEP 14, 1964	1718
2438594.5	JUL 18, 1964	1660	2438653.5	SEP 15, 1964	1719
2438595.5	JUL 19, 1964	1661	2438654.5	SEP 16, 1964	1720
2438596.5	JUL 20, 1964	1662	2438655.5	SEP 17, 1964	1721
2438597.5	JUL 21, 1964	1663	2438656.5	SEP 18, 1964	1722
2438598.5	JUL 22, 1964	1664	2438657.5	SEP 19, 1964	1723
2438599.5	JUL 23, 1964	1665	2438658.5	SEP 20, 1964	1724
2438600.5	JUL 24, 1964	1666	2438659.5	SEP 21, 1964	1725
2438601.5	JUL 25, 1964	1667	2438660.5	SEP 22, 1964	1726
2438602.5	JUL 26, 1964	1668	2438661.5	SEP 23, 1964	1727
2438603.5	JUL 27, 1964	1669	2438662.5	SEP 24, 1964	1728
2438604.5	JUL 28, 1964	1670	2438663.5	SEP 25, 1964	1729
2438605.5	JUL 29, 1964	1671	2438664.5	SEP 26, 1964	1730
2438606.5	JUL 30, 1964	1672	2438665.5	SEP 27, 1964	1731
2438607.5	JUL 31, 1964	1673	2438666.5	SEP 28, 1964	1732
2438608.5	AUG 1, 1964	1674	2438667.5	SEP 29, 1964	1733
2438609.5	AUG 2, 1964	1675	2438668.5	SEP 30, 1964	1734
2438610.5	AUG 3, 1964	1676	2438669.5	OCT 1, 1964	1735
2438611.5	AUG 4, 1964	1677	2438670.5	OCT 2, 1964	1736
2438612.5	AUG 5, 1964	1678	2438671.5	OCT 3, 1964	1737
2438613.5	AUG 6, 1964	1679	2438672.5	OCT 4, 1964	1738
2438614.5	AUG 7, 1964	1680	2438673.5	OCT 5, 1964	1739
2438615.5	AUG 8, 1964	1681	2438674.5	OCT 6, 1964	1740
2438616.5	AUG 9, 1964	1682	2438675.5	OCT 7, 1964	1741
2438617.5	AUG 10, 1964	1683	2438676.5	OCT 8, 1964	1742
2438618.5	AUG 11, 1964	1684	2438677.5	OCT 9, 1964	1743
2438619.5	AUG 12, 1964	1685	2438678.5	OCT 10, 1964	1744
2438620.5	AUG 13, 1964	1686	2438679.5	OCT 11, 1964	1745
2438621.5	AUG 14, 1964	1687	2438680.5	OCT 12, 1964	1746
2438622.5	AUG 15, 1964	1688	2438681.5	OCT 13, 1964	1747
2438623.5	AUG 16, 1964	1689	2438682.5	OCT 14, 1964	1748
2438624.5	AUG 17, 1964	1690	2438683.5	OCT 15, 1964	1749
2438625.5	AUG 18, 1964	1691	2438684.5	OCT 16, 1964	1750
2438626.5	AUG 19, 1964	1692	2438685.5	OCT 17, 1964	1751
2438627.5	AUG 20, 1964	1693	2438686.5	OCT 18, 1964	1752
2438628.5	AUG 21, 1964	1694	2438687.5	OCT 19, 1964	1753
2438629.5	AUG 22, 1964	1695	2438688.5	OCT 20, 1964	1754
2438630.5	AUG 23, 1964	1696	2438689.5	OCT 21, 1964	1755
2438631.5	AUG 24, 1964	1697	2438690.5	OCT 22, 1964	1756
2438632.5	AUG 25, 1964	1698	2438691.5	OCT 23, 1964	1757
2438633.5	AUG 26, 1964	1699	2438692.5	OCT 24, 1964	1758
2438634.5	AUG 27, 1964	1700	2438693.5	OCT 25, 1964	1759
2438635.5	AUG 28, 1964	1701	2438694.5	OCT 26, 1964	1760
2438636.5	AUG 29, 1964	1702	2438695.5	OCT 27, 1964	1761
2438637.5	AUG 30, 1964	1703	2438696.5	OCT 28, 1964	1762
2438638.5	AUG 31, 1964	1704	2438697.5	OCT 29, 1964	1763
2438639.5	SEP 1, 1964	1705	2438698.5	OCT 30, 1964	1764
2438640.5	SEP 2, 1964	1706	2438699.5	OCT 31, 1964	1765
2438641.5	SEP 3, 1964	1707	2438700.5	NOV 1, 1964	1766
2438642.5	SEP 4, 1964	1708	2438701.5	NOV 2, 1964	1767
2438643.5	SEP 5, 1964	1709	2438702.5	NOV 3, 1964	1768
2438644.5	SEP 6, 1964	1710	2438703.5	NOV 4, 1964	1769

2438704.5	NOV 5, 1964	1770
2438705.5	NOV 6, 1964	1771
2438706.5	NOV 7, 1964	1772
2438707.5	NOV 8, 1964	1773
2438708.5	NOV 9, 1964	1774
2438709.5	NOV 10, 1964	1775
2438710.5	NOV 11, 1964	1776
2438711.5	NOV 12, 1964	1777
2438712.5	NOV 13, 1964	1778
2438713.5	NOV 14, 1964	1779
2438714.5	NOV 15, 1964	1780
2438715.5	NOV 16, 1964	1781
2438716.5	NOV 17, 1964	1782
2438717.5	NOV 18, 1964	1783
2438718.5	NOV 19, 1964	1784
2438719.5	NOV 20, 1964	1785
2438720.5	NOV 21, 1964	1786
2438721.5	NOV 22, 1964	1787
2438722.5	NOV 23, 1964	1788
2438723.5	NOV 24, 1964	1789
2438724.5	NOV 25, 1964	1790
2438725.5	NOV 26, 1964	1791
2438726.5	NOV 27, 1964	1792
2438727.5	NOV 28, 1964	1793
2438728.5	NOV 29, 1964	1794
2438729.5	NOV 30, 1964	1795
2438730.5	DEC 1, 1964	1796
2438731.5	DEC 2, 1964	1797
2438732.5	DEC 3, 1964	1798
2438733.5	DEC 4, 1964	1799
2438734.5	DEC 5, 1964	1800
2438735.5	DEC 6, 1964	1801
2438736.5	DEC 7, 1964	1802
2438737.5	DEC 8, 1964	1803
2438738.5	DEC 9, 1964	1804
2438739.5	DEC 10, 1964	1805
2438740.5	DEC 11, 1964	1806
2438741.5	DEC 12, 1964	1807
2438742.5	DEC 13, 1964	1808
2438743.5	DEC 14, 1964	1809
2438744.5	DEC 15, 1964	1810
2438745.5	DEC 16, 1964	1811
2438746.5	DEC 17, 1964	1812
2438747.5	DEC 18, 1964	1813
2438748.5	DEC 19, 1964	1814
2438749.5	DEC 20, 1964	1815
2438750.5	DEC 21, 1964	1816
2438751.5	DEC 22, 1964	1817
2438752.5	DEC 23, 1964	1818
2438753.5	DEC 24, 1964	1819
2438754.5	DEC 25, 1964	1820
2438755.5	DEC 26, 1964	1821
2438756.5	DEC 27, 1964	1822
2438757.5	DEC 28, 1964	1823
2438758.5	DEC 29, 1964	1824
2438759.5	DEC 30, 1964	1825
2438760.5	DEC 31, 1964	1826

H. LISTING OF THE N-BODY PROGRAM

C

```

      N BODY TRAJECTORY      SHERVIN
      EQUIVALENCE(WM(1),XIM),(WM(2),YIM),(WM(3),ZIM),(WM(4),XIDM),
1 (WM(5),ZIDM),(WM(6),YIDM),(WL(1),XIL),(WL(2),YIL),(WL(3),ZIL),
2 (WL(4),XIDL),(WL(5),YIDL),(WL(6),ZIDL)
      DAC PX(9,67),PY(9,67),PZ(9,67),TL(67),RKM(4,6),RKL(4,6),NB(9),
1 WT(9),RAD(9),X(9),Y(9),Z(9),DIS(9),DIST(9),PH(6),PL(6),PPH(6),
2 PPL(6),QH(6),QL(6),WM(6),WL(6),XX(9),YY(9),ZZ(9),TI(6),CL(6)
      COMMON NEWORG,ZER,FMX,FLX,FMY,FLY,FMZ,FLZ,AM,AL,BM,BL,CM,CL
      COMMON NORG,NTARG,NSUN,IN,INN,NNN,T,TO,TMAX,DTMAX,HAFDT,WTE,WTV,MGM,
1 XTARG,YTARG,ZTARG,SCEN,VCEN,SMAX,GMAX,EMAX,RAD1,RAD2,RADE,WTB,
2 NDB,NBT,NBS,RADORG,SAM,SbM,SCM, SAL,SbL,SCL,XIM,XIL,YIM,YIL,ZIM,
3 ZIL,XIDM,XIDL,YIDM,YIDL,ZIDM,ZIDL,RM,RI,PP,RO,SS,RPM,PRI,TEM,TEL,
4 GMX,GLX,GMY,GLY,GMZ,GLZ,SUMX,SULX,SUMY,SULY,SUMZ,SULZ,FM,FL,GM,GL,
5 HM,HL,RRR,SSS,XN,YM,ZM,A,BX,BY,BZ,WRM,WRL,RCM,RCL,ROL,RPPM,
6 APM,XFL,TPL,ZPL,ZPL,
7 KOB,VNZ,MEDT,MSDT,MDT,NOT,MET,NOUT,NCKE,TSAB,DTA,DTB,DTC,EPI
      DAC G(2),WTS(2)
      DAC SOGOOD(6),XDOT(2),YDOT(2),ZDOT(2),WRONG(6),OX(2)
1 ,OY(2),OZ(2),XP(2),YP(2),ZP(2),XDOTP(2),YDOTP(2),ZDOTP(2),PI(2),
2 PI2(2),E(2),XMJ(2),CCON(2),XN(2)
      COMMON A1,A2,FJ1,FJ2,SFJ1,SFJ2,CFJ1,CFJ2,S1,S2,EPS1
      COMMON DT,DTime,RPM
      DAC SM(6),SL(6),XMJP(2)
      COMMON OBJ,TSABE,REA,RTA,RSN,HPI,THPI,KK,NOSW,PQM(6),PQL(6)
      MGM = 512
      EPS1 = 1.0E-11
      PI = 202622077325
      PI(2) = 147042055061
      PI2 = 203622077325
      PI2(2) = 150042055061
      HPI = 201622077325
      THPI = 203455457437
2 REWIND 26
      RIT 2,3,G(2),WTE,RADE,WTV,OBJ
3 FORMAT (E9.5)
4 RIT 2,3,EMAX,GMAX,SMAX,TMAX,TO
5 RIT 2,3,NCKE,MSDT,MET,NOUT,NOSW
      IF (MSDT) 6, 7, 6
6 RIT 2,3,DTA,DTB,DTC
      ERASE DT
      GO TO 8
7 RIT 2,3,DT,DTMAX,EPI
      HAFDT = DT/2.
8 RIT 2,3,N,NEWORG,NTARG
      RIT 2,3,(NB(I),WT(I),RAD(I),I = 1,N)
      RIT 2,3,(PM(I),I = 1,6)
      READ TAPE26, (TL(J),(PX(I,J),PY(I,J),PZ(I,J),I = 1,9),J = 3,7)
      READ TAPE26, (TL(J),(PX(I,J),PY(I,J),PZ(I,J),I = 1,9),J = 8,67)
9 NNN = 6
      T = TO
      TMAX = TO+TMAX
      G = -G(2)
      ERASE NOT,NORG,PL,KOB

```

B
 B
 B
 B
 B

```

CALL TITLE
11 CALL ORGN
   IF (TEM) 12,2,12
12 CALL TERP
   WOT 10,10
10 FORMAT (2H1 )
   CALL OUT
   IF (NCKE) 26,100,26
26 ERASE WM,WL
   XDOTP = PM(4)
   YDOTP = PM(5)
   ZDOTP = PM(6)
   XDOTP(2) = PL(4)
   YDOTP(2) = PL(5)
   ZDOTP(2) = PL(6)
27 SOGOOD (1) = PM (1)
   SOGOOD (2) = PL (1)
   SOGOOD (3) = PM (2)
   SOGOOD (4) = PL (2)
   SOGOOD (5) = PM (3)
   SOGOOD (6) = PL (3)
   CALL FAD (WM(4),WL(4),XDOTP(1),XDOTP(2),XDOT(1),XDOT(2))
   CALL FAD (WM(5),WL(5),YDOTP(1),YDOTP(2),YDOT(1),YDOT(2))
   CALL FAD (WM(6),WL(6),ZDOTP(1),ZDOTP(2),ZDOT(1),ZDOT(2))
28 CALL RECT
   WOT 10,29,E(1),A1,XN(1)
29 FORMAT (1P35H0          RECTIFICATION      E=E15.7,6H      A=E15.
1 7,6H      N=E15.7/1H0 )
30 ERASE WM, WL, DTME, VNZ
   CALL POSN
32 IF(NORG) 34,31,34
31 IF(SCEN-1.5E-4) 41,33,33
41 KOB = 1
   GO TO 34
33 ERASE KOB
34 IF (MSDT) 35, 50, 35
35 IF (SCEN-RAD2) 36, 38, 39
36 IF (SCEN-RAD1) 37, 37, 38
37 DT = DTA
   GO TO 40
38 DT = DTB
   GO TO 40
39 DT = DTC
40 CONTINUE
H   SUB MGM
H   STO HAFDT
42 CALL INTN
   GO TO 72
50 TSAVE = DTME
   TSAVE = T
   NSAV = NNN
   IF (DTMAX-DT) 99,99,98
98 DT = DT + DT

```

```

99  DT = DT + DT
H  SUB MGM
H  SLW HAFDT
DO 55 I = 1, N
XX (I) = X (I)
YY (I) = Y (I)
55  ZZ (I) = Z (I)
QM(4) = XPM
QM(5) = YPM
QM(6) = ZPM
QL(4) = XPL
QL(5) = YPL
QL(6) = ZPL
DO 60 I = 1, 6
PPM (I) = WM (I)
60  PPL (I) = WL (I)
DO 61 I = 1, 3
PQM(I) = PM(I)
61  PQL(I) = PL(I)
SM(4) = XP(1)
SM(5) = YP(1)
SM(6) = ZP(1)
SL(4) = XP(2)
SL(5) = YP(2)
SL(6) = ZP(2)
CALL INTN
SM (1) = WM (1)
SL (1) = WL (1)
SM (2) = WM (2)
SL (2) = WL (2)
SM (3) = WM (3)
SL (3) = WL (3)
66  DT = HAFDT
H  SUB MGM
H  SLW HAFDT
DTME = TSAV
T = TSAVE
IF (NNN-NSAV) 63,65,64
63  NSAV = 4
64  NNN = NSAV
65  DO 68 I = 1, N
X (I) = XX (I)
Y (I) = YY (I)
68  Z (I) = ZZ (I)
DO 67 I=1,3
PM(I) = PQM(I)
67  PL(I) = PQL(I)
DO 69 I = 1, 6
WM (I) = PPM (I)
69  WL (I) = PPL (I)
XP(1) = SM(4)
YP(1) = SM(5)
ZP(1) = SM(6)

```

```

XP(2) = SL(4)
YP(2) = SL(5)
ZP(2) = SL(6)
XPM = OM(4)
YPM = OM(5)
ZPM = OM(6)
XPL = OL(4)
YPL = OL(5)
ZPL = OL(6)
CALL INTN
DO 70 I = 1, 3
OM (I) = WM (I)
70 OL (I) = WL (I)
CALL FAD (XP(1),XP(2),WM(1),WL(1),PM(1),PL(1))
CALL FAD (YP(1),YP(2),WM(2),WL(2),PM(2),PL(2))
CALL FAD (ZP(1),ZP(2),WM(3),WL(3),PM(3),PL(3))
CALL INTN
CALL FSB (SM(1),SL(1),WM(1),WL(1),TEM,TEL)
IF (ABSF(TEM)-EP1) 73, 73, 75
73 CALL FSB (SM(2),SL(2),WM(2),WL(2),TEM,TEL)
IF (ABSF(TEM)-EP1) 74, 74, 75
74 CALL FSB (SM(3),SL(3),WM(3),WL(3),TEM,TEL)
IF (ABSF(TEM)-EP1) 72, 72, 75
75 DO 71 I = 1, 3
SM (I) = OM (I)
71 SL (I) = OL (I)
GO TO 66
72 NOT = NOT + 1
CALL FAD (XP(1),XP(2),WM(1),WL(1),PM(1),PL(1))
CALL FAD (YP(1),YP(2),WM(2),WL(2),PM(2),PL(2))
CALL FAD (ZP(1),ZP(2),WM(3),WL(3),PM(3),PL(3))
IF (NOT-NOUT) 83,84,83
83 SCEN = SORTF(PM(1)*PM(1)+PM(2)*PM(2)+PM(3)*PM(3))
GO TO 76
84 PM(4) = WM(4)+XDOTP
PM(5) = WM(5)+YDOTP
PM(6) = WM(6)+ZDOTP
SL(4) = RKM(4,4)/DT
SL(5) = RKM(4,5)/DT
SL(6) = RKM(4,6)/DT
CALL OUT
ERASE NOT
IF (EMAX-PEA) 333,333,430
430 IF (GMAX-RTA) 333,333,431
431 IF (SMAX-RSN) 333,333,76
76 IF (SCEN-RADORG) 277,277,86
277 IF (NOT) 84,279,84
279 IF (NTARG-NORG) 169,165,169
86 IF (T-TMAX) 202,278,278
278 PM(4) = WM(4)+XDOTP
PM(5) = WM(5)+YDOTP
PM(6) = WM(6)+ZDOTP
SL(4) = RKM(4,4)/DT

```

```

SL(5) = RKM(4,5)/DT
SL(6) = RKM(4,6)/DT
GO TO 150
202 IF (RET) 203,210,203
203 TEM = WTS/RCM - WTS/RPM
TEL = SUMX*SUMX+SUMY*SUMY+SUMZ*SUMZ
IF (TEM-(4.*TEL)) 207,207,210
207 ERASE NCKE
CALL FAD (WM(4),WL(4),XDOTP(1),XDOTP(2),PM(4),PL(4))
CALL FAD (WM(5),WL(5),YDDTP(1),YDDTP(2),PM(5),PL(5))
CALL FAD (WM(6),WL(6),ZDOTP(1),ZDOTP(2),PM(6),PL(6))
WOT 10,208
208 FORMAT (12H0 COWELL/2H0 )
GO TO 100
210 IF (NOSW) 211,88,211
211 IF (NBT) 212,88,212
212 IF (TEM-(WT(NBT)/DIS(NBT))) 214,212,212
214 IF (NTARG) 216,218,216
216 NEWORG = NTARG
217 CALL FAD (WM(4),WL(4),XDOTP(1),XDDTP(2),PM(4),PL(4))
CALL FAD (WM(5),WL(5),YDDTP(1),YDDTP(2),PM(5),PL(5))
CALL FAD (WM(6),WL(6),ZDOTP(1),ZDOTP(2),PM(6),PL(6))
CALL SWITCH
GO TO 26
218 NEWORG = 0
GO TO 217
88 IF (ABSF(WM(1)/XP(1))-0.05) 89,27,27
89 IF (ABSF(WM(2)/YP(1))-0.05) 90,27,27
90 IF (ABSF(WM(3)/ZP(1))-0.05) 91,27,27
91 IF (ABSF(WM(4)/XDOTP(1))-0.05) 92,27,27
92 IF (ABSF(WM(5)/YDDTP(1))-0.05) 93,27,27
93 IF (ABSF(WM(6)/ZDOTP(1))-0.05) 94,27,27
94 IF (ABSF(GMX/XPM)-0.05) 95,27,27
95 IF (ABSF(GMY/YPM)-0.05) 96,27,27
96 IF (ABSF(GMZ/ZPM)-0.05) 97,27,27
100 IF (NDRG) 1030,101,1030
101 IF (SCEN-1.5E-4) 102,103,103
102 KOB = 1
GO TO 1030
103 ERASE KDB
1030 IF (MSDT) 104,112,104
104 IF (SCEN-RAD2) 105, 107, 108
105 IF (SCEN-RAD1) 106, 106, 107
106 DT = DTA
GO TO 109
107 DT = DTB
GO TO 109
108 DT = DTC
109 CONTINUE
SUB MGM
STO HAFDT
CALL INT
GO TO 142

```

H
H

```

112  TSAV = T
     NSAV = NNN
139  IF (DTMAX-DT) 141,141,140
140  DT = DT + DT
141  DT = DT + DT
H    SUB MGM
H    SLW HAFDT
     DO 118 I = 1, N
     XX (I) = X (I)
     YY (I) = Y (I)
118  ZZ (I) = Z (I)
     DO 119 I = 1, 6
     PPM (I) = PM (I)
119  PPL (I) = PL (I)
     CALL INT
     DO 120 I = 1, 3
     SM (I) = PM (I)
120  SL (I) = PL (I)
121  DT = HAFDT
H    SUB MGM
H    SLW HAFDT
     T = TSAV
     IF (NNN-NSAV) 122,125,123
122  NSAV = 4
123  NNN = NSAV
125  DO 124 I = 1,N
     X (I) = XX (I)
     Y (I) = YY (I)
124  Z (I) = ZZ (I)
     DO 126 I = 1, 6
     PM (I) = PPM (I)
126  PL (I) = PPL (I)
     CALL INT
     DO 127 I = 1, 3
     QM (I) = PM (I)
127  QL (I) = PL (I)
     CALL INT
128  CALL FSB (SM(1),SL(1),PM(1),PL(1),TEM,TEL)
     IF (ABSF(TEM)-EP1) 130, 130, 134
130  CALL FSB (SM(2),SL(2),PM(2),PL(2),TEM,TEL)
     IF (ABSF(TEM)-EP1) 132, 132, 134
132  CALL FSB (SM(3),SL(3),PM(3),PL(3),TEM,TEL)
     IF (ABSF(TEM)-EP1) 142,142,134
134  DO 136 I = 1, 3
     SM (I) = QM (I)
136  SL (I) = QL (I)
     DO 138 I = 1, 6
     PM (I) = PPM (I)
138  PL (I) = PPL (I)
     GO TO 121
142  NOT = NOT + 1
     IF (NOUT-NOT) 146, 145, 146
145  SL(4) = RKM(4,4)/DT

```

```

SL(5) = RKM(4,5)/DT
SL(6) = RKM(4,6)/DT
CALL OUT
ERASE NOT
IF (EMAX-REA)333,333,330
330 IF (TMAX-RTA)333,333,331
331 IF (SMAX-RSN)333,333, 146
333 WOT 10,334
334 FORMAT (24H0          MAXIMUM DISTANCE)
GO TO 2
146 IF(RR-RADORG) 168,168,147
168 IF (NBT) 169,165,169
169 WOT 10,144
144 FORMAT (1H012X,13HIMPACT ORIGIN)
GO TO 2
147 DO 148 I = 1,N
IF (DIST(I)-RAD(I)) 77,77,148
148 CONTINUE
149 IF(T-TMAX) 400,250,250
400 IF (NOSW) 155,170,155
155 IF (NBT) 157,170,157
157 IF (DIST(NBT)-RR) 178,170,170
178 IF (NTARG) 179,181,179
179 NEWORG = NTARG
180 CALL SWITCH
GO TO 100
181 NEWORG = 0
GO TO 180
170 IF (MET) 175, 100, 175
175 TEL = SUMX*SUMX+SUMY*SUMY+SUMZ*SUMZ
TEM = GMX*GMX+GMY*GMY+GMZ*GMZ
IF (TEM-(4.*TEL)) 100,100,176
176 NCKE = 1
GO TO 26
250 SL(4) = RKM(4,4)/DT
SL(5) = RKM(4,5)/DT
SL(6) = RKM(4,6)/DT
150 IF (NOT) 151,152,151
151 CALL OUT
152 WOT 10,153
153 FORMAT (25H0          MAXIMUM TIME)
GO TO 2
77 IF (NOT) 78, 162, 78
78 CALL OUT
162 IF(I-1) 79,163,79
163 IF(NORG) 280, 79, 280
280 WOT 10, 281
281 FORMAT (1H012X,12HIMPACT EARTH)
GO TO 2
79 IF (I-NBT) 80,165,80
80 WOT 10, 82, NB(I)
82 FORMAT (1H012X,12HIMPACT BODY (2)
GO TO 2

```

```

165 WOT 10, 167
167 FORMAT (1H012X.13HIMPACT TARGET)
GO TO 2
END (1,1,0,0,0,1)
SUBROUTINE OUT
3 SCEN = SQRTF (PM(1)*PM(1)+PM(2)*PM(2)+PM(3)*PM(3))
VCEN = SQRTF (PM(4)*PM(4)+PM(5)*PM(5)+PM(6)*PM(6))
5 IF (NORG) 8, 9, 8
8 XEA = PM (1) - X
YEA = PM (2) - Y
ZEA = PM (3) - Z
REA = SQRTF (XEA*XEA+YEA*YEA+ZEA*ZEA)
GO TO 10
9 XEA = PM (1)
YEA = PM (2)
ZEA = PM (3)
REA = SCEN
10 IF (NORG-NTARG) 11, 12, 11
11 XTARG = PM (1) - X (NBT)
YTARG = PM (2) - Y (NBT)
ZTARG = PM (3) - Z (NBT)
RTA = SQRTF (XTARG*XTARG+YTARG*YTARG+ZTARG*ZTARG)
GO TO 14
12 XTARG = PM (1)
YTARG = PM (2)
ZTARG = PM (3)
RTA = SCEN
14 IF (NORG-1) 15, 16, 15
15 XSN = PM (1) - X (NBS)
YSN = PM (2) - Y (NBS)
ZSN = PM (3) - Z (NBS)
RSN = SQRTF (XSN*XSN+YSN*YSN+ZSN*ZSN)
GO TO 17
16 XSN = PM (1)
YSN = PM (2)
ZSN = PM (3)
RSN = SCEN
17 TOUT = T - TO
CALL HLO
WOT 10, 19, TOUT, T, DT, NORG
19 FORMAT (11H0 TIME=F9.4,14H TAPE TIME=F10.3,12H DELTA T=F
2 8.3,17H CENTER IS NO.13/112H0 POSIT FROM EARTH TA
3 RGET SUN CENTER VELOCITY AC
3 CELERATION )
20 WOT 10, 22, XEA, XTARG, XSN, PM (1), PM (4), SL (4)
22 FORMAT (8H X1P6E17.7)
WOT 10, 24, YEA, YTARG, YSN, PM (2), PM (5), SL (5)
24 FORMAT (8H Y1P6E17.7)
WOT 10, 26, ZEA, ZTARG, ZSN, PM (3), PM (6), SL (6)
26 FORMAT (8H Z1P6E17.7)
WOT 10, 28, REA, RTA, RSN, SCEN, VCEN
28 FORMAT (8H R1P6E17.7)
CALL WML

```

```

36 IF (SENSE SWITCH 1) 37, 42
37 PRINT 19, TOUT, T, DT, NORG
   PRINT 22, XEA, XTARG, XSN, PM (1), PM (4), SL (4)
39 PRINT 24, YEA, YTARG, YSN, PM (2), PM (5), SL (5)
   PRINT 26, ZEA, ZTARG, ZSN, PM (3), PM (6), SL (6)
   PRINT 28, REA, RTA, RSN, SCEN, VCEN
42 RETURN
   END (1,1,0,0,0,1)
   SUBROUTINE ORGN
4   IF (NORG) 6, 10, 6
6   WT (1) = WTS - WTV
   RAD(1) = RADORG
10  NORG = NEWORG
   IF (NORG) 12, 20, 12
12  IF (NORG-NB(1)) 13, 17, 13
13  DO 14 I = 2, N
   IF (NORG-NB(I)) 14, 15, 14
14  CONTINUE
   WOT 10, 50
50  FORMAT (1H010X, 22HORIGIN BODY IS MISSING )
   ERASE TEM
   GO TO 42
15  J = 1
   K = NB (1)
   NB (1) = NB (J)
   NB (J) = K
   TEM = WT (1)
   WT (1) = WT (J)
   WT (J) = TEM
   TEL = RAD (1)
   RAD (1) = RAD (J)
   RAD (J) = TEL
17  RAD1 = 3. * RAD (1)
   RAD2 = 100. * RAD (1)
   RADORG = RAD (1)
   RAD(1) = RADE
   WTS = WT (1) + WTV
   WTE = WT (1)
   GO TO 25
20  WTS = WTE + WTV
   RADORG = RADE
   RAD1 = 3. * RADE
   RAD2 = 100. * RADE
25  IF (NTARG) 29, 26, 29
26  IF (NORG) 28, 27, 28
27  NBT = 0
   GO TO 35
28  NBT = 1
   GO TO 35
29  IF (NTARG-NORG) 31, 30, 31
30  NBT = 0
   GO TO 35
31  DO 32 I = 1, N

```

THE ORIGINAL DOCUMENT WAS OF POOR
QUALITY. BEST POSSIBLE REPRODUCTION
FROM COPY FURNISHED ASTIA.

```
32 IF (NTARG-NB(1))32, 33, 32
   CONTINUE
   WOT 10,55
55 FORMAT (1H010X,22HTARGET BODY IS MISSING )
   ERASE TEM
   GO TO 42
33 NBT = 1
35 IF (NORG-1) 36, 39, 36
36 DO 38 I = 1, N
   IF (NB(I)-1) 38, 40, 38
38 CONTINUE
39 NBS = 0
   GO TO 41
40 NDS = 1
41 TEM = 1.
42 RETURN
   END (1,1,0,0,0,0)
   SUBROUTINE TITLE
   TEM = 1.
   WOT 10,3
3 FORMAT (1H15X,17HN BODY TRAJECTORY/1H010X,20HGENERAL ELECTRIC CO./
1 1H010X,8HM.S.V.D./1H0)
   WOT 10,5,TO
5 FORMAT (1H020X,22HSTARTING TABLE TIME = F10.3)
   IF (NEWORG) 10,7,10
7 ERASE TEM
   WOT 10,8,NEWORG,WTE
8 FORMAT (1H020X,14HORIGIN IS BODY12,8H MASS = 1PE14.6)
   GO TO 11
10 DO 12 I = 1,N
   IF (NEWORG-NB(I)) 12,9,12
9 WOT 10,8,NB(I),WT(I)
   GO TO 11
12 CONTINUE
11 IF (NTARG) 14,17,14
17 ERASE TEM
   WOT 10,13,NTARG,WTE
13 FORMAT (1H020X,19HDESTINATION IS BODY12,8H MASS = 1PE14.6)
   GO TO 20
14 DO 16 I = 1,N
   IF (NTARG-NB(I))16,15,16
15 WOT 10,13,NB(I),WT(I)
   GO TO 20
16 CONTINUE
19 FORMAT (1H020X,17HMASS OF VEHICLE = 1PE14.6)
20 WOT 10,19,WTV
   IF (N-1) 33,33,21
21 WOT 10,22
22 FORMAT (1H020X,17HOTHER BODIES ARE-)
   IF (TEM) 24,26,24
24 WOT 10,25,NOT,WTE
25 FORMAT (1H025X,6HBODY 11,8H MASS = 1PE14.6)
26 DO 32 I = 1,N
```

THE ORIGINAL DOCUMENT WAS OF POOR
 QUALITY. REPRODUCTION
 FROM COPY FURNISHED ASTIA.

```

27 IF (NEWORG-NB(1)) 27,32,27
28 IF (NTARG-NB(1)) 28,32,28
29 WOT 10,25,NB(1),WT(1)
32 CONTINUE
33 WOT 10,29,G(2)
29 FORMAT (1H020X,24HGRAVITATIONAL CONSTANT =1PE14.6)
   IF (MSDT) 34,36,34
34 WOT 10,35,DTA,DTB,DTC
35 FORMAT (1H020X,6HDT 1 =F7.3,3X,6HDT 2 =F7.3,3X,6HDT 3 =F7.3)
   GO TO 39
36 WOT 10,37,EP1,DTMAX
37 FORMAT (1H020X,24HEPSILON OF INTEGRATION = 1PE9.2,3X,18HMAXIMUM DE
1 LTA T = OPF5.1)
39 IF (MET) 40,42,40
40 WOT 10,41
41 FORMAT (1H020X,33HCOWELL AND ENCKE METHODS ARE USED)
   GO TO 50
42 IF (INKE) 43,46,43
43 WOT 10,44
44 FORMAT (1H020X,20HENCKE METHOD IS USED)
   GO TO 50
46 WOT 10,47
47 FORMAT (1H020X,21HCOWELL METHOD IS USED)
50 IF (INOSW) 52,54,52
52 WOT 10,53
53 FORMAT (1H020X,21HTHE ORIGIN MAY CHANGE)
   GO TO 58
54 WOT 10,55
55 FORMAT (1H020X,19HTHE ORIGIN IS FIXED)
58 RETURN
   END (1,1,0,0,0,0)
   SUBROUTINE TERP
10 DO 25 NN =NNN,65
20 IF (TL(NN)-T) 25, 30, 30
25 CONTINUE
26 DO 27 IT = 1, 7
   TL(IT) = TL(IT+60)
   DO 27 J = 1,9
     PX (J,IT) = PX (J,IT+60)
     PY (J,IT) = PY (J,IT+60)
27 PZ (J,IT) = PZ (J,IT+60)
   READ TAPE26, (TL(J), (PX(I,J),PY(I,J),PZ(I,J); I = 1,9), J = 8,67)
   NNN= 6
   GO TO 10
30 NNN = NN
   TI (1) = T - TL (NN-3)
   TI (2) = T - TL (NN-2)
   TI (3) = T - TL (NN-1)
   TI (4) = T - TL (NN)
   TI (5) = T - TL (NN+1)
   TI (6) = T - TL (NN+2)
32 IT = TI (4) * TI (5) * TI (6)
   TTT = TI (3)*TI

```

```

CL(1) = TI(2)*TTT/(-29859840.)
CL(2) = TI(1)*TTT/5971968.
CL(3) = TI(1) * TI(2) * TT /(- 2985984.)
TT = TI(1) * TI(2) * TI(3)
TTT = TI(4)*TT
CL(4) = TT * TI(5) * TI(6) / 2985984.
CL(5) = TTT*TI(6)/(-5971968.)
CL(6) = TTT*TI(5)/29859840.
33 DO 36 K = 1, N
    NA = NB(K)
34 X(K) = PX(NA,NN-3) * CL(1) + PX(NA,NN-2) * CL(2) + PX(NA,NN
1 -1) * CL(3) + PX(NA,NN) * CL(4) + PX(NA,NN+1) * CL(5) + PX(N
2 A,NN+2) * CL(6)
35 Y(K) = PY(NA,NN-3) * CL(1) + PY(NA,NN-2) * CL(2) + PY(NA,NN
1 -1) * CL(3) + PY(NA,NN) * CL(4) + PY(NA,NN+1) * CL(5) + PY(N
2 A,NN+2) * CL(6)
36 Z(K) = PZ(NA,NN-3) * CL(1) + PZ(NA,NN-2) * CL(2) + PZ(NA,NN
1 -1) * CL(3) + PZ(NA,NN) * CL(4) + PZ(NA,NN+1) * CL(5) + PZ(N
2 A,NN+2) * CL(6)
    IF (NORG) 40,43,40
40 DO 42 K = 2,N
    X(K) = X(K)-X
    Y(K) = Y(K)-Y
42 Z(K) = Z(K)-Z
    X = -X
    Y = -Y
    Z = -Z
43 RETURN
END (1,1,0,0,0,0)
SUBROUTINE INT
6 CALL FMPS(PM(4),PL(4),DT,RKM(1,1),RKL(1,1))
CALL FMPS(PM(5),PL(5),DT,RKM(1,2),RKL(1,2))
7 CALL FMPS(PM(6),PL(6),DT,RKM(1,3),RKL(1,3))
    SAM = PM(1)
    SAL = PL(1)
    SBM = PM(2)
    SBL = PL(2)
    SCH = PM(3)
    SCL = PL(3)
    CALL ACC
8 CALL FMPS(FMX,FLX,DT,RKM(1,4),RKL(1,4))
CALL FMPS(FMY,FLY,DT,RKM(1,5),RKL(1,5))
CALL FMPS(FMZ,FLZ,DT,RKM(1,6),RKL(1,6))
    CAL RKM-12
    SUB MGM
    SLW FM
    CAL RKL-12
    SUB MGM
    SLW FL
    CAL RKM-16
    SUB MGM
    SLW GM
    CAL RKL-16

```

```

H      SUB MGM
H      SLW GL
H      CAL RKM-20
H      SUB MGM
H      SLW HM
H      CAL RKL-20
H      SUB MGM
H      SLW HL
10     CALL FAD(PM(4),PL(4),FM,FL,AM,AL)
      CALL FAD(PM(5),PL(5),GM,GL,BM,BL)
      CALL FAD(PM(6),PL(6),HM,HL,CM,CL)
      CALL FMPS(AM,AL,DT,RKM(2,1),RKL(2,1))
      CALL FMPS(BM,BL,DT,RKM(2,2),RKL(2,2))
      CALL FMPS(CM,CL,DT,RKM(2,3),RKL(2,3))
H      CAL RKM
H      SUB MGM
H      SLW FM
H      CAL RKL
H      SUB MGM
H      SLW FL
H      CAL RKM-4
H      SUB MGM
H      SLW GM
H      CAL RKL-4
H      SUB MGM
H      SLW GL
H      CAL RKM-8
H      SUB MGM
H      SLW HM
H      CAL RKL-8
H      SUB MGM
H      SLW HL
14     CALL FAD (PM(1),PL(1),FM,FL,SAM,SAL)
      CALL FAD (PM(2),PL(2),GM,GL,SBM,SBL)
      CALL FAD (PM(3),PL(3),HM,HL,SCM,SCL)
      T = T+HAFDT
      CALL TERP
      CALL ACC
16     CALL FMPS(FMX,FLX,DT,RKM(2,4),RKL(2,4))
      CALL FMPS(FMY,FLY,DT,RKM(2,5),RKL(2,5))
      CALL FMPS(FMZ,FLZ,DT,RKM(2,6),RKL(2,6))
H      CAL RKM-13
H      SUB MGM
H      SLW FM
H      CAL RKL-13
H      SUB MGM
H      SLW FL
H      CAL RKM-17
H      SUB MGM
H      SLW GM
H      CAL RKL-17
H      SUB MGM
H      SLW GL

```

```

H      CAL RKM-21
H      SUB MGM
H      SLW HM
H      CAL RKL-21
H      SUB MGM
H      SLW HL
20     CALL FAD(PM(4),PL(4),FM,FL,AM,AL)
      CALL FAD(PM(5),PL(5),GM,GL,BM,BL)
      CALL FAD(PM(6),PL(6),HM,HL,CM,CL)
      CALL FMPS(AM,AL,DT,RKM(3,1),RKL(3,1))
      CALL FMPS(BM,BL,DT,RKM(3,2),RKL(3,2))
      CALL FMPS(CM,CL,DT,RKM(3,3),RKL(3,3))
      CAL RKM-1
      SUB MGM
      SLW FM
      CAL RKL-1
      SUB MGM
      SLW FL
      CAL RKM-5
      SUB MGM
      SLW GM
      CAL RKL-5
      SUB MGM
      SLW GL
      CAL RKM-9
      SUB MGM
      SLW HM
      CAL RKL-9
      SUB MGM
      SLW HL
24     CALL FAD (PM(1),PL(1),FM,FL,SAM,SAL)
      CALL FAD (PM(2),PL(2),GM,GL,SBM,SBL)
      CALL FAD (PM(3),PL(3),HM,HL,SCM,SCL)
      CALL ACC
      CALL FMPS(FMX,FLX,DT,RKM(3,4),RKL(3,4))
      CALL FMPS(FMY,FLY,DT,RKM(3,5),RKL(3,5))
      CALL FMPS(FMZ,FLZ,DT,RKM(3,6),RKL(3,6))
28     CALL FAD (PM(4),PL(4),RKM(3,4),RKL(3,4),AM,AL)
      CALL FAD (PM(5),PL(5),RKM(3,5),RKL(3,5),BM,BL)
      CALL FAD (PM(6),PL(6),RKM(3,6),RKL(3,6),CM,CL)
      CALL FMPS(AM,AL,DT,RKM(4,1),RKL(4,1))
      CALL FMPS(BM,BL,DT,RKM(4,2),RKL(4,2))
      CALL FMPS(CM,CL,DT,RKM(4,3),RKL(4,3))
32     CALL FAD (PM(1),PL(1),RKM(3,1),RKL(3,1),SAM,SAL)
      CALL FAD (PM(2),PL(2),RKM(3,2),RKL(3,2),SBM,SBL)
      CALL FAD (PM(3),PL(3),RKM(3,3),RKL(3,3),SCM,SCL)
      T = T+HAFDT
      CALL TERP
      VNZ = 1.
      CALL ACC
      VNZ = 0.
      CALL FMPS(FMX,FLX,DT,RKM(4,4),RKL(4,4))
      CALL FMPS(FMY,FLY,DT,RKM(4,5),RKL(4,5))

```

```

CALL FMPS(FMZ,FLZ,DT,RKM(4,6),RKL(4,6))
34 DO 42 NA = 1,6
   SDM = RKM(1,NA)
   SDL = RKL(1,NA)
   SEM = RKM(2,NA)
   SEL = RKL(2,NA)
   SFM = RKM(3,NA)
   SFL = RKL(3,NA)
   SGM = RKM(4,NA)
   SGL = RKL(4,NA)
36 CALL FAD (SEM,SEL,SFM,SFL,SEM,SEL)
   CALL FAD (SEM,SEL,SEM,SEL,SEM,SEL)
38 CALL FAD (SDM,SDL,SEM,SEL,SEM,SEL)
   CALL FAD (SGM,SGL,SEM,SEL,SEM,SEL)
   CALL FDYS (SEM,SEL,6.0,SEM,SEL)
   SFM = PM(NA)
   SFL = PL(NA)
40 CALL FAD (SFM,SFL,SEM,SEL,SFM,SFL)
   PM(NA) = SFM
42 PL(NA) = SFL
   RETURN
   END (1,1,0,0,0,0)
SUBROUTINE ACC
2   CALL SQ (SAM,SAL,AM,AL)
   CALL SQ (SBM,SBL,BM,BL)
   CALL SQ (SCM,SCL,CM,CL)
3   CALL FAD (AM,AL,BM,BL,RM,RL)
   CALL FAD (RM,RL,CM,CL,RO,RL)
4   CALL DPSGRT (RO,RL,RR,SS)
5   CALL FMP (RR,SS,RO,RL,RRM,RRL)
6   CALL FDY (WTS,ZER,RRM,RRL,TEM,TEL)
7   CALL FMP ( SAM , SAL , TEM,TEL,GMX,GLX)
   CALL FMP ( SBM , SBL , TEM,TEL,GMY,GLY)
   CALL FMP ( SCM , SCL , TEM,TEL,GMZ,GLZ)
70 IF (KOB) 71,8,71
71 CALL FMP (RO,RL,RRM,RRL,TI(1),TI(2))
   CALL FMPS (CM,CL,5.0,TEM,TEL)
   CALL FDY (TEM,TEL,RO,RL,TEM,TEL)
   CALL FSB (TEM,TEL,1.0,TEM,TEL)
72 CALL FDY (TEM,TEL,TI(1),TI(2),TEM,TEL)
   CALL FMPS(TEM,TEL,OBJ,TEM,TEL)
   CALL FMP (TEM,TEL,SAM,SAL,XM,XL)
   CALL FMP (TEM,TEL,SBM,SBL,YM,YL)
73 CALL FDY (2.0,ZER,TI(1),TI(2),ZM,ZL)
   CALL FMPS (ZM,ZL,OBJ,ZM,ZL)
   CALL FSB (TEM,TEL,ZM,ZL,ZM,ZL)
   CALL FMP (ZM,ZL,SCM,SCL,ZM,ZL)
74 CALL FSB (GMX,GLX,XM,XL,GMX,GLX)
   CALL FSB (GMY,GLY,YM,YL,GMY,GLY)
   CALL FSB (GMZ,GLZ,ZM,ZL,GMZ,GLZ)
8   ERASE SUMX,SULX,SUMY,SULY,SUMZ,SULZ
9   DO 29 J = 1, N
   XM = X (J)

```

```

YM = Y (J)
ZM = Z (J)
WTA = WT (J)
12 CALL FSBS (SAM,SAL,XM,XM,XL)
CALL FSBS (SBM,SBL,YM,YM,YL)
CALL FSBS (SCM,SCL,ZM,ZM,ZL)
13 CALL SQ (XM,XL,AM,AL)
CALL SQ (YM,YL,BM,BL)
CALL SQ (ZM,ZL,CM,CL)
14 CALL FAD (AM,AL,BM,BL,RM,RL)
CALL FAD (RM,RL,CM,CL,RM,RL)
15 CALL DPSQRT (RM,RL,RRR,SSS)
IF (VNZ) 16,17,16
16 DIS(J) = RM
DIST(J) = RRR
17 CALL FMP (RM,RL,RRR,SSS,RM,RL)
CALL FDY (XM,XL,RM,RL,AM,AL)
CALL FDY (YM,YL,RM,RL,BM,BL)
CALL FDY (ZM,ZL,RM,RL,CM,CL)
A = (X(J)*X(J)+Y(J)*Y(J)+Z(J)*Z(J))*1.5
BX = X(J)/A
BY = Y(J)/A
BZ = Z(J)/A
26 CALL FADS (AM,AL,BX,AM,AL)
CALL FADS (BM,BL,BY,BM,BL)
CALL FADS (CM,CL,BZ,CM,CL)
22 CALL FMPS (AM,AL,WTA,AM,AL)
CALL FMPS (BM,BL,WTA,BM,BL)
CALL FMPS (CM,CL,WTA,CM,CL)
23 CALL FAD (AM,AL,SUMX,SULX,SUMX,SULX)
CALL FAD (BM,BL,SUMY,SULY,SUMY,SULY)
25 CALL FAD (CM,CL,SUMZ,SULZ,SUMZ,SULZ)
CALL FAD (GMX,GLX,SUMX,SULX,FMX,FLX)
CALL FAD (GMY,GLY,SUMY,SULY,FMY,FLY)
32 CALL FAD (GMZ,GLZ,SUMZ,SULZ,FMZ,FLZ)
CALL FMPS (FMX,FLX,G,FMX,FLX)
CALL FMPS (FMY,FLY,G,FMY,FLY)
CALL FMPS (FMZ,FLZ,G,FMZ,FLZ)
RETURN
END (1,1,0,0,0,0)
SUBROUTINE SWITCH
1 WOT 10,2
2 FORMAT (8H0 SWITCH )
IF (DIST(NBT)-20.*RAD(NBT)) 5,5,8
5 DT = DT/8.
GO TO 10
8 DT = DT/2.
10 HAFDT = DT/2.
25 QM(1) = 137.
QM(2) = -300.
QM(3) = 300.
QM(4) = -200.
QM(5) = 75.

```

```

      QM(6) = -12,
      TSAVE = T
      IF (NNN-5) 14,14,15
14     NSAVE = 4
      GO TO 16
15     NSAVE = NNN-2
16     XPM = X(NBT)
      YPM = Y(NBT)
      ZPM = Z(NBT)
26     CALL FSBS (PM(1),PL(1),XPM,PPM(1),PPL(1))
      CALL FSBS (PM(2),PL(2),YPM,PPM(2),PPL(2))
      CALL FSBS (PM(3),PL(3),ZPM,PPM(3),PPL(3))
27     CALL FMPS (PPM(1),PPL(1),QM(1),WM(1),WL(1))
      CALL FMPS (PPM(2),PPL(2),QM(1),WM(2),WL(2))
      CALL FMPS (PPM(3),PPL(3),QM(1),WM(3),WL(3))
      DO 35 I = 2,6
28     CALL INT
29     SL(4) = RKM(4,4)/DT
      SL(5) = RKM(4,5)/DT
      SL(6) = RKM(4,6)/DT
      CALL OUT
      XM = X(NBT)
      YM = Y(NBT)
      ZM = Z(NBT)
      FM = QM(1)
      CALL FSBS(PM(1),PL(1),XM,QL(1),QL(2))
      CALL FSBS(PM(2),PL(2),YM,QL(3),QL(4))
      CALL FSBS(PM(3),PL(3),ZM,QL(5),QL(6))
30     CALL FMPS (QL(1),QL(2),FM,FMX,FLX)
      CALL FMPS (QL(3),QL(4),FM,FMY,FLY)
      CALL FMPS (QL(5),QL(6),FM,FMZ,FLZ)
      CALL FAD (WM(1),WL(1),FMX,FLX,WM(1),WL(1))
      CALL FAD (WM(2),WL(2),FMY,FLY,WM(2),WL(2))
35     CALL FAD (WM(3),WL(3),FMZ,FLZ,WM(3),WL(3))
      GM = -60.*DT
      CALL FDYS (WM(1),WL(1),GM,PPM(4),PPL(4))
      CALL FDYS (WM(2),WL(2),GM,PPM(5),PPL(5))
      CALL FDYS (WM(3),WL(3),GM,PPM(6),PPL(6))
      EPSL = SQRTF (PPM(1)**2+PPM(2)**2+PPM(3)**2)*4.0E-10
37     CALL ORGN
38     DO 40 I = 1,6
      PM(I) = PPM(I)
40     PL(I) = PPL(I)
      T = TSAVE
      IF (NNN-NSAVE) 41,43,42
41     BACKSPACE 26
      BACKSPACE 26
      READ TAPE26, (TL(J),(PX(I,J),PY(I,J),PZ(I,J)),I = 1,9),J = 8,67)
42     NNN = NSAVE
43     CALL TERP
      DO 44 I = 2,6
      CALL INT
44     WOT 10,45,T,PM(1),PM(2),PM(3)

```

```

45  FORMAT (1HOF12.4,1P3E17.7)
50  CALL FSB (QL(1),QL(2),PM(1),PL(1),SM(1),SL(1))
    CALL FSB (QL(3),QL(4),PM(2),PL(2),SM(2),SL(2))
    CALL FSB (QL(5),QL(6),PM(3),PL(3),SM(3),SL(3))
    DO 53 I = 1,3
52  IF (ABS(SM(I))-EPSL) 53,53,58
53  CONTINUE
55  RETURN
58  HM = I-TSAVE
    CALL FDYS (SM(1),SL(1),HM,PM(1),PL(1))
    CALL FDYS (SM(2),SL(2),HM,PM(2),PL(2))
    CALL FDYS (SM(3),SL(3),HM,PM(3),PL(3))
    CALL FAD (PPM(4),PPL(4),PM(1),PL(1),PPM(4),PPL(4))
    CALL FAD (PPM(5),PPL(5),PM(2),PL(2),PPM(5),PPL(5))
    CALL FAD (PPM(6),PPL(6),PM(3),PL(3),PPM(6),PPL(6))
    GO TO 38
END (1,1,0,0,0,0)
RECTIFICATION BY MARY ELLEN
SUBROUTINE RECT
EQUIVALENCE(WM(1),XIM),(WM(2),YIM),(WM(3),ZIM),(WM(4),XIDM),
1 (WM(6),ZIDM),(WM(5),YIDM),(WL(1),XIL),(WL(2),YIL),(WL(3),ZIL),
2 (WL(4),XIDL),(WL(5),YIDL),(WL(6),ZIDL)
DAC IX(9,67),IY(9,67),IZ(9,67),TL(67),RKM(4,6),RKL(4,6),NB(9),
1 WT(9),RAD(9), DUMMY(27),DIS(9),DIST(9),PM(6),PL(6),PPM(6),
2 PPL(6),QM(6),QL(6),WM(6),WL(6),XX(9),YY(9),ZZ(9),TI(6),CL(6)
COMMON NEWORG,ZER,FMX,FLX,FMY,FLY,FMZ,FLZ,AM,AL,BM,BL,CM,CL
COMMON NORG,NTARG,NSUN,N,NN,NNN,T,TO,TMAX,DTMAX,HAFDT,WTE,WTW,MGM,
1 XTARG,YTARG,ZTARG,SCEN,VCEN,SMAX,GMAX,EMAX,RAD1,RAD2,RADE,WTB,
2 NBE,NBT,NBS,RADORG,SAM,SBM,SCM, SAL,SBL,SCL,XIM,XIL,YIM,YIL,ZIM,
3 ZIL,XIDM,XIDL,YIDM,YIDL,ZIDM,ZIDL,RM,RL,RR,RO,SS,RRR,RKL,TEM,TEL,
4 GMX,GLX,GMY,GLY,GMZ,GLZ,SUMX,SULX,SUMY,SULY,SUMZ,SULZ,FM,FL,GM,GL,
5 HM,HL,RRR,SSS,XM,YM,ZM,A,BX,BY,BZ,WRM,WRL,RCM,RCL,ROM,RUL,RPPM,
6 XPM,XPL,YPM,YPL,ZPM,ZPL
7 KOB,VNZ,MEDT,MSDT,MDT,NOT,MET,ROUT,NCKE,TSAB,DTA,DTB,DTC,EP1
DAC XKSG(2), XMI(2)
DAC X(2),Y(2),Z(2),XDOT(2),YDOT(2),ZDOT(2),PX(2),PY(2),PZ(2),QX(2)
1 ,QY(2),QZ(2),XP(2),YP(2),ZP(2),XDOTP(2),YDOTP(2),ZDOTP(2),PI(2),
2 PI2(2),E(2),XMJ(2),CCON(2),XN(2)
COMMON A1,A2,FJ1,FJ2,SFJ1,SFJ2,CFJ1,CFJ2,S1,S2,EPS1
COMMON DT,DTNE,RPM
DAC SM(6),SL(6),XMJP(2)
COMMON OBJ,TSAB,REA,RTA,RSN,HPI,THPI,KK,NOSW
100 CALL FMP (X(1),X(2),XDOT(1),XDOT(2),RR1,RR2)
101 CALL FMP (Y(1),Y(2),YDOT(1),YDOT(2),T1,T2)
102 CALL FAD (T1,T2,RR1,RR2,RR1,RR2)
103 CALL FMP (Z(1),Z(2),ZDOT(1),ZDOT(2),T1,T2)
104 CALL FAD (T1,T2,RR1,RR2,RR1,RR2)
    VECTOR DOT PRODUCT OF R,RDOT IN LOCS. RR1,RR2
105 CALL SQ (XDOT(1),XDOT(2),SD1,SD2)
106 CALL SQ (YDOT(1),YDOT(2),T1,T2)
107 CALL FAD (SD1,SD2,T1,T2,SD1,SD2)
108 CALL SQ (ZDOT(1),ZDOT(2),T1,T2)
109 CALL FAD (T1,T2,SD1,SD2,SD1,SD2)

```

```

C      VECTOR DOT PRODUCT OF RDOT WITH ITSELF (SDOT**2) IN SD1,2
110 CALL SQ (X(1), X(2), AR1, AR2)
111 CALL SQ (Y(1), Y(2), T1, T2)
112 CALL FAD (T1, T2, AR1, AR2, AR1, AR2)
113 CALL SQ (Z(1), Z(2), T1, T2)
114 CALL FAD (T1, T2, AR1, AR2, AR1, AR2)
115 CALL DPSORT (AR1, AR2, AR1, AR2)
C      MAGNITUDE OF VECTOR R IN LOCS. AR1,AR2
120 CALL FMPS (XMI(1),XMI(2),XKSO(2),C1,C2)
121 CALL FDY (2.0, 0.0, AR1, AR2, T1, T2)
122 CALL FDY (SD1, SD2, C1, C2, TT1, TT2)
123 CALL FSB (T1, T2, TT1, TT2, T1, T2)
124 CALL FDY (1.0, 0.0, T1, T2, A1, A2)
C      SECTION 120-124 CALCULATES VALUE A, STORED IN LOCS. A1,A2
125 CALL FDY (AR1, AR2, A1, A2, T1, T2)
126 CALL FSB (1.0, 0.0, T1, T2, CON1, CON2)
130 IF (A1) 133, 131, 137
C      QUANTITY A = 0 INDICATES PARABOLIC ORBIT. SET A = -.1E-8 AND
C      USE EQUATIONS FOR HYPERBOLIC ORBIT.
131 A1 = -1.0 E-8
132 ERASE A2
133 CALL FMPS(A1,A2,-1.0,A1,A2)
C      SET A = ABSF(A) FOR COMPUTING EASE IN THIS SUBROUTINE
135 M = 1
C      QUANTITY A NEGATIVE INDICATES HYPERBOLIC ORBIT - SET M = 1
136 GO TO 138
C      QUANTITY A POSITIVE INDICATES ELLIPTIC ORBIT - SET M = 2
137 M = 2
138 CALL FMP(C1,C2,A1,A2,S1,S2)
139 CALL SQ (RR1,RR2,TT1,TT2)
140 CALL FDY (TT1,TT2,S1,S2,T1,T2)
141 CALL DPSGRT(S1,S2,S1,S2)
143 CALL FDY (RR1,RR2,S1,S2,SV1,SV2)
144 CALL CUBE(A1,A2,SAV1,SAV2)
C      EXTRA CALCULATIONS TO OBTAIN MAXIMUM ACCURACY
145 CALL SQ (CON1, CON2, TT1, TT2)
146 GO TO (147, 150), M
147 CALL FSB (TT1, TT2, T1, T2, ESQ1, ESQ2)
148 GO TO 151
150 CALL FAD (TT1, TT2, T1, T2, ESQ1, ESQ2)
151 CALL DPSORT (ESQ1, ESQ2, E(1), E(2))
C      E CALCULATED IN SECTION 143-151
153 IF (E(1)) 900,910,154
C      E = 0 INDICATES CIRCULAR ORBIT - ERROR RETURN - NERR = 3
154 CALL FDY (SV1, SV2, E(1), E(2), T1, T2)
155 CALL FDY (CON1, CON2, E(1), E(2), TT1, TT2)
156 GO TO (160, 180), M
C      SECTION 160 - 172 USED WHEN A IS NEG., M=1, HYPERBOLIC ORBIT
160 CALL FAD (T1, T2, TT1, TT2, T1, T2)
161 CALL DPLOG (T1, T2, FJ1, FJ2, I)
C      SECTION 160-161 CALCULATES FJ IN LOCS. FJ1,FJ2
162 GO TO (163, 900), I
163 CALL DPSINH (FJ1, FJ2, SFJ1, SFJ2, I)

```

THE ORIGINAL DOCUMENT WAS OF POOR
 QUALITY. BEST POSSIBLE REPRODUCTION
 FROM COPY FURNISHED ASTIA.

```

164 GO TO (165, 900), I
165 CALL FMP (E(1), E(2), SFJ1, SFJ2, T1, T2)
166 CALL FSB (T1, T2, FJ1, FJ2, XMJ(1), XMJ(2))
C      M SUB J COMPUTED IN SECTION 162-166, STORED XMJ(2)
167 CALL FSBS (ESQ1, ESQ2, 1.0, T1, T2)
168 CALL DPSORT (T1, T2, CCON(1), CCON(2))
C      ERROR RETURN - NERR = 4 - IF E SQUARED MINUS 1 IS NEGATIVE
170 CALL FDY(-1.0, 0.0, CCON(1), CCON(2), CON1, CON2)
171 CALL DPCOSH (FJ1, FJ2, CFJ1, CFJ2, I)
172 GO TO (200, 900), I
C      SECTION 180 - 195 USED WHEN A IS POSITIVE, M= 2, ELLIPTIC ORBIT
180 IF (T1) 181, 184, 184
181 IF (TT1) 182, 183, 183
182 NOP = 3
    GO TO 187
183 NOP = 4
    GO TO 187
184 IF (TT1) 185, 186, 186
185 NOP = 2
    GO TO 187
186 NOP = 1
187 IF (ABSF(T1) - ABSF(TT1)) 188, 189, 189
188 CALL SQ (TT1, TT2, TT1, TT2)
    CALL FSB (1.0, 0.0, TT1, TT2, TT1, TT2)
    CALL DPSORT (TT1, TT2, T1, T2)
C      ERROR RETURN NERR = 6 IF UNABLE TO CALC. COS EJ OR SIN EJ
189 CALL OPASIN (T1, T2, FJ1, FJ2, I)
    IF (I) 920, 920, 1890
1890 GO TO (1899, 1892, 1893, 1893), NOP
1892 CALL FSB (PI(1), PI(2), FJ1, FJ2, FJ1, FJ2)
    GO TO 1899
1893 XNUM = FJ1 / ABSF(FJ1)
1894 CALL FMPS(FJ1, FJ2, XNUM, FJ1, FJ2)
1895 GO TO (1899, 1899, 1896, 1897), NOP
1896 CALL FAD (PI(1), PI(2), FJ1, FJ2, FJ1, FJ2)
    GO TO 1899
1897 CALL FSB (PI2(1), PI2(2), FJ1, FJ2, FJ1, FJ2)
1899 CALL DPSC (FJ1, FJ2, SFJ1, SFJ2, CFJ1, CFJ2, I)
190 CALL FMP (E(1), E(2), SFJ1, SFJ2, T1, T2)
191 CALL FSB (FJ1, FJ2, T1, T2, XMJ(1), XMJ(2))
C      SECTION 186-191 COMPUTES M SUB J -STORED IN LOCS. XMJ(2)
192 CALL FSB (1.0, 0.0, ESQ1, ESQ2, T1, T2)
C      SECTION 192-195 FOR ELLIPTIC CASE PARALLELS SECTION 167-171
C      FOR HYPERBOLIC CASE
193 CALL DPSORT (T1, T2, CCON(1), CCON(2))
195 CALL FDY (1.0, 0.0, CCON(1), CCON(2), CON1, CON2)
C      SECTION 200 USED FOR BOTH TYPES OF ORBITS
200 CALL FDY (CFJ1, CFJ2, AR1, AR2, ESQ1, ESQ2)
201 CALL FDY (A1, A2, C1, C2, T1, T2)
    CALL DPSORT (T1, T2, T1, T2)
202 CALL FMP (T1, T2, SFJ1, SFJ2, RR1, RR2)
203 CALL FDY (SFJ1, SFJ2, AR1, AR2, SV1, SV2)
204 CALL FSB (CFJ1, CFJ2, E(1), E(2), TT1, TT2)

```

```

205 CALL FMP (TT1, TT2, T1, T2, SD1, SD2)
206 GO TO (207, 210), M
207 CALL FMPS(SV1,SV2,-1.0,SV1,SV2)
208 CALL FMPS(A1,A2,-1.0,A1,A2)
C      CHANGE SIGN OF A TO MINUS AGAIN
C      SECTION 210-218 CALCULATES 3 COMPONENTS OF VECTOR P FOR
C      BOTH TYPES OF ORBITS
210 CALL FMP (X(1), X(2), ESD1, ESQ2, TT1, TT2)
211 CALL FMP (XDOT(1), XDOT(2), RR1, RR2, T1, T2)
212 CALL FSB (TT1, TT2, T1, T2, PX(1), PX(2))
213 CALL FMP (Y(1), Y(2), ESD1, ESQ2, TT1, TT2)
214 CALL FMP (YDOT(1), YDOT(2), RR1, RR2, T1, T2)
215 CALL FSB (TT1, TT2, T1, T2, PY(1), PY(2))
216 CALL FMP (Z(1), Z(2), ESQ1, ESQ2, TT1, TT2)
217 CALL FMP (ZDOT(1), ZDOT(2), RR1, RR2, T1, T2)
218 CALL FSB (TT1, TT2, T1, T2, PZ(1), PZ(2))
C      SECTION 220-242 CALCULATES 3 COMPONENTS OF VECTOR Q FOR
C      BOTH TYPES OF ORBITS
220 CALL FMP (X(1), X(2), SV1, SV2, T1, T2)
221 CALL FMP (XDOT(1), XDOT(2), SD1, SD2, TT1, TT2)
222 CALL FAD (T1, T2, TT1, TT2, QX(1), QX(2))
223 CALL FMP (Y(1), Y(2), SV1, SV2, T1, T2)
224 CALL FMP (YDOT(1), YDOT(2), SD1, SD2, TT1, TT2)
225 CALL FAD (T1, T2, TT1, TT2, DY(1), DY(2))
226 CALL FMP (Z(1), Z(2), SV1, SV2, T1, T2)
227 CALL FMP (ZDOT(1), ZDOT(2), SD1, SD2, TT1, TT2)
228 CALL FAD (T1, T2, TT1, TT2, DZ(1), DZ(2))
240 CALL FMP (QX(1), QX(2), CON1, CON2, DX(1), QX(2))
241 CALL FMP (QY(1), DY(2), CON1, CON2, DY(1), QY(2))
242 CALL FMP (QZ(1), QZ(2), CON1, CON2, DZ(1), DZ(2))
245 CALL FDY (C1,C2,SAV1,SAV2,T1,T2)
246 CALL DPSORT (T1,T2,XN(1),XN(2))
250 RETURN
900 STOP 77777
910 STOP 77777
920 STOP 77777
END (1,1,D,D,0,0)
C      POSITIDN      BY MARY ELLEN
C      SUBROUTINE POSN
C      EQUIVALENCE (WM(1),XIM),(WM(2),YIM),(WM(3),ZIM),(WM(4),XIDM),
1 (WM(6),ZIDM),(WM(5),YIDM),(WL(1),XIL),(WL(2),YIL),(WL(3),ZIL),
2 (WL(4),XIDL),(WL(5),YIDL),(WL(6),ZIDL)
C      DAC IX(9,67),IY(9,67),IZ(9,67),TL(67),RKM(4,6),RKL(4,6),NB(9),
1 WT(9),RAD(9), DUMMY(27),DIS(9),DIST(9),PM(6),PL(6),PPM(6),
2 PPL(6),DR(6),DL(6),WM(6),WL(6),XX(9),YY(9),ZZ(9),TI(6),CL(6)
C      COMMON NEWDRG,ZER,FMX,FLX,FMY,FLY,FMZ,FLZ,AM,AL,BM,BL,CM,CL
C      COMMON NORG,NTARG,NSUN,N,NN,NNN,T,TD,TMAX,DTMAX,HAFDT,WTE,WTW,MGM,
1 XTARG,YTARG,ZTARG,SCEN,VCEN,SMAX,GMAX,EMAX,RAD1,RAD2,RADE,WTB,
2 NBE,NBT,NDS,RADDRG,SAM,SBM,SCM, SAL,SBL,SCL,XIM,XIL,YIM,YIL,ZIM,
3 ZIL,XIDM,XIDL,YIDM,YIDL,ZIDM,ZIDL,RM,RL,RR,RO,SS,RRM,RRL,TEM,TEL,
4 GMX,GLX,GMY,GLY,GMZ,GLZ,SUMX,SULX,SUMY,SULY,SUMZ,SULZ,FM,FL,GM,GL,
5 HM,HL,RRR,SSS,XM,YM,ZM,A,BX,BY,BZ,WRM,WRL,RCM,RCL,RDM,ROL,RPPM,
6 XPM,XPL,YPM,YPL,ZPM,ZPL,

```

THE ORIGINAL DOCUMENT WAS OF POOR
QUALITY. BEST POSSIBLE REPRODUCTION
FROM COPY FURNISHED ASTIA.

```

7 X0B,VNZ,MEDT,MSDT,MDT,NOT,MET,NOUT,NCKE,TSAB,DTA,DTB,DTC,EP1
  DAC XKSQ(2), XMI(2)
  DAC X(2),Y(2),Z(2),XDOT(2),YDOT(2),ZDOT(2),PX(2),PY(2),PZ(2),QX(2)
1  ,QY(2),QZ(2),XP(2),YP(2),ZP(2),XDOTP(2),YDOTP(2),ZDOTP(2),PI(2),
2  PI2(2),E(2),XMJ(2),CCON(2),XN(2)
  COMMON A1,A2,FJ1,FJ2,SFJ1,SFJ2,CFJ1,CFJ2,S1,S2,EPS1
  COMMON DTME,DT,RPM
  DAC SM(6),SL(6),XMJP(2)
  COMMON OBC,TSAB,REA,RTA,RSN,HPI,THPI,KK,NOSW
90  CALL FMP (A1,A2,CCON(1),CCON(2),TC1,TC2)
91  IF (A1) 92,900,99
92  CALL FMPS(TC1,TC2,-1.0,TC1,TC2)
C    QUANTITY A NEGATIVE INDICATES HYPERBOLIC ORBIT - SET M=1
93  M = 1
94  GO TO 102
C    QUANTITY A POSITIVE INDICATES ELLIPTIC ORBIT - SET M = 2
99  M = 2
102  CALL FMPS(XN(1),XN(2),DT,SD1,SD2)
103  CALL FAD (XMJ(1),XMJ(2),SD1,SD2,XMJP(1),XMJP(2))
104  EJ1 = FJ1
105  EJ2 = FJ2
C    USE VALUE EJ OR FJ AT T=1 FOR FIRST GUESS AT T= TJ +DELTA T
106  SEJ1 = SFJ1
107  SEJ2 = SFJ2
108  CEJ1 = CFJ1
109  CEJ2 = CFJ2
C    SECTION 110 - 160 DOES NEWTON-RAPHSON ITERATION FOR E(J+1)
110  DO 160 K = 1, 99
111  GO TO (120,112),M
112  CALL FMP (E(1),E(2),SEJ1,SEJ2,T1,T2)
113  CALL FSB (EJ1,EJ2,T1,T2,T1,T2)
114  CALL FMP (E(1),E(2),CEJ1,CEJ2,TT1,TT2)
115  CALL FSB (1.0,0.0,TT1,TT2,TT1,TT2)
116  GO TO 130
C    SECTION 112-116 INITIALIZES DELTA F CALC. FOR ELLIPTIC CASE
120  CALL FMP (E(1),E(2),SEJ1,SEJ2,T1,T2)
121  CALL FSB (T1,T2,EJ1,EJ2,T1,T2)
122  CALL FMP (E(1),E(2),CEJ1,CEJ2,TT1,TT2)
123  CALL FSB (TT1,TT2,1.0,TT1,TT2)
C    SECTION 120-123 INITIALIZES DELTA F CALC. FOR HYPERBOLIC CASE
130  CALL FSB (XMJP(1),XMJP(2),T1,T2,XNJ1,XNJ2)
131  CALL FDY (XNJ1,XNJ2,TT1,TT2,DEJ1,DEJ2)
132  IF (ABS(DEJ1)-EPS1) 170, 170, 140
140  CALL FAD (EJ1,EJ2,DEJ1,DEJ2,EJ1,EJ2)
C    REPLACE OLD GUESS WITH NEW ONE
148  GO TO (155,150),M
150  CALL DPSC (EJ1,EJ2,SEJ1,SEJ2,CEJ1,CEJ2,1)
151  GO TO 160
155  CALL DPSINH (EJ1,EJ2,SEJ1,SEJ2,1)
156  GO TO (157,900), 1
157  CALL DPCOSH (EJ1,EJ2,CEJ1,CEJ2,1)
158  GO TO (160,900), 1
160  CONTINUE

```

```

C          GIVE NEWTON-RAPHSON 99 CHANCES TO CONVERGE
161 GO TO 900
C          MAKE ALL SORTS OF TESTS ON SIN,COS EJ TO DETERMINE FINAL VALUE
C          EJ AT T+DELTA T - SECTION 171-193 FOR ELLIPTIC CASE
170 GO TO (200,171),M
171 IF (SEJ1) 176,178,172
172 IF (CEJ1) 176,176,173
173 AMAX = HPI
174 ERASE XMIN
175 GO TO 183
176 XMAX = PI
177 XMIN = HPI
178 GO TO 183
178 IF (CEJ1) 179,179,181
179 XMAX = THPI
180 XMIN = PI
181 GO TO 183
181 XMAX = PI2(1)
182 XMIN = THPI
183 IF (EJ1 -XMAX) 184,200,185
184 IF (EJ1 -XMIN) 186,200,200
185 CALL FSD(EJ1,EJ2,PI2(1),PI2(2),EJ1,EJ2)
186 GO TO 187
186 CALL FAD (EJ1,EJ2,PI2(1),PI2(2),EJ1,EJ2)
187 IF (EJ1 -XMAX) 188,110,185
188 IF (EJ1 -XMIN) 186,110,110
200 CALL FSD (CEJ1,CEJ2,EI1),E(2),T1,T2)
201 CALL FMP (T1,T2,A1,A2,XW1,XW2)
202 CALL FMP(TC1,TC2,SEJ1,SEJ2,YW1,YW2)
C          SECTION 200-202 COMPUTES XW AND YW AT J+1
204 CALL SQ (XW1,XW2,T1,T2)
205 CALL SQ (YW1,YW2,TT1,TT2)
206 CALL FAD (T1,T2,TT1,TT2,T1,T2)
207 CALL DPSQRT (T1,T2,AR1,AR2)
C          SECTION 210-215 COMPUTES XW DOT, YW DOT AT J+1
210 CALL FMP (S1,S2,SEJ1,SEJ2,T1,T2)
211 CALL FDY (T1,T2,AR1,AR2,XWD1,XWD2)
212 CALL FMPS (XWD1,XWD2,-1.0,XWD1,XWD2)
213 CALL FMP(S1,S2,CCON(1),CCON(2),T1,T2)
214 CALL FMP (T1,T2,CEJ1,CEJ2,T1,T2)
215 CALL FDY (T1,T2,AR1,AR2,YWD1,YWD2)
C          SECTION 220-228 COMPUTES 3COMPONENTS OF VECTORS R,ROOT AT
C          T = T +DELTA T (J+1)
220 CALL FMP (XW1,XW2,PX(1),PX(2),T1,T2)
221 CALL FMP (YW1,YW2,QX(1),QX(2),TT1,TT2)
222 CALL FAD (T1,T2,TT1,TT2,XP(1),XP(2))
223 CALL FMP (XW1,XW2,PY(1),PY(2),T1,T2)
224 CALL FMP (YW1,YW2,QY(1),QY(2),TT1,TT2)
225 CALL FAD (T1,T2,TT1,TT2,YP(1),YP(2))
226 CALL FMP (XW1,XW2,PZ(1),PZ(2),T1,T2)
227 CALL FMP (YW1,YW2,QZ(1),QZ(2),TT1,TT2)
228 CALL FAD (T1,T2,TT1,TT2,ZP(1),ZP(2))
      CALL SQ (XP(1),XP(2),AM,AL)

```

THE ORIGINAL DOCUMENT WAS OF POOR
 QUALITY. BEST POSSIBLE REPRODUCTION
 FROM COPY FURNISHED ASTIA

```

CALL SQ (YP(1),YP(2),BM,BL)
CALL SQ (ZP(1),ZP(2),CM,CL)
CALL FAD (AM,AL,BM,BL,RCM,RCL)
CALL FAD (CM,CL,KCM,RCL,RPM,RPL)
CALL DPSURT (RPM,RPL,RCM,RCL)
CALL FMP (KCM,RCL,RPM,RPL,RCM,RCL)
CALL FDY (XMI,ZER,RCM,RCL,RWM,RWL)
CALL FMP (XP(1),XP(2),RWM,RWL,XPM,XPL)
CALL FMP (YP(1),YP(2),RWM,RWL,YPM,YPL)
CALL FMP (ZP(1),ZP(2),RWM,RWL,ZPM,ZPL)
IF (VNZ) 230,243,230
230 CALL FMP (XWD1,XWD2,PX(1),PX(2),T1,T2)
231 CALL FMP (YWD1,YWD2,QX(1),QX(2),TT1,TT2)
232 CALL FAD (T1,T2,TT1,TT2,XDUTP(1),XDUTP(2))
233 CALL FMP (XWD1,XWD2,PY(1),PY(2),T1,T2)
234 CALL FMP (YWD1,YWD2,QY(1),QY(2),TT1,TT2)
235 CALL FAD (T1,T2,TT1,TT2,YDUTP(1),YDUTP(2))
236 CALL FMP (XWD1,XWD2,PZ(1),PZ(2),T1,T2)
237 CALL FMP (YWD1,YWD2,QZ(1),QZ(2),TT1,TT2)
238 CALL FAD (T1,T2,TT1,TT2,ZDUTP(1),ZDUTP(2))
243 FJ1 = EJ1
    FJ2 = EJ2
    RETURN
900 STOP 77777
    END (1,1,0,0,0,0)
    SUBROUTINE INTN
      6 CALL FMPS (XIDM,XIDL,DT,RKM(1,1),RKL(1,1))
        CALL FMPS (YIDM,YIDL,DT,RKM(1,2),RKL(1,2))
        CALL FMPS (ZIDM,ZIDL,DT,RKM(1,3),RKL(1,3))
      8 SAM = PM (1)
        SAL = PL (1)
        SBM = PM (2)
        SBL = PL (2)
        SCM = PM (3)
        SCL = PL (3)
        CALL ACCN
      12 CALL FMPS (FMX,FLX,DT,RKM(1,4),RKL(1,4))
        CALL FMPS (FMY,FLY,DT,RKM(1,5),RKL(1,5))
        CALL FMPS (FMZ,FLZ,DT,RKM(1,6),RKL(1,6))
        CAL RKM-12
          SUB MGM
          SLW FM
        CAL RKL-12
          SUB MGM
          SLW FL
        CAL RKM-16
          SUB MGM
          SLW GM
        CAL RKL-16
          SUB MGM
          SLW GL
        CAL RKM-20
          SUB MGM
  
```

```

H      SLW HM
H      CAL RKL-20
H      SUB MGM
H      SLW HL
14     CALL FAD (XIDM,XIDL,FM,FL,AM,AL)
      CALL FAD (YIDM,YIDL,GM,GL,DM,DL)
      CALL FAD (ZIDM,ZIDL,HM,HL,CM,CL)
      CALL FMPS (AM,AL,DT,RKM(2,1),RKL(2,1))
      CALL FMPS (DM,DL,DT,RKM(2,2),RKL(2,2))
      CALL FMPS (CM,CL,DT,RKM(2,3),RKL(2,3))
      CAL RKM
      SUB MGM
      SLW FM
      CAL RKL
      SUB MGM
      SLW FL
      CAL RKM-4
      SUB MGM
      SLW GM
      CAL RKL-4
      SUB MGM
      SLW GL
      CAL RKM-8
      SUB MGM
      SLW HM
      CAL RKL-8
      SUB MGM
      SLW HL
18     DTME = DTME + HAFDT
      T = T + HAFDT
      CALL TERP
      CALL POSN
20     CALL FAD (XIM,XIL,XP(1),XP(2),XAM,XAL)
      CALL FAD (YIM,YIL,YP(1),YP(2),YAM,YAL)
      CALL FAD (ZIM,ZIL,ZP(1),ZP(2),ZAM,ZAL)
      CALL FAD (XAM,XAL,FM,FL,SAM,SAL)
      CALL FAD (YAM,YAL,GM,GL,SBM,SBL)
      CALL FAD (ZAM,ZAL,HM,HL,SCM,SCL)
22     CALL ACCN
      CALL FMPS (FMX,FLX,DT,RKM(2,4),RKL(2,4))
      CALL FMPS (FMY,FLY,DT,RKM(2,5),RKL(2,5))
      CALL FMPS (FMZ,FLZ,DT,RKM(2,6),RKL(2,6))
      CAL RKM-13
      SUB MGM
      SLW FM
      CAL RKL-13
      SUB MGM
      SLW FL
      CAL RKM-17
      SUB MGM
      SLW GM
      CAL RKL-17
      SUB MGM

```

THE ORIGINAL DOCUMENT WAS OF POOR
QUALITY. BEST POSSIBLE REPRODUCTION
FROM COPY FURNISHED ASTIA.

```

H      SLW GL
H      CAL RKM-21
H      SUB MGM
H      SLW HM
H      CAL RKL-21
H      SUB MGM
H      SLW HL
24     CALL FAD (XIDM,XIDL,FM,FL,AM,AL)
        CALL FAD (YIDM,YIDL,GM,GL,BM,BL)
        CALL FAD (ZIDM,ZIDL,HM,HL,CM,CL)
        CALL FMPS (AM,AL,DT,RKM(3,1),RKL(3,1))
        CALL FMPS (BM,BL,DT,RKM(3,2),RKL(3,2))
        CALL FMPS (CM,CL,DT,RKM(3,3),RKL(3,3))
        CAL RKM-1
        SUB MGM
        SLW FM
        CAL RKL-1
        SUB MGM
        SLW FL
        CAL RKM-5
        SUB MGM
        SLW GM
        CAL RKL-5
        SUB MGM
        SLW GL
        CAL RKM-9
        SUB MGM
        SLW HM
        CAL RKL-9
        SUB MGM
        SLW HL
28     CALL FAD (XAM,XAL,FM,FL,SAM,SAL)
        CALL FAD (YAM,YAL,GM,GL,SBM,SBL)
        CALL FAD (ZAM,ZAL,HM,HL,SCM,SCL)
        CALL ACCN
        CALL FMPS (FMX,FLX,DT,RKM(3,4),RKL(3,4))
        CALL FMPS (FMY,FLY,DT,RKM(3,5),RKL(3,5))
        CALL FMPS (FMZ,FLZ,DT,RKM(3,6),RKL(3,6))
32     CALL FAD (XIDM,XIDL,RKM(3,4),RKL(3,4),AM,AL)
        CALL FAD (YIDM,YIDL,RKM(3,5),RKL(3,5),BM,BL)
        CALL FAD (ZIDM,ZIDL,RKM(3,6),RKL(3,6),CM,CL)
        CALL FMPS (AM,AL,DT,RKM(4,1),RKL(4,1))
        CALL FMPS (BM,BL,DT,RKM(4,2),RKL(4,2))
        CALL FMPS (CM,CL,DT,RKM(4,3),RKL(4,3))
36     DTME = DTME + HAFDT
        T = T + HAFDT
        CALL TERP
        VNZ = 1.
        CALL POSN
40     CALL FAD (XIM,XIL,RKM(3,1),RKL(3,1),AM,AL)
        CALL FAD (YIM,YIL,RKM(3,2),RKL(3,2),BM,BL)
        CALL FAD (ZIM,ZIL,RKM(3,3),RKL(3,3),CM,CL)
        CALL FAD (AM,AL,XP(1),XP(2),SAM,SAL)

```

```

CALL FAD (BM,BL,YP(1),YP(2),SBM,SBL)
CALL FAD (CM,CL,ZP(1),ZP(2),SCM,SCL)
CALL ACCN
ERASE VNZ
CALL FMPS (FMX,FLX,DT,RNM(4,4),RKL(4,4))
CALL FMPS (FMY,FLY,DT,RNM(4,5),RKL(4,5))
CALL FMPS (FMZ,FLZ,DT,RNM(4,6),RKL(4,6))
44 DO 52 NA = 1,6
   SUM = RNM(1,NA)
   SDL = RKL(1,NA)
   SEM = RNM(2,NA)
   SEL = RKL(2,NA)
   SFM = RNM(3,NA)
   SFL = RKL(3,NA)
   SGM = RNM(4,NA)
   SGL = RKL(4,NA)
46 CALL FAD (SEM,SEL,SFM,SFL,SEM,SEL)
CALL FAD (SEM,SEL,SEM,SEL,SEM,SEL)
48 CALL FAD (SDM,SDL,SEM,SEL,SEM,SEL)
CALL FAD (SGM,SGL,SEM,SEL,SEM,SEL)
CALL FDYS (SEM,SEL,6.0,SEM,SEL)
SFM = WM(NA)
SFL = WL(NA)
50 CALL FAD (SFM,SFL,SEM,SEL,SFM,SFL)
WM(NA) = SFM
52 WL(NA) = SFL
RETURN
END (1,1,0,0,0,0)
SUBROUTINE ACCN
2 CALL SQ (SAM,SAL,AM,AL)
CALL SQ (SBM,SBL,BM,BL)
CALL SQ (SCM,SCL,CM,CL)
3 CALL FAD (AM,AL,BM,BL,RM,RL)
CALL FAD (RM,RL,CM,CL,RO,RL)
4 CALL DPSORT (RO,RL,RR,SS)
5 CALL FMP (RR,SS,RO,RL,RRM,RRL)
6 CALL FDY (WTS,ZER,RRM,RRL,TEM,TEL)
7 CALL FMP ( SAM , SAL , TEM,TEL,GMX,GLX)
CALL FMP ( SBM , SBL , TEM,TEL,GMY,GLY)
CALL FMP ( SCM , SCL , TEM,TEL,GMZ,GLZ)
CALL FSB (GMX,GLX,XPM,XPL,GMX,GLX)
CALL FSB (GMY,GLY,YPM,YPL,GMY,GLY)
CALL FSB (GMZ,GLZ,ZPM,ZPL,GMZ,GLZ)
70 IF (KOB) 71,8,71
71 CALL FMP (RO,RL,RRM,RRL,TI(1),TI(2))
CALL FMPS (CM,CL,5.0,TEM,TEL)
CALL FDY (TEM,TEL,RO,RL,TEM,TEL)
CALL FSB (TEM,TEL,1.0,TEM,TEL)
72 CALL FDY (TEM,TEL,TI(1),TI(2),TEM,TEL)
CALL FMPS (TEM,TEL,OBJ,TEM,TEL)
CALL FMP (TEM,TEL,SAM,SAL,XM,XL)
CALL FMP (TEM,TEL,SBM,SBL,YM,YL)
73 CALL FBY (2.0,ZER,TI(1),TI(2),ZM,ZL)

```

THE ORIGINAL DOCUMENT WAS OF POOR
QUALITY. BEST POSSIBLE REPRODUCTION
FROM COPY FURNISHED ASTIA.

```

CALL FMPS (ZM,ZL,OBJ,ZM,ZL)
CALL FSD (TEM,TEL,ZM,ZL,ZM,ZL)
CALL FMP (ZM,ZL,SCM,SCL,ZM,ZL)
74 CALL FSB (GMX,GLX,XM,XL,GMX,GLX)
CALL FSB (GMY,GLY,YM,YL,GMY,GLY)
CALL FSB (GMZ,GLZ,ZM,ZL,GMZ,GLZ)
8 ERASE SUMX,SULX,SUMY,SULY,SUMZ,SULZ
9 DO 29 J = 1, N
  XM = X (J)
  YM = Y (J)
  ZM = Z (J)
  WTA = WT (J)
12 CALL FSDS (SAM,SAL,XM,XM,XL)
CALL FSDS (SBM,SBL,YM,YM,YL)
CALL FSDS (SCM,SCL,ZM,ZM,ZL)
13 CALL SO (XM,XL,AM,AL)
CALL SO (YM,YL,BM,BL)
CALL SO (ZM,ZL,CM,CL)
14 CALL FAD (AM,AL,DM,DL,RM,RL)
CALL FAD (RM,RL,CM,CL,RM,RL)
15 CALL UPSORT (RM,RL,RRR,SSS)
IF (VNZ) 16,17,16
16 DIS(J) = RM
DIST(J) = RRR
17 CALL FMP (RM,RL,RRR,SSS,RM,RL)
CALL FDY (XM,XL,RM,RL,AM,AL)
CALL FDY (YM,YL,RM,RL,BM,BL)
CALL FDY (ZM,ZL,RM,RL,CM,CL)
A = (X(J)*X(J)+Y(J)*Y(J)+Z(J)*Z(J))**1.5
BX = X(J)/A
BY = Y(J)/A
BZ = Z(J)/A
26 CALL FADS (AM,AL,BX,AM,AL)
CALL FADS (BM,BL,BY,BM,BL)
CALL FADS (CM,CL,BZ,CM,CL)
22 CALL FMPS (AM,AL,WTA,AM,AL)
CALL FMPS (BM,BL,WTA,BM,BL)
CALL FMPS (CM,CL,WTA,CM,CL)
23 CALL FAD (AM,AL,SUMX,SULX,SUMX,SULX)
CALL FAD (BM,BL,SUMY,SULY,SUMY,SULY)
29 CALL FAD (CM,CL,SUMZ,SULZ,SUMZ,SULZ)
CALL FAD (GMX,GLX,SUMX,SULX,FMX,FLX)
CALL FAD (GMY,GLY,SUMY,SULY,FMY,FLY)
32 CALL FAD (GMZ,GLZ,SUMZ,SULZ,FMZ,FLZ)
CALL FMPS (FMX,FLX,G,FMX,FLX)
CALL FMPS (FMY,FLY,G,FMY,FLY)
CALL FMPS (FMZ,FLZ,G,FMZ,FLZ)
RETURN
END (1,1,0,0,0,0)

```

APPENDIX B

OPERATIONAL DIRECTORIES, LISTING AND CHECK PROBLEMS FOR SECTIONS II, III AND IV

A. TWO POSITION VECTOR PROGRAM

a. Operational Directory

Purpose

To find the position and velocity vector of an observed body at time T_0 from two-range vectors.

Usage

Input - All decimal input is read by a modified DBC FORTRAN sub-routine which accepts variable length fields. All fields are floating point numbers except for starred fields which are integers. Following is the list of input quantities in the order in which they are read into the program. All range measurements must be converted to units of earth's equatorial radius (6378.388 km. = equatorial radius of earth). All angles are to be expressed in degrees and decimals of a degree. Time is to be in days and decimals of a day.

Field 1 - ρ_0	Magnitude of range measurement at time, T_0
Field 2 - ρ_1	Magnitude of range measurement at time, T_1
Field 3 - X_0 ,	Geocentric, equatorial coordinates
Field 4 - Y_0 ,	of observer's position on earth
Field 5 - Z_0 ,	at time, T_0 .
Field 6 - X_1 ,	Geocentric, equatorial coordinates
Field 7 - Y_1 ,	of observer's position on earth

Field 8 - Z_1 , at time, T .

Field 9 - δ_0 Declination of observed body at time, T_0 .

Field 10 - δ_1 Declination of observed body at time, T_1

Field 11 - α_0 Right ascension of observed body at time, T_0

Field 12 - α_1 Right ascension of observed body at time, T_1

Field 13 - T_0 , Time

Field 14 - T_1 , Time

Field 15 - Control parameter, KO. If $KO \leq 0$, the unit of time will be equal to 806.996813 sec.. If $KO \geq 1$, the unit of time will be 58.132441 days.

Sample Input

Card 1

F 1.41889, 1.47513, 1.00082, .05063, .02196*

Card 2

F 2.3587, -.27808, -.19578, -9.34, -10.51*

Card 3

F 342.34, 341.465, 72.5, 80.5, XO*

Output - The X, Y, Z components of the position vector are printed in units of Earth's equatorial radius, kilometers, and astronomical units. The $\dot{X}$, $\dot{Y}$, $\dot{Z}$ components of the velocity vector are printed in units of Earth's equatorial radius per 806.996813 sec., km. per sec. and A. U. per hr., if $KO \leq 0$. If $KO \geq 1$, the velocity will be printed out in units of Earth's equatorial radius per 58.132441 days, km. per sec. and A. U. per hr.

b. Two Position Vector Program

```
DIMENSION PM(6), PL(6), PZM(6), PZL(6)
1  RITZ, 16, RHO, RHOI, XO, YO, ZO, XI, YI, ZI, PHIO, PHII, ALPO,
1  ALPI, TO, TI, KO
16  FORMAT (515)
    ERASE K, KNT
    NO = 1
2  CALL DPSC(PHIO, O., SPOM, SPOL, CPOM, CPOL, O)
    CALL DPSC(PHII, O., SPIM, SPIL, CPIM, CPIL, O)
    CALL DPSC(ALPO, O, SAOM, SAOL, CAOM, CAOL, O)
    CALL DPSC(ALPI, O., SAIM, SAIL, CAIM, CAIL, O)
    CALL FMP(CPOM, CPOL, CAOM, CAOL, CCM, CCL)
    CALL FMPS(CCM, CCL, RHO, CCM, CCL)
    CALL FADS(CCM, CCL, XO, PM(1), PL(1) )
    CALL FMP(CPOM, CPOL, SAOM, SAOL, CCM, CCL)
    CALL FMPS(CCM, CCL, RHO, CCM, CCL)
    CALL FADS(CCM, CCL, YO, PM(2), PL(2) )
    CALL FMPS(SPOM, SPOL, RHO, CCM, CCL)
    CALL FADS(CCM, CCL, ZO, PM(3), PL(3) )
    CALL FMP(CPIM, CPIL, CAIM, CAIL, CCM, CCL)
    CALL FMPS(CCM, CCL, RHOI, CCM, CCL)
    CALL FADS(CCM, CCL, XI, XIM, XIL)
    CALL FMP(CPIM, CPIL, SAIM, SAIL, CCM, CCL)
    CALL FMPS(CCM, CCL, RHOI, CCM, CCL)
    CALL FADS(CCM, CCL, YI, YIM, YIL)
    CALL FMPS(SPIM, SPIL, RHOI, CCM, CCL)
    CALL FADS(CCM, CCL, ZI, ZIM, ZIL)
3  CALL SQ(PM(1), PL(1), XSQOM, XSQOL)
    CALL SQ(PM(2), PL(2), YSQOM, YSQOL)
    CALL SQ(PM(3), PL(3), ZSQOM, ZSQOL)
```

CALL FAD(XSQOM, XSQOL, YSQOM, YSQOL, CCM, CCL)
 CALL FAD(ZSQOM, ZSQOL, CCM, CCL, RO2M, RO2L)
 CALL DPSQRT(RO2M, RO2L, ROM, ROL)
 CALL CUBE(ROM, ROL, ROCM, ROCL)
 CALL FDY(1., 0., ROCM, ROCL, MUM, MUL)
 CALL FSBS(TI, 0., TO, CCM, CCL)
 IF (KO) 30, 30, 31
 30 TU = 1.7072813E+2
 GO TO 32
 31 TU = .017202098
 32 CALL FMPS(CCM, CCL, TU, TAUM, TAUL)
 CALL SQ(TAUM, TAUL, TAU2M, TAU2L)
 CALL CUBE(TAUM, TAUL, TAU3M, TAU3L)
 CALL SQ(TAU2M, TAU2L, TAU4M, TAU4L)
 CALL FMP(TAU2M, TAU2L, TAU3M, TAU3L, TAU5M, TAU5L)
 CALL FMP(MUM, MUL, TAU3M, TAU3L, MTM, MTL)
 CALL FDYS(MTM, MTL, 6., GIM, GIL)
 CALL FSB(TAUM, TAUL, GIM, GIL, GIM, GIL)
 CALL FMP(MUM, MUL, TAU2M, TAU2L, FIM, FIL)
 CALL FMPS(FIM, FIL, .5, FIM, FIL)
 CALL FSB(1., 0., FIM, FIL, FIM, FIL)
 CALL FMPS(MTM, MTL, .5, AM, AL)
 CALL FMP(MUM, MUL, TAU4M, TAU4L, MCM, MCL)
 CALL FDYS(MCM, MCL, 24., CM, CL)
 CALL FMPS(MCM, MCL, .25, HM, HL)
 CALL FMP(MUM, MUL, TAU5M, TAU5L, MDM, MDL)
 CALL FDYS(MDM, MDL, -8., EM, EL)
 CALL FDYS(MDM, MDL, 120., OM, OL)
 CALL FAD(MUM, MUL, MUM, MUL, DM, DL)
 CALL FMPS(DM, DL, 4., QM, QL)
 GM = GIM

```

GL = GIL
FM = FIM
FL = FIL
4 CALL FMP(PM(1), PL(1), FM, FL, CCM, CCL)
  CALL FSB(XIM, XIL, CCM, CCL, CCM, CCL)
  CALL FDY(CCM, CCL, GM, GL, DXOM, DXOL)
  CALL FMP(PM(2), PL(2), FM, FL, CCM, CCL)
  CALL FSB(YIM, YIL, CCM, CCL, CCM, CCL)
  CALL FDY(CCM, CCL, GM, GL, DYOM, DYOL)
  CALL FMP(PM(3), PL(3), FM, FL, CCM, CCL)
  CALL FSB(ZIM, ZIL, CCM, CCL, CCM, CCL)
  CALL FDY(CCM, CCL, GM, GL, DZOM, DZOL)
  GO TO (9, 10), NO
9 NO = 2
  GO TO 6
10 CALL FSB(DXOM, DXOL, DXM, DXL, DIXM, DIXL)
  IF (ABSF(DIXM) -4E-8) 11, 11, 5
11 CALL FSB(DYOM, DYOL, DYM, DYL, DIYM, DIYL)
  IF (ABSF(DIYM) 04E-8) 12, 12, 5
12 CALL FSB(DZOM, DZOL, DZM, DZL, DIZM, DIZL)
  IF (ABSF(DIZM) -4E-8) 13, 13, 5
13 K = K + 1
  IF (K-2) 6, 14, 14
5 ERASE K
6 KNT = KNT + 1
  CALL SQ(DXOM, DXOL, DSQXM, DSQXL)
  CALL SQ(DYOM, DYOL, DSQYM, DSQYL)
  CALL SQ(DZOM, DZOL, DSQZM, DSQZL)
  CALL FAD(DSQXM, DSQXL, DSQYM, DSQYL, DSM, DSL)
  CALL FAD(DSM, DSL, DSQZM, DSQZL, DRO2M, DRO2L)
  CALL FMP(PM(1), PL(1), DXOM, DXOL, XDXM, XDXL)

```

CALL FMP(PM(2), PL(2), DYOM, DYOL, YDYM, YDYL)
 CALL FMP(PM(3), PL(3), DZOM, DZOL, ZDZM, ZDZL)
 CALL FAD(XDXM, XDXL, YDYM, YDYL, CCM, CCL)
 CALL FAD(CCM, CCL, ZDZM, ZDZL, RDRM, RDRL)
 CALL FDY(RDRM, RDRL, RO2M, RO2L, SIGMAM, SIGMAL)
 CALL FDY(DRO2M, DRO2L, RO2M, RO2L, OMEGAM, OMEGAL)
 CALL SQ(SIGMAM, SIGMAL, SIGMSM, SIGMSL)
 CALL FMPS(SIGMSM, SIGMSL, 7., RM, RL)
 CALL FMPS(SIGMSM, SIGMSL, 15., SM, SL)
 CALL FMPS(SM, SL, 3., TM, TL)
 CALL FMPS(OMEGAM, OMEGAL, 3., UM, UL)
 CALL FMPS(UM, UL, 3., VM, VL)
 CALL FMP(AM, AL, SIGMAM, SIGMAL, TAM, TAL)
 CALL FSB(UM, UL, DM, DL, CCM, CCL)
 CALL FSB(CCM, CCL, SM, SL, TSM, TSL)
 CALL FMP(CM, CL, TSM, TSL, TSM, TSL)
 CALL FSB(CCM, CCL, RM, RL, CCM, CCL)
 CALL FMP(EM, EL, CCM, CCL, CDM, CDL)
 CALL FMP(CDM, CDL, SIGMAM, SIGMAL, TRM, TRL)

C COMPUTE F

CALL FAD(FIM, FIL, TAM, TAL, FM, FL)
 CALL FAD(FM, FL, TSM, TSL, FM, FL)
 CALL FAD(FM, FL, TRM, TRL, FM, FL)
 CALL FMP(HM, HL, SIGMAM, SIGMAL, HTM, HTL)
 CALL FSB(VM, VL, QM, QL, TOM, TOL)
 CALL FSB(TOM, TOL, TM, TL, TOM, TOL)
 CALL FMP(TOM, TOL, OM, OL, TOM, TOL)
 CALL FAD(TOM, TOL, HTM, HTL, HTM, HTL)
 CALL FAD(HTM, HTL, GIM, GIL, GM, GL)
 DXM = DXOM
 DXL = DXOL

```

DYM=DYOM
DYL=DYOL
DZM=DZOM
DZL=DZOL
IF (KNT-100) 4, 4, 22
14 PM(4) = DXOM
   PL(4) = DXOL
   PM(5) = DYOM
   PL(5) = DYOL
   PM(6) = DZOM
   PL(6) = DZOL
   IF (KO) 17, 17, 18
17 WOT 10, 15, TO, (PM(I), I=1, 6)
   GO TO 20
18 WOT 10, 19, TO, (PM(I), I=1, 6)
15 FORMAT(1H13X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X 1HZ/
1 1HO3X, 8HPOSITION 9X, 1PE40.7, 9X, E16.7, 11X, E14.7/1H 6X
2 20HUNITS OF EARTH RADII/1HO3X, 8HVELOCITY35X, E14.7,
3 11X, E14.7, 11X, E14.7/1H 6X, 33HUNITS OF EARTH RADII/
4 806.928 SEC. ///)
19 FORMAT(1H13X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/1
1 HO3X, 8HPOSITION 9X, 1PE40.7, 9X, E16.7, 11X, E14.7/1H 6X,
2 20HUNITS OF EARTH RADII/1HO3X, 8HVELOCITY35X, E14.7,
3 11X, E14.7, 11X, E14.7/1H 6X, 33HUNITS OF EARTH RADII/
4 58.13244 DA. ///)
20 DO 50 I= 1, 3
   PS = PM(I)
   PSL = PL(I)
   CALL FMPS(PS, PSL, 6378.388, PAM, PAL)
   PZM(I) = PAM
   PZL(I) = PAL
   CALL FDYS(PAM, PAL, 149.5042132E+6, PAM, PAL)

```

```

      PM(I) = PAM
50  PL(I) = PAL
      DO 51 I = 4, 6
      PS = PM(I)
      PSL = PL(I)
      IF (KO) 60, 60, 61
60  CALL FMPS(PS, PSL, 7.90453641, PAM, PAL)
      GO TO 62
61  CALL FMPS(PS, PSL, .126992648E-2, PAM, PAL)
62  PZM(I) = PAM
      PZL(I) = PAL
      CALL FMPS(PAM, PAL, .24079588E-4, PAM, PAL)
      PM(I) = PAM
51  PL(I) = PAL
      WOT 10, 24, TO, (PZM(I), I = 1, 6)
      WOT 10, 27, TO, (PM(I), I = 1, 6)
24  FORMAT(1HO3X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/
1  1HO3X, 8HPOSITION 9X, 1PE40.7, 5H KM E20.7, 3H KM8X.
2  E14.7, 3H KM/1HO3X, 8HVELOCITY35X, E14.7, 7H KM/SEC4X,
3  E14.7, 7H KM/SEC4X, E14.7, 7H KM/SEC///)
27  FORMAT(1HO3X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/
1  1HO3X, 8HPOSITION 9X, 1PE40.7, 7H A. U. E18.7, 5H A. U.
2  6X, E14.7, 5H A. U. /1HO3X, 8HVELOCITY 35X, E14.7, 8H A. U. /
3  HR3X, E14.7, 8H A. U. /HR 3X, E14.7, 8H A. U. /HR)
      GO TO 1
22  WOT 10, 23
23  FORMAT(1H15X, 9XGIVING UP)
      GO TO 1
      END (1, 1, 0, 0, 0, 1)

```

c. Two Position Vector Program

Check Problem

Output:

Time = 72.50

Position - Units of Earth Radii

X = 2.3358772E 00 Y = -3.7095247E-01 Z = -2.0855989E-01

Velocity - Units of Earth Radii/58.13244 DAY

X = 1.7789361E-01 Y = 6.7356692E-01 Z = 9.2517561E-02

Time = 72.50

Position

X = 1.4899131E 04KM Y = -2.3660788E 03KM Z = 1.3302759E
03KM

Velocity

X = 2.2591180E-04KM/SEC Y = 8.5538046E-04KM/SEC

Z = 1.1749050E-04KM/SEC

Time = 72.50

Position

X = 9.9656929E-05 A. U. Y = -1.5826168E-05 A. U.

Z = -8.8979160E-06 A. U.

Velocity

X = 5.4398631E-09 A. U. /HR Y = 2.0597209E-08 A. U. /HR

Z = 2.8291228E-09 A. U. HR

Input:

Card 1: F 1.41889, 1.47513, 1.00082, .05063, .02196*

Card 2: F .98156, .175430, .07609, -9.35, -10.6166667*

Card 3: F 342.475, 341.775, 72.5, 80.5*

Card 4: X1*

B. THREE ANGULAR POSITION PROGRAM

a. Operational Directory

Purpose

To find the position and velocity of an observed body at Time, T_0 , from measurements of the right ascension and declination or azimuth and elevation at three different Times, T_1 , T_0 , T_3 .

Usage

Input - All decimal input is read by a modified DBC FORTRAN subroutine which accepts variable length fields. All fields are floating point numbers except starred fields which are integers. The list of input quantities follows in the order in which they must be read into the program and then the input for a sample problem. All angle inputs must be in degrees and decimals of a degree. Range measurements must be in units of Earth's equatorial radius, (6378.388 km. = equatorial radius of Earth).

Card 1

*Field 1 -

Control Parameter, KO If $KO \leq 0$, the unit of time will be equal to 58.132441 days. If $KO \geq 1$, the unit of time will equal to 806.996813 sec.

Card 2

Field 1 - T_1 ,

Time T_1 in days and decimals of a day.

Field 2 - α_1 ,

right ascension in degrees and decimals of a degree at T_1 .

Field 3 - δ_1 ,

declination in degrees and decimals of a degree at T_1 .

Field 4 - X_1

Field 5 - Y_1

Field 6 - Z_1

Geocentric, equatorial coordinates of observer's position on Earth at time T_1 in units of earth's equatorial radius.

Card 3 - $T_0, \alpha_0, \delta_0, x_0, y_0, z_0$; Same format as Card 2.

Card 4 - $T_3, \alpha_3, \delta_3, x_3, y_3, z_3$; Same format as Card 2.

Sample Input

Card 1

X1*

Card 2

F 64.5, 343.279, - 7.98, 1.0012, - .0712, - .03258*

Card 3

F 72.5, 342.280, - 9.34, 1.00082, .05063, .02196*

Card 4

F 80.5, 341.469, - 10.56, .98125, .17543, .07609*

Output - The X, Y, Z components of the position vector are printed out in units of Earth's equatorial radius, kilometers, and astronomical units; the X, Y, Z components of the velocity vector are printed out in units of Earth's equatorial radius per 806.996813 sec., km. per sec. and A. U. per hr., if $KO \geq 1$. If $KO \leq 0$, the velocity will be printed out in units of Earth's equatorial radius per 58.132441 days, km. per sec. and A. U. per hr.

b. Three Angular Position Program

```
DIMENSION T(3), ALPHA(3), PHI(3), X(3), Y(3), Z(3), YOUM (3),  
1  YOUL(3), VEEM(3), VEEL(3), PIM(3), PIL(3), QM(3), QL(3), PM(6)  
2  PL(6)  
DIMENSION PZM(6), PZL(6)  
6  RIT2, 1, KO, (T(I), ALPHA(I), PHI(I), X(I), Y(I), Z(I), I = 1, 3)  
1  FORMAT (515)  
ERASE KNT  
DO 5 I = 1, 3  
ALPM = ALPHA (I)
```

PHIM = PHI (I)
 CALL DPSC (ALPM, O. , SINAM, SINAL, COSAM, COSAL, O.)
 CALL DPSC (PHIM, O. , SINPM, SINPL, COSPM, COSPL, O.)
 CALL FDY (SINAM, SINAL, COSAM, COSAL, TANAM, TANAL)
 CALL FDY (SINPM, SINPL, COSPM, COSPL, TANPM, TANPL)
 YOUM (I) = TANAM
 YOUL (I) = TANAL
 CALL FDY (TANPM, TANPL, COSAM, COSAL, TASEM, TASEL)
 VEEM (I) = TASEM
 VEEL (I) = TASEL
 XM = X (I)
 CALL FMPS (TANAM, TANAL, XM, UXM, UXL)
 YM = Y (I)
 CALL FSB (YM, O. , UXM, UXL, YUXM, YUXL)
 PIM (I) = YUXM
 PIL (I) = YUXL
 CALL FMPS (TASEM, TASEL, XM, VXM, VXL)
 ZM = Z (I)
 CALL FSB (ZM, O. , VXM, VXL, ZVXM, ZVXL)
 QM (I) = ZVXM
 5 QL (I) = ZVXL
 IF (KO) 9, 9, 10
 9 TU = 58.132441
 GO TO 11
 10 TU = .93394389E-2
 11 CALL FSBS (T(1), O. , T (2), DTM, DTL)
 CALL FDYS (DTM, DTL, TU, TAUM1, TAUL1)
 CALL FSBS (T(3), O. , T(2), DTM, DTL)
 CALL FDYS (DTM, DTL, TU, TAUM3, TAUL3)
 CALL FSB (TAUM3, TAUL3, TAUM1, TAUL1, DTAUM, DTAUL)
 CALL FSB (YOUM(1), YOUL(1), YOUM(2), YOUL(2), UNM1, UNL1)

CALL FDY (UNM1, UNL1, TAUM1, TAUL1, UM1, UL1)
 CALL FSB (YOUM (3), YOUL(3), YOUM(2), YOUL(2), UNM3, UNL3)
 CALL FDY (UNM3, UNL3, TAUM3, TAUL3, UM3, UL3)
 CALL FSB (VEEM (1), VEEL(1), VEEM(2), VEEL(2), VNM1, VNL1)
 CALL FDY (VNM1, VNL1, TAUM1, TAUL1, VM1, VL1)
 CALL FSB (VEEM(3), VEEL(3), VEEM(2), VEEL(2), VNM3, VNL3)
 CALL FDY (VNM3, VNL3, TAUM3, TAUL3, VM3, VL3)
 CALL FSB (PIM (1), PIL(1), PIM(2), PIL(2), PNM1, PNL1)
 CALL FDY (PNM1, PNL1, TAUM1, TAUL1, PM1, PL1)
 CALL FSB (PIM(3), PIL(3), PIM(2), PIL(2), PNM3, PNL3)
 CALL FDY (PNM3, PNL3, TAUM3, TAUL3, PM3, PL3)
 CALL FSB (QM(1), QL(1), QM(2), QL(2), QNM1, QNL1)
 CALL FDY (QNM1, QNL1, TAUM1, TAUL1, QM1, QL1)
 CALL FSB (QM(3), QL(3), QM(2), QL(2), QNM3, QNL3)
 CALL FDY (QNM3, QNL3, TAUM3, TAUL3, QM3, QL3)
 12 NO = 1
 PAM = UM1
 PAL = UL1
 PBM = UM3
 PBL = UL3
 13 CALL FMP (TAUM3, TAUL3, PAM, PAL, TMVM, TMVL)
 CALL FMP (TAUM1, TAUL1, PBM, PBL, TSVM, TSVL)
 CALL FSB (TMVM, TMVL, TSVM, TSVL, TNM, TNL)
 CALL FDY (TNM, TNL, DTAUM, DTAUL, DOM, DOL)
 CALL FSB (PBM, PBL, PAM, PAL, TNM, TNL)
 CALL FDY (TNM, TNL, DTAUM, DTAUL, D2OM, D2OL)
 GO TO (20, 21, 22, 23), NO
 20 DUM = DOM
 DUL = DOL
 D2UM = D2OM
 D2UL = D2OL

```

PAM = VM1
PAL = VL1
PBM = VM3
PBL = VL3
NO = NO + 1
GO TO 13
21  DVM = DOM
    DVL = DOL
    D2VM = D2OM
    D2VL = D2OL
    PAM = PM1
    PAL = PL1
    PBM = PM3
    PBL = PL 3
    NO = NO + 1
    GO TO 13
22  DPM = DOM
    DPL = DOL
    D2PM = D2OM
    D2PL = D2OL
    PAM = QM1
    PAL = QL1
    PBM = QM3
    PBL = QL3
    NO = NO + 1
    GO TO 13
23  DQM = DOM
    DQL = DOL
    D2QM = D2OM
    D2QL = D2OL
    CALL FMP(D2UM, D2UL, DVM, DVL, UVMM, UVML)

```

CALL FMP(D2VM, D2VL, DUM, DUL, UVSM, UVSL)
 CALL FSB(UVSM, UVSL, UVMM, UVML, DM, DL)
 CALL FMP(D2PM, D2PL, DVM, DVL, PVMM, PVML)
 CALL FMP(D2QM, D2QL, DUM, DUL, QUMM, QUML)
 CALL FSB(PVMM, PVML, QUMM, QUML, AM, AL)
 CALL FMP(PIM(2), PIL(2), DVM, DVL, PVMM, PVML)
 CALL FMP(QM(2), QL(2), DUM, DUL, QUMM, QUML)
 CALL FSB(PVMM, PVML, QUMM, QUML, BM, BL)
 CALL SQ(VEEM(2), VEEL(2), VSQM, VSQL)
 CALL SQ(YOUM(2), YOUL(2), USQM, USQL)
 CALL FAD(VSQM, VSQL, USQM, USQL, UVSQM, UVSQL)
 CALL FADS(UVSQM, UVSQL, 1., GM, CL)
 CALL FMP(YOUM(2), YOUL(2), PIM(2), PIL(2), UPM, UPL)
 CALL FMP(VEEM(2), VEEL(2), QM(2), QL(2), VQM, VQL)
 CALL FAD(UPM, UPL, VQM, VQL, EM, EL)
 CALL SQ(PIM(2), PIL(2), PSQM, PSQL)
 CALL SQ(QM(2), QL(2), QSQM, QSQL)
 CALL FAD(PSQM, PSQL, QSQM, QSQL, FM, FL)
 CALL FMP(D2QM, D2QL, D2UM, D2UL, D2QUM, D2QUL)
 CALL FMP(D2PM, D2PL, D2VM, D2VL, D2PVM, D2PVL)
 CALL FSB(D2QUM, D2QUL, D2PVM, D2PVL, GM, GL)
 CALL FMP(D2UM, D2UL, QM(2), QL(2), D2UQM, D2UQL)
 CALL FMP(D2VM, D2VL, PIM(2), PIL(2), D2VPM, D2VPL)
 CALL FSB(D2UQM, D2UQL, D2VPM, D2VPL, HM, HL)

RM = 1.02

RL = 0.

30 CALL CUBE(RM, RL, R3M, R3L)
 CALL FAD(R3M, R3L, R3M, R3L, R3M, R3L)
 CALL FDY(BM, BL, R3M, R3L, BRM, BRL)
 CALL FAD(AM, AL, BRM, BRL, BARM, BARL)
 CALL FDY(BARM, BARL, DM, DL, XM, XL)

CALL SQ (XM, XL, X2M, X2L)
 CALL FMP (X2M, X2L, CM, CL, CXM, CXL)
 CALL FMP (XM, XL, EM, EL, EXM, EXL)
 CALL FAD (EXM, EXL, EXM, EXL, EXM, EXL)
 CALL FAD (CXM, CXL, EXM, EXL, ECXM, ECXL)
 CALL FAD (ECXM, ECXL, FM, FL, RNM, RNL)
 CALL DPSQRT (RNM, RNL, RNM, RNL)
 WOT 10, 3, XM, RNM
 3 FORMAT (1HO10X, 4HX = 1 PE16.7, 10X, 4HR = E16.7)
 KNT = KNT + 1
 CALL FSB (RNM, RNL, RM, RL, DRM, DRL)
 IF (ABSF(DRM) - 1E - 8) 33, 33, 34
 34 IF (KNT - 100) 35, 35, 36
 35 RM = RNM
 RL = RNL
 GO TO 30
 36 WOT 10, 4
 4 FORMAT (1HO10X, 9HGIVING UP)
 GO TO 6
 33 CALL CUBE (RNM, RNL, RNM, RNL)
 CALL FAD (RNM, RNL, RNM, RNL, RNM, RNL)
 CALL FDY (BM, BL, RNM, RNL, BRM, BRL)
 CALL FAD (AM, AL, BRM, BRL, BARM, BARL)
 CALL FDY (BARM, BARL, DM, DL, PM(1), PL(1))
 CALL FDY (HM, HL, RNM, RNL, HRM, HRL)
 CALL FAD (HRM, HRL, GM, GL, HRM, HRL)
 CALL FDY (HRM, HRL, DM, DL, PM(4), PL(4))
 CALL FMP (YOUM(2), YOUL(2), PM(1), PL(1), XUM, XUL)
 CALL FAD (XUM, XUL, PIM(2), PIL(2), PM(2), PL(2))
 CALL FMP (DUM, DUL, PM(1), PL(1), DXUM, DXUL)
 CALL FMP (YOUM(2), YOUL(2), PM(4), PL(4), DUXM, DUXL)
 CALL FAD (DXUM, DXUL, DUXM, DUXL, DYM, DYL)

```

CALL FAD(DYM, DYL, DPM, DPL, PM(5), PL(5) )
CALL FMP(VEEM(2), VEEL(2), PM(1), PL(1), VXM, VXL)
CALL FAD(VXM, VXL, QM(2), QL(2), PM(3), PL(3) )
CALL FMP(DVM, DVL, PM(1), PL(1), DVXM, DVXL)
CALL FMP(VEEM(2), VEEL(2), PM(4), PL(4), DXVM, DXVL)
CALL FAD(DVXM, DVXL, DXVM, DXVL, DXM, DXL)
CALL FAD(DXM, DXL, DQM, DQL, PM(6), PL(6) )
IF (KO) 17, 17, 18
17  WOT 10, 19, T(2), (PM(I), I = 1, 6)
    GO TO 63
18  WOT 10, 15, T(2), (PM(I), I = 1, 6)
15  FORMAT (1H13X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/
1    1HO3X, 8HPOSITION 9X, 1PE40.7, 9X, E16.7, 11X, E14.7/1H
2    6X, 20HUNITS OF EARTH RADII/1HO3X, 8HVELOCITY35X,
3    E14.7, 11X, E14.7, 11X, E14.7/1H 6X, 33HUNITS OF EARTH RADII/
4    806.928 SEC. ///)
19  FORMAT (1H13X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/
1    1HO3X, 8HPOSITION 9X, 1PE40.7, 9X, E16.7, 11X, E14.7/ 1H 6X,
2    20 HUNITS OF EARTH RADII/1HO3X, 8HVELOCITY35X, E14.7,
3    11X, E14.7, 11X, E14.7/ 1H 6X, 33HUNITS OF EARTH RADII/
4    58.13244 DA. ///)
63  DO 50 I = 1, 3
    PS = PM(I)
    PSL = PL(I)
    CALL FMPS(PS, PSL, 6378.388, PAM, PAL)
    PZM(I) = PAM
    PZL(I) = PAL
    CALL FDYS(PAM, PAL, 149.5042132E+6, PAM, PAL)
    PM(I) = PAM
50  PL(I) = PAL
    DO 51 I = 4, 6

```

```

      PS = PM (I)
      PSL = PL (I)
      IF (KO) 60, 60, 61
60    CALL FMPS (PS, PSL, .12992648E-2, PAM, PAL)
      GO TO 62
61    CALL FMPS (PS, PSL, 7.90453641, PAM, PAL)
62    PZM (I) = PAM
      PZL (I) = PAL
      CALL FMPS (PAM, PAL, .24079588E-4, PAM, PAL)
      PM (I) = PAM
51    PL (I) = PAL
      WOT 10, 24 T(2), (PZM (I), I = 1, 6)
      WOT 10, 27, T(2), (PM (I), I = 1, 6)
24    FORMAT (1HO3X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/
1      1HO3X, 8HPOSITION 9X, 1PE40.7, 5H KM E20.7, 3H KM8X,
2      E14.7, 3H KM/1HO3X, 8HVELOCITY 35X, E14.7, 7H KM/SEC4X,
3      E14.7, 7H KM/SEC4X, E14.7H KM/SEC///)
27    FORMAT (1HO3X, 6HTIME = F9.2, 39X, 1HX, 24X, 1HY, 24X, 1HZ/
1      1HO3X, 8HPOSITION 9X, 1PE40.7, 7H A. U. E18.7, 5H A. U.
2      6X, E14.7, 5H A. U. /1HO3X, 8HVELOCITY35X, E14.7, 8H A. U. /
3      HR3X, E14.7, 8H A. U. /HR3X, E14.7, 8H A. U. /HR)
40    GO TO 6
      END (1, 1, 0, 0, 0, 1)

```

c. Three Angular Position Program

Check Problem

Output:

Time 33.91

Position-Units of Earth Radii

X = 2.2272140E 00 Y = -6.4261167E-01 Z = -2.4354754E-01

Velocity-Units of Earth Radii/58.13244 DAY

X = 2.5257830E-01 Y = 6.6070658E-01 Z = 8.8773156E-02

Time = 33.91

Position

X = 1.4206035E 04 KM Y = -4.0988266E 03KM Z=1.5534407E 03KM

Velocity

X = 3.2816609E-04 KM/SEC Y = 8.5843279E-04 KM/SEC Z

= 1.1533984E-04 KM/SEC

Time = 33.91

Position

X = 9.5020968E-05 A. U. Y = -2.7416128E-05 A. U. Z

= -1.0390615E-05 A. U.

Velocity

X = 7.9021043E-09 A. U. /HR Y = 2.0670708E-08 A. U./HR Z

= 2.7773358E-09 A. U. /HR

Input:

Card 1: XO*

Card 2: F 30.006, 346.5265, -3.690944, .9217386, -.3782763,
-.16402741*

Card 3: F 33.9067, 345.92583, -4.510222, .9460249, -.3214131,
-.1393582*

Card 4: F 37.9351, 345.28958, -5.365694, .9667071, -.2612860,
-.1132835*

C. CONVERSION OF COORDINATES FROM EQUINOX TO EQUINOX

a. Operational Directory

Purpose

To rotate a given vector $X = \begin{pmatrix} x \\ y \\ z \end{pmatrix}$ from the equinox of 1950.0
to other equinoxes and vice versa.

Usage

Input - All decimal input is read by a modified DBC FORTRAN subroutine which accepts variable length fields. All fields are floating point numbers except for starred fields which are integers.

Following is the list of input quantities in the order in which they are read into the program:

Card 1

*Field 1 - N5, Control Parameter

If $N5 \geq 1$, X will be rotated from equinox of date to equinox of 1950.0.

If $N5 \leq 0$, X will be rotated from equinox of 1950.0 to equinox of date.

*Field 2 - NP, Control Parameter

NP must be equal to the number of vectors which are to be rotated as specified by N5. $1 \leq NP \leq 10$.

Cards 2 - NP + 1

Field 1 - Whole number component of Julian Date. The Julian Date must correspond to the beginning of the Besselian Year.

Field 2 - Decimal Component of Julian Date.

Field 3 - X component of vector to be rotated.

Field 4 - Y component of vector to be rotated.

Field 5 - Z component of vector to be rotated.

Sample Input

Card 1 - Columns 1-5

X1, 2*

Card 2 - Columns 1-32

Card 2 - Columns 1-32

F 2437203., .5, .2985, .3740, -.6739*

Card 3 - Columns 1-32

F 2437008., .5, .0046, -.5968, -.3702*

Output - The vector components are printed out referenced to the new equinox.

b. Conversion of Coordinates from Equinox to Equinox

```
DAC AM(3,3), AL(3,3), PZM(10,3), PZL(10,3), DJM(10), DJL(10),
1  X(10), Z(10), Y(10), XL(10), YL(10), ZL(10)
C   N5 = 1, REDUCTION OF X, Y, Z OF DATE TO EQUINOX OF 1950.0
C   N5 = 0, REDUCTION OF X, Y, Z OF 1950.0 TO MEAN EQUINOX OF
1   DATE
1   RIT 2, 3, N5, NP
3   FORMAT (515)
11  RIT 2, 3, (DJM(I), DJL(I), X(I), Y(I), Z(I), I = 1, NP)
    ERASE XL, YL, ZL
    DO 500 J = 1, NP
    DJIM = DJM(J)
    DJIL = DJL(J)
    IF (N5) 61, 71, 61
61  CALL FSB(2433282., .5, DJIM, DJIL, VM, VL)
    GO TO 62
71  CALL FSB(DJIM, DJIL, 2433282., .5, VM, VL)
62  CALL FDYS(VM, VL, 36525., VM, VL)
    CALL SQ(VM, VL, VSQM, VSQJ)
    CALL CUBE(VM, VL, VCUM, VCUL)
    CALL FMPS(VSQM, VSQJ, .00029696, CM, CL)
    CALL FMPS(VCUM, VCUL, .00000014, DM, DL)
    CALL FSB(1., 0., CM, CL, CM, CL)
```

```

CALL FSB(CM, CL, DM, DL, AM(1, 1), AL(1, 1) )
CALL FMPS (VM, VL, -. 02234941, CM, CL)
CALL FMPS(VSQM, VSQ, . 00000676, DM, DL)
CALL FMPS(VCUM, VCUL, . 00000221, EM, EL)
CALL FSB(CM, CL, DM, DL, CM, CL)
CALL FAD(CM, CM, EL, AM(1, 2), AL(1, 2) )
CALL FMPS(VM, VL, -. 00971691, CM, CL)
CALL FMPS(VSQM, VSQ, . 00000206, DM, DL)
CALL FMPS(VCUM, VCUL, . 00000098, EM, EL)
CALL FAD(CM, CL, DM, DL, CM, DL)
CALL FAD(CM, CL, EM, EL, AM(1, 3), AL(1, 3) )
AM(2, 1) = -AM(1, 2)
AL(2, 1) = -AL(1, 2)
CALL FMPS(VSQM, VSQ, . 00024975, CM, CL)
CALL FMPS(VCUM, VCUL, . 00000015, DM, DL)
CALL FSB(1., 0., CM, CL, CM, CL)
CALL FSB(CM, CL, DM, DL, AM(2, 2), AL(2, 2) )
CALL FMPS(VSQM, VSQ, -. 00010858, CM, CL)
CALL FMPS(VCUM, VCUL, . 00000003, DM, DL)
CALL FSB(CM, CL, DM, DL, AM(2, 3), AL(2, 3) )
AM(3, 1) = AM(1, 3)
AL(3, 1) = -AL(1, 3)
AM(3, 2) = AM(2, 3)
AL(3, 2) = AL(2, 3)
CALL FMPS(VSQM, VSQ, . 00004721, CM, CL)
CALL FMPS(VCUM, VCUL, . 00000002, DM, DL)
CALL FSB(1. 0., CM, CL, CM, CL)
CALL FAD(CM, CL, DM, DL, AM(3, 3), AL(3, 3) )
DO 7 I=1, 3
CALL FMP(AM(I, 1), AL(I, 1), X(J), XL(J), CM, CL)
CALL FMP(AM(I, 2), AL(I, 2), Y(J), YL(J), DM, DL)

```

```

      CALL FMP(AM(I, 3), AI(I, 3), Z(J), ZL(J), EM, EL)
      CALL FAD(CM, CL, DM, DL, CM, CL)
7     CALL FAD(CM, CL, EM, EL, PZM(J, I), PZL(J, I) )
500   CONTINUE
      DO 9 J = 1, NP
      X (J) = PZM(J, 1)
      Y (J) = PZM(J, 2)
      Z (J) = PZM(J, 3)
      XL(J) = PZL(J, 1)
      YL(J) = PZL(J, 2)
9     ZL(J) = PZL(J, 3)
      IF (N5) 20, 20, 21
20    WOT 10, 24, (X(I), Y(I), Z(I), I = 1, NP)
24    FORMAT(1H16X, 62H  COORDINATES REFERENCED TO MEAN
1     EQUINOX OF DATE/(1H06X, 2HX = 1PE14. 7, 10X, 2HY = E14. 7, 10X
2     2HZ = E14. 7) )
      GO TO 1
21    WOT 10, 30
30    FORMAT (1H0)
      WOT 10, 25, (X(I), Y(I), Z(I), I = 1, NP)
25    FORMAT(1H06X, 62H  COORDINATES REFERENCED TO MEAN
1     EQUINOX OF 1950/(1H06X, 2HX = 1PE14. 7, 10X, 2HY = E14. 7, 10X,
2     2HZ = E14. 7) )
      GO TO 1
      END (1, 1, 0, 0, 0, 1)

```

c. Conversion of Coordinates from Equinox to Equinox

Check Problem

Output:

Coordinates Referenced to Mean Equinox of 1950

X = 1.0008215E 00 Y = 5.0628301E-02 Z = 2.1963697E-02

Coordinates Referenced to Mean Equinox of Date

X = 1.0010150E 00 Y = 4.7274507E-02 Z = 2.0501011E-02

Input:

Card 1: X 1, 1*

Card 2: 2428072., .5, 1.0010150, .04727450, .02050101*

Card 3: X 0, 1*

Card 4: 2428072., .5, 1.0008215, .05062830, .02196369*

D. CONVERSION OF RIGHT ASCENSION AND DECLINATION FROM
EQUINOX TO EQUINOX

a. Operational Directory

Purpose

To reduce right ascension and declination referenced to mean equinox of date to right ascension and declination referenced to mean equinox of 1950.0 and vice versa.

Usage

Input - All decimal input is read by a modified DBC FORTRAN subroutine which accepts variable length fields. All fields are floating point numbers except for starred fields which are integers.

The list of input quantities in the order in which they are read into the program follows:

Card 1

*Field 1 - N3, Control Parameter

If $N3 \geq 1$, α and δ will be reduced from equinox of 1950.0 to equinox of date.

If $N3 \leq 0$, α and δ will be reduced from equinox of date to equinox of 1950.0.

*Field 2 - NP, Control Parameter

NP must be equal to the number of reductions which are
to be made as specified by N3, $1 \leq NP \leq 10$.

Cards 2 - NP + 1

Field 1 - Whole number component of Julian Date.

Field 2 - Decimal component of Julian Date.

Field 3 - Right ascension in degrees and decimals of a degree,

Field 4 - Declination in degrees and decimals of a degree.

Sample Input

Card 1: Columns 1-5

XO, 1*

Card 2: Columns 1 - 37

F 2415020., .5, 332.2054167, -80.9374167*

Output - The right ascension and declination are printed out in
degrees and decimals of a degree referenced to desired equinox.

b. Conversion of Right Ascension and Declination from Equinox to Equinox

```
DAC DJM(10), ALPHAM(10), APL(20), APM(20), DDM(20), DDL(20),  
1 DJL(10), ALPHAL(10), DELTAM(10), DELTAL(10)  
1 RIT 2, 3, N3, NP  
3 FORMAT(515)  
2 RIT 2, 3, (DJM(I), DJL(I), ALPHAM(I), DELTAM(I), I=1, NP  
C CONVERSION OF ALPHA + DELTA FROM DATE TO EQUINOX OF  
1 1950.0, N3 = 3  
C CONVERSION OF ALPHA + DELTA FROM EQUINOX TO DATE,  
1 N3 = +1  
DO 400I = 1, NP  
440 FORMAT(1H1)  
ERASE KNT, ALPHL, DELTL  
DJIM = DJM(I)
```

```

DJIL = DJL(I)
CALL FSB(DJIM, DJIL, 2433281., .5, AMM, AML)
CALL FDYS(AMM, AML, 365.25, RDM, RDL)
CALL FSB(2433281., .5, DJIM, DJIL, REM, REL)
CALL FDYS(REM, REL, 365.25, REM, REL)
C   COMPUTE M AND N, AMM = M, ANM = N
CALL FMPS(RDM, RDL, .25, AQM, AQL)
CALL FMPS(AQM, AQL, .000279, AMM, AML)
CALL FADS(AMM, AML, 46.09905, AMM, AML)
CALL FDYS(AMM, AML, 3600., AMM, AML)
CALL FMPS(AQM, AQL, .000085, ANM, ANL)
CALL FSB(20.0426, 0., ANM, ANL, ANM, ANL)
CALL FDYS(ANM, ANL, 3600., ANM, ANL)
ALPHM = ALPHAM(I)
DELTM = DELTAM(I)
60  CALL DPSC(ALPHM, ALPHL, SALPHM, SALPHL, CALPHM,
1    CALPHL, 0)
    CALL DPSC(DELM, DELTL, SDELM, SDELT, CDELM,
1    CDELT, 0)
C   COMPUTE DALPHA/DT AND DDELTA/DT
    CALL FDY(SDELM, SDELT, CDELM, CDELT, TDELM,
1    TDELT)
    CALL FMP(TDELM, TDELT, SALPHM, SALPHL, DADTM,
1    DADTL)
    CALL FMP(DADTM, DADTL, ANM, ANL, DADTM, DADTL)
    CALL FAD(DADTM, DADTL, AMM, AML, DADTM, DADTL)
    CALL FMP(ANM, ANL, CALPHM, CALPHL, DDDTM, DDDTL)
    KNT = KNT + 1
    IF (N3) 50, 50, 51
50  RDM = REM
    RDL = REL

```

```

51  CALL FMP(RDM, RDL, DADTM, DADTL, APIM, APIL)
    CALL FAD(APIM, APIL, ALPHAM(I), ALPHAL(I), APM(KNT)
1   APL(KNT) )
    CALL FMP(RDM, RDL, DDDTM, DDDTL, DDIM, DDIL)
    CALL FAD(DDIM, DDIL, DELTAM(I), DELTAL(I), DDM(KNT),
1   DDL(KNT) )
    IF (KNT - 2) 53, 54, 54
54  CALL FSB(APM(KNT), APL(KNT), APM(KNT-1), APL(KNT-1),
1   DAP, DAL)
    CALL FSB(DDM(KNT), DDL(KNT), DDM(KNT-1), DDL(KNT-1),
1   DDD, DAL)
    IF (ABSF(DAP) - 1E-8) 55, 53, 53
55  IF (ABSF(DDD) - 1E-8) 62, 53, 53
53  CALL FAD(APM(KNT), APL(KNT), ALPHAM(I), ALPHAL(I), ALPHM,
1   ALPHL)
    CALL FMPS(ALPHM, ALPHL, .5, ALPHM, ALPHL)
    CALL FAD(DDM(KNT), DDL(KNT), DELTAM(I), DELTAL(I), DELTM,
1   DELTL)
    CALL FMPS(DELTM, DELTL, .5, DELTM, DELTL)
    IF (KNT-20) 60, 80, 80
80  WOT 10, 8
    8  FORMAT(1H06X, 9HGIVING UP)
    GO TO 400
62  ALPHAM(I) = APM(KNT)
    ALPHAL(I) = APL(KNT)
    DELTAM(I) = DDM(KNT)
    DELTAL(I) = DDL(KNT)
400  CONTINUE
    IF (N3) 70, 70, 71
70  WOT 10, 5, (ALPHAM(I), DELTAM(I), I = 1, NF)
    5  FORMAT(1H115X, 62HASCENSION AND DECLINATION

```

```

1  REFERENCED TO MEAN EQUINOX OF 1950.0/(1HO20X,
2  6HALPHA = 1PE14.7, 16H DEGREES DELTA = E14.7, 8H DEGREES) )
  GO TO 1
71  WOT 10, 6(ALPHAM(I), DELTAM(I), I = 1, NP)
6   FORMAT(1H115X, 62HASCENSION AND DECLINATION
1   REFERENCED TO MEAN EQUINOX OF DATE/(1HO20X,
2   6HALPHA - 1PE14.7, 16H DEGREES DELTA = 14.7, 8 H DEGREES) )
  GO TO 1
  END (1.1, 0, 0.0, 1)

```

c. Conversion of Right Ascension and Declination from Equinox to Equinox

Check Problem

Output:

Right Ascension and Declination Referenced to Mean Equinox of Date

Alpha = 3.4327915E 02 Degrees

Delta = -7.9466670E 00 Degrees

Alpha = 3.4111123E 02 Degrees Delta = -1.0696111E 01 Degrees

Input:

Card 1: X 1, 2*

Card 2: F 2428064., .5, 343.46521, -7.87047*

Card 3: F 2428080., .5, 341.29838, -10.621060*

Right Ascension and Declination Referenced to Mean Equinox of 1950.0

Alpha - 3.4346521E 02 Degrees

Delta = - 7.8704700E 00 Degrees

Alpha - 3.4129838E 02 Degrees

Delta = -1.0621060E 01 Degrees

Input:

Card 1: X 0, 2*

Card 2: F 2428064., .5, 343.27915, -7.946667*

Card 3: F 2428080., .5, 341.111249, -10.696111*

E. COMPUTATION OF RECTANGULAR GEOCENTRIC SITE
COORDINATES AND CONVERSION OF AZIMUTH AND ELEVATION
TO RIGHT ASCENSION AND DECLINATION

a. Operational Directory

Purpose

To compute the geocentric site coordinate and to convert azimuth and elevation to right ascension and declination.

Usage

Input - All decimal input is read by a modified DBC FORTRAN subroutine which accepts variable length fields. All fields are floating point numbers except for starred fields which are integers. Following is the list of input quantities in the order in which they must be read into the program and then the input for a sample problem.

*Field 1 - N4, Control parameter

If $N4 \geq 1$, right ascension and declination will be computed from the corresponding azimuth and elevation.

If $N4 \leq 0$, right ascension and declination will not be computed.

*Field 2 - NP, Control Parameter which must be equal to the number of cases to be run. $1 \leq NP \leq 10$

Field 3 - ϕ , geocentric latitude of site in degrees and decimals of a degree (+ if North, - if South).

Field 4 - h, height of site above sea level in units of Earth's equatorial radius. (6378.388 km. = equatorial radius of Earth)

Field 5 - λ , geographic longitude of site in degrees and decimals of a degree. (+ if East, - if West)

Field 6 - Whole number component of Julian Date.

Field 7 - Decimal component of Julian Date.

Field 8 - Decimal component of corresponding universal time.

NOTE: If $N4 \leq 0$, no more input is required; however, the input must include "NP" sets of data, each set of which must be composed of Fields 3-8.

If $N4 \geq 1$, then each set of the "NP" sets must be composed of Fields 3-10.

Field 9 - Elevation in degrees and decimals of a degree.

Field 10 - Azimuth in degrees and decimals of a degree.

Sample Inputs

Example 1

Card 1: X 1, 1*

Card 2: F 50.35, 023E-6, 4.358, 2428048.,
.5, 0., 25.46, 209.35*

Example 2

Card 1: X 0, 2*

Card 2: F 53.2, .013E-4, 6.37, 2428072., .5, 0*

Card 3: F 55.2, .014E-5, 6.39, 2428078., .5, 0*

Output - If $N4 \leq 0$, only the rectangular geocentric site coordinates will be printed out in units of Earth's equatorial radius.

If $N4 \geq 1$, the right ascension and declination corresponding to each site vector will be printed out in degrees. Both site coordinates and angles will be referenced to mean equinox of date.

- b. Computation of Rectangular Geocentric Site Coordinates and Conversion of Azimuth and Elevation to Right Ascension and Declination

DAC PHIPM(10), PHIPL(10), RM(10), GMSTM(10),

1 GMSTL(10), PHI(10), H(10), BAMDA(10), DJM(10), DJL(10), T(10).

```

2  BSTM(10), BSTL(10), SPHIPM(10), SPHIPL(9), CPHIPM(10)
3  CPHIPL(10), X(10), Y(10), Z(10)
   DAC CDELTM(10), CDELTIL(10), SDELTM(10), SDELTIL(10),
1  DELTAM(10), DELTAL(10), ALPHAM(10), ALPHAL(10), E(10),
2  A(10), SALPHM(10), CALPHM(10), SALPHL(10), CALPHL(10),
3  HAB(10)
4  FORMAT (15)
1  RIT 2, 4, N4, NP
   IF (N4) 3, 3, 6
3  RIT 2, 4, (PHI(I), H(I), BAMDA(I), DJM(I), DJL(I), T(I), I = 1, NP)
   GO TO 7
6  RIT 2, 4(PHI(I), H(I), BAMDA(I), DJM(I), DJL(I), T(I), E(I), A(I), I =
1  1, NP)
7  DO 100I = 1, NP
   PHIM = PHI(I)
   HT = H(I)
   DJIM = DJM(I)
   DJIL = DJL(I)
   BAMDAM = BAMDA(I)
   TPHIM = 2. *PHIM
   FPHIM = 4. *PHIM
   SPHIM = 6. *PHIM
   TA = T(I)
C  COMPUTE THE GEOCENTRIC LATITUDE PHI PRIME (I-1)
   CALL DPSC(TPHIM, 0., STPHIM, STPHIL, CTPHIM, CTPHIL, 0)
   CALL DPSC(FPHIM, 0., SFPHIM, SFPHIL, CFPHIM, CFPHIL, 0)
   CALL DPSC(SPHIM, 0., SSPHIM, SSPHIL, CSPHIM, CSPHIL, 0)
   CALL FMPS(STPHIM, STPHIL, -695.6635, CM, CL)
   CALL FMPS(SFPHIM, SFPHIL, 1.1731, DM, DL)
   CALL FMPS(SSPHIM, SSPHIL, -.0026, EM, EL)
   CALL FAD(CM, CL, DM, DL, CM, CL)

```

```

CALL FAD(CM, CL, EM, EL, CM, CL)
CALL FDYS(CM, CL, 3600., CM, CL)
CALL FADS(CM, CL, PHIM, PHIPM(I), PHIPL(I) )
C   COMPUTE THE GEOCENTRIC RADIUS VECTOR OF SITE R(II-2)
CALL FMPS(CTPHIM, CTPHIL, 1.683494E-3, CM, CL)
CALL FMPS(CFPIM, CFPIL, 3.549E-6, DM, DL)
CALL FMPS(CSPHIM, CSPHIL, 8.0E-9, EM, EL)
CALL FSB(CM, CL, DM, DL, CM, CL)
CALL FAD(CM, CL, EM, EL, CM, CL)
CALL FADS(CM, CL, .998320047, CM, CL)
CALL FADS(CM, CL, HT, RM(I), RL(I) )
C   COMPUTE THE GREENWICH MEAN SIDEREAL TIME AT U. T.
1   (II-3)
CALL FSBS(DJIM, DJIL, 2415020.0, CM, CL)
CALL FDYS(CM, CL, 36525., CM, CL)
CALL SQ(CM, CL, CSQM, CSQL)
CALL FMPS(CSQM, CSQL, .0929, TERM, TERL)
CALL FMP(CM, CL, 8640184., .542, TM, TL)
CALL FAD(TERM, TERL, TM, TL, GMSTM(I), GMSTL(I) )
CALL FADS(GMSTM(I), GMSTL(I), 23925.836, GMSTM(I), GMSTL(I) )
CALL FDYS(GMSTM(I), GMSTL(I), 3600., GMSTM(I), GMSTL(I) )
60  CALL FSBS(GMSTM(I), GMSTL(I), 24., GMSTM(I), GMSTL(I) )
    IF(GMSTM(I) -24.) 61, 61, 60
C   COMPUTE THE LOCAL SIDEREAL TIME (II-4)
61  CALL FDYS(BAMDAM, 0.15., CM, CL)
    CALL FMPS( TA, 0., 24., AM, AL)
    CALL FAD(AM, AL, CM, CL, CM, CL)
    CALL FMPS(AM, AL, .0027369, DM, DL)
    CALL FAD(DM, DL, CM, DL, STM, STL)
    CALL FAD(STM, STL, GMSTM(I), GMSTL(I), STM, STL)
    CALL FMPS(STM, STL, 15., BSTM(I), BSTL(I) )

```

```

C      (II-5)
      CALL DPSC(BSTM(I), BSTL(I), SLSTM, SLSTL, CLSTM, CLSTL, 0)
      CALL DPSC(PHIPM(I), PHIPL(I), SPHIPM(I), SPHIPL(I)
1      CPHIPM(I), CPHIPL(I), 0)
C      COMPUTE RECTANGULAR COMPONENTS (II-6)
      CALL FMP(CPHIPM(I), CPHIPL(I), CLSTM, CLSTL, XM, XL)
      CALL FMP(XM, XL, RM(I), RL(I), X(I), XL)
      CALL FMP(CPHIPM(I), CPHIPL(I), SLSTM, SLSTL, YM, YL)
      CALL FMP(YM, YL, RM(I), RL(I), Y(I), YL)
100    CALL FMP(SPHIPM(I), SPHIPL(I), RM(I), RL(I), Z(I), ZL)
      WOT 10, 5, (X(I), Y(I), Z(I), BSTM(I), I = 1, NP)
5      FORMAT (1H16X, 99HRECTANGULAR SITE COORDINATES
1      REFERENCED TO EQUINOX OF DATE AND IN UNITS OF
2      EARTHS EQUATORIAL RADIUS/(1HO3X, 2HX = 1PE14.7, 7X,
3      2HY = E14.7, 7X, 2HZ = E14.7, 7X, 20HLOCAL SIDEREAL TIME =
4      E14.7, 8 H DEGREES) )
C      CONVERSION OF AZIMUTH AND ELEVATION TO RT. ASC.
1      AND DEC (III-1)
      IF (N4) 1, 1, 8
8      DO 200 I = 1, NP
      EM = E(I)
      AM = A(I)
      SPHIM = SPHIPM(I)
      SPHIL = SPHIPL(I)
      CPHIM = CPHIPM(I)
      CPHIL = CPHIPL(I)
      CALL DPSC(EM, 0., SEM, SEL, CEM, CEL, 0)
      CALL DPSC(AM, 0., SAM, SAL, CAM, CAL, 0)
      CALL FMP(SPHIM, SPHIL, SEM, SEL, CCM, CCL)
      CALL FMP(CPHIM, CPHIL, CEM, CEL, DM, DL)
      CALL FMP(DM, DL, CAM, CAL, DM, DL)

```

```

CALL FAD(DM, DL, CCM, CCL, SDELT(I), SDELT(I) )
CALL SQ(SDELT(I), SDELT(I), SDLTSM, SDLTSL)
CALL FSB(1., 0., SDLTSM, SDLTSL, CDLTSM, CDLTSL)
CALL DPSQRT(CDLTSM, CDLTSL, CDELT(I), CDELT(I) )
CALL DPASIN(SDELT(I), SDELT(I), DELTAM(I), DELTAL(I),
1 KZ)
CALL FMPS(DELTAM(I), DELTAL(I), 57.2957795, DELTAM(I)
1 DELTAL(I) )
C COMPUTE RIGHT ASCENSION (III-2)
CALL FMP(CEM, CEL, -SAM, -SAL, DM, DL)
CALL FDY(DM, DL, CDELT(I), CDELT(I), SINHAM, SINHAL)
CALL FMP(SEM, SEL, CPHIM, CPHIL, CM, CL)
CALL FMP(CEM, CEL, SHPIM, SPHIL, DM, DL)
CALL FMP(DM, DL, CAM, CAL, DM, DL)
CALL FSB(CM, CL, DM, DL, CM, CL)
CALL FDY(CM, CL, CDELT(I), CDELT(I), COSHAM, COSHAL)
CALL DPASIN(SINHAM, SINHAL, HAM, HAL, KZ)
IF (COSHAM) 20, 21, 21
20 IF (SINHAM) 22, 23, 23
22 CALL FSB(PIM, PIL, HAM, HAL, HAM, HAL)
GO TO 25
23 CALL FSB(PIM, PIL, HAM, HAL, HAM, HAL)
C PIM, PIL, ARE TO BE READ IN ON BINARY CARDS
GO TO 25
21 IF (SINHAM) 24, 25, 25
24 CALL FAD(TPIM, TPIL, HAM, HAL, HAM, HAL)
25 CALL FMPS(HAM, HAL, 57.2957795, HAM, HAL)
HAB(I) = HAM
200 CALL FSB(BSTM(I), BSTL(I), HAM, HAL, ALPHAM(I), ALPHAL(I) )
WOT 10, 103, (DELTAM(I), ALPHAM(I), HAB(I), I = 1, NP)
103 FORMAT (1H06X, 61HRIGHT ASCENSION AND DECLINATION

```

```

1  REFERENCED TO EQUINOX OF DATE//(1H06X, 6HDELTA =
2  1PE14. 7, 16H DEGREES ALPHA = E14. 7, 1X20H DEGREES HOUR
3  ANGLE = E14. 7, 8 HDEGREES) )
110 GO TO 1
    END (1, 1, 0, 0, 0, 1)

```

- c. Computation of Rectangular Geocentric Site Coordinates and Conversion of Azimuth and Elevation to Right Ascension and Declination

Check Problem

Output:

Rectangular Site Coordinates Referenced to Equinox of Date
 Units of Earth's Equatorial Radius
 Local Sidereal Time = 9.2112108E 00 Degrees
 X = 6.2516253E-01 Y = 1.0137977E-01 Z = 7.7127761E-01
 Right Ascension and Declination Referenced to Equinox of Date
 Delta = -9.4294895E 00 Degrees
 Alpha = -1.7721417E 01 Degrees
 Hour Angle = 2.6932628E 01 Degrees

Input:

Card 1: X 1, 1*
 Card 2: F 50.7985278, .7023213E - 6, 4.3583333, 2428072., 5, 0*
 Card 3: F 25.5638611, 209.69025*

F. EPHERMERIS COMPUTATION PROGRAM

- a. Operational Directory

Purpose

The program computes the rectangular geocentric site coordinates at Time T referenced to the mean equinox of date; these coordinates are reduced to the mean equinox of 1950.0. The topocentric distance observed

at time T is computed from the site coordinates and the rectangular geocentric coordinates of the observed body. The right ascension and declination of an observed body at time T are computed referenced to the mean equinox of 1950.0 and reduced to mean equinox of date. The azimuth and elevation of the observed body at time T are computed.

Usage

All decimal input is read by a modified DBC FORTRAN subroutine which accepts variable length fields. All fields are floating point numbers except for starred fields which are integers. Following is the list of input quantities in the order in which they are read into the program:

- Field 1 - T, Whole number component of Julian Date.
- Field 2 - T, Decimal Component of Julian Date.
- Field 3 - X } Rectangular geocentric coordinates of observed
- Field 4 - Y } body at time T in units of Earth's equatorial radius
- Field 5 - Z } and reference to the mean equinox of 1950.0.
(6378.388 km. = equatorial radius of Earth)
- Field 6 - ϕ , Geocentric latitude of site in degrees and decimals
of a degree (+ if North, - if South).
- Field 7 - h, Height of site above sea level in units of Earth's
equatorial radius.
- Field 8 - λ , Geographic longitude of site in degrees and decimals
of a degree (+ if East, - if West).
- Field 9 - Decimal component of the universal time corresponding
to the Julian Date in Fields 1 and 2.

Sample Input:

Example

Card 1: F 2428072., .5, 2.3358772, - 37095247, -.208

Card 2: F 50.7985278, .7023213E-6, 4.3583333, 0*

Output:

The rectangular geocentric site coordinates in units of Earth's