

UNCLASSIFIED

AD 266 294

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOG BY ASTIA 266294

266 294

62-1-3
XEROX

DEPARTMENT OF
INDUSTRIAL AND ENGINEERING ADMINISTRATION


X SIBLEY SCHOOL OF MECHANICAL ENGINEERING

228 900



CORNELL UNIVERSITY

ITHACA, NEW YORK



USE OF THE MILITARY STANDARD
PLANS FOR HAZARD RATE
UNDER THE WEIBULL DISTRIBUTION*

Technical Report Number 7

October, 1961

Department of the Navy
Office of Naval Research
Contract Number: Nonr-401(43)

Henry P. Goode and John H.K. Kao
Department of Industrial and Engineering Administration
Sibley School of Mechanical Engineering
Cornell University, Ithaca, New York

*This research was supported by the Office of Naval Research. Reproduction in whole or in part is permitted for any purpose of the United States Government.

USE OF THE MILITARY STANDARD PLANS FOR HAZARD RATE UNDER THE WEIBULL DISTRIBUTION

Summary

This paper presents a procedure, together with necessary tables of products, for applying the MIL-STD-105B plans to acceptance sampling inspection when the quality of items in the lot is evaluated in terms of the instantaneous failure rate or hazard rate as a function of time. Inspection of sample items is by attributes with life testing truncated at the end of some pre-assigned period. The Weibull distribution (including the exponential as a special case) is assumed as the underlying life-length model. Examples of application are given.

Introduction

The procedure and tables presented in this paper are based on recent work reported on in some detail in a paper to be presented by the authors at the Eighth National Symposium on Reliability and Quality Control⁽¹⁾. The objective of this procedure and set of tables is to provide a simple means of adapting the MIL-STD-105B⁽²⁾ plans to reliability and life-testing applications for which the lot quality of interest is the hazard rate or instantaneous failure rate for the items at some specified time or life and for which the Weibull distribution (including the exponential as a special case) can be assumed. Both the procedure and tables are of a form similar to that for the procedure and tables prepared by the authors for use when lot quality is evaluated in terms of mean item life and which were presented at the Fifteenth Annual Convention of the American Society for Quality Control⁽³⁾. The two sets of tables thus supplement each other,

and since the sampling inspection procedures for both are identical, they provide a comprehensive collection offering alternative criteria for lot evaluation. Additional information on Weibull sampling plans, on estimation of the Weibull parameters, and on the mathematics involved may be found in other papers by the authors^{(4), (5)}.

The Acceptance-Sampling Procedure

The acceptance-sampling procedure to be employed with the tables presented here follows the usual pattern for attribute sampling inspection. The single variation in procedure is the testing of sample items for life (rather than for some other item quality characteristic) and the use of a pre-assigned test truncation time, t . For single-sampling, the following are the steps required:

- (a) Making use of the tables of factors provided, select a suitable sampling-inspection plan.
- (b) Draw at random a sample of items of size n as specified by the plan.
- (c) Place the sample items on life test for the specified period of time, t .
- (d) Determine the number of sample items that fail during the test period.
- (e) Compare the number of items that fail with the acceptance number, c , specified for the plan.
- (f) If the number that fail is equal to or less than the acceptance number, accept the lot; if the number failing exceeds the acceptance number, reject the lot.

Both the sample sizes and the acceptance numbers used will be those specified for the MIL-STD-105B plans. Single sampling will presumably be used, but by simple modification double or multiple sampling can be used

if desired. The selection of a suitable plan, the determination of operating characteristics in terms of hazard rate for a specified plan, and the determination of an appropriate life-testing time are all made through use of the tables of products which will be found at the end of this report. Ways for making use of these tables will be discussed in the section that follows and in the accompanying illustrative examples.

It may be noted that the probability of acceptance for a lot under the procedure outlined above depends only on the probability, which may be designated by p' , of an item failing before the end of the test period, t . The actual life at which an item fails need not be determined; inspection is on an attribute basis. For this reason it is possible to use the 105B plans to evaluate submitted lots in terms of hazard rate, $Z(t)$, at some specified time, t . The operating characteristics for any sampling plan specified by c and n depend only on t and $Z(t)$. A brief outline of the mathematics involved in the procedure will be found in the Appendix. Additional details may be found in the paper of the authors first cited⁽¹⁾.

To provide a procedure of simple form and one suitable for general use, the tables of factors for adapting the 105B plans to use in terms of hazard rates have been prepared in terms of dimensionless products of t times $Z(t)$. Actually, in order to give figures that may be more conveniently used, the tables are composed of $tZ(t) \times 100$ products. Each of the 105B plans is cataloged in terms of such $tZ(t) \times 100$ products. These product values are to be used in much the same way that percent defective values are used in the selection and application of plans for ordinary attribute inspection. With t and $Z(t)$ specified, all that must be done is to compute their product and then select a plan in its terms. If, on the other hand, a plan (n and c) and a test truncation time (t) are specified,

the product may be used to give an evaluation of operating characteristics in terms of hazard rate, $Z(t)$. Or, alternatively, the product may be used to find a suitable test truncation time, t . Examples of such application of the factors will be found in the latter part of this report.

The Weibull distribution, one will recall, is a three-parameter distribution, requiring a location or threshold parameter, a scale parameter, and a shape parameter for complete description. For the procedure and plans presented here, the scale parameter need not be ascertained or known; the $tZ(t) \times 100$ product contains information on its magnitude. For the location or threshold parameter (commonly symbolized by the letter γ), a value of zero is to be assumed in the direct application of the products and the procedure. For many applications a γ value of 0 will apply; there will be no initial period of life free of risk of failure. This assumption is equivalent to knowing the value for gamma. If γ has some non-zero value, all that is necessary is to subtract the value for γ from t to obtain a value t_0 and then use t_0 rather than t in working with the tables of products. The third parameter, the Weibull shape parameter (which is commonly symbolized by the letter β) must be known. The products depend on the value for β so that its magnitude must be known or estimated from past research, engineering, or inspection data. Separate tables of products have been provided for each of eleven values for β , values ranging from $1/3$ to 5. The assumed value for $\beta=1$ represents the special case of the exponential distribution and so may be used when this distribution seems to be the most appropriate statistical model. Estimation procedures for β or γ are available and may be found in the paper by Kao^{(4), (6)}.

One final point of procedure must be mentioned. It is that for the direct use of the tables of products, the item life at which the hazard

rate is measured or specified and the life at which the testing of sample items is truncated are assumed to be the same. That is, the t used in the $tZ(t) \times 100$ products is the same as the test truncation time, t . However, if the life at which hazard rates are to be specified or evaluated must differ from the test truncation time, a simple variation in procedure may be made to allow for any desired departure. All that must be done is to find (for the value for β assumed) the hazard rate at the test truncation time that corresponds to the hazard rate at the time used in the specification or at which lots are to be evaluated. A table of hazard rate ratios has been compiled for this purpose. It will be found as Table 2 at the end of this report. The method for its use will be described in one of the illustrative examples which will follow.

The Tables of Products

To provide the necessary data for using the 105B plans in life and reliability testing in terms of hazard rate, eleven tables of $tZ(t) \times 100$ products have been prepared. One is available for each of the following values for β : $\frac{1}{3}$, $\frac{1}{2}$, $\frac{2}{3}$, 1, $1\frac{1}{3}$, $1\frac{2}{3}$, 2, $2\frac{1}{2}$, $3\frac{1}{3}$, 4, and 5. These values encompass the range of shape parameter values that will commonly be encountered. For values of interest for which no table has been provided (but within the above range), linear interpolation will give factors accurate enough for most practical purposes. The tables of factors have been included at the end of this report as Tables I-A through I-K.

Each table provides $tZ(t) \times 100$ products for each 105B plan, that is for each combination of Sample Size Code Letter and Acceptable Quality Level the 105B Standard utilizes. The factors apply not only to the single-sampling plans, but also to the matched double-sampling and multiple-sampling plans. The sample sizes corresponding to each Sample Size Code Letter and the acceptance and rejection numbers applying to each Acceptable Quality

Level as found in the 105B Standard are thus to be used in the procedure presented in this paper.

Across the top of each table will be found $tZ(t) \times 100$ products corresponding to each of the Acceptable Quality Level values utilized in the 105B tables. Each of these matched $tZ(t) \times 100$ products provides for all of the 105B plans of the corresponding Acceptable Quality Level a measure of lot quality for which the probability of acceptance is high. The producer's risk will be low with its actual magnitude being the same as that experienced under normal use of the 105B plans. It will be recalled that this risk varies, being as low as .01 for large sample sizes and as high as .20 for small sample sizes. The risk associated with a specific plan may be obtained from the operating characteristic curves provided in the 105B standard.

Within the body of each table will be found $tZ(t) \times 100$ products for each plan for which the probability of acceptance is low. In each case this probability is .10. These products may be used as a means of estimating the consumer's risk when a Rejectable Hazard Rate is to be determined or when a plan is to be selected in such terms. Thus with pairs of factors provided for use in terms of both an Acceptable Hazard Rate as found across the top of each table and a Rejectable Hazard Rate as found within the body of each table, plans may be selected or evaluated in terms of either the producer's risk or the consumer's risk or both. Recently a proposed revision "C" of MIL-STD-105 included, among other things, the listing of LTPD values as consumer's protection measures as well as the AQL values.⁽⁷⁾

The interpretation of these $tZ(t) \times 100$ products may be demonstrated by means of a simple example. Suppose that for a product to be submitted to acceptance inspection β can be assumed to have a value of $\frac{1}{2}$ and γ a value of 0. Life testing of sample items is to be truncated at 500 hours. A single-sampling plan for Sample Size Code Letter H and an AQL of 1.5% has been

specified for use (n , the sample, size will thus be 35 and c , the acceptance number, 1). Reference to Table 1-B which contains products for $\beta = \frac{1}{2}$ shows that the $tZ(t) \times 100$ product at the Acceptable Quality Level of 1.5% is .756. With $t = 500$ thus $500Z(t) \times 100 = .756$. $Z(t)$, the hazard rate, can thus be computed as $Z(t) = .756/500 \times 100 = .000151$ (per hour). Accordingly, this figure, .000151, can be considered as the Acceptable Hazard Rate (as measured at 500 hours of life). Next, by entering the body of the table at Sample Size Code Letter H and an AQL of 1.5%, the $tZ(t) \times 100$ product for which the probability of acceptance is low (.10) is 5.5. Again with $t = 500$, $500Z(t) \times 100 = 5.5$ or $Z(t) = 5.5/500 \times 100 = .0011$. Thus the Rejectable Hazard Rate (at 500 hours of life) is .0011 (per hour). These two figures found for $Z(t)$ may be interpreted thus; (a) lots for which the hazard rate for items at 500 hours of life is .000151 per hour or less will have a high probability of acceptance (examination of the OC curves in the 105B Standards indicates the probability is slightly more than .90); lots for which the hazard rate for items at 500 hours of life is .0011 will have a low probability of acceptance (namely .10 or less).

Examples

Example (1):

A purchased electronic component is to be inspected, lot by lot, for lifelength by sampling inspection. The MIL-STD-105B plans are to be employed. The lot quality of interest is the hazard rate at a life of 500 hours. From past experience with the component it has been determined that the Weibull distribution can be applied as a statistical model and that a value for β , the shape parameter, of $\frac{2}{3}$ can be assumed and a value for γ , the location or threshold parameter, of 0 can be expected. Normal inspection is

to be employed and the lot size in each case will be 3,000 items. A plan employing an Acceptable Quality Level (in terms of the percent defective as used in the standard) of 4.0% and a test period of 500 hours have been tentatively selected, with single sampling to be utilized. Under these given conditions, the acceptance procedure and the operating characteristics in terms of hazard rate at 500 hours are to be determined.

By referring to Table III of MIL-STD-105B it will be found that for Inspection Level II (which is customarily employed unless there are special reasons for doing otherwise) and for a lot size of 3,000, Sample Size Code Letter L should be employed. Next, reference to Table IV-A of the same Military Standard shows that for Sample Size Code Letter L the sample size for single sampling is 150 items. Further reference to this latter Table shows that for the 4.0% Acceptable Quality Level selected the acceptance number to use is 11 and the rejection number 12. The acceptance-rejection procedure will accordingly be:

- (a) Draw at random from the lot a sample of 150 items.
- (b) Place the sample items on life test for 500 hours.
- (c) Determine the number of sample items that fail prior to the end of this test period.
- (d) If the number that fail is 11 or less, accept the lot; if the number that fail is 12 or more, reject it.

The operating characteristics of the above acceptance procedure in terms of hazard rate can be determined by reference to Table I-C which will be found at the end of this report. This table lists $tZ(t) \times 100$ products for application when $\beta = \frac{2}{3}$. Examination of the factors across the top of the table (immediately below the AQL figures in $p'(\%)$) shows that at 4.0% the corresponding $tZ(t) \times 100$ ratio is 2.72. With $t = 500$ and with $tZ(t) \times 100 = 2.72$, the hazard rate is thus determined by:

$$500Z(t) \times 100 = 2.72$$

$$Z(t) = \frac{2.72}{500 \times 100} = .0000544$$

This figure may be considered as an Acceptable Hazard Rate (AHR). Thus if the quality of the submitted lot is such that the hazard rate at 500 hours is .0000544 (per hour), the probability of its acceptance will be high. By reference to Table VI-L of the Military Standard, operating characteristic curves for single sampling for Code Letter L may be found. The curve for a 4.0% AQL indicates that at 4.0% the probability of acceptance is slightly more than .98; the producer's risk, then, for lots for which the hazard rate is .0000544 at 500 hours is 1.00-.98 or .02.

A Rejectable Hazard Rate (RHR), a rate at which the probability of acceptance will be low under the above plan, may also be determined by further reference to Table I-C of this report. In the body of this table at Sample Size Code Letter L and an AQL of 4.0%, a second $tZ(t) \times 100$ product for the application, one whose value is 7.9, will be found. This is the product for which the probability of acceptance is .10 or less. Using $t = 500$ and making another simple computation gives:

$$500Z(t) \times 100 = 7.9$$

$$Z(t) = \frac{7.9}{500 \times 100} = .00016$$

This answer may be considered as a Rejectable Hazard Rate (RHR). If the lot quality is such that the hazard rate is .00016 (per hour) at 500 hours of life, the probability of acceptance for the lot will be low, namely .10 or less. This figure quantifies the consumer's risk at the Rejectable Hazard Rate of .00016.

Example (2):

For another illustration of use, consider a sampling inspection application for which an Acceptable Hazard Rate of .000025 (per hour) and a Rejectable Hazard Rate of .00015 (per hour) with both at 1000 hours of life is required. A value for β of $1\frac{2}{3}$ and for γ of 0 can be assumed. The test time for sample items is to be 1,000 hours with double sampling to be employed. The problem is to select from the MIL-STD-105B plans the one that will meet most closely these requirements.

Computations at the Acceptable Hazard Rate give $tZ(t) \times 100 = 1,000 \times .000025 \times 100 = 2.5$. Reference may now be made to Table I-F of this report which lists $tZ(t) \times 100$ products for application when $\beta = 1\frac{2}{3}$. In the line of factors across the top of the table (the column headings) the factor 2.52 will be found corresponding to a 1.5% AQL. Use of any plan with this AQL percentage will thus meet closely the Acceptable Hazard Rate requirement; the probability of acceptance for lots meeting this specified figure will be high.

Computations at the Rejectable Hazard Rate give $tZ(t) \times 100 = 1,000 \times .00015 \times 100 = 15$. Examination of the column of products for the 1.5% AQL figure shows that for Sample Size Code Letter J the $tZ(t) \times 100$ product is 15. Thus use of this Code Letter (with the AQL value selected) will provide a low probability of acceptance (.10 or less) for lots at which the hazard rate is .00015 at 1000 hours. Any 105B plan (single, double, or multiple) with a 1.5 AQL and a Sample Size Code Letter J will meet closely the operational requirements.

For double sampling, reference to Table IV-B of the 105B Standard indicates the first sample size is 50 and the second sample size is 100 for Letter J. At the AQL value of 1.5 the acceptance number under normal inspection

for the first sample must be 1 and the rejection number 6; for combined samples the acceptance number must be 5 and the rejection number 6. Other details of the acceptance-rejection procedure will be those customarily employed in double sampling. It should be noted that the life testing time for the first sample must be 1,000 hours; likewise, it must be 1,000 hours for the second sample when testing of a second sample becomes necessary.

Example (3):

Consider a case for which a β value of $2\frac{1}{2}$ and a γ value of 0 can be assumed. A Rejectable Hazard Rate of .00090 (per hour) at a life of 2,000 hours has been specified. However, a test period of only 500 hours for sample items is, for practical reasons, the longest that can be utilized. The problem is to determine a single-sampling 105B plan that will meet the RHR requirement.

A suitable plan in terms of this required time for the lot quality specification but one that uses the reduced testing time can be found through application of data in Table 2 of this report, a table of hazard rate ratios. If we let t_2 represent the life at which the hazard rate is specified and t_1 represent the testing time to be employed, then the ratio between the two which is required for the use of the table may be determined. It is t_2/t_1 or 2000/500 which is 4. Entering the table at the 4.00 value for this ratio and reading across to values for use when $\beta = 2\frac{1}{2}$, a $Z(t_2)/Z(t_1)$ ratio of 8.00 may be found. Letting $Z(t_2)$ represent the hazard rate specified at time t_2 of 2,000 hours (which is .00090), a corresponding hazard rate $Z(t_1)$ at time t_1 of 500 hours can be computed. Since $Z(t_2)/Z(t_1) = 8.00$, $Z(t_1) = .00090/8.00 = .00011$. A $tZ(t) \times 100$ ratio can now be computed using this new rate to apply at 500 hours. It is $500 \times .00011 \times 100 = 5.5$

With this value for the RHR product, 5.5, one may now make reference to

Table I-H which lists products for $\beta = 2\frac{1}{2}$. Any plan for which a value at or close to 5.5 may be found in the body of this table will meet the RHR specifications. For example, a plan with an AQL of 0.25% and with Sample Size Code Letter N will do; likewise, one with an AQL of 1.0% and with Sample Size Code Letter Q meets the requirement. A choice from these or other suitable alternatives will depend on the Acceptable Hazard Rate that seems most suitable for the case. Use of the $tZ(t) \times 100$ product at the top of a column from which a plan is selected will enable one to determine the hazard rate for which the probability of acceptance will be high. For the first alternative mentioned above (0.25% and N), $tZ(t) \times 100 = .625$. Thus the AHR = $.625/500 \times 100 = .000125$ at 500 hours. At 2000 hours it depends on the ratio $Z(t_2)/Z(t_1) = 8.00$. Thus at 2000 hours the AHR, $Z(t_2) = .000125 \times 8.00 = .0010$.

Example (4):

For an example of a case for which the location or threshold parameter is not zero, consider an application for which one can assume $\beta = 4$ and $\gamma = 200$ hours. A sample size of 50 has been specified (single sampling is to be employed). A life testing time of 600 hours for sample items has been agreed upon. It seems reasonable to expect a hazard rate of .00070 at 600 hours and so this figure is selected as an Acceptable Hazard Rate and a plan is accordingly to be selected in these terms. The problem is to determine what acceptance number must be used and also what measure of consumer protection will be afforded.

The first step is to subtract the value for γ from the value for t , the test and specification time value, to get t_0 , a value in zero threshold-parameter terms. Accordingly, $t - \gamma = 600 - 200 = 400 = t_0$. This converted value may now be used in the normal manner for the tables and procedures

being described in this report.

The $t_0 Z(t) \times 100$ product at the Acceptable Hazard Rate will thus be $400 \times .00070 \times 100$ or 28. Reference may now be made to Table I-J which lists products for $\beta = 4$. Examination of the column headings indicates for an AQL of 6.5% a corresponding $tZ(t) \times 100$ product of 26.9, a figure reasonably close to 28. Reference next to table IV-A of MIL-STD-105B shows that for single sampling with a sample of size 50, and with an AQL of 6.5%, the acceptance number must be 6. Also, it may be noted that a single sample of size 50 corresponds to Sample Size Code Letter I.

To determine a measure of consumer protection when the sample size is 50 (Letter I) and the acceptance number is 6 (AQL = 6.5%), reference may now be made again to Table I-J of this report. At Letter I and an AQL of 6.5%, it will be found that the $tZ(t) \times 100$ product is 89 at the Rejectable Hazard Rate (for which the probability of acceptance is low, namely .10 or less). With this value one may determine that $t_0 Z(t) \times 100 = 400 Z(t) \times 100 = 89$, or $Z(t) = 89/400 \times 100 = .0022$. Note again for these computations the converted time value, t_0 , is used. The Rejectable Hazard Rate of .0022 as computed above actually applies, however, at a real life of $(t_0 + \gamma)$ or 600 hours.

Appendix

The Relationship Between p' and $tZ(t)$

The hazard rate at a specified time t , $Z(t)$, may be expressed by the equation

$$Z(t) = f(t) / [1 - F(t)] \quad (1)$$

for which $f(t)$ is the population density function and $F(t)$ is the cumulative distribution function.

For the Weibull case (letting γ , the location or threshold parameter equal 0), the following relationships held,

$$f(t) = (\beta/\eta) (t/\eta)^{\beta-1} \exp[-(t/\eta)^\beta] , \quad (2)$$

and

$$F(t) = 1 - \exp[-(t/\eta)^\beta] \quad (3)$$

where η is the scale parameter and β the shape parameter.

Substitution of the expression for $f(t)$ given by Equation 2 and for $F(t)$ by Equation 3 into Equation 1 and simplifying gives

$$Z(t) = (\beta/\eta) (t/\eta)^{\beta-1} . \quad (4)$$

Multiplying each side of Equation 4 by (t/β) gives the equation

$$\frac{tZ(t)}{\beta} = (t/\eta)^\beta . \quad (5)$$

The probability, p' , of an item failing before time t is given by the cumulative distribution function.

$$p' = F(t) = 1 - \exp[-(t/\eta)^\beta] \quad (6)$$

By combining Equations 5 and 6, p' in terms of $tZ(t)$ is thus found to be

$$p' = 1 - \exp\left[-\frac{tZ(t)}{\beta}\right] , \text{ or} \quad (7)$$

$$tZ(t) = -\beta \ln(1-p') . \quad (8)$$

Bibliography

1. Goode, Henry P. and Kao, John H.K., "Sampling Procedures and Tables for Life and Reliability Testing Based on the Weibull Distribution (Hazard Rate Criterion)," published in the Proceedings of the Eighth National Symposium on Reliability and Quality Control, 1962.
2. Military Standard - 105B, "Sampling Procedures and Tables for Inspection by Attributes," United States Government Printing Office, 1959.
3. Goode, Henry P. and Kao, John H.K., "An Adaptation of the MIL-STD-105B Plans to Reliability and Life Testing Applications," Transactions of the Fifteenth Annual Convention, American Society for Quality Control, 1961, pp. 245-259.
4. Kao, John H.K., "A Summary of Some New Techniques on Failure Analysis," Proceedings of the Sixth National Symposium on Reliability and Quality Control in Electronics, 1960, pp. 190-201.
5. Goode, Henry P. and Kao, John H.K., "Sampling Plans Based on the Weibull Distribution," Proceedings of the Seventh National Symposium on Reliability and Quality Control, 1961, pp. 24-40.
6. Kao, John H.K., "A Scale Estimator with Special Application to the Weibull Distribution," Technical Report No. 6 under Office of Naval Research Contract with the Department of Industrial and Engineering Administration, Cornell University, 1961.
7. Keefe, G.J., "Military Standard 105 and its "C" Revision," Semiconductor Reliability, Vol. II, scheduled for publication by Engineering Publishers, Elizabeth, N.J., 1961.

Table of $tZ(t)$ x 100 Products for $\beta = 1/3$
$$HR[P(A)] = 10$$

Table of $t_Z(t)$ x 100 Products for $\beta = 1/2$ [illegible]

Table of $tZ(t)$ x 100 Products for $\beta = 2/3$ [illegible]

TABLE I-D

1

Table of $tZ(t)$ x 100 Products for $\beta = 1.1/3$ [illegible]

Table of $tZ(t)$ x 100 Products for $\beta = 1.2/3$ [illegible]

Table of $tZ(t)$ x 100 Products for $\beta = 2$ [illegible]

TABLE 1-H

$$\overline{10} \cdot = (A)_P [$$

TABLE 1-J
Table of $tZ(t) \times 100$ Products for $\beta = 4$

Sample Size Code Letter	Acceptable Quality Level (AQL)														
	p*(%)	0.015	0.035	0.065	0.10	0.15	0.25	0.40	0.65	1.0	1.5	2.5	4.0	6.5	10.0
	tZ(t) x 100	.060	.140	.260	.400	.600	1.00	1.60	2.61	4.02	6.04	10.1	16.3	26.9	42.1
A	tZ(t) x 100 Product at RHR [P(A) = .10]	-	-	-	-	-	-	-	-	-	-	-	-	↓	470
B		-	-	-	-	-	-	-	-	-	-	-	-	310	↑
C		-	-	-	-	-	-	-	-	-	-	-	180	↑	↓
D		-	-	-	-	-	-	-	-	-	↓	130	↑	↑	230
E		-	-	-	-	-	-	-	-	↓	92	↑	↑	160	230
F		-	-	-	-	-	-	-	-	62	↑	↑	100	150	200
G		-	-	-	-	-	-	-	↓	36	↑	↑	65	89	160
H		-	-	-	-	-	-	↑	26	↑	↑	45	64	80	110
I		-	-	-	-	-	↑	18	↑	-	31	44	56	68	89
J		-	-	-	↓	12	↑	↑	14	21	28	36	44	58	81
K		-	-	↓	6.0	↑	↑	10	14	19	25	29	40	49	71
L		-	↓	3.4	8.2	↑	↑	10	14	18	21	25	35	47	69
M		↓	4.0	↑	5.2	6.9	9.5	12	14	16	23	30	45	60	85
N		3.0	↑	↑	5.2	7.0	8.8	10	12	15	21	27	38	58	79
O		↑	↑	↑	4.7	5.9	7.0	8.2	10	13	18	25	34	50	71
P		↑	2.0	2.8	3.5	4.2	5.6	6.9	8.8	11	14	21	30	45	66
Q		1.0	1.4	1.8	2.4	3.1	3.8	5.0	6.8	8.8	11	11	18	25	40

TABLE I-K

Sample Size	Code Letter
10	A
20	B
30	C
40	D
50	E
60	F
70	G
80	H
90	I
100	J
120	K
150	L
200	M
250	N
300	O
400	P
500	Q
600	R
800	S
1000	T
1200	U
1500	V
2000	W
2500	X
3000	Y
4000	Z

TABLE 2
Table of Hazard Rate Ratios

$\frac{t_2}{t_1}$	$\frac{Z(t_2)}{Z(t_1)}$										
	β										
	1/3	1/2	2/3	1	1-1/3	1-2/3	2	2-1/2	3-1/3	4	5
1.25	.862	.894	.928	1.00	1.08	1.16	1.25	1.40	1.68	1.95	2.44
1.50	.763	.816	.873	1.00	1.14	1.31	1.50	1.84	2.57	3.38	5.06
1.75	.689	.756	.830	1.00	1.21	1.45	1.75	2.32	3.69	5.36	9.38
2.00	.630	.707	.794	1.00	1.26	1.59	2.00	2.83	5.04	8.00	16.0
2.25	.583	.667	.763	1.00	1.31	1.72	2.25	3.38	6.64	11.4	25.6
2.50	.543	.632	.737	1.00	1.36	1.84	2.50	3.95	8.49	15.6	39.1
2.75	.510	.603	.714	1.00	1.40	1.96	2.75	4.56	10.6	20.8	57.2
3.00	.481	.577	.694	1.00	1.44	2.08	3.00	5.20	13.0	27.0	81.0
3.25	.456	.555	.675	1.00	1.48	2.19	3.25	5.86	15.6	34.3	112
3.50	.434	.534	.659	1.00	1.52	2.30	3.50	6.55	18.4	42.9	148
3.75	.414	.516	.643	1.00	1.55	2.42	3.75	7.26	21.8	52.7	198
4.00	.397	.500	.630	1.00	1.59	2.52	4.00	8.00	25.4	64.0	256
4.25	.381	.485	.617	1.00	1.62	2.62	4.25	8.76	29.3	76.8	326
4.50	.367	.472	.606	1.00	1.65	2.73	4.50	9.54	33.4	91.1	410
4.75	.354	.459	.595	1.00	1.68	2.83	4.75	10.4	37.9	107	509
5.00	.342	.447	.585	1.00	1.71	2.92	5.00	11.2	42.8	125	625

DISTRIBUTION LIST

Head, Logistics and Mathematical
Statistics Branch
Office of Naval Research
Washington 25, D.C.

3

Mr. R. E. Wiley
Materials Branch
Office of Naval Research
Washington 25, D.C.

1

Commanding Officer
Office of Naval Research Branch Office
Navy #100 Fleet Post Office
New York, New York

2

Miss Besse B. Day
Bureau of Ships, Code 344
Department of the Navy
Washington 25, D.C.

1

ASTIA Document Service Center
Arlington Hall Station
Arlington 12, Virginia

10

Mr. A. S. Marthens
Bureau of Ships, Code 344
Department of the Navy
Washington 25, D.C.

1

Technical Information Officer
Naval Research Laboratory
Washington 25, D.C.

6

Mr. P. Brown
Bureau of Ships, Code 344
Department of the Navy
Washington 25, D.C.

1

Institute for Defense Analyses
Communications Research Division
von Neumann Hall
Princeton, N.J.

1

Dr. H. Weingarten
Special Projects Office
Department of the Navy
Washington 25, D.C.

1

Chief of Naval Material
Code M533, Room 2236, Main Navy
Department of Navy
Washington 25, D.C.

1

Mr. F. R. Del Priore
U. S. Naval Engineering
Experiment Station
Annapolis, Maryland

1

Commanding Officer
U.S. Navy Mine Defense Laboratory
Panama City, Florida

1

Dr. Mitchell L. Cotton
Dept. of Electronics
U.S. Naval Post Graduate School
Monterey, California

1

Commander, Material Laboratory
New York Naval Shipyard
Naval Base
Brooklyn 1, New York
Attn: A. Walner

1

Commander
U.S. Naval Air Development Center
Johnsville, Pennsylvania

1

Commanding Officer
U. S. Naval Radiological Defense
Laboratory
San Francisco, California

1

Mr. H. R. Thoman
Bureau of Naval Weapons
Department of the Navy
Room 1W86 (RAAV-4423)
Washington 25, D. C.

1

Dr. Julius Lieblein
Applied Mathematics Lab., Code 820
David Taylor Model Basin
Washington 7, D.C.

1

Dr. Wm. R. Pabst
Bureau of Weapons
Room 0306, Main Navy
Department of the Navy
Washington 25, D.C.

1

Library Division
Naval Missile Center Command
U.S. Naval Missile Center
Point Mugu, California
Attn: J. L. Nickel

U.S. Naval Ammunition Depot
Quality Evaluation Laboratory
Crane, Indiana

Chief, Bureau of Naval Weapons
Quality Control Division (PQC)
Department of the Navy
Washington 25, D.C.

Chief, Bureau of Naval Weapons
Research and Development Div.
Department of the Navy
Washington 25, D.C.
Attn: Mr. G. A. Best

Chief, Bureau of Naval Weapons
Administrative Div. (SP-43)
Department of the Navy
Washington 25, D.C.

U.S. Naval Inspector of
Ordnance (QC5)
Naval Gun Factory
Washington 25, D.C.

Chief, Bureau of Naval Weapons
Engineering (RREN-8)
Department of the Navy
Washington 25, D.C.
Attn: Mr. G. S. Peratino

Commanding Officer U.S.
U.S. Naval Ordnance Laboratory
Missile Evaluation Department (6)
Corona, California
Attn: Clayborn Graves

Commander
U.S. Naval Ordnance Test Station
China Lake, California
Attn: John P. Vanderbeck

Chief, Bureau of Yards & Docks
Material Division
Department of the Navy
Washington 25, D.C.
Attn: A. Stephanides

Inspection and Quality Control Div.
Office, Assistant Secretary of
Defense (S&L)
Washington 25, D.C.
Attn: Mr. John J. Riordan
Mr. Irving B. Altman

Office, Assistant Secretary of
Defense (R&E)
Room 3D984, The Pentagon
Washington 25, D.C.
Attn: Mr. R. H. DeWitt

Office of Guided Missiles
Office, Assistant Secretary of
Defense (R&E)
Washington 25, D.C.
Attn: Mr. Carlton M. Beyer
Mr. E. J. Nucci

Technical Library
Office, Assistant Secretary of
Defense (R&E)
Room 3E1065, The Pentagon
Washington 25, D.C.

Office, Assistant Secretary of
Defense (R&E)
Room 3D165, The Pentagon
Washington 25, D.C.
Attn: Mr. Rudolph Furrer

Mr. Silas Williams, Jr.
Standards Branch
Procurement Division
DCS/Logistics, U.S. Army
Washington 25, D.C.

Office of Ordnance Research
Box CM, Duke Station
Durham, North Carolina

Mr. Fred Frishman, Chairman
Army Research Office
Arlington Hall Station
Arlington, Virginia

LTCOL W. C. Marcus
Air Research Development Command
Baltimore, Maryland

Mr. R. Beidenbender
Hq., Air Materiel Command (MOQPP)
Wright-Patterson Air Force Base
Ohio

Dr. Joseph Daly
U.S. Census Bureau
Washington 25, D.C.

Dr. Marvin Zelen
Statistical Engineering Laboratory
National Bureau of Standards
Washington 25, D.C.

Chief, Statistical Engineering Lab
National Bureau of Standards
Washington 25, D.C.
Attn: Dr. Joan R. Rosenblatt

Professor T. W. Anderson
Department of Mathematical Statistics
Columbia University
New York 27, New York

Professor Z. W. Birnbaum
Laboratory of Statistical Research
Department of Mathematics
University of Washington
Seattle 5, Washington

Professor A. H. Bowker
Applied Mathematics & Statistics Lab.
Stanford University
Stanford, California

Professor Ralph A. Bradley
Department of Statistics
Florida State University
Tallahassee, Florida

Dr. John W. Cell
Department of Mathematics
North Carolina State College
Raleigh, North Carolina

Professor Herman Chernoff
Applied Mathematics & Statistics Lab.
Stanford University
Stanford, California

Professor W. G. Cochran
Department of Statistics
Harvard University
Cambridge, Massachusetts

Dr. C. Clark Cockerham
Institute of Statistics
North Carolina State College
Raleigh, North Carolina

Professor Edward P. Coleman
Engineering Department
University of California
Los Angeles 24, California
Professor Cyrus Derman
Dept. of Industrial Engineering
Columbia University
New York 27, New York

Professor Acheson J. Duncan
Dept. of Industrial Engineering
The Johns Hopkins University
Baltimore 18, Maryland

Professor Benjamin Epstein
Applied Mathematics & Statistics Lab.
Stanford University
Stanford, California

Professor W. T. Federer
Cornell University
Department of Plant Breeding
Biometrics Units
Ithaca, New York

Dr. R. J. Freund
Department of Statistics &
Statistical Lab.
Virginia Polytechnic Institute
Blacksburg, Virginia

Professor H. P. Goode
Dept. of Industrial and Engineering
Administration
Cornell University
Ithaca, New York

Professor Eugene L. Grant
Civil Engineering Department
Stanford University
Stanford, California

Professor W. Hirsch
Institute of Mathematical Sciences
New York University
New York 3, New York

Professor Herbert Robbins
Mathematical Statistics Dept.
Fayerweather Hall
Columbia University
New York 27, New York

Professor Grant Ireson
Dept. of Industrial Engineering
Stanford University
Stanford, California

Professor Murray Resenblatt
Department of Mathematics
Brown University
Providence 12, Rhode Island

Professor Harold Hotelling
Associate Director
Institute of Statistics
University of North Carolina
Chapel Hill, North Carolina

Professor H. Rubin
Department of Statistics
Michigan State University
East Lansing, Michigan

Dr. Eugene Lukacs
Department of Mathematics
Catholic University
Washington 17, D.C.

Professor I.R. Savage
School of Business Administration
University of Minnesota
Minneapolis, Minnesota

Professor Oscar Kempthorne
Statistics Laboratory
Iowa State College
Ames, Iowa

Professor L. J. Savage
Statistical Research Laboratory
Chicago University
Chicago 37, Illinois

Professor Gerald J. Lieberman
Applied Mathematics and Statistics Lab.
Stanford University
Stanford, California

Professor W. L. Smith
Statistics Department
University of North Carolina
Chapel Hill, North Carolina

Dr. Arthur E. Mace
Battelle Memorial Institute
505 King Avenue
Columbus 1, Ohio

Professor Frank Spitzer
Department of Mathematics
University of Minnesota
Minneapolis, Minnesota

Professor J. Neyman
Department of Statistics
University of California
Berkeley 4, California

Dr. H. Teicher
Statistical Laboratory
Engineering Administration Bldg.
Purdue University
Lafayette, Indiana

Dr. F. Oberhettinger
Department of Mathematics
Oregon State College
Corvallis, Oregon

Professor M. B. Wilk
Statistics Center
Rutgers-the State University
New Brunswick, New Jersey

Professor E. G. Olds
Department of Mathematics
Carnegie Institute of Technology
Pittsburgh 13, Pennsylvania

Professor S. S. Wilks
Department of Mathematics
Princeton University
Princeton, New Jersey

Professor George J. Resnikoff
Illinois Institute of Technology
Technology Center
Department of Industrial Engineering
Chicago 16, Illinois

Professor J. Wolfowitz
Department of Mathematics
Lincoln Hall
Cornell University
Ithaca, New York

Dr. Max A. Woodbury
Dept. of Mathematics
College of Engineering
New York University
New York 53, New York

Professor Maurice H. Balz
University of Melbourne
Carlton N. 3
Victoria, Australia

Professor Tosio Kitagawa
Mathematical Institute
Faculty of Sciences
Kyusyu University
Fukuoka, Japan

Mr. John K. Borkman
Whippany Laboratory
Bell Telephone Laboratories, Inc.
Whippany, New Jersey

Mr. Cesareo Villegas
Institute de Matematica y Estadistica
Av. J. Herrera y Reissig 565
Montevideo, Uruguay

Mr. G. Burrows
Knolls Atomic Power Laboratory
Schenectady, New York

Dr. A. S. Fraser
Department of Mathematics
University of Toronto
Toronto 5, Canada

Mr. W. H. Clatworthy
Bettis Plant, Westinghouse Elec. Corp.
P. O. Box 1468
Pittsburgh 30, Pa.

Mr. R. B. Murphy
Quality Results Engineer
Bell Telephone Laboratories
433 West Street
New York 14, New York

Mr. H. F. Dodge
96 Briarcliff Road
Mountain Lakes, N.J.

Professor Milton Sobel
Department of Statistics
University of Minnesota
Minneapolis 14, Minn.

Dr. G. Kaskey
Remington RAND UNIVAC Division
of Sperry Rand Corporation
1900 West Allegheny Avenue
Philadelphia, Pa.

William A. Glenn, Statistician
Statistics Research Division
Research Triangle Institute
Post Office Box 490
Durham, North Carolina

Dr. John Tischendorf
Allentown Laboratory
Bell Telephone Laboratories, Inc.
Allentown, Pa.

Superintendent
U.S. Naval Postgraduate School
Monterey, California
Attn: Library

Mr. Leon Gilford
Operations Research Inc.
8605 Cameron St.
Silver Spring, Md.

Prof. Irving W. Burr
Div. of Mathematical Sciences
Statistical & Computing Laboratory
Purdue University
Lafayette, Indiana