

UNCLASSIFIED

AD 273 634

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATLOGGED BY ASTIA

AS AD NO. _____

273634

SEAWATER DENSITY IN THE OCEAN AS A
FUNCTION OF DEPTH, AND A METHOD FOR
UTILIZING THIS INFORMATION IN DESIGN OF
PRESSURE VESSELS WHICH WILL REMAIN
IN A CONSTANT DEPTH RANGE BETWEEN
THE SURFACE AND THE BOTTOM

NOL

8 DECEMBER 1961

ASTIA
RECEIVED
MAR 28 1962

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 61-179

- RELEASED TO ASTIA
BY THE NAVAL ORDNANCE LABORATORY
- Without restrictions
 - For Release to Military and Government Agencies Only.
 - Approval by BuWeps required for release to contractors.
 - Approval by BuWeps required for all subsequent release.

SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM

Prepared by:
William F. Warren

ABSTRACT: Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If an expendable weight is used to sink the vessel to its design depth, then it might be possible to plant as close as 200 fathoms below the surface. The extent of vertical migration can be predicted from the curves, being on the order of several hundred fathoms for a reasonably stiff pressure vessel near the surface. For deeper depths, this migration zone decreases until it is something less than fifty fathoms for 3,000 fathoms depth and below. For a particular vessel design, the migration zone can be made smaller by increasing stiffness of the vessel; i.e., by increasing wall thickness or by adding ribs to the vessel. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

NOLTR 61-179

8 December 1961

SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A
METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE
VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE
SURFACE AND THE BOTTOM

This report presents data and general procedures which are intended for design planning purposes and for preliminary design work on ordnance projects. The basic idea which generated this work; i.e., the idea of a neutrally buoyant weapon, was first proposed to the author by Mr. L. C. Fisher and Mr. C. C. Vogt of the Naval Ordnance Laboratory. Where opinions are expressed they represent the opinion of the author and of the Underwater Mechanical Engineering Department of the Naval Ordnance Laboratory. The work was done on Bureau of Weapons Task Number RUME 2E-000 PA#031.

W. D. COLEMAN
Captain, USN
Commander


L. C. FISHER
By direction

CONTENTS

	Page
Seawater Density as a Function of Depth	1
A Method for Ordnance Design	1
Example of the Method for an Aluminum Sphere	2
Comments for Future Work	3
Appendix A	4

ILLUSTRATIONS

		Title	
Figure			Page
1	Seawater Density in the North Atlantic (fathoms)		7
2	Seawater Density in the North Atlantic (feet)		8
3	Seawater Density in the World Ocean (fathoms)		9
4	Compressibility Curves for Aluminum Alloy Sphere.....		10
	North Atlantic (fathoms)		
5	Compressibility Curves for Aluminum Alloy Sphere.....		11
	North Atlantic (feet)		
6	Compressibility Curves for Aluminum Alloy Sphere.....		12
	World Ocean (fathoms)		

TABLES

Table	Title	Page
1	Extreme Values of Temperature and Salinity at Various Depths in the Atlantic, Pacific and Indian Oceans	5

REFERENCES

- (a) "Properties of Water Substance" by Dorsey
- (b) U. S. Coast & Geodetic Survey Special Publication No. 108
 by N. H. Heck and J. H. Service
- (c) "The Oceans" by Sverdrup, Johnson and Fleming
- (d) "Die Zusammendruckbarkeit des Meerwassers" by Ekman

SEAWATER DENSITY AS A FUNCTION OF DEPTH

1. Presented here are curves which show the maximum and minimum values of seawater density, expressed as specific volume, which are to be expected over the whole ocean area and from the surface down to the bottom; i.e., everywhere in the entire volume of ocean water. (See Appendix A for methods used in determining these density values). Each of the three sheets, figures 1, 2 and 3, therefore, must contain two curves, a maximum and a minimum; and all possible density values in the ocean must lie between the two curves. So, if we choose at random any longitude, latitude, water depth, and time, and then measure the density of the seawater there, we can be confident that this measured value will be somewhere between the maximum and minimum values for that depth as shown on the curves. The degree of our confidence need depend only on the temperature-salinity data which was provided by the Navy Hydrographic Office (Table 1) and on the Heck and Service experimental data as contained in reference (b).

A METHOD FOR ORDNANCE DESIGN

2. If it is desired to place a piece of ordnance at some depth in the ocean and have it remain there we might proceed as follows:

a. Design and build a suitable pressure vessel which can withstand the expected pressures and maintain approximately neutral buoyancy.

b. Measure the over-all density of the assembled unit over the expected pressure range; i.e., put it in a pressure chamber and measure the net buoyancy for the various pressures. Plot curve of net buoyancy versus pressure.

c. Add trim weights to the unit so as to match the value from the maximum density curve (curve on the left) for the upper design depth.

3. If these things are done then the unit can be dropped anywhere in the ocean and it will sink below the "design depth" never to rise above it again. The deepest possible depth which it can then reach will be defined by the minimum density curve (curve on the right) where it intersects with the buoyancy-pressure curve, as determined above, for the particular unit involved. So the unit will remain always within a specific depth zone. It can, of course, move up and down in the zone

as time changes and as the unit drifts into new areas (i. e., new temperature and salinity conditions) but it can never sink out of the zone or rise above it. The vertical dimension of this depth zone will be less for a stiff pressure vessel such as a thick walled sphere, than for a more compressible shape, such as a thin unsupported cylinder.

4. However, almost any vessel should work (i.e., always remain below the "design depth") provided it can withstand the hydrostatic pressures involved. Of course the minimum design depth and the zone of migration will both depend on the stiffness; the greater the stiffness of a vessel, the closer it can operate to the surface and the smaller will be its zone of migration. (Note: These facts might help to explain why oceanographic floats, which are long thin unsupported cylinders, have not been successful in depths shallower than 2000 meters).

EXAMPLE OF THE METHOD FOR AN ALUMINUM SPHERE

5. The method previously described will now be used to examine the performance of an aluminum sphere (any diameter, but wall thickness to be 1/10 of the mean spherical radius) as a pressure vessel for a constant depth range item of ordnance. Of course, this is just one configuration picked more or less at random to serve as an example; other configurations could be expected to perform better or worse depending on their relative compressibilities.

6. For this simple shape the compressibility can be accurately computed with specific volumes, V , as a cubic function of the depth, d , as follows:

$$V = V_0 (1 - A_d + B_d^2 - C_d^3)$$

For this example the values of B and C were found to be negligibly small for all values of d from 0 to 35,000 feet, so V became a straight-line function of d for this case. This function produced a family of curves with V_0 as the parameter, where V_0 is the specific volume of the sphere at zero pressure. The seawater density curves have been modified by adding these "compressibility curves" (in this case a family of parallel straight lines) to show the depth ranges which are possible for each "design depth" as shown in figures 4, 5, and 6. It is believed that this general approach should be applicable to a wide variety of shapes, but only the simplest shapes can be computed; most shapes being experimentally measured as explained in paragraph 2 above.

COMMENTS FOR FUTURE WORK

7. If a weapon design can be restricted to a limited area of the ocean such as the upper latitudes of the Atlantic (above 45 degrees North), or perhaps the equatorial zone of the World Ocean (between 15 degrees North and 15 degrees South), a shallower minimum planting depth should be possible and the range of migration should also be less.

8. This should also hold true for separate areas such as the Arctic Ocean and the Baltic Sea, where even more uniform densities might be expected.

9. When a new project is to be started, the planting area should first be established, then a table for this area, similar to Table 1 of this report, should be obtained from the National Oceanographic Data Center, Washington 25, D. C. A set of curves could then be constructed and the project could proceed on the basis of these curves as explained above.

APPENDIX A

From Dorsey, reference (a), we have the formula:

$$D_{s,t,d} = D_{35,0,d} - (6.48 + .00375d)t - 0.46t^2 + (f - .283t - .005t^2)(s-35)$$

$s = 31 \text{ to } 37 \text{ gm/kg}$
 $t = 0 \text{ to } 22^\circ\text{C}$

where

$D_{s,t,d}$ = specific volume in cm^3/gm

$D_{35,0,d}$ = " " at $t = 0^\circ\text{C}$ and $s = 35 \text{ gm/l}$

f = tabulated function of depth (in reference (a))

$D_{35,0,d}$ = " " " " " " " "

s = salinity - total salts per kg of seawater

t = temperature in degrees Centigrade

d = depth below surface in meters

It is assumed that the maximum possible density at each depth will correspond to the minimum temperature and maximum salinity as given in table I of this report. Likewise, the minimum density is assumed to correspond with the maximum temperature and minimum salinity from table I. Maximum and minimum densities were obtained in this way for the various depths. This information was then used to produce the curves.

See also table I of reference (b) where this same information is available in tabular form. This table is usually more convenient than the above formula for ordinary computations. It was used for all computations in this report. The formula is included for future reference on work which might involve a digital computer, where it should prove to be more easily used than the tabular data.

The formula above has been verified as usually correct to within two units in the fifth significant digit with Heck and Service experimental data as contained in reference (b).

TABLE I

Extreme values for temperature and salinity at various depths in the Atlantic, Indian, and Pacific Oceans as furnished by the Navy Hydrographic Office

Depth (meters)	Temperature (°C)		Salinity (gm/kg)	
	Max.	Min.	Max.	Min.
<u>North Atlantic</u> (equator to Greenland)				
* surface	28.0	-1.0	37.0	33.0
200	27.5	1.0	36.8	34.0
400	18.5	2.0	36.6	34.5
600	18.0	2.0	36.4	34.5
800	14.0	2.0	36.3	34.4
1000	11.5	2.0	36.5	34.5
1250	11.0	2.0	36.4	34.5
1500	9.5	3.0	36.3	34.9
2000	5.2	3.0	35.4	34.4
3000	3.9	2.5	-	-
5000	2.45	2.4	34.9	34.85
* 8500	3.0	2.9	35.0	35.0
beyond 5000	Temperature increases slightly with depth to bottom			
<u>South Atlantic</u> (equator to Antarctica)				
200	21.0	-1.2	36.2	33.9
400	15.0	-1.0	35.6	34.0
600	11.0	-1.0	35.1	34.0
800	6.0	0.0	34.8	34.0
1000	4.5	0.0	34.8	34.0
1250	4.5	0.0	34.9	34.0
1500	4.5	0.0	35.0	34.0
2000	4.0	-0.25	35.0	34.5
5000	2.5	0.0	34.9	34.6

*These values were estimated from data in reference (c).

TABLE I (cont.)

Depth (meters)	Temperature (°C)		Salinity (gm/kg)	
	Max.	Min.	Max.	Min.
<u>Pacific</u>				
1000	5.5	0.6	34.8	34.0
2000	3.5	0.6	34.7	34.5
3000	2.1	0.6	34.7	34.5
4000	2.1	0.6	34.7	34.6
5000	1.8	0.6	34.65	34.6
6000	1.5	1.0	34.65	34.6
beyond 6000			Salinity extremes remain constant (no change) from 6000 meters to the bottom	
<u>Indian Ocean</u>				
1000	8.0	-1.0	35.3	34.1
2000	4.5	-1.0	34.5	34.9
3000	2.0	-1.0	34.5	34.9
5000	1.2	-1.0	34.7	34.6




FIG.1 SEAWATER DENSITY CURVES FOR NORTH ATLANTIC OCEAN (EQUATOR TO GREENLAND) IN FATHOMS




FIG. 2 SEAWATER DENSITY CURVES FOR NORTH ATLANTIC OCEAN (EQUATOR TO GREENLAND) IN FEET




FIG. 3 SEAWATER DENSITY CURVES FOR WORLD OCEAN (ATLANTIC, INDIAN, PACIFIC)




FIG. 4 COMPRESSIBILITY CURVES FOR ALUMINUM ALLOY SPHERE
 IN NORTH ATLANTIC OCEAN (EQUATOR TO GREENLAND) IN FATHOMS




FIG. 5 COMPRESSIBILITY CURVES FOR ALUMINUM ALLOY SPHERE
 IN NORTH ATLANTIC OCEAN (EQUATOR TO GREENLAND) IN FEET




FIG. 6 COMPRESSIBILITY CURVES FOR ALUMINUM ALLOY SPHERE
IN WORLD OCEAN (ATLANTIC, INDIAN, PACIFIC) IN FATHOMS

DISTRIBUTION

	Copies
Bureau of Naval Weapons, R-1 Washington 25, D. C.	2
Office of Naval Research Washington 25, D. C.	
National Oceanographic Data Center Washington 25, D. C. Attn: R. V. Ochinero Code 3710	
David Taylor Model Basin Carderock, Maryland Attn: R. M. Ralston Code 589B	2
Naval Air Development Center Johnsville, Pennsylvania Attn: A. Scarcelli	
Chief of Naval Operations Washington 25, D. C. Attn: New Developments & Op. Eval. Div.	
U. S. Navy Hydrographic Office Washington 25, D. C. Attn: Division of Oceanography	
Commanding Officer U. S. Naval Mine Defense Laboratory Panama City, Florida	
Commanding Officer and Director U. S. Navy Electronics Laboratory San Diego 52, California	
Director Naval Research Laboratory Washington 25, D. C. Attn: NRL Library	

DISTRIBUTION (cont.)

Copies

Project Officer
Laboratory of Oceanography
Woods Hole, Massachusetts

2

Director
Woods Hole Oceanographic Institution
Woods Hole, Massachusetts

Department of the Navy
Washington 25, D. C.
Attn: Undersea Warfare R&D Council

Bureau of Naval Weapons
Washington 25, D. C.
Attn: E. M. Coppola
Code R-25

Office of Naval Research
Washington 25, D. C.
Attn: D. Waldo Lyon

Arctic Research Laboratory
Point Barrow, Alaska
Attn: Max Brewer

University of Alaska
Geophysical Institute
College, Alaska
Attn: Dr. C. T. Elvey

Office of Naval Research
Washington 25, D. C.
Attn: Dr. M. E. Britton

Bureau of Naval Weapons
Washington 25, D. C.
Attn: RUME-2

Armed Services Technical Information Agency
Arlington Hall Station
Arlington 12, Virginia

10

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. 6p. charts. Task RUME 2E-000.

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water -
2. Density
3. Oceans -
4. Depth
5. Pressure
6. vessels -
7. Design
8. Title
9. I. Warren,
10. II. William F.
11. III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. 6p. charts. Task RUME 2E-000.

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water -
2. Density
3. Oceans -
4. Depth
5. Pressure
6. vessels -
7. Design
8. Title
9. I. Warren,
10. II. William F.
11. III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. 6p. charts. Task UNCLASSIFIED

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water -
2. Density
3. Oceans -
4. Depth
5. Pressure
6. vessels -
7. Design
8. Title
9. I. Warren,
10. II. William F.
11. III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. 6p. charts. Task RUME 2E-000.

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water -
2. Density
3. Oceans -
4. Depth
5. Pressure
6. vessels -
7. Design
8. Title
9. I. Warren,
10. II. William F.
11. III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. op. charts. Task ROME 2E-000.
UNCLASSIFIED

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water - Density
2. Oceans - Depth
3. Pressure vessels - Design
- I. Title
- II. Warren, William F.
- III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. op. charts. Task ROME 2E-000.
UNCLASSIFIED

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water - Density
2. Oceans - Depth
3. Pressure vessels - Design
- I. Title
- II. Warren, William F.
- III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. op. charts. Task ROME 2E-000.
UNCLASSIFIED

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water - Density
2. Oceans - Depth
3. Pressure vessels - Design
- I. Title
- II. Warren, William F.
- III. Project

Naval Ordnance Laboratory, White Oak, Md.
(NOL technical report 61-179)
SEAWATER DENSITY IN THE OCEAN AS A FUNCTION OF DEPTH, AND A METHOD FOR UTILIZING THIS INFORMATION IN DESIGN OF PRESSURE VESSELS WHICH WILL REMAIN IN A CONSTANT DEPTH RANGE BETWEEN THE SURFACE AND THE BOTTOM (U), by William F. Warren. 8 Dec. 1961. op. charts. Task ROME 2E-000.
UNCLASSIFIED

Curves of maximum and minimum seawater density are given for the North Atlantic and for the World Ocean (Atlantic, Indian, and Pacific). These curves show that a sub-surface free floating pressure vessel is possible for all depths below 300 fathoms. If a more limited area of the ocean is to be considered, then a minimum planting depth even less than that stated above should be possible, using the methods as described in this report.

1. Sea water - Density
2. Oceans - Depth
3. Pressure vessels - Design
- I. Title
- II. Warren, William F.
- III. Project