

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AD 274 274 L

*Reproduced
by the*

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOX

SEL-62-034

7
F 22722
274274

Time Variation of Optimum Azimuth for H-F Around-the-World Propagation

by
R. B. Fenwick and O. G. Villard, Jr.

March 1962

Technical Report No. 1004-2

Prepared under
Office of Naval Research Contract Nonr 225(24), NR 373 360
Jointly supported by the U.S. Army Signal Corps,
the U.S. Air Force, and the U.S. Navy
(Office of Naval Research)

RADIOSCIENCE LABORATORY
STANFORD ELECTRONICS LABORATORIES
STANFORD UNIVERSITY • STANFORD, CALIFORNIA



TIME VARIATION OF OPTIMUM AZIMUTH
FOR H-F AROUND-THE-WORLD PROPAGATION

by

R. B. Fenwick and O. G. Villard, Jr.

March 1962

Reproduction in whole or in part
is permitted for any purpose of
the United States Government.

Technical Report No. 1004-2

Prepared under

Office of Naval Research Contract Nonr 225(24), NR 373 360

Jointly supported by the U.S. Army Signal Corps,

the U S. Air Force, and the U S. Navy

(Office of Naval Research)

Radioscience Laboratory
Stanford Electronics Laboratories
Stanford University Stanford, California

ABSTRACT

If magnetic and auroral effects are neglected and the absorption of a radio wave in the lower ionosphere is assumed to be only a function of the sun's zenith angle, the attenuation due to absorption of a high-frequency signal propagated in a great circle around the world is a minimum when the signal path misses the subsolar point by the greatest possible margin. It follows that to a first order of approximation, and considering absorption loss only, the optimum azimuth of round-the-world (RTW) propagation from a specified point on the earth's surface would be expected to vary uniformly with time of day, always being normal to the direction from the transmitter to the subsolar point.

Measurements made at Stanford, California between August 1961 and January 1962 have confirmed that the optimum RTW azimuth is a function of time, and that this azimuth is closely approximated by the normal to the azimuth of the subsolar point vs time. Differences between the experimental and predicted curves are found to exist. In one example, it was possible to show that this was primarily due to lower F2-layer critical frequencies in the predicted azimuths, thus resulting in signal loss in the predicted directions due to penetration of the ionosphere. If this circumstance is taken into account, the average optimum azimuth of RTW propagation appears to be readily predictable for any point on the earth with good accuracy.

CONTENTS

	Page
I. Introduction and Theory	1
II. Experimental Results	6
III. Conclusion	14
References	15

TABLES

1. Predicted Control Point f F2 for December, RASSN 50, for Varying Azimuth from Stanford, California, 0800 PST.	10
2. Predicted Control Point f F2 for December, RASSN 50, for Varying Azimuth, 1600 PST.	10
3. Predicted f F2 at points 6000 km from Stanford, California, December at RASSN 50, for Varying Azimuth, 1600 PST.	12

ILLUSTRATIONS

1. Examples of Minimum-Absorption Great-Circle Paths Assuming That Absorption is a Function Only of Sun's Zenith Angle	2
2. Geometry Used in Determination of the Minimum-Absorption Great-Circle Path Through Point T	2
3. Theoretical Circular Approximations to Global Constant-Absorption Curves, Determining Minimum-Absorption Great-Circle Paths Through T (ATB), T_1 (AT_1B), and E (CED)	3
4. Predicted Variation of RTW-Signal Optimum Azimuth Vs Time for $37^{\circ}25'$ N, Based on Minimum Absorption.	5
5. Examples of A-Scope Displays Showing Variation of RTW-Signal Propagation Characteristics With Time.	7
6. Experimental Points and Predicted Curve for Optimum RTW Azimuth Vs Time at Stanford, California, January 1962, 15.1 Mc.	8
7. Predicted World-Wide f F2 for 0800 PST, December, RASSN 50, With Three Great-Circle Paths Through Stanford, California	9
8. Predicted World-Wide f F2 for 1600 PST, December, RASSN 50, With Two Great-Circle Paths Through Stanford, California	11

I. INTRODUCTION AND THEORY

It has long been known that the "optimum" direction for propagating round-the-world (RTW) high-frequency signals (i.e., the transmission azimuth resulting in greatest signal strength) varies with time of day and season [Ref. 1]. However, the precise explanation for this, and the detailed manner in which this azimuth varies with time, seems not to have been explored in detail. Measurements at Stanford, California, reported earlier [Ref. 2], showed that the normal diurnal variation was approximately the same as the variation of the azimuth of the "sun's wave fronts" at the point of observation. Later observation has corroborated this conclusion, and the way of specifying the azimuth has been made less awkward.

If the absorption due to the lower layers of the ionosphere is assumed to vary in a simple manner proportional to $(\cos \chi)^n$, where χ is the sun's zenith angle and n is determined from data [Ref. 3], and if magnetic-field effects are neglected, the attenuation due to absorption of a high-frequency signal propagated around the world is a minimum when the signal path "misses" the subsolar point by the greatest distance.

Let us say, for illustration, that the sun stands above the equator as shown in Fig. 1. There exists only one path which virtually avoids absorption, and that is the path on the twilight line which, in this instance, passes through the poles.

Consider transmitting from a point P somewhere on the sunlit hemisphere as shown in Fig. 1. Minimum absorption occurs when the RTW path transverses as little of the densely absorbing region as possible. This is satisfied when the ray path is at right angles to the direction from the transmitter to the subsolar point, as shown. Figure 1 shows qualitatively that this conclusion is reasonable. Paths through points P and Q with azimuths other than those shown will enter circular regions of higher absorption (nearer the subsolar point) and will accordingly suffer greater attenuation.

A proof of this assertion is as follows, referring to the coordinate system and designations in Figs. 2 and 3.




FIG. 1. EXAMPLES OF MINIMUM-ABSORPTION GREAT-CIRCLE PATHS ASSUMING THAT ABSORPTION IS A FUNCTION ONLY OF SUN'S ZENITH ANGLE.




FIG. 2. GEOMETRY USED IN DETERMINATION OF THE MINIMUM-ABSORPTION GREAT-CIRCLE PATH THROUGH POINT T.

$$\alpha = \alpha_0 \int_{\text{path}} \cos \chi \, ds \quad \cos \chi \geq 0$$

then

$$\alpha_{\text{ATB}} = 2\alpha_0 \int_0^{\pi/2} \cos \theta_1 \cos \theta_2 \, d\theta_2$$

$$\therefore \alpha_{\text{ATB}} = 2\alpha_0 \cos \theta_1 \quad (3)$$

Equation (3) shows that the total absorption of any path normal to line SS-N at T in Fig. 3 is proportional to $\cos \theta_1$, where θ_1 is the angle subtended at the center of the earth by SS and T. Hence, the absorption of path AT_1B is greater than the absorption of ATB.

Now consider a great-circle path CTD through T making some angle β with ATB. This path enters the circle $\cos \chi = c_1$ and is tangent to some other circle $\cos \chi = c_2$ at E. By symmetry, $\alpha_{\text{CED}} = \alpha_{\text{AT}_1\text{B}} > \alpha_{\text{ATB}}$ and the assertion is proved.

The azimuth normal to the direction of the subsolar point from a specified transmission point T is given by:

$$A = 90 - \cot^{-1} \left(\frac{\tan \delta \cos \varnothing}{\sin h} - \sin \varnothing \cot h \right) \quad (4)$$

where δ is the sun's declination

$\varnothing$ is the latitude of the point T

h is the sun's hour angle relative to the point T

This azimuth is plotted in Fig. 4 for $\delta = +23^\circ 26'$ and $\delta = 0^\circ$, for Stanford, California ($\varnothing = +37^\circ 25'$).

The curves of Fig. 4 would be expected to be an accurate estimate of the variation of optimum RTW-signal azimuth with local time provided that:

- (1) D- and E-layer absorption is important in RTW propagation, and
- (2) the azimuth of highest mean F2-layer critical frequency does not vary in a greatly different manner with time than does the minimum-absorption azimuth.




FIG. 4. PREDICTED VARIATION OF RTW-SIGNAL OPTIMUM AZIMUTH VS TIME FOR 37°25' N, BASED ON MINIMUM ABSORPTION.

In an earlier report [Ref. 2], evidence was presented which indicated that RTW propagation in sunlit portions of the earth not near the poles was principally via ionosphere-ground-ionosphere hop modes. Hence, lower-ionospheric-layer absorption should be very important in determining the optimum azimuth of transmission. Further, it was shown from world maps of f_oF_2 that the "twilight zone" azimuth should be preferred for RTW propagation since the minimum F2-layer critical frequencies on those paths were usually higher than the minimum F2-layer critical frequencies on other paths. (The twilight-zone azimuth for any point may be logically defined by Eq. (4)). However, it was also indicated that propagation in regions of minimum f_oF_2 was via ionosphere-ionosphere tilt modes. For this reason, determination of optimum RTW azimuth from maps of f_oF_2 becomes more difficult, since the degree of tilt of the F2 layer at any point in the world at a given time is not accurately known.


II. EXPERIMENTAL RESULTS

During the period 31 December 1961 to 8 January 1962 measurements of optimum RTW azimuth vs time of day were made at Stanford, California at 15.1 Mc. The period was quiet magnetically, and thus the results should be typical of normal conditions. In the experiment, 1-msec, 50-kw pulses were transmitted from a rotatable log-periodic antenna having a 3-db beamwidth of 64 deg. Receiving was performed by the same antenna. Hence, to the extent that the RTW propagation took place along great circles, the received RTW pulses were attenuated by the front-to-back ratio of the antenna (approximately 20 db).

Some of the records obtained on 31 December 1961 are shown in Fig. 5. The usual A-scope displays show log-detector output (35-pulse film integrations) vs time delay. Receiver bandwidth was 3 kc. Several interesting and characteristic features are apparent on these records. These include:

1. Optimum RTW azimuth varied from 270 deg to about 330 deg in the 5 hours shown.
2. The amplitude of the RTW signal increased as the time approached local sunset. (This is shown by the change of signal-to-noise ratio.)
3. The disappearance of the RTW signal was very rapid after sunset (compare 1736 PST records with 1810 PST records).
4. Disappearance of the RTW signal was accompanied by an increase in range and a decrease in amplitude of ground-backscatter in the optimum direction.
5. Since one major vertical division on the records represents about 10 db, the record of 1626 PST suggests that the azimuthal interval in which RTW propagation was possible had a width of approximately 26 deg, since the 6-db down points were nearly 90 deg apart, and the 6-db antenna beamwidth was 64 deg (assuming 64-deg, 3-db beamwidth transmitting, and 64-deg, 3-db beamwidth receiving from the back of the antenna).

The results of 6 days of such measurements (Fig. 5) are shown in Fig. 6. The broken line with a slope of 12 deg/hr appears to be a good estimate of the experimental data. The solid line is a theoretical curve obtained from Eq. (4). The theoretical curve is an excellent estimate of the experimental results during the morning hours, but becomes a poorer estimate in the afternoon (though still very good for many purposes).



15.1 Mc
31 December 1961
Stanford, California

FIG. 5. EXAMPLES OF A-SCOPE DISPLAYS SHOWING VARIATION OF RTW-SIGNAL PROPAGATION CHARACTERISTICS WITH TIME.




FIG. 6. EXPERIMENTAL POINTS AND PREDICTED CURVE FOR OPTIMUM RTW AZIMUTH VS TIME AT STANFORD, CALIFORNIA, JANUARY 1962, 15.1 Mc.

The National Bureau of Standards world maps of f_oF_2 [Ref. 4] provide an insight into the difference between the experimental and theoretical curves. Figure 7 shows the map for 0800 PST in December, RASSN 50 (Running Average Sunspot Number). At this time, the two curves of Fig. 6 give optimum azimuths of approximately 33 deg (± 180 deg). Figure 7 shows great circles for 30-, 37-, and 51-deg (± 180 deg) azimuths, all passing through the point $37^\circ 25' N$, $120^\circ W$. (Note that Stanford, California is actually at $123^\circ W$, but that the common point at $120^\circ W$ is marked "Stanford," for simplicity.) The calibration marks on the curve appear at 1000-km intervals.

It has been shown [Ref. 2] that the variation of round-the-world MUF in the several hours following sunrise correlates closely with the variation of f_oF_2 at the "control points," that is, the points 2000 km on either side of the observation point in the optimum azimuth. The control-point critical frequencies are listed in Table 1.




FIG. 7. PREDICTED WORLD-WIDE f_oF2 FOR 0800 PST, DECEMBER, RASSN 50, WITH THREE GREAT-CIRCLE PATHS THROUGH STANFORD, CALIFORNIA.

Table 1. Predicted Control Point f_oF_2 for December, RASSN 50, for Varying Azimuth from Stanford, California, 0800 PST.

Azimuth (deg)	NE Control Point f_oF_2 (Mc)	SW Control Point f_oF_2 (Mc)	Minimum Control Point f_oF_2 (Mc)
30	6.1	6.7	6.1
37	6.5	6.3	6.3
51	7.1	5.7	5.7

It is seen from Table 1 that the highest minimum-control-point f_oF_2 occurs for a transmission azimuth between 30 and 37 deg. This is the azimuth observed experimentally and predicted theoretically on the basis of minimum absorption.

The theoretical and experimentally observed values of optimum RTW azimuth at 1600 PST, from Fig. 6, are 321 deg and 307 deg, respectively. The world map of Fig. 8 shows predictions of world-wide f_oF_2 for 1600 PST (December, RASSN 50) and shows the great circles for 309-deg and 323-deg azimuths. Analogous to Table 1, Table 2 shows f_oF_2 at the control points on the paths.

Table 2. Predicted Control Point f_oF_2 for December, RASSN 50, for Varying Azimuth, 1600 PST.

Azimuth (deg)	NW Control Point f_oF_2 (Mc)	SE Control Point f_oF_2 (Mc)	Minimum Control Point f_oF_2 (Mc)
309	8.1	7.3	7.3
323	7.7	8.0	7.7

If the criteria used at 0800 PST are applied here, it appears that the 323-deg path has the higher MUF. However, note that if the "first hop" is constrained to be ground-ionosphere-ground, as appears to be the situation for such paths in daylight [Ref. 2], the f_oF_2 at other encounters with the ionosphere will determine the maximum RTW frequency and, consequently, the azimuth width which can propagate. In this instance, it




FIG. 8. PREDICTED WORLD-WIDE f_2 FOR 1600 PST, DECEMBER, RASSN 50, WITH TWO GREAT-CIRCLE PATHS THROUGH STANFORD, CALIFORNIA.

is interesting to compare the F2 critical frequencies 6000 km from Stanford. Table 3 shows the situation at these points.

Table 3. Predicted f_oF_2 at points 6000 km from Stanford, California, December at RASSN 50, for Varying Azimuth, 1600 FST.

Azimuth (deg)	f_oF_2 6000 km NW of Stanford (Mc)	f_oF_2 6000 km SE of Stanford (Mc)	Minimum f_oF_2 6000 km from Stanford (Mc)
309	8.2	10.0	8.2
323	6.5	10.0	6.5

Note that the minimum f_oF_2 6000 km from Stanford is much higher for the 309-deg azimuth (approximately the experimentally observed value) than for the 323-deg azimuth (predicted on the basis of absorption). Further, note that the 323-deg path lies much nearer to the pre-dawn region of minimum f_oF_2 and that the 309-deg path encounters much greater gradients of f_oF_2 . The 309-deg path f_oF_2 decreases from 8 to 6 Mc in 2500 km in the region of maximum gradient while the 323-deg path gradients are primarily transverse, with the maximum longitudinal gradient being about 2 Mc in 6000 km.

Since the magnitude of the longitudinal f_oF_2 gradient is a first-order indication of the ionospheric tilt present which can enable "tilt modes" to be launched, higher frequencies can be propagated through the region of greatest longitudinal f_oF_2 gradient, for a given regional f_oF_2 . Also, in such regions, modes may propagate with a greater range of vertical angles of incidence on the layer without the layer being penetrated. If the great-circle path having minimum absorption will not support propagation at a given frequency due to MUF failure, but some other path has sufficient F2-layer critical frequencies (or greater longitudinal-layer tilts), clearly the "optimum" transmission azimuth for a given frequency cannot correspond to the minimum-absorption path.

Hence, it is concluded that the path lying closer to the East-West great circle in Fig. 8 is preferred from a critical-frequency standpoint,

and that the added energy that can propagate due to the presence of parallel ray paths (and possibly paths corresponding to different vertical takeoff angles) more than compensates for the increased absorption as the ray paths approach 270 deg.

Note that it is further suggested from Fig. 8 that the optimum azimuth will be a function of frequency, becoming slightly nearer to 270 deg as frequency is increased (up to the point of MUF failure at the 2000-km point SE of Stanford). It has not been attempted experimentally to verify this hypothesis, but such an effect has been qualitatively observed earlier [Ref. 2].

III. CONCLUSION

It has been predicted theoretically and verified experimentally that the optimum azimuth of RTW propagation is a function of time of day, and it has been shown experimentally at Stanford University for the winter solstice, 1961-62, that this azimuth agrees quite closely with the azimuth normal to the direction from Stanford to the subsolar point. It is concluded that it ought to be possible to predict the average optimum azimuth of RTW propagation quite closely, possibly to better than 10 deg, for any point on the earth at any frequency by use of the equation:

$$A = 90 - \cot^{-1} \left(\frac{\tan \delta \cos \phi}{\sin h} - \sin \phi \cot h \right)$$

and making a correction dependent on frequency derived from consideration of world maps of $f_o F_2$.

REFERENCES

1. Hess, H. A., "Investigations of High-Frequency Echoes," Proc. IRE, 36, 1948, pp. 981-992.
2. Fenwick, R. B., "Measurements of Around-The-World High Frequency Propagation," Stanford Electronics Laboratories, Stanford, California, Rept. SEL-62-011, January 1962.
3. National Bureau of Standards, "Ionospheric Radio Propagation," Natl. Bur. Stds. Circular 462, 25 July 1948.
4. National Bureau of Standards, "World Maps of F2 Critical Frequencies and Maximum Usable Frequency Factors," Natl. Bur. Stds. Tech. Note 2, April 1959.

BASIC DISTRIBUTION LIST

December 1961

Evans Signal Laboratory Belmar, New Jersey 1 Attn: Head, Solid-State Dev. Br. Dr. H. Jacobs Commanding General, USASRD Ft. Monmouth, New Jersey 1 Attn: SIGRA/SL-SC Chief, West Coast Office Pasadena 2, California Commanding Officer, Frankford Philadelphia, Pa. Ballistics Research Laboratory Aberdeen Proving Grd., Md. 2 Attn: L.A. DeLasso Commanding General Ft. Huachuca, Arizona 1 Attn: Technical Library Chief of Naval Research Washington 25, D.C. 2 Attn: Code 427 1 Attn: Code 463 Commanding Officer, ONR Br. Off San Francisco 9, California Chief Scientist, ONR BR. Office Pasadena, California Comm. Officer, ONR Br. Office Chicago 1, Illinois Comm. Officer, ONR Br. Office New York 13, New York Officer-in-Charge, ONR 15 New York, New York Director, NR Laboratory Washington 25, D.C. 1 Attn: Code 5240 1 Attn: Code 7100 1 Attn: Code 5430 1 Attn: Code 5200 1 Attn: Code 5300 1 Attn: Code 5400 1 Attn: Code 5270 1 Attn: Code 5210 GA Chief, Bureau of Ships Washington 25, D.C. 3 Attn: Code 810 1 Attn: Code 816 1 Attn: Code 820 1 Attn: Code 840 Chief, Bureau of Aeronautics Washington 25, D.C. 1 Attn: Code RAAV-33 Chief, Bureau of Naval Weapons Washington 25, D.C. 1 Attn: RREN 1 Attn: RAAV-44 Chief of Naval Operations Washington 25, D.C. 1 Attn: Code Op-94T Comm. Officer and Director San Diego 52, California U.S. Naval Post Graduate Sch. Monterey, California 1 Attn: Tech. Rpts. Librarian Commander, U.S.N. Missile Ctr. Pt. Mugu, California 1 Attn: 5321 U.S. Naval Weapons Lab. Dahlgren, Virginia 1 Attn: Tech. Library Naval Ordnance Laboratory Corona, California 1 Attn: Library	Director, NOL 1 White Oak, Maryland Commander, NADC Johnsville, Pa. 1 Attn: NADC Library Dept. of the Army Washington 25, D.C. 1 Attn: Research Support Div. Chief, P&O Division Washington 25, D.C. 1 Attn: SIGOP-5 Office of the Chief of Engr. Washington 25, D.C. Hqs., USAF (AFPRD-NU-3) Pentagon, Washington 25, D.C. 1 Attn: Mr. Harry Mulkey Chief of Staff, USAF Washington 25, D.C. 2 Attn: AFPRD-ER Commanding Officer Aeronautical Systems Division Wright-Patterson AFB, Ohio 1 Attn: ASRNEB 1 Attn: ASRNR3-2 Executive Director AF Office of Scientific Res. Washington 25, D.C. 1 Attn: Code SRYA AF Special Weapons Ctr. Kirtland AFB, New Mexico 2 Attn: SWOI Director, AUL Maxwell AFB, Alabama 1 Attn: CR 4582 Commander Patriot AFB, Florida 1 Attn: AFMTC Tech. Lib., MU-135 Commanding General Home, New York 2 Attn: RCRW Commanding General Bedford, Massachusetts 1 Attn: CRTOTT-2, Electronics AF Office of Scientific Res. Washington 25, D.C. 1 Attn: Tech. Library AF Systems Command Washington 25, D.C. 1 Attn: RDRLT, Capt. Zimmerman 1 Attn: RDRESE-Mr. Fresnell Hqs. ARDC Washington 25, D.C. 1 Attn: RDRE 1 Attn: RDRC Assistant Sec. of Defense Washington 25, D.C. 1 Attn: Tech. Library Director of Defense Washington 25, D.C. U.S. Coast Guard Washington 25, D.C. 1 Attn: EEE Dept. of Defense Washington 25, D.C. 1 Attn: Code 711, Fred Miller Advisory Grp on Electron Tubes New York 13, New York Adv. Grp on Reliability of Elec. Equipment 1 Washington 25, D.C.	Commanding Officer Diamond Ordnance Fuse Labs. Washington 25, D.C. 2 Attn: ORDTL 430, Dr. R. Young U.S. Dept. of Commerce 1 Boulder, Colorado 2 Attn: Miss V. Lincoln Director, Nat. Security Agency Ft. George G. Meade, Md. 1 Attn: REMP-2 California Inst. of Tech. Pasadena, California 1 Attn: Prof. L.M. Field California Inst. of Tech Jet Propulsion Laboratory Pasadena, California 1 Attn: Documents Library University of California Berkeley 4, California 1 Attn: Prof. R.M. Saunders, CHM U. Of California, Radiation L. Berkeley, California 1 Attn: Dr. R. K. Wakerling Univ. of California Los Angeles 24, California 1 Attn: C.T. Leondes Georgia Institute of Tech. Atlanta, Georgia 1 Attn: Mrs. J.H. Crosland, Lib. Harvard University Cambridge 38, Massachusetts 1 Attn: Mrs. E. Parkas, Lib. Illinois Inst. of Tech. Chicago 16, Illinois 1 Attn: Dr. Paul C. Yuen 1 Attn: Dr. George I. Cohn University of Illinois Urbana, Illinois 1 Attn: Prof. D. Alpert 1 Attn: Paul Coleman, EE Dept. 1 Attn: Library Serials Dept. Johns Hopkins University Baltimore 2, Maryland 1 Attn: Librarian Johns Hopkins University Silver Spring, Maryland 1 Attn: Document Library Mass. Inst. of Technology Cambridge 39, Mass. 1 Attn: Research Lab. of Elec. Mass. Inst. of Tech. Lincoln Lab 1 Lexington 73, Mass. Director, Cooley Elecs. Lab. 1 Ann Arbor, Mich. Univ. of Michigan Ann Arbor, Michigan 1 Attn: Tech. Documents Serv. University of New Mexico Albuquerque, New Mexico 1 Attn: R.K. Moore, Chm., Univ. of Nevada Reno, Nevada 1 Attn: Dr. Robt. Manhart Northwestern University Evanston, Illinois 1 Attn: Walter S. Toth Ohio State University Columbus 10, Ohio 1 Attn: Prof. E.M. Boone
---	--	--

TEPEE DISTRIBUTION LIST
March 1962

Headquarters, Foreign Technology Div., Wright-Patterson AFB, Ohio	1
Attn: ID-A3a	1
Attn: ID-E1B	1
Attn: TD-X1A	1
Headquarters, AF Cambridge Research Labs., Office of Aerospace Research, USAF, L.G. Hanscom Field, Bedford, Mass.	
Attn: ERD-CRRK Dr. Philip Newman	1
Attn: ERD-CRRI Mr. Wm. F. Ring	1
Attn: Dr. G.J. Gassman	1
Hq., USAF, Office of Assistant Chf. of Staff Intelligence Systems Branch (AFCIN-P2), Washington 25, D.C.	1
Hq., US Air Force, (AFTAC/TD-5), Washington 25, D.C.	1
Headquarters, North American Air Defense Command, Ent Air Force Base, Colorado Springs, Colorado	
Attn: NEEC	1
Headquarters, Space Systems Division, Air Force Systems Command, USAF, Air Force Unit Post Office, Los Angeles 45, California	
Attn: SSZC	1
Hq., Rome Air Development Center, AF Systems Command USAF, Griffiss Air Force Base, New York	
Attn: RALTT-Mr. F.C. Bradley	1
Attn: RAUEL-3-Mr. B. Cooper	1
Hq., Strategic Air Command, Offutt Air Force Base, Nebraska	
Attn: DOCE	1
Commanding Officer, U.S. Army Signal Radio Propagation Agency, Ft. Monmouth, New Jersey	
Attn: SIGRP-B	1
Commanding Officer, U.S. Army Signal Missile Support Agency, White Sands Missile Range, New Mexico	
Attn: SIGWS-PO	1
Office of the Chief of Ordnance, Dept. of the Army Washington 25, D.C.	
Attn: ORDTU-Dr. C.M. Hudson	1

Oregon State College
Corvallis, Oregon
1 Attn: H.J. Oorthuys

Purdue University
Lafayette, Indiana
1 Attn: Library

University of Rochester
Rochester 20, New York
1 Attn: Dr. Gerald H. Cohen

Stanford Research Institute
Menlo Park, California
1 Attn: Documents Center

Villanova University
Villanova, Pa.
1 Attn: Thomas C. Gabriele

Yale University
New Haven, Connecticut
1 Sloane Physics Laboratory
1 Dept. of Elec. Engr.
1 Dunham Laboratory, Engr. Lib.

University of Puerto Rico
Mayaguez, Puerto Rico
1 Attn: Dr. Braulio Dueno

University of Saskatchewan
Saskatoon, Canada
1 Attn: Prof. N.F. Moody

Uppsala University
Uppsala, Sweden
1 Attn: Dr. P.A. Tove

Admiral Corporation
Chicago 47, Illinois
1 Attn: N. Robertson, Lib.

Airborne Instruments Lab.
Deer Pk, L.I., New York
1 Attn: J. Dyer, VP

Bell Telephone Labs.
Murray Hill, New Jersey
1 Attn: Elecs. Res. Dept.

Bomac Laboratories
Beverly, Mass.
1 Attn: Wellesley J. Dodds

Columbia Radiation Lab.
New York 27, New York
1

Cook Research Labs.
Morton Grove, Illinois
1

Cornell Aeronautical Labs., Inc.
Buffalo 21, New York
1

General Electric TWT Product
Section
Palo Alto, California
1 Attn: Technical Library

General Electric Company
Auburn, New York
1 Attn: Mr. Gerald C. Huth

General Electric Company
Schenectady, New York
1 Attn: G.E. Felker
1 Attn: E.D. McArthur

Gilfillan Brothers
Los Angeles, California
1 Attn: Engineering Library

Hughes Aircraft Company
Culver City, California
1

Huggins Laboratories
Sunnyvale, California
1

ITT Federal Laboratories
Nutley 10, New Jersey
1 Attn: A.W. McEwan

LEL, Inc.
Copiague, L.I., New York
1 Attn: Mr. Robt. S. Mautner

Lockheed Aircraft Corporation
Sunnyvale, California
1 Attn: G.W. Price, Subsystem F
1 Attn: Dr. Harris, Mgr.

The Maxson Elecs. Corporation
New York 1, New York
1 Attn: M. Simpson

MITRE Corporation
Bedford, Mass.
1 Attn: Constance Willis, Lib.

Monsanto Corporation
St. Louis 66, Missouri
1 Attn: E. Orban, Inorganic
Development

National Company, Inc.
Malden 48, Mass.
1 Attn: Technical Librarian

Nortronics Tech. Info. Agency
Hawthorne, California
1

Polarad Corporation
Long Island City 1, New York
1 Attn: A.H. Sonneschein
Chief Systems Engr.

RCA Laboratories
Princeton, New Jersey
1 Attn: Dr. W.M. Webster
1 Attn: Harwick Johnson

Ramo-Wooldridge Corporation
Los Angeles 45, California
1 Attn: Dorothy K. Goss, Lib.

The Rand Corporation
Santa Monica, California
1 Attn: Margaret Anderson, Lib.

Raytheon Company
Burlington, Massachusetts
1 Attn: Librarian

Raytheon Manufacturing Co.
Waltham, Massachusetts
1 Attn: Librarian

Roger White Electron Devices
Haskell, New Jersey
1

STL Technical Library
Space Tech. Labs. Inc.
1 Los Angeles 45, California

Sperry Rand Corporation
Gainesville, Florida
1

Commanding Officer
Mountain View, California
1

Technical Research Group
Syosset, L.I., New York
1

Texas Instruments Inc.
Dallas, Texas
1 Attn: Dr. W. Adcock
1 Attn: M.E. Chun

Varian Associates
Palo Alto, California
1 Attn: Technical Library

Westinghouse Electric Corp.
Baltimore 3, Maryland
1 Attn: G. Ross Kilgore, Mgr.
Applied Res. Dept.
Baltimore Laboratory

TEPEE DISTRIBUTION LIST

Systems Branch, US Army Scientific Liaison And Advisory Group, Apex Station, Washington 4, D.C. Attn: Mr. Richard A. Krueger	2
• Chief, U.S. Army Security Agency, Arlington Hall Station Arlington 12, Virginia Attn: LADEV-S	1
Commanding Officer, U.S. Army Signal Electronic Research Unit, P.O. Box 205, Mt. View, Calif.	1
Commanding Officer, Picatinny Arsenal, Dover, New Jersey Attn: Technical Information Library	1
Diamond Ordnance Fuze Laboratories, Ordnance Corps, Washington 25, D.C. Attn: Walter J. Brinks (Mathematician CCM & Special Systems Branch)	1
Commanding Officer, Army Rocket & Guided Missile Agency, U.S. Army Ordnance Missile Command, Redstone Arsenal, Alabama Attn: Dr. Nils L. Muench	1
Commanding General, US Army Signal Research & Development Laboratory, Ft. Monmouth, New Jersey Attn: Mr. Murray Miller	1
Chief of Naval Operation, Dept. of the Navy, Washington 25, D.C. Attn: Op-70	1
Attn: Op-92	1
Attn: Op-92B3	1
Attn: Op-71	1
Attn: Op-733	1
Attn: Op-07TE	1
Chief, Bureau of Ships, Dept. of the Navy, Washington 25, D.C. Attn: Code 362A	1
Director, Special Projects, Dept. of the Navy Washington 25, D.C. Attn: SP-2041	1
Commanding Officer, U.S. Naval Ordnance Test Unit Patrick Air Force Base, Florida Attn: N3	1

TEPEE DISTRIBUTION LIST

Commander, U.S. Naval Missile Center, Pt. Mugu, California Attn: Technical Library, Code NO302.1	1
Commander, Naval Air Test Center, Patuxent River, Md. Attn: Weapons Systems Test Division (Code 424)	1
*Director, U.S. Naval Research Laboratory, Washington 25, D.C. Attn: Code 5320 Attn: Code 2027	1 1
Commanding Officer & Director, U.S. Navy Electronics Laboratory, San Diego 52, California Attn: Library	1
Chief of Naval Research, Dept. of the Navy, Washington 25, D.C. Attn: Code 427 Attn: Code 463 Attn: Code 420C Attn: Code 418	1 1 1 5
Commanding Officer, U.S. Naval Ordnance Laboratory, Corona, California Attn: Mr. V.E. Hildebrand	1
Chief, Bureau of Naval Weapons, Dept. of the Navy Washington 25, D.C.	1
*Armed Services Technical Information Agency, Arlington Hall Station, Arlington 12, Virginia	10
Director, Weapons Systems Evaluation Group, Rm. 1E875, The Pentagon, Washington 25, D.C.	1
Institute for Defense Analyses, Washington 6, D.C. Attn: RESD-Dr. Paul Von Handel	1
Director, Advanced Research Projects Agency, Washington 25, D.C. Attn: LCDR D. Chandler Attn: Mr. J. Ruina Attn: Dr. Cabell A. Pearse Attn: Mr. A. Van Every	1 1 1 1

*All requests for this report shall be approved by the
Office of Naval Research (Code 418), OXford 6-4476.

TEPER DISTRIBUTION LIST

Director, National Security Agency, Ft. G.G. Meade, Md.
Attn: CREF-141

1

Director, National Bureau of Standards, Boulder, Colo.
Attn: Mr. Richard C. Kirby (Chf, Radio Systems Div)
Attn: Mr. L.H. Tveten (HF/VHF Research Section)

1

1

ACF Electronics Division, ACF Industries, Inc. 3355
52nd Avenue, Hyattsville, Md.

Attn: Mr. Wm. T. Whelan (T&D)

1

**Inspector of Naval Material, 401 Water St.
Baltimore 2, Md.

Aero Geo Astro Corp., 1200 Duke St. Box 1082, Alexandria,
Virginia

Attn: Mr. D. Reiser

1

**Inspector of Naval Material, 401 Water St.
Baltimore 2, Md.

Aero Geo Astro Corp., 13624 Magnolia Ave.
Corona, Calif.

Attn: Mr. A. Walters

1

**Inspector of Naval Material, 401 Water St.
Baltimore 2, Md.

Radio Corporation of America, Aerospace Communications
and Control Division, Burlington, Mass.

Attn: Mr. J. Rubinovitz

1

**Inspector of Naval Material, 495 Summer St.
Boston 10, Mass.

Stanford Research Institute, Communications & Prop.
Laboratory, Menlo Park, Calif.

Attn: Mr. R.L. Leadabrand

1

Attn: Mr. D. Neilson (Data Center)

1

Attn: Mr. R. Vincent

1

**Commanding Officer, Office of Naval Research
Branch Office, 1000 Geary St., San
Francisco, Calif.

The University of Michigan, Radiation Laboratory,
201 Catherine St., Ann Arbor, Mich.

Attn: Dr. R.J. Leite

1

**Office of Naval Research, Resident Repr.
Univ. of Mich., 820 E. Washington St.
Ann Arbor, Mich.

**When the document is classified, send a copy of the
receipt form to this addressee.

TEPEE DISTRIBUTION LIST

Ballistic Missile Radiation Analysis Center, Institute
of Science & Technology, The University of Michigan
P.O. Box 618, Ann Arbor, Mich.

Attn: R. Jamron

**Office of Naval Research, Resident Repr.
Univ. of Mich., 820 E. Washington St.
Ann Arbor, Mich.

1

Raytheon Company, Communications & Data Processing Ops.
1415 Boston-Providence Turnpike, Norwood, Mass.

Attn: L.C. Edwards

**Resident Naval Inspector of Material
Raytheon Manufacturing Co., Waltham, Mass.

1

Mass. Institute of Technology, Radio Physics Division
Lincoln Laboratory, P.O. Box 73, Lexington 73, Mass.

Attn: Dr. John V. Harrington

Attn: Mr. Melvin L. Stone (Radio Propagation Group)

Attn: Mr. James H. Chisholm (Radio Propagation Group)

**Inspector of Naval Material, 495 Summer St.
Boston 10, Mass.

1

Westinghouse Electric Corporation, Air Arm Division
Engineering Library, P.O. Box 746, Baltimore 3, Md.

Attn: Mr. David Fales

**Inspector of Naval Material, 401 Water St.
Baltimore 2, Md.

1

Georgia Institute of Technology, 722 Cherry St., N.W.
Atlanta 13, Georgia

Attn: Mr. Wrigley

**Contract Administrator Southeastern Area
Office of Naval Research, 2110 G. St., N.W.
Washington 7, D.C.

1

Rand Corporation, 1700 Main St., Santa Monica, Calif.

Attn: Dr. Cullen M. Crain

**Inspector of Naval Material, 929 S. Broadway
Los Angeles 15, Calif.

1

Pickard & Burns, Inc., 103 Fourth Ave., Waltham 54, Mass.
(Subsidiary of Gorham Corp.)

Attn: Dr. J. Williams

**Inspector of Naval Material, 495 Summer St.
Boston 10, Mass.

University of California, Berkeley 4, Calif.

Attn: Dr. E. Pinney

**Office of Naval Research Br. Office, 1000 Geary
St., San Francisco 9, Calif.

1

**When document is classified, send a copy of the receipt
form to this addressee.

TEPEE DISTRIBUTION LIST

General Electric Corp., Court St., Syracuse, New York
Attn: Dr. G.H. Millman

1

Battelle Memorial Institute
505 King Ave.
Columbus 1, Ohio
Attn: BMI-Defender

1