

UNCLASSIFIED

AD 275 087

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

275087

275 087

762-3-3

TECHNICAL REPORT FRL-TR-57

METHOD FOR OBTAINING PRECISE VELOCITIES
OF RAPIDLY MOVING FRAGMENTS

FRANK R. SCHWARTZ

APRIL 1962




FELTMAN RESEARCH LABORATORIES
PICATINNY ARSENAL
DOVER, N. J.

OMS CODE: 5010.11.818.X01

DEPT. OF THE ARMY PROJECT: 503-05-021

COPY

25



**METHOD FOR OBTAINING PRECISE VELOCITIES
OF RAPIDLY MOVING FRAGMENTS**

by

Frank R. Schwartz

April 1962


**Feltman Research Laboratories
Picatinny Arsenal
Dover, N. J.**

Technical Report FRL-TR-57

OMS 5010.11.818.X01

Dept of Army Project 503-05-021

Approved:



**L. H. ERIKSEN
Chief, Explosives and
Propellants Laboratory**

TABLE OF CONTENTS

	Page
Abstract	1
Conclusion	1
Introduction	1
Discussion	2
Experimental Procedure	4
Reference	5
Distribution List	10
Figures	
1 Exploded view of charge assembly	6
2 Mounted charge assembly	7
3 Test setup showing relative arrangement of charge assembly and scale	7
4 Firing record of single frame with single sweep	8
5 Firing record showing three pellets fired simultaneously using the rewriting technique	8
6 Block diagram showing a typical arrangement of components used in rewriting technique	9

ABSTRACT

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by rewinding affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

CONCLUSION

The technique described herein is of value in the precise determination of the velocities of fragments whose geometry is known or whose center of mass can be estimated. This method is appropriate for the study of luminous (hypervelocity) or nonluminous fragments whose trajectories can be predicted. The time resolution of the framing camera at its highest operating speed is 0.02%.

INTRODUCTION

The simplest procedure for determining the velocity of a projectile in flight by photographic means is to use a single exposure camera and obtain some form of multiple exposure of the event against a calibrated scale. This can be accomplished by using successive flashes from a high-intensity light source.

Further refinements of this technique make use of multiple flashes and associated optics to give separate time-displaced frames of the event. Electro-optical shutters can be used in a similar manner, the shutter being pulsed instead of the light source to give the same results. In all the above methods, the accuracy with which the average velocity during the recording interval can be determined depends upon the least precise determination of either position or time. Moreover, even with successive high-intensity flashes of short duration, and with precise interval timers or time delay generators, it is difficult to obtain time resolutions of the order of a microsecond. However, if the distances of travel and the times involved are long, determinations of the average velocities of projectiles in flight can be made with a high relative accuracy.

Ordinarily the study of large masses in flight can be readily accomplished by well-established techniques for ballistic study. As the size of the projectile is reduced and the velocity increased, the standard techniques can still be used, but only at the expense of some loss in accuracy. If, in addition, account must

be taken of some randomness in flight, this poses an added restriction as to the type and position of the sensing or recording elements. The sensing grids or coils used in exterior ballistic study are usually relatively massive elements which must be spaced far apart to reduce the inherent error of these devices.

During an investigation into the relative energies of explosives and their ability to accelerate metal fragments, the need arose for a precise method of obtaining plate velocities. The high-speed rotating-mirror framing camera is an excellent tool for the study of high speed phenomena and has been used for determining the velocity of fragments. However, it was decided that this instrument would yield more precise data if it was operated in a slightly modified way. Accordingly, the system described in this report was developed and is being used.

DISCUSSION

The camera used for this study was the Beckman Whitley Model No. 189 camera, which is the commercial model of the Bowen RC-4 type rotating-mirror framing camera. The optical system of this camera consists of an objective lens, a field lens, and a rotating mirror which is driven by an air turbine at speeds up to 5000 rps. The event which is imaged on the rotating mirror is swept by the mirror through 25 complete sets of relay lenses and imaged as 25 separate frames on a strip of 35 mm film positioned at the periphery of a circle with the axis of the mirror at its center.

The objective lens supplied with this camera is a simple air-spaced achromat with a focal length of 24 inches. The camera has a minimum focusing distance of 8 feet and an effective aperture of f14. Because of the space limitations of the firing chamber, the maximum distance of the camera from the event was 14 feet; at this distance, the field covered by the camera was approximately 6 inches in the direction of flight. To improve the versatility of the camera, the optical system was modified to accommodate lenses of different focal lengths. The objective lens was replaced by a relay lens system consisting of a 24½-inch cemented achromat and a 7-inch f2.5 Aero-Ektar lens barrel-mounted in the camera objective housing with the longer focal length lens closest to the rotating mirror. This arrangement was such that any real image formed at the focus of the 7-inch lens was relayed onto the film plane. Thus a single lens mount with adaptors for lenses of various focal lengths could be used to form the aerial image for the above assembly. The present study was made using a 3-inch f2.3 Balter lens, the effective aperture of the system being f16. At 14 feet from the camera, the present optical system covers approximately 15 inches of target area.

Ordinarily, in photographing an event, the framing camera gives a burst of 25 frames whose total framing time covers 20 microseconds at 5000 rps with approximately 0.3 microsecond exposure per frame. For pellets in flight this 0.3 microsecond represents also the space-time movement of the pellet in flight, which can be assumed to be the same

from frame to frame. However, the time between frames is not uniform throughout the film and thus a correction factor must be applied which depends on the geometry of the individual camera. This correction factor must be applied if some degree of precision is to be obtained.

For objects moving at high velocity, wherein the displacement is known to be 0.1% or better, the calibrated camera method could be used to obtain velocities with a maximum accuracy of 0.1%.

In the present study, it was found that, when the framing camera is used in an intentional rewriting manner, the movement of the event over long distances and through a time element of at least 200 microseconds gives multiple records of high accuracy which can be checked from frame to frame, the space movement of the object on each frame being identical (assuming uniform velocity).

The manner in which the rewrite technique can be used to give accuracies to 0.1% or better can readily be understood from the following considerations: For objects moving at moderate speeds up to about 3.0 mm/microsecond (the upper limit is purely arbitrary since it represents the framing rate of the camera and its associated lens system), the distance through which the object could travel up to the end of the first recording period can be considered its flight distance prior to recording plus the distance travelled in 20 microseconds (the framing rate of the camera at 5000 rps with the object travelling at the above upper limit). By re-recording the event 200

microseconds later when the event is that much further along the range, a series of pictures is obtained, each frame representing a complete record. The position measurements then determine the accuracy of the velocity determination up to 0.02% (the accuracy with which the elapsed time is measured). Thus a series of 25 individual records can be obtained, giving additional checks on this determination. When this technique is used, no correction is needed for elapsed time since each frame represents a space movement during one complete mirror revolution, which can be monitored to plus or minus one revolution at 5000 rps. The space smear incurred by movement of the object during framing is approximately 0.3 microsecond in duration.

At a distance of 15 feet from the camera, parallax is significant and must be corrected for in making any precise determination. On the assumption that the true distance of the fragment from the scale is precisely $1\frac{1}{2}$ inches, the error due to parallax in the reduction of the record would be approximately 0.8%. The simplest method of correcting for parallax is to use the shadow cast by the fragment. If the light source is placed at a known angle to the target, the distance of the shadow from the pellet can be used to determine the distance of the pellet from the scale. Position can be determined to an accuracy of better than 0.02%.

If the path of the trajectory is precisely known, however, the experiment may be modified so that no correction for parallax

is required. In this case, the calibrated scale is placed precisely in the plane of the trajectory and illuminated by a conventional nondestructive high intensity light source. With the camera operating at moderate speeds, a series of still pictures of the scale is photographed over the 25 frames. Thereafter, the scale is removed and a diffusion screen backlighted by an argon flash bomb is set up at a convenient distance behind this plane. The event is then fired as previously described using the rewriting technique. The record thus obtained will have the projectile and scale in the same frame of reference.

Moreover, since there are 25 frames, each frame being a complete record, there will be 25 individual determinations of the average velocity over the distance of travel. In addition, if one handles the records obtained as one would in normal operation without rewriting, the initial 20 microseconds can be used to determine an initial velocity for the first framing interval and a similar velocity determination can be made for the second or rewriting period. The initial and final velocities of the pellets in flight can then be ascertained to an accuracy of 0.1%. This technique can be used to give data concerning angle of flight as well as drag.

It has been stated that the framing camera cannot be used in the study of hypervelocity fragments travelling at high speeds (about 16 mm/microsecond), since the fragments would pass across the normal field of view (12 inches) in

20 microseconds. This field of view does not, however, impose an upper limit for any particular event, since by the use of mirrors two separate portions of the scale can be viewed on a single frame, the frame being split either vertically or horizontally. This would give either two half views of the scale spaced approximately 12 feet apart or two full views of the scales placed one above the other on each frame in a manner similar to the rangefinder principle. The supposition here is that the event can be bracketed by synchronization.

EXPERIMENTAL PROCEDURE

The charge assemblies used in this study were set up in accordance with the procedure used by G. D. Dorough, et al (Ref 1). They consisted of cylindrical charges of high explosive 0.340 inch in diameter and 1.400 inches long, cased in steel cylinders 1.000 inch in diameter and 2.000 inches long with a 0.340-inch central perforation. The projectiles were steel disks 0.340 inch in diameter varying in length from 0.0625 to 0.250 inch (Fig 1, p 6). All the components were cemented into the casing with a minimum of glue to assure good contact between components (Fig 2, p 7). Initiation was by an electric PETN detonator with a tetryl booster, the high explosive under study being adjacent to the steel pellet, whose exposed surface was flush with the base of the case.

The charge assembly was positioned approximately fifteen feet from camera and in a plane normal to its optical

axis. The target (scale) and charge assembly were set normal to the axis of the camera by optical means. The assembly was placed so that the projectile in flight would pass approximately $1\frac{1}{2}$ inches in front of the assessment scale. From the measured framing rate together with the geometry of the camera, the elapsed time between frames was determined to 0.1%. Before firing, the assembled charge was arranged as in Figure 3 (p 7), the field of view of the camera being 14 inches.

Figure 6 (p 8) shows schematically the arrangement of the camera and the argon flash bombs as well as the associated firing circuitry. The pulse from the camera is delayed by the first time delay generator so that the total time for the firing of the event and the movement of the pellet into the field of view of the camera should occur during the framing interval of the camera. In like manner, the second time delay generator delays

its pulse to permit the argon flash to reach maximum intensity simultaneously with the above. A third time delay generator is used to fire a second argon light source after the rotating mirror has completed one revolution.

For comparative purposes, Figure 4 (p 8) shows the pellet in flight followed by the shadow cast by the argon flash. In like manner, Figure 5 (p 9) shows three pellets fired simultaneously and recorded by the rewriting technique. The spots closest to the center of the record are the shadows cast by the pellets.

REFERENCE

1. G. D. Dorough, H. C. Hornig, J. W. Kury, D. C. Oakley, "The Role of Density and Energy in Plate Acceleration," University of California Radiation Laboratory Report No. 4854 (Secret-Restricted Data)




Fig 1 Exploded view of charge assembly.




Fig 2 Mounted charge assembly




Fig 3 Test setup showing relative arrangement of charge assembly and scale




Fig 4 Firing record of single frame with single sweep




Fig 5 Firing record showing three pellets fired simultaneously using the rewriting technique




Fig 6 Block diagram showing a typical arrangement of components used in rewriting technique

DISTRIBUTION LIST

	Copy No.
Commanding Officer Picatinny Arsenal ATTN: Technical Information Section Dover, N. J.	1 - 5
Scientific Information Section Research Branch Research and Development Division Office, Assistant Chief of Staff, G-4 Department of the Army Washington 25, D. C.	6
Office of the Chief of Ordnance Department of the Army ATTN: ORDTB Washington 25, D. C.	7
Commanding General OSWAC ATTN: ORDSW-A	8
ORDSW-W Picatinny Arsenal Dover, N. J.	9
Commanding General Aberdeen Proving Ground ATTN: Dr. R. Eichelberger - BRL Maryland	10
Commanding Officer Watertown Arsenal ATTN: Watertown Arsenal Laboratories	11
Dr. E. W. Ross, Jr. Watertown 72, Massachusetts	12

	Copy No.
Commanding Officer Diamond Ordnance Fuze Laboratories ATTN: ORDTL-012 Connecticut Ave and Van Ness Street, NW Washington 25, D. C.	13
Director Ordnance Materials Research Office Watertown Arsenal Watertown 72, Massachusetts	14
Commanding Officer Signal Corps Engineering Laboratory ATTN: Director of Research Fort Monmouth, N. J.	15
Commanding Officer Engineering Research and Development Laboratories ATTN: Dr. Z. V. Harvalik Fort Belvoir, Virginia	16
Armed Services Technical Information Agency Arlington Hall Station Arlington 12, Virginia	17 - 26
Commanding Officer Army Research Office ATTN: Paul Greer	27
Dr. Herman Robl	28
Dr. S. Kumar	29
Box CM, Duke Station Durham, North Carolina	
U. S. Naval Ordnance Laboratory ATTN: Technical Library White Oak, Silver Spring 19, Maryland	30
Office of Naval Research Washington 25, D. C.	31

	Copy No.
Director Naval Research Laboratory Washington 25, D. C.	32
Commander U. S. Naval Ordnance Test Station Inyokern, China Lake California	33
U. S. Naval Propellant Plant ATTN: Mr. F. A. H. Rice Indian Head, Maryland	34
Commanding General Air Materiel Command ATTN: Mr. F. N. Bubbs, Chief Scientist Wright-Patterson Air Force Base Dayton 2, Ohio	35
Air Force Special Weapons Center ATTN: Lt. Patrick Roszel Kirtland Air Force Base New Mexico	36
National Aeronautics and Space Administration ATTN: Chief, Div of Research Information 1512 H Street, NW Washington 25, D. C.	37
Ernest O. Lawrence Radiation Laboratory ATTN: Dr. John S. Foster Dr. John Kury P. O. Box 808 Livermore, California	38 39
Dr. Paul W. Levy Brookhaven National Laboratory Upton, Long Island New York	40

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.
**METHOD FOR OBTAINING PRECISE VELOCITIES OF
RAPIDLY MOVING FRAGMENTS**
Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp,
figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the
velocities of small masses can be precisely deter-
mined with an ultra-high-speed (rotating mirror) framing
camera. Intentional double exposure of the film by re-
writing affords multiple records of the projectile in
flight, each frame being an individual record with an
accuracy limited by the operating characteristics of the
camera. (Time resolution depends upon mirror speed.)

1. Velocity —
Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity

Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.
**METHOD FOR OBTAINING PRECISE VELOCITIES OF
RAPIDLY MOVING FRAGMENTS**
Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp,
figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the
velocities of small masses can be precisely deter-
mined with an ultra-high-speed (rotating mirror) framing
camera. Intentional double exposure of the film by re-
writing affords multiple records of the projectile in
flight, each frame being an individual record with an
accuracy limited by the operating characteristics of the
camera. (Time resolution depends upon mirror speed.)

1. Velocity —
Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity

Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.
**METHOD FOR OBTAINING PRECISE VELOCITIES OF
RAPIDLY MOVING FRAGMENTS**
Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp,
figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the
velocities of small masses can be precisely deter-
mined with an ultra-high-speed (rotating mirror) framing
camera. Intentional double exposure of the film by re-
writing affords multiple records of the projectile in
flight, each frame being an individual record with an
accuracy limited by the operating characteristics of the
camera. (Time resolution depends upon mirror speed.)

1. Velocity —
Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity

Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.
**METHOD FOR OBTAINING PRECISE VELOCITIES OF
RAPIDLY MOVING FRAGMENTS**
Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp,
figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the
velocities of small masses can be precisely deter-
mined with an ultra-high-speed (rotating mirror) framing
camera. Intentional double exposure of the film by re-
writing affords multiple records of the projectile in
flight, each frame being an individual record with an
accuracy limited by the operating characteristics of the
camera. (Time resolution depends upon mirror speed.)

1. Velocity —
Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity

Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

AD _____ Accession No. _____
Feltman Research Laboratories
Picatinny Arsenal, Dover, N. J.

METHOD FOR OBTAINING PRECISE VELOCITIES OF RAPIDLY MOVING FRAGMENTS

Frank R. Schwartz

Technical Report FRL-TR-57, April 1962, 12 pp, figures. DA Proj 503-05-021, OMS 5010.11.818.X01.
Unclassified report

An experimental technique is described by which the velocities of small masses can be precisely determined with an ultra-high-speed (rotating mirror) framing camera. Intentional double exposure of the film by re-writing affords multiple records of the projectile in flight, each frame being an individual record with an accuracy limited by the operating characteristics of the camera. (Time resolution depends upon mirror speed.)

1. Velocity — Measurement
2. Fragments — Velocity
3. Rotating mirror cameras
- I. Schwartz, Frank R.
- II. OMS 5010.11.818.X01
- III. DA Proj 503-05-021

UNITERMS

High velocity
Measurement
Fragments
Rotating mirror
Cameras
Schwartz, F. R.
OMS 5010.11.818.X01
DA Proj 503-05-021

UNCLASSIFIED

UNCLASSIFIED