

UNCLASSIFIED

AD 288 752

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

63-1-4


288 752*

ITEM OF INTEREST

Prepared by

Aerospace Information Division

AUG 3 1962



SUBJECT: Heat Stability of Propellants: Hydrazine Perchlorate

SOURCE: Shidlovskiy, A.A., V.I. Semishin, and L.F. Shmagin. Thermal decomposition and combustion of hydrazine perchlorate. Zhurnal prikladnoy khimii, v. 35, no. 4, Apr 1962, 756-759. (S/080/62/035/004)

The thermal and combustion stabilities of hydrazine perchlorate (HP), as well as density, melting point, and heats of solution and decomposition, have been determined at the Moscow Institute of Chemical Machinery and will supplement available data on this compound. The values found for the above physicochemical properties were in good agreement with the literature, except that the melting point of HP was shown to be 140.5 - 141.0°C.

Calculations showed that the combustion temperature of HP at constant pressure was 2200°C and that 864 liters of gas and 770 kcal of heat per kg were liberated. The thermal stability of HP was much lower than that of ammonium perchlorate: weight losses due to HP decomposition after 6 min at 180, 200, 220, and 240°C were 0.3, 0.7, 3.1, and 5.4%, respectively. Rapid combustion occurred at 250°C. Flash point, determined in a Wood's alloy bath heated 20° per min from 100°C, was 277 to 283°C (cf. over 360°C for ammonium perchlorate). The addition of 5% of MnO₂ lowered the flash point of HP to 254 - 259°C, while 5% Cu₂Cl₂ caused detonation at about 170°C.

HP was more sensitive to impact than TEN and highly sensitive to friction, giving 88% detonations under a 5-kg weight dropped from 15 cm (as compared with 68% detonations for TEN) and exploding violently when lightly ground in a porcelain mortar.

Study of the combustion speed in glass tubes at room temperature and 1 atm showed that steady combustion of HP did not occur in the absence of catalysts but took place with the addition of 5% of MnO₂, CoO, or Cu₂Cl₂. Combustion speeds increased in the order MnO₂ < CoO < Cu₂Cl₂ (see Table). The addition of 5% CuCl₂·2H₂O did not produce steady HP combustion, but a mixture of 2.5% CuCl₂·2H₂O plus 2.5% Cu₂Cl₂ unexpectedly caused pulsating

288 752

combustion of 2/3 of the substance, followed by a violent explosion. Conditions and catalysts being the same, the combustion speed of HP was 2 to 3 times higher than that of NH_4ClO_4 .

COMBUSTION OF $\text{N}_2\text{H}_4 \cdot \text{HClO}_4$ WITH CATALYTIC ADDITIVES

Inside diameter of tube, 1.05 cm; combustion speed timed with a stopwatch

Catalytic additive, 5%	Characteristics of burned samples		Test results	
	Height of column, cm	Density of material, g/cm ³	Combustion, sec	Combustion speed, cm/sec
MnO_2 }	1.0	1.27	7.8	0.13
	1.0	1.27	7.6	0.13
CoO }	1.3	1.28	2.0	~ 0.7
	1.2	1.30	1.2	~ 1.0
Cu_2Cl_2 }	1.4	1.30	1.0	~ 1.4
	1.6	1.23	1.0	~ 1.6

In conclusion, it was noted that a mixture of NH_4ClO_4 with 30 to 60% of HP without catalytic additives burned steadily at 0.13 to 0.22 cm/sec in a tube 1.05 cm in (inside) diameter at room temperature and at 1 atm.

[The work reviewed in the article is a continuation of studies of the thermal decomposition and combustion of salts of ammonia and hydrazine (see AID Report 60-42).]