

UNCLASSIFIED

AD 295 670

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

295 670

**DESIGN AND TESTING
OF A
PYROGEN IGNITER FOR A LO_2 - LH_2
ROCKET ENGINE**

TECHNICAL DOCUMENTARY REPORT NO. SSD-TDR-62-201

DECEMBER 1962

**6593d TEST GROUP (DEVELOPMENT)
EDWARDS, CALIFORNIA**

**HEADQUARTERS
SPACE SYSTEMS DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE**

**ASTIA
FEB 7 1963**

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified requesters may obtain copies of this report from the Armed Services Technical Information Agency, (ASTIA), Arlington Hall Station, Arlington 12, Virginia.

DESIGN AND TESTING
OF A
PYROGEN IGNITER FOR A LO_2 - LH_2
ROCKET ENGINE


TECHNICAL DOCUMENTARY REPORT NO. SSD-TDR-62-201

December 1962

Authors

Harold W. Gale, 1/Lt, USAF
Philip C. Moedt, 1/Lt, USAF

This report has been reviewed and approved.


HAROLD W. NORTON
Colonel, USAF
Commander

6593d Test Group (Development)
Edwards, California
Space Systems Division
Air Force Systems Command
United States Air Force

FOREWORD

This technical report has been prepared to present the design and test results, of a solid propellant pyrogen igniter for a liquid rocket engine incorporating LO_2 - LH_2 propellants and the segmented chamber concept.

ABSTRACT

This technical documentary report presents the development and current status of a solid propellant pyrogen igniter used with the $\text{LO}_2\text{-LH}_2$ segmented engine. The objective of this igniter project was to provide the liquid chamber with a long duration (four second), hot flame which would be capable of igniting $\text{LO}_2\text{-LH}_2$ under the most difficult propellant mixing conditions. Fourteen (14) checkout igniter firings were made and over sixty (60) integrated system tests have been conducted to date. The results of these tests have shown that the igniter is extremely reliable, very durable, and safe to work with.

TABLE OF CONTENTS

	<u>PAGE</u>
Introduction	1
Approach	1
Igniter Description	1
System Description	2
Test Results	2
Conclusions	3
Table I	3
Figure 1	4
Photograph 1	5
Figure 2	6
Figure 3	7
Figure 4	8
Figure 5	9
Figure 6	10

DESIGN AND TESTING OF A PYROGEN IGNITER FOR A LIQUID ROCKET ENGINE INCORPORATING THE SEGMENTED CHAMBER CONCEPT

INTRODUCTION.

The objective of the igniter project was to develop an igniter which could give a continuous stream of flame for about four seconds, while operating into a $\text{LO}_2\text{-LH}_2$ segmented engine. The duration of four seconds was desired so that ignition would be assured throughout the early stages of propellant mixing in the liquid engine.

APPROACH.

The basic design parameters for the igniter, Table I, were determined by the liquid rocket system requirements. Final design was based primarily on simplicity, safety, ease of handling, durability, system compatibility and reliability.

IGNITER DESCRIPTION.

The igniter is mounted into the side wall of the segmented LO_2LH_2 engine chamber (Figure 1.). The igniter is a small, end burning solid rocket motor which burns for about four seconds. A drawing of the igniter is shown in Figure 2. The propellant grain is manufactured by curing propellant in a short laminated plastic tube and inhibiting one end. The grain is in cartridge form, which can be easily replaced after each firing. The motor case is 4130 steel with a safety factor of about five, based on 1000 psi chamber pressure. The propellant used has no metal additives. This is to avoid deposition in the small throat and possible contamination of the instrumentation in the main segmented engine. The igniter for the pyrogen igniter is an initiator-pyrocord combination as shown in Figure 3. The pressure tap in the igniter is used to start the complete liquid systems test operation after pyrogen ignition.

SYSTEM DESCRIPTION.

The igniter is mounted on the side of the liquid test chamber as shown in Figure 1, and Photograph 1. Initial checkout firings were done on a simulated liquid chamber, as shown in Photograph 1. The pyrogen hot flame enters through the side of the liquid chamber just below the injector. When the chamber pressure in the pyrogen igniter reaches a pre-set level, 410 psi, a pressure transducer initiates the liquid propellant valves. Ignition of the LO_2 - LH_2 mixture is assured by the long flame duration.

TEST RESULTS.

Test firing data were obtained by the use of a Brush recorder, Figure 4, 5, and 6. With the checkout firings both igniter chamber pressure and flame impingement temperatures were obtained, while with the operational system firings only the igniter chamber pressure was taken.

The results of the fourteen (14) checkout test firings gave the Liquid Systems Branch confidence in handling and using the igniter. The propellant grains used in the first ten (10) checkout tests were made at the Rocket Research Laboratories from available JATO's. Even though two minor mishaps did occur (firings three and four) because of faulty grains, the problems of system integration, grain storage, initiator pyrocord fabrication, igniter assembly and count down procedures were quickly solved. Throughout all fourteen (14) tests, the same igniter case was used. Two graphite nozzle inserts in the igniter case and two graphite inserts in the side of the liquid chamber were also used. Igniter flame temperatures impinging on the liquid chamber were about 1500°F . A typical pressure-time trace of these checkout firings is illustrated on Figure 4.

The results of the sixty (60) operational tests to date have shown the igniter to be very successful. One minor problem did occur in test firing number two, when a hang-fire occurred. This did not effect the final test objectives.

The same igniter case used in the checkout tests was used throughout these operational tests and will continue to be used in future tests. The replacement rate of the igniter nozzle insert and chamber insert is currently

one per every eight firings. Some typical pressure-time traces of the igniter chamber and the effect of the operating liquid chamber on it are illustrated in Figures 5 and 6.

CONCLUSIONS.

Test results to date have indicated the igniter is safe, durable, reliable, economical, and easy to use. It will continue to be used throughout the segmented engine program and future liquid rocket programs where very severe requirements for ignition reliability exist.

TABLE I
IGNITER SPECIFICATIONS

Case Material		4130. Steel
Graphite Material		HLM 8 5
Safety Factor		5.0
Propellant Type		Lockheed 6 cpx-83-44-4 (Polysulfide)
Propellant Wt		= 0.823 lbs.
Grain Length		= 2.08 inches
Action Time		= 4.6 seconds
Thrust		= 36.8 lbs.
Thrust Coefficient	C_F	= 1.215
Chamber Pressure	P_c	= 800. psi
Expansion Ratio	A_e/A_t	= 1.0
Burn Rate		= 0.45 in/sec.
Throat Area	A_T	= .039 in ²
Throat Diameter	D_T	= .220 in
Burning Rate Exponent		= 0.38
Specific Impulse	I_{sp}	= 205. sec.
Ratio of Specific Heats C_P/C_V		= 1.23
Propellant Density		= 0.062 lbs/in ³




Figure 1. System Diagram



Photograph 1.




Figure 2. Pyrogen System Assembly




Figure 3. Igniter for Pyrogen




Figure 4. Igniter Test - 7 November 1962




Figure 5. System Test Firing - 13 June 1962 (Run No. 17)




Figure 6. System Test Firing - 6 July 1962 (Run No. 24)

DISTRIBUTION

Solid Propellant Information Agency distribution list dated May 1962 NOTE: 6593d T. G. (Dev) will make distribution.	150
ASTIA	10
Space Systems Division DCLMT (Mrs. Densmore) AF Unit Post Office Los Angeles 45, Calif.	1
Air Force Flight Test Center FTOOT Edwards Air Force Base, Calif.	10
6593d Test Group (Dev) Edwards, Calif.	
DGS	50
DGLP	10
AFSC (STLO) Lewis Research Center (NASA) Cleveland 35, Ohio	1
	232

Rocket Research Laboratories, Edwards, Calif. Rpt. No. SSD-TDR-62-201. DESIGN AND TESTING OF A PYROGEN IGNITER FOR A LO₂-LH₂ ROCKET ENGINE (U). December 62, 10p. incl figures. Unclassified Report Design and use of a solid propellant rocket Pyrogen igniter with a LO₂-LH₂ liquid rocket engine is presented. Initial firing data are included. Pyrogen initiator is of unique design.	1. Pyrogen 2. Igniter 3. LO₂-LH₂ Rocket Igniter I. AFSC Project 3059 II. P Moedt 1/Lt., USAF III. H. W. Gale 1/Lt., USAF
--	--

Rocket Research Laboratories, Edwards, Calif. Rpt. No. SSD-TDR-62-201. DESIGN AND TESTING OF A PYROGEN IGNITER FOR A LO₂-LH₂ ROCKET ENGINE (U). December 62, 10p. incl figures. Unclassified Report Design and use of a solid propellant rocket Pyrogen igniter with a LO₂-LH₂ liquid rocket engine is presented. Initial firing data are included. Pyrogen initiator is of unique design.	1. Pyrogen 2. Igniter 3. LO₂-LH₂ Rocket Igniter I. AFSC Project 3059 II. P Moedt 1/Lt., USAF III. H. W. Gale 1/Lt., USAF
--	--

Rocket Research Laboratories, Edwards, Calif. Rpt. No. SSD-TDR-62-201. DESIGN AND TESTING OF A PYROGEN IGNITER FOR A LO₂-LH₂ ROCKET ENGINE (U). December 62, 10p. incl figures. Unclassified Report Design and use of a solid propellant rocket Pyrogen igniter with a LO₂-LH₂ liquid rocket engine is presented. Initial firing data are included. Pyrogen initiator is of unique design.	1. Pyrogen 2. Igniter 3. LO₂-LH₂ Rocket Igniter I. AFSC Project 3059 II. P Moedt 1/Lt., USAF III. H. W. Gale 1/Lt., USAF
--	--

Rocket Research Laboratories, Edwards, Calif. Rpt. No. SSD-TDR-62-201. DESIGN AND TESTING OF A PYROGEN IGNITER FOR A LO₂-LH₂ ROCKET ENGINE (U). December 62, 10p. incl figures. Unclassified Report Design and use of a solid propellant rocket Pyrogen igniter with a LO₂-LH₂ liquid rocket engine is presented. Initial firing data are included. Pyrogen initiator is of unique design.	1. Pyrogen 2. Igniter 3. LO₂-LH₂ Rocket Igniter I. AFSC Project 3059 II. P Moedt 1/Lt., USAF III. H. W. Gale 1/Lt., USAF
--	--