

UNCLASSIFIED

AD NUMBER
AD325021
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution: Further dissemination only as directed by Commanding Officer, Bureau of Naval Weapons, Washington, DC., 28 Feb 1973, or higher DoD authority.
AUTHORITY
USNOL ltr, 29 Aug 1974

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD NUMBER

AD325021

CLASSIFICATION CHANGES

TO: **unclassified**

FROM: **confidential**

LIMITATION CHANGES

TO:

Distribution: Further dissemination only as directed by Commanding Officer, Bureau of Naval Weapons, Washington, DC., 28 Feb 1973, or higher DoD authority.

FROM:

Controlling DoD Organization... Commanding Officer, Bureau of Naval Weapons, Washington, DC.

AUTHORITY

28 Feb 1973, per document marking, DoDD 5200.10; 28 Feb 1973, DoDD 5230.24

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 325021

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

CLASSIFICATION CHANGED

TO UNCLASSIFIED

FROM CONFIDENTIAL

PER AUTHORITY LISTED IN

Pul. no. 65-21

1 Nov. 1965.



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

FOR ERRATA

AD 325021

THE FOLLOWING PAGES ARE CHANGES

TO BASIC DOCUMENT

ERATA

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK
SILVER SPRING, MARYLAND



To all holders of NAVWEPS REPORT 7380
insert change; write on cover 'Change 2 inserted'
Approved by Commander, U.S. NOL

Change 2
8 September 1964
1 page

[Signature]
By direction

This publication is changed as follows:

19 Oct 1964

Downgrade classification of pentolite data from CONFIDENTIAL
to UNCLASSIFIED; specifically

- (a) Pentolite similitude equations for p_m , E, I, and θ given in the Abstract and on Page 6.
- (b) The nomograph for pentolite (Figure 8).

Insert this change sheet between the cover and the title page of your copy.

~~CONFIDENTIAL~~

NAVWEPS REPORT

7380

REVISED SIMILITUDE EQUATIONS FOR THE UNDERWATER SHOCKWAVE PERFORMANCE OF PENTOLITE AND HBX-1 (U)

- RELEASED TO ASTIA
BY THE NAVAL ORDNANCE LABORATORY
- ☒ Without restrictions
 - ☐ For release to Military and Government Agencies only.
 - ☐ Approval by BuWeps required for release to other agencies.
 - ☐ Approval by BuWeps required for all subsequent release.

1 FEBRUARY 1961




NOTICE: This material contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

NAVWEPS 7380

XEROX

Downgraded at 3 Year Intervals
Declassified after 12 Years. DOD Dir 5200.10



Best Available Copy

DATA 311A 325021

625-200

REVISED SIMILITUDE EQUATIONS FOR THE UNDERWATER
SHOCKWAVE PERFORMANCE OF PENTOLITE AND HBX-1 (U)

by
M. A. Thiel

Reviewed by: C. R. Niffenegger

Approved by: E. Swift, Jr., Chief
Underwater Explosions Division

ABSTRACT: All available data obtained from spherical and squat cylindrical HBX-1 and pentolite charges fired at the Naval Ordnance Laboratory and the Woods Hole Oceanographic Institution were used to determine revised similitude equations for underwater shockwave parameters. The revised equations are: HBX-1,

$$p_m = 2.38 \times 10^4 \left(\frac{W^{1/3}}{R} \right)^{1.15}, \quad E = 2.96 \times 10^3 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{2.00},$$

$$I = 1.57 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{0.85}, \quad \theta = 0.049 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{-0.29}; \text{ pentolite,}$$

$$p_m = 2.35 \times 10^4 \left(\frac{W^{1/3}}{R} \right)^{1.14}, \quad E = 2.66 \times 10^3 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{2.04},$$

$$I = 1.48 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{0.91}, \quad \theta = 0.052 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{-0.23}.$$

Each equation represents an average and so when plotted lies in the band formed by the curves of previously obtained similitude equations. Nomographs for obtaining shockwave parameters are included (c).

EXPLOSIONS RESEARCH DEPARTMENT
U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

CONFIDENTIAL

NAWEPS Report 7380

1 February 1961

The work described in this report is part of the continuing program of investigation of the underwater performance of explosive mixtures, under Task RUME-3-E-002/2121/ F008-10-004. Results shown here represent the best absolute values available at present for the underwater explosion parameters of HBX-1 and pentolite, which are used as standards of underwater explosive performance. The values for pentolite supersede those given in NAVORD Report 2575. The nomographs given here are also included as a revision in NAVORD Report 2986, "Explosion Effects Data Sheets".

W. D. COLEMAN
Captain, USN
Commander



C. J. ARONSON
By direction

CONFIDENTIAL
NAVWEPS Report 7380

CONTENTS

	Page
1. Introduction	1
2. Discussion of Data.....	1
2.1 Data Chosen.....	1
2.2 Parameters.....	3
2.3 Effect of Gage Size.....	3
3. Treatment of Data.....	4
3.1 General.....	4
3.2 HBX-1 Peak Pressure.....	4
3.3 Energy and Impulse.....	5
3.4 Time Constant.....	5
4. Results.....	5
4.1 Similitude Equations.....	5
4.2 Discussion of Equations.....	6
4.3 Nomographs.....	7

ILLUSTRATIONS

Figure 1. Peak Pressure vs $W^{1/3}/R$ for 1/4-, 3/8-, and 1/2-in. Gages	10
Figure 2. Peak Pressure vs $W^{1/3}/R$ for all HBX-1 Data.....	11
Figure 3. Comparison of Revised and NavOrd 2986 HBX-1 Similitude Equations - p_m and $I/W^{1/3}$	12
Figure 4. Comparison of Revised and NavOrd 2986 HBX-1 Similitude Equations - $E/W^{1/3}$ and $\theta/W^{1/3}$	12
Figure 5. Comparison of Revised and NavOrd 2986 Pentolite Similitude Equations - p_m and $I/W^{1/3}$	13
Figure 6. Comparison of Revised and NavOrd 2986 Pentolite Similitude Equations - $E/W^{1/3}$ and $\theta/W^{1/3}$	13
Figure 7. Underwater Shockwave Parameters HBX-1.....	14
Figure 8. Underwater Shockwave Parameters Pentolite.....	15

TABLES

Table I. Sources of Data.....	2
Table II. Comparison of Revised and NavOrd 2986 Similitude Equations	6
References.....	8

REVISED SIMILITUDE EQUATIONS FOR THE UNDERWATER
SHOCKWAVE PERFORMANCE OF PENTOLITE AND HBX-1 (U)

1. INTRODUCTION

A large amount of underwater shockwave data for HBX-1 and pentolite has been accumulated in the past 15 years from the explosives testing programs of the Naval Ordnance Laboratory (NOL) and the Woods Hole Oceanographic Institution (WHOI). In the past the data have been treated in small groups, and similitude equations have been derived from each firing program. This has led to some discrepancies between various sets of results. A review of the available data was therefore made in order to resolve these discrepancies and to provide consistent and reliable values of underwater parameters for pentolite and HBX-1. In this report the method of treating the data is given, and new similitude equations and nomographs for peak pressure, time constant, impulse, and energy of pentolite and HBX-1 are presented.

2. DISCUSSION OF DATA

2.1 Data Chosen: All data used herein were obtained from spherical and squat cylindrical charges; data from elongated charges were excluded. Charge weights ranged from 0.5 to 80 pounds. Pressure-time measurements were made at reduced distances, $R/W^{1/3}$ (where R is the charge-to-gage distance in feet and W is the charge weight in pounds), ranging from approximately 1.2 to 25. The instrumentation used at NOL is described in Reference (a)* and modifications to it are described in References (b - e). The equipment used at WHOI is described in Reference (f). Most of the data were obtained by NOL. Table I describes briefly the data used for this study.

*The list of references is on page 7.

CONFIDENTIAL
NAWWEPS Report 7380

TABLE I
SOURCES OF DATA

Reference	Source	Charge Wt. (lbs)	Charge Shape	Gage Dia. (in.)	Charge-to- Gage Dist. (ft.)	Number of*** Data Points
HBX-1						
(g)	WHOI	50	Sphere	1/4, 1/2	5-100	12
(g)	WHOI	80	Sphere	1/4, 1/2	5-100	12
(k)	NOL	1.1	Cyl.	1/4	2-6	3
(d)	NOL	45	Cyl.	1/4, 3/8*	6-50	9
(l)	NOL	45	Cyl.	1/4, 3/8*	6-50	8
(n)	NOL	45	Cyl.	1/4, 3/8*	6-50	8
(o)	NOL	45	Cyl.	1/4, 3/8*	6-50	8
(p)	NOL	47	Cyl.	1/4, 3/8*	6-40	4
(q)	NOL	46	Cyl.	1/2	6-50	8
(r)	NOL	10	Cyl.	1/4, 3/8**	4.5-45.5	4
(r)	NOL	30	Cyl.	1/4, 3/8**	7-48	4
(r)	NOL	50	Cyl.	1/4, 3/8**	9-50	4
(s)	NOL	10	Cyl.	1/4	4.5-43.5	4
Pentolite						
(i)	WHOI	51	Sphere	1/4, 1/2	12-100	12
(i)	WHOI	80	Sphere	1/4, 1/2	12-100	12
(h)	WHOI	0.55	Sphere	1/4	1.4-1.7	2
(j)	WHOI	1.1	Sphere	1/4, 3/8	1-7	45
(j)	WHOI	2.3	Sphere	1/4, 3/8	1-7	7
(m)	NOL	0.66	Cyl.	1/4	2-6	3
(m)	NOL	1.0	Cyl.	1/4	2-6	3
(m)	NOL	1.32	Cyl.	1/4	2-6	3
(m)	NOL	1.65	Cyl.	1/4	2-6	3
(m)	NOL	44	Cyl.	1/4, 3/8*	6-50	8

*Tests on which incorrect slope of pressure-distance relationship was obtained; 1/4 in. gages at distances close to the charge and 3/8 in. gages at far out positions. See paragraph 2.3.

**1/4 and 3/8 in. gages paired at each distance.

***Each data point was the average of 2-4 individual records.

CONFIDENTIAL
NAWWEPS Report 7380

2.2 Parameters: The shockwave parameters which were included in this study are:

p_m The pressure at the shock front. (psi)

θ The time constant; the time at which $p = p_m/e$. (The first portion of the shockwave is approximately an exponential until this time.) (milliseconds)

I The impulse = $\int_0^{5\theta} p dt$ (psi-sec)

E The energy = $\frac{1 - (1.7 \times 10^{-6})}{\rho_o c_o} \int_0^{5\theta} p^2 dt$ (in.-lbs/in.²)

where $\rho_o c_o = 5.14 + 0.0144 t^0$ Cent.

The values of each parameter obtained from the original records were accepted substantially as reported; none of the records was re-read.

2.3 Effect of Gage Size: All of the pressure-time recordings were made with tourmaline piezoelectric gages whose diameters were 1/4, 3/8, or 1/2 inch. Different combinations of gage sizes were used from time to time, and the particular arrangement used seemed to correlate with variations in the experimental results.* These variations appeared in the NOL data.

Prior to 1954 NOL pressure-time recordings were made with small gages, usually 1/4-in., at positions close to the charge, and slightly larger gages, usually 3/8-in., at the farther positions. The peak pressure-distance similitude relationship so obtained showed a considerably different slope (exponent) from the earlier WHOI relationships. Examination of the data showed that a separate similitude equation could be derived for each gage size with an exponent having almost the same value as that in the corresponding similitude equation obtained by WHOI. Thus while each size of gage was yielding a consistent result by itself, combining the close-in results with the farther-out results yielded a slope in disagreement with the previous work.

A careful study was made of the effect of gage size on the shockwave measurements. (See Appendix C of Reference (r).) It was found that while there is an effect, it is of such small magnitude that it could not account for the differences observed between the large and small gage results. Although the cause of the differences has not been found, gage size was taken into account in the grouping of the data for analysis.

*While the discussion below is restricted to peak pressure variations, similar results are found in the impulse and energy data.

CONFIDENTIAL
NAVWEPS Report 7380

Since 1954 all NOL data have been taken using two sizes of gage at each position.

3. TREATMENT OF DATA

3.1 General: Each of the parameters was treated in the same general manner. The data were separated by gage size into groups and then each group was plotted on log-log graph paper. From these plots slopes and similitude equations were determined. For each parameter, several slopes were obtained which were identical or nearly so. An average slope was then used in drawing the best line through all the data points on one plot. The procedure is illustrated with the HBX-1 p_m data in the following section.

3.2 HBX-1 Peak Pressure: HBX-1 p_m data were divided into six groups, as follows: NOL 1/4-in. gages, NOL 3/8-in. gages, NOL 1/2-in. gages, NOL 1/4 and 3/8-in. gages paired, and WHOI gages. Figure 1 shows the 1/4-in., 3/8-in., and 1/2-in. data plotted. The data from gages of unknown size were not used; each of the other groups was plotted on log-log paper and an equation derived. The equations obtained were:

$$\begin{aligned} p_m &= 2.40 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.15} && 1/4\text{-in.} \\ &= 2.10 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.15} && 3/8\text{-in.} \\ &= 2.24 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.15} && 1/2\text{-in.} \\ &= 2.56 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.15} && 1/4 - 3/8\text{-in. paired} \\ &= 2.48 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.15} && \text{WHOI} \end{aligned}$$

The exponent (1.15) representing the slope of the log-log p_m vs $\frac{w^{1/3}}{R}$ plot is the same for the above equations.

To obtain the final over-all equation, all data points were plotted on log-log paper and the best line drawn to a slope of 1.15. Figure 2 shows this plot. The resulting equation is:

$$p_m = 2.38 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.15}$$

CONFIDENTIAL
NAWEPs Report 7380

The slopes obtained from such sets of plots occasionally were not identical; the maximum variation was 3 - 4%. The best slope was then determined by taking a weighted average of the slopes of the different plots.

The other parameters were treated in the same manner with the exceptions noted below.

3.3 Energy and Impulse: The NOL shockwave records were integrated to 50 while WHOI records were integrated to 6.70. To make the data comparable, the WHOI integrations were corrected to 50. This was done by multiplying energy values by 0.98 and impulse values by 0.92. The factors are from Figures 9.4 and 9.6 of Reference (t). While these factors were determined from a study of HBX-2 records, they are also applicable here.

3.4 Time Constant: WHOI time constant data were not used since NOL and WHOI used different methods for determining time constant.* While this results in slight differences in θ , either set of values may be considered reliable within the limits of accuracy, and the difference should have only a slight effect on the derived parameters of energy and impulse.

4. RESULTS

4.1 Similitude Equations: The similitude equations for HBX-1 and pentolite obtained in the manner described are:

$$\begin{aligned} \text{HBX-1: } p_m &= 2.38 \times 10^4 \left(\frac{W^{1/3}}{R} \right)^{1.15} \\ E &= 2.96 \times 10^3 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{2.00} \\ I &= 1.57 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{0.85} \\ \theta &= 0.049 W^{1/3} \left(\frac{W^{1/3}}{R} \right)^{-0.29} \end{aligned}$$

*At WHOI the time constant was read from an enlargement of the pressure-time record. At NOL the pressure-time records were plotted on semi-log paper and the time constant was determined from the line drawn through the initial decay of the record.

CONFIDENTIAL
NAWEPs Report 7380

$$\begin{aligned} \text{Pentolite: } p_m &= 2.35 \times 10^4 \left(\frac{w^{1/3}}{R} \right)^{1.14} \\ E &= 2.66 \times 10^3 w^{1/3} \left(\frac{w^{1/3}}{R} \right)^{2.04} \\ I &= 1.48 w^{1/3} \left(\frac{w^{1/3}}{R} \right)^{0.91} \\ \theta &= 0.052 w^{1/3} \left(\frac{w^{1/3}}{R} \right)^{-0.23} \end{aligned}$$

4.2 Discussion of Equations: The most widely used HBX-1 and pentolite similitude equations have been those of References (g) and (i) which are the equations reported in NavOrd Report 2986. These equations were obtained at WHOI. There was no gage size effect in the data used to derive the equations. The revised equations represent an average of all currently available data with allowances made for gage size effect. In Table II are shown coefficients and exponents of both sets of equations for comparison.

TABLE II

COMPARISON OF REVISED AND NAVORD 2986 SIMILITUDE EQUATIONS

		HBX-1				Pentolite			
		p_m	E	I	θ	p_m	E	I	θ
Coefficient	2986	2.48	3.55	1.80	0.055	2.25	3.27	2.18	0.060
	Revised	2.38	2.96	1.57	0.049	2.35	2.66	1.48	0.052
Exponents	2986	1.15	2.06	0.87	-0.27	1.13	2.12	1.05	-0.18
	Revised	1.15	2.00	0.85	-0.29	1.14	2.04	0.91	-0.23

The revised and the NavOrd 2986 equations are plotted in Figures 3, 4, 5, and 6. The absolute difference between the two sets of equations at

CONFIDENTIAL
NAVWEPS Report 7380

different reduced distances can be seen directly. Peak pressure and reduced energy show lesser differences than do reduced impulse and reduced time constant. For peak pressure the difference between the two sets of equations is not significant. The difference shown by the other parameters is probably not significant for practical purposes.

The similitude equations found in References (d), (l), (m), (n), (o), and (p) should not be used. These equations came from data in which a gage size effect was present. The gage size effect resulted in incorrect exponents in the similitude equations.

The revised equations may change in the future. Because of errors of measurement inherent in the experimental technique and lack of absolute reproducibility of small charge results, these equations may well be modified as more series are shot.

4.3 Nomographs: Figures 3 and 4 are nomographs for the shockwave parameters based on the new similitude equations.

CONFIDENTIAL
NAWEPs Report 7380

REFERENCES

- (a) "Instrumentation for Recording Underwater Shock Pressures Generated by Explosives", H. H. Hall, NAVORD Report 477, March 1949, Unclassified.
- (b) "A Comparison of the Underwater Explosive Efficiency of Baronex and HBX-1 in Weapon A", E. A. Christian et al, NOIM 9961, 23 December 1948, Confidential.
- (c) "Present Status of Pressure-Measuring Instrumentation Aboard KPCS-1413", J. Petes and B. W. Scott, NOIM 10866, April 1950, Unclassified.
- (d) "The Effect of Aluminum on Underwater Explosive Performance: Shockwave Parameters from 50-Lb Charges", Jean A. Goertner et al, NAVORD Report 2368, 1 March 1952, Confidential.
- (e) "Underwater Shockwave Parameters for TNT", J. P. Slifko and T. E. Farley, NAVORD Report 6634, 1 June 1959, Unclassified.
- (f) "The Measurement of Underwater Explosions from Service Weapons at the Underwater Explosives Research Laboratory (UERL)", J. S. Coles, NDRS Report A-362, OSRD Report 6240, March 1946, Confidential.
- (g) "Shockwave Parameters from Spherical HBX and TNT Charges Detonated Under Water", J. S. Coles et al, NAVORD Report 103-46, December 1946, Confidential.
- (h) "The Measurement of Small-Charge Shock-Wave Parameters with UERL Type B Underwater Gages", A. B. Arons and P. F. Smith, NAVORD Report 104-46, 24 December 1946, Confidential.
- (i) Division 2 Interim Report on "Underwater Explosives and Explosions", UE-32 OSRD 4874, 15 March 1945 - 15 April 1945, Confidential.
- (j) "Multiple Charge Effect from Two 500 Gram Pentolite Charges Under Water", E. A. Christian et al, NAVORD Report 405, 5 December 1947, Confidential.
- (k) "The Effect of Aluminum on Underwater Explosive Performance: Shockwave Parameters from 1-lb Charges", R. W. Astheimer, E. A. Christian, and E. Swift, Jr., NAVORD Report 2317, 1 January 1952, Confidential.
- (l) "The Underwater Performance of an HBX and Three Explosives Containing Ammonium Perchlorate", Jean A. Goertner, C. R. Niffenegger, and J. P. Slifko, NAVORD Report 2553, 1 July 1952, Confidential.
- (m) "Underwater Explosion Parameters for 50-50 Pentolite", Jean A. Goertner and E. Swift, Jr., NAVORD Report 2575, 15 July 1952, Confidential.

CONFIDENTIAL
NAVWEPS Report 7380

- (n) "Underwater Performance of Explosives Containing Ammonium Perchlorate, II", Jean A. Goertner and C. R. Niffenegger, NAVORD Report 2736, 1 January 1953, Confidential.
- (o) "Underwater Performance of Explosives Containing Ammonium Perchlorate, III", E. A. Christian and C. R. Niffenegger, NAVORD Report 3563, 1 November 1953, Confidential.
- (p) "Underwater Performance of Explosives Containing Ammonium Perchlorate, IV. Preliminary Results from Several Mixtures", E. A. Christian, NAVORD Report 3728, 10 June 1954, Confidential.
- (q) "The Underwater Performance of Three Explosives Containing TNETB", C. R. Niffenegger and E. Swift, Jr., NAVORD Report 3782, 15 July 1954, Confidential.
- (r) "Underwater Performance of Explosives Containing Ammonium Perchlorate, V. Review of Available Data", E. A. Christian and C. R. Niffenegger, NAVORD Report 3897, 1 February 1955, Confidential.
- (s) "Comparisons of the Underwater Power of Explosives in Small Charges: V. Miscellaneous One-Lb and Ten-Lb Charges", E. A. Christian and M. A. Thiel, NAVORD Report 4301, 1 September 1956, Confidential.
- (t) "Underwater Free-Field Pressures to Just Beyond Target Location", C. J. Aronson et al, Operation WIGWAM, Project 1.2, WT-1005, 27 May 1957, Confidential Formerly Restricted Data

CONFIDENTIAL
NAVWEPS REPORT 7380




FIG. 1 PEAK PRESSURE VS $W^{1/3}/R$
FOR 1/4, 3/8, AND 1/2-IN. GAGES
NOL HBX-1 DATA

CONFIDENTIAL
NAVWEPS REPORT 7380




FIG. 2 PEAK PRESSURE VS W^{1/3}/R
ALL HBX-I DATA




FIG. 3 COMPARISON OF REVISED AND NAVORD 2986 HBX-1 SIMILITUDE EQUATIONS- P_m AND $I/W^{1/3}$




FIG. 4 COMPARISON OF REVISED AND NAVORD 2986 HBX-1 SIMILITUDE EQUATIONS- $E/W^{1/3}$ AND $\theta/W^{1/3}$






FIG. 5 COMPARISON OF REVISED AND NAVORD 2986 PENTOLITE SIMILITUDE EQUATIONS - P_m AND $I/W^{1/3}$

FIG. 6 COMPARISON OF REVISED AND NAVORD 2986 PENTOLITE SIMILITUDE EQUATIONS - $E/W^{1/3}$ AND $\theta/W^{1/3}$




TIME CONSTANT TO BE READ ONLY WITH USE OF REFERENCE




THE NOMOGRAPH YIELDS p_m , THE PEAK PRESSURE, θ , THE TIME CONSTANT (i.e., THE TIME AT WHICH THE PRESSURE HAS DECAYED TO p_m/e), I , THE POSITIVE IMPULSE, AND E , THE ENERGY, OF AN UNDERWATER SHOCKWAVE. THE SCALES CORRESPOND TO EMPIRICAL EQUATIONS, SHOWN ON THE NOMOGRAPH, WHICH WERE OBTAINED FROM MEASUREMENTS OF SQUAT CYLINDRICAL OR SPHERICAL CHARGES WEIGHING 1, 10, 30, 46, 50 AND 80 LBS.

THE SHOCKWAVE PRESSURE-TIME CURVE IS ESSENTIALLY AN EXPONENTIAL OF THE FORM $p=p_m e^{-t/\theta}$ AT LEAST UNTIL A TIME $t < \theta$, BUT AT LATER TIMES THE PRESSURES DECREASE AT A RATE SLOWER THAN EXPONENTIAL. CONSEQUENTLY, IT IS NECESSARY TO MEASURE IMPULSE AND ENERGY TO SOME CHOSEN TIME IN ORDER TO OBTAIN A COMPARABLE VALUE; THE TIME LIMIT USED HERE IS 5θ . THE VALUES SHOWN FOR I (5θ) SHOULD BE INCREASED ABOUT 8% FOR A LIMIT OF 6.7θ , AND ABOUT 20% FOR A LIMIT OF 10θ . THE VALUES OF E (5θ) SHOWN HERE SHOULD BE INCREASED BY ABOUT 2% FOR A LIMIT OF 6.7θ AND ABOUT 4% FOR A LIMIT OF 10θ .

2





THE NOMOGRAPH YIELDS p_m , THE PEAK PRESSURE, θ , THE TIME CONSTANT (i.e., THE TIME AT WHICH THE PRESSURE HAS DECAYED TO p_m/e), I , THE POSITIVE IMPULSE, AND E , THE ENERGY OF AN UNDERWATER SHOCKWAVE. THE SCALES CORRESPOND TO EMPIRICAL EQUATIONS, SHOWN ON THE NOMOGRAPH, WHICH WERE OBTAINED FROM MEASUREMENTS OF SQUAT CYLINDRICAL OR SPHERICAL CHARGES WEIGHING $\frac{1}{2}$, 1, 2, 44, 51, AND 80 LBS.

THE SHOCKWAVE PRESSURE-TIME CURVE IS ESSENTIALLY AN EXPONENTIAL OF THE FORM $p = p_m e^{-t/\theta}$ AT LEAST UNTIL A TIME $t < \theta$, BUT AT LATER TIMES THE PRESSURES DECREASE AT A RATE SLOWER THAN EXPONENTIAL. CONSEQUENTLY, IT IS NECESSARY TO MEASURE IMPULSE AND ENERGY TO SOME CHOSEN TIME IN ORDER TO OBTAIN A COMPARABLE VALUE; THE TIME LIMIT USED HERE IS 5θ . THE VALUES SHOWN FOR I (50) SHOULD BE INCREASED ABOUT 8% FOR A LIMIT OF 6.7θ , AND ABOUT 20% FOR A LIMIT OF 10θ . THE VALUES OF E (50) SHOWN HERE SHOULD BE INCREASED BY ABOUT 2% FOR A LIMIT OF 6.7θ AND ABOUT 4% FOR A LIMIT OF 10θ .

NAVWEPS Report 7380

DISTRIBUTION

	Copies
Chief, Bureau of Naval Weapons, Attn: Library, DIS-3	2
Attn: RUME-3	1
Attn: RRRRE-6	1
Chief of Naval Operations, Attn: OP 36	1
Chief of Naval Research, Attn: Code 466	1
Attn: Code 418	1
Chief, Bureau of Ships, Attn: Code 423	2
Chief, Bureau of Yards and Docks	1
Commanding Officer and Director, U. S. Naval Radiation Defense Laboratory, San Francisco 24, California, Attn: Code 911	1
Attn: Code 934	1
Attn: Code 222	1
Commander, Norfolk Naval Shipyard, Portsmouth, Virginia	
Attn: Code 280, Underwater Explosions Research Div.	2
Commanding Officer, Naval Propellant Plant, Indian Head, Maryland	1
Commander, Naval Weapons Laboratory, Dahlgren, Virginia	
Attn: Experimental Officer	1
Commander, Naval Ordnance Test Station, China Lake, California	
Attn: Technical Library	1
Director, Naval Research Laboratory, Washington, D. C.	2
Director David Taylor Model Basin, Washington 7, D. C.	2
Superintendent, U. S. Naval Postgraduate School, Monterey, California	1
Director, U. S. Navy Electronics Laboratory, San Diego, California	1
Commanding Officer, U. S. Naval Underwater Ordnance Station, Newport, Rhode Island	1
Commander, U. S. Naval Weapons Station, Yorktown, Virginia	
Attn: Research and Development Division	1
Commanding Officer, Naval Torpedo Station, Keyport, Washington	1
Commanding Officer and Director, U. S. Navy Underwater Sound Laboratory, New London, Conn.	1
Commanding Officer, U. S. Naval Air Development Center, Johnsville, Pennsylvania	1
Commanding Officer, U. S. Naval Ammunition Depot, Navy Number 66, Fleet Post Office, San Francisco, California,	
Attn: Quality Evaluation Laboratory	1
Commanding Officer, U. S. Navy Mine Defense Laboratory, Panama City, Florida	1
Commanding Officer, U. S. Naval Nuclear Ordnance Evaluation Unit, Kirtland Air Force Base, Albuquerque, New Mexico, Attn: Code 401	1
Chief of Research and Development, Department of the Army, Washington, D. C.	
Chief of Ordnance, Department of the Army, Washington, D. C.	2
Chief of Engineers, Department of the Army, Washington, D. C.	
Attn: ENONE	2
Attn: ENGEB	1

NAVWEP's Report 7380

	Copies
Director, Waterways Experiment Station, Vicksburg, Mississippi	
Attn: F. R. Brown	1
Commanding General, Ballistic Research Laboratories,	
Aberdeen, Maryland	1
Commanding Officer, Picatinny Arsenal, Dover, New Jersey	1
Commanding Officer, Engineer Research and Development Laboratory,	
Fort Belvoir, Virginia, Attn: Chief, Tech. Support Branch	1
Commanding Officer, USA Signal R and D Laboratory,	
Fort Monmouth, New Jersey, Attn: Tech. Documents Center	1
Director of Research and Development, Headquarters, U. S. Air	
Force, Washington 25, D. C.	1
Commander, Ooama, Attn: Air Force Ammunition Services Office,	
Hill Air Force Base, Utah	1
Commander, Air Force Armament Center, Eglin Air Force Base,	
Florida, Attn: ACX	1
Commander, Air Materiel Command, Wright-Patterson Air Force Base,	
Dayton, Ohio	1
Commander, Wright Air Development Center, Wright-Patterson Air	
Force Base, Dayton, Ohio	1
Commander, Air Force Special Weapons Center, Kirtland Air Force	
Base, Albuquerque, New Mexico, Attn: Technical Library	1
Director, Defense Research and Engineering, Washington 25, D. C.	
Attn: Technical Library	1
Director, Applied Physics Laboratory, Johns Hopkins University,	
Silver Spring, Maryland	1
Chief, Defense Atomic Support Agency, Washington 25, D. C.	3
Director, Applied Physics Laboratory, University of Washington,	
Seattle, Washington	1
Director, Operations Research Office, Johns Hopkins University,	
6935 Arlington Road, Bethesda, Maryland, Attn: Document Control	
Office, Washington 14, D. C.	1
Director, Ordnance Research Laboratory, University of Pennsylvania,	
State College, Pennsylvania	1
Director, Woods Hole Oceanographic Institution, Woods Hole, Mass.	1
Director, Scripps Institute of Oceanography, La Jolla, California	1
Director, Hudson Laboratory, Columbia University, New York, New York	1
Director, Lawrence Radiation Laboratory, Livermore, California	1
Director, Los Alamos Scientific Laboratory, Los Alamos,	
New Mexico, Attn: Dr. D. P. MacDougall	2
Director, National Bureau of Standards, Washington, D. C.	
Attn: Security Officer	1
Administrator, NASA, 1512 H Street, N. W., Washington, D. C.	1
Sandia Corporation, Sandia Base, Albuquerque, New Mexico	
Attn: Classified Document Division	1
Armed Services Technical Information Agency, Arlington Hall	
Station, Arlington 12, Virginia, Attn: TIPDR	10
Amherst College, Amherst, Massachusetts, Attn: Dr. Arnold Arons,	
Physics Dept.	1

CLASSIFIED

NAVWEP's Report 7380

	Copies
New York University, University Heights, New York 53, New York Attn: Dr. G. E. Hudson, Dept. of Physics	1
Michigan State University, East Lansing, Michigan (Class. Material c/o Mr. Gerald Knapp, Security Officer, Administration Bldg., Michigan State University), Attn: Dr. T. Triffet, Dept. of Applied Mechanics	1
Harvey Mudd College, Claremont, California (Class. Material: Via: ONR Branch Office, Pasadena, Calif.), Attn: Dr. A. B. Focke, Dept. of Physics	1
Columbia University, New York 27, New York, Attn: Dr. Hans H. Bleich, Dept. of Civil Engr. and Engr. Mech.	1
E. I. duPont de Nemours and Co., Eastern Laboratory, Explosives Department, Gibbstown, New Jersey, Attn: Dr. D. L. Coursen (Contract NOW-60-0095-C)	1
Daystrom Electric, Division of Daystrom, Inc., 229-A Manchester Road, Poughkeepsie, New York, Attn: Mr. D. K. Tower (Contract NOrd 17771)	1

Naval Ordnance Laboratory, White Oak, Md. (NAVWEPS report 7380) REVISED SIMILITUDE EQUATIONS FOR THE UNDERWATER SHOCKWAVE PERFORMANCE OF PENTOLITE AND HEX-1 (U), by M.A. Thiel. 1 Feb. 1961. 9p. charts, tables. Project ROME-3-E-002/2121/FO08-10-004. CONFIDENTIAL All available data obtained from spherical and squat cylindrical HEX-1 and pentolite charges fired at the Naval Ordnance Laboratory and the Woods Hole Oceanographic Institution were used to determine revised similitude equations for underwater shockwave parameters. Equations represent an average and so when plotted lies in the band formed by the curves of previously obtained similitude equations. Nomographs for obtaining shockwave parameters are included. Abstract card is confidential	1. Explosions, Underwater - Shock waves 2. Explosives, Underwater 3. HBX-1 4. Pentolites I. Title II. Thiel, Mitchell A. III. Project Downgraded at 3 year intervals; declassified after 12 years DOD dir 5200.10
Naval Ordnance Laboratory, White Oak, Md. (NAVWEPS report 7380) REVISED SIMILITUDE EQUATIONS FOR THE UNDERWATER SHOCKWAVE PERFORMANCE OF PENTOLITE AND HEX-1 (U), by M.A. Thiel. 1 Feb. 1961. 9p. charts, tables. Project ROME-3-E-002/2121/FO08-10-004. CONFIDENTIAL All available data obtained from spherical and squat cylindrical HEX-1 and pentolite charges fired at the Naval Ordnance Laboratory and the Woods Hole Oceanographic Institution were used to determine revised similitude equations for underwater shockwave parameters. Equations represent an average and so when plotted lies in the band formed by the curves of previously obtained similitude equations. Nomographs for obtaining shockwave parameters are included. Abstract card is confidential	1. Explosions, Underwater - Shock waves 2. Explosives, Underwater 3. HBX-1 4. Pentolites I. Title II. Thiel, Mitchell A. III. Project Downgraded at 3 year intervals; declassified after 12 years DOD dir 5200.10
Naval Ordnance Laboratory, White Oak, Md. (NAVWEPS report 7380) REVISED SIMILITUDE EQUATIONS FOR THE UNDERWATER SHOCKWAVE PERFORMANCE OF PENTOLITE AND HEX-1 (U), by M.A. Thiel. 1 Feb. 1961. 9p. charts, tables. Project ROME-3-E-002/2121/FO08-10-004. CONFIDENTIAL All available data obtained from spherical and squat cylindrical HEX-1 and pentolite charges fired at the Naval Ordnance Laboratory and the Woods Hole Oceanographic Institution were used to determine revised similitude equations for underwater shockwave parameters. Equations represent an average and so when plotted lies in the band formed by the curves of previously obtained similitude equations. Nomographs for obtaining shockwave parameters are included. Abstract card is confidential	1. Explosions, Underwater - Shock waves 2. Explosives, Underwater 3. HBX-1 4. Pentolites I. Title II. Thiel, Mitchell A. III. Project Downgraded at 3 year intervals; declassified after 12 years DOD dir 5200.10