

UNCLASSIFIED



AD NUMBER

AD-326 783

CLASSIFICATION CHANGES

TO UNCLASSIFIED

FROM CONFIDENTIAL

AUTHORITY

OCA; Jul 25, 1973

1999 06/8003

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED



AD NUMBER

AD-326 783

NEW LIMITATION CHANGE

TO

DISTRIBUTION STATEMENT: A

Approved for public release; Distribution is unlimited.

LIMITATION CODE: 1

FROM

No Prior DoD Distr Scty Cntrl St'mt Assgn'd

AUTHORITY

U.S. Naval Ordnance Lab, White Oak, MD; Aug 29, 1974

THIS PAGE IS UNCLASSIFIED

GENERAL DECLASSIFICATION SCHEDULE

**IN ACCORDANCE WITH
DOD 5200.1-R & EXECUTIVE ORDER 11652**

THIS DOCUMENT IS:

CLASSIFIED BY _____

**Subject to General Declassification Schedule of
Executive Order 11652-Automatically Downgraded at
2 Year's Intervals- DECLASSIFIED ON DECEMBER 31, 1972**

BY

**Defense Documentation Center
Defense Supply Agency
Cameron Station
Alexandria, Virginia 22314**

UNCLASSIFIED AD 326 7631

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

UNCLASSIFIED

THE THERMAL BEHAVIOR OF EXPLOSIVES SUBJECTED TO SIMULATED
AERODYNAMIC HEATING, III (U)

- RELEASED TO ASTIA
BY THE NAVAL ORDNANCE LABORATORY
- Without restrictions
 - For Release to Military and Government Agencies Only.
 - Approval by BuWeps required for release to contractors.
 - Approval by BuWeps required for all subsequent release.

25 JULY 1961

NOTICE: This material contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.



U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

NAVWEPS 7363

XEROX

Downgraded at 3 Year Intervals
Declassified after 12 Years. DOD Dir 5200.10

UNCLASSIFIED

APPROVED BY ASTIA
AD No. 326783

UNCLASSIFIED

NAVWEPS Report 7363

THE THERMAL BEHAVIOR OF EXPLOSIVES SUBJECTED TO
SIMULATED AERODYNAMIC HEATING, III (U)

Prepared by:

N. L. Coleburn
B. E. Drimmer

Approved by:

S. K. ... acting
Chief, Explosion Dynamics Division

ABSTRACT: Ignition time and heat flow have been measured for six explosives, tested in one-dimensional, unconfined analogues of cylindrical, steel-cased warheads. They were unidirectionally heated at rates corresponding to aerodynamic heating associated with the sea-level flight of supersonic missiles and aircraft at low Mach numbers. With heating rates up to 100° C per minute the runaway reaction occurs as a rapid deflagration beginning on the explosive's surface touching the steel case. When a temperature of 455° C was applied to the outer surface of the 1-cm thick steel warhead case, the explosive ignition times were:

Tetryl	- 135 sec
TNT	- 164 sec
PBX N-1	- 180 sec
Pentolite	- 139 sec
H-6	- 169 sec
Composition B	- 202 sec.

PBX 9404 showed a small but inconclusive increase in impact-hammer sensitivity (the 50% point changed from 26 to 31 cm) after three thermal cycles between 20° and 200° C.

Explosions Research Department
U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

UNCLASSIFIED

UNCLASSIFIED



NAVWEPS Report 7363

25 July 1961

This report on six explosives is the third in a series which has described work done under Task RUME 3E012/212 1/FO08 10 004, Properties of Explosives (formerly called Explosives Applied Research) for the purpose of gaining a clearer understanding of the ignition behavior of explosives heated rapidly to temperatures associated with aerodynamic heating during flights of missiles and aircraft at supersonic speeds. The first report, NAVORD Report 6216, outlined the experimental approach and gave data on the plastic-bonded explosive PBX 9404, and the aluminized explosive H-6. The second, NAVWEPS Report 7338, treated work done to determine the ignition properties of the heat-resistant explosive, DATB.

W. D. COLEMAN
Captain, USN
Commander

C. J. ARONSON
By direction



UNCLASSIFIED

CONFIDENTIAL
NAVWEPS Report 7363

CONTENTS

	Page
1. INTRODUCTION	1
2. EXPERIMENTAL ARRANGEMENT	1
3. RESULTS	2
3.1 TNT	2
3.2 Pentolite	3
3.3 Tetryl	3
3.4 H-6	3
3.5 PBX N-1	3
3.6 Composition B	4
3.7 <u>Impact Sensitivity of PBX 9404 after Thermal Cycling</u>	4
4. DISCUSSION	5
5. CONCLUSIONS	5
6. ACKNOWLEDGMENTS	6
7. REFERENCES	7
8. BIBLIOGRAPHY	7

TABLES

TABLE I	Summary of Experimental Data: Heating-to-Deflagration of Explosives	9
TABLE II	Impact Sensitivity of PBX 9404 after Thermal Cycling	10

FIGURES

Figure 1	Experimental Arrangement	11
Figure 2	Thermocouple Designations	12
Figure 3	Deflagration of TNT. Initial Forcing Temperature, 456° C.	13
Figure 4	Deflagration of Pentolite. Initial Forcing Temperature, 444° C.	14
Figure 5	Deflagration of Tetryl, Sample 2. Initial Forcing Temperature, 450° C.	15
Figure 6	Deflagration of H-6. Initial Forcing Temperature, 457° C.	16
Figure 7	Deflagration of PBX N-1, Sample 1. Third Thermal Cycle. Initial Forcing Temperature, 424° C.	17
Figure 8	Deflagration of PBX N-1, Sample 2. Fourth Thermal Cycle. Initial Forcing Temperature, 455° C.	18
Figure 9	Deflagration of Composition B. Initial Forcing Temperature, 458° C.	19

CONFIDENTIAL
NAWEPs Report 7363

THE THERMAL BEHAVIOR OF EXPLOSIVES SUBJECTED TO
SIMULATED AERODYNAMIC HEATING, III (U)

1. INTRODUCTION

New problems involving the thermal response of explosives arise from the aerodynamic heating of warheads during supersonic flights of military aircraft and guided missiles. The extent of this response could readily affect the safety of aircraft and personnel, and in addition could modify seriously the performance of the heated warhead when it reaches its target. This report is the third of a series (1,2) in which we have described experimental work done to develop a clearer understanding of the ignition behavior of some of the explosives which are of interest to ordnance engineers designing such warheads.

To simplify the theoretical analysis, we have attacked these problems experimentally by designing our studies to conform to a one-dimensional heat flow problem. In this model a heat pulse is rapidly imposed over the entire surface of a steel plate (simulating the missile wall) supporting a slab of solid explosive. For at least the central portion of the system, the heat is conducted unidirectionally through the steel, into the explosive. In the present work we have obtained data for six explosives wherein the steel missile wall was subjected to an initial forcing temperature of 455° C: TNT, Pentolite, Tetryl, Composition B, H-6 and PBX N-1. In addition an impact-hammer sensitivity test was run on thermally-cycled PBX 9404 to determine if the warhead in a missile, or an externally carried aircraft bomb, subjected to elevated temperatures by aerodynamic heating and then cooling on return to base, could still be considered safe.

2. EXPERIMENTAL ARRANGEMENT

The method described in detail in reference 1 was used in the present experiments: an approximately cylindrical brass block, 30.5 cm high, 30.5 cm in diameter at its base and 25.4 cm in diameter at its top, was preheated to a given "initial forcing temperature". A 20.3-cm diameter steel disc, 1-cm thick, supporting a 17.8-cm diameter explosive disc, 2.5-cm thick, was then quickly placed on top of the brass. (A 1-cm thick replaceable copper disc, with two 0.16 cm by 0.16 cm, 8.9-cm long grooves for thermocouples on each face, was placed first on the brass just prior to the experiment.) (See Figure 1.)

CONFIDENTIAL
NAWEPs Report 7363

It was assumed that the heat flow was unidirectional along the central axis of the test explosive disc. The reasonable assumption was then made, in view of the large radius of the disc, that the heat flow was unidirectional at least out to 1.27 cm from the disc axis (i.e. for at least 14 per cent of the radius). Accordingly, small diameter (less than 0.1 cm) iron-constantan thermocouples were imbedded in the explosive at different, known depths, on the circumference of a circle 1.27-cm in radius, Figure 2. The couple leads were buried in narrow grooves machined into the disc from its periphery. Powdered explosive, the same as the test disc, was gently pressed into the grooves to hold the couples in place and to minimize the disturbance to the heat flow caused by the grooves.

3. RESULTS

The experimental data obtained for the six explosives heated to ignition are summarized in Table I. The high thermal gradient observed in the heated explosive implies that the highest temperature experienced by the non-burning explosive occurred at the steel-explosive interface, just prior to ignition. Therefore the explosive "ignition temperature" was considered to be the temperature recorded at the steel-explosive interface at the time of the visual observation or temperature-recorder indication of evidence of rapid burning. The ignition time ("cycle duration" of Table I) is the time recorded between the initial copper-steel contact and this evidence of deflagration of the explosive sample. Temperature-time profiles for the tested explosives are displayed in Figures 3 to 9. The 50% impact-hammer sensitivity test results for PBX 9404 after this explosive had been heated in three thermal cycles are listed in Table II.

The following paragraphs describe in detail the test results obtained for the individual explosives.

3.1 TNT; density = 1.62 g/cm³.

Figure 3 shows the temperature-time observations made on cast TNT under an initial forcing temperature of 456° C. This explosive was tested to study the effect of the phase change (melting point, 80.5° C) on the results. However, the experimental arrangement was such as to prevent detailed measurements of this effect. Beginning at about 45 seconds, at least some of the explosive (in contact with the steel disc) exceeded the melting point. By the time deflagration of the sample was detected, 164 seconds after steel-copper contact,

CONFIDENTIAL
NAVWEPS Report 7363

an explosive layer about 7 mm thick experienced temperatures exceeding the melting point. While steel sides had been placed around the explosive to minimize flow of the liquid phase, the density difference between the liquid and solid phases (plus some fluid flow around the solid phase) must have modified the initial experimental geometry. Thus, thermocouple E-2, starting 2 mm away from the steel interface, may have moved toward, or away from the steel by the end of the experiment.

3.2 Pentolite (PETN/TNT 50/50); density = 1.65 g/cm³.

The temperature-time profile of Figure 4 shows the deflagration of cast pentolite occurring 139 seconds after the steel outside wall of the missile was subjected to an initial forcing temperature of 444° C. The sudden rise in the temperature of the 2-mm layer at 80 seconds could be due to a geometry change affecting thermocouple TE-2; however, there are indications of possible self-heating occurring twenty seconds later, as seen by the sudden inflections in the other thermocouple recordings.

3.3 Tetryl; density = 1.61 g/cm³.

Two samples of tetryl, under initial forcing temperatures of 450° C, ignited in 132 seconds for one sample, and 138 seconds for the other, at which time the steel-tetryl interface reached 221 ± 2° C. Typical results are shown in Figure 5; when this sample deflagrated, the temperature at the 2-mm depth was only 110° C.

3.4 H-6 (RDX/TNT/Al/Wax - 47/31/22/5); density = 1.75 g/cm³.

In Figure 6, the erratic behavior of thermocouple TE-1 (indicated by the broken line) is probably due to the melting of TNT, a major component of H-6. Under an initial forcing temperature of 457° C, the steel-H-6 interface was heated rapidly from its initial temperature of 10° C to 200° C in two minutes. When the sample deflagrated at 169 seconds, the interface temperature had reached 231° C while the interior of the explosive was still relatively cool, thermocouple TE-7 recording only 40° C.

3.5 PBX N-1 (RDX/Al/Nylon - 66/25/9); density = 1.77 g/cm³.

The heating curves for these two samples are shown in Figures 7 and 8. Sample 1, heated with an initial forcing temperature of 424° C, deflagrated after 270 seconds (Figure 7). Sample 2, driven with an initial forcing temperature of 455° C

CONFIDENTIAL
NAWEPs Report 7363

(Figure 8) deflagrated after only 180 seconds. The steel-explosive interface temperatures at ignition, for both tests were within 4° C of 216° C indicating that the previous history of the samples played only a minor role in determining their ignition temperatures (Sample 1 had received two 5-minute thermal cycles under forcing temperatures of 100° C and 200° C; while Sample 2 received three thermal cycles: 100°, 200°, and 300° C).

3.6 Composition B (RDX/TNT/Wax - 60/40/1); density = 1.68 g/cm³.

Some of the thermocouples in this test "misbehaved", as shown in Figure 9. It is not clear exactly why thermocouple TE-2 held steady at 80° C for about 30 seconds, and at the same time TE-3 held steady at about 70° C for about 50 seconds. It would be tempting to explain the 80° plateau as due to the melting of TNT; however, during the test of TNT alone, Figure 3, no such plateau was observed. Another mystery is the unusually high ignition temperature, 285° C, reached at the steel-explosive interface. This compares with the 226° C ($\pm 5^\circ$ C) observed for the other TNT-based explosives tested in this series. An examination of the records, instruments, calibrations showed all in order; nevertheless the shape of the heating curves, coupled with the unusual temperatures observed, leads one to place a low level of reliance on these Composition B results.

3.7 Impact Sensitivity of PBX 9404 after Thermal Cycling.

Impact-hammer sensitivity tests were run on PBX 9404 in an effort to measure the change in shock sensitivity due to thermal cycling. Two samples were heated in the same geometry as in the above deflagration tests, until the steel-explosive interface reached about 180° C, at which time the test rig was raised from the brass block. Heating of the samples was repeated one day apart, for three cycles, after which time several grams of explosive were obtained from the upper and lower surfaces of the explosive discs. The 50% impact-hammer sensitivity heights are compared in Table II, with a sample of PBX 9404 that had not been heated. No difference in sensitivity was observed between the top or bottom (hotter) parts of the test disc: one sample had 50% impact heights of 29 cm, the other 33 cm. These are slightly higher than the 26 cm obtained for the unheated material, a value which agrees with previous NOL data (3) for this explosive.

CONFIDENTIAL
NAWWEPS Report 7363

4. DISCUSSION

In our tests the surfaces of the unconfined explosive were heated rapidly (up to 100° C per minute). The resulting rapid temperature rise affected an explosive layer only a few millimeters thick, so that at the time of ignition, most of the explosive had experienced relatively small increases in temperature.

Evidence of self-heating was not clearly defined. The heating curves for Pentolite and Composition B (Figures 4 and 9) contain curves which might be interpreted as due to self-heating. However, since ignition occurred well after the temperatures in the first few millimeters of explosive were significantly above the melting point of TNT, possible motion of the couples within the liquid phase could have caused the erratic behavior of the temperatures. Tetryl (melting point = 129° C) burned rapidly when the temperatures within the first 2-mm explosive layer were between 110° C and 230° C, showing that its runaway reaction also began within the liquid phase.

When H-6 and PBX N-1 (sample 2) were heated at the same rate, the ignition times of the two explosives, 175 seconds (± 5 seconds), and ignition temperatures 225° C (± 5 ° C) were essentially the same. These data indicate that these aluminized explosives are reasonably similar in their responses to such thermal shocks.

On the other hand, in the test with Composition B (which differs from H-6 only in aluminum content) the steel-explosive interface thermocouple recorded 225° C approximately 80 seconds sooner than in the case of H-6. The higher thermal conductivity of the aluminized explosive is believed to be responsible for this time difference.

Comparison of the impact test results of 29 cm and 33 cm for the two thermally cycled PBX 9404 samples, with the 26.4 cm obtained for the control sample, indicates a small decrease in sensitivity due to such cycling. However, the standard deviations were too large to permit a firm conclusion that the change had resulted from thermal cycling.

5. CONCLUSIONS

In these tests ignition of the unconfined explosive usually began as a runaway reaction at the steel-explosive interface. This reaction was a rapid burning which, in our

CONFIDENTIAL
NAVWEPS Report 7363

tests, never built up to a detonation. With the high rates of heat input used in these tests, the explosive layers more than 3 or 4 mm from the surface experienced relatively little temperature rise before ignition. This confirms our previous conclusion (1) that deflagration of the explosive may be significantly delayed by an insulator layer only one or two millimeters thick. It also suggests the important safety concept that detonation probabilities in a fire could be minimized by designing ordnance to have minimum confinement during the fire, thus permitting a deflagration to consume the explosive; blowout plugs or other gas-venting systems might be useful for this purpose.

Under an initial forcing temperature of 450°C , deflagration of tetryl and pentolite occurred at essentially the same time, 135 (± 4) seconds, at which time the final steel-explosive interface temperatures were 221°C ($\pm 2^{\circ}\text{C}$). TNT lasted 164 seconds under these same thermal conditions, with T_{S-E} recording 225°C . Composition B burned in 202 seconds, with the final interface temperature at an unexpected high of 285°C .

H-6 and PBX N-1 exhibited similar thermal characteristics, (neglecting the phase change of TNT in H-6), each deflagrating in 175 ± 5 seconds, under an initial forcing temperature of 455°C .

Increasing the thermal conductivity of explosives by adding aluminum results in an increase in the time required for the steel-explosive interface temperature to attain higher temperatures. (Thus the Composition B-steel interface reached 225°C eighty seconds sooner than the H-6-steel interface.)

The 50% impact sensitivity height of two PBX 9404 samples after repeated thermal cycling to about 180°C were 29 and 33 cm. This small increase over the 26-cm impact height for normal unheated samples cannot be considered statistically significant.

6. ACKNOWLEDGMENTS

The assistance of E. A. Duck in preparing the experimental arrangements and conducting the tests, and the cooperation of H. Heller and S. Duck who made the impact-hammer sensitivity measurements, are noted with thanks.

CONFIDENTIAL
NAWWEPS Report 7363

7. REFERENCES

1. N. L. Coleburn and B. E. Drimmer; "The Thermal Behavior of Explosives to Simulated Aerodynamic Heating, I (U)"; NAVORD Report 6216; 15 Oct 1959, (Confidential).
2. N. L. Coleburn and B. E. Drimmer; "The Thermal Behavior of Explosives to Simulated Aerodynamic Heating, II: DATB"; NAWWEPS Report 7338 (in publication), (Confidential).
3. H. Heller; NOL, Informal Communication.

8. BIBLIOGRAPHY

1. G. C. Cook; Proceedings of the Royal Society, A 246, 154 (1958).
2. J. W. Enig; "A Method for the Rapid Numerical Solution of the Heat Conduction Equation for Composite Slabs"; NAVORD Report 6666; 20 Aug 1959, (Unclassified).
3. K. G. Shipp and M. E. Hill; "Heat Resistant Explosives II; 1,3-Diamino-2,4,6 Trinitrobenzene; DATB"; NAVORD Report 6016; 31 Mar 1958, (Confidential).
4. J. R. Holden, A. H. Rosen, and J. M. Rosen; "Heat Resistant Explosives VI; Properties of 1,3-Diamino-2,4,6-Trinitrobenzene; DATB"; NAVORD Report 6299; 17 Mar 1959, (Confidential).
5. N. L. Coleburn, B. E. Drimmer, and T. P. Liddiard; "The Detonation Properties of DATB (1,3-Diamino-2,4,6-Trinitrobenzene) (U)"; NAVORD Report 6750; 12 Oct 1960, (Confidential).
6. Translation Report No. F-78 3110-RE; "Heat Insulation of Outer Casing of a Missile to Avoid Decomposition of the Explosive Charge"; Headquarters Air Material Command, Wright Field, Dayton, Ohio.
7. R. J. Finkelstein and G. Gamow; "Theory of the Detonation Process"; NAVORD Report 90-46; 20 Apr 1947.

CONFIDENTIAL
NAVWEPS Report 7363

BIBLIOGRAPHY (Cont'd.)

8. H. A. Strecker and E. C. Broge; "The Effect of Heat on Confined Explosives"; OSRD 3956; 5 Jun 1947.
9. "Explosion Effects Data Sheets"; NAVORD Report 2986, Change 1; 14 Jun 1955.
10. G. Riel, R. H. F. Stresau, and W. M. Slie; "Cook-off Studies of the Booster XW-7 and Variants"; NAVORD Report 4383; 15 Oct 1957.
11. "Investigations for Improving the Usefulness of High Explosives at Elevated Temperatures"; Contract NORD 17881, Report No. 0136-01-1; Explosive Ordnance Division, Aerojet-General Corporation, Azusa, California; 23 May 1958.
12. N. Jacob; "Heat Transfer", Vol. II; John Wiley and Sons, Inc., New York; 1957.
13. G. Brown, C. Hoyler, and R. Bierwirth; "Theory and Application of Radio-Frequency Heating"; D. Van Nostrand Co., Inc.; 1947.

TABLE I
 Summary of Experimental Data: Heating-to-Deflagration of Explosives

Explosive Sample	Fig. No.	Thermal Cycle	Cycle Duration (sec)	Initial Temp. °C	Initial Forcing Temp. °C (T _{cu})	Final Forcing Temp. °C (T _{cu})	Final Steel Wall Temp. °C (T _{cu-s})	Final Steel Explosive Interface Temp. °C (T _{s-e})
TNT	3	1	164	13	456	390	290	225
Pentolite	4	1	139	23	444	360	230	222
Tetryl (Sample No. 1)	-	1	138	20	450	385	230	220
Tetryl (Sample No. 2)	5	1	132	28	450	369	235	223
H-6	6	1	169	14	457	350	244	231
PBX N-1 (Sample No. 1)	7	3	270	7	424	344	224	212
PBX N-1 (Sample No. 2)	8	4	180	10	455	365	260	220
Composition B	9	1	202	15	458	362	300	285

TABLE II
 Impact Sensitivity of PBX 9404 after Thermal Cycling

Explosive Sample	Thermal Cycle	Cycle Duration (sec)	Initial Temp (°C)	Final Steel-Explosive Interface Temp. (°C)	Final Temp. at Sample Top (°C)	50% Impact Sensitivity (cm)
1	First	203	7	190	31	- - -
1	Second	135	3	175	21	- - -
1	Third	130	14	180	24	Recovered Top: 29 cm ($\sigma = \pm 0.14$ log units) Bottom: 29 cm ($\sigma = \pm 0.09$ log units)
2	First	200	5	160	27	- - -
2	Second	270	10	170	31	- - -
2	Third	261	10	170	32	Recovered Top: 33 cm ($\sigma = \pm 0.07$ log units) Bottom: 33 cm ($\sigma = \pm 0.12$ log units)
3	- -	- -	-	- -	- -	26 cm ($\sigma = \pm 0.07$ log units)




FIG. 1 EXPERIMENTAL ARRANGEMENT




FIG. 2 THERMOCOUPLE DESIGNATIONS




FIG. 3 DEFLAGRATION OF TNT. INITIAL FORCING TEMPERATURE, 456°C.




FIG. 4 DEFLAGRATION OF PENTOLITE. INITIAL FORCING TEMPERATURE, 444 °C.




FIG. 5 TETRYL. DEFLAGRATION OF SAMPLE 2.
INITIAL FORCING TEMPERATURE, 450°C.

CONFIDENTIAL
NAWEPs REPORT 7363




FIG. 6 H-6. DEFLAGRATION OF SAMPLE I.
INITIAL FORCING TEMPERATURE,
457 °C.




FIG. 7 PBX N-1. DEFLAGRATION OF SAMPLE I.
THIRD THERMAL CYCLE. INITIAL FORCING
TEMPERATURE, 424°C.




FIG. 8 PBX N-1 DEFLAGRATION OF SAMPLE 2.
FOURTH THERMAL CYCLE. INITIAL FORCING
TEMPERATURE, 455°C.




FIG. 9 DEFLAGRATION OF COMPOSITION B.
INITIAL FORCING TEMPERATURE, 458°C.

DISTRIBUTION LIST

	Copies
Chief, Bureau of Naval Weapons	
Department of the Navy	
Washington 25, D. C.	
DIS-32	2
RRRE-5	1
RUME-11	1
RUME-32	1
RMMO-5	1
Director, Special Projects Office	
Department of the Navy	
Washington 25, D. C.	
SP	1
Chief, Bureau of Ships	
Department of the Navy	
Washington 25, D. C.	1
Chief of Naval Research	
Department of the Navy	
Washington 25, D. C.	
Chemistry Branch	2
Commander, Operational Development Force	
U. S. Atlantic Fleet	
U. S. Naval Base	
Norfolk 11, Virginia	2
Commander, U. S. Naval Ordnance Test Station	
China Lake, California	
Code 556	1
Code 4572	1
Technical Library	2
Director, David Taylor Model Basin	
Carderock, Maryland	
Dr. A. H. Keil	2
Commander, U. S. Naval Weapons Laboratory	
Dahlgren, Virginia	
Technical Library	2
Weapons Laboratory	1
Terminal Ballistics Laboratory	1

DISTRIBUTION LIST (Cont'd.)

	Copies
Commander, Norfolk Naval Shipyard Portsmouth, Virginia Underwater Explosions Research Division	2
Commanding Officer, U. S. Naval Weapons Station Yorktown, Virginia R & D Division	2
Commanding Officer, U. S. Naval Ordnance Laboratory Corona, California	2
Commanding Officer, U. S. Naval Propellant Plant Indian Head, Maryland Technical Library	1
EODTC	1
Commander, Naval Radiological Defense Laboratory San Francisco, California Ruth Schneider	1
Commanding Officer, U. S. Naval Ordnance Plant Macon, Georgia	1
Commanding Officer, Naval Ammunition Depot Crane, Indiana	1
Commanding Officer, U. S. Naval Ammunition Depot Navy Number Six Six (66) c/o Fleet Post Office San Francisco, California Quality Evaluation Laboratory	1
Commanding Officer, U. S. Naval Weapons Evaluation Facility Kirtland Air Force Base Albuquerque, New Mexico	1
Office of Chief of Ordnance Department of the Army Washington 25, D. C. ORDGU	1
ORDTB	1
ORDTN	1
Commander, Army Rocket and Guided Missile Agency Redstone Arsenal, Alabama ORDXR-FH	1

UNCLASSIFIED

DISTRIBUTION LIST (Cont'd.)

Copies

Commanding General, Picatinny Arsenal
 Dover, New Jersey

ORDBB-TH8, Technical Information	1
ORDBB-TJ1, H. E. Section	1
ORDBB-TK3, Prep. and Expl. Unit	1
ORDBB-TM1, Chem. Res. Section	1
ORDBB-TP1, Proj. Fuze Section	1
ORDBB-TP2, GM, Rkt. and Bomb Fuze	1
ORDBB-TP3, Init. and Spec. Dev.	2
ORDBB-TR2, Phys. Res. Section	1
ORDBB-TS1, Pyrotech. Lab.	1

Commanding Officer, Diamond Ordnance Fuze Laboratory
 Connecticut Avenue & Van Ness Street, N.W.
 Washington 25, D. C.

Ordnance Development Laboratory	1
M. Lipnick (Code 005)	1

Commanding Officer, Engineer Research & Development Laboratory
 U. S. Army, Ft. Belvoir, Virginia

Technical Intelligence Branch	1
---	---

Commanding General, U. S. Army Proving Ground
 Aberdeen, Maryland

Technical Library	1
Dr. R. J. Eichelberger	1
M. Sultanoff	1

Commanding General, Redstone Arsenal
 Huntsville, Alabama

Technical Library	1
-----------------------------	---

Commanding Officer, Chemical Corps
 Chemical & Radiological Laboratory
 Army Chemical Center, Maryland

	1
--	---

Commanding Officer
 Fort Dietrick, Maryland

	1
--	---

Commanding General, U. S. Army Ordnance Ammunition Center
 Joliet, Illinois

	1
--	---

Commanding Officer, Holston Ordnance Works
 Kingsport, Tennessee

	1
--	---

Commanding General, White Sands Proving Ground
 White Sands, New Mexico

	1
--	---



UNCLASSIFIED

UNCLASSIFIED

DISTRIBUTION LIST (Cont'd.)

	Copies
Commanding Officer, Office of Ordnance Research Box CM, Duke Station Durham, North Carolina	1
Chief of Staff U. S. Air Force Washington 25, D. C. AFORD-AR	1
Commander, Wright Air Development Center Wright-Patterson Air Force Base Dayton, Ohio WWAD	2
Headquarters, Air Proving Ground Center U. S. Air Force, ARDC Eglin Air Force Base, Florida PGTRI, Technical Library	1
Commander, Air Research & Development Command Andrews Air Force Base Washington 25, D. C.	1
Commanding Officer, Air Force Missile Test Center Patrick Air Force Base, Florida	1
Commander, Air Force Cambridge Research Center L. G. Hanscom Field Bedford, Massachusetts	1
Armed Services Technical Information Agency Arlington Hall Station Arlington 12, Virginia	10
Chief, Defense Atomic Support Agency Washington 25, D. C.	5
Atomic Energy Commission Washington 25, D. C. DMA	1
Director, U. S. Bureau of Mines Division of Explosive Technology 4800 Forbes Street Pittsburgh 13, Pennsylvania Dr. R. W. Van Dolah	1



UNCLASSIFIED

UNCLASSIFIED

DISTRIBUTION LIST (Cont'd.)

Copies

National Aeronautics & Space Administration
Headquarters
1520 H Street, N. W.
Washington 25, D. C. 1

National Aeronautics & Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 1

Director, USAF Project RAND
(Via USAF Liaison Office)
The Rand Corporation
1700 Main Street
Santa Monica, California
Librarian 1

Lawrence Radiation Laboratory
University of California
P. O. Box 808
Livermore, California
Technical Information Division 1
Dr. C. Godfrey 1
Dr. J. Kury 1

Director, Los Alamos Scientific Laboratory
P. O. Box 1663
Los Alamos, New Mexico
Library 1

Director, Applied Physics Laboratory
John Hopkins University
8621 Georgia Avenue
Silver Spring, Maryland 2
Solid Propellants Agency 1

Commander
Air Force Special Weapons Center
Kirtland Air Force Base
Albuquerque, New Mexico 1

UNCLASSIFIED

Naval Ordnance Laboratory, White Oak, Md.
(NAVWEPS report 7363)
THE THERMAL BEHAVIOR OF EXPLOSIVES SUB-
JECTED TO SIMULATED AERODYNAMIC HEATING, III
(U), by N.L. Coleburn and B.E. Drimmer.
25 July 1961. 10p. charts, tables. Task
RUMC 3E012/212 1/FOCS 10 004. CONFIDENTIAL

1. Explosives - Aerodynamic heating
2. Explosives - Ignition
3. Tetryl
4. PEX N-1
5. Pentolites
6. Explosives - H-6
7. Explosives - Composition B
- I. Title
- II. Coleburn, Nathaniel L.
- III. Drimmer, Bernard E., jt. author
- IV. Project

Ignition time and heat flow have been measured for six military explosives, tested in one-dimensional, unconfined analogues of cylindrical, steel-cased warheads. When a temperature of 455°C was applied to the outer surface of the 1-cm thick warhead case, the explosive ignition times (in seconds) were:
Tetryl -- 135 TNT -- 164 PEX N-1 -- 180
Pentolite -- 139 H-6 -- 169 Comp B -- 202

Abstract card is confidential
DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS. DOD DIR 5200.10

Naval Ordnance Laboratory, White Oak, Md.
(NAVWEPS report 7363)
THE THERMAL BEHAVIOR OF EXPLOSIVES SUB-
JECTED TO SIMULATED AERODYNAMIC HEATING, III
(U), by N.L. Coleburn and B.E. Drimmer.
25 July 1961. 10p. charts, tables. Task
RUMC 3E012/212 1/FOCS 10 004. CONFIDENTIAL

1. Explosives - Aerodynamic heating
2. Explosives - Ignition
3. Tetryl
4. PEX N-1
5. Pentolites
6. Explosives - H-6
7. Explosives - Composition B
- I. Title
- II. Coleburn, Nathaniel L.
- III. Drimmer, Bernard E., jt. author
- IV. Project

Ignition time and heat flow have been measured for six military explosives, tested in one-dimensional, unconfined analogues of cylindrical, steel-cased warheads. When a temperature of 455°C was applied to the outer surface of the 1-cm thick warhead case, the explosive ignition times (in seconds) were:
Tetryl -- 135 TNT -- 164 PEX N-1 -- 180
Pentolite -- 139 H-6 -- 169 Comp B -- 202

Abstract card is confidential
DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS. DOD DIR 5200.10

Naval Ordnance Laboratory, White Oak, Md.
(NAVWEPS report 7363)
THE THERMAL BEHAVIOR OF EXPLOSIVES SUB-
JECTED TO SIMULATED AERODYNAMIC HEATING, III
(U), by N.L. Coleburn and B.E. Drimmer.
25 July 1961. 10p. charts, tables. Task
RUMC 3E012/212 1/FOCS 10 004. CONFIDENTIAL

1. Explosives - Aerodynamic heating
2. Explosives - Ignition
3. Tetryl
4. PEX N-1
5. Pentolites
6. Explosives - H-6
7. Explosives - Composition B
- I. Title
- II. Coleburn, Nathaniel L.
- III. Drimmer, Bernard E., jt. author
- IV. Project

Ignition time and heat flow have been measured for six military explosives, tested in one-dimensional, unconfined analogues of cylindrical, steel-cased warheads. When a temperature of 455°C was applied to the outer surface of the 1-cm thick warhead case, the explosive ignition times (in seconds) were:
Tetryl -- 135 TNT -- 164 PEX N-1 -- 180
Pentolite -- 139 H-6 -- 169 Comp B -- 202

Abstract card is confidential
DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS. DOD DIR 5200.10