

UNCLASSIFIED

AD NUMBER	
AD361253	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Distribution: Further dissemination only as directed by Director, Naval Research Laboratory, Washington, DC 20390, 12 MAY 1965, or higher DoD authority.
AUTHORITY	
OPNAVINST 5510.1h, 29 Apr 1988, per document marking, NRL Code/1221; NRL Code/1221 ltr dtd 30 Nov 1995	

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD NUMBER
AD361253
CLASSIFICATION CHANGES
TO
confidential
FROM
secret
AUTHORITY
31 May 1977, per document marking, DoDD 5200.10

THIS PAGE IS UNCLASSIFIED

AD

3 6 1 2 5 3 L

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



SECRET

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOTICE:

THIS DOCUMENT CONTAINS INFORMATION
AFFECTING THE NATIONAL DEFENSE OF
THE UNITED STATES WITHIN THE MEAN-
ING OF THE ESPIONAGE LAWS, TITLE 18,
U.S.C., SECTIONS 793 and 794. THE
TRANSMISSION OR THE REVELATION OF
ITS CONTENTS IN ANY MANNER TO AN
UNAUTHORIZED PERSON IS PROHIBITED
BY LAW.

5323 A

NRL Report 6272
Copy No. 192

Extended-Range Aircraft Tracking [Unclassified Title]

J. L. AHEARN, W. C. HEADRICK, J. M. HEADRICK,
C. B. TESAURO, AND E. N. ZETTLER


*Radar Techniques Branch
Radar Division*

May 12, 1965

AD 361253
Comp. 1/10/00

DECLASSIFIED by authority of
OPNAVINST 5510.114, 29 April 88
Site Authority Date
C-266615 11-30-95 1221
Entered by NRL Code

UNCLASSIFIED



U.S. NAVAL RESEARCH LABORATORY
Washington, D.C.

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

SECRET

SECURITY

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

DDC AVAILABILITY NOTICE

All distribution of this report is controlled. Qualified DDC users shall request through Director, U.S. Naval Research Laboratory, Washington, D.C. 20390.

SECRET

SECRET

CONTENTS

Abstract	ii
Problem Status	ii
Authorization	ii
INTRODUCTION	1
EXPERIMENTAL RESULTS	1
APPARENT ECHCING CROSS SECTION	6
COMMENTS	10
REFERENCES	11
DISTRIBUTION	12

SECRET

ABSTRACT**[Secret]**

As part of the evaluation of the Madre radar system at the Chesapeake Bay Annex of the Naval Research Laboratory, data on a number of controlled over-the-horizon aircraft flights have been taken. Of particular interest is a flight which took place on 29 November 1962. The plane was a P3V (similar to the commercial Electra) and it was flying at an altitude of 24,000 ft from Lajes, Azores, to Norfolk, Virginia. The radar operated at 18.036 Mc/s with 4.6 Mw peak power. The plane was tracked over a great circle ground range from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case.

PROBLEM STATUS

This is an interim report on one phase of the problem; work is continuing on this and other phases.

AUTHORIZATION

NRL Problem R02-23
Projects RF 001-02-41-4007, and
AF MIPR (30-602) 63-2928, (30-602) 63-2929,
and (30-602) 63-2995

Manuscript submitted March 11, 1965.

EXTENDED-RANGE AIRCRAFT TRACKING [Unclassified Title]

INTRODUCTION

A part of the Naval Research Laboratory high-frequency radar mission is to furnish feasibility and specification data for the extension of radar range by using ionospheric refraction. The installation, located at the Chesapeake Bay Annex (CBA) of the Naval Research Laboratory (NRL), is a high-power, coherent, pulse doppler system (1) which employs earth-backscatter rejection filters able to handle in excess of 70-db clutter-to-signal ratios (2). After clutter filtering, a zero frequency i-f is sampled and stored with range segregation on a magnetic drum or disk using a packing ratio of 82,800 to 1. The previous 20 sec of signal information is continuously available for study in each 1/180-sec interval because of the time compression. The form of analysis used for the results given herein consists of a complete doppler-versus-range analysis for each time period of 1.8 sec. The resolution bandwidth is the equivalent of 1/3 cps (3,4).

In this report, radar display data taken of a flight made specifically for NRL use is given. The flight took place on 29 November 1962. The aircraft was a P3V (similar to the commercial Electra), and it flew at an altitude of 24,000 ft from Lajes, Azores, to Norfolk, Virginia. Radar tracking was performed between great circle ground ranges of 1978 naut mi and 1391 naut mi from the Chesapeake Bay Annex of NRL. Apparent aircraft echoing cross sections for this P3V are given, and the variations in apparent echoing area are discussed.

EXPERIMENTAL RESULTS

During the controlled P3V flight of 29 November 1962, the radar operated on 18.036 Mc/s with 4.6 Mw peak power, 60 kw average power, and a free-space antenna gain of 19.6 db. Figure 1 shows an amplitude-vs-range distribution of earth backscatter, in the direction of the flight, that was obtained during the test. The higher level backscatter extends from 975 naut mi to about 2000 naut mi, and this is the region in which the flight was tracked.

Figures 2(a) and (b) show a sequence of range-velocity-intensity display scans during the portion of the flight from about 12:18:09 p.m. to 12:32:09 p.m. EST. Time after 12:15 p.m. is indicated below each frame in minutes and seconds. The ordinate in each frame indicates doppler frequency (from which we obtain velocity) from 0 to 45 cps, while the abscissa indicates approximate radar range from 1350 to 1800 naut mi. Range and range-rate strobes are used for precise target logging. The P3V return appears at (200,18) in the first frame of Fig. 2(a), and a calibration signal appears at (240,12). The target moves to (90,18) in the last frame of Fig. 2(b). During this 14-min period the radar range measured by the range strobe changes by 80 naut mi. This corresponds to a range rate of 343 knots. The average range-rate strobe reading during the same time was 347 knots.

Figure 3 shows the P3V apparent radar cross section as the plane closed in range. The equation used to find the cross section is

$$\sigma = \frac{4\pi R^4 P_r}{G^2 P_t}$$




Fig. 1 - Amplitude-vs-range distribution of earth backscatter during P3V flight of 29 Nov. 1962

where P_r and P_t are the received and transmitted powers, respectively, R is the slant range to the target, and G is the maximum one-way antenna gain (25.6 db). This equation does not take into account any loss, other than spreading loss, due to transmission in the medium. Computed cross-section values will be lower than those resulting if the medium loss factor were included. The task of even roughly presenting loss figures in the medium for the paths involved in long-distance over-the-horizon (OTH) detections is far from simple, and such losses have been ignored. The dashed portions of Fig. 3 indicate times when the radar was inoperative. Received signal amplitudes are taken every minute; in ten cases the echo was not present at the reading time. These cases correspond to zero cross section and are carried as such in computing average and median values. The zero cross-section values are plotted on Fig. 3 along the base line, which corresponds to a cross section of 10 sq m. The median value for the radar cross section is 370 sq m and the average is 760 sq m. In computing, a maximum available antenna gain of 25.6 db is used since 6 db is added to the free-space gain of 19.6 db to account for placement of the antenna over ground. There will be times when the target energy doesn't come into the antenna on the nose of a lobe, and again the computed target cross section will be lower than if the actual antenna gain had been used.

Fig. 4(a) shows a doppler time history of the 6-min portion of this P3V flight when the plane was in the 1570-naut-mi slant range region. For this type of presentation the incoming signals are range gated with a 300-sec gate which moves with the target. The aircraft doppler track appears as a broken line. This technique allows one to observe the target situation from minutes in the past until the present time and, in this respect, it gives a doppler time history of the target.




Fig. 2(a) - Sequence of range-velocity-intensity display scans for P3V flight.
Primary display of flight from 12:18:09 to 12:25:14 p.m. EST.




Fig. 2(b) - Sequence of range-velocity-intensity display scans for P3V flight.
Primary display of flight from 12:25:40 to 12:32:00 p.m. EST.






Fig. 3 - Radar cross section during P3V flight



(a)



(b)

Fig. 4 - Doppler time history plots of (a) P3V aircraft and (b) an aircraft detected during AMR test 3797

Figure 4(b) is another example of this type of analysis. It shows 3 min of doppler time history for an aircraft observed while the radar was set up for observation of AMR test 3797, the A2 Polaris launch of 23 August 1963. In this analysis mode the incoming signals are range gated with a $225\text{-}\mu\text{sec}$ gate. The aircraft track appears as a broken line in the 20-cps doppler region. The range gate ran from 740 to 758 naut mi and was in an optimum position for this aircraft, but the gate was out too far in range for the best missile effect. The missile signature shows after 60 sec and smears upward past the essentially horizontal aircraft track. The doppler time history technique allows one to observe the target situation from minutes in the past until the present time.

Figure 5 compares aircraft great-circle over-the-ground range to CBA, as derived from the navigator's position reports, with slant range taken from the radar display. The difference between slant range and ground range can be estimated roughly with data such as given in Fig. 1, and it can be estimated more precisely with complete knowledge of the prevailing ionospheric conditions.

The P3V data given above were taken on a transatlantic path at times when few other targets were present. It is of interest to show a radar display taken when viewing an area of greater aircraft population. Figure 6 shows aircraft returns on the radar doppler-range display when looking over the continental USA. This observation was a by-product of a setup for the observation of a West Coast missile launch and was made with a smaller gain antenna. Operating parameters for this setup were as follows:

Operating frequency - 18.036 Mc/s
Antenna bearing - 279° (i.e., looking west from NRL-CBA)
Antenna - 3 db, beamwidth 30° , free-space gain 11.6 db
Power output - 100 kw (average)
Pulse repetition frequency (prf) - 90 per sec
1st-hop backscatter range - 1000 naut mi to 1950 naut mi
Date and time - 12/13/63, 3:35 p.m. EST.

The receiver was gated on for the range intervals 450-900, 1350-1800, 2250-2700, etc., naut mi. The backscatter conditions indicated that the observed returns could only come from the 1350 to 1800-naut-mi ranges. Figure 6 shows doppler frequency along the ordinate, from 0 to 45 cps, and the range from 1350 to 1800 naut mi is shown along the abscissa. The large signal at 30 cps and 1700 naut mi is a calibration signal which corresponds to a 10-V peak-to-peak signal at the antenna terminals. A target giving the same signal strength at this range would have a cross section of $1.156 \cdot 10^4$ sq m for an antenna gain 6 db above the 11.6-db free-space gain. There are at least nine aircraft echoes in this display, which encompasses a range depth of 450 naut mi, situated west of Denver, Colorado, with azimuthal coverage from Helena, Montana, in the north to White Sands, New Mexico, in the south.

APPARENT ECHOING CROSS SECTION

A discussion of transmission medium effects upon apparent echoing cross section may be helpful in studying the aircraft detection problem. Three idealized cases will be treated.




Fig. 5 - Navigator-reported over-the-ground range compared with radar slant range for P3V flight




Fig. 6 - Aircraft targets viewed over interior of continental USA with radar facility at CBA

Case I: Consider an antenna and a target in free space with the antenna being used for both transmitting and receiving (Fig. 7(a)). The power density S_t at the target is $S_t = P_t G_a / (4\pi R^2)$ where P_t is the power into the antenna, G_a is the free-space gain of the antenna, and R is the range to the target. The power density S_r at the antenna due to the echo from the target is $S_r = S_t \sigma / (4\pi R^2)$ where σ is the target echoing cross section. The cross section for the free-space condition will be used to define $\sigma_0 = 4\pi R^2 S_r / S_t$. Since $S_t = P_t / A$, where P_t is

power available for the receiver and $A = G_o \lambda^2 / 4\pi$ is the capture area of the antenna with λ being the wavelength,

$$\sigma_o = \frac{4\pi R^2 S_r}{S_t} = \frac{P_r (4\pi)^3 R^4}{P_t G_o^2 \lambda^2}$$

Case II: For this case the same antenna and target are placed over a conducting surface. The antenna orientation is such that maximum gain is parallel to the conducting surface. In Fig. 7(b) radiation from the antenna at A can reach the target at P by the path AP and by path ABP. Assuming that no loss occurs from the reflection at B and that $ABP = AP \ll AP$, the electric field at P will be twice the free-space value E_o when the electrical path length ABP differs from AP by $n\lambda$ and will be zero when the path length difference is $(n + 1/2)\lambda$. As the elevation angle ϕ is increased from zero to 90 degrees, the number of maxima where the field is $2E_o$ is $2h/\lambda$ where h is the antenna height. Since power is proportional to E^2 , the maximum power density at P is $S = (2E_o)^2$, or four times the free-space value. Applying the same argument to the echo paths from the target to the receiver gives another increase in power by a factor of four. Thus, to calculate σ_o , $4G_o$ would be used in the place of G_o when P is at a point of maximum field.

Case III: In this case the target is placed over the horizon and is illuminated via the ionosphere. Figure 7(c) shows the target illuminated by four different paths, and if the four are in phase, $S_t = (4E_o)^2 = 16E_o^2$. On the return to the receiving antenna, another increase by a factor of sixteen with respect to the free-space case would be realized. To calculate σ_o in an idealized lossless situation where the radiation arrived at the target in phase, $16G_o$ would be used in the place of G_o .




Fig. 7 - Geometrically distinct paths for (a) free-space, (b) line-of-sight, and (c) OTH propagation

The NRL antenna used in tracking aircraft over the horizon has a comparatively narrow beamwidth in the horizontal plane, but it has free-space directivity in the vertical plane of 12.5 to 25 degrees between the 3-db points over the design frequency range. The antenna height of 166 ft gives a fairly small number of lobes in the vertical plane. The 3-db points of the lowest two lobes are probably 4 degrees apart, yet they illuminate a ground range hundreds of miles in extent via the ionosphere.

A different situation exists at the target end of the OTH path. Here the target is usually thousands of feet above the earth's surface, and lobe structure due to target height above the earth is quite extensive. For example, for an aircraft flying at 24,000 ft, an operating frequency of 18.036 Mc/s would give 880 lobes in the vertical plane. With a moderately fast aircraft, target returns could easily go through maxima and minima at the rate of one per minute. The effective cross section computed from the amplitude of OTH aircraft echoes would vary, due to this cause alone, from a zero value to a value 24 db greater than σ_0 .

Based on a simplified model, i.e., considering only spreading loss and four (ideal) paths, Fig. 8 shows how the power received from an OTH target will vary as a function of over-the-ground target range for the four-path case. The free-space reference is a hypothetical, single, free-space path which does not involve any ground or ionospheric reflection. The




Fig. 8 - Computed received power ratio as a function of target over-the-ground range: (a) target at 24 and 1 kft, and (b) expanded graph of target at 1-kft height. Transmitting antenna height was chosen as 166 ft and ionospheric height as 300 km.

The NRL antenna used in tracking aircraft over the horizon has a comparatively narrow beamwidth in the horizontal plane, but it has free-space directivity in the vertical plane of 12.5 to 25 degrees between the 3-db points over the design frequency range. The antenna height of 166 ft gives a fairly small number of lobes in the vertical plane. The 3-db points of the lowest two lobes are probably 4 degrees apart, yet they illuminate a ground range hundreds of miles in extent via the ionosphere.

A different situation exists at the target end of the OTH path. Here the target is usually thousands of feet above the earth's surface, and lobe structure due to target height above the earth is quite extensive. For example, for an aircraft flying at 24,000 ft, an operating frequency of 18.036 Mc/s would give 880 lobes in the vertical plane. With a moderately fast aircraft, target returns could easily go through maxima and minima at the rate of one per minute. The effective cross section computed from the amplitude of OTH aircraft echoes would vary, due to this cause alone, from a zero value to a value 24 db greater than σ_0 .

Based on a simplified model, i.e., considering only spreading loss and four (ideal) paths, Fig. 8 shows how the power received from an OTH target will vary as a function of over-the-ground target range for the four-path case. The free-space reference is a hypothetical, single, free-space path which does not involve any ground or ionospheric reflection. The




Fig. 8 - Computed received power ratio as a function of target over-the-ground range: (a) target at 24 and 1 kft, and (b) expanded graph of target at 1-kft height. Transmitting antenna height was chosen as 166 ft and ionospheric height as 300 km.

data shown were computed using a G-15 computer. Target heights of 1 kft (1000 ft) and 24 kft are indicated. The height factor affects the time it takes a moving target to go through a maximum and minimum cycle. The table below shows the time for the returns from a 400-knot target to go from a maximum value to the next maximum value for this simplified model. The target is on a great-circle course which passes over the radar site.

Target Altitude (kft)	Over-the-Ground Speed (knots)	Max to Max Time (min)
1	400	21
24	400	1

In real life the ionosphere does not reflect exactly like a perfect mirror. This difference from the ideal case treated above tends to apply a smoothing to the signal peaks and nulls, and at times even introduce additional peaks and nulls. However, the results shown in Fig. 8 and the table illustrate a difference between low-altitude and high-altitude detection requirements. That is, a longer period of surveillance is required in the detection of low-altitude targets.

COMMENTS

In this report, the results of tracking one transatlantic P3V flight have been treated in some detail. One hf frequency, 18.036 Mc/s, was used to obtain adequate coverage of the interval between 1000 and 2000 naut mi distance from the radar. The P3V was tracked almost continuously for the distance between 1475 and 2000 naut mi except for two periods when the radar was not operating. After the aircraft closed to 1475 naut mi, tracking was terminated due to demand for a different radar use; continued observation was possible in to about 1000 naut mi. This example is illustrative of what can be done with an extended range radar.

An important feature of hf OTH radars is that aircraft targets can be detected at any altitude as long as they have sufficient relative velocity. The fading pattern of targets is dependent upon altitude to some extent, with the faster fade rates being associated with higher target altitudes.

Thousands of real-time OTH aircraft detections have been made with the NRL radar in the 500 to 2000-naut-mi interval. In hundreds of cases a study of aircraft echo has been made by tracking for some distance and recording received signal amplitudes (5-7). The aircraft have ranged from the F100 (38-ft wing span and 47-ft length) to the larger KC-135 and have included piston and turbo-prop types. Exclusive of times of ionospheric disturbance, or storm, and times when the required operating frequency was outside the capability of this experimental radar, fair illumination of a portion of the distance between 500 and 2000 naut mi has been always possible.

The following are the essential features of the radar:

- a. One-way antenna gain of approximately 20 db,
- b. Radiated power of 60 to 100 kw average, 4.6 Mw peak,

- c. In excess of 70-db rejection of earth backscatter, and
- d. 1/3 cps bandwidth predetection signal filter.

It is felt that sufficient experience has been accumulated to estimate system requirements for one-hop OTH aircraft detection. Principal deficiencies in knowledge are due to limited experience and to the use of frequencies above 13.5 Mc/s.

REFERENCES

1. Boyd, F.E., and Rohlf, D.C., "A Very-High-Power High-Frequency Pulse Transmitter and Antennas," NRL Report 5903 (Secret Report, Unclassified Title), May 1963
2. McGeogh, J.E., Jensen, G.K., and Uniacke, C.L., "A 100-KC Quartz Crystal Comb Rejection Filter," NRL Report 5589 (Confidential Report, Unclassified Title), Feb. 1961
3. Page, R.M., and George, S.F., "Magnetic Drum Storage Applied to Surveillance Radar," NRL Report 4878 (Confidential Report, Unclassified Title), Jan. 1957
4. Wyman, F.E., and Zettle, E.N., "Magnetic Drum Storage Cross Correlation Radar," NRL Report 5023 (Secret Report, Unclassified Title), Nov. 1957
5. Gager, F.M., Headrick, W.C., Morgan, G.A., Utley, F.H., and Zettle, E.N., "Madre Performance, Part 1 - Observations of January 18 and 25, 1962," NRL Report 5862 (Secret Report, Unclassified Title), Dec. 1962
6. Gager, F.M., Headrick, W.C., Morgan, G.A., Rohlf, D.C., Tesauero, C.B., and Zettle, E.N., "Madre Performance, Part 2 - Observations of February 8, 1962," NRL Report 5898 (Secret Report, Unclassified Title), Feb. 1963
7. Gager, F.M., Morgan, G.A., Tesauero, C.B., Skaggs, G.A., and Zettle, E.N., "Madre Performance, Part 3 - Observations of February 12, 1962," NRL Report 5991 (Secret Report, Unclassified Title), Aug. 1963

DISTRIBUTION

	<u>Copy No.</u>
CNO Attn: Op-03EG	1 - 2
Op-92	3 - 6
Op-30	7
Op-70	8
Op-07TE	9
Op-723E	10
ONR Attn: Code 406	11
427	12
418	13
463	14
402C	15
Dir., Advanced Research Projects Agency, Wash., D.C. Attn: Mr. A. Van Every (2)	16 - 17
Dir., Weapons Systems Evaluation Group, Rm. 1E880, Pentagon, Wash., D.C. Attn: Mrs. Sjogven (2)	18 - 19
National Bureau of Standards, Boulder Labs., Boulder, Colo. Attn: Mr. L.H. Tveten, 85.20	20
Dir., National Security Agency, Fort George G. Meade, Md. Attn: C3/TDL	21
CO, U.S.NavOrdTestUnit, Atlantic Missile Range, Patrick Air Force Base, Fla. Attn: CDR A.L. Jacobson	22
SPP002	23
CDR R.E. Colopy	24
CO & Dir., USNEL, San Diego, Calif. 92152 Attn: Technical Library (2)	25 - 26
CRD, Pacific Missile Range, Point Mugu, Calif. Attn: Code 3215	27
BuWeps Attn: Code RTOS	28
BuShips Attn: 362A	29
CO, ONRBC London, England	30
CDR, Naval Missile Center, Point Mugu, Calif. Attn: Technical Library, Code N03022	31
Research & Technical Div., Hdqs., AF Systems Command, Bolling AFB, Washington, D.C. Attn: LTCOL R.M. Cosel	32

DISTRIBUTION (cont'd)

Copy No.

Dir., Special Projects Office, Dept. of the Navy, Wash., D.C.	
Attn: Code SP-204	33
SP-2041	34
Dir., Defense Research & Engineering, Dept. of Defense, Wash., D.C.	
Attn: Dir Defense (2)	35 - 36
CO, U.S. NATC, Patuxent River NavAirSta, Patuxent River, Md.	
Attn: Mr. D. Decker	37
Code 32, WSTD	38
Code 323, WSTD	39
CO, USNOL, Corona, Calif.	
Attn: Mr. V. Hildebrand	40
Missile Development Div.	41
Technical Library	42
USNOTS, China Lake, Calif.	
Attn: Technical Library	43
USNPGS, Monterey, Calif.	
Attn: Technical Library	44
USNADC, Johnsville, Pa.	
Attn: Technical Library	45
ASD, Wright-Patterson AFB, Dayton, Ohio	
Attn: ASAPRD-Distr.	46
Rome Air Development Center, Rome, N.Y.	
Attn: EMIA	47
RALTT (Mr. F. Bradley)	48
RCLTS (Mr. T. Maggio)	49
RAUEL-3 (Mr. G.R. Weatherup)	50
USAFCRC, Hanscom Field, Bedford, Mass.	
Attn: Code CRTOTT-2	51
CRUI (Mr. William F. Ring)	52
CRUP (Dr. G.J. Gassmann)	53
CRRIP (Mr. Thomas D. Conley)	54
ESRDT (Mr. Harry Byram)	55
Dir., USAFL, Hqs. USA Electronics Command, Ft. Monmouth, N.J. 07703	
Attn: AMSEL-RD-ADT	56
AMSEL-RD-DR	57
AMSEL-RD-X	58
SIGRP-A, Army Signal Radio Propagation Agency	59
CO, Harry Diamond Labs., Wash., D.C. 20438	
Attn: AMXDO-TIA (Tech. Library)	60

DISTRIBUTION (cont'd)

	<u>Copy No.</u>
USAERDL, Ft. Belvoir, Va. 22061 Attn: STINFO Branch	61 - 62
ODD (R&E) Attn: Technical Library Branch	63 - 64
CO, U.S. Army Materiel Command, Wash., D.C. Attn: AMCRD-D Dr. C.M. Hudson (ORDTX), Gravelly Point, Va.	65
CO, U.S. Army Munitions Command, Picatinny Arsenal, Dover, N.J. Attn: SMUPA-VA6	66
Hdqs., U.S. Army Liaison Group, Project Michigan, Univ. of Michigan, P.O. Box 618, Ann Arbor, Mich. Attn: BAMIRAC Info. Center	67
CO, U.S. Army Electronics Research Unit, P.O. Box 205, Mountain View, Calif.	68
ODD(R&E), Office of Electronics, Rm. 301033, Pentagon, Wash., D.C. Attn: Mr. J.J. Donovan	69
Hdqs., U.S. Air Force, Office, Asst. Chief of Staff, Intelligence, Wash., D.C. Attn: MAJ A.T. Miller Policy & Programs Group, AFNINC	70 71
CO, USAERDA, White Sands Missile Range, New Mexico Attn: Mr. James M. Hardison SELWS-WT RR-315, Technical Library	72 73 74
Hdqs., USAF, Dept. of the Air Force, Office for Atomic Energy, DCS/O, Wash., D.C.	75
Hdqs., USAF, Wash., D.C. Attn: LTCOL K. Baker, AFRDP-A MAJ L.N. Brubaker, AFCIN ICI	76 77
CDR, Air Force Office of Scientific Research, Wash., D.C. Attn: Code SRY	78
Hdqs., Offutt Air Force Base, Nebraska Attn: Strategic Air Command	79
CDR, Air Force Ballistic Missile Div., Air Force Unit Post Office, Los Angeles 45, Calif. Attn: SSD(SOCE)	80
Hdqs., North American Air Defense Command, Ent Air Force Base, Colorado Springs 12, Colo. Attn: NELC (Advanced Projects Group) LTCOL Kaminski, ADLPC-SA (2) LTCOL M.R. Cripe (NPSD-R) ADC(ADOOA) ADLAN Section	81 82 - 83 84 85 86

SECRET

DISTRIBUTION (cont'd)

Copy No.

Electro-Physics Labs., ACF Electronics Div., 3355 - 52nd Ave., Hyattsville, Md. Attn: Mr. W.T. Whelan	87
Stanford Electronics Lab., Stanford Univ., Stanford, Calif. Attn: Prof. O.G. Villard, Jr.	88
Foreign Technology Div., Wright-Patterson AFB, Ohio Attn: TDEED, Mr. W.L. Picklesimer	89
TDATA, M. G.A. Long, Jr.	90
TDCE, Mr. M.S. Graebner	91
Raytheon Co., Box 155, 1415 Boston-Providence Turnpike, Norwood, Mass. Attn: Mr. L.C. Edwards	92
Raytheon Mfg. Co., Wayland Laboratory, Waltham, Mass. Attn: Mr. D.A. Hedlund	93
General Electric Co., Court St., Syracuse, New York Attn: Dr. G.H. Millman	94
Mr. T.E. Manwarren, FRP-1-138	95
Lockheed Aircraft Corp., Calif. Div., Burbank, Calif. Attn: Mr. R.A. Bailey	96
Pilotless Aircraft Div., Boeing Airplane Co., Seattle 24, Wash. Attn: Mr. F.S. Holman	97
The Martin Co., Baltimore 3, Md. Attn: Dr. D.M. Sukhia	98
Radio Corp. of America, Aerospace Communications & Controls, Div., Burlington, Mass. Attn: Mr. J. Rubinovitz	99
Radio Corp. of America, Missile & Surface Radar Div., Moorestown, New Jersey Attn: Mr. A. Leder, 101-201	100
Mr. F. Papasso, 101-130	101
MIT, Lincoln Labs., Lexington 73, Mass. Attn: Dr. J.H. Chisholm	102
Mr. Melvin Stone	103
The Pennsylvania State Univ., University Park, Pa. Attn: Dr. A.H. Waynick	104
The Rand Corp., 1700 Main St., Santa Monica, Calif. Attn: Dr. Cullen Crain	105
Technical Library	106
Pickard & Burns, Inc., 103 Fourth Ave., Waltham 54, Mass. Attn: Dr. John C. Williams, Research Dept.	107

DISTRIBUTION (cont'd)

	<u>Copy No.</u>
Bendix Systems Div., The Bendix Corp., 3300 Plymouth Road, Ann Arbor, Mich. Attn: Mr. C.M. Shaar, Assoc. Dir. of Engr.	108
Smyth Research Associates, 3555 Aero Court, San Diego 11, Calif. Attn: Mr. Steven Weisbrod	109
Convair Div. of General Dynamics, 3165 Pacific Coast Highway, San Diego 12, Calif. Attn: Dr. Bond	110
USAEL, Ft. Monmouth, N.J. Attn: SELRA/SRD, Mr. R. Dunn	111
Stanford Research Institute, Menlo Park, Calif. Attn: Mr. R. Vincent	112
Mr. L.T. Dolphin, Jr.	113
Thompson Ramo-Wooldridge, Inc., Box 90534, Airport Station, Los Angeles, Calif. Attn: Tech. Information Services	114
Applied Physics Labs., Johns Hopkins Univ., 8621 Georgia Ave., Silver Spring, Md. Attn: Mr. G.L. Seielstad (NavOrd 7386)	115
Chief, Army Security Agency, Arlington Hall Station, Arlington 12, Va.	116
Univ. of Calif., Dept. of Mathematics, Berkeley 4, Calif. Attn: Dr. Edmund J. Pinney	117
HRB Singer, Inc., Science Park, P.O. Box 60, State College, Pa.	118
Aircraft Instruments Laboratory, Melville, L.I., New York Attn: Mr. Scott Hall	119
U.S. Army Ordnance Missile Command, Redstone Arsenal, Ala. Attn: Mr. James E. Norman	120
DOFL, Ordnance Corps, Washington 25, D.C. Attn: Mr. Percy Griffen	121
Institute for Defense Analyses, 400 Army Navy Drive, Arlington, Virginia Attn: Dr. Nils L. Muench	122
Dr. Paul Von Handel	123
Westinghouse Electric Corp., Defense Center - Baltimore, Technical Information Center, P.O. Box 1683, Baltimore 3, Md.	124
Westinghouse Electric Corp., Air Arm Div., Box 746, Baltimore, Md. Attn: Mr. David Fales	125
Systems Branch, U.S. Army Scientific Liaison & Advisory Group, P.O. Box 7157, Apex Station, Washington 4, D.C. Attn: Mr. Richard A. Krueger	126

DISTRIBUTION (cont'd)

Copy No.

KELTEC Industries, Inc., P.O. Box 1082, Edsall & Lincolnia Roads, Alexandria, Va.	127
KELTEC, 13624 Magnolia Ave., Corona, Calif. Attn: Mr. A.W. Walters	128
Dir., DASA Data Center, P.O. Drawer QQ, Santa Barbara, Calif.	129
Astrophysics Research Corp., 2444 Wilshire Blvd., Rm. 512. Santa Monica, Calif. Attn: Dr. Alfred Reifman	130
Hdqs., USAF, Wash., D.C. Attn: AFNICAA, MAJ Patrick Long	131
Defense Intelligence Agency, Wash., D.C. Attn: DIASA-2C	132
General Electric Co., Electronics Park, Syracuse, New York Attn: Mr. B.L. Holtzelaw Mr. G.R. Nelson	133 134
Stanford Research Institute Data Center, c/o Communication Group, Bldg. 303B, Menlo Park, Calif.	135
Mitre Corp., Bedford, Mass. Attn: Technical Library	136
DDC, Alexandria, Va. Attn: TIPDR (20 cys.)	137 - 156

SECRET

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body, of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) U.S. Naval Research Laboratory Washington, D.C. 20390		2a. REPORT SECURITY CLASSIFICATION SECRET
		2b. GROUP 3
3. REPORT TITLE (Unclassified) EXTENDED-RANGE AIRCRAFT TRACKING		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) An interim report on one phase of the problem.		
5. AUTHOR(S) (Last name, first name, initial) Ahearn, J.L., Headrick, W.C., Headrick, J.M., Tesauro, C.B., and Zettle, E.N.		
6. REPORT DATE May 12, 1965	7a. TOTAL NO. OF PAGES 22	7b. NO. OF REFS 7
8a. CONTRACT OR GRANT NO. NRL Problem R02-23	9a. ORIGINATOR'S REPORT NUMBER(S) NRL Report 6272	
b. PROJECT NO. RF 001-02-41-4007		
c. AF MIPR (30-602) 63-2928 (30-602) 63-2929	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned to this report) None	
d. (30-602) 63-2995		
10. AVAILABILITY/LIMITATION NOTICES All distribution of this report is controlled. Qualified DDC users shall request through Director, U.S. Naval Research Laboratory, Washington, D.C. 20390		
11. SUPPLEMENTARY NOTES None	12. SPONSORING MILITARY ACTIVITY Dep't of the Navy (Office of Naval Research) and the Dep't of the Air Force	
13. ABSTRACT (Secret) As part of the evaluation of the Madre radar system at the Chesapeake Bay Annex of the Naval Research Laboratory, data on a number of controlled over-the-horizon aircraft flights have been taken. Of particular interest is a flight which took place on 29 November 1962. The plane was a P3v (similar to the commercial Electra) and it was flying at an altitude of 24,000 ft from Lajes, Azores, to Norfolk, Virginia. The radar operated at 18.036 Mc/s with 4.6 Mw peak power. The plane was tracked over a great circle ground range from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case.		

DD FORM 1473

19

SECRET

Security Classification

SECRET
Security Classification

14. KEY WORDS (Unclassified)	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
High-frequency radar Aircraft tracking Target cross-section measurements						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, R, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph represented as: (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words, but will be followed by an indication of technical content. The assignment of links, roles, and weights is optional.

SECRET U.S. Naval Research Laboratory. Report 6272 (SECRET-Group 3). EXTENDED-RANGE AIRCRAFT TRACKING. Unclassified Title 1, by J.L. Ahearn, W.C. Headrick, J.M. Headrick, C.B. Tesaro, and E.N. Zettie, 20 pp. and figs., May 12, 1965. As part of the evaluation of the Madre radar system at the Chesapeake Bay Annex of the Naval Research Laboratory, data on a number of controlled over-the-horizon aircraft flights have been taken. Of particular interest is a flight which took place on 29 November 1962. The plane was a P3V (similar to the commercial Electra) and it was flying at an altitude of 24,000 ft from La Joes, Azores, to Norfolk, Virginia. The radar operated at 18,036 Mc/s with 4.6 Mw peak power. The plane was tracked over a great circle ground range SECRET (over)	SECRET U.S. Naval Research Laboratory. Report 6272 (SECRET-Group 3). EXTENDED-RANGE AIRCRAFT TRACKING. Unclassified Title 1, by J.L. Ahearn, W.C. Headrick, J.M. Headrick, C.B. Tesaro, and E.N. Zettie, 20 pp. and figs., May 12, 1965. As part of the evaluation of the Madre radar system at the Chesapeake Bay Annex of the Naval Research Laboratory, data on a number of controlled over-the-horizon aircraft flights have been taken. Of particular interest is a flight which took place on 29 November 1962. The plane was a P3V (similar to the commercial Electra) and it was flying at an altitude of 24,000 ft from La Joes, Azores, to Norfolk, Virginia. The radar operated at 18,036 Mc/s with 4.6 Mw peak power. The plane was tracked over a great circle ground range SECRET (over)
SECRET U.S. Naval Research Laboratory. Report 6272 (SECRET-Group 3). EXTENDED-RANGE AIRCRAFT TRACKING. Unclassified Title 1, by J.L. Ahearn, W.C. Headrick, J.M. Headrick, C.B. Tesaro, and E.N. Zettie, 20 pp. and figs., May 12, 1965. As part of the evaluation of the Madre radar system at the Chesapeake Bay Annex of the Naval Research Laboratory, data on a number of controlled over-the-horizon aircraft flights have been taken. Of particular interest is a flight which took place on 29 November 1962. The plane was a P3V (similar to the commercial Electra) and it was flying at an altitude of 24,000 ft from La Joes, Azores, to Norfolk, Virginia. The radar operated at 18,036 Mc/s with 4.6 Mw peak power. The plane was tracked over a great circle ground range SECRET	SECRET U.S. Naval Research Laboratory. Report 6272 (SECRET-Group 3). EXTENDED-RANGE AIRCRAFT TRACKING. Unclassified Title 1, by J.L. Ahearn, W.C. Headrick, J.M. Headrick, C.B. Tesaro, and E.N. Zettie, 20 pp. and figs., May 12, 1965. As part of the evaluation of the Madre radar system at the Chesapeake Bay Annex of the Naval Research Laboratory, data on a number of controlled over-the-horizon aircraft flights have been taken. Of particular interest is a flight which took place on 29 November 1962. The plane was a P3V (similar to the commercial Electra) and it was flying at an altitude of 24,000 ft from La Joes, Azores, to Norfolk, Virginia. The radar operated at 18,036 Mc/s with 4.6 Mw peak power. The plane was tracked over a great circle ground range SECRET

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

SECRET

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

SECRET

SECRET

U.S. Naval Research Laboratory, Report 6272
SECRET-Group 3, EXTENDED-RANGE AIRCRAFT
TRACKING (Unclassified Title), by J.L. Ahearn, W.C.
Headrick, J.M. Headrick, C.B. Tesauru, and E.N.
Zettie, 20 pp. and figs., May 12, 1965.

As part of the evaluation of the Madre radar system
at the Chesapeake Bay Annex of the Naval Research
Laboratory, data on a number of controlled over-the-
horizon aircraft flights have been taken. Of particular
interest is a flight which took place on 29 November
1962. The plane was a P3V (similar to the commercial
Electra) and it was flying at an altitude of 24,000 ft
from Lajes, Azores, to Norfolk, Virginia. The radar
operated at 18,036 Mc/s with 4.6 Mw peak power. The
plane was tracked over a great circle ground range

- I. Early warning
radar systems -
Effectiveness
2. Radar echo
areas -
Measurements

- I. MADRE
- II. Ahearn, J.L.
- III. Headrick, W.C.
- IV. Headrick, J.M.
- V. Tesauru, C.B.
- VI. Zettie, E.N.

SECRET

SECRET

U.S. Naval Research Laboratory, Report 6272
SECRET-Group 3, EXTENDED-RANGE AIRCRAFT
TRACKING (Unclassified Title), by J.L. Ahearn, W.C.
Headrick, J.M. Headrick, C.B. Tesauru, and E.N.
Zettie, 20 pp. and figs., May 12, 1965.

As part of the evaluation of the Madre radar system
at the Chesapeake Bay Annex of the Naval Research
Laboratory, data on a number of controlled over-the-
horizon aircraft flights have been taken. Of particular
interest is a flight which took place on 29 November
1962. The plane was a P3V (similar to the commercial
Electra) and it was flying at an altitude of 24,000 ft
from Lajes, Azores, to Norfolk, Virginia. The radar
operated at 18,036 Mc/s with 4.6 Mw peak power. The
plane was tracked over a great circle ground range

- I. Early warning
radar systems -
Effectiveness
2. Radar echo
areas -
Measurements

- I. MADRE
- II. Ahearn, J.L.
- III. Headrick, W.C.
- IV. Headrick, J.M.
- V. Tesauru, C.B.
- VI. Zettie, E.N.

SECRET

SECRET

U.S. Naval Research Laboratory, Report 6272
SECRET-Group 3, EXTENDED-RANGE AIRCRAFT
TRACKING (Unclassified Title), by J.L. Ahearn, W.C.
Headrick, J.M. Headrick, C.B. Tesauru, and E.N.
Zettie, 20 pp. and figs., May 12, 1965.

As part of the evaluation of the Madre radar system
at the Chesapeake Bay Annex of the Naval Research
Laboratory, data on a number of controlled over-the-
horizon aircraft flights have been taken. Of particular
interest is a flight which took place on 29 November
1962. The plane was a P3V (similar to the commercial
Electra) and it was flying at an altitude of 24,000 ft
from Lajes, Azores, to Norfolk, Virginia. The radar
operated at 18,036 Mc/s with 4.6 Mw peak power. The
plane was tracked over a great circle ground range

- I. Early warning
radar systems -
Effectiveness
2. Radar echo
areas -
Measurements

- I. MADRE
- II. Ahearn, J.L.
- III. Headrick, W.C.
- IV. Headrick, J.M.
- V. Tesauru, C.B.
- VI. Zettie, E.N.

(over)

SECRET

SECRET

U.S. Naval Research Laboratory, Report 6272
SECRET-Group 3, EXTENDED-RANGE AIRCRAFT
TRACKING (Unclassified Title), by J.L. Ahearn, W.C.
Headrick, J.M. Headrick, C.B. Tesauru, and E.N.
Zettie, 20 pp. and figs., May 12, 1965.

As part of the evaluation of the Madre radar system
at the Chesapeake Bay Annex of the Naval Research
Laboratory, data on a number of controlled over-the-
horizon aircraft flights have been taken. Of particular
interest is a flight which took place on 29 November
1962. The plane was a P3V (similar to the commercial
Electra) and it was flying at an altitude of 24,000 ft
from Lajes, Azores, to Norfolk, Virginia. The radar
operated at 18,036 Mc/s with 4.6 Mw peak power. The
plane was tracked over a great circle ground range

- I. Early warning
radar systems -
Effectiveness
2. Radar echo
areas -
Measurements

- I. MADRE
- II. Ahearn, J.L.
- III. Headrick, W.C.
- IV. Headrick, J.M.
- V. Tesauru, C.B.
- VI. Zettie, E.N.

(over)

SECRET

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

SECRET

from 1978 naut mi to 1391 naut mi. Radar cross-section measurements of the plane are included in this report, as well as an idealized treatment of the four-path over-the-horizon case. [Secret Abstract]

SECRET

SECRET

MEMORANDUM

20 February 1997

Subj: Document Declassification

Ref: (1) Code 5309 Memorandum of 29 Jan. 1997
(2) Distribution Statements for Technical Publications
NRL/PU/5230-95-293

Encl: (a) Code 5309 Memorandum of 29 Jan. 1997
(b) List of old Code 5320 Reports
(c) List of old Code 5320 Memorandum Reports

1. In Enclosure (a) it was recommended that the following reports be declassified, four reports have been added to the original list:

Formal: 5589, 5811, 5824, 5825, 5849, 5862, 5875, 5881, 5903, 5962, 6015, 6079, 6148, 6198, 6272, 6371, 6476, 6479, 6485, 6507, 6508, 6568, 6590, 6611, 6731, 6866, 7044, 7051, 7059, 7350, 7428, 7500, 7638, 7655. Add 7684, 7692.

Memo: 1251, 1287, 1316, 1422, [REDACTED], 1500, 1527, 1537, 1540, 1567, 1637, 1647, 1727, 1758, 1787, 1789, 1790, 1811, 1817, 1823, 1885, 1939, 1981, 2135, 2624, 2701, 2645, 2721, 2722, 2723, 2766. Add 2265, 2715.

The recommended distribution statement for the these reports is: **Approved for public release; distribution is unlimited.**

2. The above reports are included in the listings of enclosures (b) and (c) and were selected because of familiarity with the contents. The rest of these documents very likely should receive the same treatment.

J. M. Headrick
J. M. Headrick
Code 5309

Copy:

Code 1221 — *CR OK 7/1/97*

Code 5300

Code 5320

Code 5324