

UNCLASSIFIED

AD NUMBER

AD385563

CLASSIFICATION CHANGES

TO: UNCLASSIFIED

FROM: CONFIDENTIAL

LIMITATION CHANGES

TO:
Approved for public release; distribution is unlimited.

FROM:
Distribution authorized to DoD only;
Administrative/Operational Use; OCT 1967. Other requests shall be referred to Picatinny Arsenal, Attn: SMUPA-DR7, Dover, NJ 07801.

AUTHORITY

31 Dec 1973, per Document marking; USAMC ltr,
27 Jun 1974

THIS PAGE IS UNCLASSIFIED

GENERAL DECLASSIFICATION SCHEDULE

IN ACCORDANCE WITH
DOD 5200.1-R & EXECUTIVE ORDER 11652

THIS DOCUMENT IS:

CLASSIFIED BY DDC

Subject to General Declassification Schedule of
Executive Order 11652-Automatically Downgraded at
2 Years Interval. DECLASSIFIED ON DECEMBER 31, 73

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

21
L
CONFIDENTIAL

AD

Technical Information Report 33.4.1.3

ANTITANK MINE, XM34 (U)

Interim Report

October 1967

ARMY MATERIEL COMMAND

Prepared by the University of Pittsburgh
Research Staff, 1776 Massachusetts
Avenue, NW, Washington, D. C. 20036,
under Contract DA-49-186-AMC-214(D)

DA Project Number: 1X143312D413
Task Number: 01

DDC
RECEIVED
DEC 6
RECEIVED
D

DISTRIBUTION STATEMENT

In addition to security requirements which apply to this document and must be met, each transmittal outside the Department of Defense must have prior approval of the Commanding Officer, Picatinny Arsenal, attn: SMUPA-DR7, Dover, New Jersey 07801.

This material contains information affecting the national defense of the United States within the meaning of the espionage laws, Title 18, U. S. C., Sections 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

**DOWNGRADED AT 3 YEAR INTERVALS;
DECLASSIFIED AFTER 12 YEARS.
DOD DIR 5200.10**

CONFIDENTIAL

AD 385563

When this report is no longer needed, Department of the Army organizations will destroy it in accordance with the procedures given in AR 380-5. Navy and Air Force elements will destroy it in accordance with applicable directives. Department of Defense contractors will destroy the report according to the requirements of paragraph 19 of the Industrial Security Manual for Safeguarding Classified Information. All others will return the report to the Commanding Officer, Picatinny Arsenal, attn: SMUPA-DR7, Dover, New Jersey 07801.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

SUMMARY

(U) This report traces the development of the XM34 antitank mine, which is designed to immobilize enemy armored vehicles. Because it can be air-dropped, it is useful for antitank mining in areas hitherto inaccessible.

RELATED TIR'S

7-66	TIR 18. 2. 1. 11	Aircraft Mine-Dispersing Subsystem, XM47
10-67	TIR 33. 4. 1. 2(2)	Aircraft Mine-Dispersing Subsystem, XM56
7-64	TIR 33. 4. 2. 2	Antipersonnel Mine, XM27
6-65	TIR 33. 4. 4. 1	Antitank Mine Fuze, XM608 Series
1-66	TIR 33. 4. 5. 1	Antipersonnel Mine Dispenser, XM3
2-62	TIR 4-3-1A9(1)	Antipersonnel Mine, XM22

CONFIDENTIAL

ANTITANK MINE, XM34 (U)

(C) The XM34 antitank mine is a blast-type mine that causes immobilization (M-kill) of the target vehicle. The XM34 is designed for use in the XM56 aircraft mine-dispersing subsystem and can be dispersed aurally, from ground vehicles, or manually. The other major item of the subsystem is the SUU-13/A antitank mine dispenser. Because it can be air-dropped, the XM34 is useful for antitank mining in areas hitherto inaccessible. The major parts of the mine assembly are a body, a pressure plate with integral fuze, and H6 explosive.

(C) This antitank mine is suited to being sown in mixed minefields with antipersonnel mines against both armor and infantry attack. Aerial and vehicular means of sowing enable a commander to pick the best placement zones to suit his tactical needs and delay emplacement of the mines until the last possible moment to surprise the enemy. The XM34 is highly countermeasure resistant and difficult to defeat.


(C) The mine fuze is actuated by a sustained pressure of 250 pounds on its pressure plate for a period of 350 milliseconds. Its firing train is out of line, and therefore unarmed, until the correct sustained pressure simultaneously arms and fires the fuze by bringing the detonator into line. If the pressure is released in less than the required time, the arming mechanism returns to its original zero setting. This built-in actuation delay makes the fuze highly resistant to such countermeasures as rollers, flails, and explosive charges, and also provides the airdrop capability. Another advantage resulting from the actuation delay is that the detonation occurs beyond the first road wheel of the tank, where the vehicle is most vulnerable. For this reason, less high explosive is needed than is normally required in other antitank mines. Although it contains only 3.5 pounds of H6 explosive, the XM34 mine was effective in tests in immobilizing tanks equipped with Russian JS-3 tracks.

(C) The mine has the configuration of a longitudinally split half cylinder 4.625 inches in diameter and 9.75 inches long. The XM608E3 fuze is in a well, which is covered by a 2.5-inch-diameter pressure plate supported by a 250-pound spring; the pressure plate is sealed to protect it against the environment. A plunger makes contact with the pressure plate and the fuze input piston. There is also a groove for a safety clip and a safety yoke to prevent accidental depression of the pressure plate. A positive mechanical lockup SAFE position and an ARMED position are separated by 90° of rotation. The ARMED position is really a commit-to-arm position because arming takes place only when the fuze is subjected to the necessary actuating pressure for the required time. This standard arming method is used whether the mines are emplaced by hand, from a surface vehicle, or from an aircraft. Each mine has a cavity to accommodate the pressure


CONFIDENTIAL

TIR 33.4.1.3


ANTITANK MINE, XM34



(CONFIDENTIAL) CROSS SECTION OF XM34 MINE (U)



(CONFIDENTIAL) XM34 MINE ASSEMBLY (U)



(CONFIDENTIAL) XM608E3 FUZE SUBASSEMBLY (U)

plate of another mine, thereby making it possible to nest two mines together to form a cylindrical storage unit within each tube. The mines are then bore safe and completely protected from accidental detonation until ejected from the dispenser tube because the fuzes are not exposed. The case and other components of the mine are made of steel and aluminum; because of the structural soundness of its case, the mine will not be damaged when it hits the ground after being air-dropped, nor will it function when a vehicle passes over part of the mine but does not contact the pressure plate. A self-sterilization, or self-destruction, feature functioning in 8 to 10 hours is being considered for the XM34.

(C) Dummy mines and a limited number of XM34 mines have been dropped from aircraft in tests. The fuzed mines showed little or no damage and inert mines survived impact with the ground. None of the XM608E3 fuzes (the XM608E3 is to be replaced by a new, integral fuze) functioned accidentally upon impact and all fuzes operated properly when deliberately actuated later. A limited number of tests, made by running an M48 tank equipped with US and Russian tracks over test mines, indicated a 90% functioning reliability. Mines have also been dispensed from the air into satisfactory patterns.

CONFIDENTIAL

TIR 33.4.1.3

ANTITANK MINE, XM34

The mine is in the early stages of its revised form. The principal problem is to work out the design for the integral fuze.

(CONFIDENTIAL) TENTATIVE PRINCIPAL CHARACTERISTICS (U)

Type	blast, antitank
Model	XM34
Configuration	longitudinally split half cylinder
Weight	6.7 lb
Dimensions	
Length	9.75 in
Diameter	4.625 in
Explosive	
Type	H6
Weight	3.7 lb
Fuze	
Type	pressure, contact (sustained)
Model	none; integral with mine
Detonation	delayed
Signature	
Weight	250 lb
Time sustained	350 milliseconds
Safeties	mechanical pull device, out-of-line detonator
Sensing range	contact area of target
Orientation	fuze up or fuze down
Self-neutralization	self-destruct module, 8 to 10 hours being considered
Countermeasure resistance	blast, roller, and flail resistant
Emplacement	surface, by ground vehicle, aircraft, or manual means
Lethality	M-kill
Storage	2 mines per tube, 80 mines per dispenser

UNCLASSIFIED

Security Classification

UNCLASSIFIED

10.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	<p>*Mines (ordnance), *Air-dropped mines, *Antitank mines, Antipersonnel mines, Mine components, Mine fuzes, Antitank mine-dispensing subsystems, SUU-13/A dispenser, XM3 antipersonnel mine dis- penser, XM608E3 fuze, Standard Army aircraft, Fixed-wing aircraft, Rotary wing aircraft, XM56 aircraft mine-dispersing subsystem (U)</p>						

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and inclusion annotations must be entered when the report is classified)

1. ORIGINATING ACTIVITY (Agency symbol) Pittsburgh Univ Washington D C Research Staff		2. REPORT SECURITY CLASSIFICATION CONFIDENTIAL	
3. REPORT TITLE ANTITANK MINE, XM34 (U)			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Interim Report			
5. AUTHOR(S) (Last name, middle initial, first name)			
6. REPORT DATE October 1967	7a. TOTAL NO. OF PAGES 4	7b. NO. OF SECS	
8a. CONTRACT OR GRANT NO. DA-49-186-AMC-214(D)	8b. ORIGINATOR'S REPORT NUMBER(S) TIR 33.4.1.3		
8c. PROJECT NO.	9a. OTHER REPORT NUMBERS (Any other numbers that may be assigned this report)		
9b.	9c.		
9d.	9e.		
10. DISTRIBUTION STATEMENT In addition to security requirements which apply to this document and must be met, each transmittal outside the Department of Defense must have prior approval of the Commanding Officer, Picatinny Arsenal, attn: SMUPA-DR7, Dover, New Jersey 07801.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Research & Development Directorate Army Materiel Command	
13. ABSTRACT This report traces the development of the XM34 antitank mine, which is designed to immobilize enemy armored vehicles. Emplacement can be done manually, from ground vehicles, and from aircraft. Because it can be air-dropped, it is useful for antitank mining in areas hitherto inaccessible. By sowing the XM34 simultaneously with suitable antipersonnel mines, a mine field can be established, excluding both enemy infantry and armor. (U)			

DD FORM 1473

1 NOV 67

UNCLASSIFIED

Security Classification