

UNCLASSIFIED



AD NUMBER

AD-393 552

CLASSIFICATION CHANGES

TO UNCLASSIFIED

FROM CONFIDENTIAL

AUTHORITY

USABRL Notice; Jun 20, 1975

19990317088

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED



AD NUMBER

AD-393 552

NEW LIMITATION CHANGE

TO

DISTRIBUTION STATEMENT: A

Approved for public release; Distribution is unlimited.

LIMITATION CODE: 1

FROM

No Prior DoD Distr Scty Cntrl St'mt Assgn'd

AUTHORITY

USAARDCOM ltr; Mar 16, 1981

THIS PAGE IS UNCLASSIFIED

~~CONFIDENTIAL~~

THIS DOCUMENT CONSISTS OF 38 PAGES  
COPY ~~1~~ OF 100 COPIES, SERIES A

AD

BRL MR 1939

**BRL**

AD393552

MEMORANDUM REPORT NO. 1939

AERODYNAMIC FORCE TESTS OF CONE CYLINDER FLECHETTE  
MODELS AT SUPERSONIC MACH NUMBERS (U)

by

Klaus O. Opalka

October 1968

8 1968

In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Commanding Officer, U.S. Army Aberdeen Research and Development Center, Aberdeen Proving Ground, Maryland.

U.S. ARMY ABERDEEN RESEARCH AND DEVELOPMENT CENTER  
BALLISTIC RESEARCH LABORATORY  
ABERDEEN PROVING GROUND, MARYLAND

GROUP 3  
DOWNGRADED AT 12 YEAR INTERVALS  
NOT AUTOMATICALLY DECLASSIFIED

~~CONFIDENTIAL~~

Reproduced From  
Best Available Copy

19990317088

# **SECURITY**

---

# **MARKING**

**The classified or limited status of this report applies to each page, unless otherwise marked.**

**Separate page printouts MUST be marked accordingly.**

---

**THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.**

**NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.**

When this report is no longer needed, Department of the Army organizations will destroy it in accordance with the procedures given in AR 380-5. Navy and Air Force elements will destroy it in accordance with applicable directives. Department of Defense contractors will destroy the report according to the requirements of Section 14 of the Industrial Security Manual for Safeguarding Classified Information. All others will return the report to Commanding Officer, U.S. Army Aberdeen Research and Development Center, Aberdeen Proving Ground, Maryland.

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18 U. S. C. Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

~~CONFIDENTIAL~~

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1939

OCTOBER 1968

AERODYNAMIC FORCE TESTS OF CONE CYLINDER FLECHETTE MODELS  
AT SUPERSONIC MACH NUMBERS (U)

Klaus O. Opalka

Exterior Ballistics Laboratory

In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Commanding Officer, U.S. Army Aberdeen Research and Development Center, Aberdeen Proving Ground, Maryland.

This document  
Does not contain  
Information  
Its transmission  
Should be controlled

Classification  
is the  
of 794.  
and in any  
of the

RDT&E Project No. 1T22901A201

ABERDEEN PROVING GROUND, MARYLAND

The following page is blank.

~~CONFIDENTIAL~~

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1939

KOOpalka/lca  
Aberdeen Proving Ground, Md.  
October 1968

AERODYNAMIC FORCE TESTS OF CONE CYLINDER FLECHETTE MODELS  
AT SUPERSONIC MACH NUMBERS (U)

(UNCLASSIFIED)

ABSTRACT

Wind tunnel force tests were performed to determine the influence of varying afterbody length on the aerodynamic characteristics of five slender cone cylinder flechette models. The test was performed in the supersonic wind tunnel No. 1 of the U.S. Army Ballistic Research Laboratories. Force and static stability parameters were determined at Mach numbers 1.5 to 4.0 at nearly constant Reynolds numbers. The results are presented and compared with theoretical data obtained from supersonic small disturbance theory.

(UNCLASSIFIED)

TABLE OF CONTENTS

|                                                                                   | Page |
|-----------------------------------------------------------------------------------|------|
| ABSTRACT . . . . .                                                                | 3    |
| LIST OF ILLUSTRATIONS . . . . .                                                   | 7    |
| LIST OF SYMBOLS . . . . .                                                         | 9    |
| 1. INTRODUCTION . . . . .                                                         | 11   |
| 2. EXPERIMENTAL INVESTIGATION . . . . .                                           | 12   |
| 2.1 Equipment . . . . .                                                           | 12   |
| 2.2 Procedure . . . . .                                                           | 13   |
| 2.3 Data Reduction . . . . .                                                      | 13   |
| 3. THEORETICAL PREDICTION . . . . .                                               | 14   |
| 4. RESULTS . . . . .                                                              | 15   |
| 4.1 Basic Aerodynamic Coefficients Versus Angle of Attack . .                     | 15   |
| 4.2 Aerodynamic Coefficients Versus Afterbody Length<br>and Mach Number . . . . . | 15   |
| 5. DISCUSSION . . . . .                                                           | 16   |
| 5.1 Center of Pressure . . . . .                                                  | 16   |
| 5.2 Slope of the Normal Force Curve . . . . .                                     | 17   |
| 5.3 Base Pressure . . . . .                                                       | 18   |
| 5.4 Axial Force . . . . .                                                         | 18   |
| 6. CONCLUSION . . . . .                                                           | 19   |
| 7. REFERENCES . . . . .                                                           | 35   |
| DISTRIBUTION LIST . . . . .                                                       | 36   |



(UNCLASSIFIED)

LIST OF ILLUSTRATIONS

| Figure                                                                                                                 | Page |
|------------------------------------------------------------------------------------------------------------------------|------|
| 1. Test Section With Installed Model . . . . .                                                                         | 20   |
| 2. External Dimensions of Balance . . . . .                                                                            | 20   |
| 3. Flechette Model Configurations . . . . .                                                                            | 21   |
| 4. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 1 at $Re_d \approx 5.5 \times 10^5$ . . . . .  | 22   |
| 5. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 1 at $Re_d \approx 2.7 \times 10^5$ . . . . .  | 23   |
| 6. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 2 at $Re_d \approx 5.5 \times 10^5$ . . . . .  | 24   |
| 7. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 3 at $Re_d \approx 5.5 \times 10^5$ . . . . .  | 25   |
| 8. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 3 at $Re_d \approx 2.7 \times 10^5$ . . . . .  | 26   |
| 9. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 4 at $Re_d \approx 5.5 \times 10^5$ . . . . .  | 27   |
| 10. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 5 at $Re_d \approx 5.5 \times 10^5$ . . . . . | 28   |
| 11. Aerodynamic Coefficients Versus Angle of Attack for<br>Configuration 5 at $Re_d \approx 2.7 \times 10^5$ . . . . . | 29   |
| 12. Center of Pressure Location Versus Afterbody Length . . . . .                                                      | 30   |
| 13. Center of Pressure Location Versus Mach Number . . . . .                                                           | 30   |
| 14. Center of Pressure Location Versus Mach Number -<br>Comparison With Theory and Free Flight Test Data . . . . .     | 31   |
| 15. Slope of Normal Force Coefficient Versus Afterbody Length . . . . .                                                | 31   |
| 16. Slope of Normal Force Coefficient Versus Mach Number . . . . .                                                     | 32   |

(UNCLASSIFIED)

LIST OF ILLUSTRATIONS

| Figure                                                                                                                                   | Page |
|------------------------------------------------------------------------------------------------------------------------------------------|------|
| 17. Slope of Normal Force Coefficient Versus Mach Number -<br>Comparison With Theory . . . . .                                           | 32   |
| 18. Base Pressure Coefficient Versus Afterbody Length<br>and Mach Number . . . . .                                                       | 33   |
| 19. Base Pressure Coefficient and Zero Lift Forebody Axial<br>Force Coefficient Versus Mach Number - Comparison<br>With Theory . . . . . | 33   |
| 20. Zero Lift Total Axial Force Coefficient Versus Mach Number -<br>Comparison With Theory and Free Flight Test Data . . . . .           | 34   |

(UNCLASSIFIED)

LIST OF SYMBOLS

|               |                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------|
| $C_A$         | zero lift total axial force coefficient, $F_A / (\frac{\pi}{4} d^2 q_\infty)$                               |
| $C_{PB}$      | base pressure coefficients, $(p_\infty - p_B) / q_\infty$                                                   |
| $C_{AFO}$     | zero lift forebody axial force coefficient, $C_{Ao} - C_{PB}$                                               |
| $C_M$         | pitching moment coefficient (reference at the model base),<br>$M / (\frac{\pi}{4} d^3 q_\infty)$            |
| $C_N$         | normal force coefficient, $F_N / (\frac{\pi}{4} d^2 q_\infty)$                                              |
| $C_{N\alpha}$ | slope of normal force curve, $\partial C_N / \partial \alpha$ , for zero angle of attack                    |
| $d$           | reference model diameter                                                                                    |
| $F_A$         | axial force                                                                                                 |
| $F_N$         | normal force                                                                                                |
| $M_\infty$    | free stream Mach number                                                                                     |
| $M$           | pitching moment (reference at the model base)                                                               |
| $p_\infty$    | free stream pressure                                                                                        |
| $p_B$         | base pressure                                                                                               |
| $q_\infty$    | free stream dynamic pressure $(\gamma/2) p_\infty M_\infty^2$                                               |
| $Re_d$        | Reynolds number based on reference model diameter and free stream conditions                                |
| $X_{CP}$      | center of pressure location with reference to the cone cylinder junction or to the model base (in calibers) |
| $X_{CYL}$     | length of the cylindrical afterbody (in calibers)                                                           |
| $\alpha$      | angle of attack                                                                                             |
| $\gamma$      | ratio of specific heats                                                                                     |

# CONFIDENTIAL

(CONFIDENTIAL)

## 1. INTRODUCTION

Nonspinning very slender bodies of revolution were stabilized in the past primarily by an array of tail mounted fins. These fins, however, have caused many problems since they have been in use. They are usually of a weak structure and, therefore, prone to be damaged. Seen from this point of view, mass stabilization appears to be advantageous over fin stabilization. Interest has arisen recently in the technique of mass stabilizing these bodies, referred to as flechettes.

Therefore, an investigation was initiated by the U.S. Army Munitions Command, Picatinny Arsenal. O'Keefe and Wassermann<sup>1</sup> found from a literature review that the most promising flechette configurations consisted of 8 to 10 caliber cones with a short afterbody of 1.5 to 3.0 calibers in length. They further determined the optimum cone for their purposes to be 8.85 calibers. Having their choice narrowed down by these findings, the investigators contacted the Ballistic Research Laboratories (BRL) at the Aberdeen Proving Ground and asked that the Exterior Ballistics Laboratory perform a wind tunnel force test on five flechette models at Mach numbers between 1.5 and 4.0 in order to determine the influence of the varying length of the afterbody on the aerodynamic characteristics of the flechettes.

The test was performed in July 1966, and the results are published in this report. Furthermore, they are also compared with theoretical data<sup>2</sup>, obtained from supersonic small disturbance theory.

Apart from this program, a free flight investigation was conducted in the range of the Exterior Ballistics Laboratory<sup>3</sup>. Thirteen rounds of the shortest model version (Configuration 1), measuring 0.2 inch in diameter at the base, were fired in February 1967 in order to obtain aerodynamic data. Seven of these rounds yielded good results and were included in this report for comparison.

Earlier experimental work on cone cylinders was published in 1954 by L. E. Schmidt<sup>4</sup>, who investigated the dynamic properties of pure cones and cone cylinders, and by W. E. Buford and S. Shatunoff<sup>5</sup>, who studied

CONFIDENTIAL

# CONFIDENTIAL

the effects of fineness ratio and Mach number on the normal force and the center of pressure of cone cylinders. The current data provide additional information on the flow past cone cylinders for configurations not investigated previously.

## (UNCLASSIFIED) 2. EXPERIMENTAL INVESTIGATION

The tests were conducted in the Supersonic Wind Tunnel No. 1 of the Exterior Ballistics Laboratory, BRL.

### 2.1 Equipment

The supersonic wind tunnel No. 1<sup>6</sup> is continuously operated and has a closed circuit. The test section is 15 inches high and 13 inches wide, and the angle of attack ranges from -10 to +10 degrees. Figure 1 shows a picture of the test section with the model (Configuration 1) installed. The flexible nozzle is calibrated for Mach numbers between 1.5 and 5.0; accuracy of the calibration is  $\pm 0.01$  absolute error. The Reynolds number can be varied between  $0.1 \times 10^6$  and  $0.6 \times 10^6$  per inch.

A three component strain gage balance was used in the test to detect the aerodynamic forces acting on the model. Its load capacities are

|              |                       |
|--------------|-----------------------|
| Normal force | 12 lbs. between gages |
| Axial force  | 5 lbs.                |

The external dimensions of the balance, belonging to a set of eight are given in Figure 2.

For determining the contribution of the base pressure on the axial force, the base pressure was measured through a 1/16 inch diameter flexible tube and monitored by a pressure transducer of appropriate range.

The model dimensions are given in Figure 3. All five configurations consist of the same cone, measuring 8.85 calibers in length and 1.15 inches in diameter at the base. The cylindrical afterbody varies in length from 1.5 to 3.5 calibers.

# CONFIDENTIAL

## 2.2 Procedure

The test schedule and the test conditions are given in the following table

| M   | $Re_d \times 10^{-6}$ | Configurations |
|-----|-----------------------|----------------|
| 1.5 | .541                  | 1 2 3 4 5      |
|     | .276                  | 1 3 5          |
| 2.0 | .552                  | 1 2 3 4 5      |
|     | .265                  | 1 3 5          |
| 2.5 | 0.541                 | 1 2 3 4 5      |
|     | 0.265                 | 1 3 5          |
| 3.0 | .541                  | 1 2 3 4 5      |
|     | .173                  | 1 3 5          |
| 3.5 | 0.564                 | 1 2 3 4 5      |
|     | 0.276                 | 1 3 5          |
| 4.0 | 0.564                 | 1 2 3 4 5      |
|     | 0.276                 | 1 3 5          |

After the flow was established, the standard procedure was to record the aerodynamic forces every full degree angle of attack beginning with the maximum angle ( $11^\circ$ ) and proceeding towards its minimum value ( $-6^\circ$ ). A zero angle of attack reference check is made at the beginning and at the end of each test run. To obtain more test points for the determination of the derivatives of normal force and pitching moment, readings were taken every half degree between plus and minus two degrees. Schlieren photographs were taken at zero degree angle of attack.

## 2.3 Data Reduction

The data were reduced on the BRL computer (ORDVAC) using the standard program for three component measurements. The derivative of the normal force at zero lift,  $C_{N_{\alpha 0}}$ , was averaged analytically and graphically from seven test points between  $+2$  and  $-2$  degrees. The analytical method employed to obtain the derivative was that of least squares. The results of both methods were compared in order to eliminate erroneous

test points affecting the least squares fit.

From calibration data and repeatability tests, the accuracy of the data was estimated to be better than  $\pm 0.05$  and  $\pm 0.1$  absolute error in the normal and axial force coefficients respectively and 0.1 calibers in the center of pressure. The derivative of the normal force coefficient was found to be accurate within 5% of its value.

All angles of attack have been corrected for strut deflection due to aerodynamic load and for the flow inclination in the tunnel.

### (UNCLASSIFIED) 3. THEORETICAL PREDICTION

Extensive theoretical studies of the supersonic flow past cone cylinders have been made at the NRL by Clippinger, Hesse and Carter<sup>1</sup> in 1950 using the method of characteristics. During the past few years, R. L. McCoy<sup>2</sup> has been providing predictions on cone cylinder models based on supersonic small disturbance theory. This latter method avoids the disadvantages of the method of characteristics (laborious and time consuming) and yet provides adequate accuracy for most practical cases.

The current computational scheme is based on Van Dyke's hybrid theory<sup>8</sup>. It consists of a second order solution for the axisymmetric flow past slender bodies of revolution onto which a first order approximation of the cross flow is superimposed. This inviscid flow model yields a pressure distribution that is integrated and resolved into normal and axial force components. The method has proven excellent agreement with the method of characteristics.

Corrections accounting for the effects of viscosity were also incorporated into the program. The principal contributions of viscosity at the considered Mach numbers (1.5 thru 5.0) arise from skin friction, boundary layer thickness and flow structure in the near wake. The latter will influence the base pressure.

Van Driest's theory for laminar and turbulent compressible boundary layers<sup>9</sup> was selected for the calculation of skin friction. Chapman's

and Sternberg's<sup>11</sup> theories were chosen to obtain a prediction of the base pressure.

(UNCLASSIFIED)

#### 4. RESULTS

The experimental results of the wind tunnel test are presented in two groups of graphs. In the first group, the basic aerodynamic coefficients are plotted versus angle of attack. In the second group, the influence of afterbody length and Mach number on the force and stability coefficients at zero angle of attack is shown, and the experimental results are compared with the theoretical prediction.

##### 4.1 Basic Aerodynamic Coefficients Versus Angle of Attack

The normal force coefficient,  $C_N$ , the center of pressure,  $X_{CP}$ , the total axial force at zero lift,  $X_A$ , and the base pressure coefficient,  $C_{PB}$ , are plotted versus angle of attack in Figures 4 through 11.

The data of one configuration at all Mach numbers and at constant Reynolds number are presented on a single plot. For completeness sake, all test data are presented including those at the lower test Reynolds number ( $0.27 \times 10^6$ ). These data are included to serve as background for the summary data and for further information. In the following evaluation, however, only the test data at the higher test Reynolds number ( $0.55 \times 10^6$ ) have been considered.

##### 4.2 Aerodynamic Coefficients Versus Afterbody Length and Mach Number

The influence of the afterbody and the Mach number on the center of pressure are shown in Figures 12 and 13. The two groups of curves represent two reference positions on the model. The data of the upper group represent the center of pressure as measured from the base of the model. In the lower group the location of the C.P. is given with respect to the cone cylinder junction, i.e. the base of the cone alone. In Figure 14 the C.P. location of the shortest (1) and the longest (5) flechette configuration are compared with the results of the theoretical prediction prepared by R. L. McCoy<sup>2</sup>. Some of the free flight test data



# CONFIDENTIAL

of Configuration 1 are also included for comparison.

The effect of afterbody and Mach number on the slope of normal force curve is shown in Figures 15 and 16. Figure 17 presents a comparison of the experimental data with the prediction for Configurations 1 and 5.

The data for the base pressure and the axial force are given in Figures 18 through 21. The base pressure coefficient (Figure 19) and the total axial force coefficient (Figure 20) are compared with the results of the prediction. Drag data obtained from free flight tests are included in Figure 23.

(CONFIDENTIAL)

## 5. DISCUSSION

The primary objective of the wind tunnel test was to determine the center of pressure (C.P.) position on the model. In addition, the other data were obtained representing the remaining properties of the model with regard to lift and drag.

### 5.1. Center of Pressure

The distance between the center of mass (C.G.) and the center of pressure (C.P.) on the model

$$D = \bar{x}_{CG} - \bar{x}_{CP}$$

is the most important parameter for the originator of this wind tunnel test<sup>1</sup>. Highest possible stability is obtained when the distance between the two centers is greatest; that is to say that the C.G. should lie as forward as possible on the model and the C.P. as aft as possible.

The method of stabilization being investigated is to add a light cylindrical skirt to a massive cone in an attempt to move the C.P. aft with only a slight adverse effect on the C.G. If the mass of the skirt is enough to influence the C.G. significantly, then the advantage is partly or even completely offset.

# CONFIDENTIAL

# CONFIDENTIAL

The results in Figure 12 (lower curves) show that the C.P. moves aft with increasing cylinder length only by a small amount ( $0 - 0.5$  caliber C.P. caliber cylinder length) depending on the Mach number, and it can be concluded that the method is not very effective particularly at the lower test Mach numbers ( $M = 1.5 - 2.5$ ).

The influence of the Mach number on the C.P. location may be seen in Figure 13. Here the model with the shortest afterbody appears to be advantageous as the C.P. location will change least among the model series during the flight from higher to lower Mach numbers.

A comparison between our experimental data, McCoy's theoretical prediction<sup>2</sup> and the available free flight test results<sup>3</sup> is given in Figure 14. The experimental data fall between the curve for inviscid flow and that one corrected for fully turbulent boundary layer. (The correction for laminar boundary layer was not available.) In fact, the boundary layer of the wind tunnel models was found to be predominantly laminar, the transition occurring somewhere on the rear portion (second half) of the model (see also section 5.1). The free flight and wind tunnel data agree quite well and the differences between prediction and experiment amount to 13% of the theoretical value. The Reynolds number based on model diameter range from  $1.5 \times 10^5$  at Mach number 1.5 to  $1.1 \times 10^6$  at Mach number 3.5 for the free flight data. The wind tunnel data were measured at nearly constant Reynolds number ( $5.5 \times 10^5 \pm 0.1 \times 10^5$ ).

## 5.2 Slope of the Normal Force Curve

The influence of the afterbody length on the slope of the normal force curve,  $C_{N_{\alpha}}$  (Figure 15) increases with increasing Mach number. The change in the slope of the fittings in Figure 15 from zero to positive values combined with the reversal in the magnitude of the value of  $C_{N_{\alpha}}$  for the shorter afterbody lengths has also been observed by Euford and Shatunoff in their investigation of the effects of the afterbody length of cone cylinder models.

CONFIDENTIAL

# CONFIDENTIAL

The influence of the Mach number on  $C_{L_{max}}$  is demonstrated in Figure 16 and the data for the shortest and the longest configuration are compared with the prediction in Figure 17. The deviation between the inviscid flow prediction and the experimental data is generally less than 1% of the theoretical value except for the data of configuration 1 at and above  $M_{\infty} = 3$ .

## 5.3 Base Pressure

The influence of afterbody length and Mach number on the base pressure are shown in Figure 18. As there is no influence of the afterbody length evident from the tests, only the data of the shortest (1) and the longest (5) flechette configuration are plotted versus the Mach number and the trend is represented by one fitting. A comparison between the experimental findings and the theoretical base pressure prediction is given in Figure 19. The prediction is based on empirical theories<sup>10, 11</sup> which presuppose the existence of a turbulent boundary layer.

A study of the available schlieren pictures disclosed that the boundary layer was predominantly laminar on the wind tunnel tested models and the percentage of turbulent boundary layer along the models appeared to increase with higher Mach numbers. Therefore, the discrepancy between prediction and experiment is not surprising.

## 5.4 Axial Force

The afterbody length has only a very slight influence on the zero lift axial force stemming from the friction along the afterbody surface, and the data were, therefore, not shown plotted versus this parameter.

A comparison of the results for the axial force versus Mach number obtained from free flight tests, theoretical prediction and the wind tunnel test is shown in Figure 20.

The free flight drag data (obtained at angle of attack varying between 1.5 and 4.0 degrees) appear to agree with the prediction for turbulent boundary layer (at zero angle of attack).

# CONFIDENTIAL

The comparison of the wind tunnel data with the prediction suggests a laminar boundary layer in the wind tunnel test and the difference between theory and experiment could then be explained primarily as the difference between the measured and the predicted base pressure (Figure 19). The coincidence of the predicted and the measured zero lift forebody axial force in Figure 19 confirms that this explanation is correct.

However, the forebody axial force data also indicate (in agreement with flow photographs) that the boundary layer was not fully laminar in the test and that it tended to become more turbulent with increasing Mach number. This may account for a secondary contribution to the differences of the axial force data in Figure 20.

(UNCLASSIFIED)

## 6. CONCLUSION


The method of mass stabilizing cone cylinder flechettes by increasing the length of a cylindrical skirt up to 3.5 caliber is found to be of little effectiveness. Within the scope of the test, the most favorable C.P. location is obtained for a short cylindrical skirt of 1.0 to 2.5 caliber in length.

The experimental wind tunnel data for the center of pressure agree with the theoretical prediction within 1% and with the available results from free flight tests in the range of this Laboratory within 5%.

The differences in the axial force measurements resulting from the wind tunnel test and from the free flight range test are caused by different boundary layer conditions.

# CONFIDENTIAL





CONFIDENTIAL




Figure 4. (C) Aerodynamic Coefficients Versus Angle of Attack  
for Configuration 1 at  $Re = 5.5 \times 10^6$  (1)

CONFIDENTIAL

CONFIDENTIAL




Figure 5. (c) Aerodynamic Coefficients Versus Angle of Attack  
for Configuration 1 at  $Re = 2.5 \times 10^5$  (U)

CONFIDENTIAL



CONFIDENTIAL





Figure 1. (1) Aerodynamic characteristics versus Angle of Attack  
for configuration 1 at Reynolds number  $Re = 10^6$

CONFIDENTIAL


CONFIDENTIAL

CONFIDENTIAL



CONFIDENTIAL

CONFIDENTIAL



ANGLE OF ATTACK, DEG

Figure 1. (1) Airfoil, Configuration 2 Versus Angle of Attack  
for Configuration 2 at  $M_{\infty} = 1.5$  to 3.0 (2)


CONFIDENTIAL

CONFIDENTIAL

CONFIDENTIAL

MACH

• 1.5  
▲ 2.5  
▼ 3.0  
+ 3.5  
x 4.0  
⊗ 5.0



ANGLE OF ATTACK, DEG.

Fig. 1. (\*) Aerodynamic coefficients versus angle of attack for the configuration shown in Fig. 2. (°)

CONFIDENTIAL

CONFIDENTIAL





Figure 1. (2) Aerodynamic Coefficients Versus Angle of Attack  
for Configuration 3 at  $M_\infty = 2.0$  x 2. (ii)

CONFIDENTIAL

CONFIDENTIAL

MACH  
3.5  
3.0  
2.5  
2.0  
1.5  
1.0  
0.5



ANGLE OF ATTACK, DEG

Figure 1. (a) Wind-tunnel measurements of lift and drag coefficients  
(b) Calculated results from the program (c)

CONFIDENTIAL

CONFIDENTIAL




Figure 1. (C) Aerodynamic Coefficients Versus Angle of Attack for Configuration 5 at  $Re_1 = 5.0 \times 10^6$  (C)

CONFIDENTIAL

CONFIDENTIAL




Figure 11. (2) Aerodynamic Characteristics versus Angle of Attack  
for Configuration 5 at  $Re = 2.0 \times 10^6$  (1)

CONFIDENTIAL



CONFIDENTIAL




Figure 12. (C) Center of Pressure Location Versus Afterbody Length (U)




Figure 13. (C) Center of Pressure Location Versus Mach Number (U)

CONFIDENTIAL

CONFIDENTIAL




Figure 14. (C) Center of Pressure Location Versus Mach Number - Comparison With Theory and Free Flight Test Data (U)




Figure 15. (C) Slope of Normal Force Coefficient Versus Afterbody Length (U)

CONFIDENTIAL

CONFIDENTIAL




Figure 16. (C) Slope of Normal Force Coefficient Versus Mach Number (U)




Figure 17. (C) Slope of Normal Force Coefficient Versus Mach Number - Comparison With Theory (U)

CONFIDENTIAL

**CONFIDENTIAL**




Figure 18. (C) Base Pressure Coefficient Versus Afterbody Length and Mach Number (U)




Figure 19. (C) Base Pressure Coefficient and Zero Lift Forebody Axial Force Coefficient Versus Mach Number-Comparison With Theory (U)

**CONFIDENTIAL**

CONFIDENTIAL




Figure 20. (c) Zero Lift Total Axial Force Coefficient Versus Mach Number - Comparison With Theory and Free Flight Test Data (U)

CONFIDENTIAL

(UNCLASSIFIED)

REFERENCES

1. W. O'Keefe and S. Wasserman. "Supersonic Wind Tunnel and Instrumented Free Flight Tests of Cone Cylinder, Mass Stabilized Flechettes (U)." Picatinny Arsenal (May 1967). To be published. CONFIDENTIAL
2. R. L. McCoy. "Estimation of Supersonic Static Aerodynamic Characteristics of Pointed Bodies of Revolution at Small Angles of Attack." BRL Communication. Unpublished.
3. V. Cskay. "Review of Cone Cylinder Flechette Tests." BRL Memorandum. Unpublished.
4. L. E. Schmidt. "The Dynamic Properties of Pure Cones and Cone Cylinders." BRL Memorandum Report No. 749, July 1954.
5. W. E. Buford and S. Chaturhoff. "The Effects of Fineness Ratio and Mach Number on the Normal Force and Center of Pressure of Conical and Ogival Head Bodies." BRL Memorandum Report No. 760, February 1954.
6. J. C. McMullen. "Wind Tunnel Testing Facilities at the Ballistic Research Laboratories." BRL Memorandum Report No. 1292, July 1957.
7. R. F. Clippinger, J. H. Giese and W. C. Charter. "Tables of Supersonic Flows About Cone Cylinders." BRL Report No. 729, July 1950.
8. E. D. Van Dyke. "First and Second Order Theory of Supersonic Flow Past Bodies of Revolution," JAS, March 1951.
9. E. R. Van Driest, "Turbulent Boundary Layer in Compressible Fluids." JAS, March 1951.
10. D. R. Chapman. "An Analysis of Base Pressure at Supersonic Velocities and Comparison With Experiment," NACA Report No. 1051, 1951.
11. J. Sternberg, "Effect of a Boattail on the Base Pressure." May 1948, published by B. G. Karpov in BRL Report No. 1295, 1965.

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |                                                                                                                                                   |                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| 1. ORIGINATING ACTIVITY (Corporate author)<br>U.S. Army Aberdeen Research and Development Center<br>Ballistic Research Laboratories<br>Aberdeen Proving Ground, Maryland                                                                                                                                                                                                                                                                                                                                                                               |  | 2a. REPORT SECURITY CLASSIFICATION<br>Confidential                                                                                                |                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  | 2b. GROUP<br>3                                                                                                                                    |                     |
| 3. REPORT TITLE<br>AERODYNAMIC FORCE TESTS ON CONE CYLINDER FLECHETTE MODEL AT SUPERSONIC<br>FLOW CONDITIONS (U)                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |                                                                                                                                                   |                     |
| 4. DESCRIPTIVE NOTES (Type of report and inclusive dates)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |  |                                                                                                                                                   |                     |
| 5. AUTHOR(S) (First name, middle initial, last name)<br>Camp, C. Ernest                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |                                                                                                                                                   |                     |
| 6. REPORT DATE<br>1957                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  | 7a. TOTAL NO OF PAGES<br>10                                                                                                                       | 7b. NO OF REFS<br>0 |
| 8a. CONTRACT OR GRANT NO.<br>b. PROJECT NO. W-16-ATT-27-129-1231<br>c.<br>d.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  | 9a. ORIGINATOR'S REPORT NUMBER(S)<br>Memorandum Report No. 1231<br>9b. OTHER REPORT NO(S) (Any other numbers that may be assigned<br>this report) |                     |
| 10. DISTRIBUTION STATEMENT In addition to security requirements which must be met, this document is subject to special export controls and its transmittal to foreign governments or foreign nationals may be made only with prior approval of Commanding Officer, U.S. Army Aberdeen Research and Development Center, Aberdeen Proving Ground, Maryland                                                                                                                                                                                               |  |                                                                                                                                                   |                     |
| 11. SUPPLEMENTARY NOTES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  | 12. SPONSORING MILITARY ACTIVITY<br>U. S. Army Materiel Command<br>Washington, D. C.                                                              |                     |
| 13. ABSTRACT<br>Wind tunnel force tests were performed to determine the influence of varying afterbody length on the aerodynamic characteristics of five slender cone cylinder flechette models. The test was performed in the supersonic wind tunnel No. 1 of the U. S. Army Ballistic Research Laboratory. Force and static stability parameters were determined at Mach numbers 1.5 to 4.0 at nearly constant Reynolds numbers. The results are presented and compared with theoretical data obtained from supersonic small disturbance theory. (U) |  |                                                                                                                                                   |                     |

DD FORM 1473  
1 NOV 66

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS  
OBSOLETE FOR ARMY USE.

Unclassified

Security Classification

Unclassified

Security Classification

| 14. | KEY WORDS                                                                                                | LINK A |    | LINK B |    | LINK C |    |
|-----|----------------------------------------------------------------------------------------------------------|--------|----|--------|----|--------|----|
|     |                                                                                                          | ROLE   | WT | ROLE   | WT | ROLE   | WT |
|     | Flechettes<br>Wind Tunnel Test<br>Cone Cylinders<br>Supersonic Aerodynamics<br>Experimental Aerodynamics |        |    |        |    |        |    |

Unclassified

Security Classification