

UNCLASSIFIED

AD **400 782**

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

400 782

41315

21

STEP
26.5110

S/170/62/005/010/008/009
B104/B186

AUTHOR: Zhuk, I. P.

TITLE: Calculation of the temperature field of a multilayered wall

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, v. 5, no. 10, 1962, 100 - 103

TEXT: This is studied for the following cases: (a) the temperature field on the outer surface changes harmonically ($t_1(0, \tau) = t_{10} + t_m \cos \omega \tau$, $t_1(0, 0) = t_{10} + t_m = T_1$), while the temperature on the inner surface remains constant: ($t_n(l_n, \tau) = T_n$). (b) The temperature field on the outer surface changes harmonically ($t_1(0, \tau) = t_{10} + t_m \cos \omega \tau = t_1(0, \tau)$, $t_{10} + t_m = T_1$), while on the inner surface heat is exchanged with a medium at constant temperature ($\lambda_n \frac{\partial t_n}{\partial x} = -\alpha(t - t_{mean})$) $x = l_n$. The general solution

Card 1/4

Calculation of the temperature...

S/170/62/005/010/008/009
B104/B186

$$t_k(x, \tau) = d_k x + b_k + t_m [\Phi_k(\rho, x, \tau)|_{\rho=0} + \text{Re} \Phi_k(x, \rho, \tau)|_{\rho=l_n}] + \sum_{j=1}^{\infty} A \Phi'_k(\rho, x, \tau)|_{\rho=-l_j^2}$$

$$\Phi_k = \frac{\Delta_k e^{q_k x} + \Delta_{-k} e^{-q_k x}}{\Delta} \exp(\rho \tau); \quad q_k = \sqrt{\frac{\rho}{a_k}}; \quad (2)$$

$$\Delta = \begin{vmatrix} 1 & 1 & 0 & 0 & \dots & 0 \\ a_{11} & a_{12} & a_{13} & a_{14} & \dots & a_{1 \ 2n} \\ \dots & \dots & \dots & \dots & \dots & \dots \\ a_{2n-1 \ 1} & a_{2n-1 \ 2} & a_{2n-1 \ 3} & a_{2n-1 \ 4} & \dots & a_{2n-1 \ 2n} \end{vmatrix}$$

to system

$$\frac{\partial t_k}{\partial \tau} = a_k \frac{\partial^2 t_k}{\partial x^2} \quad k = 1, \dots, n; \quad (1)$$

$$t_{k+1}(l_k, \tau) = t_k(l_k, \tau); \quad \frac{\lambda_k}{\lambda_{k+1}} \frac{\partial t_k}{\partial x} = \frac{\partial t_{k+1}}{\partial x} \Big|_{x=l_k}$$

Card 2/4

Calculation of the temperature...

S/170/62/005/010/008/009
B104/B186

of this problem takes the form

$$t_1(x, \tau) = d_1 x + b_1 - t_m [A_1(x) - B_1(x) \cos(\omega\tau - \gamma + \beta_{1x})] + \sum_{j=1}^{\infty} D_1(x) \exp(-\mu_j^2 \tau), \quad (3)$$

$$t_2(x, \tau) = d_2 x + b_2 - 2t_m [A_2(x) - B_2(x) \cos(\omega\tau - \gamma - \beta_{2x})] + \sum_{j=1}^{\infty} D_2(x) \exp(-\mu_j^2 \tau), \quad (4)$$

$$t_3(x, \tau) = d_3 x + b_3 - 4t_m [A_3(x) - B_3(x) \cos(\omega\tau - \gamma - \beta_{3x})] + \sum_{j=1}^{\infty} D_3(x) \exp(-\mu_j^2 \tau), \quad (5)$$

for a three-layered wall. This solution is discussed for the cases (a) and (b). Thus it is possible to calculate the heat transfer through a wall in which the heat is multiply reflected, also to determine the times when thermal oscillations occur and when the maximum temperature is attained.

Card 3/4

Calculation of the temperature...

S/170/62/005/010/008/009
B104/B186

ASSOCIATION: Energeticheskiy institut AN BSSR, g. Minsk (Institute of Power Engineering AS BSSR, Minsk)

SUBMITTED: May 26, 1962

Card 4/4