

UNCLASSIFIED

AD NUMBER
AD400783
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; DEC 1962. Other requests shall be referred to US Library of Congress, Attn: Aerospace Technology Division, Washington, DC.
AUTHORITY
ATD ltr, 2 Dec 1965

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD

400 783

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

400 783

41316

STEP
26.5/100S/170/62/005/010/009/009
B104/B186

AUTHOR: Temkin, A. G.

TITLE: Temperature field of a multilayered wall

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, v. 5, no. 10, 1962, 104 - 117

TEXT: If k finite measurement values are available the equation of heat conduction through a multilayered wall is

$$C(r) \frac{\partial t}{\partial \tau} = r^{1-k} \frac{\partial}{\partial r} \left[\lambda(r) r^{k-1} \frac{\partial t}{\partial r} \right] \quad (1.1)$$

The specific heat C and the coefficient of heat conduction λ of this wall depend considerably on the coordinates and are piece-wise continuous functions.

$$\frac{\partial t}{\partial F} = \frac{1}{C(N) N^{k-1}} \frac{\partial}{\partial N} \left[\Lambda(N) N^{k-1} \frac{\partial t}{\partial N} \right] \quad (1.6)$$

is obtained from (1) by introducing the dimensionless coordinate $N = r/r_e$, the Fourier number $F = \alpha_0 \tau / r_e^2$, the dimensionless thermal conductivity

Card 1/4

Temperature field of a multilayered...

S/170/62/005/010/009/009
B104/B186

$\Lambda(N) = \lambda(r) / \lambda_0$ and the dimensionless specific heat $C(N) = C(r) / \alpha_0 \lambda_0$.
 $t(N_1, F) = t_1(F)$, $\Lambda(N_2) \frac{\partial t(N, E)}{\partial N} = q(F)$ are the mixed boundary conditions.

The solution is obtained as a series

$$t(N, F) = t_1(F) 1 + t_2'(F) \nabla^{-2} 1 + \dots + t_1^{(n)}(F) \nabla^{-2n} 1 + \dots + q(F) \alpha(N) + q'(F) \nabla^{-2} \alpha + \dots + q_1^{(n)}(F) \nabla^{-2n} \alpha + \dots \quad (2.4)$$

arranged with respect to the derivatives of the quantities to be measured and the radial quasipolynomials of the problem. The function (2.4) describes the temperature field at sufficiently long time values for the initial temperature distribution no longer to influence the heat conduction. The Fourier integral makes it possible to construct the field of the aftereffect of this problem. It can be shown that this field gradually vanishes and that at the initial moment a temperature distribution appears contradicting the initial value of the function (2.4). If the temperatures on the surfaces N_1 and N_2 are known functions of time,

then the field of the action can be represented as the sum of the two series:
Card 2/4

Temperature field of a multilayered...

S/170/62/005/010/009/009
B104/B186

$$t(N, F) = \sum_{n=0}^{\infty} t_1^{(n)}(F) P_n(N, N_1) + t_2^{(n)}(F) P_n(N, N_2) \quad (3.3).$$

The series are arranged accordingly with respect to the derivatives of the temperatures to be measured and with respect to the radial quasipolynomial of the problem. The convective heat exchange with media at variable temperatures is studied with the aid of the boundary conditions

$$[t_1(F) - t(N_1, F)] B_1 = -\Lambda(N_1) \frac{\partial t(N_1, F)}{\partial N} \quad (4.1)$$

$$[t(N_2, F) - t_2(F)] B_2 = -\Lambda(N_2) \frac{\partial t(N_2, F)}{\partial N} \quad (4.2)$$

of the third kind. For the field of action

$$t(N, F) = t_1(F) P_0(N, N_1) + t_1^{(1)}(F) P_1(N, N_1) + \dots + t_1^{(n)}(F) P_n(N, N_1) + \dots + t_2(F) P_0(N, N_2) + t_2^{(1)}(F) P_1(N, N_2) + \dots + t_2^{(n)}(F) P_n(N, N_2) + \dots \quad (4.4)$$

is obtained in a similar way. This series is arranged with respect to the
Card 3/4

Temperature field of a multilayered...

S/170/62/005/010/009/009
B104/B186

derivatives of the temperatures of the inner and outer medium. If the temperature on the inner surface is kept constant, and if the temperature on the outer surface varies periodically, then

$$t(N, F) = t_1 P_0(N, N_1) + t_1 [P_0(N, N_2) - \omega^2 P_2(N, N_2) + \omega^4 P_4(N, N_2) - \dots] \cos \omega F + t_2 [-\omega P_1(N, N_2) + \omega^3 P_3(N, N_2) - \omega^5 P_5(N, N_2) + \dots] \sin \omega F, \quad (5.20)$$

is valid for the field of action.

ASSOCIATION: Tekhnicheskiy institut rybnoy promyshlennosti i khozyaystva, g. Kaliningrad (Technical Institute of the Fish Industry and Fisheries, Kaliningrad)

SUBMITTED: July 23, 1962

Card 4/4