

UNCLASSIFIED

AD. 401_250

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

FOR OFFICIAL USE ONLY

CATALOGED BY
AS AD
ASTIA 401 250

401 250

Technical Report

R 112 SUPPLEMENT

SNOW-COMPACTION EQUIPMENT —
VIBRATORY FINISHERS

21 June 1962



U. S. NAVAL CIVIL ENGINEERING LABORATORY
Port Hueneme, California

ASTIA
JUL 25 1962

**SUPPLEMENT TO TR-112, SNOW-COMPACTION EQUIPMENT — VIBRATORY
FINISHERS**

Y-F015-11-079

Type B Final Report

by

E. H. Moser, Jr., S. E. Gifford

ABSTRACT

This supplement identifies the proprietary components used in the shoe-type and rolling-type vibratory finishers and auxiliary equipment described in TR-112. These finishers were used to investigate the feasibility of surface-hardening compacted snow by vibration in the construction of load-bearing areas by the Navy cold-processing techniques.

SHOE-TYPE VIBRATORY FINISHER

The initial design of the shoe-type vibratory finisher was developed in 1954 by the Pettibone-Wood Manufacturing Company, North Hollywood, California, under contract NOy 73253. This design, detailed in the manufacturer's drawings 6425 and 6426, included the following proprietary items:

1. A 300-inch-pound vibrator, Pettibone-Wood assembly 6050.
2. A 5-hp, 1750-rpm, 3-phase, 60-cycle, 220/440-volt standard electric motor with a U. S. Electric Motor's Inc. varidrive: frame 23-254-21, model VEVGH, 4:1 reduction.
3. A manually operated clutch, Rockford LMS-5520 with drive plate LM-526, and driving cup and hub bearing assembly ULM-530-20 bored 1.376.375 inches with a 3/8- x 3/16-inch keyway.

Modifications to the shoe-type finisher by the Laboratory between 1955 and 1957 resulted in the replacement of the varidrive electric motor and manual clutch with a hydraulic motor and flexible coupling. These changes, shown on Y&D drawings 943610 and 943611, resulted in the use of the following proprietary items:

1. A hydraulic motor rated at 7.7 hp at 1800 rpm and 24.4 gpm of hydraulic fluid at 1000 psi, Vickers model M2-334-60-1C.
2. A double roller-chain flexible coupling, Morse model 4016.
3. Two 20-foot lengths of 3/4-inch-diameter low-temperature hydraulic hose, Aeroquip model 1513 industrial hose fitted with a Snap-tite VEC-12F type 3/4-inch quick-disconnect coupler at one end and a 3/4-inch male pipe fitting at the opposite end.
4. One 20-foot length of 1-inch-diameter low-temperature hydraulic hose, Aeroquip model 30302 fitted with a Snap-tite VEC-16F type 1-inch quick-disconnect coupler at one end and a 1-inch male pipe fitting at the opposite end.

ROLLING-TYPE VIBRATORY FINISHER

The roller-type vibratory finisher was developed by the Essick Manufacturing Company, Los Angeles, California. A modified unit was obtained in 1958 under contract NBy-3164. The unit, shown in the manufacturer's drawings 4-D-44, 4-D-45, 4-D-46, 4-M-22, and 4-M-23, includes the following proprietary items:

1. A vibrator roller, Essick Manufacturing Company model VR-72-TEC, including:
 - a. A 59-hp (1800-rpm) gasoline engine, Continental Motor Corporation model F-226.
 - b. A Vee-belt drive using a matched set of five belts, Gates Rubber Company Vulco V-V drive C-112.
 - c. An automatic centrifugal clutch, engaging at 800 rpm.
 - d. A hand-operated plate clutch.
2. A remote-reading tachometer, Sun Electric Corporation.

PORTABLE HYDRAULIC POWER-PACK UNIT

The portable hydraulic power-pack unit used to energize the hydraulic motor on the shoe-type finisher was manufactured in 1956 by Vickers, Incorporated, El Segundo, California, under contract NBy-3112. It was designed as a CJO-21226 hydraulic power unit assembly, which consisted of:

1. A Vickers 60-gallon reservoir and cover assembly, complete with engine-to-pump coupling, coupling guard, piping, pump spacers, suction filter, baffle, air-level gage, filler cap, and breather assembly.
2. A Vickers pump V-334-24-1A-11.
3. A Vickers valve FRG-06-28-11.
4. A Vickers subplate FRGM-06-10.
5. A Continental Model F-162, 20-hp, 1400-rpm, 6-volt, liquid-cooled engine complete with starter and generator, water-temperature gage, tachometer, and hour meter.
6. A maintenance manual assembled by Vickers for Continental engine and hydraulic components.

HYDRAULIC POWER TAKE-OFF ON THE NAVY DUAL-RAIL SNOW TRACTOR

The Model D-4 tractor modified with dual rails to a low-ground-pressure snow tractor, * which was used to tow the finisher, is manufactured by the Caterpillar Tractor Company, Peoria, Illinois. It is fitted with a Caterpillar No. 44 hydraulic control for operating a dozer blade.

Two sets of rear hydraulic lines are available for this control; one for direct drive from the pump unit and one for combination drive with the dozer blade. The D-4 snow tractor was fitted with both sets of lines, each of which was modified for use with quick-disconnect couplings. These modifications entailed replacing the tubing through the tractor cab with double-strength black iron pipe and fitting the terminal ends of the pipe with Snap-tite VEN-16F type 1-inch quick-disconnect nipples.

* NCEL Technical Report R-106, Dual-Rail Snow Tracks for the Caterpillar D-4 Tractor, by A. C. Scott and Douglas Taylor.

Distribution List

No. of copies

10	Chief, Bureau of Yards and Docks (Code 70)
1	President, Marine Corps Equipment Board, Marine Corps School, Quantico, Va.
1	Director, U. S. Army Engineer Research and Development Laboratories, Attn: Information Resources Branch, Fort Belvoir, Va.
10	Armed Services Technical Information Agency, Arlington Hall Station, Arlington, Va.
1	U. S. Army Cold Regions Research and Engineering Laboratory, Corps of Engineers, P. O. Box 282, Hanover, New Hamp.
1	Commander, U. S. Naval Support Force, Antarctica, 6th and Independence Ave., S. W., Washington, D. C.
1	Director of U. S. Antarctic Research Program, National Science Foundation, Washington, D. C.
1	Chief of Naval Operations (OP-07T), Navy Department, Washington, D. C.
1	Antarctic Projects Office, Department of Defense, Washington, D. C.
1	Commander, Antarctic Support Activities, Navy No. 20, FPO, San Francisco, Attn: Public Works Officer