

63-3-2

UNALOGED BY ASTIA
AS AD No. 402147



MEMORANDUM REPORT NO. 1438
NOVEMBER 1962

CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY
PULSE EXPERIMENTAL REACTOR ASSEMBLY

Frederick H. Gregory



Department of the Army Project No. 512-10-001
BALLISTIC RESEARCH LABORATORIES

ABERDEEN PROVING GROUND, MARYLAND

ASTIA AVAILABILITY NOTICE

Qualified requestors may obtain copies of this report from ASTIA.

**The findings in this report are not to be construed
as an official Department of the Army position.**

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1438

NOVEMBER 1962

**CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY PULSE
EXPERIMENTAL REACTOR ASSEMBLY**

Frederick H. Gregory

Terminal Ballistics Laboratory

Department of the Army Project No. 512-10-001

ABERDEEN PROVING GROUND, MARYLAND

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1438

FHGregory/ic
Aberdeen Proving Ground, Md.
November 1961

CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY PULSE
EXPERIMENTAL REACTOR ASSEMBLY

ABSTRACT

Calculations are made to estimate, as a function of distance, the radiation dose levels which would occur during full capacity operation of the Army Pulse Reactor Assembly (APRA) scheduled for construction at Aberdeen Proving Ground, Maryland. Calculations of the neutron dose are made by two methods. The first calculation (Method A) is made by utilizing an experimentally determined effective dose mean free path, which probably includes the effect of ground scattering. The second calculation (Method B) is made by utilizing the result of a Monte Carlo calculation of neutron transmission in air. The results of this calculation indicate considerably higher dose levels than indicated by Method A. Experimental data are available which substantiate the result of Method A. The gamma dose at distances of interest is found to be unimportant when considered in light of the uncertainty in the neutron dose.

TABLE OF CONTENTS

	Page
I. INTRODUCTION	7
II. CALCULATION OF NEUTRON DOSE.	7
A. Method A.	9
B. Method B.	9
C. Tabulation of Results	15
III. CALCULATION OF GAMMA DOSE	16
A. Fission Gammas.	16
B. Nitrogen Capture Gammas	19
C. Composite Gamma Dose.	21
IV. ANALYSIS OF CALUCLATION.	22
A. Results.	22
B. Factors Bearing on the Results	22
V. REFERENCES	25

LIST OF FIGURES AND TABLES

<u>FIGURES</u>	Page
1. Godiva Leakage Neutron Spectrum.	8
2. Number of Neutrons per Square Centimeter Equivalent to a Dose of One Rem.	10
3. Dose-Distance Curves for APRA	12
4. Dose-Distance Curve for Gamma Radiation from APRA.	23

<u>TABLES</u>	
1. Neutron Calculations for 1500 Meters.	13
2. Dose-Distance Data for Neutrons.	15
3. Calculation of Photon Transmission Due to Fission Product Decay and Neutron Capture by Nitrogen.	17
4. Photon Emission Energies and Probabilities of Neutron Capture by Nitrogen	20

I. INTRODUCTION

In order to determine the degree to which operation of the Army Pulse Reactor Assembly (APRA) at the proposed Aberdeen Proving Ground site will disrupt other nearby activities, it is necessary to calculate the radiation dose which will be delivered at various distances from the nuclear reactor.

In the case of an unshielded reactor such as APRA, the exclusion area will be determined by the dose produced by radiation emanating from the reactor. The proposed site is in the industrial area of the Proving Ground. Access to this area by the public and by all Aberdeen Proving Ground employees except those who have industrial area passes is restricted. The following proposals have been made to further restrict access to the reactor site and, at the same time, to provide adequate protection to insure the safety of persons not directly under the administrative control of the reactor staff.

a. There should be a barbed wire fence with appropriate signs attached at a distance such that the maximum weekly dose outside of this fence is 10 mrem.

b. There should be a security fence (6 or 8 foot fence with barbed wire barrier on top) at a distance such that the maximum daily dose outside of this fence is 10 rem.


Members of the Hazards Evaluation Branch of the AEC have indicated that these restrictions would probably be considered adequate for exclusion of "non-occupational" personnel.

II. CALCULATION OF NEUTRON DOSE

The Godiva II neutron* leakage spectrum is used as a source model for the calculation by Method B. See Reference 1. This spectrum is included as Figure 1. The total source is assumed to be 80×10^{17} fissions, and the number of leakage neutrons per fission is assumed to be 1.4 (Reference 2, p. 9). This source is equivalent to 40 pulses per week at 2×10^{17} fissions per pulse. 2×10^{17} fissions is the probable maximum yield which the APRA will deliver in one pulse. The dose-distance calculation has been made by two different methods.

*The γ dose is estimated at about 2 per cent of the neutron dose at distances of interest. See Section III.

FIG. 1.



A. Method A

A simplified recipe for calculating the dose in air at several mean free paths from a neutron source has been proposed (Reference 3). The proposed method is as follows: (1) Use an infinite mean free path (no absorption) for the first 300 feet. (2) Use a mean free path of 212 yards from 300 feet on out. Changes in air density would cause, presumably, a change in mean free path.


A calculation was made using the above method with an infinite mean free path for the first 100 meters. This method predicts 10 mrem/wk at 1110 meters (1215 yards).

B. Method B

A more complex calculation was made using the data presented by Mehl (Reference 4). Mehl gives dose-distance data in air for nine monoenergetic sources. The Godiva spectrum was approximated by building up a spectrum composed of the nine monoenergetic sources given by Mehl. An appropriate number of neutrons was assigned to each source according to the number of neutrons of the Godiva spectrum in the energy range corresponding to monoenergetic source. For each of the nine monoenergetic sources, Reference 4 gives the number of neutrons of a given energy at various distances from the source. For instance if one is interested in finding the dose received at 1000 meters from a source of 1 Mev neutrons, data are given to enable one to determine the number of neutrons in each of several energy ranges. The neutron dose at a distance R is determined by accumulating the number of neutrons arriving at R in each energy range from all source energies. The number of neutrons of a given energy required to make one rem is given in Reference 5. These data are presented in Figure 2. A sample calculation (with R = 1500 meters) is given on pages 6 and 7. The calculation is based on a total source of one neutron. Source neutron energies are distributed as indicated in Figure 1. Symbols used are defined as follows:

- i - subscript used to denote source neutron energy.
- ΔE_i - Energy range of the source neutrons
- F_i - Fraction of the source neutrons in energy range ΔE_i as determined from Figure 1.

FIG. 2.



- R - Range (distance) from the source in cm.
- j - Subscript used to denote neutron energy range at R.
- ΔE_j - Energy range of the neutrons at R
- N_{1j} - Number of neutrons per square cm at R in energy range ΔE_j which started with a source energy in ΔE_1 (assuming total source of one neutron)
- C_j - Conversion factor for determining the number of neutrons/cm² of energies ΔE_j necessary to make one rem.
- D_j - Neutron dose at R due to neutrons with energies in energy range ΔE_j .

The air density used by Mehl is 1.07 grams/liter. The mean July air conditions for APG are as follows:

$$T_{\text{avg}} = 24^{\circ} \text{ C}$$

$$B = 761.5 \text{ mm Hg}$$

$$\text{Rel. Hum} = 71 \text{ per cent}$$

These conditions indicate a mean July (when the monthly mean density is lowest) density of 1.181 grams/liter. A density correction is applied according to the following formulas:

$$\rho_1 R_1 = \rho_2 R_2$$

$$D_1 \left(\frac{\rho_1}{\rho_2} \right) = \left(\frac{\rho_1}{\rho_2} \right)^2 D_2 \left(\frac{\rho_2}{\rho_1} \right)$$

where ρ = air density

R = distance from the source

D = dose

In the calculation above, we have $R_1 = 1500$ meters, $D_1 = 2.42 \times 10^{-21}$ rem/source neutron, $\rho_1 = 1.07$ grams/liter, $\rho_2 = 1.181$ grams/liter. Using these values in the above equations, one gets: $R_2 = 1359$ meters, $D_2 = 2.95 \times 10^{-21}$ rem/source neutron (1.4 source neutrons/fission) = 4.13×10^{-21} rem/fission. Additional dose-distance data are shown in tabular form in Table II and in graphical form in Figure 3. The "inverse square loss only" curve is shown for comparison purposes only.

FIG 3. DOSE-DISTANCE CURVES FOR APRA




TABLE I (Continued)

$\sum_1^{N_{1j}}$ (n/cm ²)	C _j (n/cm ² /rem)	D _j (rem/n)
x10 ¹⁵	x10 ⁻⁷	x10 ²²
42.17	79.0	.534
79.75	33.0	2.417
15.85	7.8	2.032
29.11	4.0	7.278
12.45	2.74	4.544
6.70	2.64	2.538
10.83	2.84	3.813
2.386	2.78	.858
.506	2.6	<u>.195</u>
Total dose/n =		24.2 x 10 ⁻²² rem/n

C. Tabulation of results

TABLE II

Dose-Distance Data for Neutrons

<u>Calc. Method</u>	<u>Range (Meters)</u>	<u>Dose (rem/fission)</u>
A	960	3.75×10^{-21}
A	550	9.41×10^{-20}
A	200	4.31×10^{-18}
B	1359	4.13×10^{-21}
B	906	6.83×10^{-20}
B	272	7.00×10^{-18}
C*	1200	2.02×10^{-19}
C	900	3.58×10^{-19}
C	500	1.16×10^{-18}
C	300	3.23×10^{-18}
C	180	8.96×10^{-18}
C(and A)	100	2.90×10^{-17}

In addition to the above data there are some experimental data available from the Sandia Pulse Reactor. The following data are reported (Reference 14) for the reactor operated at the outdoor site.

<u>Range (feet)</u>	<u>Dose (rem/fission)</u>
250	8×10^{-17}
1750	5×10^{-20}

These data agree very closely with calculation A as shown in Figure 3.

*Calculated dose assuming no attenuation other than inverse square loss.

III. CALCULATION OF GAMMA DOSE

A. Fission Gammas

The total fission gamma source (delayed plus prompt) is assumed to be 13.1 Mev/fission. See Reference 6, p. 336. The distribution of gammas is taken as $n(E) = A \exp^{-cE}$ where $c = 1.16$ after Reference 7. By setting $A = c^2$, one normalizes the distribution to a total source of 1 Mev. Note that the average energy is

$$\bar{E} = \frac{\int_0^{\infty} E n(E) dE}{\int_0^{\infty} n(E) dE} = \frac{1}{c}$$

If $c = 1.16$, $\bar{E} = 0.86$ Mev. For prompt gammas, c is sometimes taken as ≈ 1.4 (e.g., Reference 7; also the estimated slope of the straight line drawn through data of Figure 2, Reference 6 is such that $c \approx 1.4$). This gives \bar{E} for prompt gammas of $\approx .7$ Mev. However, Reference 6, p. 369 gives, for prompt gammas in the energy range .3 to 10 Mev, 7.2 ± 0.8 Mev/fission carried by 7.4 ± 0.8 photons/fission, or an \bar{E} of ≈ 1.0 . By manipulation of data presented in Reference 6, one finds that $\bar{E}_t \approx 0.95$ Mev averaged over fission gammas emitted promptly, short delayed and long time delayed. If $\bar{E}_t \approx 0.95$ Mev, the calculations given here indicate a gamma dose which is too small by 5 to 10 percent when one takes into account the fact that the nitrogen capture gamma dose is dominant at large distances. Since it will be shown that the gamma dose is small in comparison with the neutron dose for the situation under consideration, no further attempt will be made to resolve this apparent contradiction.

Using the distribution $n(E) = 13.1 c^2 \exp^{-cE}$, the energy range 0 to 8 Mev is broken down into energy groups of 1/2 Mev width as shown in Table III. The number of gammas in each group, n_{10} , is assigned the median energy of the energy range, E_1 .

$$n_{10} = \int_{E_1}^{E_2} n(E) dE = 13.1 c \left[\exp(-cE_1) - \exp(-cE_2) \right]$$

The number of photons in each energy group (n_{10}) is then attenuated according to the formula

$$n_1(\text{f.p.}) = n_{10} B_E(\mu_s Z, E) \exp(-\mu_s Z)$$

TABLE III

Calculation of Photon Transmissions Due To Fission Products Decay And Neutron Capture By Nitrogen

i	Energy Range Mev	E_1 Mev	$\frac{\mu_{m\gamma}}{\text{cm}^2/\text{gm} \times 10^2}$	$\frac{\mu_{m\alpha}}{\text{cm}^2/\text{gm} \times 10^2}$	$\frac{\mu_d}{\text{s}^{-1} \text{cm}^{-1}}$	$\frac{\mu_z}{\text{s}^{-1} \text{cm}^{-1}}$	R_E
1	0 - .25	-					
2	.25 - .75	.5	18.5	8.79	31.8	4.75	1.49
3	.75 - 1.25	1.0	7.8	5.81	13.8	3.58	1.79
4	1.25 - 1.75	1.5	5.58	4.70	9.97	3.09	1.77
5	1.75 - 2.25	2.0	4.89	4.15	8.74	2.88	1.79
6	2.25 - 2.75	2.5	4.69	3.90	8.37	2.84	1.74
7	2.75 - 3.25	3.0	4.50	3.66	8.03	2.76	1.69
8	3.25 - 3.75	3.5	4.50	3.58	8.01	2.75	1.65
9	3.75 - 4.25	4.0	4.51	3.50	8.01	2.75	1.60
10	4.25 - 4.75	4.5	4.54	3.47	8.06	2.78	1.56
11	4.75 - 5.25	5.0	4.58	3.44	8.10	2.78	1.53
12	5.25 - 5.75	5.5	4.64	3.43	8.20	2.80	1.49
13	5.75 - 6.25	6.0	4.70	3.43	8.30	2.82	1.45
14	6.25 - 6.75	6.5	4.76	3.45	8.40	2.83	1.43
15	6.75 - 7.25	7.0	4.82	3.47	8.52	2.84	1.40
16	7.25 - 7.75	7.5	4.88	3.49	8.76	2.89	1.37
17	7.75 - 8.25	8.0	4.95	3.51	8.71	2.86	1.34
18	8.25 - 8.75	8.5					
19	8.75 - 9.25	9.0					
20	9.25 - 11	10.0					

TABLE III (Continued)

1	n_{10} (f.p.) No./fiss. $\times 10^2$	n_1 (f.p.) No./fiss. $\times 10^3$	n_1 (comp) No./fiss. $\times 10^2$	$r(1000, E_1)$ Mev/cm ² -Photon $\times 10^{16}$	$n_1 r_1(1000)$ Mev/cm ² -fiss $\times 10^{18}$	$r(1500, E_1)$ Mev/cm ² -Photon $\times 10^{17}$	$n_1 r_1(1500)$ Mev/cm ² -fiss $\times 10^{19}$	$n_1(f.p.)r(1000)$ Mev/cm ² -fiss $\times 10^{18}$
1	382.6							
2	500.5	64.6	6.46	.0082	.053	.0006	.004	.053
3	280.3	140	14.0	.047	.658	.0113	.158	.658
4	156.9	126.6	12.66	.121	1.532	.052	.658	1.532
5	88.0	88.5	8.85	.243	2.15	.140	1.239	2.150
6	49.6	50.0	5.00	.400	2.00	.270	1.350	2.000
7	27.5	29.4	2.49	.547	1.362	.474	1.180	1.362
8	15.5	16.4	1.64	.710	1.164	.700	1.148	1.164
9	8.63	8.84	.884	.896	.791	1.00	.885	.791
10	4.83	4.68	1.633	1.09	1.78	1.30	2.123	.510
11	2.71	2.57	.257	1.26	.324	1.61	.414	.324
12	1.52	1.38	5.671	1.45	8.223	1.95	11.06	.200
13	.85	.736	.074	1.65	.122	2.31	.171	.122
14	.49	.413	1.35	1.83	2.471	2.70	3.645	.076
15	.27	.221	.299	1.99	.595	3.06	.915	.044
16	.15	.114	.826	2.20	1.817	3.45	2.85	.025
17	.08	.061	.006	2.42	.015	3.90	.023	.015
18			.277	2.56	.709	4.40	1.219	
19			.131	2.77	.363	4.60	.603	
20			1.465	3.56	5.215	5.65	8.277	
			Totals		31.3 $\times 10^{-18}$		37.9 $\times 10^{-19}$	11.0 $\times 10^{-18}$

where $B_E(\mu_g Z, E)$ is the energy buildup factor for a plane monodirectional gamma source in uranium obtained from Reference 8, p. 146. $n_1(f.P.)$ is the number of photons due to fission products in energy group 1 which escape from the reactor. $\mu_g(E)Z$ is the "effective" number of relaxation lengths for the photon energy E . This factor takes into account the fact that many of the photons produced are absorbed in the reactor core itself. The relationship between the number of source radius relaxation lengths, $\mu_g(E)d$, and the "effective" number of relaxation lengths is given in Reference 9, p. 73.

The radius of the reactor core, d , is assumed to be 4.5 inches of which 7 percent (of the radius) is gaseous coolant channel which we will assume to be non-attenuating. These values were estimated from data given in Reference 10, p. 42. The reactor core is 90 percent U and 10 percent by weight Mo. The linear absorption coefficients are calculated by

$$\mu_g(E) = 0.93 \left[0.9 \mu_{mU} + 0.1 \mu_{mMo} \right] \rho_{UMo}$$

where

μ_{mU} = the mass absorption coefficient for U,

μ_{mMo} = the mass absorption coefficient for Mo,

ρ_{UMo} , the density of the U-Mo, is taken to be 17.08 gm/cm³ after Reference 11, p. 4. Values of the mass absorption coefficients $\mu_m(E)$ are taken from Reference 12. Thus the number of photons in each energy group escaping from the reactor is determined.

Nitrogen Capture Gammas

B. This source is directly dependent on the number of leakage neutrons per fission, η . The value of η is taken as 1.4 neutrons/fission (Reference 2, p. 9). The number of Mev of nitrogen capture (N.C.) gammas produced per fission, U_{Mo} , is computed as follows:

$$U_{NC} = \eta \left(\frac{\sigma_N}{\sigma_{air}} \right)_{abs} \cdot \left(\frac{\sigma_\gamma}{\sigma_a} \right)_N \cdot \gamma_T \bar{E}_O$$

where $\left(\frac{\sigma_N}{\sigma_{air}} \right)_{abs}$ = ratio of neutron absorption in nitrogen to that in air.

$\left(\frac{\sigma_\gamma}{\sigma_a} \right)_N$ = ratio of radiative capture (N.C.) to absorption in nitrogen.

γ_T = average number of photons/N.C.

\bar{E}_O = average energy of photons emitted in N.C.

The values used in this calculation are:

$$\left. \frac{\sigma_N}{\sigma_{\text{air}}} \right)_{\text{abs}} = 1.0$$

$$\left. \frac{\sigma_\gamma}{\sigma_a} \right)_N = \frac{.1}{1.84}$$

$$\gamma_T = \frac{7.53}{5.23} = 1.44$$

$$\bar{E}_O = \frac{48.46}{7.53} = 6.44$$

$$U_{\text{NC}} = 0.71 \text{ Mev/fission}$$

The distribution of gammas emitted in neutron captures in nitrogen is given in Table IV (taken from Reference 7).

TABLE IV

Photon Emission Energies and Probabilities of Neutron Capture by Nitrogen

k	Energy E_k , Mev	Relative No. n_k	P_k
1	10.816	1.0	.01456
2	9.156	.09	.00131
3	8.278	.19	.00277
4	7.356	.56	.00815
5	7.164	.19	.00277
6	6.318	.90	.01310
7	5.554	1.5	.02184
8	5.287	2.3	.03349
9	4.485	<u>.8</u>	.01165
	Total	7.53	

$$\sum_{k=1}^9 n_k E_k = 48.76 \text{ Mev}$$

$$P_k = \frac{n_k(.71)}{48.76} = \text{No. of photons of Energy } E_k \text{ per fission}$$

The number of photons, P_k , of energy E_k is then assigned to the median energy E_1 of the particular energy group in which the energy E_k falls as indicated in Table III.

The nitrogen capture gammas are treated as a point source positioned at the reactor center. This approximation is justified on the basis that in this calculation we are only interested in the dose at 1000 yards or more and the great majority of all neutrons are absorbed well within this distance.

C. Composite Gamma Dose

The number of gammas in each of 19 energy ranges between 0-11 Mev, $n_1(\text{comp}) = n_1$, is determined by adding the contributions from fission gammas and N.C. gammas. The values of n_1 are listed in Table III. Also listed in Table III are values of $r(x, E_1) = r_1$ which is the energy in Mev deposited per cm^3 in air at a distance x in yards from a source of one photon of energy E_1 . Values of r_1 are given in Reference 7 and are calculated by the formula

$$r_1 = \frac{B_{r1} E_1 \mu_1^i \exp(-\mu_1 x)}{4\pi x^2}$$

where B_{r1} is the dose buildup factor in air for photons of energy E_1 , μ_1^i is the linear absorption coefficient not including compton scattering component, μ_1 is the total linear absorption coefficient including the compton scattering component, and x is the distance from the source in cm. The buildup factors are taken from Reference 7 as before. The air density for the gamma calculations is taken as 1.205 gm/l rather than 1.181 gms/l since data are already available at 1.205 gm/l. This small difference will result in very little inaccuracy of the final results.

From Table III, we see that

$$\sum_1 n_1 r(1000, E_1) = 3.13 \times 10^{-17} \text{Mev/cm}^3 - \text{fission}$$

and

$$\sum_1 n_1 r(1500, E_1) = 3.79 \times 10^{-18} \text{Mev/cm}^3 - \text{fission}$$

Using the conversion factors,

$$\left(1.6 \times 10^{-6} \text{ ergs/Mev}\right) \left(\frac{\text{roentgen}}{87.7 \text{ ergs/gm}}\right) \left(\frac{1}{1.181 \times 10^{-3} \text{ cm}^3/\text{gm}}\right) = 1.545 \times 10^{-3} \text{ r/Mev/cm}^3,$$

one obtains the gamma dose per fission shown in Figure 4. For a 2×10^{17} fission pulse the gamma dose is ~ 0.1 mr at 1000 yds and ~ 0.01 mr at 1500 yards.

IV. ANALYSIS OF CALCULATION

A. Results

The gamma dose is less than 2 per cent of the neutron dose (as calculated by Method B) for distances out to about 1500 meters. Therefore, we may neglect the gamma dose.

The distance at which 10 mrem/wk will be accumulated from a weekly source of 80×10^{17} fissions is 1215 yards based on calculation Method A. The corresponding figure for Method B is 1700 yards.


The distance at which 10 rem/day will be accumulated is 195 yards by Method A and 315 yards by Method B.

B. Factors Bearing on the Results

It is believed that the results of Method A are more correct than the results of Method B. This contention is supported mainly by the experimental data presented. Factors having an effect on either or both of the two methods will be enumerated. The applicable calculational method is indicated by the letter (s) preceding.

- A,B 1. The radiation leakage from the APRA may be more (or less) per fission than that for Godiva (which was used in these calculations).
- B 2. Thermal and resonance neutrons arriving at the detector below 200 ev energy have not been accounted for in this calculation.
- A,B 3. The APRA neutron leakage spectrum may not be the same as the Godiva spectrum (which was used in these calculations).
- B 4. This calculation is made for an infinite medium of air with a point source of neutrons (and gammas). The ground-air interface may decrease the dose at large distances from the reactor particularly when the reactor is operated close to the ground. Data are available for gammas

FIG 4. DOSE-DISTANCE CURVE FOR GAMMA RADIATION FROM APRA



(Reference 13, p. 89); however, no data has been found for neutron transmission. The non-nitrogen capture gamma dose will probably be reduced by about a factor of 2 or 3 at a distance of 1500 meters. It would not necessarily follow that this same figure can be used for neutrons, however.

- A,B 5. It may not be necessary to pulse the reactor once per hour. Nevertheless, it would be desirable to be able to do so.
- A,B 6. The APRA may not be capable of producing a pulse which is 13 times as large as the nominal Godiva II pulse of 1.5×10^{16} fissions/pulse.
- B 7. Excessive moisture in the air will reduce the dose level below that calculated here. Mehl's calculations assume a constant air density of 1.07×10^{-3} gm/cm³ with relative atom fractions of nitrogen, oxygen, and hydrogen of 0.7778, 0.2135 and 0.0085 respectively. APG air contains more than twice the amount of moisture as that used in Mehl's calculations (assuming mean July conditions for APG, the atom fraction for hydrogen is .0209).
- B 8. The data used to calculate the dose by Method B are estimated to be accurate to within ± 50 per cent according to the author of Reference 4 (assuming an infinite medium of air).
- A,B 9. Any attenuation of neutrons in the walls of the reactor building or experimental equipment positioned around the reactor will reduce the dose at distances of interest.

Of the above items, perhaps only the last one may be expected to result in a significant change in the predicted dose.

Frederick H. Gregory
FREDERICK H. GREGORY

REFERENCES

1. R. E. Peterson and G.A. Newby, An Unreflected U-235 Critical Assembly, Nuclear Science and Engineering, 1, No. 2, 112-125 (1956).
2. L. J. Zipprich, Radiation Effects Testing at the Los Alamos Godiva II Facility, SCR 76 (1959).
3. Payne S. Harris, LASL, private communication.
4. C. R. Mehl, A Monte Carlo Calculation of the Neutron Flux from a Monoenergetic Point Source in Air SC 4174 (TR) (1958).
5. Federal Register, Title 10, Atomic Energy, Chapter I, Atomic Energy Commission, Part 20, Standards for Protection against Radiation, Sept 7, 1960.
6. F. C. Maienschein, et al, Gamma Rays Associated with Fission, Peaceful Uses of Atomic Energy, V 15, A/Conf. 15/P/670 (1958).
7. D. C. Borg, and C. Eisenhauer, Spectrum and Attenuation of Initial Gamma Radiation from Nuclear Weapons, AFSWP 502B (Secret RD) (1955).
8. Herbert Goldstein, and J.E. Wilkins, Jr. Calculations of the Penetration of Gamma Rays, NYO 3075 (1954).
9. John Moteff, Miscellaneous Data for Shielding Calculations APEX 176 (1954).
10. Preliminary Hazards Summary Report for the Ordnance Pulse Experimental Research Assembly, AN 436, September 1961.
11. W. E. Kinney and J. T. Mihalczko, Oak Ridge National Laboratory Fast Burst Reactor: Critical Experiments and Calculations CF 61-8-71 (Aug 61)/
12. Ellery Storm, et al, Gamma Ray Absorption Coefficients for Elements 1 through 100 Derived from the Theoretical Values of the National Bureau of Standards, LA 2237 (1958).
13. Martin J. Berger, Effects of Boundaries and Inhomogeneties on the Penetration of Gamma Radiation, Proceedings of the Shielding Symposium Held at the Naval Radiological Defense Laboratory, Vol. 1, 17-19 Oct, 1956.
14. G. E. Tucker, Jr., Sandia Corporation, private communication.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
10	Director Armed Services Technical Information Agency ATTN: TIPCR Arlington Hall Station Arlington 12, Virginia	2	Commanding General U. S. Army Missile Command ATTN: ORDAB-DV C. G. Morgan, Ord Missile Labs. Redstone Arsenal, Alabama
1	Chief Defense Atomic Support Agency ATTN: Capt Fort A. Vesser Washington, D. C.	3	Commanding General Frankford Arsenal ATTN: Pitman-Dunn Laboratories H. P. George, 1320-64-4 S. Berk, 1334-312 G. White, 1010-110-1 Philadelphia 37, Pennsylvania
1	Commanding General Field Command Defense Atomic Support Agency ATTN: FC Technical Library Sandia Base P. O. Box 5100 Albuquerque, New Mexico	3	Commanding Officer Picatinny Arsenal ATTN: Plastics Technical Evaluation Center A. E. Molzon J. J. Begley Dover, New Jersey
1	Director of Defense Research and Engineering (OSD) Washington 25, D. C.	1	Commanding Officer Rock Island Arsenal ATTN: ORDBC Rock Island, Illinois
1	Commanding General U. S. Army Materiel Command ATTN: AMCRD-DE-N Research and Development Directorate Washington 25, D. C.	8	Commanding Officer Watertown Arsenal ATTN: WAL, P. V. Riffin F. S. Mascianica W. E. Leavitt Restricted Data Control Officer OMRO, G. A. Darcy D. W. Weeks L. S. Foster B. Goldberg Watertown 72, Massachusetts
3	Commanding General U. S. Army Materiel Command ATTN: AMCRD-RS-PE-Bal AMCRD-DE-W AMCRD-DE-MI Research and Development Directorate Washington 25, D. C.	3	Commanding General U. S. Army Mobility Command ATTN: J. G. Brookes W. L. Riggle Capt MacGregor 1501 Beard Street Detroit 9, Michigan
1	Commanding Officer Harry Diamond Laboratories ATTN: Technical Information Office, Branch 012 Washington 25, D. C.		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commanding General White Sands Missile Range ATTN: Chief, White Sands Annex, BRL New Mexico	1	Director Walter Reed Army Institute of Research Walter Reed Army Medical Center Washington, D. C.
1	Commanding Officer Army Research Office (Durham) ATTN: R. Mace Box CM, Duke Station Durham, North Carolina	1	Commanding General U. S. Army Signal Engineering Laboratories ATTN: Atomics Branch Fort Monmouth, New Jersey
1	Commanding General U. S. Army Chemical Corps Research and Development Command Washington 25, D. C.	1	Commanding General Quartermaster Research and Engineering Command Natick, Massachusetts
1	Commanding Officer U. S. Army Chemical Corps Field Requirement Agency Ft. McClellan, Alabama	1	Commanding Officer Transportation Research and Engineering Command Ft. Eustis, Virginia
3	Commanding Officer U. S. Army Chemical Warfare Laboratories ATTN: R. C. Tompkins H. Donnert H. Tiller Army Chemical Center, Maryland	1	Radiological Operations Division Dugway Proving Ground Dugway, Utah
2	Commanding General Engineering Research and Development Laboratories ATTN: Special Projects Branch Chief, Camouflage Branch Ft. Belvoir, Virginia	1	TRECOM Liaison Office Detroit Arsenal Centerline, Michigan
2	The Surgeon General U. S. Army Medical Research Laboratory Fort Knox, Kentucky	1	Commanding General U. S. Continental Army Command Ft. Monroe, Virginia
		1	Commanding General U. S. Army Combat Developments Command Fort Belvoir, Virginia
		1	Commanding Officer U. S. Army Armor Combat Developments Agency Fort Knox, Kentucky
		1	Commanding Officer Office of Special Weapons Developments Fort Bliss 16, Texas

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commandant Command and General Staff College Fort Leavenworth, Kansas	1	Commander Naval Ordnance Test Station ATTN: Technical Library China Lake, California
2	Army Research Officer 3045 Columbia Pike Arlington, Virginia	1	Director U. S. Naval Research Laboratory Washington 25, D. C.
1	Chief of Naval Research Department of the Navy Washington 25, D. C.	2	Chief, Bureau of Ships Department of the Navy Washington 25, D. C.
1	U. S. Naval Medical Research Institute National Naval Medical Center Bethesda 14, Maryland	1	Chief, Bureau of Medicine and Surgery Navy Department, Potomac Annex Washington 25, D. C.
2	Commanding Officer and Director U. S. Naval Radiological Defense Laboratory ATTN: W. E. Kreger San Francisco 24, California	1	Superintendent U. S. Naval Postgraduate School Monterey, California
3	Chief, Bureau of Naval Weapons ATTN: DIS-33 Department of the Navy Washington 25, D. C.	1	Commanding Officer Naval Medical Field Research Laboratory Camp Lejeune, North Carolina
2	Commander U. S. Naval Weapons Laboratory Dahlgren, Virginia	1	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D. C.
2	Commander Naval Ordnance Laboratory White Oak Silver Spring 19, Maryland	1	Commandant Marine Corps School Quantico, Virginia
2	Commander Naval Ordnance Laboratory White Oak Silver Spring 19, Maryland	2	Commander Air Proving Ground Center ATTN: PGTRI Eglin Air Force Base, Florida
1	Commanding Officer and Director U. S. Naval Civil Engineering Laboratory ATTN: Capt. Chilton Port Hueneme, California	1	Director, Project RAND Department of the Air Force 1700 Main Street Santa Monica, California

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander Air Force Cambridge Research Laboratory L. G. Hanscom Field ATTN: Dr. Marcus O'Day Bedford, Massachusetts	1	U. S. Public Health Service Washington, D. C.
		1	U. S. Atomic Energy Commission ATTN: Dr. Thomas H. Johnson, Director, Div. of Research Washington 7, D. C.
2	Commander Aeronautical Systems Division Wright-Patterson Air Force Base Ohio	2	U. S. Atomic Energy Commission ATTN: Document Library, Research Division Washington 25, D. C.
1	Commander Air Force Systems Command Andrews Air Force Base Washington 25, D. C.	10	U. S. Atomic Energy Commission Technical Information Service P. O. Box 62 Oak Ridge, Tennessee
2	Commander Air Force Special Weapons Center Kirtland Air Force Base, New Mexico	2	U. S. Atomic Energy Commission Los Alamos Scientific Laboratory ATTN: Technical Library P. O. Box 1663 Los Alamos, New Mexico
1	Director Air University Library ATTN: AUL (T-AUL-60-118) Maxwell Air Force Base, Alabama	2	U. S. Atomic Energy Commission Army Reactor Division of Reactor Development Washington 25, D. C.
1	U. S. Atomic Energy Commission Aircraft Nuclear Propulsion ATTN: Restricted Data Control Officer U. S. Air Force Washington 25, D. C.	2	University of California Lawrence Radiation Laboratory ATTN: Restricted Data Control Officer P. O. Box 808 Livermore, California
3	Director National Bureau of Standards ATTN: L. V. Spencer M. Berger C. Eisenhauer 232 Dynamometer Building Washington 25, D. C.	2	Oak Ridge National Laboratory ATTN: E. P. Blizzard W. Zobel Oak Ridge, Tennessee
		1	Hanford Atomic Products Operation Richland, Washington
2	Office of Civilian and Defense Mobilization Battle Creek, Michigan	1	Brookhaven National Laboratory Upton, Long Island, New York

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Argonne National Laboratory 9700 South Cass Avenue Lemont, Illinois	10	The Scientific Information Officer Defence Research Staff British Embassy 3100 Massachusetts Avenue Washington 8, D. C.
1	Aerojet-General Corporation Azusa, California		
1	Armour Research Foundation ATTN: C. Terrell Illinois Institute of Technology Technology Center Chicago 16, Illinois	5	Defence Research Member Canadian Joint Staff 2450 Massachusetts Avenue, N. W. Washington 8, D. C.
			Of Interest to:
3	Lockheed Aircraft Corporation Lockheed Nuclear Products ATTN: M. Burrell J. Rosen J. Perkins Georgia Division Marietta, Georgia		Library Atomic Energy Commission, Limited Chalk River Ontario, Canada
3	CONVAIR, A Division of General Dynamics Corporation ATTN: Sam Dominey Fort Worth, Texas		
1	Technical Operations, Inc. ATTN: Dr. Clarke South Avenue Burlington, Massachusetts		
2	United Nuclear Corporation ATTN: D. Spielberg White Plains, New York		
1	Westinghouse Electric Corporation Atomic Power Division Pittsburgh 30, Pennsylvania		

AD Accession No.

Ballistic Research Laboratories, AFG

CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY
PULSE EXPERIMENTAL REACTOR ASSEMBLY

F. H. Gregory

EPL Memorandum Report No. 1438 November 1962

DA Proj No. 512-10-001

UNCLASSIFIED Report

UNCLASSIFIED

Reactor radiation -
Transmission

Calculations are made to estimate, as a function of distance, the radiation dose levels which would occur during full capacity operation of the Army Pulse Reactor Assembly (APRA) scheduled for construction at Aberdeen Proving Ground, Md. Calculations of the neutron dose are made by two methods. The first calculation (Method A) is made by utilizing an experimentally determined effective dose mean free path, which probably includes the effect of ground scattering. The second calculation (Method B) is made by utilizing the result of a Monte Carlo calculation of neutron transmission in air. The results of this calculation indicate considerably higher dose levels than indicated by Method A. Experimental data are available which substantiate the result of Method A. The gamma dose at distances of interest is found to be unimportant when considered in light of the uncertainty in the neutron dose.

AD Accession No.

Ballistic Research Laboratories, AFG

CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY
PULSE EXPERIMENTAL REACTOR ASSEMBLY

F. H. Gregory

EPL Memorandum Report No. 1438 November 1962

DA Proj No. 512-10-001

UNCLASSIFIED Report

UNCLASSIFIED

Reactor radiation -
Transmission

Calculations are made to estimate, as a function of distance, the radiation dose levels which would occur during full capacity operation of the Army Pulse Reactor Assembly (APRA) scheduled for construction at Aberdeen Proving Ground, Md. Calculations of the neutron dose are made by two methods. The first calculation (Method A) is made by utilizing an experimentally determined effective dose mean free path, which probably includes the effect of ground scattering. The second calculation (Method B) is made by utilizing the result of a Monte Carlo calculation of neutron transmission in air. The results of this calculation indicate considerably higher dose levels than indicated by Method A. Experimental data are available which substantiate the result of Method A. The gamma dose at distances of interest is found to be unimportant when considered in light of the uncertainty in the neutron dose.

AD Accession No.

Ballistic Research Laboratories, AFG

CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY
PULSE EXPERIMENTAL REACTOR ASSEMBLY

F. H. Gregory

EPL Memorandum Report No. 1438 November 1962

DA Proj No. 512-10-001

UNCLASSIFIED Report

UNCLASSIFIED

Reactor radiation -
Transmission

Calculations are made to estimate, as a function of distance, the radiation dose levels which would occur during full capacity operation of the Army Pulse Reactor Assembly (APRA) scheduled for construction at Aberdeen Proving Ground, Md. Calculations of the neutron dose are made by two methods. The first calculation (Method A) is made by utilizing an experimentally determined effective dose mean free path, which probably includes the effect of ground scattering. The second calculation (Method B) is made by utilizing the result of a Monte Carlo calculation of neutron transmission in air. The results of this calculation indicate considerably higher dose levels than indicated by Method A. Experimental data are available which substantiate the result of Method A. The gamma dose at distances of interest is found to be unimportant when considered in light of the uncertainty in the neutron dose.

AD Accession No.

Ballistic Research Laboratories, AFG

CALCULATION OF RADIATION DOSE LEVELS FOR THE ARMY
PULSE EXPERIMENTAL REACTOR ASSEMBLY

F. H. Gregory

EPL Memorandum Report No. 1438 November 1962

DA Proj No. 512-10-001

UNCLASSIFIED Report

UNCLASSIFIED

Reactor radiation -
Transmission

Calculations are made to estimate, as a function of distance, the radiation dose levels which would occur during full capacity operation of the Army Pulse Reactor Assembly (APRA) scheduled for construction at Aberdeen Proving Ground, Md. Calculations of the neutron dose are made by two methods. The first calculation (Method A) is made by utilizing an experimentally determined effective dose mean free path, which probably includes the effect of ground scattering. The second calculation (Method B) is made by utilizing the result of a Monte Carlo calculation of neutron transmission in air. The results of this calculation indicate considerably higher dose levels than indicated by Method A. Experimental data are available which substantiate the result of Method A. The gamma dose at distances of interest is found to be unimportant when considered in light of the uncertainty in the neutron dose.