

UNCLASSIFIED

AD 402 900

*Reproduced
by the*

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

TECHNICAL MEMORANDUM

(TM Series)

ASTIA AVAILABILITY NOTICE

Qualified requesters may obtain
copies of this report from ASTIA.

This document was produced by SDC in performance of contract AF 19(628)-1648, Space
Systems Division Program, for Space Systems Division, AFSC.

Program Design Specifications for
Modifications to MULTICON

by

J. Hillhouse and H. Frieden

1 April 1963

Approved

J. B. Munson

SYSTEM

DEVELOPMENT

CORPORATION

2500 COLORADO AVE.

SANTA MONICA

CALIFORNIA

The views, conclusions or recommendations expressed in this document do not necessarily reflect the official views or policies of agencies of the United States Government.

Permission to quote from this document or to reproduce it, wholly or in part, should be obtained in advance from the System Development Corporation.

Although this document contains no classified information it has not been cleared for open publication by the Department of Defense. Open publication, wholly or in part, is prohibited without the prior approval of the System Development Corporation.



1 April 1963

- 1 -

TM-(L)-891/006/00

TABLE OF CONTENTS

	<u>Page</u>
1.0 INTRODUCTION.....	1
2.0 TASK I - SPLICE.....	1
2.1 PURPOSE.....	1
2.2 METHOD.....	1
2.3 FUNCTION CARD FORMAT.....	2
2.4 RESTRICTIONS.....	3
SPLICE Flow Diagram.....	4
3.0 TASK II - MATCH.....	5
3.1 PURPOSE.....	5
3.2 METHOD.....	5
3.3 FUNCTION CARD FORMAT.....	5
3.4 RESTRICTIONS.....	5
3.4.1 On-Line Printouts.....	6
MATCH Flow Diagram.....	7
4.0 TASK III - MODIFY TAPEIN.....	9
4.1 PURPOSE.....	9
4.2 METHOD.....	9
4.3 FUNCTION CARD FORMAT.....	9
4.4 RESTRICTIONS.....	9
TAPEIN Flow Diagram.....	10
5.0 TASK IV - MAXIMUM ELEVATION ON STAOUT LISTING.....	14
6.0 TASK V - DOUBLE SPACING ON STAOUT LISTING.....	14
7.0 TASK VI - EQUIPMENT CHANGEOVER TIME.....	14
8.0 TASK VII - PLOT MULTICON OUTPUT (PLOT).....	14
PLOT Flow Diagram.....	17
9.0 TASK VIII - REVOLUTION NUMBER PRINTOUT.....	19
10.0 TASK IX - MODIFICATIONS TO "RESOLVE".....	19

1 April 1963

- 11 -

TM-(L)-891/006/00

	<u>Page</u>
11.0 TASK X - LIST CONFLICT TIME.....	19
12.0 TASK XI - PROVIDE CORE SPACE FOR THE PRECEDING TASKS.....	20
APPENDIX A - Figure 1 - Sample Plotted MULTICON Output.....	21
APPENDIX B - SPLICE Tape Format (BCD).....	22
APPENDIX C - PATCH Tape Format (BCD).....	24

1.0 INTRODUCTION

This document gives the program design specifications for accomplishing the modifications to MULTICON listed in TM-(L)-890/007/00 and TM-(L)-890/007/00A.

2.0 TASK I - SPLICE2.1 PURPOSE

SPLICE replaces the old PATCH function. Like PATCH, the SPLICE function prepares the data input to the MULTICON system. SPLICE does not rewind or write an end of file on the output tape. If the set of data generated by SPLICE is to be the first set on the output tape, a separate function (e.g., REWIND) is referenced for this task before calling SPLICE. A set of data is defined as a header record, acquisition data records (identified by a D in character two), and an end of data record for the vehicle designated on the SPLICE function card. Sets of data for more than one vehicle can be written on a SPLICE tape file by repeatedly calling SPLICE. End of file is written by a separate function (e.g., WEOF).

2.2 METHOD

A listing of station acquisitions is generated for all stations in the LOOK Table, for the interval of time designated on the SPLICE function card, by calling the ACQTABLE Function as a subroutine. Mod AB of the ACQTABLE Function is used to produce an acquisition table format of two words per entry:

<u>Word</u>	<u>Bits</u>	<u>Contents</u>
0	47-24	Revolution number
	23- 0	Station Number
1	47-26	Duration
	25- 0	Mid-time

Maximum elevation is computed by SPLICE, using subroutine TTE.

1 April 1963

- 2 -

TM-(L)-891/006/00

A set of data is automatically placed on the output tape each time the function SPLICE is called. Acquisitions over a long time interval are possible, since the ACQTABLE Function is repeatedly called automatically by SPLICE until all of the acquisitions for the entire interval are found.

The output records consist of 80 BCD character records and are compatible with punched cards. The output data consists of the following: a vehicle number; station number and name; revolution number (to the nearest tenth); date of rise time; rise time in hours, minutes, and seconds; fade time in hours, minutes and seconds; pass duration in hours, minutes, and seconds; maximum pass elevation; sequence number; and run identification. See Appendix B for the SPLICE tape format.

2.3 FUNCTION CARD FORMAT

*SPLICE A B C D E F G H I J K L

where:

A = vehicle number

B = month

C = day

D = hours

E = minutes

F = seconds (floating)

} Start Date

G = month

H = day

I = hours

J = minutes

K = seconds (floating)

} Stop Date

L = tape number for output (if blank, output is on Tape Unit 5).

2.4 RESTRICTIONS

- a. SPLICE does not rewind the output tape; therefore, a separate function (e.g., REWIND) is required for this task.
- b. The methods of determining fade time in PATCH and SPLICE vary slightly. Therefore, a comparison of a MATCH (see Section 3.0) converted PATCH tape and a SPLICE tape might point out a one-second difference in fade time for a specific acquisition.

Fade time is computed in the following manner:

PATCH : Midtime + Duration/2 = Fade Time


SPLICE: Rise time + Duration = Fade Time

PATCH tapes contain only Rise and Fade times; therefore, MATCH must compute duration by finding the difference between these two times. SPLICE tapes contain duration obtained directly from RESETBL. Because of the above stated difference in Fade time, duration might also differ by one second.

1 April 1963

- 4 -

TM-(L)-891/006/00



3.0 TASK II - MATCH

3.1 PURPOSE

MATCH is used to convert an old or new format PATCH output tape to the format of a SPLICE output tape. See Appendices B and C for SPLICE and PATCH tape formats.

3.2 METHOD

The input PATCH tape is placed on Tape Unit 4 and the output SPLICE tape is on Unit 5. If an old format PATCH tape, which contains revolution number as an integer, is being converted, revolution number to the nearest tenth is written on the converted tape with the fractional portion set to zero. BCD blanks are written for maximum elevation. If the reference pool item, IDBCD, is not set by a separate function (e.g., RUNNUM), BCD blanks appear in the characters for tape identification.

Multiple file PATCH tapes can be converted by successive MATCH calls.

The MATCH function does not rewind the output tape so that a separate function (e.g., REWIND) is utilized for this task. An end of file is written on the output tape upon reaching the file mark on the input tape.

3.3 FUNCTION CARD FORMAT

*MATCH

No parameters are required.

3.4 RESTRICTIONS

Maximum elevation is set to BCD blanks.

The master tape routine TAPE is referenced for read and write functions.

1 April 1963

- 6 -

TM-(L)-891/006/00

3.4.1 On-Line Printouts

Errors incurred by the TAPE routine are noted by on-line error comments. After any of the following printouts, a stop is effected at the first logical instruction in MATCH.

- a. End of file was read while trying to read PATCH header record.

EOF READ. TRYING TO READ PATCH HEADER. POSITION TAPE
TO START OF FILE, START.

- b. Buffer length error occurred while trying to read PATCH tape header. Either the PATCH tape was positioned incorrectly, or an illegal tape was mounted on Tape Unit 4.

BUFFER LENGTH ERROR. TRYING TO READ PATCH HEADER.
POSITION TAPE TO START OF FILE, START.

- c. Parity error on PATCH tape.

READ PARITY ERROR. DEPRESS START TO REINITIATE MATCH.

- d. Parity error on output tape.

WRITE PARITY ERROR. REWIND TAPES, DEPRESS START TO
REINITIATE MATCH.

- e. Output buffer length error.

WRITE BUFFER LENGTH ERROR. REWIND TAPES, DEPRESS START
TO REINITIATE MATCH.


- f. Output tape too short.

EOT. MOUNT LONGER TAPE ON UNIT 5, REWIND PATCH TAPE, START.

1 April 1963

- 7 -


TM-(L)-891/006/00



1 April 1963

- 8 -

TM-(L)-891/006/00



4.0 TASK III - MODIFY TAPEIN

4.1 PURPOSE

This modification enables TAPEIN to read a ten word per record SPLICE tape, rather than a PATCH tape with variable length records. See Appendices B and C for SPLICE and PATCH tape formats.

4.2 METHOD

The I/O1607 Functions of MTCII are used for tape manipulation. Maximum elevation is stored in bits 24-47 of the REVTAB Table as a binary integer.

4.3 FUNCTION CARD FORMAT

TAPEIN is referenced internally by MULTICON; therefore, no function card is required.


4.4 RESTRICTIONS

The REVTAB Table was originally designed to contain only revolution number, bits 0-47. The maximum revolution number can be contained in 24 bits, which leaves sufficient space for maximum elevation. This modification to Table REVTAB necessitates logical referencing of maximum elevation and revolution number in both the REVTAB and REVTABS Tables.

1 April 1963

- 10 -


TM-(1)-891/006/00



1 April 1963

- 11 -


TM-(L)-891/006/00



1 April 1963

- 12 -


TM-(L)-891/006/00



1 April 1963

- 13 -

TM-(L)-891/006/00



5.0 TASK IV - MAXIMUM ELEVATION ON STAOUT LISTING

The original STAOUT listing format allocated space for elevation in degrees, minutes, and seconds. This space is filled with BCD blanks, and is free to accept maximum elevation to the nearest degree, obtained from bits 24-47 of the REVTABS Table, generated by ABSAO from the REVTAB Table. One of the OUTPUT calls in subroutine MULTIOUT must be modified to include a conversion of maximum elevation.

6.0 TASK V - DOUBLE SPACING ON STAOUT LISTING

The MULTIOUT subroutine is used to list the various outputs of MULTICON. The STAOUT subroutine sets up the inputs to MULTIOUT to produce the STAOUT listing. Modification of the MULTIOUT OUTPUT carriage control character to 12 (octal), immediately preceding the reference to MULTIOUT in STAOUT, produces double spacing rather than single spacing. Upon return to STAOUT, the single space control character is replaced. The page eject control will also have to be adjusted for double spaced lines.

7.0 TASK VI - EQUIPMENT CHANGEOVER TIME

- a. Subroutine SELECT will be modified so that changeover times will no longer need to be ordered and maximum changeover time will be found, and saved.
- b. In subroutine EVALUATE, all changeover times will be tested to see if there is a changeover time conflict for the particular station and vehicle.

8.0 TASK VII - PLOT MULTICON OUTPUT (PLOT)

An attempt will be made to include PLOT as an integral part of MULTICON. The available core space can be utilized best by executing PLOT after all other listings have been made. Areas of memory, which are no longer required (such as the STACON buffer), can then be used as a storage area for PLOT.

1 April 1963

- 15 -

TM-(L)-891/006/00

The input to PLOT will be the acquisition messages ordered by acquisition time. An extra entry to MERGE will be needed to re-order the acquisition messages, since they are presently in vehicle order, at the end of MULTICON.

Appendix A contains a sample of the PLOT output. The day, month, hour, and minute are printed at the left for each minute between the first acquisition and the last fade. A letter in one of the 100 possible station-vehicle columns indicates that the vehicle can be seen by the station at some time during this minute. Revolution number is printed above the letters indicating the vehicle-station contact, and maximum elevation (in degrees) is printed below.

The numbers 1-9 separate the stations and aid in identifying them. Each page is completely filled, and there are no page headings after the first page.

PLOT will make use of six parallel tables, each one being 100 words long for the 100 possible station-vehicle combinations.

The entries in Table 1 will have the following format:

SOOOLLOOCCWWWW

S	= 0 if the entry is inactive.
S	= 4 if the entry is active.
LL	= the vehicle letter for this entry.
CC	= the shift count for positioning a character for this entry in the output word.
WWWW	= the location of the output word in the output buffer for this entry.

(Table 2 will contain the SSU mask corresponding to the shift count in Table 1.

1 April 1963

- 16 -

TM-(L)-891/006/00

Table 3 will contain the minute during which acquisition occurs.

Table 4 will contain the minute during which fade occurs.

Table 5 will contain the revolution number, converted to BCD, left justified, with trailing blanks. As each character of revolution number is printed, the entry in Table 5 will be shifted left one character.


Table 6 will contain the maximum elevation (a blank plus two characters) converted to BCD, left justified, with trailing blanks. As each character of maximum elevation is printed, the entry in Table 6 will be shifted left one character.

For each minute of the plot, the acquisition message table will be checked for any upcoming station-vehicle contacts. If there are any, the "entry active" bit will be set in Table 1 and entries made to Tables 3-6. Then, Table 1 will be checked for active entries by doing a masked equality search on the sign bit. For each active entry, current time will be compared with the times in Tables 3 and 4 to determine which character should be entered in the output buffer. After maximum elevation has been printed, the "entry active" bit will be reset.

1 April 1963

- 17 -


TM-(L)-891/006/00



1 April 1963

- 18 -

TM-(L)-891/006/00



9.0 TASK VIII - REVOLUTION NUMBER PRINTOUT

On the MERGEOUT and STAOUT listings, the extra column for revolution number will be obtained by moving the vehicle number one space to the left. The other listings already have the space available. The necessary changes require modifications to existing OUTPUT calls.

10.0 TASK IX - MODIFICATIONS TO "RESOLVE"

When a solution cannot be found for a station-vehicle matrix, the lowest priority vehicle will be deleted and the highest priority vehicle added in again to keep the matrix square. This process will be repeated, if necessary, until a solution is found.

In the above procedure (and also in the original "squaring" of the matrix), it is possible for the deletion of a vehicle to cause the matrix row for a station to become zero; i.e., the station cannot service any of the remaining vehicles. The matrix is insoluble if any row is zero. Therefore, the station will be deleted and the dimension of the matrix reduced by one. The lowest priority vehicle will then be deleted to keep the matrix square.

11.0 TASK X - LIST CONFLICT TIME

- a. Conflict Time = |minimum fade time-maximum acquisition time| for two vehicles in a REALTIME or CHANGEOVER conflict.
- b. Conflict Time will be added to the MERGEOUT, STAOUT, VEHOUT, and CONLIST listings. Subroutine MULTIOUT produces the MERGEOUT, STAOUT, and VEHOUT listings.
- c. Conflict Time cannot conveniently be saved. It will be re-computed at the time of listing. STACON gives the acquisition times of the conflicting vehicles. The fade time can be obtained by searching for an entry with an equal acquisition time in the STARES Table.
- d. Conflict time will be listed to the nearest minute. It will be placed between the revolution number of the conflicting vehicle and the type of conflict.

12.0 TASK XI - PROVIDE CORE SPACE FOR THE PRECEDING TASKS

The current version of MULTICON uses almost all of the core locations available under the COPII system. The following changes are intended to provide the extra core space needed to accomplish the preceding tasks.

- a. Remove all uses of subroutines TAPE, INPUT, and EOT. Use MTCII's TAPEIO and CARDIO to accomplish the tasks now done by these subroutines. INPUT is only used to read the data cards. Conversion is done by GCIR. There is also an unused subroutine (INOUT8), which references INPUT, but which should be removed.
- b. Remove MULTICON subroutine PR1612 and replace with MTCII's subroutine PRNT1612. Most of the calls to PR1612 will remain the same, but some may have to be modified.
- c. Remove MULTICON subroutine CHEKEOT and all its references. The current version of OUTPUT checks for end-of-tape and error exits if it is detected. The error returns from OUTPUT will have to be changed.
- d. Subroutinize the code in ABSAO, which sorts the acquisition messages into acquisition time order. Then, replace the sort code in MERGE with a call for the new sort subroutine. This will have the further advantage of reducing MULTICON's execution time, since the sort in MERGE takes about ten times longer than the sort in ABSAO.
- e. Replace duplicate constants with EQU cards.
- f. Use the same area of core for non-conflicting temporary storage. This has already been done for some of the MULTICON subroutines.

1 April 1963

- 21 -

TM-(L)-891/006/00

APPENDIX A

VEHICLE CODE
3600 A
7094 B
1107 C
7070 D
1620 E

DAY	TIME	COOK	TASC	AME	KODI
		A B C D E F G H I J	A B C D E F G H I J	A B C D E F G H I J	A B C D E F G H I J
30JUN2350		1	1		4
30JUN2351		1	1		4
30JUN2352		1	1		4
30JUN2353		1	1		4
30JUN2354		1	1		4
30JUN2355		1	1		4
30JUN2356		1	1		4
30JUN2357		1	1		4
30JUN2358		1	1		4
30JUN2359		1	1		4
000000		1	1		4
1JUL0001		1	1		4
1JUL0002		1	1		4
1JUL0003		1	1		4
1JUL0004		1	1		4
1JUL0005		1	1		4
1JUL0006		1	1		4
1JUL0007		1	1		4
1JUL0008		1	1		4
1JUL0009		1	1		4

1 April 1963

- 22 -

TM-(1.)-891/006/00

APPENDIX B

SPLICE Tape Format (BCD)

Header Record: 10 words

Characters: 5- 7 - FTV
10-16 - STATION
21-23 - REV
29-32 - DATE
37-40 - RISE
47-49 - SET
55-62 - DURATION
64-67 - ELEV
69-71 - SEQ
74-79 - RUNNUM

Data Record: 10 words

Characters: 2 - D
5- 8 - Vehicle number
11 - Station number
13-16 - Station name
19-24 - Revolution number
28-29 - Day
30-32 - Month
35-36 - Hour
38-39 - Minute
41-42 - Second

} Date
} Rise time

1 April 1963

- 23 -

MM-(L)-891/006/00

45-46 - Hour	}	Set time
48-49 - Minute		
51-52 - Second		
55-56 - Hour	}	Duration
58-59 - Minute		
61-62 - Second		
65-66 - Maximum pass elevation		
68-71 - Sequence number		
73-80 - Identification		

End Data Record: 10 words

Characters:

68-71 - Number of acquisition data records
in this file.
74-78 - TOTAL

1 April 1963

- 24 -
(Last Page)

FM- (1) - 891/006/00

APPENDIX C

PATCH Tape Format (BCD)

Header Record: 5 words

Words:	0	- PATCH
	1	- Tape sequence number
	2	- BCD blanks
	3	- Month (biased)
	4	- Day (biased)

Data Record: usually 35 words (maximum) - this record can contain less than 35 words but the number of words will always be a multiple of 7.

Words:	0,7,14,21,28	- BCD blanks
	1,8,15,22,29	- Revolution number
	2,9,16,23,30	- Vehicle number
	3,10,17,24,31	- Station number
	4,11,18,25,32	- Acquisition time
	5,12,19,26,33	- Fade time
	6,13,20,27,34	- BCD blanks

End Data Record: 2 words

Words:	0	- 0000000
	1	- Number of acquisitions in this file.

The old and new format PATCH tapes differ in only one respect: revolution number on the old format tape does not contain a fractional part, whereas the new format tape shows revolution number in tenths.

1 April 1963

TM-(L)-891/006/00

DISTRIBUTION
(EXTERNAL)

Space Systems Division
(Contracting Agency)

Maj. C. R. Bond (SSOCD)
Maj. N. D. LaVally (SAFSP-206)

PIR-E4 (GE-3198 Chestnut)

J. F. Butler
C. A. Cummings
H. D. Gilman

6594th Aerospace Test Wing
(Contracting Agency)

Colonel. A. W. Dill (TWRD)
Lt. Col. M. S. McDowell (TWRU) (4)
TWACS (20 copies)

PIR-E4 (GE-Bethesda)

W. L. Massey

PIR-E4 (GE-Box 8661)

F. T. Clark
J. D. Rogers
W. R. Weinrich

PIR-E1 (Lockheed)

J. A. Boysen
N. N. Epstein
W. E. Moorman (5)
G. F. Taylor
R. L. Vader
P. E. Williams

PIR-E5 (Aerospace)

F. M. Adair
A. Bakst
J. W. Bengston
R. V. Bigelow
R. O. Brandsberg
L. H. Garcia
C. J. Hansen (3 copies)
L. J. Kreisberg
M. L. Luther
T. R. Parkin
E. E. Retzlaff
H. M. Reynolds
D. Saadeh
R. G. Stephenson
D. D. Stevenson
V. White

PIR-E2 (Philco)

J. A. Bean
J. A. Isaacs
R. Morrison
S. M. Stanley

PIR-E3 (LFE)

D. F. Criley
K. B. Williams

PIR-E4 (GE-Santa Clara)

D. Alexander

PIR-E8 (Mellonics)

F. Druding

PIR-E4 (GE-Sunnyvale)

J. Farrentine
N. Kirby

1 April 1963

TM-(L)-891/006/00

DISTRIBUTION
(INTERNAL)

<u>NAME</u>	<u>ROOM</u>	<u>NAME</u>	<u>ROOM</u>
D. Allfree	24083	J. Haake	22153
J. Aldana	22131	D. Henley	22094
L. Alexander	22134	C. Hill	22101
N. Alperin	22153	J. Hillhouse	22078
E. Armstrong	24123	H. Holzman	24065
		G. Hudson	24126
C. Baccerra	24082		
D. Biggar	24118	R. Johnson	22125
R. Bilek	23007		
L. Brenton	24103	P. Kastama	22076
B. Burke	24086	M. Katz	25014
R. Burke	22158	F. Kayser	24109
R. Busch	22088	J. Keddy	24105
C. Bustya	22134	D. Key	23013
		R. Keyes	24073
M. Champaign	22152	J. Kneemeyer	22088
C. Chiodini	24091	R. Knight	22119
B. Ciacchia	24082	L. Kolbo	22155
R. Clements	22109		
B. Cline	24127	J. Laughlin	24073
J. Cogley	22156	J. LaVine	24093
L. Conger	24088	H. Lewis	23010
P. Cooley	24086	J. Little	24088
D. Crum	24105	F. Long	22156
		J. Lytton	24077
L. DeCuir	24053		
W. Derango	24082	G. Madrid	22081
G. Dexter	25016	G. Mahon	24089
R. Disse	23014	J. Marioni	24076
G. Dobbs	22116	R. Marshall	22160
W. Dobrusky	24065	W. Martin	24127
R. Dugas	22125	J. McKeown	23013
		J. Milanese	22155
R. Ellis	22131	J. Munson	22087
R. Ericksen	22113	G. Myers	22095
H. Feldstein	24128	P. Nelson	24075
C. Francis	25013	J. Ng	22077
H. Franks	24122	L. Ngou	24127
H. Frey	22078		
L. Friedman	22122	M. Olson	22161
S. Gardner	25026	L. Padgett	24110
V. Gergen	25014	E. Patin	Sunnyvale
I. Greenwald	22094	D. Persico	24083
		T. Polk	24113

1 April 1963

TM-(L)-891/006/00

<u>NAME</u>	<u>ROOM</u>
D. Reilly	24121
A. Robinson	24132
M. Rockwell	24086
J. Schroeder	24124
R. Scott	24110
C. Seacat	Sunnyvale
H. Seiden	22126
R. Shapiro	24110
S. Shoel	23007
R. Skelton	22152
N. Speer	24086
E. Stone	24058
M. Sweeney	25026
W. Taber	22101
T. Tennant	27029
J. Thompson	24088
C. Toche	24121
R. Totschek	24120
A. Tucker	22109
A. Vorhaus	24076
M. Weinstock	22131
S. Weems	22109
G. West	Sunnyvale
G. P. West	22116
H. Williams	22110
G. Wilson	24124
M. Winsor	22156
J. Winter	24117
R. Wise	22085
J. Wong	Sunnyvale
C. Zubris	24075
AFCPL (5)	14059

UNCLASSIFIED

System Development Corporation,
Santa Monica, California
PROGRAM DESIGN SPECIFICATIONS FOR
MODIFICATIONS TO MULTICON.
Scientific rept., TM(L)-891/006/00,
by J. Hillhouse, H. Frieden. 1 April 1963,
24p.
(Contract AF 19(628)-1648, Space Systems
Division Program, for Space Systems
Division, AFSC)

Unclassified report

DESCRIPTORS: Programming (Computers).
Satellite Networks.

UNCLASSIFIED

Presents the program design
specifications for the
modifications to MULTICON listed
in TM(L)-890/007/00 and
TM(L)-890/007/00A.

UNCLASSIFIED

UNCLASSIFIED