

UNCLASSIFIED

AD 407 706

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

63-4-2

CHINESE (MAINLAND)
SCIENCE AND TECHNOLOGY
JOURNALS

Table of Contents


CATALOGED BY DDC
AS AD NO. 407706

Date of Preparation: January 1963
Prepared by: N. H. Ng
Editor: Sister Marie-Margarita, S. N. D.

407706

Prepared for the Air Force Cambridge Research Laboratories
Research Library, L. G. Hanscom Field, Bedford, Massachusetts,
by the Emmanuel College Research Language Center, under
Contract Number AF 19 (604) - 8505.

Report No. - Mechanics 1 -



CONTENTS

LI-HSUEH HSUEH-PAO (ACTA MECHANICA SINICA)

	Page
Vol. 3, No. 1	1
No. 3	3
No. 4	6
Vol. 4, No. 1	11
No. 2	16

LI-HSUEH HSUEH-PAO

(力学学报)

ACTA MECHANICA SINICA

Vol. 3, No. 1, January 1959

CONTENTS

Local Hypothesis Used in the Turbulent Flow of a Viscous Fluid

L. G. Loitsyansky
Kalinin Institute of Technology,
Leningrad
Translated by Tung Wu-min (童務民)

Calculation of Liquid Flow in a Radial-Axial Turbine

S. V. Vallander
Leningrad University
Translated by Wu Shih-k'o (吳士科)

Stability of Compressed Bars in the Presence of Creep

Huang K'e-chih (黃克智)
Tsinghua University

Simple Method for Designing a Small High-speed Propeller-type Turbine
(of a Capacity below 40 kw)

Zhang Hou-mei (張厚玫)
Institute of Mechanics, Academia Sinica

Determination of Loading Coefficients for Absolute Maximum Grinding

Productivity and of Force-Relations in the Operation of a Ball Mill

Liu Hsien-chih (劉先志)
Shantung Institute of Technology,
Chi-nan

Flow of Underground Water to an Imperfect Well in a Homogeneous
Anisotropic Porous Medium

Liu Tz'u-ch'ün (劉慈羣)
Institute of Mechanics, Academia Sinica

LI-HSUEH HSUEH-PAO

(力学学报)

ACTA MECHANICA SINICA

Vol. 3, No. 3, July 1959

CONTENTS

Laws of the Deformation of Material during Complex Loading

A. A. Il'yushin
V. S. Lenskii
Moscow University

Basic Problems of Anisotropic Non-homogeneous Elastic-plastic Mediums

W. Olszak
W. Urbanowski
Polish Academy of Sciences

Model Testing Techniques for Dynamic Resistance of Arch Dams

Structural Dynamics Testing Group
Dairen Institute of Technology

Elastic Stresses and Deformations Produced in a Semi-infinite Elastic Solid by a Point Source of Heat beneath Its Free Surface

Liu Hsien-chih (劉先志)
Shantung Institute of Technology

Matrix Method Analysis of the Framework of a Multi-story Structure

Lu Tzu-hua (呂子華)
Nanking Construction Engineering School

Generalized Formula for the Interference of Oil Wells on Horizontal, Inclined and Conical Strata under Hydraulic Pressure

V. I. Shurov
Li Tang (李 璽)
Peking Petroleum Institute

ABSTRACT

Elastic Stresses and Deformations Produced
in a Semi-infinite Elastic Solid
by a Point Source of Heat beneath Its Free Surface

For the purpose of solving our problem, we have, first of all, deliberately set up the displacement function

$$\Phi = \frac{1+\nu}{1-\nu} \cdot \frac{\alpha_0 Q}{4\pi\lambda_0} (\sqrt{|z-h|^2 + r^2} - \sqrt{(z+h)^2 + r^2}) \quad (19)$$

aiming to fulfill the Poisson equation

$$\Delta\Phi \equiv \left(\frac{\partial^2}{\partial r^2} + \frac{1}{r} \frac{\partial}{\partial r} + \frac{\partial^2}{\partial z^2} \right) \Phi = \frac{1+\nu}{1-\nu} \alpha_0 T, \quad (10)$$

where the temperature field T , aroused by the point source of heat, amounts to

$$T = \frac{Q}{4\pi\lambda_0} \left(\frac{1}{\sqrt{|z-h|^2 + r^2}} - \frac{1}{\sqrt{(z+h)^2 + r^2}} \right). \quad (17)$$

In order to warrant the unloaded conditions of the free surface of the semi-infinite elastic solid, which, in general, will not always be fulfilled by the sought displacement function Φ , we have resorted to a search for a second displacement function, whose derivation was carried out in another paper by the author entitled "Elastic stresses and deformations produced in a semi-infinite solid by the application of tangential traction to its free surface" (LI-HSUEH HSUEH-PAO/ACTA MECHANICA SINICA, Vol. 3, No. 2, 1959, 120).

When we superpose the stresses as well as the displacements corresponding to the two above-mentioned displacement functions, we obtain the

following expressions as the solution to this thermal stress problem:

$$\sigma_z = \bar{\sigma}_z + \bar{\sigma}_z = GK \left\{ -\frac{2(z-h)^2 + r^2}{[|z-h|^2 + r^2]^{3/2}} + \frac{2(z+h)^2 + r^2}{[(z+h)^2 + r^2]^{3/2}} \right\} + 2GKhz \frac{2(z+h)^2 - r^2}{[r^2 + (z+h)^2]^{3/2}}; \quad (34)$$

$$\tau_{rz} = \bar{\tau}_{rz} + \bar{\tau}_{rz} = -GK \left\{ \frac{r(z-h)}{[|z-h|^2 + r^2]^{3/2}} + \frac{r(z+h)}{[(z+h)^2 + r^2]^{3/2}} \right\} - 2GK \frac{hr}{[r^2 + (z+h)^2]^{3/2}} + 6GK \frac{h zr(z+h)}{[r^2 + (z+h)^2]^{5/2}}; \quad (35)$$

$$\sigma_r = \bar{\sigma}_r + \bar{\sigma}_r = GK \left\{ -\frac{(z-h)^2 + 2r^2}{[|z-h|^2 + r^2]^{3/2}} + \frac{(z+h)^2 + 2r^2}{[(z+h)^2 + r^2]^{3/2}} \right\} + 2GK \frac{h(3z+2h)}{[r^2 + (z+h)^2]^{3/2}} - 2GKhz \frac{2(z+h)^2 - r^2}{[r^2 + (z+h)^2]^{3/2}} - 2GKh \frac{\lambda + 2\mu}{(\lambda + \mu)r^2} \left(1 - \frac{z+h}{\sqrt{r^2 + (z+h)^2}} \right); \quad (36)$$

$$\sigma_\theta = \bar{\sigma}_\theta + \bar{\sigma}_\theta = -GK \left\{ \frac{1}{\sqrt{|z-h|^2 + r^2}} - \frac{1}{\sqrt{(z+h)^2 + r^2}} \right\} - \frac{2GK}{\lambda + \mu} \cdot \frac{h(\mu z - \lambda h)}{[r^2 + (z+h)^2]^{3/2}} + 2GK \frac{\lambda + 2\mu}{\lambda + \mu} \cdot \frac{h}{r^2} \left(1 - \frac{z+h}{\sqrt{r^2 + (z+h)^2}} \right); \quad (37)$$

$$u_r = \bar{u}_r + \bar{u}_r = \frac{K}{2} \left(\frac{r}{\sqrt{|z-h|^2 + r^2}} - \frac{r}{\sqrt{(z+h)^2 + r^2}} \right) + GK \frac{\lambda + 2\mu}{\mu(\lambda + \mu)} \cdot \frac{h}{r} \left(1 - \frac{z+h}{\sqrt{r^2 + (z+h)^2}} \right) - \frac{GK}{\mu} \cdot \frac{h zr}{[r^2 + (z+h)^2]^{3/2}}; \quad (38)$$

$$u_z = \bar{u}_z + \bar{u}_z = \frac{K}{2} \left(\frac{z-h}{\sqrt{|z-h|^2 + r^2}} - \frac{z+h}{\sqrt{(z+h)^2 + r^2}} \right) - \frac{GK}{\lambda + \mu} \cdot \frac{h}{\sqrt{r^2 + (z+h)^2}} - \frac{GK}{\mu} \frac{h z(z+h)}{[r^2 + (z+h)^2]^{3/2}}; \quad (39)$$

All the above expressions for the stresses and the displacements have been numerically evaluated with appropriate data and discussed in detail with accompanying graphs in Figures 1 to 18 (original text). The variations of these expressions representing the complete solution to this thermal elastic boundary value problem are shown by the curves in Figures 19 to 36 (original text).

.....

LI-HSUEH HSUEH-PAO

(力学学报)

ACTA MECHANICA SINICA

Vol. 3, No. 4, October 1959

CONTENTS

Development of Mechanical Science and Technology in China in the
Past Decade (1949-1958)

Institute of Mechanics
Academia Sinica

Similarity Structure of Vorticity Fluctuation and the Theory of
Turbulence

Chou Pei-yuan (周培源)
Peking University

Engineering Applications of the Plasticity Theory of Non-homogeneous
Mediums

W. Olszak
Polish Academy of Sciences

Limit Analysis and Design of Non-homogeneous and Orthotropic Structures

Part I: Plates

W. Olszak
A. Sawczuk
Polish Academy of Sciences

Problems Concerning Non-linear Creep

Chao Tsu-wo (趙祖武)
Tientsin University

Creep of Circular Symmetrical Plates and Cylindrical Shells

Huang K'e-chih (黄克智)
Tsinghua University

Importance and Possibility of Numerical Evaluation in Aerodynamics

A. A. Doro
Soviet Academy of Sciences

Experimental Verification of Several Creep Theories by Creep Tests
on No. 45 Steel

Ko Shou-chuan (柯受全)
Lu Si-nien (卢锡年)
Lee Tao-ngo (李桃考)
Institute of Mechanics
Academia Sinica

ABSTRACTS

Similarity Structure of Vorticity Fluctuation
and the Theory of Turbulence

The fluctuation motion in a turbulent flow is considered to consist in the random motion of vortices governed by the equations of turbulent vorticity fluctuation derived by taking the curl of the equations of velocity fluctuation. In the downward-moving system at mean velocity of the fluid, the vortices in the fluid are assumed to have similarity structure. In other words, according to the present theory, dynamically similar solutions are chosen for the equations of vorticity fluctuation in a moving system of reference.

Special problems are solved for turbulent flows limited by channel-like boundaries, along a semi-infinite plate and through a circular pipe, and, for free turbulence, in the two-dimensional and axially symmetrical wakes. It is shown that by neglecting the terms for the degree of viscosity in the equations of vorticity fluctuation in the moving system, the dynamical similarity condition leads to von Karman's well-known similarity regulations for boundary-limited flows in the central region of the wakes; while in the outer region within the wake interior, where the effect of viscosity cannot be ignored, the similarity condition yields the experimentally established relation that the Reynolds apparent shearing stress component is proportional to the transversal gradient of the mean flow velocity.

The requirement that the turbulent vorticity structure should have dynamical similarity leads to the conclusion that all the components of the Reynolds stress are mutually proportional to each other in the flow region where a definite type of similarity prevails. This theoretical result has experimental verification both in the boundary-limited flows and in the two-dimensional wake. The velocity correlations between two distinct points should also be independent of their position within the flow region having the same type of similarity, so long as the relative displacement between the two points remains the same. This also agrees qualitatively with the observations available.

The application of the condition of dynamical similarity gives us a length Λ , characterizing the size of vortices which compose the turbulent fluctuation. In the Karman type of similarity, Λ depends only upon the space derivatives of the mean velocity and is independent of the fluid viscosity, while Λ of the other type of vortices in the outer part of the wake interior is dependent upon the coefficient of viscosity. The size of the latter kind is much smaller than the former. These two kinds of vortices in turbulent motion have long been anticipated in theoretical investigations of turbulence.

In view of the fact that the condition of dynamical similarity can only be applied within a definite flow region and that not only in different flow problems but also in different flow regions of the same problem there are different similarity solutions as in the central and outer regions of the wake interior, we can see the limited nature of the application of the similarity concept in the turbulence theory.

Hence more rigorous solutions of the original vorticity fluctuation equation should be sought in order to connect the different types of similarity solutions present, for instance, in the wake problem.

The non-dimensional equations of vorticity fluctuation are still non-linear after the similarity transformation. It is difficult to obtain their solutions and (based upon them) to build the velocity correlation functions between two distinct points by the space average method. Since Taylor's scale of microturbulence λ is defined by a double velocity correlation, here again there is difficulty in obtaining the accurate relation between λ and the present scale of turbulent vorticity Λ .

Besides dealing with the heat conductivity problem in turbulent flows, the paper also gives applications for heated wakes. The theoretical result for the two-dimensional heated wake agrees with the existing experimental measurement.

.....

Experimental Verification of Several Creep Theories by Creep Tests on No. 45 Steel

Utilizing creep curves obtained for No. 45 steel under 500° C and different stresses, several typical creep theories, i.e., strain hardening theory-- $f(\sigma, \epsilon, \epsilon) = 0$, time hardening theory-- $f(\sigma, \epsilon, t) = 0$, and plastic hereditary theory-- $\varphi(\epsilon) = \sigma(t) + \int_0^t K(t - \tau)\sigma(\tau)d\tau$, are verified. Results are analyzed and simple methods for checking these theories are given.

.....

LI-HSUEH HSUEH-PAO

(力学学报)

ACTA MECHANICA SINICA

Vol. 4, No. 1, January 1960

CONTENTS

Problems Concerning the Development of Construction Mechanics

V. V. Bolotin
V. Z. Vlasov (The late)
I. I. Gol'denblat

Anisotropy, Non-linearity, Plasticity and Rheology in the Theory of Structures

W. Olszak
Polish Academy of Sciences

Free Edge Rectangular Plates on Elastic Foundations

Chen Shu-tao (陳叔陶)
Sian College of Metallurgy

Effect of Earthquakes on Dams (1)

Kuo Han-yen (郭漢彥)
Kin Sun-shu (金詢叔)
Institute of Mechanics
Academia Sinica

Problems Concerning the Kinetic Stability of Systems with Variable Coefficients

Chang Ssu-ying (張嗣瀛)
Northeast Institute of Technology

Efficiency of Water Wheels in Hydrodynamics

Chang Hou-mei (張厚致)
Hu Hai-chang (胡海昌)
Liu Shih-ning (劉士寧)
Liu Chuen-tu (柳春圖)
Institute of Mechanics
Academia Sinica

Determination by a Direct Method of Stresses and Displacements Produced
in a Semi-infinite Elastic Solid by a Fixed Point Source of Heat on Its
Surface

Liu Hsien-chih (劉先志)
Shantung Institute of Technology

ABSTRACTS

Free Edge Rectangular Plates on Elastic Foundations

This paper is a generalization of an article by H. Hapel entitled "Über das Gleichgewicht von elastischen Platten unter einer Einzellast" (Mathematische Zeitschrift, 6, 1920). It differs from the article in four respects:

- (1) Both symmetrical and asymmetrical loadings are discussed in detail.
- (2) The origin of the coordinates is placed at the corner of the plate instead of at the center. In this way the functions U and V and their integrals are considerably simplified.
- (3) Both isotropic and orthotropic plates are treated.
- (4) Both the Ritz and the Galerkin method of variation are used to solve the problem.

In the paper the variation equations are written in standard form and the values of the functions U and V and their second derivatives at 11×11 points are tabulated. Once the dimensions a and b , the rigidity D of the plate, the modulus k of the foundation, and the concentrated loads P are known, the reader may calculate the deflections of and the moments in the plate by direct application of these equations.

.....

Effect of Earthquakes on Dams (1)

In this paper, the results of a model test of earthquake effect on dams are presented.

The experimentation consists of measuring the strains and displacements at various points on the surface of the model when it is suddenly set into vibration by a horizontal impulse applied to its base. The model is fixed to a rigid table suspended on cables, and the impulse is calibrated so that a known amount of momentum is transferred to the table by impact of the pendulum. The duration of impact is made much shorter than the second natural period of vibration of the model. The swing of the table after impact, being of very low frequency, does not cause any appreciable additional distortion to the model and can be neglected.

Insofar as the model may be regarded as a linear elastic system, if we denote the stress (or displacement) measured at any point by $K(t)$, then for arbitrary ground acceleration $\ddot{Z}(t)$, such as produced by an earthquake, the stress (or displacement) at the same point may be evaluated by means of Duhamel's integral, i.e.,

$$\sigma(t) = \int_0^t K(t-\tau) \ddot{Z}(\tau) d\tau.$$

The model is made of rubber. Bonded resistance wire gauges are used for the measurement of strain. The strain gauges, because of their high rigidity in comparison with that of rubber, alter in a significant way the local strain distribution of the model, so that the apparent strain readings taken by the ordinary method do not give the actual strains which would be produced when no strain gauges were used.

However, it is found by our experiment that a definite ratio exists between the apparent and actual strains.

The results of the experiment are given in Figures 3 to 8 (original text).

$K(t)$ can be resolved into various components of free vibration, each component being of the type $e^{-\eta_i \omega_i t} \sin \sqrt{1 - \eta_i^2} \omega_i t$. Conversion of the results of the model experiment to the prototype is direct provided one makes certain modifications to account for the difference in damping coefficients and neglects the difference in Poisson's ratios. Making use of this fact, the stresses are computed by means of Duhamel's integrals, for which an actual acceleration seismogram is used. Similarly, use is made of published strong earthquake spectra to find the upper bounds of stresses which may possibly occur during strong earthquakes.

.....

Efficiency of Water Wheels in Hydrodynamics

Among the various small types of low water-head power systems or hydroelectric power stations, the one operated by water wheels is the most suitable for the present rural areas of China. The use of water wheels in these facilities is more efficient than any type of water turbine, especially when the available water-head is less than two meters.

In this paper the head losses in the "middle-push" type water wheel are analyzed, their magnitudes estimated and the similarity law derived. It is pointed out that the kinetic energy flowing out from the water wheel can be recovered by a well-designed open channel.

.....

LI-HSUEH HSUEH-PAO

(力学学报)

ACTA MECHANICA SINICA

Vol. 4, No. 2, April 1960

CONTENTS

Stresses and Displacements of a Water Turbine Shell

Wu Chi-tse (郭紀澤)

Hu Chia-jui (胡家瑞)

Institute of Machines, Academia Sinica

Heat Exchanger Tube-sheet Design

W. Urbanowski

Strength of a Thick-walled Multi-layer Pressure Container

Z. Klebowski

W. Urbanowski

Design for the Runner Vanes of Francis Water Turbines (1)

Pan Liang-ju (潘良儒)

Cheng Che-min (鄭哲敏)

Tsoon Wan-shia (鍾禹勳)

Liu Hsi (劉曦)

Chyi Jing-tay (齊景泰)

Wang Li-li (王礼立)

Institute of Mechanics, Academia Sinica

Stress on the Planes of Isotropic Elastic Solids

Iwan Chr. Ganev

ABSTRACT

Design for the Runner Vanes of Francis Water Turbines (1)

Under Vallander's assumption the stream surfaces in a Francis water turbine remain the same with or without the runner vanes. The equation governing the flow in a thin sheet between two adjacent stream surfaces is

$$\frac{\partial^2 \phi}{\partial u^2} + \frac{\partial^2 \phi}{\partial z^2} + \frac{1}{h} \frac{\partial h}{\partial z} \frac{\partial \phi}{\partial z} = 0$$

or

$$\frac{\partial^2 \psi}{\partial u^2} + \frac{\partial^2 \psi}{\partial z^2} - \frac{1}{h} \frac{\partial h}{\partial z} \frac{\partial \psi}{\partial z} = 0,$$

where ϕ and ψ denote the velocity potential and the stream function, u and z are the transformed coordinates and h is the thickness of the thin stream surface sheet under consideration.

By the transformations $\phi = \sqrt{h} \Phi$ and $\psi = \frac{1}{\sqrt{h}} \Psi$, the pair of equations is reduced to

$$\nabla^2 \Phi = 0 \text{ and } \nabla^2 \Psi = 0,$$

if $\frac{d}{dz} \left(\frac{1}{h} \frac{dh}{dz} \right)$ and $\left(\frac{1}{h} \frac{dh}{dz} \right)^2$ are small by comparison with the square of the number of runner vanes.

The flow around the vanes in a thin stream surface sheet was also treated by Vallander and Kiselev; however, the relation between the flows in two adjacent stream surface sheets remains as yet unknown. In this paper the same relation is adopted to connect the flows in adjacent sheets as in Bauersfeld-Voznesensky's two dimensional theory, that is, the circulation along the contour between any two meridional planes and

outside of the runner vane is constant.

The solution is based on the method of singularities. At the end of the paper the vortex distribution function is discussed. It is found that the addition of a term corresponding to the flow about a flat plate results in a definite angle of attack and thereby increases load near the leading edge of a vane, which may be desirable in certain cases. But the distribution function needs to be further improved for a good design.

It is worthy of note that the present solution is also applicable to the case where k is not constant and small as assumed in Kiselev's method, and that it would avoid the lengthy computation of Vallander's method, although Vallander's solution is more accurate.

.....