

UNCLASSIFIED

AD 408 136

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY DDC

408136

AS


408 136

63-4-2


USAELRDL Technical Report 2359

SOLID-STATE MICROMINIATURE CIRCUITRY
FOR THE RADIOSONDE

M. Robert Miller



June 1963



UNITED STATES ARMY
ELECTRONICS RESEARCH AND DEVELOPMENT LABORATORY
FORT MONMOUTH, N.J.

U. S. ARMY ELECTRONICS RESEARCH AND DEVELOPMENT LABORATORY
FORT MONMOUTH, NEW JERSEY

June 1963

USAELRDL Technical Report 2359 has been prepared under the supervision of the Director, Electronic Components Department, and is published for the information and guidance of all concerned. Suggestions or criticisms relative to the form, contents, purpose, or use of this publication should be referred to the Commanding Officer, U. S. Army Electronics Research and Development Laboratory, Fort Monmouth, New Jersey, Attn: Chief, Semiconductor and Microelectronics Branch, Solid State and Frequency Control Division.

J. M. KIMBROUGH, JR.
Colonel, Signal Corps
Commanding

OFFICIAL:

HOWARD W. KILLAM
Major, SigC
Adjutant

DISTRIBUTION:

Special

QUALIFIED REQUESTERS MAY OBTAIN COPIES
OF THIS REPORT FROM ASTIA.

THIS REPORT HAS BEEN RELEASED TO THE OFFICE OF
TECHNICAL SERVICES, U. S. DEPARTMENT OF COMMERCE,
WASHINGTON 25, D. C., FOR SALE TO THE GENERAL
PUBLIC.

SOLID-STATE MICROMINIATURE CIRCUITRY
FOR THE RADIOSONDE

M. Robert Miller

DA TASK NR. 3A99-21-003-02

ABSTRACT

This report describes the manner in which functions performed in the present radiosonde by means of tube circuits and mechanical clocks and switches can be performed by integrated circuits. The use of integrated circuitry, coupled with work now being done to develop a tunnel diode oscillator for the transmitter, should result in a size reduction of 95% or greater, as well as considerable savings in weight and power consumption.

The rocket version of the radiosonde is an application to which integrated circuitry is ideally suited if digital type circuits are used.

U. S. ARMY ELECTRONICS RESEARCH AND DEVELOPMENT LABORATORY
FORT MONMOUTH, NEW JERSEY

CONTENTS

	Page
ABSTRACT	i
INTRODUCTION	1
DISCUSSION	
General	1
Timing	1
Switching	2
Modulation	2
CONCLUSIONS	2
REFERENCES	3

FIGURES

1. Timing Multivibrator	4
2. Timing Pulses	5
3. Gating Sequence	5
4. Measuring Multivibrator	6
5. Modulator Output	7
6. Tunnel Diode Oscillator	8
7. Integrated Gating Circuit	9

SOLID-STATE MICROMINIATURE CIRCUITRY FOR THE RADIOSONDE

INTRODUCTION

The present radiosonde is an instrument which is carried aloft by a balloon and radios information on atmospheric temperature, humidity, and barometric pressure back to a ground receiving station. This is done while the balloon is being tracked for wind velocity information. This balloon-borne equipment is, however, limited to a maximum altitude of 150,000 feet, and in order to get higher altitude measurements an alternate system is being considered. In this system, the radiosonde is carried up by a rocket with measurements made as it parachutes back down. A rocket of this type will require a substantial reduction in the size and weight of the instrument.

This report describes a system for performing the functions of timing, measurement, and modulation using microminiature integrated circuitry. The use of integrated circuitry, coupled with work now being done to develop a tunnel diode oscillator for the transmitter, should result in a size reduction of 95% or greater.

DISCUSSION

General

The radiosonde transmitter is modulated by negative pulses. The repetition rate of these pulses is related to the resistance of the temperature or humidity sensor or reference resistor. These resistors, the temperature sensor (thermistor), humidity sensor, and reference resistor, must be switched into the measuring circuit one at a time and left on for a period long enough to make a measurement before the next one is switched into the circuit.

The required functions, then, are timing, switching, and modulation. At present the timing is done by a mechanical clock motor and switching by a commutator. The modulating circuit is a tube type blocking oscillator. These same functions can be performed by transistor circuits which could be produced as integrated circuits.

Timing

A period of about 2 seconds is desired as the "on" time for each resistor to be in the measuring circuit. In order to achieve a period this long with an astable multivibrator (Fig. 1) the time constant, determined largely by R_b and C , must be very large. It is desirable to limit C because large values of capacitance become physically very large. Therefore, the long R - C time constant must be achieved by making R large.

R is limited by the current requirements of the transistor. The current through R_b must be sufficient to drive the transistor into

saturation. These requirements can all be met if "micropower" transistors, which only recently have become available, are used.

The transistors used in the initial circuit were similar to the 2N929 and had an h_{FE} of 40 at $I_C = 5\mu A$. Since the transistor has sufficient gain, even at ultra-low current levels, large resistors can be used. In this circuit, the values used were:

$$C = .1\mu f, R_b = 10M, R_L = 470k, V_{CC} = 3V$$

and this resulted in a period of about 1.5 sec. This period can be changed over a wide range by changes in capacitance. Letting $C = 8\mu f$ in this circuit produced a period of about 2 min. This circuit could be produced in integrated form except for the large capacitors. Outboard capacitors of the proper value need not be too large because of the low working voltage.

Switching

The timing signal consists of a square wave that has equal on and off periods of 2 sec each. This waveform appears at both of the outputs with a 180° phase difference between them. The negative pulse from one of these outputs is used to drive a bistable multivibrator to give a total of four states as in Fig. 2. These signals are sent to four NOR gates so that three are at low potential and one is high at any time. This is illustrated in Fig. 3.

Modulation

The modulation is done by an astable multivibrator (Fig. 4) similar to the timing circuit. This multivibrator, however, is not symmetrical. One pulse is very short and fixed while the other is long and is controlled by the sensing resistors. The sensing resistors are inserted in the base of one of the transistors, and variations in this resistance vary the time required to charge the capacitance. Two reference resistors are used since four states are available. One is a high resistance and the other is low, providing calibration at both ends. The output then is a series of short pulses whose repetition rate depends on the resistance in the base circuit at that time. This is the type of modulation generally used in the radiosonde (Fig. 5).

This output can be used to modulate the tunnel diode oscillator (Fig. 6) in any of several ways. A transistor in the oscillator power supply can turn off the oscillator completely for the duration of each pulse or reduce the input voltage and thereby change the oscillator frequency.

CONCLUSIONS


The rocket version of the radiosonde is an application to which integrated circuitry is ideally suited if digital type circuits are used. The savings in size, weight, and power are evident advantages.

Also, the fact that long-period timing circuits are possible with transistors operating at very-low power levels may be of interest in other applications.



The power requirements of these circuits are very small, on the order of a few milliwatts. Therefore, the battery requirements in the radiosonde will be determined largely by the tunnel diode oscillator.

REFERENCES



1. Engineering Report - "Radiosonde Set AN/AMQ-9 ()" - by Arnold C. Peterson, 15 Jan 1958, Report No. E-1223.
2. "L-Band Tunnel Diode Oscillator" - Quarterly Progress Reports, Nos. 1 and 2, 1 June-31 Aug, 1 Sept-30 Nov, 1962. Contract No. DA 36-039 SC-90773.




TIMING MULTIVIBRATOR
FIG. 1



TIMING PULSES
FIG. 2




GATING SEQUENCE
FIG. 3




MEASURING MULTIVIBRATOR

FIG. 4




MODULATOR OUTPUT
FIG. 5



TUNNEL DIODE OSCILLATOR
FIG. 6



M-62-554



INTEGRATED GATING CIRCUIT
FIG. 7

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Addressee</u>	<u>No. of Copies</u>	<u>Addressee</u>
3	Commanding General U.S.Army Electronics Command Attn: AMSEL-AD Fort Monmouth, New Jersey	1	USAEIRDL Liaison Officer U. S. Army Combat Developments Command CDCLN-EL Fort Belvoir, Virginia
1	Office of the Assistant Secretary of Defense (Research and Engineering) Attn: Technical Library Room 3E1065, The Pentagon Washington 25, D.C.	1	C. O., U. S. Army Engineer Research and Development Laboratories Attn: Technical Documents Center Fort Belvoir, Virginia
2	Chief of Research and Development Department of the Army Washington 25, D.C.	1	Commanding Officer U.S. Army Chemical Warfare Laboratories Attn: Technical Library, Bldg. 330 Army Chemical Center Maryland
1	Chief, United States Army Security Agency Attn: ACofS, G4 (Technical Library) Arlington Hall Station Arlington 12, Virginia	1	Commanding Officer Harry Diamond Laboratories Attn: Library, Bldg. 92 Room 211 Washington 25, D.C.
1	Commanding Officer U.S.Army Electronics Research and Development Activity Attn: Technical Library Fort Huachuca, Arizona	2	Headquarters, U.S. Air Force Attn: AFCIN Washington 25, D.C.
1	Commanding Officer U.S. Army Electronics Research and Development Activity Attn: SELWS-AJ White Sands, New Mexico	1	Rome Air Development Center Attn: RAALD Griffiss Air Force Base New York
1	Commanding Officer U. S. Army Electronics Research Unit P.O. Box 205 Mountain View, California	1	Headquarters Ground Electronics Engineering Installation Agency Attn: ROZMEL Griffiss Air Force Base, New York
1	Commanding Officer U.S.Army Electronics Materiel Support Agency (Attn:SELMS-ADJ) Fort Monmouth, N. J.		

DISTRIBUTION LIST (Cont)

<u>No. of Copies</u>	<u>Addressee</u>	<u>No. of Copies</u>	<u>Addressee</u>
2	Commanding General U.S.Army Materiel Command Attn: R&D Directorate Washington 25, D.C.	1	Chief of Naval Research Attn: Code 427 Department of the Navy Washington 25, D.C.
1	Aeronautical Systems Div. Attn: ASAPRL Wright-Patterson Air Force Base, Ohio	1	Bureau of Ships Technical Library Attn: Code 312 Main Navy Bldg., Room 1528 Washington 25, D.C.
1	U.S. Air Force Security Service Attn: ESD San Antonio, Texas	1	Chief, Bureau of Ships Attn: Code 454 Department of the Navy Washington 25, D.C.
1	Headquarters Strategic Air Command Attn: DOCE Offutt Air Force Base, Nebraska	1	Chief, Bureau of Ships Attn: Code 686B Dept. of the Navy Washington 25, D.C.
1	Headquarters Research & Technology Div. Attn: RTH Bolling Air Force Base Washington 25, D.C.	1	Director U.S. Naval Research Laboratory Attn: Code 2027 Washington 25, D.C.
1	Air Proving Ground Center Attn: PGAPI Eglin Air Force Base, Florida	1	Commanding Officer & Director U.S. Navy Electronics Laboratory Attn: Library San Diego 52, California
2	Air Force Cambridge Research Laboratories Attn: CRXL-R L.G. Hanscom Field Bedford, Massachusetts	1	Commander U.S. Naval Ordnance Laboratory White Oak Silver Spring 19, Maryland
2	Headquarters Electronic Systems Div. Attn: ESAT L.G. Hanscom Field Bedford, Massachusetts	20	Commander Armed Services Technical Information Agency Attn: TISIA Arlington Hall Station Arlington 12, Virginia
1	AFSC Scientific/Technical Liaison Office U.S. Naval Air Development Center Johnsville, Pa.	1	USAE LRDL Liaison Officer U.S. Army Tank-Automotive Center Detroit Arsenal Center Line, Michigan

DISTRIBUTION LIST (Cont)

<u>No. of Copies</u>	<u>Addressee</u>	<u>No. of Copies</u>	<u>Addressee</u>
1	USAELRDL Liaison Officer Naval Research Laboratory Attn: Code 1071 Washington 25, D.C.	1	Marine Corps Liaison Office SELRA/LNR, USAELRDL
1	USAELRDL Liaison Officer Massachusetts Institute of Technology Building 26, Room 131 77 Massachusetts Avenue Cambridge 39, Mass.	2	USACDC Liaison Office SELRA/LNF, USAELRDL
1	USAELRDL Liaison Office Aeronautical Systems Division Attn: ASDL-9 Wright-Patterson Air Force Base, Ohio	1	Commanding Officer U.S. Army Security Agency Processing Center Deal Area - Bldg. 5001
1	U.S. Army Research Liaison Office Lincoln Laboratory P.O. Box 73 Lexington, Mass.	1	Mr. A. H. Young Semiconductor Group Code 681A1A Bureau of Ships Department of the Navy Washington 25, D.C.
1	USAELRDL Liaison Officer Rome Air Development Center Attn: RAOL Griffiss Air Force Base New York	6	Chief, Technical Information Division, Hq, USAELRDL
1	USAFMSA Liaison Engineer USASCAJ APO 343 San Francisco, California	1	USAELRDL Technical Documents Center SELRA/ADT, Hexagon
1	Technical Director, SELRA/CS Headquarters, USAELRDL	1	Director, Electric Components Dept., USAELRDL
1	USAELRDL-White Sands Liaison Office SELRA/LNW, USAELRDL	1	Director, Solid State & Frequency Control Div., EC Dept
1	AFSC Scientific/Technical Liaison Office SELRA/LNA, USAELRDL	1	Deputy Director, Solid State & Frequency Control Div., EC Dept.
1	Corps of Engineers Liaison Office, SELRA/LNE, USAELRDL	5	Chief, Technical Staff, Solid State & Frequency Control Div
		5	Chief, Piezoelectric Crystal & Circuitry Br, Solid State & Frequency Control Div.

/

DISTRIBUTION LIST (Cont)

<u>No. of Copies</u>	<u>Addressee</u>
25	Chief, Semiconductor & Microelectronics Br, Solid State & Frequency Control Div.
5	Chief, Microwave & Quantum Electronics Br, Solid State & Frequency Control Div.
1	File Unit Nr.1, Rm 3D-116 Hexagon
1	Chief Scientist U. S. Army Electronics Command Attn: AMSEL-SC Fort Monmouth, N. J.

AD	Div.	UNCLASSIFIED	AD	Div.	UNCLASSIFIED
Army Electronics Research and Development Laboratory, Fort Monmouth, N. J. SOLID-STATE MICROMINIATURE CIRCUITRY FOR THE RADIOSONDE, by M. Robert Miller, June 1963, 9 p. incl illus., 2 refs. (AELRDL Technical Report 2359 (DA Task 3A99-21-003-02) Unclassified report This report describes the manner in which functions performed in the present radiosonde by means of tube circuits and mechanical clocks and switches can be performed by integrated circuits. The use of integrated circuitry, coupled with work now being done to develop a tunnel diode oscillator for the transmitter, should result in a size reduction of 95% or greater, as well as considerable savings in weight and power consumption. The rocket version of the radiosonde is an application to which integrated circuitry is ideally suited if digital type circuits are used.		1. Radiosonde 2. Micropower Transistors 3. Integrated Circuitry I. Miller, M. Robert II. Army Electronics Research & Development Laboratory Fort Monmouth, N. J. III. DA Task 3A99-21-003-02	Army Electronics Research and Development Laboratory, Fort Monmouth, N. J. SOLID-STATE MICROMINIATURE CIRCUITRY FOR THE RADIOSONDE, by M. Robert Miller, June 1963, 9 p. incl illus., 2 refs. (AELRDL Technical Report 2359 (DA Task 3A99-21-003-02) Unclassified report This report describes the manner in which functions performed in the present radiosonde by means of tube circuits and mechanical clocks and switches can be performed by integrated circuits. The use of integrated circuitry, coupled with work now being done to develop a tunnel diode oscillator for the transmitter, should result in a size reduction of 95% or greater, as well as considerable savings in weight and power consumption. The rocket version of the radiosonde is an application to which integrated circuitry is ideally suited if digital type circuits are used.		1. Radiosonde 2. Micropower Transistors 3. Integrated Circuitry I. Miller, M. Robert II. Army Electronics Research & Development Laboratory Fort Monmouth, N. J. III. DA Task 3A99-21-003-02
AD Div. UNCLASSIFIED		AD Div. UNCLASSIFIED		AD Div. UNCLASSIFIED	
Army Electronics Research and Development Laboratory, Fort Monmouth, N. J. SOLID-STATE MICROMINIATURE CIRCUITRY FOR THE RADIOSONDE, by M. Robert Miller, June 1963, 9 p. incl illus., 2 refs. (AELRDL Technical Report 2359 (DA Task 3A99-21-003-02) Unclassified report This report describes the manner in which functions performed in the present radiosonde by means of tube circuits and mechanical clocks and switches can be performed by integrated circuits. The use of integrated circuitry, coupled with work now being done to develop a tunnel diode oscillator for the transmitter, should result in a size reduction of 95% or greater, as well as considerable savings in weight and power consumption. The rocket version of the radiosonde is an application to which integrated circuitry is ideally suited if digital type circuits are used.		1. Radiosonde 2. Micropower Transistors 3. Integrated Circuitry I. Miller, M. Robert II. Army Electronics Research & Development Laboratory Fort Monmouth, N. J. III. DA Task 3A99-21-003-02	Army Electronics Research and Development Laboratory, Fort Monmouth, N. J. SOLID-STATE MICROMINIATURE CIRCUITRY FOR THE RADIOSONDE, by M. Robert Miller, June 1963, 9 p. incl illus., 2 refs. (AELRDL Technical Report 2359 (DA Task 3A99-21-003-02) Unclassified report This report describes the manner in which functions performed in the present radiosonde by means of tube circuits and mechanical clocks and switches can be performed by integrated circuits. The use of integrated circuitry, coupled with work now being done to develop a tunnel diode oscillator for the transmitter, should result in a size reduction of 95% or greater, as well as considerable savings in weight and power consumption. The rocket version of the radiosonde is an application to which integrated circuitry is ideally suited if digital type circuits are used.		1. Radiosonde 2. Micropower Transistors 3. Integrated Circuitry I. Miller, M. Robert II. Army Electronics Research & Development Laboratory Fort Monmouth, N. J. III. DA Task 3A99-21-003-02