

UNCLASSIFIED

AD 408 721

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

408 721

CATALOGED BY DDC

AS AD NO. 408721

NOLTR 63-8

NOL

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

8 APRIL 1963

A COMPARISON OF NUMERICAL SCHEMES TO
CALCULATE THE SOLUTIONS OF A NON-
LINEAR PARTIAL DIFFERENTIAL EQUATION
WITH SHOCKS

DDC
RECEIVED
JUL 9 1963
TICOM A

63-4-2

NOLTR 63-8

NOLTR 63-8

Mathematics Department Report M-33

A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS
OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS

Prepared by:
A. Douglis

ABSTRACT: In a simple problem with shocks and rarefactions for the equation

$$u_t + \left(\frac{1}{2} u^2 + u\right)_x = 0 ,$$

six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.

U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

NOLTR 63-8

8 April 1963


This report is a study of the relative accuracy of six alternative methods of calculating a solution involving shocks and a rarefaction wave for the equation

$$u_t + \left(\frac{1}{2} u^2 + u\right)_x = 0 .$$

The equation is equivalent to that proposed by Burgers as a simplified model for shock problems in fluid dynamics. The results are believed to be suggestive as to calculations in such problems.

This work was carried out under NOL Task No. FR-30.

ROBERT ODENING
Captain, USN
Commander



RICHARD C. ROBERTS
By direction

NOLTR 63-8

CONTENTS

	Page
INTRODUCTION	1
THE CALCULATION SCHEMES TESTED	4
1. Lax's original centered difference method	4
2. A left difference method without viscosity	4
3. The viscosity method of Lax and Wendroff	5
4. A modified Lax-Wendroff scheme	5
CONCLUSIONS	8
APPENDIX	21
FOOTNOTES	29
REFERENCES	30

TABLES

Table

1	Mesh Widths, Mesh Width Ratios, and Indices of Cost	7
2	Average Errors	9
3	Average Calculation Error in Region of Rapid Transitions	11
4	Centered Difference Method of Lax: Method 1, $C=32^*$. Calculated Values	12
5	Left Difference Method Without Viscosity: Method 2, $C=32^*$. Calculated Values	13
6	Lax-Wendroff Method Without Added Viscosity: Method 3.0, $C=32^*$. Calculated Values	14
7	Lax-Wendroff Method With Added Viscosity: Method 3.1, $C=32^*$. Calculated Values	15
8	Modified Lax-Wendroff Method Without Added Viscosity: Method 4.0, $C=32^*$. Calculated Values	16
9	Left Difference Method Without Viscosity: Method 2, $C=32$. Exact Minus Calculated Values in Region of Rapid Transition*	17
10	Lax-Wendroff Method Without Added Viscosity: Method 3.0, $C=32$. Exact Minus Calculated Values in Region of Rapid Transition*	19
11	Lax-Wendroff Method With Added Viscosity: Method 3.1, $C=32$, $B=1/4$. Exact Minus Calculated Values in Region of Rapid Transition	20

FIGURE

Figure

1	Exact Solution	3
---	--------------------------	---

A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS

INTRODUCTION

A simple problem with shocks and rarefactions for the equation

$$(1) \quad u_t + \left(\frac{1}{2}u^2 + u\right)_x = 0$$

has been subjected to calculation by various procedures and all the results compared with the exact solution. The methods thus tested are

- (1) Lax's original centered difference method [1],
- (2) a left difference method without viscosity [2],
- (3) the viscosity method of Lax and Wendroff [3]
 - (3.0) without added artificial viscosity,
 - (3.1) with added artificial viscosity,
- (4) a modification of the Lax-Wendroff method for which convergence has been proved [4]
 - (4.0) without added artificial viscosity,
 - (4.1) with added artificial viscosity.

The programming of these schemes for an IBM 704 machine was performed mainly by W. Parr, with the assistance of Mrs. S. Madigosky, for whose patience and intelligent care I wish to express my gratitude and thanks.

Only calculations of roughly the same cost are compared. A multiplication or division costing about the same as ten additions, the measure of relative cost has been taken as

$$C = \frac{10u + a}{10,000 \text{ hk}},$$

where h and k are the horizontal and the vertical distances, respectively, between consecutive grid points (thus, $1/hk$ measures the total number of calculations performed in unit area of the x,t -plane), μ denotes the number of multiplications and divisions performed at a typical grid point, and α the number of other operations at that point.

The problem treated is that of finding a generalized solution ^{1/} of (1) with initial data prescribed as

$$u(x,0) = \begin{cases} 0 & \text{for } x < 0 \\ 2 & \text{for } 0 < x < 0.3 \\ 1 & \text{for } 0.3 < x < 0.9 \\ 0 & \text{for } x > .9 \end{cases}$$

This problem is easily solved explicitly with a rarefaction wave centered at $(0,0)$ and shocks issuing from $(.3,0)$ and $(.9,0)$, each shock being a line of slope

$$\frac{dx}{dt} = 1 + \frac{u_+ + u_-}{2},$$

where u_+ and u_- are the limiting values of the solution at the right and at the left of the shock, respectively. In the interval $0 \leq t \leq 0.6$, in particular, the solution of the problem is given by

$$u(x,t) = \begin{cases} 0 & \text{for } x \leq t \\ \frac{x}{t} - 1 & \text{for } t \leq x \leq 3t \\ 2 & \text{for } 3t < x < .3 + \frac{5}{2}t \\ 1 & \text{for } .3 + \frac{5}{2}t < x < .9 + \frac{3}{2}t \\ 0 & \text{for } x > .9 + \frac{3}{2}t \end{cases}$$

(See Figure 1.) This solution is known to be unique.^{2/}




FIG.1 EXACT SOLUTION

Note that, in this problem, $0 \leq u \leq M$, where

$$M = 2.$$

The same bounds, by a priori reasoning, applies to the calculated values of u in the first, second, and fourth schemes, and for present purposes will be assumed in the third. Note also that all schemes considered, except the third, have been proved to render approximations to the solution which are as close as desired, provided h and k are sufficiently small and the ratio $\Theta = k/h$ appropriately bounded.

THE CALCULATION SCHEMES TESTED

The notation in the following is that of [4]: v_{ij} denotes the value of u , as calculated according to the scheme in question, at the grid point $x = ih$, $t = jk$; $w_{ij} = (v_{i+1,j} - v_{ij})/h$ and $W_{ij} = hw_{ij} = v_{i+1,j} - v_{ij}$; $F(u) = u^2/2 + u$; $F_{ij} = F(v_{ij})$, $F'_{ij} = F'(v_{ij})$. Also, as above, $\Theta = k/h$.

1. Lax's original centered difference method. Lax's original scheme was based on the difference equations

$$v_{i,j+1} = \frac{1}{2}(v_{i+1,j} + v_{i-1,j}) - \frac{\Theta}{2}(F_{i+1,j} - F_{i-1,j}).$$

According to N. D. Vvedenskaya [6] (Theorem 1), the scheme converges when $\Theta \max |F'(v)| \leq 1$, or, in our case, when $\Theta \leq 1/(1 + M) = 1/3$.

2. A left difference method without viscosity. In this scheme,

$$v_{i,j+1} = v_{ij} - \Theta(F_{ij} - F_{i-1,j}).$$

The asymmetry of the scheme is permitted because of the non-negativity of F' . According to a remark at the end of the appendix below, convergence occurs when $\Theta \leq 1/4$.

3. The viscosity method of Lax and Wendroff. In this method,

$$v_{i,j+1} = v_{ij} - \frac{\Theta}{2}(F'_{i+1,j} - F'_{i-1,j}) + \frac{\Theta^2}{4}[(F'_{ij})^2 + F'_{i+1,j}(v_{i+1,j} - v_{ij}) - (F'_{i-1,j})^2 + F'_{ij}(v_{ij} - v_{i-1,j})] + \Theta(Q_{i-1,j} - Q_{ij}),$$

where $Q_{ij} = -B|F'_{ij} - F'_{i+1,j}|(v_{i+1,j} - v_{ij})$, B being

a non-negative constant here taken as zero in method 3.0 and as $1/4$ in method 3.1. Lax and Wendroff [3, p. 227] expect the scheme should be stable, in the case $B = 1/4$, when $\Theta \max |F'_{ij}| \leq .78$, thus when $\Theta \leq .78/(1+M) = .26$. Stability in the case $B = 0$ by their formula demands merely $\Theta \leq 1/3$. (The B in this paper is one fourth the quantity Lax and Wendroff call B .)

4. A modified Lax-Wendroff scheme. The calculation scheme here considered is

$$v_{i,j+1} = v_{ij} - \Theta(F'_{ij} - F'_{i-1,j}) + \frac{\Theta^2}{2}[F'_{ij}(v_{i+1,j} - v_{ij}) - F'_{i-1,j}(v_{ij} - v_{i-1,j})] + \Theta(Q_{i-1,j} - Q_{ij}),$$

the constant B entering Q_{ij} being taken as zero in Method (4.0) and as $1/4$ in Method (4.1). For $B \geq 0$, it is proved in [4] that this method converges if Θ is sufficiently small, but larger possible choices for Θ than emerge from that discussion are determined in the appendix below; these are

NOLTR 63-8

$$\begin{aligned}\Theta &= .16 \text{ for } B = 0 \text{ (Method (4.0))} \\ &= .156 \text{ for } B = 1/4 \text{ (Method (4.1)).}\end{aligned}$$

Two cost levels ($C = 8$ and $C = 32$) were arbitrarily fixed for all the above schemes and values of Θ selected near their permitted maxima. Then mesh widths h and k were obtained to accord in each case with the predetermined C and Θ . The values of the parameters thus entering are displayed in Table 1.

MESH WIDTHS, MESH WIDTH RATIOS, and INDICES OF COST

	1	2	3.0	3.1	4.0	1	2	3.0	3.1	4.0	4:1
h	.05148	.05477	.07282	.09682	.09478	.02575	.02739	.03641	.04841	.04739	.05993
k	.01699	.01369	.02403	.02517	.01516	.008495	.006845	.01202	.01258	.007582	.008030
ϕ	.3300	.2499	.3300	.2600	.1599	.3299	.2499	.3301	.2599	.1600	.1340
ϕ_{per}	1/3	.25	1/3	.26	.16	1/3	.25	1/3	.26	.16	.156
R	7.0	6.0	14.0	19.5	11.5	7.0	6.0	14.0	19.5	11.5	15.4
C	8.003	8.002	8.001	8.002	8.004	32.00	32.00	31.99	32.02	32.01	32.00

 h = mesh width in direction of x-axis k = mesh width in direction of t-axis ϕ = k/h ϕ_{per} = maximum permissible value of ϕ from a priori considerations R = index of relative cost = $\mu + a/10$, μ denoting the number of multiplications and divisions performed at a typical grid point and a the number of other operations at that point C = index of total cost = $(R/hk) \cdot 10^{-3}$.

Table 1

CONCLUSIONS

The results of the calculations by each method except 4.1 were tabulated after some thinning for the rectangle

$$R: \begin{array}{l} 0 < x \leq 1.8 \\ 0 < t \leq .6 \end{array},$$

the case $C = 32$ being presented here in Tables 4 - 8. The mean absolute error and root mean square error over all mesh points in R and, separately, in its top boundary line L are given for all calculations in Table 2. These results suggest the following observations, at least with respect to the example studied:

1. The use of artificial quadratic viscosity ($B \neq 0$) in Method 3.1 did not clearly reduce the average error and in Method 4.1 greatly increased it. Other values of B and lower mesh width ratios might, however, have led to better results.

2. Lax-Wendroff viscosity worked well in the method of centered differences (3.0) for which it had been proposed, but disappointingly in the left-difference scheme (4.0). Perhaps the latter method would have performed better, however, at a higher cost level at which the x -axis would be more finely subdivided.

3. Quadrupling the cost less than halved the average error.

4. Methods 2, 3.0, and 3.1 worked best: at identical costs, closely comparable mean errors resulted from the simple scheme and refined mesh of Method 2 and the refined schemes and coarser mesh of Methods 3.0 and 3.1.

Additional conclusions arise from comparing the three most successful methods on a region of relatively great transitions.

NOLTR 63-8

AVERAGE ERRORS

Method	C = 8.00				C = 32.00			
	E_R	E_L	S_R	S_L	E_R	E_L	S_R	S_L
1	.20	.18	.31	.28	.12	.11	.20	.18
2	.14	.12	.23	.20	.08	.08	.15	.16
3.0	.16	.11	.29	.22	.08	.07	.18	.23
3.1	.18	.11	.29	.18	.09	.08	.18	.19
4.0	.24	.21	.34	.32	.16	.15	.25	.25
4.1*					.34	.34	.55	.63

R denotes the rectangle $0 < x \leq 1.8$, $0 < t \leq .6$.

L denotes the line segment $0 < x \leq 1.8$, $t = [.6]_k$, where $[s]_k$ is the largest exact multiple of k that does not exceed s .

E_R = average absolute deviation of calculated from exact values of the solution at the lattice points in R.

E_L = average absolute deviation of calculated from exact values of solution at the lattice points on L.

S_R = root mean square deviation at the lattice points in R.

S_L = root mean square deviation at the lattice points on L.

C = index of total cost.

*Better results were obtained by Method 4.1 with $B = 1$ and a value of Θ much $< \Theta_{per}$; they still compared poorly with the others.

Table 2

For $C = 32$, in Tables 9, 10, and 11 we present with no thinning in the x -direction such a comparison over the trapezoid

$$T: \begin{aligned} &-.05 + 3t \leq x \leq .95 + 3t/2 \\ &.3 \leq t \leq .6, \end{aligned}$$

this area covering much of the vicinity of the two shocks and a small part of the rarefaction wave. The mean absolute error and the root mean square error over all the mesh points of T appear in Table 3. From these compilations it seems reasonable to add the following conclusions:

5. By all three methods (2, 3.0 and 3.1), calculated values tend to be too low to the left and too high to the right of a shock. These methods thus dull the apparent sharpness of a shock, but Method 2 perhaps to the greatest extent.

6. Method 3.0 seems most prone to occasional wild errors (occurring in this example to the right of the first shock); these errors, however, are rapidly corrected.

7. The average absolute error over T is about the same for the three methods; the mean square error, however, is appreciably less under Methods 2 and 3.1 than under Method 3.0.

Further study of our six methods might consider the effects, at constant cost, of varying the mesh width ratios below their maximum permissible values and also of varying the coefficient of artificial viscosity B .

NOLTR 63-8

AVERAGE CALCULATION ERROR
IN
REGION OF RAPID TRANSITIONS

Method	C = 32	
	E_T	S_T
2	.25	.29
3.0	.23	.36
3.1	.23	.29

T denotes the trapezoid $-.05 + 3t \leq x \leq .95 + 3t/2$
 $.3 \leq t \leq .6$

E_T = average absolute deviation of calculated from exact values
of the solution at the lattice points in T .

S_T = root mean square deviation at the lattice points in T .

C = index of total cost

Table 3

TABLE 4 CENTERED DIFFERENCE METHOD OF LAX: METHOD I, C=32.*
CALCULATED VALUES

X	0.	0.08	0.15	0.23	0.31	0.39	0.46	0.54	0.62	0.70	0.77	0.85	0.93	1.00	1.08	1.16	1.24	1.31	1.39	1.47	1.54	1.62	1.70	1.78	1.85	1.93
t	0.	0.00	0.00	0.01	0.03	0.06	0.09	0.16	0.22	0.32	0.40	0.52	0.61	0.74	0.84	0.98	1.08	1.23	1.33	1.49	1.57	1.69	0.92	0.27	0.11	0.02
0.56	0.	0.00	0.01	0.02	0.06	0.10	0.18	0.26	0.38	0.48	0.62	0.73	0.90	1.01	1.19	1.30	1.50	1.61	1.82	1.25	0.89	0.40	0.09	0.03	0.00	0.00
0.47	0.	0.00	0.02	0.06	0.11	0.21	0.31	0.47	0.59	0.78	0.92	1.13	1.27	1.51	1.65	1.99	1.30	0.98	0.80	0.35	0.16	0.02	0.01	0.00	0.00	0.00
0.37	0.	0.00	0.05	0.13	0.26	0.40	0.61	0.78	1.05	1.23	1.54	1.73	1.99	1.29	1.05	0.97	0.78	0.54	0.12	0.04	0.00	0.00	0.00	0.00	0.00	0.00
0.28	0.	0.01	0.05	0.13	0.26	0.40	0.61	0.78	1.05	1.23	1.54	1.73	1.99	1.29	1.05	0.97	0.78	0.54	0.12	0.04	0.00	0.00	0.00	0.00	0.00	0.00
0.19	0.	0.04	0.19	0.35	0.55	0.90	1.15	1.61	2.00	1.99	1.27	1.04	1.00	0.98	0.92	0.49	0.22	0.02	0.00	0.	0.	0.	0.	0.	0.	0.
0.09	0.	0.15	0.56	0.97	2.00	2.00	1.99	1.24	1.00	1.00	1.00	0.93	0.78	0.13	0.02	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
0.	0.	2.00	2.00	2.00	2.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.

* $h = .02575$, $k = .008495$, $\phi = .3299$

TABLE 5 LEFT DIFFERENCE METHOD WITHOUT VISCOSITY: METHOD 2, C=32.*

CALCULATED VALUES

x	0.	0.08	0.16	0.25	0.33	0.41	0.49	0.58	0.66	0.74	0.82	0.90	0.99	1.07	1.15	1.23	1.31	1.40	1.48	1.56	1.64	1.73	1.81	1.89
t	0.	0.00	0.00	0.00	0.00	0.02	0.06	0.13	0.23	0.35	0.47	0.59	0.72	0.85	0.98	1.11	1.24	1.37	1.49	1.61	1.63	1.73	1.81	1.89
0.57	0.	0.00	0.00	0.00	0.00	0.02	0.06	0.13	0.23	0.35	0.47	0.59	0.72	0.85	0.98	1.11	1.24	1.37	1.49	1.61	1.63	1.73	1.81	1.89
0.48	0.	0.00	0.00	0.00	0.02	0.07	0.16	0.29	0.42	0.57	0.72	0.87	1.03	1.18	1.33	1.48	1.62	1.76	1.90	0.91	0.21	0.01	0.00	0.00
0.38	0.	0.00	0.00	0.02	0.08	0.20	0.36	0.54	0.72	0.91	1.09	1.28	1.46	1.64	1.77	1.54	1.06	0.94	0.57	0.02	0.00	0.00	0.00	0.00
0.29	0.	0.00	0.02	0.10	0.27	0.48	0.72	0.96	1.20	1.44	1.66	1.84	1.66	1.07	1.00	0.98	0.57	0.04	0.00	0.00	0.00	0.00	0.00	0.00
0.19	0.	0.01	0.13	0.39	0.72	1.06	1.40	1.71	1.92	1.76	1.08	1.00	1.00	0.99	0.77	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
0.10	0.	0.08	0.70	1.30	1.82	2.00	1.85	1.08	1.00	1.00	1.00	1.00	0.92	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
0.	0.	2.00	2.00	2.00	2.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.


* h = .02739, k = .006845, e = .2499

TABLE 6 LAX-WENDROFF METHOD WITHOUT ADDED VISCOSITY: METHOD 3.0, C=32. *

X	0.	0.07	0.15	0.22	0.29	0.36	0.44	0.51	0.58	0.66	0.73	0.80	0.87	0.95	1.02	1.09	1.17	1.24	1.31	1.38	1.46	1.53	1.60	1.67	1.75	1.82	1.89
t	0.	0.07	0.15	0.22	0.29	0.36	0.44	0.51	0.58	0.66	0.73	0.80	0.87	0.95	1.02	1.09	1.17	1.24	1.31	1.38	1.46	1.53	1.60	1.67	1.75	1.82	1.89
0.58	0.	-0.00	0.00	-0.01	0.02	-0.00	-0.05	-0.02	0.07	0.17	0.29	0.40	0.52	0.64	0.76	0.88	1.00	1.12	1.24	1.36	1.48	1.60	1.71	1.87	0.01	0.01	0.00
0.48	0.	0.00	-0.01	0.02	-0.01	-0.05	0.01	0.12	0.25	0.38	0.52	0.66	0.80	0.95	1.09	1.23	1.37	1.51	1.66	1.80	1.95	2.10	2.25	0.50	0.01	0.00	0.00
0.38	0.	-0.00	0.02	-0.02	-0.05	0.00	0.19	0.35	0.52	0.70	0.87	1.05	1.22	1.40	1.57	1.74	1.92	2.13	2.35	2.57	2.79	3.01	3.23	0.01	0.00	0.00	0.00
0.29	0.	0.01	-0.03	-0.04	0.10	0.30	0.52	0.75	0.98	1.21	1.43	1.66	1.88	2.01	2.15	2.29	2.43	2.57	2.71	2.85	2.99	3.13	3.27	0.00	0.00	0.00	0.00
0.19	0.	-0.03	-0.01	0.22	0.53	0.85	1.18	1.50	1.82	2.00	2.08	2.14	2.00	1.00	0.96	1.14	0.56	0.01	0.00	0.00	0.00	0.00	0.00	-0.01	-0.01	-0.01	-0.01
0.10	0.	0.09	0.52	1.09	1.66	2.00	2.00	2.16	2.02	1.00	1.00	0.99	1.09	0.63	0.01	0.00	-0.01	-0.01	-0.01	-0.01	-0.01	-0.01	-0.01	-0.01	-0.01	-0.01	-0.01
0.	0.	2.00	2.00	2.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.

* h = .03641, k = .01202, θ = .3301

TABLE 7 LAX-WENDROFF METHOD WITH ADDED VISCOSITY: METHOD 3.1. C=32.*
CALCULATED VALUES



* $h = .04841$, $k = .01258$, $\theta = .2509$,

TABLE 8 MODIFIED LAX-WENDROFF METHOD WITHOUT ADDED VISCOSITY; METHOD 4.0 C=32.
CALCULATED VALUES

$x \backslash t$	0.	0.09	0.19	0.28	0.38	0.47	0.57	0.66	0.76	0.85	0.95	1.04	1.14	1.23	1.33	1.42	1.52	1.61	1.71	1.80	1.90
0.59	0.	0.00	0.00	0.01	0.04	0.10	0.19	0.30	0.42	0.55	0.68	0.81	0.93	1.05	1.16	1.25	1.29	1.27	1.09	0.64	0.16
0.49	0.	0.00	0.01	0.03	0.10	0.20	0.33	0.48	0.63	0.78	0.93	1.07	1.20	1.29	1.35	1.32	1.16	0.75	0.25	0.04	0.00
0.39	0.	0.00	0.03	0.10	0.22	0.39	0.57	0.75	0.93	1.10	1.25	1.36	1.41	1.36	1.19	0.84	0.37	0.07	0.01	0.00	0.00
0.30	0.	0.01	0.09	0.25	0.46	0.70	0.93	1.14	1.33	1.45	1.48	1.38	1.16	0.89	0.51	0.14	0.02	0.00	0.00	0.00	0.00
0.20	0.	0.07	0.29	0.60	0.92	1.22	1.45	1.58	1.53	1.31	1.08	0.94	0.69	0.24	0.03	0.00	0.00	0.00	0.00	0.00	0.00
0.10	0.	0.34	0.89	1.38	1.69	1.75	1.47	1.11	1.01	0.99	0.87	0.41	0.04	0.00	0.00	0.00	-0.	-0.	-0.	-0.	-0.
0.	0.	2.00	2.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.

* $h = .04739$, $k = .007582$, $\theta = .1600$

NOLTR 63-8

TABLE 9 LEFT DIFFERENCE
EXACT MINUS CA

J \ I	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47
88															
86															
84															
82															
80															
78															
76															
74															
72															
70															
68															
66															
64															
62															.215
60													.203	.230	.258
58												.216	.247	.248	.280
56										.206	.230	.247	.239	.288	.426
54								.220	.247	.232	.233	.300	.464	.320	-
52						.212	.235	.245	.218	.229	.319	.507	.274	.119	-
50				.226	.252	.226	.204	.230	.346	.445	.230	.095	.033	-	-
48		.220	.243	.250	.208	.193	.236	.380	.393	.190	.074	.025	.006	-	-
46	.235	.261	.228	.190	.184	.249	.422	.340	.153	.057	.018	.004	.004	-	-
44	.229	.253	.258	.206	.173	.179	.270	.472	.288	.121	.043	.013	.003	.003	.014

* The dashed line is the right hand boundary of the rarefaction wave: the solid lines intersecting it are the two shocks. The coordinates

$$x = .02739 (I - 1), \quad t = .006845 (J - 1)$$

to which any particular entry corresponds are ascribed to the decimal point for that

1

MOD WITHOUT VISCOSITY: METHOD 2, C=32.
 TED VALUES IN REGION OF RAPID TRANSITION *

49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68
																.563	.584	-.533	-.206
														.358	.588	.969	-.587	-.248	
													.387	.619	.050	.640	-.295		
										.282	.420	.642	-.063	.309	-.348	-.137			
								.307	.438	.659	-.071	.262	-.405	-.172					
					.241	.335	.487	.680	-.074	.217	-.466	-.213							
			.261	.368	.509	.296	-.073	.178	-.529	-.261									
		.218	.284	.391	.535	-.270	-.069	.144	.409	-.316	-.130								
	.234	.310	.406	.564	-.242	-.063	.115	.349	-.376	-.165									
.207	.253	.325	.425	.597	-.213	-.056	.091	.293	.440	-.207									
.220	.274	.330	.448	.567	-.185	-.049	.071	.242	-.506	-.255									
36	.282	.339	.477	.330	-.158	-.041	.055	.197	.428	-.310	-.128								
78	.352	.511	-.291	-.132	-.034	.043	.159	.364	-.371	-.163									
71	.549	-.252	-.109	-.028	.033	.126	.305	.436	-.204										
10	-.215	-.088	-.022	.025	.099	.251	-.504	-.253											
80	-.071	-.017	.019	.077	.203	.429	-.309	-.126											
56	-.013	.014	.059	.163	.365	-.370	-.161												
10	.011	.045	.128	.304	.435	-.202													
08	.034	.100	.250	.503	-.251														
25	.077	.201	.429	-.306	-.123														
59	.160	.363	-.368	-.158															
25	.302	.434	-.199																




50	49	48	47	46	45	44	43	42	41	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25
1.133	1.079	1.024	0.969	0.914	0.859	0.804	0.749	0.694	0.639	0.584	0.529	0.474	0.419	0.364	0.309	0.254	0.199	0.144	0.089	0.034	-0.021	-0.076	-0.131	-0.186	-0.241
1.120	1.066	1.011	0.956	0.901	0.846	0.791	0.736	0.681	0.626	0.571	0.516	0.461	0.406	0.351	0.296	0.241	0.186	0.131	0.076	0.021	-0.034	-0.089	-0.144	-0.199	-0.254
1.107	1.053	0.998	0.943	0.888	0.833	0.778	0.723	0.668	0.613	0.558	0.503	0.448	0.393	0.338	0.283	0.228	0.173	0.118	0.063	0.008	-0.047	-0.102	-0.157	-0.212	-0.267
1.094	1.040	0.985	0.930	0.875	0.820	0.765	0.710	0.655	0.600	0.545	0.490	0.435	0.380	0.325	0.270	0.215	0.160	0.105	0.050	-0.005	-0.060	-0.115	-0.170	-0.225	-0.280
1.081	1.027	0.972	0.917	0.862	0.807	0.752	0.697	0.642	0.587	0.532	0.477	0.422	0.367	0.312	0.257	0.202	0.147	0.092	0.037	-0.018	-0.073	-0.128	-0.183	-0.238	-0.293
1.068	1.014	0.959	0.904	0.849	0.794	0.739	0.684	0.629	0.574	0.519	0.464	0.409	0.354	0.299	0.244	0.189	0.134	0.079	0.024	-0.031	-0.086	-0.141	-0.196	-0.251	-0.306
1.055	1.001	0.946	0.891	0.836	0.781	0.726	0.671	0.616	0.561	0.506	0.451	0.396	0.341	0.286	0.231	0.176	0.121	0.066	0.011	-0.044	-0.099	-0.154	-0.209	-0.264	-0.319
1.042	0.988	0.933	0.878	0.823	0.768	0.713	0.658	0.603	0.548	0.493	0.438	0.383	0.328	0.273	0.218	0.163	0.108	0.053	-0.002	-0.057	-0.112	-0.167	-0.222	-0.277	-0.332
1.029	0.975	0.920	0.865	0.810	0.755	0.700	0.645	0.590	0.535	0.480	0.425	0.370	0.315	0.260	0.205	0.150	0.095	0.040	-0.015	-0.070	-0.125	-0.180	-0.235	-0.290	-0.345
1.016	0.962	0.907	0.852	0.797	0.742	0.687	0.632	0.577	0.522	0.467	0.412	0.357	0.302	0.247	0.192	0.137	0.082	0.027	-0.028	-0.083	-0.138	-0.193	-0.248	-0.303	-0.358
1.003	0.949	0.894	0.839	0.784	0.729	0.674	0.619	0.564	0.509	0.454	0.399	0.344	0.289	0.234	0.179	0.124	0.069	0.014	-0.041	-0.096	-0.151	-0.206	-0.261	-0.316	-0.371
0.990	0.936	0.881	0.826	0.771	0.716	0.661	0.606	0.551	0.496	0.441	0.386	0.331	0.276	0.221	0.166	0.111	0.056	0.001	-0.054	-0.109	-0.164	-0.219	-0.274	-0.329	-0.384
0.977	0.923	0.868	0.813	0.758	0.703	0.648	0.593	0.538	0.483	0.428	0.373	0.318	0.263	0.208	0.153	0.098	0.043	-0.012	-0.067	-0.122	-0.177	-0.232	-0.287	-0.342	-0.397
0.964	0.910	0.855	0.800	0.745	0.690	0.635	0.580	0.525	0.470	0.415	0.360	0.305	0.250	0.195	0.140	0.085	0.030	-0.025	-0.080	-0.135	-0.190	-0.245	-0.300	-0.355	-0.410
0.951	0.897	0.842	0.787	0.732	0.677	0.622	0.567	0.512	0.457	0.402	0.347	0.292	0.2												

$$x = .03641 (i - 1), \quad t = .01202 (j - 1),$$

to which any particular entry corresponds are ascribed to the decimal point for that entry.

TABLE II LAX-WENDROFF METHOD WITH ADDED VISCOSITY: METHOD 3.1, C=32, B=1/4
EXACT MINUS CALCULATED VALUES IN REGION OF RAPID TRANSITION*



APPENDIX

Our aim here is to find as large values of Θ as possible for which methods 4.0 and 4.1 will converge. Two procedures will be compared, the first that described in [4] and the second a modification of it. The second procedure turns out to be the better and leads to the values actually used above.

Calculation scheme 4 is that of [4] with

$$f = F, \quad g = 0, \quad s = 0, \quad q_{ij} = -\frac{k}{2}(1 + v_{ij})^2 w_{ij} + Q_{ij},$$

see pp. 5 and 21 and equation (4.4b)^{3/} In inequality (4.7), in particular, therefore, as we see at once,

$$b_{ij} = \frac{\Theta}{2}(1 + v_{i-1,j})^2 + B|w_{i-1,j}|, \quad c_{ij} = \frac{\Theta}{2}(1 + v_{ij})^2 + B|w_{ij}|,$$

$$d_{ij} = e_{ij} = 0.$$

To obtain inequality (4.8), it is well to note that

$$Q_{ij} = -B|w_{ij}|w_{ij} = f(w_{ij}), \quad \text{where } f(w) = -B|w|w,$$

and to use the method described for case (4.5c). In the result, we evidently will have

$$B_{ij} = \frac{\Theta}{2}(1 + v_{ij})^2 + 2B|w'_{ij}|, \quad C_{ij} = \frac{\Theta}{2}(1 + v_{i+1,j})^2 + 2B|w''_{ij}|, \quad H = \max H_{ij},$$

$$H_{ij} = 1 + (v_{ij} + v_{i+1,j})/2, \quad D_{ij} = E_{ij} = E'_{ij} = E''_{ij} = 0,$$

where w'_{ij} and w''_{ij} are numbers between w_{ij} and $w_{i-1,j}$, and between w_{ij} and $w_{i+1,j}$, respectively.

Both ways of bounding Θ begin with the argument for Theorem 5.1. In this argument, Θ is restricted by the single requirement that the coefficient of v_{ij} in the right member of (5.2) be non-negative, and, therefore, that

$$1 - \Theta(F'^* + b^* + c^* = ks^*) \geq 0 ,$$

the star in each case indicating a maximum value of the quantity concerned for the various possible values of its indices or arguments. Since

$$F'^* = 1 + M, \quad b^* = c^* = \frac{\Theta}{2}(1 + M)^2 + MB, \quad s^* = 0, \quad \text{we have the condition}$$

$$(2) \quad (1 + M)^2\Theta^2 + (1 + M + 2MB)\Theta - 1 \leq 0 .$$

M being equal to 2, for $B = 0$ we thus have

$$(3)_0 \quad \Theta \leq (5^{1/2} - 1)/6 = .206^+$$

and for $B = 1/4$

$$(3)_1 \quad \Theta \leq \frac{13-2}{9} = .178 .$$

In the first of the two ways of bounding, Θ now is subjected to an additional restriction arising from the argument for Theorem 5.2. According to this argument, the coefficients

$$p_{ij} = 1 - \Theta[1 + v_{ij} + \frac{\Theta}{2}(1 + v_{1,j})^2 + \frac{\Theta}{2}(1 + v_{1+1,j})^2 + 2B|w'_{ij}| + 2B|w''_{ij}|]$$

and

$$a = \frac{1}{2}(1 - 2\Theta(1+M))$$

in (5.8) ($b=0$ in this equation) must be made to satisfy the conditions

(p.14) $p_{ij} \geq 2/3$ and $a > 0$; hence, we require

$$(1 + M)^2 \theta^2 + (1 + M + 4BM)\theta - 1/3 \leq 0 \quad \text{and} \quad \theta < 1/2(1+M).$$

The first of these inequalities would imply the second. Since $M = 2$, the first inequality is equivalent to

$$(4)_0 \quad \theta \leq \frac{(7/3)^{1/2} - 1}{6} = .087^+ \quad \text{for } B = 0$$

and to

$$(4)_1 \quad \frac{\sqrt{37} - 5}{18} = .06 \quad \text{for } B = 1/4$$

It expresses the first of the two alternative bounds we have considered upon θ .

The second method of bounding θ comes from a second method of proof of Theorem 5.2 in which an argument of Vvedenskaya has been applied. We begin with inequality (5.7) which, in the present case, reads

$$w_{i,j+1} \leq [1 - \theta(F'_{ij} + B_{ij} + C_{ij})]w_{ij} + \theta(F'_{ij} + B_{ij})w_{i-1,j} + \theta C_{ij}w_{i+1,j} \\ - \frac{k}{2}[\bar{F}_{ij} - 2\theta(1 + \frac{v_{ij} + v_{i+1,j}}{2})]w_{ij}^2 - \frac{k}{2}\bar{F}_{ij}w_{i-1,j}^2,$$

single or double bars connoting intermediate values of the arguments as occurring in Taylor's theorem with remainder. The bracketed part of the coefficient of w_{ij}^2 is required to be positive, as previously, but the coefficient of w_{ij} , unlike before, is to be merely non-negative. Hence, θ now is to be such that $\min F'' - 2\theta(1+M) > 0$ and $1 - \theta(F'^* + B^* + C^*) \geq 0$, the star again signifying maxima of the quantities in question.

Since $F'' = 1$, the first of these conditions is

$$(5)_0 \quad \theta < 1/2(1+M) = \frac{1}{6} = .166^+.$$

The second, which we write as

$$(1+M)^2 \theta^2 + (1 + M + 4MB)\theta - 1 \leq 0,$$

reduces to $(3)_0$ for $B = 0$ and to the condition

$$(5)_1 \quad \theta \leq \frac{\sqrt{61} - 5}{18} = .156 \quad \text{for } B = 1/4.$$

No stronger condition, as we shall now see, arises out of the further argument. Let

$$\tilde{w}_{ij} = \max(w_{i-1,j}, w_{ij}, 0), \quad N_j = \max(0, \max_i w_{ij}).$$

From the above inequality, we have

$$(6) \quad w_{i,j+1} \leq (1 - \theta C_{ij}) \tilde{w}_{ij} + \theta C_{ij} N_j - \frac{c}{2} k \tilde{w}_{ij}^2,$$

where $c = \min F'' - 2\theta(1+M) = 1 - 2\theta(1+M)$. (In this type of argument we follow Vvedenskaya.) Since θ is supposed to satisfy the conditions of the previous paragraph, $c > 0$.

Next, like Vvedenskaya [6], consider the quadratic expression

$$H(y) \equiv H_{ij}(y) \equiv (1 - \theta C_{ij})y - \frac{c}{2}ky^2.$$

H will be monotonically increasing, i.e., $H'(y) = 1 - \theta C_{ij} - kcy \geq 0$, if $y \leq (1 - \theta C_{ij})/kc$. Hence, in particular

$$(7) \quad H(\tilde{w}_{ij}) \leq H(N_j) ,$$

if, for all i , $N_j \leq (1 - \theta C_{ij})/kc$. In (5.10) we have proved, however, that $N_j \leq \sup_i w_{i0} \leq m/h$, m being a bound for v_{i0} . (In the present case, $w_{ij} = W_{ij}$ as used on p. 14, and $b = 0$.) Hence, N_j satisfies the desired condition (7), if θ is so fixed that, for all i , $m/h \leq (1 - \theta C_{ij})/kc$. Substituting in this for c and also replacing C_{ij} by its upper bound $\frac{\theta}{2}(1 + M)^2 + 2MB$, we arrive at the condition

$$(1+M)(2m - \frac{1}{2}(1 + M)\theta^2 - (m + 2MB)\theta + 1) \geq 0 ,$$

which, for $m = M = 2$ becomes

$$\frac{15}{2} \theta^2 - (2 + 4B)\theta + 1 \geq 0$$

For $B = 0$ or $B = 1/4$, the quadratic expression on the left is definite: the inequality is satisfied for every value of θ and does not really constitute a restriction.

We are enabled by (7) to replace $\tilde{w}_{ij}$ in the right member of (6) by N_j and, thus, to obtain

$$w_{i,j+1} \leq N_j - \frac{c}{2} k N_j^2 ,$$

and, therefore,

$$(8) \quad N_{j+1} \leq N_j - \frac{c}{2} k N_j^2 .$$

From this, it is easy to produce an upper bound for N_j completing this alternative proof of Theorem 5.2. We shall show, to be specific, that

$$(9) \quad N_j \leq 2/cjk .$$

Set $z(t) = 2/ct$, $z_j = z(jk)$. Since $dz/dt = -cz^2/2$, integrating we obviously have

$$z_{j+1} - z_j = -\frac{c}{2} \int_{jk}^{(j+1)k} z(t)^2 dt > -\frac{c}{2} k z_j^2 ,$$

or

$$(10) \quad z_{j+1} > H(z_j) ,$$

where

$$H(y) \equiv y - cky^2/2 .$$

From this we shall prove by induction that

$$(11) \quad z_j \geq N_j , \quad j = 1, 2, \dots ;$$

these inequalities are equivalent to (9). The first step is to note that $z_1 \geq N_1$, $z_2 \geq N_2$, consequences of the fact discussed in a previous paragraph that $1/ck > m/h \geq N_1, N_2$. Next observe that $H(y)$ monotonically increases for $y \leq 1/ck$ and, furthermore, that $z_j \leq 1/ck$ for $j \geq 2$. Therefore, if $z_j \geq N_j$ for some index $j \geq 2$, for that index $H(z_j) \geq H(N_j)$. From this, (10), and (8), if for a particular index $j \geq 2$ we know $z_j \geq N_j$, we can conclude that

$$z_{j+1} > H(z_j) \geq H(N_j) \geq N_{j+1} .$$

The induction for (11) is thus complete.

We note in summary that our first method bounds Θ according to (3) and (4), our second method according to (3) and (5). The second results are obviously better; they permit use of the values

$$(12) \quad \begin{aligned} \Theta &= .166 \quad \text{for } B = 0 \\ &= .156 \quad \text{for } B = 1/4 \end{aligned}$$

in the calculations.

Remark: The left difference scheme without viscosity of section 2 is of type (4.4b) with

$$f_{ij} = F_{ij}, \quad g_{ij} = q_{ij} = s_{ij} = 0.$$

Reasoning like that above concerning Theorem 5.1 shows that, in this situation, $M = m$ if $\Theta \max F' \leq 1$, i.e., if $\Theta \leq 1/(1+M) = 1/3$. The further restriction

$$(13) \quad \Theta \leq 1/2m = 1/4$$

is easily seen to be required to bound w_{ij} (by the second method) according to Theorem 5.2. To show this, we start from (5.6) which, here, leads to the inequality

$$w_{i,j+1} \leq (1 - \Theta F'_{ij}) w_{ij} + \Theta F'_{ij} w_{i-1,j} - \frac{k}{2} (F''_{ij} w_{ij}^2 + F''_{ij} w_{i-1,j}^2)$$

and thus, in previous notation, to

$$w_{i,j+1} \leq \tilde{w}_{ij} - \frac{k}{2} \tilde{w}_{ij}^2$$

since $F'' = 1$ and since the coefficients on the right are all positive

NOLTR 63-8

because of the first restriction upon Θ . The previous argument leading to the desired upper bound for w_{ij} will apply completely, provided we now require $2m/h \leq 1/k$, a restriction which is the equivalent of (13).

FOOTNOTES

1/ By generalized solution we mean essentially a piecewise continuous solution satisfying the pertinent shock condition along discontinuities. More refined concepts of generalized solution are to be found in [2] and the accompanying references.

2/ For uniqueness theorem, cf [5].

3/ This and other numbered equations, theorems, etc., not belonging to the present paper are to be found in [4].

REFERENCES

1. P. D. Lax, Weak solutions of nonlinear hyperbolic equations and their numerical computation, Comm. Pure Appl. Math., 7(1954), 159-193
2. A. Douglis, On discontinuous solutions of quasi-linear, first order partial differential equations, NAVORD Report 6775, U. S. Naval Ordnance Lab., White Oak, Md., 1960, pp. 1-75
3. P. D. Lax and B. Wendroff, Systems of Conservation Laws, Comm. Pure Appl. Math., 13(1960), 217-238
4. A. Douglis, On calculating solutions of quasi-linear, first order partial differential equations, NAVWEPS Report 7254, U. S. Naval Ordnance Lab., White Oak, Md., 1960, pp. 1-23
5. O. A. Oleinik, On discontinuous solutions of nonlinear differential equations, Dokl. Akad. Nauk SSSR 109(1956), 1098-1101
6. N. D. Vvedenskaya, The difference method solution of Cauchy's problem for a non-linear equation with discontinuous initial values, Dokl. Akad. Nauk SSSR 111(1956), 517-521

NOLTR 63-8

EXTERNAL DISTRIBUTION LIST (M1)

	Copies		Copies
Chief, Defense Atomic Support Agency Washington 25, D. C. Attn: Document Library Branch	2	Director of Intelligence Headquarters, USAF Washington 25, D. C. Attn: AOIN-3B	
Commanding General Aberdeen Proving Ground, Md. Attn: Tech. Information Branch	2	Langley Research Center Hampton, Virginia Attn: Theoretical Aero- dynamics Division	1
Attn: Director, Ballistic Research Laboratories	2	Attn: Librarian	2
National Aeronautics and Space Agency Geo. C. Marshall Space Flight Center Huntsville, Alabama Attn: M-SandS-PT (Mr. H. A. Connell)	3	Attn: Adolf Busemann	1
ASTIA Arlington Hall Arlington, Va.	10	Attn: John Stack	2
Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: DLI-3	4	National Aeronautics and Space Agency 1512 H Street, N. W. Washington 25, D. C. Attn: B. A. Mulcahy, Chief Div. of Research Information	
Attn: RR-14	1	Ames Research Center Moffett Field, California Attn: Librarian	
Attn: RMMS	1	NASA Flight Research Center Edwards, California Attn: Mr. W. C. Williams	
Attn: RRRE	1	Lewis Research Center 21000 Brookpark Road Cleveland, 11, Ohio Attn: Librarian	
Attn: RRMA	1	Attn: Chief, Supersonic Propulsion Div.	
Attn: RMGA	1	Commander, Pacific Missile Range Point Mugu, California Attn: Technical Library	2
Commanding Officer and Director David Taylor Model Basin Aerodynamics Laboratory Washington 7, D. C. Attn: Library		National Bureau of Standards Washington 25, D. C. Attn: Applied Math. Div.	
Commanding Officer and Director David Taylor Model Basin Applied Mathematics Laboratory Washington 7, D. C. Attn: Dr. H. Polachek Attn: Dr. D. Shanks		Commanding Officer and Director David Taylor Model Basin Applied Mathematics Laboratory Washington 7, D. C. Attn: Dr. Betty Cuthill Attn: Dr. Charles W. Dawson	
Commanding Officer Diamond Ordnance Fuse Laboratory Washington 25, D. C. Attn: Library, Bldg. 92, Rm.211			
Los Alamos Scientific Laboratory University of California P. O. Box 1663 Los Alamos, New Mexico Attn: Dr. Burton Wendroff			

NOLTR 63-8

EXTERNAL DISTRIBUTION LIST (M1)

	Copies		Copies
Commander U. S. Naval Ordnance Test Station China Lake, California Attn: Technical Library Attn: Code 406 Attn: Code 507 Attn: Code 5019		The Avco Manufacturing Corp., Research Laboratories 2385 Revere Beach Pkwy Everett 49, Massachusetts	
Commander U. S. Naval Weapons Laboratory Dahlgren, Virginia Attn: Technical Library	2	CONVAIR Corporation A Division of General Dynamics Corp., Daingerfield, Texas.	
Commanding Officer ONR Branch Office Box 39, Navy 100 Fleet Post Office New York, New York		Cornell Aeronautical Lab. Inc., P. O. Box 235, 4455 Genessee St., Buffalo 21, New York Attn: Librarian	
Office of Naval Research T-3 Building, Room 2715 Washington 25, D. C. Attn: Head, Mechanics Branch Attn: Dr. J. Weyl		Douglas Aircraft Company Santa Monica Division 3000 Ocean Park Blvd., Santa Monica, California Attn: Chief Engineer	
Naval Research Laboratory Washington 25, D. C. Attn: Dr. H. M. Trent, Code 6230 Attn: Code 2027		Navy Ordnance Division Eastman Kodak Company 50 West Main Street Rochester 14, New York Attn: Mr. W. B. Forman	2
Commander Aeronautical Systems Division Air Force Systems Command Wright-Patterson AF Base, Ohio Attn: WCOSI-3	2	Missile and Ordnance Systems Dept., General Electric Co., 3198 Chestnut Street Philadelphia 4, Pennsylvania Attn: L. Chasen, Mgr. Library	2
Oak Ridge National Laboratory Oak Ridge, Tennessee Attn: Dr. A. S. Householder		Mathematics Research Center U. S. Army University of Wisconsin Madison, Wisconsin Attn: Prof. R.E. Langer Attn: Dr. Donald Greenspan	
AER, Inc., 871 E. Washington Street Pasadena, California Attn: Dr. A.J.A. Morgan		Courant Institute of Mathematical Sciences New York University New York 3, New York Attn: Prof. Peter D. Lax Attn: Prof. Eugene Isaacson Attn: Prof. R. D. Richtmyer	
Allied Research Associates, Inc., 43 Leon Street Boston 15, Massachusetts Attn: Miss Joyce Larkin			

NOLTR 63-8

EXTERNAL DISTRIBUTION LIST (MI)

<u>No. of Copies</u>		<u>No. of Copies</u>	
	Guggenheim Aeronautical Laboratory California Institute of Technology Pasadena 4, California	1	Case Institute of Technology Cleveland 6, Ohio Attn: G. Kuerti
1	Attn: Aeronautics Library		Cornell University Graduate School of Aero. Eng. Ithaca, New York
	Hughes Aircraft Co. Florence Avenue at Teale Street Culver City, California	1	Attn: Prof. W. R. Sears
1	Attn: Mr. Dana H. Johnson R & D Tech Library		Applied Physics Laboratory Johns Hopkins University 8621 Georgia Avenue Silver Spring, Maryland
	McDonnell Aircraft Corp. P. O. Box 516 St. Louis 3, Missouri	2	Attn: Technical Reports Group
1	Attn: Engineering Library, Dept. 644		The Johns Hopkins University Charles and 34th Streets Baltimore 18, Maryland
	United Aircraft Corporation 400 Main Street East Hartford 8, Connecticut	1	Attn: Dr. Francis H. Clauser
1	Attn: Chief Librarian		Mathematics Department Harvard University Cambridge 39, Massachusetts
	Superintendent U. S. Naval Postgraduate School Monterey, California	1	Attn: Prof. G. Birkhoff
1	Attn: Library, Technical Reports Section	2	Director Institute for Fluid Dynamics and Applied Mathematics University of Maryland College Park, Maryland
	University of California Berkeley 4, California		Massachusetts Institute of Tech. Cambridge 39, Massachusetts
1	Attn: Dr. S. A. Schaaf	1	Attn: Prof. Joseph Kaye, Room 1-212
	University of California Los Angeles 24, California		University of Michigan Randall Laboratory Ann Arbor, Michigan
1	Attn: Dr. G. E. Forsythe	1	Attn: Prof. Otto Laporte
	California Institute of Technology Pasadena 4, California		Supervisor Technical Documents Services Willow Run Laboratories University of Michigan Willow Run Airport Ypsilanti, Michigan
1	Attn: Aeronautics Department		
	Jet Propulsion Laboratory California Institute of Technology Pasadena 4, California		
1	Attn: Library		

NOLTR 63-8

EXTERNAL DISTRIBUTION LIST (M1)

No. of
Copies

1	University of Minnesota Minneapolis 14, Minnesota Attn: Mechanical Eng. Dept.
1	The Ohio State University Research Foundation Columbus 10, Ohio Attn: Security Officer, Carlos Brewer
1	Attn: Dr. Paul M. Pepper
1	Applied Math. & Statistics Lab. Stanford University Stanford, California
1	Defense Research Laboratory The University of Texas P. O. Box 8092 Austin 12, Texas Attn: H. D. Krick, Asst. Director
1	Department of Civil Engineering Colorado State University Fort Collins, Colorado Attn: Professor J. E. Cermak
1	Applied Physics Laboratory Johns Hopkins University 8621 Georgia Avenue Silver Spring, Maryland Attn: Dr. N. H. Choksy
1	General Electric Company Missile and Space Division 3198 Chestnut Street Philadelphia, Pa. Attn: Mr. Jerome Persh
1	University of Michigan Serials and Documents Section Ann Arbor, Michigan

CATALOGING INFORMATION FOR LIBRARY USE

BIBLIOGRAPHIC INFORMATION

	DESCRIPTORS	CODES	SECURITY CLASSIFICATION AND CODE COUNT	DESCRIPTORS	CODES
SOURCE	NOL technical report	NOLTR		Unclassified - 30	U030
REPORT NUMBER	63-8	630008	CIRCULATION LIMITATION		
REPORT DATE	8 April 1963	0463	CIRCULATION LIMITATION OR BIBLIOGRAPHIC		
			BIBLIOGRAPHIC (SUPPL., VOL., ETC.)		

SUBJECT ANALYSIS OF REPORT

DESCRIPTORS	CODES	DESCRIPTORS	CODES	DESCRIPTORS	CODES
Calculating	COMA	Accuracy	ACUR	Programmed	PROR
Solutions	SOLG	Method	METD	IBM	IBMA
Equation	EQUA	Mesh	MESH	Computer	COMP
Shock waves	SHWV	Size	SIZE	704	0704
Comparison	CMRI	Fluid	FLUI	Shock	SHOC
Numerical	NUMB	Dynamics	DYNA	Explosion	EXPS
Schemes	FLAG	Lax	LAXZ		
Non-linear	NONI	Difference equation	DIES		
Partial	PARI	Viscosity	VISC		
Differential	DIFE	Wendroff	WEND		
Rarefaction wave	RRFC	Artificial	SYNT		
Cost	COST	Convergence	CNVC		

Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-8) A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS (U), by A. Douglass, 8 April 1963. 30p. tables. (Mathematics Dept. report M-33) NOL task FR-30. UNCLASSIFIED In a simple problem with shocks and rarefactions for the equation $u_t + \left(\frac{1}{2}u^2 + u\right)x = 0,$ six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.	1. Fluid dynamics Equations 2. Non-linear equations I. Title II. Douglass, Avron III. Series IV. Project Abstract card is unclassified.	Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-8) A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS (U), by A. Douglass, 8 April 1963. 30p. tables. (Mathematics Dept. report M-33) NOL task FR-30. UNCLASSIFIED In a simple problem with shocks and rarefactions for the equation $u_t + \left(\frac{1}{2}u^2 + u\right)x = 0,$ six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.	1. Fluid dynamics Equations 2. Non-linear equations I. Title II. Douglass, Avron III. Series IV. Project Abstract card is unclassified.	Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-8) A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS (U), by A. Douglass, 8 April 1963. 30p. tables. (Mathematics Dept. report M-33) NOL task FR-30. UNCLASSIFIED In a simple problem with shocks and rarefactions for the equation $u_t + \left(\frac{1}{2}u^2 + u\right)x = 0,$ six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.	1. Fluid dynamics Equations 2. Non-linear equations I. Title II. Douglass, Avron III. Series IV. Project Abstract card is unclassified.
Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-8) A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS (U), by A. Douglass, 8 April 1963. 30p. tables. (Mathematics Dept. report M-33) NOL task FR-30. UNCLASSIFIED In a simple problem with shocks and rarefactions for the equation $u_t + \left(\frac{1}{2}u^2 + u\right)x = 0,$ six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.	1. Fluid dynamics Equations 2. Non-linear equations I. Title II. Douglass, Avron III. Series IV. Project Abstract card is unclassified.	Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-8) A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS (U), by A. Douglass, 8 April 1963. 30p. tables. (Mathematics Dept. report M-33) NOL task FR-30. UNCLASSIFIED In a simple problem with shocks and rarefactions for the equation $u_t + \left(\frac{1}{2}u^2 + u\right)x = 0,$ six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.	1. Fluid dynamics Equations 2. Non-linear equations I. Title II. Douglass, Avron III. Series IV. Project Abstract card is unclassified.	Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 63-8) A COMPARISON OF NUMERICAL SCHEMES TO CALCULATE THE SOLUTIONS OF A NON-LINEAR PARTIAL DIFFERENTIAL EQUATION WITH SHOCKS (U), by A. Douglass, 8 April 1963. 30p. tables. (Mathematics Dept. report M-33) NOL task FR-30. UNCLASSIFIED In a simple problem with shocks and rarefactions for the equation $u_t + \left(\frac{1}{2}u^2 + u\right)x = 0,$ six alternative calculation procedures have been tested as to cost and accuracy. Best results were given by the least elaborate method with the finest mesh and by the most elaborate method with the coarsest mesh.	1. Fluid dynamics Equations 2. Non-linear equations I. Title II. Douglass, Avron III. Series IV. Project Abstract card is unclassified.