

CATALOGED BY DDC
AS AD NO. 109599

63-4-2

Office of Naval Research


Contract Nonr 1886 (02)

Technical Report No. 15

UNSYMMETRICAL BUCKLING
OF THIN SHALLOW SPHERICAL SHELLS

By

Nai - Chien Huang



Division of Engineering and Applied Physics
Harvard University
Cambridge, Massachusetts

March - 1963

409 599

OFFICE OF NAVAL RESEARCH

Contract Nonr 1866(02)

Technical Report No. 15

UNSYMMETRICAL BUCKLING OF THIN SHALLOW SPHERICAL SHELLS

by

Nai-Chien Huang

Division of Engineering and Applied Physics
Harvard University
Cambridge, Mass.

March 1963

Reproduction in whole or in part
is permitted for any purpose of
the United States Government

UNSYMMETRICAL BUCKLING OF THIN SHALLOW SPHERICAL SHELLS*

by

Nai-Chien Huang

INTRODUCTION

This paper is concerned with the theoretical study of buckling of clamped shallow spherical shells under uniform external pressure (Figure 1). For sufficiently large deflection, deformations of such shells are not proportional to the applied pressure. The shell deforms axisymmetrically under sufficiently low pressure and if we assume that the deflection remains axisymmetrical, the pressure-deflection relation may be represented by a curve such as OAB in Figure 2. At the maximum pressure q_{cr} , the shell tends to jump from A to B. So q_{cr} is the buckling pressure for axisymmetrical snapping. The problem of axisymmetrical snapping has been solved by different numerical methods in References (1-4) and the results agree with each other and are represented by the curve in Figure 3. As shown in Figure 3, the buckling pressures obtained in such a manner are too high as compared with experimental results obtained in References (5-6). Initial imperfections of the shell and unsymmetrical buckling are presumed to be the sources of this discrepancy between axisymmetrical buckling theory and experiment. Unsymmetrical deformation could conceivably start to develop at point C in Figure 2. After unsymmetrical deformation has been superimposed, the pressure-deflection curve might be represented by a branch CD or CE at C as shown. The pressure at C is defined as the critical

* This work was sponsored by the Office of Naval Research under Contract Nour 1866(02).

pressure for unsymmetrical buckling. Grigolyuk^{(7)*} applied the Galerkin method to solve the problem of unsymmetrical buckling, but no numerical results were given in his work. Gjelsvik and Bodner⁽⁸⁾ and Parmerter and Fung⁽⁹⁾ worked on this problem by the energy method and numerical calculations were carried out only for a particular unsymmetrical buckling mode. Weinitschke⁽¹⁰⁾ used a power series method to solve this problem and obtained extensive numerical results, but, as will be shown, the buckling pressures obtained in his work are in serious disagreement with the results of this paper.

BASIC EQUATIONS OF SHALLOW SPHERICAL SHELLS

A shell is called "thin" if the ratio of its thickness to the radius of curvature of its middle surface is much less than unity; and a spherical shell is called "shallow" if the ratio of its rise at the center to the base diameter is less than, say, 1/8. The middle surface of a shallow spherical shell can be represented by the paraboloid

$$z = H[1 - (\frac{r}{a})^2] \quad (1)$$

where H is the rise of the middle surface at the center and a is the base radius, as shown in Figure 1. The radius of curvature of the shell is

$$R = \frac{a^2}{2H} \quad (2)$$

The stress resultants and bending moments per unit length of the shell are shown in Figure 4, where N_r , N_θ and $N_{r\theta}$ are membrane forces respectively;

* Numbers in the raised parenthesis refer to the references at the end of this report.

Q_r and Q_θ are transverse shears and M_r , M_θ and $M_{r\theta}$ are meridional, circumferential and twisting moments respectively. Let U , V and W be the horizontal radial, horizontal tangential and vertical components of displacement respectively (Fig. 4) and let q be the external pressure which can be considered to be vertical.

In the following equations, we use the notations

$$(\)' = \frac{\partial}{\partial r}(\) \quad \text{and} \quad (\dot{\ }) = \frac{\partial}{\partial \theta}(\)$$

Equilibrium of moments requires

$$(rM_r)' + \dot{M}_{r\theta} - M_\theta - rQ_r = 0 \quad (3)$$

$$(rM_{r\theta})' + \dot{M}_\theta + M_{r\theta} - rQ_\theta = 0 \quad (4)$$

Equilibrium of stress resultants requires

$$(rN_r)' + \dot{N}_{r\theta} - N_\theta = 0 \quad (5)$$

$$(rN_{r\theta})' + \dot{N}_\theta + N_{r\theta} = 0 \quad (6)$$

$$[rN_r(W-z)' + N_{r\theta}(\dot{W-z}) + (rQ_r)']' + [\frac{1}{r}N_\theta(\dot{W-z}) + N_{r\theta}(W-z)' + Q_\theta] + rq = 0 \quad (7)$$

Note that nonlinearity has been introduced in Eq. (7) by considering the influence of W .

The stress strain relations are

$$\epsilon_r = \frac{1}{tE}(N_r - \nu N_\theta) \quad (8)$$

$$\epsilon_\theta = \frac{1}{tE}(N_\theta - \nu N_r) \quad (9)$$

$$\gamma_{r\theta} = \frac{2(1+\nu)}{tE} N_{r\theta} \quad (10)$$

$$M_r = D(\kappa_r + \nu \kappa_\theta) \quad (11)$$

$$M_{\theta} = D(\kappa_{\theta} + \nu \kappa_r) \quad (12)$$

$$M_{r\theta} = (1-\nu)D \kappa_{r\theta} \quad (13)$$

where E and ν are the elastic modulus and Poisson's ratio respectively; t stands for the thickness of the shell and $D = \frac{Et^3}{12(1-\nu^2)}$.

The strain displacement relations are also nonlinear

$$\epsilon_r = U' - z'W' + \frac{1}{2}(W')^2 \quad (14)$$

$$\epsilon_{\theta} = \frac{1}{r}U + \frac{1}{r}\dot{V} - \frac{1}{r^2}\dot{z}\dot{W} + \frac{1}{2}\left(\frac{1}{r}\dot{W}\right)^2 \quad (15)$$

$$\gamma_{r\theta} = \frac{1}{r}\dot{U} - \frac{1}{r}V + V' - \frac{1}{r}\dot{z}W' - \frac{1}{r}z'\dot{W} + \frac{1}{r}\dot{W}W' \quad (16)$$

$$\kappa_r = -W'' \quad (17)$$

$$\kappa_{\theta} = -\frac{1}{r^2}\ddot{W} - \frac{1}{r}W' \quad (18)$$

$$\kappa_{r\theta} = -\left(\frac{1}{r}\dot{W}\right)' \quad (19)$$

Equations (5) and (6) can be satisfied by setting

$$N_r = \frac{1}{r}F' + \frac{1}{r^2}\ddot{F} \quad (20)$$

$$N_{\theta} = F'' \quad (21)$$

$$N_{r\theta} = -\left(\frac{1}{r}\dot{F}\right)' \quad (22)$$

where F is a stress function.

Eliminating the transverse shears Q_r and Q_{θ} from Eqs. (3), (4) and (7), we have

$$\begin{aligned} &[(rM_r)' + \dot{M}_{r\theta} - M_{\theta}]' + \frac{1}{r}[(rM_{r\theta})' + \dot{M}_{\theta} + M_{r\theta}] + rN_r(W-z)'' + N_{\theta}\left[\frac{1}{r}(W-z)'' + (W-z)'\right] \\ &+ 2N_{r\theta}\left[(W-z)' - \frac{1}{r}(W-z)\right] + q_r = 0 \end{aligned} \quad (23)$$

Then the equation of equilibrium obtained by direct substitution is

$$\begin{aligned} D\nabla^2 \nabla^2 W = & \left(\frac{1}{r} F' + \frac{1}{2} \ddot{F} \right) (W-z)'' + \frac{1}{2} F'' (\ddot{W}-z) + \frac{1}{r} F'' (W-z)' \\ & + 2 \left(\frac{1}{r} \dot{F}' - \frac{1}{2} \dot{F} \right) \left(\frac{1}{r} \dot{z}' - \frac{1}{r} \dot{W}' - \frac{1}{2} \dot{z} + \frac{1}{2} \dot{W} \right) + q \end{aligned} \quad (24)$$

$$\text{where } \nabla^2 () = ()'' + \frac{1}{r} ()' + \frac{1}{2} \ddot{()} .$$

Using Eqs. (8)-(10) and (20)-(22), we can show that

$$\frac{1}{r} (r e_\theta)'' - \frac{1}{r} e_r' - \frac{1}{r^2} (r \dot{\gamma}_{r\theta})' + \frac{1}{r^2} \ddot{e}_r = \frac{1}{Et} \nabla^2 (N_r + N_\theta) = \frac{1}{Et} \nabla^4 F \quad (25)$$

Substituting Eqs. (14)-(16) into the left hand side, we get another fundamental equation involving F and w

$$\begin{aligned} \nabla^4 F = Et \left\{ -2 \left(\frac{1}{r} \dot{z}' - \frac{1}{2} \dot{z} \right) \left(\frac{1}{r} \dot{W}' - \frac{1}{2} \dot{W} \right) + z'' \left(\frac{1}{r} W' + \frac{1}{2} \ddot{W} \right) + W'' \left(\frac{1}{r} z' + \frac{1}{2} \ddot{z} \right) \right. \\ \left. + \left(\frac{1}{r} \dot{W}' - \frac{1}{2} \dot{W} \right)^2 - W'' \left(\frac{1}{r} W' + \frac{1}{2} \ddot{W} \right) \right\} \end{aligned} \quad (26)$$

which is the compatibility equation of shallow spherical shells.

Substituting Eq. (1) into Eqs. (24) and (26), we get Marguere's nonlinear differential equations⁽¹¹⁾ in polar coordinates for shallow spherical shells under uniform pressure,

$$D\nabla^4 W = \frac{1}{R} \nabla^2 F + \left(\frac{1}{r} F' + \frac{1}{2} \ddot{F} \right) W'' + \left(\frac{1}{r} W' + \frac{1}{2} \ddot{W} \right) F'' - 2 \left(\frac{1}{r} \dot{F}' - \frac{1}{2} \dot{F} \right) \left(\frac{1}{r} \dot{W}' - \frac{1}{2} \dot{W} \right) + q \quad (27)$$

$$\nabla^4 F = Et \left[-\frac{1}{R} \nabla^2 W + \left(\frac{1}{r} \dot{W}' - \frac{1}{2} \dot{W} \right)^2 - \left(\frac{1}{r} W' + \frac{1}{2} \ddot{W} \right) W'' \right] \quad (28)$$

Let us introduce the following nondimensional quantities:

$$\lambda = 2[3(1-\nu^2)]^{1/4} (H/t)^{1/2}$$

$$x = \frac{\lambda}{a} r$$

$$w = \frac{\lambda^2}{2H} W$$

$$\psi = \frac{\lambda^4}{4EH^2 t} F$$

$$p = \frac{q}{q_0}$$

where $q_0 = \frac{32EH^3 t}{\lambda^2 a^4}$ is the classical buckling pressure of a complete spherical shell of the same radius of curvature and thickness. Then the nondimensional forms of Eqs. (27) and (28) are

$$\nabla^4 w = \nabla^2 \psi + \left(\frac{1}{x} \psi' + \frac{1}{x^2} \ddot{\psi}\right) w'' + \left(\frac{1}{x} w' + \frac{1}{x^2} \ddot{w}\right) \psi'' - 2\left(\frac{1}{x} \dot{\psi}' - \frac{1}{x^2} \dot{\psi}\right) \left(\frac{1}{x} \dot{w}' - \frac{1}{x^2} \dot{w}\right) + 4p \quad (29)$$

$$\nabla^4 \psi = -\nabla^2 w + \left(\frac{1}{x} \dot{w}' - \frac{1}{x^2} \dot{w}\right)^2 - \left(\frac{1}{x} w' + \frac{1}{x^2} \ddot{w}\right) w'' \quad (30)$$

where $(\)' = \frac{\partial}{\partial x}(\)$ and $\nabla^2(\) = \left(\frac{\partial^2}{\partial x^2} + \frac{1}{x} \frac{\partial}{\partial x} + \frac{1}{x^2} \frac{\partial^2}{\partial \theta^2}\right)(\)$.

The edge of the shell is completely clamped; therefore, on the boundary $r = a$, we have

$$W = 0 \quad (31)$$

$$W' = 0 \quad (32)$$

$$U = 0 \quad (33)$$

$$V = 0 \quad (34)$$

From the last two boundary conditions, we can show by the strain displacement relations that

$$\epsilon_\theta = 0 \quad (35)$$

$$a\epsilon_\theta' - \epsilon_r - \dot{\gamma}_{r\theta} = 0 \quad (36)$$

on the boundary $r = a$.

Expressed in terms of the stress function, these equations become

$$F'' - \frac{\nu}{a} F' - \frac{\nu}{a^2} \ddot{F} = 0 \quad (37)$$

$$a(F'' - \frac{\nu}{r} F' - \frac{\nu}{r^2} \ddot{F})' - \frac{1}{a} F' - \frac{1}{a^2} \ddot{F} + \nu F'' + 2(1+\nu)(\frac{1}{r} \ddot{F})' = 0 \quad (38)$$

on $r = a$.

The nondimensional forms of Eqs. (31), (32), (33) and (34) are

$$w = 0 \quad (39)$$

$$w' = 0 \quad (40)$$

$$\Psi'' - \frac{\nu}{\lambda} \Psi' - \frac{\nu}{\lambda^2} \ddot{\Psi} = 0 \quad (41)$$

$$\lambda(\Psi'' - \frac{\nu}{x} \Psi' - \frac{\nu}{x^2} \ddot{\Psi})' - \frac{1}{\lambda} \Psi' - \frac{1}{\lambda^2} \ddot{\Psi} + \nu \Psi'' + 2(1+\nu)(\frac{1}{x} \ddot{\Psi})' = 0 \quad (42)$$

on $x = \lambda$.

In addition, at the center of the shell, w and Ψ must fulfil the requirement of finite stresses.

GOVERNING EQUATIONS FOR BUCKLING OF CLAMPED SHALLOW SPHERICAL SHELLS

As mentioned before, the shell necessarily deforms axisymmetrically only under sufficiently low pressure. The pressure might reach a critical limit (point C in Fig. 2) such that the shell bifurcates from an axisymmetrical deformation path to one of unsymmetrical deformation.

Just after bifurcation, the functions w and Ψ can be written as

$$w = \omega^*(x) + \omega(x, \theta) \quad (43)$$

$$\Psi = \psi^*(x) + \psi(x, \theta) \quad (44)$$

where $\omega^*(x)$ and $\psi^*(x)$ are the nondimensional vertical deflection and the

nondimensional stress function just before buckling and hence are axisymmetrical; $\omega(x, \theta)$ and $\psi(x, \theta)$ are due to unsymmetrical buckling and these are considered to be infinitesimally small at the beginning of unsymmetrical buckling. From Eqs. (29) and (30), we have

$$\nabla^4 \omega^* = \nabla^2 \psi^* + \frac{1}{x} \psi^{*'} \omega^{*''} + \frac{1}{x} \psi^{*''} \omega^{*'} + 4p \quad (45)$$

$$\nabla^4 \psi^* = -\nabla^2 \omega^* - \frac{1}{x} \omega^{*'} \psi^{*''} \quad (46)$$

Put $\theta^* = -\omega^{*'}$ and $\xi^* = \psi^{*'}$, Eqs. (45) and (46) can be written, after one integration, as

$$(x\theta^{*'}) - \frac{\theta^*}{x} + x\xi^* = -2px^2 + \theta^*\xi^* \quad (47)$$

$$(x\xi^{*'})' - \frac{\xi^*}{x} - x\theta^* = -\frac{1}{2} \theta^{*2} \quad (48)$$

Also, the boundary conditions can be reduced to

$$\theta^*(\lambda) = 0 \quad (49)$$

$$\lambda \xi^{*'}(\lambda) - \nu \xi^*(\lambda) = 0 \quad (50)$$

These are the governing equations of the symmetrical problem which has been solved numerically in References 1-4.

Substituting Eqs. (43) and (44) into Eqs. (29) and (30) and using Eqs. (45) and (46), we obtain

$$\nabla^4 \omega = \nabla^2 \psi - \left(\frac{1}{x} \psi' + \frac{1}{2} \ddot{\psi}\right) \theta^{*'} + \frac{1}{x} \omega' \xi^* - \frac{1}{x} \psi'' \theta^{*'} + \left(\frac{1}{x} \omega' + \frac{1}{2} \ddot{\omega}\right) \xi^{*'} \quad (51)$$

$$\nabla^4 \psi = -\nabla^2 \omega + \left(\frac{1}{x} \omega' + \frac{1}{2} \ddot{\omega}\right) \theta^{*'} + \frac{1}{x} \omega'' \theta^* \quad (52)$$

where only the linear terms in ω and ψ have been retained. These are two linear differential equations for the functions ω and ψ . Hence our problem has been reduced to an eigenvalue problem where the eigenvalue p is implicit and involved in the solution θ^* and ξ^* of the nonlinear problem as defined

by Eqs. (47)-(50).

Let

$$\omega(x, \theta) = \sum_{n=0}^{\infty} \omega_n(x) \cos n\theta \quad (53)$$

$$\psi(x, \theta) = \sum_{n=0}^{\infty} \psi_n(x) \cos n\theta \quad (54)$$

$$L_n(\) = \left(\frac{d^2}{dx^2} + \frac{1}{x} \frac{d}{dx} - \frac{n^2}{x^2} \right) (\) ; \quad L_n^2(\) = L_n L_n(\)$$

Substituting Eqs. (53) and (54) into (51) and (52), we have, for each n ,

$$L_n^2 \omega_n = L_n \psi_n - \left(\frac{1}{x} \psi_n' - \frac{n^2}{x^2} \psi_n \right) \theta^{*'} + \frac{1}{x} \omega_n'' \theta^{*} - \frac{1}{x} \psi_n'' \theta^{*'} + \left(\frac{1}{x} \omega_n' - \frac{n^2}{x^2} \omega_n \right) \theta^{*'} \quad (55)$$

$$L_n^2 \psi_n = -L_n \omega_n + \left(\frac{1}{x} \omega_n' - \frac{n^2}{x^2} \omega_n \right) \theta^{*'} + \frac{1}{x} \omega_n'' \theta^{*} \quad (56)$$

The boundary conditions can be derived from Eqs. (39)-(42). These are

$$\omega_n(\lambda) = 0 \quad (57)$$

$$\omega_n'(\lambda) = 0 \quad (58)$$

$$\psi_n''(\lambda) - \frac{\nu}{\lambda} \psi_n'(\lambda) + \frac{n^2 \nu}{\lambda^2} \psi_n(\lambda) = 0 \quad (59)$$

$$\lambda \psi_n'''(\lambda) - \frac{1}{\lambda} [1 - \nu + (2+\nu)n^2] \psi_n'(\lambda) + \frac{3n^2}{\lambda^2} \psi_n(\lambda) = 0 \quad (60)$$

Equations (55)-(60) are the governing differential equations and the boundary conditions of the problem of unsymmetrical buckling of clamped shallow spherical shells. Existence of a solution for any integer n at a pressure less than the critical pressure of axisymmetrical snapping implies existence of a critical pressure for unsymmetrical buckling.

SOME PRELIMINARY STUDIES

Modified Problems

Before the main problem was treated, it was considered advisable to study some problems of unsymmetrical buckling of shells with modified boundary conditions for which the solutions can be obtained analytically. The purpose of this study is to find whether unsymmetrical buckling rather than axisymmetrical snapping would control in these modified problems. The answers for the critical pressure for unsymmetrical buckling obtained here can be also used to check the accuracy of the numerical procedures for the main problem.

In the first modified problem the edge of the shell is supported by rollers which can slide along a conical wall without changing the slope along the edge of the shell as shown in Figure 5. In the second modified problem the edge condition is the same as that in the first modified problem except that the edge is imagined to be suddenly clamped just before buckling occurs. In both modified problems the shell contracts uniformly before buckling and therefore, $\theta^* = 0$ and $\phi^* = -2px$.

The critical pressures for these modified problems are calculated for $n = 0, 1, 2$ and 3 in Appendix A and are plotted against λ in Figures 5 and 6, where n is the number of waves along the circumferential direction in the buckling mode. In both modified problems it is found that unsymmetrical buckling ($n \neq 0$) dominates for some values of λ . These calculated critical pressures are higher than the classical buckling pressure of a complete spherical shell. In the first modified problem the calculated critical pressures meet the classical buckling pressure periodically at certain values of λ and in the second modified problem the calculated critical pressure approaches the classical

buckling pressure asymptotically when λ approach infinity. In both problems the results are not realistic because of initial imperfections.

Approximation by Variational Principle

A variational principle is developed in Appendix B for a preliminary study of the critical pressure of unsymmetrical buckling of clamped shallow spherical shells. The boundary conditions (57) and (58) of the main problem were specified in the application of this principle. The differential equations (55) and (56) are the Euler's equations and the boundary conditions (59) and (60) are the natural boundary conditions of this variational principle. A Rayleigh-Ritz method is used in conjunction with the variational principle in Appendix B and numerical results have been obtained for $\lambda = 6$ as shown in Table 1. These critical pressures for unsymmetrical buckling are lower than the critical pressure for axisymmetrical snapping, and this certainly tends to confirm the suspicion that unsymmetrical buckling does occur for clamped shallow spherical shells. However, the numerical results obtained by this variational principle are not necessarily either upper bounds or lower bounds to the exact critical pressure for unsymmetrical buckling.

NUMERICAL SOLUTION

Difference Equations

The most popular practical method to solve differential equations is to reduce them to difference equations by confining the range of the independent variables to a network of mesh points. In this problem we define

$$x = jh \quad j = 0, 1, \dots, N = \lambda/h$$

where h is the mesh size.

Let $\omega_j = \omega_n(jh)$; $\psi_j = \psi_n(jh)$; $\theta_j^* = \theta^*(jh)$ and $\phi_j^* = \phi^*(jh)$. Using

$$u_j = \omega_j'' \quad (61)$$

$$v_j = \psi_j'' \quad (62)$$

The differential equations (55) and (56) at $j = 1, 2, \dots, N$ can be written as

$$\begin{aligned} u_j'' + \frac{2}{x} u_j' - \frac{1+2n^2}{x^2} u_j + \frac{1+2n^2}{x^3} \omega_j' - \frac{4n^2-n^4}{x^4} \omega_j = v_j + \frac{1}{x} \psi_j' - \frac{n^2}{x^2} \psi_j - \left(\frac{1}{x} \psi_j' - \frac{n^2}{x^2} \psi_j \right) \theta_j^* \\ + \frac{1}{x} u_j \phi_j^* - \frac{1}{x} v_j \theta_j^* + \left(\frac{1}{x} \omega_j' - \frac{n^2}{x^2} \omega_j \right) \phi_j^* \quad j = 1, 2, \dots, N \end{aligned} \quad (63)$$

$$\begin{aligned} v_j'' + \frac{2}{x} v_j' - \frac{1+2n^2}{x^2} v_j + \frac{1+2n^2}{x^3} \psi_j' - \frac{4n^2-n^4}{x^4} \psi_j = -u_j - \frac{1}{x} \omega_j' + \frac{n^2}{x^2} \omega_j + \left(\frac{1}{x} \omega_j' - \frac{n^2}{x^2} \omega_j \right) \theta_j^* \\ + \frac{1}{x} u_j \theta_j^* \quad j = 1, 2, \dots, N \end{aligned} \quad (64)$$

The boundary conditions (57)-(60) can be written as

$$\omega_N = 0 \quad (65)$$

$$\omega_N' = 0 \quad (66)$$

$$v_N - \frac{\nu}{\lambda} \psi_N' + \frac{n^2 \nu}{\lambda^2} \psi_N = 0 \quad (67)$$

$$\lambda v_N' - \frac{1}{\lambda} [1 - \nu + (2+\nu)n^2] \psi_N' + \frac{3n^2}{\lambda^2} \psi_N = 0 \quad (68)$$

We shall use the following finite difference approximations for the first and second derivatives:

$$f_j' = \frac{1}{2h} (-f_{j-1} + f_{j+1}) \quad (69)$$

$$f_j'' = \frac{1}{h^2} (f_{j-1} - 2f_j + f_{j+1}) \quad (70)$$

The error of these approximations are $O(h^2)$. Equations (61)-(64) can be

written as

$$A_j y_{j+1} + B_j y_j + C_j y_{j-1} = 0 \quad j = 1, 2, \dots, N \quad (71)$$

where one fictitious station $j = N+1$ has been added off the edge of the shell for convenience. Equations (65)-(68) can be written as

$$G y_{N+1} + K y_N - G y_{N-1} = 0 \quad (72)$$

where

$$y_j = \begin{bmatrix} \omega_j \\ \psi_j \\ u_j \\ v_j \end{bmatrix} \quad (73)$$

$$A_j = \begin{bmatrix} -1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ \frac{1+2n^2}{2j^3} - \frac{h^2}{2j} \theta_j^{*'} & -\frac{h^2}{2j} (1-\theta_j^{*'}) & h^2(1+\frac{1}{j}) & 0 \\ \frac{h^2}{2j} (1-\theta_j^{*'}) & \frac{1+2n^2}{2j^3} & 0 & h^2(1+\frac{1}{j}) \end{bmatrix} \quad (74)$$

$$B_j = \begin{bmatrix} 2 & 0 & h^2 & 0 \\ 0 & 2 & 0 & h^2 \\ -\frac{4n^2-n^4}{j^4} + \frac{h^2 n^2}{j^2} \theta_j^{*'} & \frac{h^2 n^2}{j^2} (1-\theta_j^{*'}) & -h^2(2+\frac{1+2n^2}{j^2} + \frac{1}{j} \theta_j^{*'}) & -h^3(h-\frac{1}{j} \theta_j^{*'}) \\ -\frac{h^2 n^2}{j^2} (1-\theta_j^{*'}) & -\frac{4n^2-n^4}{j^4} & h^3(h-\frac{1}{j} \theta_j^{*'}) & -h^2(2+\frac{1+2n^2}{j^2}) \end{bmatrix} \quad (75)$$

$$C_j = \begin{bmatrix} -1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ -\frac{1+2n^2}{2j^3} + \frac{h^2}{2j} \theta_j^{*'} & \frac{h^2}{2j} (1-\theta_j^{*'}) & h^2(1-\frac{1}{j}) & 0 \\ -\frac{h^2}{2j} (1-\theta_j^{*'}) & -\frac{1+2n^2}{2j^3} & 0 & h^2(1-\frac{1}{j}) \end{bmatrix} \quad (76)$$

$$G = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & -\frac{\nu}{2h\lambda} & 0 & 0 \\ 0 & -\frac{1}{2h\lambda} [1 - \nu + (2+\nu)n^2] & 0 & \frac{\lambda}{2h} \end{bmatrix} \quad (77)$$

and

$$K = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & \frac{n^2 \nu}{\lambda^2} & 0 & 1 \\ 0 & \frac{3n^2}{\lambda^2} & 0 & 0 \end{bmatrix} \quad (78)$$

From the conditions that all components of stress resultant and moment are bounded at the center of shell, it can be shown that, near $x = 0$ $\omega_n \sim x^n$ and $\psi_n \sim x^n$. Therefore $C_1 y_0 = 0$, and the first equation of (71) will simply be

$$A_1 y_2 + B_1 y_1 = 0 \quad (79)$$

Determination of Buckling Pressure

Let

$$y_j = Q_j y_{j+1} \quad (80)$$

then

$$y_{j-1} = Q_{j-1} y_j \quad (81)$$

Substituting Eq. (81) into Eq. (71), we get

$$y_j = -(B_j + C_j Q_{j-1})^{-1} A_j y_{j+1}$$

or

$$Q_j = -(B_j + C_j Q_{j-1})^{-1} A_j \quad (82)$$

From Eq. (79)

$$Q_1 = -B_1^{-1}A_1 \quad (83)$$

which also can be obtained from Eq. (82) by setting

$$Q_0 = 0 \quad (84)$$

Equation (82) is a recurrence formula by which all Q 's can be evaluated.

Substituting Eq. (80) into Eq. (72), we get

$$Sy_{N+1} = 0 \quad (85)$$

where

$$S = G(I - Q_{N-1}Q_N) + KQ_N \quad (86)$$

and I is a 4×4 unit matrix. For a nontrivial solution $y_{N+1} \neq 0$,

$$|S| = 0 \quad (87)$$

which is the characteristic equation for determination of critical pressures of unsymmetrical buckling.

The case $n = 1$ is a special case where Eqs. (55)-(60) can be satisfied for all p by an exact solution $\omega_1 = 0$ and $\psi_1 = x$. Since the difference equations are exact for linear functions Eqs. (71) and (72) can be satisfied by

$$y_j = \begin{bmatrix} 0 \\ j \\ 0 \\ 0 \end{bmatrix}$$

Equation (85) can be written as

$$[S] \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix} = 0$$

for $n = 1$ and so all elements in the second column of matrix S vanish. For $n = 1$, Eq. (56) is reduced to

$$\frac{d}{dx} [x^2 \psi''' - 3\psi' + \frac{3}{x} \psi + x^2 \omega' - x\omega - (x\omega' - \omega)\theta] = 0$$

Integrating from $x = 0$ to $x = \lambda$ and using Eqs. (57) and (58), we can obtain Eq. (60). Thus, for $n = 1$, Eq. (60) is dependent and can be omitted. We have

$$[\bar{S}] \begin{bmatrix} \omega_{N+1} \\ u_{N+1} \\ v_{N+1} \end{bmatrix} = 0$$

where $\bar{S}$ is the resulting matrix obtained by striking out the second column and the fourth row of the matrix S . For a nontrivial solution,

$$|\bar{S}| = 0 \quad (88)$$

which is the characteristic equation for determination of critical pressures for unsymmetrical buckling for $n = 1$.

Numerical Procedure and Results

The numerical procedure of this problem consists of two parts. The first part is to calculate θ^* , ϕ^* and their derivatives for the axisymmetrical deformation before unsymmetrical buckling. We used the iterative method given in Reference (1)*. The Poisson's ratio ν was taken equal to 1/3 in all calculations and the interval Δx used was 0.25. The first derivatives of θ^* and ϕ^* were calculated by Eq. (69). The values of Kelvin functions and their first derivatives used were found in Reference (12).

In the second part of the calculation, the elements of matrices A_j , B_j ,

* The criterion of convergence of the iterative procedure used in this computation is that the final answer for average deflection agrees to four significant figures with the mean of the results of the five previous iterations.

C_j , G and K were calculated first for different values of n and Q_j , S and $|S|$ could be obtained. In general, $|S|$ does not vanish if the trial value of p is not the buckling pressure p_{cr} . The values of $|S|$ were plotted against p . The critical pressure is the lowest root of $|S| = 0$. When $n = 1$ $\bar{S}$ must be calculated instead of S . This procedure continued for different values of n until axisymmetrical snapping occurred before unsymmetrical buckling appeared.

Two mesh sizes, $h = 0.25$ and $h = 0.125$, were used in the calculation for $\lambda = 6$. Since the mesh size 0.25 was used in the first part of the calculation, in the computation for $h = 0.125$, the values of θ^* , ϕ^* and their first derivatives at the intermediate stations were obtained by linear interpolation. The difference of buckling pressures calculated by these two mesh sizes was about 0.1 %. Hence we use $h = 0.25$ in our calculation*.

The validity of this numerical procedure was checked by comparing solutions of the second modified problem in Appendix A (Fig. 6) with solutions obtained by this numerical method. Computations were carried out for the cases $\lambda = 6$ and $\lambda = 10$ and the maximum error in p_{cr} was 0.4 %.

All numerical calculations were made on the IBM 7090 digital computer and the programming was written in the FORTRAN language. The critical pressures for different values of λ and n are given in Table 2 and also plotted in Figure 8. The lowest value of these critical pressures at a given λ is the governing pressure for unsymmetrical buckling. These governing pressures are shown by a heavy line in Figure 7. Buckling modes were evaluated for these governing

* This choice of mesh size provides a reasonable number of stations within the boundary layer of the buckling mode.

pressures and are shown in Figure 8.

According to the results of the calculation, unsymmetrical buckling ($n \neq 0$) does not occur for $\lambda \leq 5.5$. Unsymmetrical buckling starts to appear when λ is slightly greater than 5.5. As λ keeps increasing the buckling mode shows more and more waves along the circumferential direction and also shows a distinct boundary layer near the edge of the shell along the radial direction when λ is high. An asymptotic analysis has been done in Appendix C where an asymptotic value of the critical pressure for unsymmetrical buckling is found to be 0.864 when λ approaches infinity, and the ratio n/λ is found to approach 0.817.

DISCUSSION

The shell may snap-through under the critical pressure for unsymmetrical buckling if the tangent of the branch on the pressure deflection curve has a negative slope at that critical pressure (as shown by the branch CD in Fig. 2). On the other hand, if that branch has a positive slope (as CE), deformation of the shell changes from the axisymmetrical type to the unsymmetrical type suddenly under the critical pressure but no snapping appears. The determination of the branch of pressure-deflection curve involves the analysis of the post-buckling behavior of the shell.

In Figure 9 the results of previous attempts to calculate critical pressures for buckling of shells are plotted for the purpose of comparison with the present results. Gjelsvik and Bodner⁽⁸⁾ and Parmerter and Fung⁽⁹⁾ calculated the critical pressures based on an approximate solution for the cases $n = 0$ and $n = 1$. The junctions of curves for $n = 0$ and curves for $n = 1$ in Figure 9 are represented by tick marks. Weinitschke⁽¹⁰⁾ obtained critical pressures for

an extensive range of λ and n by a method which was claimed to be accurate, but the buckling pressures obtained in his work are in serious disagreement with the present results. It is noted that, for $n = 1$ the present result is much closer to the results of References (8) and (9) than Weinitschke's result*. In References (7), (8) and (9) the curves representing critical pressures for $n = 0$ are shown to be tangent to those for $n = 1$ at their junctions. However, this tangency does not appear in the curve of present work. The present theoretical buckling pressures are still higher than the experimental results. The effects of initial unsymmetrical geometrical imperfections and variation of shell thickness are presumed to be the source of this discrepancy, but the analysis of such problem is very complicated.

* More recently, in a private communication, G. A. Thurston stated that he found a lower bound to the critical pressure $p_{cr} = 0.753$ for $n = 4$ and $\lambda = 8$, which is close to the present result $p_{cr} = 0.766$ (Table 2).

APPENDIX A

Analysis of Shells with Modified Boundary Conditions

As mentioned before, in both modified problems

$$\theta^* = 0 \quad (A1)$$

$$\delta^* = -2px \quad (A2)$$

Substituting them into Eqs. (55) and (56) one obtains

$$L_n^2 \omega_n = L_n \psi_n - 2p L_n \omega_n \quad (A3)$$

$$L_n^2 \psi_n = -L_n \omega_n \quad (A4)$$

The general solutions are expressed in terms of Bessel's functions

$$\omega_n = A_n J_n(\mu x) + B_n J_n\left(\frac{x}{\mu}\right) + C_n x^n + E_n Y_n(\mu x) + F_n Y_n\left(\frac{x}{\mu}\right) + G_n x^{-n} \quad (A5)$$

$$\psi_n = \frac{A_n}{\mu} J_n(\mu x) + B_n \mu^2 J_n\left(\frac{x}{\mu}\right) + D_n x^n + \frac{E_n}{\mu^2} Y_n(\mu x) + F_n \mu^2 Y_n\left(\frac{x}{\mu}\right) + H_n x^{-n} \quad (A6)$$

where

$$p = \frac{1}{2} \left(\mu^2 + \frac{1}{\mu^2} \right) \quad (A7)$$

All components of stress resultant and moment are bounded at the center of the shell, therefore,

$$\omega_n = A_n J_n(\mu x) + B_n J_n\left(\frac{x}{\mu}\right) + C_n x^n \quad (A8)$$

$$\psi_n = \frac{A_n}{\mu} J_n(\mu x) + B_n \mu^2 J_n\left(\frac{x}{\mu}\right) + D_n x^n \quad (A9)$$

The boundary conditions of the first modified problem are conveniently obtained from the principle of virtual work

$$\int_0^{2\pi} \int_0^a (M_r \delta \kappa_r + M_\theta \delta \kappa_\theta + M_{r\theta} \delta \kappa_{r\theta} + N_r \delta \epsilon_r + N_\theta \delta \epsilon_\theta + N_{r\theta} \delta \gamma_{r\theta} - q \delta W) r dr d\theta = 0 \quad (A10)$$

Using the strain displacement relations we get

$$\begin{aligned}
 & - \int_0^{2\pi} \int_0^a \left\{ \left[(rM_r)' + \left(\frac{\ddot{M}_\theta}{r} \right) - M_\theta' + \frac{2}{r} (\dot{r}\dot{M}_{r\theta})' - (rN_{rz})' - \left(\frac{\dot{N}_\theta \dot{z}}{r} \right) - (N_{r\theta} \dot{z})' - (\dot{N}_{r\theta} z') + qr \right] \delta W \right. \\
 & \quad + [(rN_r)' + \dot{N}_{r\theta} - N_\theta] \delta U + [(rN_{r\theta})' + \dot{N}_\theta + N_{r\theta}] \delta V \Big\} r \, dr \, d\theta \\
 & \quad + \int_0^{2\pi} \left\{ \left[(rM_r)' + 2\dot{M}_{r\theta} - M_\theta \right] \delta \zeta + \left[\frac{2H}{a} ((rM_r)' + 2\dot{M}_{r\theta} - M_\theta + 2HN_r) + aN_r \right] \delta \xi - aM_r \delta W' \right. \\
 & \quad \left. + aN_{r\theta} \delta V \right\} d\theta = 0 \quad (A11)
 \end{aligned}$$

where ζ and ξ are the displacements along the wall and perpendicular to the wall respectively, therefore,

$$\zeta = \frac{2H}{a} U - W \quad (A12)$$

$$\xi = U + \frac{2H}{a} W \quad (A13)$$

By substitution, we get the boundary conditions

$$(rM_r)' + 2\dot{M}_{r\theta} - M_\theta = 0 \quad (A14)$$

$$W' = 0 \quad (A15)$$

$$\xi = 0 \quad (A16)$$

$$N_{r\theta} = 0 \quad (A17)$$

In terms of the nondimensional quantities, these are

$$\omega_n' = 0 \quad (A18)$$

$$\lambda(L_n \omega_n)' + (1-\nu) \frac{n^2}{\lambda^2} \omega_n = 0 \quad (A19)$$

$$\lambda \psi_n' - \psi_n = 0 \quad (A20)$$

$$L_n \psi_n - \lambda(L_n \psi_n)' + (1+\nu)(n^2-1)\psi_n + \omega_n = 0 \quad (A21)$$

Substituting Eqs. (A8) and (A9) into Eqs. (A18)-(A21) and eliminating the coefficient of D_n , we have the following characteristic equation from the resulting equations

$$\begin{vmatrix} \mu\lambda J'_n(\mu\lambda) & \frac{\lambda}{\mu} J'_n\left(\frac{\lambda}{\mu}\right) & n \\ -\mu^3 \lambda^3 J'_n(\mu\lambda) + (1-\nu)n^2 J_n(\mu\lambda) & -\frac{\lambda^3}{\mu^3} J'_n\left(\frac{\lambda}{\mu}\right) + (1-\nu)n^2 J_n\left(\frac{\lambda}{\mu}\right) & (1-\nu)n^2 \\ \frac{1}{\mu\lambda} J'_n(\mu\lambda) - \frac{n}{\mu^2 \lambda^2} J_n(\mu\lambda) & \frac{\mu}{\lambda} J'_n\left(\frac{\lambda}{\mu}\right) - n \frac{\mu^2}{\lambda^2} J_n\left(\frac{\lambda}{\mu}\right) & \frac{n-1}{n+1} \frac{1}{(1+\nu)\lambda^2} \end{vmatrix} = 0 \quad (A22)$$

The case $n = 1$ is also a special case in the modified problems. However, Eq. (A22) still holds for $n = 1$.

The buckling pressures are plotted against λ for different values of n in Figure 5. The case $n = 0$ represents an axisymmetrical buckling.

The boundary conditions of the second modified problem are the same as those of the main problem. Substituting Eqs. (A8) and (A9) into Eqs. (57)-(60) and eliminating the coefficient of D_n , we get the following characteristic equation

$$\begin{vmatrix} J_n(\mu\lambda) & J_n\left(\frac{\lambda}{\mu}\right) & 1 \\ \mu\lambda J'_n(\mu\lambda) & \frac{\lambda}{\mu} J'_n\left(\frac{\lambda}{\mu}\right) & n \\ \frac{n}{\mu\lambda} J'_n(\mu\lambda) - \frac{n(1+n)}{2\mu^2 \lambda^2} J_n(\mu\lambda) & \frac{n\mu}{\lambda} J'_n\left(\frac{\lambda}{\mu}\right) - \frac{n(1+n)\mu^2}{2\lambda^2} J_n\left(\frac{\lambda}{\mu}\right) & -\frac{1}{1+\nu} \end{vmatrix} = 0 \quad (A23)$$

This equation holds for the special case $n = 1$ but is not applicable for $n = 0$ where we can show by using Eqs. (55) and (56) that Eqs. (57)-(60) are linearly dependent. Omitting the last boundary condition equation (60), we can get the characteristic equation for $n = 0$, which is

$$\mu\lambda J_0\left(\frac{\lambda}{\mu}\right) J'_0(\mu\lambda) - \frac{\lambda}{\mu} J_0(\mu\lambda) J'_0\left(\frac{\lambda}{\mu}\right) + (1+\nu)\left(\mu^2 - \frac{1}{\mu^2}\right) J'_0(\mu\lambda) J_0\left(\frac{\lambda}{\mu}\right) = 0 \quad (A24)$$

The $p_{cr} - \lambda$ curves for the second modified problem are shown in Figure 6.

APPENDIX B

Variational Principle for Buckling of Clamped Shallow Spherical Shells

A variational principle for the problem of clamped shallow spherical shells was first considered by Weinitschke⁽¹³⁾ for the problem of axisymmetrical deformation of shells. From a modified Reissner variational principle⁽¹⁴⁾, we can show that Eqs. (45), (46), (49) and (50) are equivalent to the following variational principle:

$$\delta \int_0^\lambda \left\{ \frac{1}{x} \psi^{*'} [\kappa \omega^{*'} + \frac{1}{2} (\omega^{*'})^2] + \frac{1}{2} (\nabla^2 \omega^*)^2 - \frac{1}{2} (\nabla^2 \psi^*)^2 - 4p\omega^* \right\} x dx + \frac{1}{2} (1+\nu) \delta [\psi^{*'}(\lambda)]^2 = 0 \quad (B1)$$

where $\omega^*(\lambda) = \omega^{*'}(\lambda) = 0$ is specified. Furthermore, Eqs. (55)-(60) are equivalent to the following variational principle:

$$\delta \int_0^\lambda \left\{ \frac{1}{2x} \psi_n^{*'} (\omega_n')^2 + \frac{1}{2} \psi_n^{*''} \frac{n^2}{x^2} (\omega_n')^2 + \left(\frac{1}{x} \psi_n' - \frac{n^2}{x^2} \psi_n \right) (x\omega_n' + \omega_n^{*'} \omega_n') - n^2 \left(\frac{1}{x} \psi_n' \right)' \left(\omega_n + \frac{\omega_n \omega_n^{*'}}{x} \right) + \frac{1}{2} (L_n \omega_n)^2 - \frac{1}{2} (L_n \psi_n)^2 \right\} x dx + \frac{1}{2} (1+\nu) \delta [(\psi_n')^2 - n^2 \left(\frac{\psi_n}{x} \right)']_{x=\lambda} = 0 \quad (B2)$$

where $\omega_n(\lambda) = \omega_n'(\lambda) = 0$ is specified and variations are taken with respect to ω_n and ψ_n .

In order to apply these variational principles we try

$$\omega^* = (x^2 - \lambda^2)(Ax^2 + B\lambda^2)/\lambda^4 \quad (B3)$$

$$\psi^* = Cx^4 + D\lambda^2 x^2 \quad (B4)$$

$$\omega_n = Ex^n (x^2 - \lambda^2)^2 \quad (B5)$$

$$\psi_n = x^n (Fx^4 + G\lambda^2 x^2 + H\lambda^4) \quad (B6)$$

Substituting these expressions into Eq. (B1) and taking variations with

respect to A , B , C and D , we obtain four nonlinear equations for the unknowns A , B , C and D ; their values can be calculated numerically for any assigned p . Substituting Eqs. (B3)-(B6) into Eq. (B2) and taking variations with respect to E , F , G and H , we obtain four homogeneous linear equations and hence the characteristic equation from which the buckling pressure can be determined for any n . The numerical calculation has been done for $\lambda = 6$ and the buckling pressures are shown in Table 1.

APPENDIX C

Asymptotic Solution for Buckling Pressure for

Shallow Spherical Shells with Large λ

It is interesting to consider the asymptotic behavior of clamped shallow spherical shells when λ approaches infinity. A boundary layer is found near the edge of the shell when the shell deforms axisymmetrically before buckling. In the region outside the boundary layer the shell deforms essentially by a rigid body downward displacement, hence all components of stress resultant and moment, except N_r , vanish.

Let

$$\bar{\bar{\phi}} = \bar{\phi}^* + 2px \quad (C1)$$

Equations (47)-(50) can be written as

$$\theta^{*''} + \frac{\theta^{*'}}{x} - \frac{\theta^*}{x^2} + \bar{\bar{\phi}} = -2p\theta^* + \frac{\bar{\bar{\phi}}\theta^*}{x} \quad (C2)$$

$$\bar{\bar{\phi}}'' + \frac{\bar{\bar{\phi}}'}{x} - \frac{\bar{\bar{\phi}}}{x^2} - \theta^* = -\frac{1}{2x} \theta^{*2} \quad (C3)$$

$$\theta^*(\lambda) = 0 \quad (C4)$$

$$\bar{\bar{\phi}}'(\lambda) - \frac{\nu}{\lambda} \bar{\bar{\phi}}(\lambda) = 2(1-\nu)p \quad (C5)$$

In the region of boundary layer where x approaches infinity, the following equations can be used:

$$\theta^{*''} + \bar{\bar{\phi}} = -2p\theta^* \quad (C6)$$

$$\bar{\bar{\phi}}'' - \theta^* = 0 \quad (C7)$$

$$\theta^*(\lambda) = 0 \quad (C8)$$

$$\bar{\bar{\phi}}'(\lambda) = 2(1-\nu)p \quad (C9)$$

When $p < 1$ this problem can be solved analytically. The final results are

$$\theta^* = \frac{2\sqrt{2p}(1-\nu)}{\sqrt{1+p}} e^{-\sqrt{\frac{1-p}{2}}(\lambda-x)} \sin \sqrt{\frac{1+p}{2}}(\lambda-x) \quad (C10)$$

$$\bar{\phi} = \frac{2\sqrt{2p}(1-\nu)}{\sqrt{1+p}} e^{-\sqrt{\frac{1-p}{2}}(\lambda-x)} [\sqrt{1-p^2} \cos \sqrt{\frac{1+p}{2}}(\lambda-x) - p \sin \sqrt{\frac{1+p}{2}}(\lambda-x)]$$

or

$$\bar{\phi}^* \approx -2px \quad (C11)$$

From Figure 8 it can be seen that a boundary layer also appears in the buckling mode of unsymmetrical buckling. Let δ_b be an effective boundary layer thickness and

$$\bar{x} = x + \delta_b - \lambda \quad (C12)$$

$$(\quad)' = \frac{d}{d\bar{x}} (\quad)$$

then, in the region of boundary layer, Eqs. (55)-(60) become

$$\omega'''' - 2\sigma \omega'' + \sigma^2 \omega - \psi'' + \sigma(1-\theta^*)\psi + 2p\omega'' - 2p\sigma \omega = 0 \quad (C13)$$

$$\psi'''' - 2\sigma \psi'' + \sigma^2 \psi + \omega'' - \sigma(1-\theta^*)\omega = 0 \quad (C14)$$

$$\omega(\delta_b) = 0 \quad (C15)$$

$$\omega'(\delta_b) = 0 \quad (C16)$$

$$\psi''(\delta_b) + \nu \sigma \psi(\delta_b) = 0 \quad (C17)$$

$$\psi'''(\delta_b) - (2+\nu)\sigma \psi'(\delta_b) = 0 \quad (C18)$$

where

$$\sigma = \lim_{\lambda \rightarrow \infty} \left(\frac{n}{\lambda}\right)^2 \quad (C19)$$

and

$$\theta^* = 2p(1-\nu)e^{-\sqrt{\frac{1-p}{2}}(\delta-\bar{x})} \left[\sqrt{\frac{1-p}{1+p}} \sin \sqrt{\frac{1+p}{2}}(\delta-\bar{x}) - \cos \sqrt{\frac{1+p}{2}}(\delta-\bar{x}) \right] \quad (C20)$$

Also

$$\omega(0) = \omega''(0) = \psi(0) = \psi''(0) = 0 \quad (C21)$$

By the same method as given in the main problem the asymptotic value of the critical pressures can be evaluated numerically. In the calculation, δ_b was chosen equal to 40. The critical pressures p_{cr} are plotted against σ in Figure 10. The minimum of this curve determines the required asymptotic value of the critical pressure for λ equal to infinity which is found to be $p_{cr} = 0.864$ when the ratio n/λ approaches 0.817. The buckling mode is also calculated and is shown in Figure 11 from which the actual boundary layer thickness is found to be 12 approximately.

ACKNOWLEDGMENT

The author wishes to acknowledge his deep indebtedness to Professor B. Budiansky who has given constant encouragement and illuminating advice in the whole course of research. Discussions with Professor J. L. Sanders have been particularly enlightening.

REFERENCES

- (1) Budiansky, B., "Buckling of Clamped Shallow Spherical Shells", Proceedings of the Symposium on the Theory of Thin Elastic Shells, Delft, August 1959, North Holland Publishing Co., Amsterdam.
- (2) Weinitschke, H., "On the Stability Problem for Shallow Spherical Shells", Journal of Mathematics and Physics, Vol. 38, No. 4, p. 209, January 1960.
- (3) Thurston, G. A., "A Numerical Solution of the Nonlinear Equations for Axisymmetric Bending of Shallow Spherical Shells", Journal of Applied Mechanics, Vol. 28, No. 4, p. 557, December 1961.
- (4) Archer, R. R., "On the Numerical Solution of the Nonlinear Equations for Shells of Revolution", Journal of Mathematics and Physics, Vol. 40, No. 3, p. 165, September 1962.
- (5) Kaplan, A. and Fung, Y. C., "A Nonlinear Theory of Bending and Buckling of Thin Elastic Shallow Spherical Shells", NACA Technical Note 3212, August 1954.
- (6) Homewood, R. H., Brine, A. C. and Johnson, A. E. Jr., "Experimental Investigation of the Buckling Instability of Monocoque Shells", Proceedings of the Society for Experimental Stress Analysis, Vol. 18, No. 1, p. 88, 1961.
- (7) Grigolyuk, E. I., "On the Unsymmetrical Snapping of Shells of Revolution", Proceedings of the Symposium on the Theory of Thin Elastic Shells, Delft, August 1959, North Holland Publishing Co., Amsterdam.
- (8) Gjelsvik, A. and Bodner, S. R., "The Non-symmetrical Snap Buckling of the Clamped Spherical Cap", Technical Report No. 30, Division of Engineering, Brown University, March 1962.
- (9) Parmerter, R. D. and Fung, Y. C., "On the Influence of Non-symmetrical Modes on the Buckling of Shallow Spherical Shells under Uniform Pressure", NASA TND-1510, p. 491, 1962.
- (10) Weinitschke, H. J., "Asymmetric Buckling of Clamped Shallow Spherical Shells", NASA TND-1510, p. 481, 1962.
- (11) Marguerre, K., "Zur Theorie der gekrümmten Platte grosser Formänderung", Jahrbuch der 1939 der deutschen Luftfahrtforschung, p. 413.
- (12) Lowell, H. H., "Tables of the Bessel-Kelvin Functions ber , bei , Ker , Kei , and their Derivatives for the Argument Range $0(0.01)107.50$ ", NASA TR-32, 1959.
- (13) Weinitschke, H. J., "On the Nonlinear Theory of Shallow Spherical Shells", Journal of the Society for Industrial and Applied Mathematics, Vol. 6, p. 209, 1958.
- (14) Reissner, E., "On a Variational Theorem for Finite Elastic Deformations", Journal of Mathematics and Physics, Vol. 32, p. 129, 1953.

n	P_{cr} calculated by variational principle
1	> 0.85
2	0.770
3	0.751
4	0.850

Buckling Pressures Calculated by Variational Principle for $\lambda = 6$

Table 1

n	λ																	
	3.5	4	5	5.5	6	7	8	9	10	11	12	13	14	15	16	17	18	
0	0.614	0.578	0.629	0.762 0.763	0.995	1.068	1.130	0.931 0.94	0.822 0.83	0.83 0.84	0.96 0.97	0.96 0.97	0.98 0.99	0.98 0.99	0.92 0.93	0.90 0.91	0.94 0.95	
1					0.919	1.023												
2					0.775	0.796	0.893											
3					0.827	0.760	0.774	0.846										
4					0.931	0.812	0.766	0.777	0.814		0.899							
5						0.902	0.813	0.777	0.776	0.800	0.841	0.872	0.900	0.929				
6						1.000	0.887	0.816	0.780	0.776	0.798	0.826	0.850	0.874	0.905			
7							0.973	0.877	0.812	0.782	0.780	0.794	0.814	0.835	0.859	0.879	0.906	
8							1.057			0.810	0.790	0.781	0.790	0.807	0.828	0.847	0.861	
9											0.815	0.792	0.782	0.790	0.803	0.818	0.838	
10											0.853	0.816	0.801	0.785	0.792	0.800	0.818	
11											0.896	0.849	0.815	0.797	0.790	0.792	0.802	
12											0.942	0.892	0.843	0.814	0.800	0.792	0.793	
13												0.928	0.876	0.843	0.818	0.800	0.794	
14													0.918	0.873	0.842	0.814	0.803	
15													0.951	0.911	0.872	0.837	0.818	
16														0.945	0.901	0.864	0.835	
17														0.976		0.892	0.860	
18																	0.888	
19																	0.911	

CALCULATED BUCKLING PRESSURES OF CLAMPED SHALLOW SPHERICAL SHELLS

TABLE 2




FIG. 1 GEOMETRY OF CLAMPED SHALLOW SPHERICAL SHELLS




FIG. 2 PRESSURE-DEFLECTION CURVE OF CLAMPED SHALLOW SPHERICAL SHELLS




FIG. 3 CALCULATED CRITICAL PRESSURES FOR AXISYMMETRICAL SNAPPING AND EXPERIMENTAL RESULTS




FIG. 4 STRESS RESULTANTS, MOMENTS AND DISPLACEMENTS IN SHELLS




FIG. 5 BUCKLING PRESSURES IN THE FIRST MODIFIED PROBLEM




FIG. 6 BUCKLING PRESSURES IN THE SECOND MODIFIED PROBLEM




FIG. 7 CALCULATED BUCKLING PRESSURES OF CLAMPED SHALLOW SPHERICAL SHELLS AND EXPERIMENTAL RESULTS




FIG. 8 BUCKLING MODES OF CLAMPED SHALLOW SPHERICAL SHELLS




FIG. 9 COMPARISON OF CALCULATED PRESSURES OF UNSYMMETRICAL BUCKLING WITH PREVIOUS RESULTS




FIG. 10 $p_{cr} - \sigma$ CURVE



FIG. 11 BUCKLING MODE OF CLAMPED SHALLOW SPHERICAL SHELLS
WHEN $\lambda \rightarrow \infty$

Chief of Naval Research Department of the Navy Washington 25, D.C. Attn: Code 138 (2)	Commanding Officer Office of Naval Research Branch Office 105 Sumner Street Boston 10, Massachusetts (2)	Commanding Officer ONR Branch Office John Overair Library Building 86 East Randolph Street Chicago 11, Illinois (1)	Commander U.S. Naval Proving Grounds Dahlgren, Virginia (1)	Superintendent Naval Gun Factory Washington 25, D.C. (1)	Commander Naval Ordnance Test Station Ingramm, China Lake, California Attn: Physics Division (1)
Commanding Officer Office of Naval Research Branch Office 136 Broadway New York 13, N.Y. (1)	Commanding Officer Office of Naval Research Branch Office 1030 R. Green Street Pasadena, California (1)	Commanding Officer Office of Naval Research Branch Office 1000 Geary Street San Francisco, California (1)	Commander Naval Ordnance Test Station 3202 S. Fortchill Boulevard Pasadena 8, California Attn: Mechanics Division (1)	Commander Naval Ordnance Test Station 3202 S. Fortchill Boulevard Pasadena 8, California Attn: Structures Division (1)	Mr. K.W. Koopman, Secretary Welding Research Council of The Engineering Foundation 29 W. 39th Street New York 18, New York (2)
Commanding Officer Office of Naval Research Hwy No. 100, Fleet Post Office New York, N.Y. (25)	Director Naval Research Laboratory Washington 25, D.C. Attn: Tech. Info. Office (6)	Director Naval Research Laboratory Washington 25, D.C. Attn: Code 6200 (1)	Commanding Officer and Director Naval Engineering Experiment Station Annapolis, Maryland (1)	Superintendent Naval Postgraduate School Monterey, California (1)	Commander Marine Corps Schools Quantico, Virginia Attn: Director, Marine Corps Development Center (1)
Director Naval Research Laboratory Washington 25, D.C. Attn: Code 6205 (1)	Director Naval Research Laboratory Washington 25, D.C. Attn: Code 6230 (1)	Director Naval Research Laboratory Washington 25, D.C. Attn: Code 6260 (1)	Commanding General U.S. Air Force Washington 25, D.C. Attn: Research and Development Division (1)	Commander U.S. Air Force Inst. of Technol. Wright-Patterson Air Force Base Dayton, Ohio (1)	Director of Intelligence Headquarters, U.S. Air Force Washington 25, D.C. Attn: F.V. Branch (Air Targets Division) (1)
Armed Services Technical Information Agency Arlington Hall Station Arlington 18, Virginia (5)	Office of Technical Services Department of Commerce Washington 25, D.C. (1)	Office of the Secretary of Defense Research and Development Div. The Pentagon Washington 25, D.C. Attn: Technical Library (1)	Commander Air Research and Development Command P.O. Box 1395 Baltimore 25, Maryland Attn: RMDP (1)	U.S. Atomic Energy Commission Washington 25, D.C. Attn: Director of Research (2)	Prof. Walter T. Daniels School of Engineering and Architecture Washington 25, D.C. Washington 1, D.C. (1)
Chief, Armed Forces Special Weapon Project The Pentagon Washington 25, D.C. Attn: Techn. Info. Div. (2)	Office, Secretary of the Army The Pentagon Washington 25, D.C. Attn: Army Library (1)	Chief of Staff Department of the Army Washington 25, D.C. Attn: Development Branch (R and D Div.) (1)	Director National Bureau of Standards Washington 25, D.C. Attn: Division of Mechanics (1)	Director National Bureau of Standards Washington 25, D.C. Attn: Engineering Mechanics Section (1)	Director National Bureau of Standards Washington 25, D.C. Attn: Aircraft Structures (1)
Chief of Staff Department of the Army Washington 25, D.C. Attn: Research Branch (R and D Div.) (1)	Chief of Staff Department of the Army Washington 25, D.C. Attn: Special Weapons Branch (R and D Div.) (1)	Office, Chief of Engineers Department of the Army Washington 25, D.C. Attn: ENO-ML Library Br., Adm. Ser. Div. (1)	Commandant, U.S. Coast Guard 3300 K Street, N.W. Washington 25, D.C. Attn: Chief, Testing and Development Division (1)	U.S. Maritime Administration General Administration Office Bldg. Washington 25, D.C. Attn: Chief, Division of Pre- mises Design (1)	Director National Bureau of Standards Washington 25, D.C. Attn: Aircraft Structures (1)
Office, Chief of Engineers Department of the Army Washington 25, D.C. Attn: ENO-WE Engr. Div., Civil Works (1)	Office, Chief of Engineers Department of the Army Washington 25, D.C. Attn: ENO-WE Planning Div., Civil Works (1)	Office, Chief of Engineers Department of the Army Washington 25, D.C. Attn: ENO-WE Prot. Const. Br., Engr. Div., Mil. Const. (1)	Director Langley Aeronautical Lab. Langley Field, Virginia Attn: Structures Division (2)	Director Forest Products Laboratory Madison, Wisconsin (1)	Civil Aeronautics Administration Department of Commerce Washington 25, D.C. Attn: Chief, Airframe and Equipment Branch (1)
Office, Chief of Engineers Department of the Army Washington 25, D.C. Attn: ENO-MA Structures Br., Engr. Div., Mil. Const. (1)	Office, Chief of Engineers Department of the Army Washington 25, D.C. Attn: ENO-WE Spec. Engr. Br., Engr. R and D Div. (1)	Commanding Officer Engineer Research Development Laboratory Fort Belvoir, Virginia (1)	National Science Foundation 1200 B Street, N.W. Washington, D.C. Attn: Engineering Sciences Division (1)	National Academy of Science 2101 Constitution Avenue Washington 25, D.C. Attn: Technical Director, Com- on Ships' Structural Design (1)	Professor R.A. Rolay Department of Civil Engineering Columbia University New York 27, N.Y. (1)
Office, Chief of Ordnance Department of the Army Washington 25, D.C. Attn: Research and Materials Branch (Ord R and D Div.) (1)	Office, Chief Signal Officer Department of the Army Washington 25, D.C. Attn: Engineering and Technical Division (1)	Commanding Officer Jaterson Arsenal Waterloo, Massachusetts Attn: Laboratory Division (1)	Professor R.L. Baptinghoff Department of Aeronautical Eng. Massachusetts Institute of Technology Cambridge 39, Massachusetts (1)	Professor H.H. Blisch Department of Civil Engineering Columbia University New York 27, N.Y. (1)	Professor R.A. Rolay Department of Civil Engineering Columbia University New York 27, N.Y. (1)
Commanding Officer Frankford Arsenal Bridgeway Station Philadelphia 27, Pennsylvania Attn: Laboratory Division (1)	Office of Ordnance Research 2127 Myrtle Drive Duke Station Durham, North Carolina Attn: Div. of Eng.Sciences (1)	Commanding Officer Spicer Signal Laboratory Fort Monmouth, New Jersey Attn: Components and Materials Branch (2)	Professor O.F. Carrier Pierce Hall Harvard University Cambridge 38, Massachusetts (1)	Professor Herbert Derosiewicz Northwestern University Evanston, Illinois (1)	Professor D.C. Bruchler Department of Engineering Brown University Providence 12, Rhode Island (1)
Director Veterarys Experiment Station P.O. Box 631 Vicksburg, Mississippi Attn: Library (1)	Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 300 (1)	Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 327 (2)	Professor A.C. Eringen Department of Aeronautical Engineering Purdue University Lafayette, Indiana (1)	Professor W. Flügge Department of Mechanical Engineering Stanford University Stanford, California (1)	Professor J.M. Goodier Department of Mechanical Engineering Stanford University Stanford, California (1)
Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 371 (1)	Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 423 (1)	Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 410 (1)	Professor L.E. Goodman Engineering Experiment Station University of Minnesota Minneapolis, Minnesota (1)	Professor M. Ketyel The Technological Institute Northwestern University Evanston, Illinois (1)	Professor F.O. Hedge Illinois Institute of Technology Technology Center Chicago 30, Illinois (1)
Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 412 (1)	Chief, Bureau of Aeronautics Department of the Navy Washington 25, D.C. Attn: AEN-2 (1)	Chief, Bureau of Aeronautics Department of the Navy Washington 25, D.C. Attn: DE (1)	Professor M.J. Hoff, Head Division of Aeronautical Eng. Stanford University Stanford, California (1)	Professor J. Kemper Dept. of Aeronaut. Eng., Appl. Mech. and Polytchnic Institute of Brooklyn 99 Livingston Street Brooklyn 2, New York (1)	Professor H.L. Langhaar Department of Theoretical and Applied Mechanics University of Illinois Urbana, Illinois (1)
Chief, Bureau of Aeronautics Department of the Navy Washington 25, D.C. Attn: DE-23 (1)	Chief, Bureau of Aeronautics Department of the Navy Washington 25, D.C. Attn: TD-12 (1)	Chief, Bureau of Ordnance Department of the Navy Washington 25, D.C. Attn: A43 (1)	Professor E.L. Appl Division of Applied Mathematics Stanford University Stanford, California (1)	Professor George M. Lee Director of Research Rensselaer Polytechnic Institute Troy, New York (1)	Mr. M.M. Lemcoe Research Institute 8500 Columbia Road San Antonio 6, Texas (1)
Chief, Bureau of Ordnance Department of the Navy Washington 25, D.C. Attn: Re (1)	Chief, Bureau of Ordnance Department of the Navy Washington 25, D.C. Attn: ReP (1)	Chief, Bureau of Ordnance Department of the Navy Washington 25, D.C. Attn: ReM (1)	Professor R.D. Mindlin Department of Civil Engineering University of Illinois 612 W. 125th Street New York 27, N.Y. (1)	Dr. A. Nield 116 Cherry Valley Road Pittsburgh 21, Pennsylvania (1)	Professor Paul M. Naghdi Department of Engineering Mechanics University of California Berkeley, California (1)
Chief, Bureau of Ordnance Department of the Navy Washington 25, D.C. Attn: SP (1)	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-210 (1)	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-213 (1)	Professor William A. Nash Department of Engineering Mech. University of Florida Gainesville, Florida (1)	Professor W.M. Mearns Department of Civil Engineering University of Illinois Urbana, Illinois (1)	Professor Aris Phillips Department of Civil Engineering 15 Prospect Street New Haven, Connecticut (1)
Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-220 (1)	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-222 (1)	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-210 (1)	Professor W. Prager Brown University Providence 12, Rhode Island (1)	Professor E. Reissner Department of Mathematics Massachusetts Institute of Technology Cambridge 39, Massachusetts (1)	Professor M.A. Sadowsky Department of Mathematics Rensselaer Polytechnic Institute Troy, New York (1)
Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-210 C (1)	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-210 (1)	Chief, Bureau of Yards and Docks Department of the Navy Washington 25, D.C. Attn: Code D-500 (1)	Prof. Bernard W. Shaffer Dept. of Mechanical Engineering New York University University Heights New York 25, New York (1)	Professor Eli Sternberg Division of Applied Mathematics Brown University Providence 12, Rhode Island (1)	Professor J.P. Timoshenko School of Engineering Stanford University Stanford, California (1)
Commanding Officer and Director David Taylor Model Basin Washington 1, D.C. Attn: Code 647 (1)	Commanding Officer and Director David Taylor Model Basin Washington 1, D.C. Attn: Code 700 (1)	Commanding Officer and Director David Taylor Model Basin Washington 1, D.C. Attn: Code 710 (1)	Professor A.S. Valentos Department of Civil Engineering University of Illinois Urbana, Illinois (1)	Professor Dana Young Yale University New Haven, Connecticut (1)	Dr. John F. Bredt Department of Engineering University of California Los Angeles, California (1)
Commander U.S. Naval Ordnance Laboratory White Oak, Maryland Attn: Technical Library (2)	Commander U.S. Naval Ordnance Laboratory White Oak, Maryland Attn: Tech. Evaluation Dept. (1)	Director Materials Laboratory New York Naval Shipyard Brooklyn 1, New York (2)	Mr. Martin Goland, Vice President Southwest Research Institute 8500 Columbia Road San Antonio, Texas (1)	Prof. J.E. Cernak Dept. of Civil Engineering Colorado State University Fort Collins, Colorado (1)	Professor W. J. Hall Dept. of Civil Engineering University of Illinois Urbana, Illinois (1)
Officer-in-Charge Naval Civil Engineering Research and Eval. Lab., U.S. Naval Constr. Detachment Center Port Hueneme, California (2)	Director Naval Air Experimental Station Nav. Air Res. Center, Naval Base Philadelphia 12, Pennsylvania Attn: Materials Lab. (1)	Officer-in-Charge Underwater Explosion Research Div. Norfolk Naval Shipyard Portsmouth, Virginia Attn: Dr. A.N. Kail (1)	Prof. R.P. Harrington, Head Dept. of Aeronautical Engineering University of Cincinnati Cincinnati, Ohio (1)	Prof. Eugene T. Druelle, Jr. Dept. of Aeronautical Eng. Princeton University Princeton, New Jersey (1)	Commander WAGO Wright Patterson AFB, Ohio Attn: WAGOS (1)
			Commander WAGO Wright Patterson AFB, Ohio Attn: WAGOS (1)	Commander WAGO Wright Patterson AFB, Ohio Attn: WAGOS (1)	Legislative Reference Service Library of Congress Washington 25, D.C. Attn: Dr. K. Monk (1)
			C.O. USNR/OCU Kirkland Air Force Base Albuquerque, New Mexico Attn: Code 20 (1)		