

UNCLASSIFIED

AD 410440

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

research and development

410440

CARBORUNDUM®

DOCUMENT RELEASE STATUS
NAVWEPS FORM 3900/3 (8-62)

This paper is chemically
treated. No carbon paper
is required.

SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	CONTRACT AND/OR PROJECT (WEP TASK) NO. N600(9)-59749	ENCLOSURE Carborundum Co. A STUDY OF FUNDAMENTAL MECHANICAL PROPERTIES OF SINGLE CERAMIC CRYSTALS. Mar 15 - May 14, 1963 10 copies
REPORT NO. 2d Bimonthly Progress Report	DATE OF REPORT 22 May 1963	

TO: [Commander
Armed Services Technical Information Agency
Arlington Hall Station
Arlington 12, Virginia]

AD NUMBER (For ASTIA use only)

410440

Enclosure is forwarded for distribution, subject to limitations checked below. Request that AD number be inserted in space provided, one copy of this letter be returned to originating activity, if shown, and one copy sent to Chief, Bureau of Naval Weapons.

☒ Qualified requesters may obtain copies of this report direct from ASTIA	U.S. Government Agencies may obtain copies of this report direct from ASTIA. Other qualified ASTIA users should request through no source. (Not available to non-Government ASTIA users.)
☐ Qualified requesters may obtain copies of this report direct from ASTIA. Foreign announcement and dissemination of this report by ASTIA is limited.	
☐ U.S. Government Agencies may obtain copies of this report direct from ASTIA. Other qualified ASTIA users should request through the Chief, Bureau of Naval Weapons, Washington 25, D.C.	U.S. Military Agencies may obtain copies of this report direct from ASTIA. Other qualified ASTIA users should request through no source. (Not available to non-military ASTIA users.)
☐ U.S. Military Agencies may obtain copies of this report direct from ASTIA. Other qualified ASTIA users should request through the Chief, Bureau of Naval Weapons, Washington 25, D.C.	All distribution of this report is controlled. Qualified ASTIA users should request through the Chief, Bureau of Naval Weapons, Washington 25, D.C.

SIGNATURE

W.H. Plant


TITLE

**W.H. PLANT
By Direction**

CODE

DATE

[Chief, Bureau of Naval Weapons (DL1-302)
Navy Department
Washington 25, D. C.]



Second Bi-Monthly Progress Report


A STUDY OF FUNDAMENTAL
MECHANICAL PROPERTIES OF
CERAMIC SINGLE CRYSTALS

Contract N600 (19)-59749

March 15 through May 14, 1963

By: P. T. B. Shaffer
H. D. Batha

May 22, 1963



This program is supported by
Bureau of Naval Weapons
Department of the Navy
Washington 25, D. C.

SUMMARY

Additional data on strength and elastic properties of boron-doped silicon carbide crystals have been obtained on thin (10-70 μ) crystals. Analyses are being made to determine the specific effect of impurities on strength.

TABLE OF CONTENTS

	<u>Page No.</u>
I. INTRODUCTION	1
II. WORK PROGRESS	1
A. Apparatus	1
B. Strength	1
C. Young's Modulus	1
III. DISCUSSION AND FUTURE PLANS	1

I. INTRODUCTION

This is the second bi-monthly progress report to be released on research sponsored by the Bureau of Naval Weapons under Contract N-600 (19)-59749. It covers the period March 15 through May 14, 1963. This research is a continuation of that previously conducted under Bureau of Naval Weapons Contract NOW-61-0676-c.

II. WORK PROGRESS

A. Apparatus

The apparatus for measuring elastic modulus and breaking strength of thinner crystals (10-70 μ thick) has been put in operation. The minimum and maximum detectable load and deflection are 0.225 and 40 grams, and 0.000354 and 0.100 inches, respectively.

B. Strength

Twenty-six additional samples of boron-doped silicon carbide, ultrasonically cut from large crystals, were broken. No exceptional strength values were obtained (see Table No. I).

C. Young's Modulus

Seventeen sample bars cut from boron-doped silicon carbide crystals were measured. Elastic modulus values from 38 to 102 million psi were obtained (see Table No. I).

III. DISCUSSION AND FUTURE PLANS

The work during this report period has been directed to a large extent toward the refinement of apparatus and a study of existing data. Chemical analyses obtained on the boron-doped crystals reported earlier are as yet incomplete. When these data are available a statistical study of the boron-thickness-strength and boron-thickness-elasticity relationships will be made.

The effects of various polishing techniques will be investigated in order to find a means of improving specimen geometry with a minimum sacrifice in mechanical properties.

TABLE NO. I

Strength and Young's Modulus of Boron-Doped Silicon
Carbide Crystals*

Crystal No.	Thickness (μ)	Young's Modulus (10^6 psi)	MOR (10^3 psi)
A-363-84	56.5	72.5	- **
-85	68.7	46.2	-
-86	59.7	93.7	110.0
-87	41.2	61.0	108.0
-88	93.5	43.7	-
-89	58.0	55.0	-
-90	49.3	52.8	62.2
-91	50.8	93.7	178.0
-92	56.4	92.3	65.7
-93	48.5	62.0	-
-94	56.5	53.1	70.8
-95	45.2	67.0	96.2
-96	28.5	102.0	22.2
-100	73.7	84.3	-

**Available load failed to fracture several samples.

*Ultrasonically cut from larger crystals.

A-485-2	102.0	-	47.0
-3	127.0	-	36.4
-4	38.2	-	12.1
-5	127.0	-	70.5
-6	112.0	-	10.5
-7	76.2	-	194.0
-8	71.0	-	3.3
-9	140.0	-	30.2
-10	96.5	-	31.8
-11	76.2	-	35.2
-12	43.2	-	57.7
-13	61.0	-	102.0
-14	58.5	-	32.4
-15	61.0	-	30.8
-16	25.4	56.2	115.0
-17	43.2	-	64.7
-18	28.8	44.1	96.0
-19	30.5	38.0	74.3

DISTRIBUTION LIST

	<u>No. Copies</u>
Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: RRMA-2	15 1 Reproducible Copy Balance of 50 copies
Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Code 342B	1
Office of Naval Research Department of the Navy Washington 25, D. C. Attn: Code 423	1
Naval Air Material Center Aeronautical Materials Laboratory Philadelphia 12, Pennsylvania	1
Wright Air Development Division Wright-Patterson Air Force Base Ohio Attn: Code WWRCMP Attn: Code ASRCMC	2
National Aeronautics and Space Administration 1520 H Street, N. W. Washington 25, D. C.	1
Bureau of Naval Weapons Department of the Navy Washington 25, D. C. Attn: SP-27 Attn: RMMP	2
Technical Information Service Extension U. S. Atomic Energy Commission P. O. Box 62 Oak Ridge, Tennessee	1
Director National Bureau of Standards Washington 25, D. C.	1

DISTRIBUTION LIST (cont'd)

	<u>No. Copies</u>
Commanding Officer Office of Ordnance Research Box CM, Duke Station Durham, North Carolina	1
Commanding Officer Watertown Arsenal Watertown 72, Massachusetts Attn: OMRO	1
U. S. Atomic Energy Commission Document Library Germantown, Maryland	1
Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTB	1
Battelle Memorial Institute 505 King Avenue Columbus 1, Ohio Attn: Defense Metals Information Center	1
National Aeronautics and Space Administration Lewis Research Center 21000 Brookpark Road Cleveland 35, Ohio	1
Professor Thomas D. McGee Department of Ceramic Engineering Iowa State University Ames, Iowa	1
The Carborundum Company Research and Development Division Niagara Falls, New York	10