

UNCLASSIFIED

AD 417516

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA




UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

417516

CATALOGED BY DDC

AS AD No. 417516



HYDRONAUTICS, incorporated research in hydrodynamics

Research, consulting, and advanced engineering in the fields of NAVAL and INDUSTRIAL HYDRODYNAMICS. Offices and Laboratory in the Washington, D. C., area: Pindell School Road, Howard County, Laurel, Md.

HYDRONAUTICS, Incorporated

TECHNICAL REPORT 231-3

WAVES DUE TO A SUBMERGED BODY

By

B. Yim

May 1963

Prepared Under

Office of Naval Research

Department of the Navy

Contract Nonr 3680(00)

NR 220-016

HYDRONAUTICS. Incorporated

-11-

TABLE OF CONTENTS

	Page No.
INTRODUCTION.....	1
WAVE HEIGHT DUE TO A SIMPLE SOURCE.....	2
EVALUATION OF THE REGULAR WAVE.....	4
Stationary Phase.....	4
In the Vicinity of the Singularity.....	10
EVALUATION OF THE LOCAL DISTURBANCE.....	13
In the Vicinity of the Singularity.....	13
When P/f is not too Small.....	17
WAVE DUE TO A SUBMERGED SOURCE LINE.....	19
WAVES DUE TO A SUBMARINE.....	22
APPENDIX 1	25
APPENDIX 2	27
REFERENCES.....	33

HYDRONAUTICS, Incorporated

-iii-

LIST OF SYMBOLS

A_1	Airy function
f	Depth of a point source
$F(\theta)$	Expression defined in Equation (7.1)
g	Acceleration of gravity
H	Depth of keel of submarine
k_0	$= U^2/g$
K_0, K_1	Modified Bessel Functions of 2nd kind
$L_n^{(1)}, L_n^{(2)}$	Integrals defined in Equation (19) and (20), respectively
M	Strength of point source
M_1	Strength of line source per unit length
N	$= k_0 R$
p_m, q_m	Coefficients of asymptotic expansion defined in Equation (A9)
Q	$= \sqrt{1 - 8 \tan^2 \delta}$
R	Radial distance from singularity defined in Equation (2)
U	Relative velocity of water at infinity
x, y, z	Rectangular cartesian coordinates, x in the direction of U and z vertically upward
x_1	x coordinate of singularity
δ	Angle defined in Equation (2)
θ_c	Critical angle of δ defined in Equation (8.1)
θ_1, θ_2	Constant defined in Equation (8)

HYDRONAUTICS, Incorporated

-iv-

μ	Fictitious frictional force
$\mu(\delta), v(\delta)$	Coefficients of transformation defined in Equation (A4)
ϕ	Velocity potential
ω	Expression defined in Equation (2)
ζ	Wave height due to a point source
ζ_r, ζ_l	Regular wave and local disturbance due to a point source respectively
ζ_1	Wave height due to a source line
ζ_{1r}, ζ_{1l}	Regular wave and local disturbance due to a source line respectively
ζ_{rt}, ζ_{rd}	Transverse and divergent waves, respectively.

INTRODUCTION

The pattern and the height of surface waves due to a surface ship or a submerged body has been considered by many hydrodynamists since Lord Kelvin (1891) worked out the wave system due to a pressure point on the surface. This problem is attractive not only because of practical applications in connection with the wave resistance or stability of ships but also as a basic physical phenomenon and because of the delicate application of mathematics involved.

Kelvin calculated the integral representing the wave height by the method of stationary phase which is reasonably valid far behind the pressure point inside the critical angle ($\pm 19^{\circ} 28'$). Havelock (1906) evaluated the wave height on the critical line. Hogner (1923) investigated the wave height due to a Kelvin source in the vicinity of the critical line. Peters (1949) and Ursell (1960) improved the theory and the result using the method of steepest descent.

Havelock investigated the wave due to a submerged sphere (1928) [see also Wigley (1930)], and the infinite draft ship (1932). Minaka also investigated waves of the infinite draft ship and performed the numerical evaluation (1957).

In this paper, the wave height due to a submerged point source and a source line is investigated. The wave height consists of two parts; the regular wave and the local disturbance. The method of evaluating the integral representing regular waves is different in two regions, that in the vicinity and that far behind the singularity. In the vicinity of the singularity, the numerical integration is performed by the method of Gauss' quadrature. At the far place, the method of stationary phase

is used. The behavior of the wave height near the critical line is discussed.

For the local disturbance, the integral can be evaluated in the closed form immediately above the singularity. A scheme involving numerical computation by high speed machine is worked out for other points.

As an example, the wave height due to a simple form of submarine with given dimensions is calculated in detail. The influence of the submarine sail is included.

WAVE HEIGHT DUE TO A SIMPLE SOURCE

As usual, the water is assumed to be inviscid, homogeneous and incompressible. Hence there exists a potential ϕ . The coordinate system is fixed in the singularity and only the steady problem is considered. The origin of the right handed coordinate system O-xyz is located on the mean free surface; x is directed along the uniform relative velocity of the water, and z is vertically upward. The surface wave is assumed to be small compared with the wave length, and the principle of superposition holds.

The derivation of the formula of the wave height ζ due to a point source located at $(x_1, 0, -f)$, with the strength M is well known (e.g. see Wigley 1949).

$$\zeta = \frac{U}{g} \phi_x = - \frac{M}{2\pi U} \operatorname{Re} \int_{-\pi}^{\pi} \int_0^{\infty} \frac{12 k_0 k \sec \theta e^{k(1\omega - f)}}{k - k_0 \sec^2 \theta - i\mu \sec \theta} dk d\theta \quad (1)$$

where

$$\begin{aligned} \omega &= (x - x_1) \cos \theta + y \sin \theta \\ &= R \cos (\theta - \delta), \text{ with } x - x_1 = R \cos \delta, y = R \sin \delta \end{aligned} \quad (2)$$

$$k_0 = \frac{g}{U^2}, \quad \delta = \arctan \left(\frac{y}{x - x_1} \right) \quad (3)$$

μ is the fictitious frictional force which is to be put zero after the evaluation of the integral. By contour integration (see Appendix 1) ζ becomes the sum of two integrals,

$$\zeta = \zeta_r + \zeta_f \quad (4)$$

$$\zeta_r = 4 \frac{M}{U} k_0 \int_{-\pi/2 + \delta}^{\pi/2} \exp(-k_0 r \sec^2 \theta) \sec^3 \theta \cos(k_0 \omega \sec^2 \theta) d\theta \quad (5)$$

$$\begin{aligned} \zeta_f &= -\frac{2M}{\pi U} \int_{-\pi/2 + \delta}^{\pi/2 + \delta} \int_0^\infty \frac{\exp(-m\omega) m \sec \theta}{k_0^2 r^2 \sec^4 \theta + m^2} \times \\ &\quad \times \{k_0 \sec^2 \theta \sin(mf) - m \cos(mf)\} dm d\theta \\ &= -\frac{2M}{U\pi f} \int_{-\pi/2}^{\pi/2} \int_0^\infty \frac{\exp(-m \frac{R}{f} \cos \theta) m \sec \theta}{k_0^2 r^2 \sec^4 \theta + m^2} \{k_0 f \sec^2 \theta \sin m \\ &\quad - m \cos m\} dm d\theta \end{aligned} \quad (6)$$

where $\theta_0 = \theta + \delta$, ζ_r is called the regular wave and ζ_δ is the local disturbance which diminishes with large k .

This is the fundamental formula for the surface wave since the body in the water is usually represented by source distributions. The wave height due to a given body is then obtained by superposition of all the waves produced by each source. The wave due to higher order singularities such as a doublet is the derivative of Equation (4) with respect to the position in the direction of the higher order singularity.

The evaluations of ζ_r and ζ_δ in Equations (4) and (6) are not simple. These will be discussed separately in the following two sections.

EVALUATION OF THE REGULAR WAVE

The evaluation of the integral ζ_r of Equation (5) is different in the two regions, near and far behind the singularity.

(A) Stationary Phase. On the surface far behind the singularity, i.e. when $k_0 R$ is large, the method of stationary phase can be applied to the integral (5). This method was originated by Lord Kelvin (1887) and can be found discussed in any related text (e.g. Lamb 1945, p. 395).

Let us consider the integral

$$\zeta_r \approx 4 M k_0 \int_{-\pi/2}^{\pi/2} \exp(-k_0 r \sec^2 \theta) \sec^3 \theta \cos(Nr(\theta)) d\theta \quad (7)$$

$$\text{where } F(\theta) = \sec^2 \theta \cos(\theta - \delta), \quad N = k_0 R. \quad (7.1)$$

HYDRONAUTICS, Incorporated

-5

Since N is large, the part of integration between $-\pi/2$ and $-\pi/2 + \epsilon$ is negligible.

The root of the derivative of $F(\theta)$ with respect to θ is obtained as

$$F'(\theta) = 0$$

or

$$2 \tan^2 \theta + \tan \theta \tan \delta + 1 = 0$$

$$\left. \begin{array}{l} \tan \theta_1 \\ \tan \theta_2 \end{array} \right\} = -\frac{1}{4} (\cot \delta \pm \sqrt{(\cot^2 \delta - 8)}) \quad (8)$$

which is only significant when $\cot^2 \delta - 8 \geq 0$ or $\delta \leq \tan^{-1} \frac{1}{2\sqrt{2}} = \delta_c$
(8.1)

Now (7) can be evaluated as the sum of two waves, ζ_{rt} transverse, ζ_{rd} divergent,

$$\zeta_r = \zeta_{rt} + \zeta_{rd}$$

$$\left. \begin{aligned} \zeta_{rt} &= 4k_0 \frac{M}{U} \sec^3 \theta_1 \exp(-k_0 f \sec^2 \theta_1) \sqrt{\frac{2\pi}{N|F'(\theta_1)|}} \cos(NF(\theta_1) \pm \frac{\pi}{4}) \\ \zeta_{rd} &= 4k_0 \frac{M}{U} \sec^3 \theta_2 \exp(-k_0 f \sec^2 \theta_2) \sqrt{\frac{2\pi}{N|F'(\theta_2)|}} \cos(NF(\theta_2) \pm \frac{\pi}{4}) \end{aligned} \right\} (9)$$

HYDRONAUTICS, Incorporated

-6-

where

$$F''(\theta) = (6 \tan^2 \theta + 1) \sec^2 \theta \cos(\delta - \theta) + 4 \sec^2 \theta \tan \theta \sin(\delta - \theta) \quad (10)$$

and the sign of $\pm \pi/4$ is decided as the sign of $F''(\theta)$.

However, this is only for $\delta < \delta_c$. When $\delta = \delta_c$, which means the centerline, $\theta_1 = 0$, $\theta_2 = -\pi/2$,

and

$$F''(\theta_1) = 1$$

$$F''(\theta_2) = -\infty$$

Hence

$$\zeta_r = \zeta_{rt} = 4k_0 \frac{M}{U} \exp(-k_0 f) \sqrt{\frac{2\pi}{N}} \cos(N + \frac{\pi}{4}) \quad (11)$$

Since $N \equiv k_0 R \equiv \frac{gR}{U^2}$, the wave length on the centerline is

$$2\pi U^2/g \quad (11.1)$$

When $\delta = \delta_c$ which is the critical line, $\theta_1 = \theta_2$,

$F''(\theta_1) = 0$ and this makes Equation (9) singular. When $\delta > \delta_c$ the right hand side of Equation (8) becomes imaginary. In the vicinity of this critical line far behind the singularity, Hogner (1923), Peters (1949), and Ursell (1960) investigated thoroughly the situation for the wave due to a pressure point.

Putting $\tan \theta = u$ in Equation (5) and neglecting the interval $(-\pi/2, -\pi/2 + \delta)$, we obtain

$$\begin{aligned}\zeta_1 &= 8k_0 \frac{M}{U} \exp(-k_0 f) \int_0^\infty \sqrt{1+u^2} \exp(-k_0 f u^2) X \\ &\quad \times \cos[k_0 t \sqrt{1+u^2}] \cos(k_0 y u \sqrt{1+u^2}) du \\ &= 4k_0 \frac{M}{U} \exp(-k_0 f) \operatorname{Re} \int_{-\infty}^\infty \sqrt{1+u^2} \exp(-k_0 f u^2) X \\ &\quad \times \exp[iN\{(\cos \delta - u \sin \delta) \sqrt{1+u^2}\}] du \quad (12)\end{aligned}$$

$$\text{where } k_0 x = N \cos \delta \quad k_0 y = N \sin \delta.$$

We note that the expression for the wave height due to the pressure point on the surface is exactly the same as that due to the submerged doublet with the corresponding strength and zero depth (compare Equation (2.2) of Ursell (1960) with Havelock's (1928) Equation (12) at far behind the singularity by the change of variable as above). We mentioned already the relation between the wave heights due to a doublet and a point source.

The method of Chester, Friedman, and Ursell (1957) can be adopted for the asymptotic expansion of the above equation in the vicinity of the critical line as in Ursell's paper (1960). The idea is that in order to use the method of steepest descent in the vicinity of the critical line (where the usual method of steepest descent fails) the integral is represented in a series

of Airy functions (see Jeffreys and Jeffreys, 1946 § 17.07) by the regular transformation of the variable of integration. Chester et al (1957) worked out the rigorous theory. The only difference between the two cases of the pressure point (by Ursell (1960)) and the submerged point source is in the form of the analytic function $g(z)$ in the integral

$$\int g(u) \exp [Nf(u)] \quad (12a)$$

(of Chester et al. Equation (1.1)).

The way of deriving the asymptotic expansion of Equation (12) in the vicinity of the critical angle is exactly the same as Ursell's (1960). His coefficient of transformation $\mu(\delta)$ and $v(\delta)$ are exactly the same for each angle, which are tabulated in his paper. The coefficients of the asymptotic expansion of p_0 and q_0 are different. These are derived in Appendix 2 keeping the close connection with Ursell's paper (1960). The result is:

$$p_0(\delta) = \frac{3^{\frac{3}{4}}}{2^{\frac{7}{2}}} \frac{\cos \delta}{\sin^{\frac{3}{2}} \delta} \left(\frac{\mu(\delta)}{1 - 8 \tan^2 \delta} \right)^{\frac{1}{4}} \left[\exp \left\{ - \frac{k_0 f}{16} \cot^2 \delta (1+Q)^2 \right\} (1+Q)^{\frac{3}{4}} \left(1 - \frac{1}{3}Q \right)^{\frac{3}{4}} \right. \\ \left. + \exp \left\{ - \frac{k_0 f}{16} \cot^2 \delta (1-Q)^2 \right\} (1-Q)^{\frac{3}{4}} \left(1 + \frac{1}{3}Q \right)^{\frac{3}{4}} \right] \quad (13)$$

$$q_0(\delta) = \frac{3^{\frac{3}{4}}}{2^{\frac{1}{4}}} \frac{\cos \delta}{\sin^{\frac{3}{2}} \delta} \left(\frac{\mu(\delta)}{1 - 8 \tan^2 \delta} \right)^{\frac{1}{4}} Q^{-1} \left[\exp\left\{-\frac{k_0 f}{16} \cot^2 \delta (1-Q)^2\right\} (1+Q)^{\frac{3}{4}} \left(1 - \frac{1}{3}Q\right)^{\frac{3}{4}} \right. \\ \left. - \exp\left\{-\frac{k_0 f}{16} \cot^2 \delta (1-Q)^2\right\} (1-Q)^{\frac{3}{4}} \left(1 + \frac{1}{3}Q\right)^{\frac{3}{4}} \right] \quad (14)$$

where $Q = \sqrt{1 - 8 \tan^2 \delta}$.

Thus we obtain the asymptotic expansion of the wave height taking the real part of the integral (12) (instead of imaginary part as in Ursell's (1960) Equation (3.6))

$$\zeta_1 \sim 4k_0 \frac{M}{U} \exp(-k_0 f) \left\{ \frac{p_0(\delta)}{N^{\frac{1}{3}}} A_1(-N^{\frac{2}{3}} \mu(\delta)) \cos(Nv(\delta)) \right. \\ \left. - \frac{q_0(\delta)}{N^{\frac{2}{3}}} A_1'(-N^{\frac{2}{3}} \mu(\delta)) \sin(Nv(\delta)) \right\} \quad (15)$$

which is valid in some finite angle including $\delta = \delta_c$ by the theory proved by Chester et al. (1957). The terms neglected in the asymptotic series (15) are of order $N^{-\frac{4}{3}} A_1$, and $N^{-\frac{5}{3}} A_1'$ at most. (See Appendix 2)

As was pointed out previously, the difference between the wave height due to a pressure point and a doublet is only in the depth effect. Hence, for the case of a submerged doublet, p_0 and q_0 (in Ursell's table) should only be multiplied by corresponding exponential factor, $\exp[-k_0 f (1 + u_+^2)]$ and

$\exp \{-k_0 f (1 + u_-^2)\}$ respectively. Since $u_+ = u_- - \frac{\cot \delta}{4}$ on the line $\delta = \delta_0$, the same factor $\exp \{-k_0 f (1 + \frac{\cot \delta}{4})\}$ applied to p_0 and q_0 would be sufficient in the very close vicinity of the critical line. Namely the wave pattern will be the same in the close vicinity of the critical line except that the wave height is reduced relative to that of the pressure point. However, the wave height due to a submerged point source, Equation (15) is different not only in p_0 and q_0 but also the sine and cosine are exchanged from that of the pressure point (Urabe's (4.12)).

(B) In the Vicinity of the Singularity-

Equation (5) can be written as

$$\begin{aligned}\zeta_1 &= 4k_0 \frac{M}{U} \int_{-\pi/2 + \delta}^{\pi/2} \sec^3 \theta \exp(-k_0 f \sec^2 \theta) \cos(k_0 \omega \sec^2 \theta) d\theta \\ &= 4k_0 \frac{M}{U} \int_{-\pi/2}^{\pi/2} \sec^3 \theta \exp(-k_0 f \sec^2 \theta) \cos(k_0 \omega \sec^2 \theta) d\theta \\ &\quad - 4k_0 \frac{M}{U} \int_{\pi/2 - \delta}^{\pi/2} \sec^3 \theta \exp(-k_0 f \sec^2 \theta) \cos[k_0 R \cos(\theta + \delta) \sec^2 \theta] d\theta\end{aligned}$$

(16)

For the first integral on the right hand side of the above equation, a useful table is available from the Admiralty Research Laboratory (1956). This is derived from the numerical evaluation of the related integral by the method of Wilson (1957). The second term is negligible when $x - x_1$ is large, but in the near field this term may be important. If a high speed calculating machine is used, ζ_1 for reasonably small R/f can be readily evaluated by the use of Gauss' mechanical quadrature formula.

If we change the variable θ by $\tan \theta = u$ as in Equation (12), Equation (16) becomes

$$\begin{aligned} \zeta_1 = & 4k_0 M \exp(-k_0 f) \int_{-\infty}^{\infty} \sqrt{1+u^2} \exp(-k_0 f u^2) \cos[k_0 x \sqrt{1+u^2}] X \\ & X \cos[k_0 y u \sqrt{1+u^2}] du \\ & - 4k_0 M \exp(-k_0 f) \int_{x/f}^{\infty} \sqrt{1+u^2} \exp(-k_0 f u^2) X \\ & X \cos[k_0 R \cos(\arctan u + \delta)(1+u^2)] du \quad (17) \end{aligned}$$

with $x_1 = 0$ for convenience.

The first integral of the right hand side can be evaluated by the Hermite-Gauss quadrature formula for which the weights (Christoffel numbers) and the zeros of the Hermite polynomials calculated by

HYDRONAUTICS, Incorporated

-12-

Kopal are available up to the order 20. For the second integral, if x is small, the limit of the integral may better be changed to

$$\int_{\frac{x}{y}}^{\infty} = \int_0^{\infty} - \int_0^{\frac{x}{y}}$$

When x/y is sufficiently large by the change of variable

$$t = u^2$$

the second integral of the right hand side of Equation (17) will become

$$2 \frac{M}{Uf} \exp \left[-k_o f \left(1 + \frac{x^2}{y^2} \right) \right] \int_0^{\infty} \sqrt{(1+t)} \exp(-t_1) \times \\ \times \cos \left[k_o R \cos(\tan^{-1} \sqrt{t} + \delta)(1+t) \right] \frac{dt}{\sqrt{t}} \quad (18)$$

$$\text{where } t = \frac{t}{k_o f} + \frac{x^2}{y^2}.$$

This can be evaluated by Laguerre-Gauss quadrature for which the weights and the zeros of the Laguerre polynomials obtained by Zalzer and Zucker (1949) are available up to the order 15.

Of course, by using a high speed machine such as the IBM 7090, the other method of direct integration of (17) even with

Simpson's rule is applicable to the extent that the oscillation is rapid and the amplitude is small enough to be neglected. But the speed of calculation also highly depends on the magnitude of R/f . The advantage of the method of Gauss' quadrature lies in its simplicity and in time saving, but the error is extremely difficult to estimate.

EVALUATION OF THE LOCAL DISTURBANCE

The evaluation of the integral (6) representing the local disturbance is also extremely complicated. There has been no analytical form of the result. Even the numerical method is not easy, especially in the vicinity directly above the singularity, because of the slow convergence of the integral. Numerical evaluation of equation (6) was obtained for a certain range of parameters by Wigley(1949). The evaluation can be treated separately in two regions - in the vicinity of the singularity and away from it.

(A) In the Vicinity of the Singularity

At the point immediately above the singularity the integral can be evaluated analytically in closed form. The expression (6), involves a type of integral

$$L_n^{(1)}(p, q, s) = \int_0^\infty \frac{m^{2n} e^{-mp} \cos mq}{s^2 + m^2} dm \quad (19)$$

and

$$L_n^{(2)}(p, q, s) = \int_0^\infty \frac{m^{2n+1} e^{-mp} \sin mq}{s^2 + m^2} dm \quad (20)$$

$$\begin{aligned} \text{for} \quad & p > 0, n > 0 \\ & p \geq 0, n = 0 \end{aligned}$$

which reduce to the well known Laplace integrals (See Erdelyi 1953) when $p = n = 0$

$$L_c^{(2)}(0, q, s) = \frac{\pi}{2} e^{-qs} \quad (21)$$

Fortunately a part of the integral (6), is exactly in this form when $R = 0$ or $\omega = 0$. The other part is of the form $L_1^{(1)}(0, q, s)$ which is the divergent integral. However this can be evaluated as the limit of $R \rightarrow 0$, which can not only be derived formally but also can be justified rigorously without difficulty.

$$\begin{aligned} L_1^{(1)}(0, q, s) &= \lim_{p \rightarrow 0} \int_0^\infty \frac{m^2 e^{-mp} \cos mq}{s^2 + m^2} dm \\ &= \lim_{p \rightarrow 0} \frac{d}{dq} \int_0^\infty \frac{m e^{-mp} \sin mq}{s^2 + m^2} dm \\ &= -\frac{\pi s}{2} e^{-qs} \end{aligned} \quad (22)$$

From Equations (19) - (22),

$$\int_0^\infty \frac{mk_0 \sec^3 \theta \sin(mf)}{k_0^2 \sec^4 \theta + m^2} dm = \frac{\pi}{2} k_0 \sec^3 \theta \exp(-k_0 f \sec^2 \theta)$$

$$\lim_{\bar{R} \rightarrow 0} \int_0^{\infty} \frac{\exp(-mR \cos \theta) m^2 \sec \theta \cos(mf)}{k_0^2 \sec^4 \theta + m^2} dm = -\frac{\pi}{2} k_0 \sec^3 \theta \exp(-k_0 f \sec^2 \theta)$$

Hence from (6)

$$\begin{aligned} \zeta_y &= -\frac{2}{R} \frac{M}{U} \lim_{R \rightarrow 0} \int_{-\pi/2}^{\pi/2} \int_0^{\infty} \frac{\exp(-mR \cos \theta) m \sec \theta}{k_0^2 \sec^4 \theta + m^2} \times \\ &\quad \times [k_0 \sec^2 \theta \sin(mf) - m \cos(mf)] dm d\theta \\ &= -2k_0 \frac{M}{U} \int_{-\pi/2}^{\pi/2} \sec^3(\theta + \delta) \exp[-k_0 f \sec^2(\theta + \delta)] d\theta \end{aligned}$$

where $\theta_0 = \theta + \delta$, but if $\delta = 0$,

$$\zeta_y = -k_0 \frac{M}{U} \exp(-k_0 f/2) [K_0(k_0 f/2) + K_1(k_0 f/2)] \quad (23)$$

where K_0, K_1 are modified Bessel functions of the 2nd kind.

(See, e.g. Lunde 1952, page 33).

It is easy to see that ζ_y is antisymmetric with respect to the y axis. Hence, $\zeta_y = 0$ on $x = 0$ or $\delta = \pi/2$. Besides, ζ_y has a discontinuity in appearance on the line $y = 0$. Physically this is impossible. However, it is obvious in equation (6) that

ζ_ℓ is a continuous function of δ even when $R \rightarrow 0$, taking the value between $\zeta_\ell (R \rightarrow 0, \delta = 0)$ and $\zeta_\ell (R \rightarrow 0, \delta = \pi)$ - $-\zeta_\ell (R \rightarrow 0, \delta = 0)$. This means that, even on $R \rightarrow 0$, the water surface is continuous although the derivative is not so except in the direction $\delta = \pi/2$. Of course, we have to remember that we neglected the viscosity and the surface tension.

When R is very small but not equal to zero, there is no easy method to integrate, even numerically. However, it may be worth while mentioning Barakat's work (1941) on integrating L functions and the use of it here.

Using the notations (19) and (20), Equation (6) can be written,

$$\zeta_\ell = -\frac{2M}{nfU} \int_{-\pi/2}^{\pi/2} [k_o f \sec^3 \theta_o L_o^{(2)} \left\{ \frac{R}{f} \cos \theta, 1, k_o f \sec^2 \theta_o \right\} - \sec \theta_o L_o^{(1)} \left\{ \frac{R}{f} \cos \theta, 1, k_o f \sec^2 \theta_o \right\}] d\theta \quad (24)$$

where $\theta_o = \theta + \delta$.

Barakat changed the L function which has an oscillating integrand into other non-oscillating integrals plus known functions, i.e.

$$L_o^{(1)}(p, q, s) = \frac{(ps)}{2s} e^{-qs} \int_0^{qs} \frac{e^t}{(ps)^2 + t^2} dt - \frac{(ps)}{2s} e^{qs} \int_0^{qs} \frac{e^{-t}}{(ps)^2 + t^2} dt + \frac{1}{s} [C_1(ps) \sin(ps) + \left\{ \frac{\pi}{2} - S_1(rs) \right\} \cos(ps)] e^{-qs} \quad (25)$$

$$\begin{aligned}
L_0^{(2)}(p, q, s) = & \frac{(ps)}{2} e^{-qs} \int_0^{qs} \frac{e^t dt}{(ps)^2 + t^2} + \frac{(ps)}{2} \int_0^{qs} \frac{e^{-t} dt}{(ps)^2 + t^2} \\
& + [C_1(ps) \sin(ps) + \{\frac{\pi}{2} - S_1(ps)\} \cos(ps)] e^{-qs} \quad (26)
\end{aligned}$$

where C_1 and S_1 are cosine and sine integrals respectively, and

$$L_1^{(1)}(p, q, s) = -s^2 L_0^{(1)} + \frac{p}{p^2 + q^2} \quad (27)$$

(See Barakat (1961) Equations (27), (28) and (29)).

If we use Equations (24) - (27), the integrand of Equation (24) can be evaluated at certain points. Then the usual method of integration can be used with respect to θ .

B. When R/f is not too small - the integral (6) converges reasonably well. We may then use a combination of quadrature methods. Equation (6) can be written,

HYDRONAUTICS, Incorporated

$$\zeta_1 = -\frac{2M}{2\pi fU} \int_{-\pi/2}^{\pi/2} \sum_{n=0}^{\infty} \int_{-\pi/2}^{2\pi} \frac{\exp(-m_0 \frac{R}{f} \cos \varphi) m \sin \theta \{k_0^2 \sec^2 \theta_0 \sin m-m_0 \cos m\}}{k_0^2 f^2 \sec^4 \theta_0 + m_0^2} dmd\theta$$

where $m_0 = m + 2n\pi$, $\theta_0 = \theta + \varphi$

$$= -\frac{2M}{\pi fU} \int_{-\pi/2}^{\pi/2} \sum_{n=0}^{\infty} \int_{-\pi/2}^{\pi/2} \left[\frac{\exp\{(-m_1 + 2n\pi) \frac{R}{f} \cos \theta\} (m_1 + 2n\pi)}{k_0^2 f^2 \sec^4 \theta_0 + (2n\pi + m_1)^2} \right]$$

$$- \frac{\exp\{-(m_1 + (2n+1)\pi) \frac{R}{f} \cos \theta\} [m_1 + (2n+1)\pi]}{k_0^2 f^2 \sec^4 \theta_0 + ((2n+1)\pi + m_1)^2} k_0^2 f^2 \sec^3 \theta_0 \cos m dmd\theta$$

$$- \frac{2M}{\pi fU} \int_{-\pi/2}^{\pi/2} \sum_{n=0}^{\infty} \int_{-\pi/2}^{\pi/2} \left[\frac{\exp\{-(m_1 + 2n\pi) \frac{R}{f} \cos \theta\} (m_1 + 2n\pi)^2}{k_0^2 f^2 \sec^4 \theta_0 + (2n\pi + m_1)^2} \right]$$

$$- \frac{\exp \left[- \left(m_1 + (2n+1)\pi \right) \frac{R}{f} \cos \theta \right] \left(m_1 + (2n+1)\pi \right)^2}{k_0^2 f^2 \sec^4 \theta_0 + \left((2n+1)\pi + m_1 \right)^2} \Big] \sec \theta_0 \sin m \, d m d \theta$$

(28)

$$\text{where } m_1 = m + \frac{\pi}{2}.$$

Because of the exponential term, the integrand diminishes rapidly when n increases. We may either use Gauss' or Simpson's quadrature formulas between $-\frac{\pi}{2}$ and $\frac{\pi}{2}$ for both integrals. Especially when $\frac{R}{f} \cos \theta$ is reasonably large, say $>.5$, we may directly apply the Laguerre-Gauss quadrature formula to the integral with respect to m of Equation (6), and then the Legendre-Gauss or Simpson's quadrature formula to the integral with respect to θ .

In Figure 1, the value of (6) is plotted for each Froude number with respect to the depth versus the distance, x/y , where the curves for Froude numbers 1 and .707 are plotted using the table by Wigley for the sake of comparison.

WAVE DUE TO A SUBMERGED SOURCE LINE

The wave height ζ_1 due to a submerged finite source line can be obtained by integrating equations (4), (5) and (6) with respect to the depth f from the top f_1 to the bottom f_2 . The method of evaluating the integrals involved are exactly similar to the case of a point source. If we non-dimensionalize the physical quantities by the depth f_1 of the top of infinite submerged source line, the result can be used for the case of a finite source line by matching the corresponding parameters.

We write

$$\zeta_1 = \zeta_{1r} + \zeta_{1\ell}$$

where ζ_{1r} is the regular wave and $\zeta_{1\ell}$, the local disturbance.

$$\zeta_{1r} = \frac{M}{U} \left[\exp(-k_0 f) \int_0^{\infty} \exp(-k_0 f u^2) (1+u^2)^{-\frac{1}{2}} \cos[k_0 x \sqrt{(1+u^2)}] \cos[k_0 y u \sqrt{(1+u^2)}] \right]$$

$$-\frac{1}{2} \exp(-k_0 f) \int_0^{\infty} \exp(-k_0 f u^2) (1+u^2)^{-\frac{1}{2}} \cos(k_0 R \cos(\arctan u + \theta)) \cos(k_0 y u \sqrt{(1+u^2)}) du \Big]_{f_2}^{f_1}$$

where M_1 is the strength of the source line per unit length.

HYDRONAUTICS, Incorporated

$$\zeta_{12} = -\frac{2M}{\pi U} \int_{-\pi/2}^{\pi/2} \int_0^{\infty} \frac{\exp(-mR \cos \theta) \sec \theta (k_0 \sec^2 \theta \cos mf + m \sin mf)}{k_0^2 \sec^4 \theta_1 + m^2} dmd\theta \quad \begin{matrix} f=f_1 \\ f=f_2 \end{matrix}$$

$$= \left[\frac{2M}{\pi U} \int_{-\pi/2}^{\pi/2} \sum_{n=0}^{\infty} \int_{-\pi/2}^{\pi/2} \left\{ \frac{\exp[-(m_1 + 2n\pi) \frac{R}{f} \cos \theta]}{k_0^2 f^2 \sec^4 \theta_1} \right\} \right]$$

-21-

$$\frac{\exp[-(m_1 + (2n+1)\pi) \frac{R}{f} \cos \theta]}{k_0^2 f^2 \sec^4 \theta_1 + [m_1 + \pi(2n+1)]^2} \left. \right\} k_0 f \sec^3 \theta_1 \sin m d m d \theta$$

$$-\frac{2M}{\pi U} \int_{-\pi/2}^{\pi/2} \sum_{n=0}^{\infty} \int_{-\pi/2}^{\pi/2} \left\{ \frac{\exp[-(m_1 + 2n\pi) \frac{R}{f} \cos \theta] (m_1 + 2n\pi)}{k_0^2 f^2 \sec^4 \theta_1 + (m_1 + 2n\pi)^2} \right\}$$

$$-\frac{\exp[-(m_1 + \pi(2n+1)) \frac{R}{f} \cos \theta] (m_1 + (2n+1)\pi)}{k_0^2 f^2 \sec^4 \theta_1 + [m_1 + \pi(2n+1)]^2} \left. \right\} \times$$

$$\times \sec \theta_0 \cos m d m d \theta \quad \begin{matrix} f=f_1 \\ f=f_2 \end{matrix}$$

where $\theta_0 = \theta + \delta$, $m_1 = m + \frac{\pi}{2}$

At $R \rightarrow 0$

$$\zeta_{1,l} = -\frac{2M_1}{U} \int_{-\pi/2}^{\pi/2} \sec \theta_0 (\exp(-k_0 f_1 \sec^2 \theta_0) - \exp(-k_0 f_2 \sec^2 \theta_0)) d\theta$$

where $\theta_0 = \theta + \delta$. When $\delta = 0$ and $R \rightarrow 0$.

$$\begin{aligned} \zeta_{1,l} = & -\frac{2M_1}{U} [\exp(-k_0 f_2/2) K_0(k_0 f_2/2) \\ & - \exp(-k_0 f_1/2) K_0(k_0 f_1/2)] \end{aligned}$$

Figures 2 and 3 show the local disturbance for the submerged infinite source line for the different distances x/f_1 versus Froude number with respect to f_1 , and for the different Froude numbers versus x/f_1 respectively.

WAVES DUE TO A SUBMARINE

If we represent the submarine hull by a Rankine ovoid and the sail of the submarine by a combination of a source line and a sink line, the wave height due to the submarine can be obtained by the methods described above. In Figure 4, the dimensions of the submarine to be used as an example are shown. Figure 5 shows the corresponding positions and strengths of a point source and a point sink for the hull, and a source line and a sink line for the sail. These are obtained using the theory of Rankine's

solids (see e.g. Milne-Thomson page 441) for the hull, and the two dimensional theory (see Milne-Thomson page 203) for the sail, which is approximately valid. All figures related to the submarine are shown with dimensional quantities. Figure 6a shows the amplitude of the regular wave immediately behind and 5 wave lengths behind the stern for several depths. Since the wave length is $2\pi V^2/g$ as shown in Equation (11.1), the interactions between the sources and the sinks of the hull and sail cause the wiggling of the curve. The effect of speed on the wave height is so great that 5 cycle semi-log paper is used to plot the amplitudes.

Figure 6b shows the comparison of the amplitudes due to hull and sail at a distance 5 wave lengths behind the stern. We can see that the sail waves are dominant up to a speed of about 11 knots for each depth, while the hull waves become gradually dominant with increasing speed above 11 knots.

In Figures 7-11 the wave heights near the submarine are plotted for several angles from the bow of the sail or the bow of the hull. The two Figures 7 and 8 of these five figures are transformed to contour diagrams in Figures 12 and 13. As was shown in Equation (15), for large N , the wave in the vicinity of the critical line decays like $N^{-\frac{1}{3}}$ while the wave in $\delta \ll \delta_c$ decays like $N^{-\frac{1}{2}}$ where $N = k_0 R$. In the vicinity of the submarine, it is noticeable that the transverse wave is first prominent and gradually the divergent wave becomes more prominent when the distance increases.

In Figures 14 - 17 the local disturbance on the centerline due to the sail is plotted. The local disturbance due to a point source or a line source is antisymmetric with respect to

HYDRONAUTICS, Incorporated

-24-

the axis perpendicular to the velocity through the projection of the singularity on the mean free surface, as shown before. The local disturbance due to a sink is exactly opposite in sign. Therefore, the local disturbance due to the sail or the hull is exactly symmetric with respect to the midsail or the midship plane. Figure 18 shows the local disturbances in different directions.

In Figures 19 - 22 the local disturbance due to the hull is plotted for different depths and different speeds.

APPENDIX 1

To evaluate

$$-\phi_x = \frac{1}{2\pi} \int_{-\pi}^{\pi} \int_0^{\infty} \frac{12k_0 k \sec \theta \exp[k(i\omega - f)]}{k - k_0 \sec^2 \theta - i\mu \sec \theta} dk d\theta$$

$$\omega = (x - x_1) \cos \theta + y \sin \theta$$

$$= R \cos (\theta - \delta)$$

$$\delta = \arctan \left(\frac{y}{x - x_1} \right)$$

Note the only singularity at $k = k_0 + i\mu \sec \theta$,

where $\sec \theta > 0$ for $-\frac{\pi}{2} < \theta < \frac{\pi}{2}$

$\sec \theta < 0$ for $\frac{\pi}{2} < \theta \leq \pi$, $-\pi < \theta < -\frac{\pi}{2}$

when $\omega > 0$ or $-\frac{\pi}{2} + \delta < \theta < \frac{\pi}{2} + \delta$, we take the contour ABO instead of OA in Figure A1. When $\omega < 0$, or $\frac{\pi}{2} + \delta < \theta < \pi$ and $-\pi < \theta < -\frac{\pi}{2} + \delta$, we take the contour ACO instead of OA.

Then the singularity in the case $-\frac{\pi}{2} < \theta < -\frac{\pi}{2} + \delta$ and

$\frac{\pi}{2} < \theta < \frac{\pi}{2} + \delta$ is outside the contour. Thus we obtain:

HYDRONAUTICS, Incorporated

$$-\phi_x = - \left[\int_{-\frac{\pi}{2} + \delta}^{\frac{\pi}{2}} - \int_{-\pi}^{-\frac{\pi}{2} + \delta} \right] 2 k_o^2 \sec^3 \theta \exp [k_o \sec^2 \theta (i\omega - f)] d\theta$$

$$- \frac{1}{2\pi} \int_{-\frac{\pi}{2} + \delta}^{\frac{\pi}{2} + \delta} \int_{-\frac{\pi}{2}}^{\frac{\pi}{2}} \frac{12 k_o m \sec \theta \exp [im(i\omega - f)]}{im - k_o \sec^2 \theta} dm d\theta$$

$$= - \frac{1}{2\pi} k_o^2 \int_{-\frac{\pi}{2} + \delta}^{\frac{\pi}{2}} \sec^3 \theta \exp (-k_o f \sec^2 \theta) \cos (k_o \omega \sec^2 \theta) d\theta$$

$$- \frac{4}{2\pi} \int_{-\frac{\pi}{2} + \delta}^{\frac{\pi}{2} + \delta} \int_{-\frac{\pi}{2}}^{\frac{\pi}{2}} \frac{m \sec \theta \exp(-m\omega) (k_o \sec^2 \theta \sin mf - m \cos mf)}{k_o^2 \sec^4 \theta + m^2} dm d\theta$$

APPENDIX 2

To apply the method of steepest descent to Equation (12), first Debye's curves through two saddle points are given by Peters (1949) in his Figures 5, 6 and 7. These are the roots of

$$\frac{df}{du}(u, \delta) \equiv \frac{d}{du} [(\cos \delta - u \sin \delta) \sqrt{1 + u^2}] = 0 \quad (A1)$$

Namely, the points

$$\delta_+(\delta) = \frac{1}{4} [\cot \delta + \sqrt{(\cot^2 \delta - \delta)}]$$

and

$$\delta_-(\delta) = \frac{1}{4} [\cot \delta - \sqrt{(\cot^2 \delta - \delta)}] \quad (A2)$$

By the method of Chester et al. (1957), the integral can be expressed in terms of the Airy function (see Jeffreys and Jeffreys 1946 § 17.07).

$$\begin{aligned} A_1(Z) &= \frac{1}{2\pi i} \int_{\infty \exp(-\frac{1}{3}\pi i)}^{\infty \exp(\frac{1}{3}\pi i)} \exp\left(\frac{1}{3}t^3 - Zt\right) dt \\ &= \frac{1}{\pi} \int_0^{\infty} \cos\left(\frac{1}{3}t^3 + Zt\right) dt \end{aligned} \quad (A3)$$

where Z is real, we transform the variable u by

$$F(u, \delta) \equiv (\cos \delta - u \sin \delta) \sqrt{1 + u^2} = -\frac{1}{3}v^3 + \mu(\delta)v^{1/2}(\delta) \quad (A4)$$

which is proved to be a regular one-to-one transformation if the zeros of Equation (1), $u_{\pm}$ and the zeros of

$$\frac{2F(u, \delta)}{du} \frac{du}{dv} = -v^2 + \mu(\delta) = 0 \quad (A5)$$

or

$$v = \pm \mu^{\frac{1}{2}} \quad (A6)$$

correspond. Urseil (1960) calculated $\mu(\delta)$ and $v(\delta)$ for each δ near δ_c , which can be used here without any change. Now the analytic function $g(v) \frac{du}{dv}$ in Equation (12a) or the corresponding expression in Equation (12)

$$\exp(-k_0 f u^2) (1 + u^2)^{\frac{1}{2}} du/dv \quad (A7)$$

is expanded in the form

$$\sum_{m=0}^{\infty} p_m(\delta) (v^2 - \mu(\delta))^m + v \sum_{m=0}^{\infty} q_m(\delta) (v^2 - \mu(\delta))^m \quad (A8)$$

which holds uniformly when v and $\delta - \delta_c$ are sufficiently small. Coefficients p_m 's and q_m 's can be found by repeatedly differentiating both sides and putting $u = u_{\pm}$ and $v = \pm \mu^{\frac{1}{2}}$. Then the asymptotic expansion of the integral (12) is shown to be

$$\begin{aligned} & \sum p_m(\delta) \int (v^2 - \mu(\delta))^m \exp\{iN(-\frac{1}{3}v^3 + \mu v - v)\} dv \\ & + \sum q_m(\delta) \int v(v^2 - \mu(\delta))^m \exp\{iN(-\frac{1}{3}v^3 + \mu v - v)\} dv \end{aligned} \quad (A9)$$

where the integration can be extended with a negligible error from $-\infty \exp(\frac{\pi}{6})$ to $\infty \exp(-\frac{\pi}{6})$ (cf Peters Figure 6). To obtain the dominant term it is sufficient to calculate the leading coefficients $p_0(\delta)$ and $q_0(\delta)$. Putting $u = u_{\pm}(\delta)$, $v = \pm \mu^{\frac{1}{2}}(\delta)$ in Equation (19), we obtain

$$\exp(-k_0 f u^2_{\pm})(1 + u^2_{\pm})^{\frac{1}{2}} \left(\frac{du}{dv}\right)_{\pm} = p_0(\delta) \pm \mu^{\frac{1}{2}}(\delta) q_0(\delta) \quad (A10)$$

where $\left(\frac{du}{dv}\right)_{\pm}$ can be obtained as follows:

$$\frac{\delta^2 F}{\delta u^2} \left(\frac{du}{dv}\right)^2 + \frac{\delta F}{\delta u} \frac{d^2 u}{dv^2} = -2v$$

whence
$$\left(\frac{\delta^2 F}{\delta u^2}\right)_{\pm} \left(\frac{du}{dv}\right)_{\pm}^2 = \mp 2 \mu^{\frac{1}{2}}$$

If we put $Q \equiv \sqrt{1 - 8 \tan^2 \theta}$, from (A2)

$$u_{\pm} = \frac{\cot \theta}{4} (1 \pm Q)$$

and
$$1 + u^2_{\pm} = \frac{3}{16} \cot^2 \theta (1 \pm Q) \left(1 \mp \frac{1}{3} Q\right) \quad (A11)$$

From (A4)
$$\left(\frac{\delta^2 F}{\delta u^2}\right)_{\pm} = \mp \frac{4}{3^{\frac{1}{2}}} \sin \theta Q (1 \pm Q)^{-\frac{1}{2}} \left(1 \mp \frac{1}{3} Q\right)^{-\frac{1}{2}}$$

Hence
$$\left(\frac{dv}{du}\right)_{\pm} = \frac{3^{\frac{1}{4}}}{2^{\frac{1}{2}}} \frac{\mu^{\frac{1}{4}}}{\sin^{\frac{1}{2}} \theta} Q^{-\frac{1}{2}} (1 \pm Q)^{\frac{1}{4}} \left(1 \mp \frac{1}{3} Q\right)^{\frac{1}{4}} \quad (A12)$$

From (A11) and (A12)

$$\begin{aligned} & \exp(-k_o^f u_+^2)^{\frac{1}{2}} \left(\frac{du}{dv} \right)_+ \\ &= \exp\left[-\frac{k_o^f}{16} \cot^2 \delta (1+Q)^2\right] \frac{3^{\frac{1}{2}} \cos \delta}{2^{\frac{1}{2}} \sin^2 \delta} \left(\frac{\mu(\theta)}{1-8 \tan^2 \delta} \right)^{\frac{1}{2}} (1+Q)^{\frac{1}{2}} \left(1+\frac{1}{3}Q\right)^{\frac{1}{2}} \end{aligned} \quad (A13)$$

Solving the simultaneous equations in (A10)

$$\begin{aligned} p_o(\theta) &= \frac{3^{\frac{1}{2}} \cos \delta}{2^{\frac{1}{2}} \sin^2 \delta} \left(\frac{\mu(\theta)}{1-8 \tan^2 \delta} \right)^{\frac{1}{2}} \left[\exp\left[-\frac{k_o^f}{16} \cot^2 \delta (1+Q)^2\right] (1+Q)^{\frac{1}{2}} \left(1-\frac{1}{3}Q\right)^{\frac{1}{2}} \right. \\ & \quad \left. + \exp\left[-\frac{k_o^f}{16} \cot^2 \delta (1-Q)^2\right] (1-Q)^{\frac{1}{2}} \left(1+\frac{1}{3}Q\right)^{\frac{1}{2}} \right] \end{aligned} \quad (A14)$$

$$\begin{aligned} q_o(\theta) &= \frac{3^{\frac{1}{2}} \cos \delta}{2^{\frac{1}{2}} \sin^2 \delta} \left(\frac{\mu(\theta)}{1-8 \tan^2 \delta} \right)^{\frac{1}{2}} Q^{-1} \left[\exp\left[-\frac{k_o^f}{16} \cot^2 \delta (1+Q)^2\right] (1+Q)^{\frac{1}{2}} \left(1-\frac{1}{3}Q\right)^{\frac{1}{2}} \right. \\ & \quad \left. - \exp\left[-\frac{k_o^f}{16} \cot^2 \delta (1-Q)^2\right] (1-Q)^{\frac{1}{2}} \left(1+\frac{1}{3}Q\right)^{\frac{1}{2}} \right] \end{aligned} \quad (A15)$$

where $Q = \sqrt{1 - 8 \tan^2 \delta}$.

Putting these p_0 and q_0 into Equation (A9) we obtain the first two terms of the asymptotic expansions of the integral (12)

$$2\pi i \exp(-iNv(\delta)) \left[iN^{-\frac{1}{3}} p_0(\delta) A_1(-N^{\frac{2}{3}} \mu(\delta)) \right. \\ \left. + N^{-\frac{2}{3}} q_0(\delta) A_1'(-N^{\frac{2}{3}} \mu(\delta)) \right]$$

Then the asymptotic expansion of ζ_1 is obtained taking the real part

$$\zeta_1 = 4k_0 M \exp(-k_0 f) \left[\frac{p_0(\delta)}{N^{\frac{1}{3}}} A_1(-N^{\frac{2}{3}} \mu(\delta)) \cos(Nv(\delta)) \right. \\ \left. - \frac{q_0(\delta)}{N^{\frac{2}{3}}} A_1'(-N^{\frac{2}{3}} \mu(\delta)) \sin(Nv(\delta)) \right] \quad (A16)$$

which is valid in some finite angle including $\delta = \delta_c$.

Since (A9) can be rearranged in the form

$$\frac{A_1'(-N^{\frac{2}{3}} \mu)}{N^{\frac{1}{3}}} \approx \frac{a_n(\mu)}{N^{2n}} + \frac{A_1'(-N^{\frac{2}{3}} \mu)}{N^{\frac{2}{3}}} \sum \frac{b_n(\mu)}{N^{2n}} \\ + \frac{A_1'(-N^{\frac{2}{3}} \mu)}{N^{\frac{2}{3}}} \sum \frac{c_n(\mu)}{N^{2n}} + \frac{A_1'(-N^{\frac{2}{3}} \mu)}{N^{\frac{4}{3}}} \approx \frac{b_n(\mu)}{N^{2n}}$$

(See Chester et al. (1957)).

HYDRONAUTICS, Incorporated

-32-

where the first two terms come from the first summation related to p_m of expression (A9) and the other two from the first related to q_m in (A9). Hence the terms neglected in (A16) by taking only $m = 0$ are of order $N^{-\frac{4}{3}} A_1$ and $N^{-\frac{5}{3}} A_1$ at most.

REFERENCES

Admiralty Research Laboratory, Teddington, Middlesex England,
Tables of

$$\int_0^{\pi/2} \exp(-\alpha^2 \sec^2 \theta) \sec^n \theta \frac{\cos}{\sin} (\beta \sec \theta) d\theta$$

A.R.L./T.9/Math 2.7 - November 1955.

Barakat, R., On a Class of Integrals Related to Those of Raabe and Laplace Occurring in the Theory of ... Waves, J. of Math. and Phys. Vol XL pp 244-248, 1961.

Chester, C., Friedman, N., and Ursell, F. Proc. Camb. Phil. Soc. 53. pp 399-511, 1957.

Erdelyi, A., (editor) Higher Transcendental Functions, Vol. 2 McGraw-Hill Book Company, New York, 1953.

Havelock, T. H., The Propagation of Groups of Waves in Dispersive Media with Application to Waves on Water Produced by a Travelling Disturbance, Proc. Roy. Soc. A, 81 pp 398-430, 1908.

Havelock, T. H., The Wave Pattern of a Doublet in a Stream, Proc. Roy. Soc. A 121, pp 515-23, 1928.

Havelock, T. H., Ship Waves: the Calculation of Wave Profiles, Proc. Roy. Soc. A 135, pp 1-13, 1932.

Hogner, E., Ark. Mat. Astr. Fys. 17, No. 12, 1-50, 1923.

Hogner, E., Ark. Mat. Astr. Fys. 16, No. 10, 1-9, 1924.

Hogner, E., Proc. Roy. Soc. A 155 p 292, 1936.

Jinnaka, T., Wave Patterns and Ship Waves, J. S. N. A. Japan 60th Anniversary Series Vol. 2 Tokyo, 1957

Lamb, H., Hydrodynamics, Dover Pub. New York, N. Y., 1945.

HYDRONAUTICS, Incorporated

-34-

- Lunde, J. K., On The Theory of Wave Resistance and Wave Profile, Skipsmodelltankens Meddelse NR 10, p 34, April 1952.
- Lunde, J. K., On The Linearized Theory of Wave Resistance for Displacement Ships in Steady and Accelerated Motion, Tran. Soc. Naval Arch. and Mar. Engrs. 59 pp 24-85, 1951.
- Milne-Thomson, L. M., Theoretical Hydrodynamics, Third Edition, The MacMillan Company, New York, 1955.
- Peters, A. S., A New Treatment of the Ship Wave Problem Comm. on Pure and Applied Math. Vol. 2 No. 2-3 pp 123-148, 1948.
- Thomson, W., (Lord Kelvin) Proc. Roy. Soc. 42 p 27, 1837.
- Ursell, F., Kelvin's Ship-Wave Pattern, J. of Fluid Mech. of Part 3 pp 418-431, July 1960.
- Wigley, C., A.T.M.A. (Paris) Vol. 48 p 533, 1949.
- Wigley, C., A Note On the Use of Tables of a Certain Integral in Connection with Wave Making Calculations, TINA p 378, 1949.
- Wigley, C., Proc. 3rd International Congress of Applied Mech. Stockholm Vol. 1 pp 58-73, 1930.
- Wilson, E. M., A Family of Integrals Occurring in the Theory of Water Waves. The Quart. Journal of Mech. and Applied Math. Vol. 10 part 2, May 1957.




FIGURE 1- NON-DIMENSIONAL LOCAL DISTURBANCE DUE TO A SUBMERGED POINT SOURCE




FIGURE 2 - LOCAL DISTURBANCE DUE TO AN INFINITE SOURCE LINE




FIGURE 3 - LOCAL DISTURBANCE DUE TO AN INFINITE SOURCE LINE

HYDRONAUTICS, INCORPORATED




FIGURE 4 - TYPICAL SUBMARINE USED IN SUBMARINE WAVE STUDIES




FIGURE 5 - POSITIONS OF SOURCE AND SINK




FIGURE 6a - AMPLITUDE OF REGULAR WAVES ON THE CENTERLINE




FIGURE 6b - AMPLITUDE OF REGULAR WAVES ON THE CENTERLINE
FIVE WAVE LENGTHS AFT OF STERN




FIGURE 7 - REGULAR WAVE, DUE TO SUBMARINE WITH SAIL
 $J = 7.5$ KNOTS
 $\eta = 58$ FT.




FIGURE 8 - REGULAR WAVES DUE TO SUBMARINE WITH SAIL

$U = 15$ KNOTS
 $L = 83$ FT.




FIGURE 9 - REGULAR WAVE DUE TO SUBMARINE WITH SAIL
 $U = 12.5$ KNOTS
 $H = 83$ FT.




FIGURE 10 - REGULAR WAVE DUE TO SUBMARINE WITH SAIL
 U - 12.5 KNOTS
 H - 108 FT




FIGURE 11—REGULAR WAVE DU_c TO SUBMARINE WITH SAIL
 $U = 17.5$ KNOTS
 $H = 12.8$ FT.




FIGURE 12 -- CONTOURS OF WAVE HEIGHT (FT) DUE TO SUBMARINE NEAR THE SAIL
 $U = 7.5 \text{ KNO}''\text{S}$, $H = 58 \text{ FT}$




FIGURE 13 - CONTOURS OF WAVE HEIGHT (FT) DUE TO SUBMARINE
 $U = 15$ KNOTS, $H = 83$ FT




FIGURE 14 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO SAIL ALONE
 $H_s = 25$ FT.




FIGURE 15 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO SAIL ALONE
 $H_s = 50$ FT




FIGURE 16 -- LOCAL DISTURBANCE ALONG CENTERLINE DUE TO SAIL ALONE
 $H_s = 75$ FT.




FIGURE 17 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO SAIL ALONE
 $H_s = 100$ FT




FIGURE 18 -- LOCAL DISTURBANCE DUE TO SAIL ALONE

$U = 5 \text{ KNOTS}, H_s = 25 \text{ FT}$




FIGURE 19 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO HULL ALONE
H = 53 FT.




FIGURE 20 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO HULL ALONE
 $H = 83$ FT.




FIGURE 2 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO HULL ALONE
 $H = 108$ FT.




FIGURE 22 - LOCAL DISTURBANCE ALONG CENTERLINE DUE TO HULL ALONE
 $H = 133 \text{ FT}$




FIGURE A1 - CONTOUR OF INTEGRATION

HYDRONAUTICS, Incorporated

DISTRIBUTION LIST

Chief of Naval Research Department of the Navy Washington 25, D. C. Attn: Codes 438	(1)	Commanding Officer and Director David Taylor Model Basin Washington 7, D. C.	(1)
416	(1)	Director	
461	(1)	Naval Research Laboratory	
407V	(1)	Washington 25, D. C.	
104	(1)	Attn: Codes 2000	(1)
406T	(1)	5500	(1)
402C	(1)	6100	(1)
427	(1)	2020	(1)
400	(1)	2027	(6)
446	(1)	5300	(1)
466	(1)	7300	(1)
		5000	(1)
Commanding Officer Office of Naval Research Branch Office 495 Summer Street Boston 10, Massachusetts	(1)	Chief, Bureau of Ships Department of the Navy Washington 25, D. C.	
Commanding Officer Office of Naval Research Branch Office 86 East Randolph Street Chicago 1, Illinois	(1)	Attn: Codes 305	(1)
Commanding Officer Office of Naval Research Branch Office 207 West 24th Street New York 11, New York	(1)	335	(1)
		370	(1)
		374	(1)
		421	(1)
Commanding Officer Office of Naval Research Branch Office 1030 East Green Street Pasadena 1, California	(1)	Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D. C.	
Commanding Officer Office of Naval Research Branch Office 1000 Geary Street San Francisco 9, California	(1)	Attn: Codes RU	(1)
		RU-2	(1)
		RU-31	(1)
		RUDC	(1)
		RUDC-#3	(1)
		RRRE-4	(1)
		Chief of Naval Operations Department of the Navy Washington 25, D. C.	
		Attn: Codes OP-71B	(1)
		OP-07C	(1)
		OP-07T	(1)
		OP-717	(1)

HYDRONAUTICS, Incorporated

-2-

Commanding Officer	New York University
U. S. Naval Ordnance Laboratory	Department of Oceanography
Corona, California (1)	University Heights
Commander	New York 53, New York
U. S. Naval Ordnance Test Station	Attn: Prof. J.W. Pierson, Jr (1)
Pasadena Annex	The Johns Hopkins University
3202 E. Foothill Boulevard	Baltimore 18, Maryland
Pasadena 8, California (1)	Attn: Prof. O.M. Phillips (1)
Superintendent	California Institute of
U. S. Naval Postgraduate School	Technology
Monterrey, California	Pasadena 4, California
Attn: Library (1)	Attn: Prof. T.Y. Wu (1)
Commanding Officer and Director	University of California
Naval Electronic Laboratory	Berkeley 4, California
San Diego 52, California (1)	Attn: Prof. E.V. Laitone (1)
Office of Technical Services	Director
Department of Commerce	Scripps Institution of
Washington 25, D. C. (1)	Oceanography
Defense Documentation Center	Applied Oceanography Group
Arlington Hall Station	University of California
Arlington 12, Virginia (10)	LaJolla, California (1)
Fluid Mechanics Section	Iowa Institute of Hydraulic
National Bureau of Standards	Research
Washington 25, D. C.	State University of Iowa
Attn: Dr. G.E. Schubauer (1)	Iowa City, Iowa
National Academy of Sciences	Attn: Prof. H. Rouse (1)
National Research Council	Prof. P.G. Hubbard (1)
2101 Constitution Ave., N.W.	Harvard University
Washington 25, D. C. (1)	Cambridge 38, Massachusetts
National Research Council	Attn: Prof. G.P. Carrier (1)
Montreal Road	Massachusetts Institute of
Ottawa 2, Canada	Technology
Attn: Mr. E. S. Turner (1)	Cambridge 39, Massachusetts
Institute of Mathematical	Attn: Prof. A.T. Ippen (1)
Sciences	Brown University
New York University	Providence 12, Rhode Island
25 Waverly Place, New York 3, N.Y.	Attn: Dr. R.E. Meyer (1)
Attn: Prof. J.J. Stoker (1)	
Prof. J. Keller (1)	

HYDRONAUTICS, Incorporated

-3-

Stevens Institute of
Technology

Davidson Laboratory
Hoboken, New Jersey

Attn: Mr. D. Savitsky (1)

Dr. S.J. Lukasik (1)

Director

Woods Hole Oceanographic
Institute

Woods Hole, Massachusetts (1)

Dr. B. Zarwyn

Airborne Instruments

Laboratory

Division of Cutler-Hammer Inc.

Walt Whitman Road, Melville

Long Island, New York (1)

Mr. Myron J. Block

Block Associates, Inc.

385 Putnam Avenue

Cambridge 39, Mass. (1)

Director

Hudson Laboratories

Dobbs Ferry, New York (1)

Dr. Savet

American Bosch Arms Corp.

Arms Division

Garden City, New York (1)

Dr. Ira Dyer

Bolt, Beranek, and

Newman, Inc.

50 Moulton Street

Cambridge, Massachusetts (1)

HYDRONAUTICS, Incorporated

Pindell School Road

Howard County

Laurel, Maryland

Attn: Mr. P. Eisenberg, Pres. (1)

Mr. M.F. Tulin, V. Pres. (1)

Dr. L. L. Higgins

Space Technology Laboratories, Inc.

Canoga Park Facility

8433 Fallbrook Avenue

Canoga Park, California (1)