

UNCLASSIFIED

AD 4 3 7 6 3 0

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

437630

437630



EDGERTON, GERMESHAUSEN & GRIER, INC.

PRE-BANSHEE CALIBRATION DETONATION

MAY 5 1964

Authors:

Clyde B. Dobbie

Charles S. Fitzgerald

Edgerton, Germeshausen & Grier, Inc.
Boston, Massachusetts

EG&G Report No. B-2687
CONTRACT NO. DA49-146-XZ-092

This work was accomplished under
NWER Subtask 01.001 for the
Defense Atomic Support Agency
Washington 25, D. C.

437630

BOSTON AND SALEM, MASSACHUSETTS
LAS VEGAS, NEVADA • SANTA BARBARA, CALIFORNIA

"This report has been approved for open publication
by the Department of Defense, Office of the Assistant
Secretary of Defense (Public Affairs). "

"Qualified requestors may obtain
copies of this report from DDC. "

11 December 1963

DASA Report 1446

PRE-BANSHEE CALIBRATION DETONATION

Authors:

Clyde B. Dobbie
Charles S. Fitzgerald

Edgerton, Germeshausen & Grier, Inc.
Boston, Massachusetts

EG&G Report No. B-2687
CONTRACT NO. DA49-146-XZ-092

This work was accomplished under
NWER Subtask 01.001 for the
Defense Atomic Support Agency
Washington 25, D. C.

ABSTRACT

Electromagnetic measuring equipment was installed at Aberdeen Proving Grounds, Maryland, and operated during the sea level detonation of a spherical 500 pound Pentolite charge. The purpose of this project was to check the operational readiness of the equipment to be used during the BANSHEE test series, to obtain some indication of its EM detecting capabilities, and additionally to obtain a crude measure of the EM signal generated by such a detonation for use in future calibrations.

Each set of equipment used consisted of three mutually orthogonal loop antennae, low level amplifiers and matching networks, a 4-channel tape recorder, and a Fiducial generator Type TD-2A.

A signal was detected on only one antenna which was located 1,000 feet from the detonation. There are uncertainties regarding the source and character of the detected signal which have not been resolved.

ACKNOWLEDGEMENT

The authors wish to acknowledge the efforts of James R. Mazurek, their associate at EG&G, Inc. , in contributing to this project. Mr. Mazurek was responsible for the assembling of the equipment in Boston, for seeing to its safe arrival at Aberdeen Proving Grounds, Maryland, and for the installation and initial checkout of the equipment when it arrived.

Additionally, Mr. Mazurek performed some of the initial data analysis.

TABLE OF CONTENTS

ABSTRACT	iii
CHAPTER 1 INTRODUCTION	1
CHAPTER 2 PROCEDURE	3
Calibration	3
Measured Data	5
CHAPTER 3 RESULTS	9
CHAPTER 4 CONCLUSIONS	13
APPENDIX A ELECTROMAGNETIC RECORDING SYSTEM XSY-30	A1
A. 1 General	A1
A. 2 Radio Tone Receiver	A2
A. 3 Power Distribution Rack	A3
A. 4 Antenna Section	A3
A. 5 Recording Rack	A3
APPENDIX B FIDUCIAL MARKER TD-2A	B1
FIGURES	
1 Time rate of change of magnetic field $\left(\frac{dH}{dt}\right)$ detected by horizontal loop antenna 1,000 feet from detonation	7
2 The magnetic field (H) detected by the horizontal loop antenna, 1,000 feet from detonation	8
A. 1 EMR System, block diagram	A2
A. 2 Power Distribution Rack	A4
A. 3 Antenna Section	A5

TABLE OF CONTENTS (Continued)

FIGURES

A. 4	Recording Rack	A6
A. 5	Power Supply schematic, Electromagnetic Recording System XSY-30	A7
A. 6	Functional diagram, Electromagnetic Recording System	A9
B. 1	Circuit diagram, Fiducial Marker TD-2A	B2

CHAPTER 1

INTRODUCTION

The purpose of making electromagnetic (EM) measurements during the Banshee series was to determine if a significant amount of EM energy is generated by the expulsion of the earth's magnetic field as a result of the expansion of the detonation wave front within, and the expansion of the shock front in the atmosphere outside of an explosive charge. The measurements would test the Magnetic Bubble Theory of EM Generation proposed by Dr. R. C. O' Rourke of EG&G.

Prior to EG&G's participation in Phase II of the Banshee HE test series at White Sands Missile Range (WSMR), the equipment to be used was installed at the Aberdeen Proving Grounds and operated during the detonation of a 500 pound spherical charge of pentolite. The purpose of this Pre-Banshee Calibration detonation was to check the operational readiness of the EM monitoring system to be used during Project Banshee and to obtain a crude measure of the EM signal generated by a high explosive (HE) detonation at sea level. These close-in EM measurements would then be used as a basis for predicting signal strengths and determining the sensitivity settings of the monitoring equipment to be used during the Banshee tests.

The EM detecting and recording equipment was that which was designed and constructed for the proposed "Lollipop" nuclear event which was to take place at some later date. There were two identical systems each consisting of a set of three mutually orthogonal loop antennas, low level amplifiers and matching networks, and a 4-channel tape recorder. A detailed description of this system is given in Appendix A of this report.

A fiducial pulse, used for time correlation between photographic and EM data, was supplied by an EG&G type TD-2A Fiducial Marker, which is described in Appendix B.

CHAPTER 2

PROCEDURE

Antennae sets were located approximately 1,000 feet and 1350 feet from the point of detonation. Each antenna set was oriented with one loop horizontal, one loop vertical and normal to the line of sight between it and the charge, and the third loop with its plane coincident with the vertical plane containing the charge and the antenna set. The two antennas were on a magnetic bearing of approximately 290° from the charge.

The EM recording equipment was housed in Building 1196 on Spesutic Island at a distance of approximately 1200 feet from the 500 pound HE charge. Each antenna section relayed the received signals to the Recording Rack. The signals were amplified at the antennas and at the Recording Rack prior to being recorded on magnetic tape. The Recording Rack also contained provisions for a manual check out of the entire system (see Appendix A).

In addition to the foregoing, the TD-2A detected the flash of the detonation to be used as a correlation between the photographic and EM data. The output from the TD-2A was a time signal fiducial pulse which was applied to the timing channel of each tape recorder (see Appendix B).

CALIBRATION

The system was calibrated by the shield injection method. A current was driven through the electrostatic shield of each antenna to produce a known total flux of a known frequency at the antenna coil.

This magnetic flux, $\phi(t)$, as a function of time, was of the form

$$\phi(t) = \Phi_o \sin (400 \times 2\pi t) \quad \text{oersteds} \quad (1)$$

where

Φ_o is the peak magnitude of the magnetic flux

The output from the antenna is proportional to the rate of change of flux. This is shown by

$$\begin{aligned} e_{\text{out}} &= -K_1 \frac{d\phi}{dt} \\ &= -K_1 \Phi_o 800\pi \cos 800\pi t \end{aligned} \quad (2)$$

where

e_{out} is the voltage out of the terminals of the sensing loop

$\frac{d\phi}{dt}$ is the rate of change of flux with respect to time
in oersteds/sec

and

K_1 is the scale factor

A signal proportional to e_{out} was recorded on one track of the tape recorder.

Data retrieval was accomplished by recording on a visicorder, the playback of the output from the tape recorder. By also recording a calibration signal on the same visicorder track, a scale factor relating gauss per second per deflection (in inches) was derived. This scalar factor assumed the existence of a uniform magnetic flux density surrounding the receiving antenna.

In addition to amplitude calibration, a polarity calibration was used. A positive deflection on the visicorder trace was made to

correspond to an increasing magnetic flux in the vertical (up) direction on the one channel which recorded significant data.

MEASURED DATA

The curve in Figure 1 is a plot of the recorded $\frac{dH}{dt}$ signal with the appropriate scale factor applied. The plot represents the output from the nearest horizontal antenna which detected the only significant data during this test. This output signal is the local time rate of change of magnetic field at the pickup antenna.

The curve in Figure 1 has been integrated to produce the curve in Figure 2, since the magnitude of the magnetic field is more amenable to interpretation than the $\frac{dH}{dt}$ plot. Figure 2 is now a plot of the absolute values of the magnetic flux density caused by the source transmitter in the vicinity of the receiving antenna.

It is customary to specify field strength in terms of the electric field rather than the magnetic field. At distances greater than one-sixth of a wavelength from the transmitting antenna, the electric and magnetic fields are related by a constant

$$\mathcal{E} = 3 \times 10^4 H$$

where

$\mathcal{E}$ is the electric field measured in volts per meter

and

H is the magnetic field measured in gauss

During this particular test, the shortest wavelength to which the system was sensitive was approximately 50,000 feet (20 kc). Since our antenna was located about 1,000 feet from the point of detonation, it is obviously less than one-sixth wavelength from the source and was not in the radiation zone. The relationship between the electric and magnetic fields is therefore, considerably more complex than that indicated by the

expression above. This mode of energy transfer corresponds very closely to simple magnetically coupled circuits so the data has been presented in terms of magnetic field strengths which was the quantity actually measured.




Figure 1. Time rate of change of magnetic field ($\frac{dH}{dt}$) detected by horizontal loop antenna, 1,000 feet from detonation.




Figure 2. The magnetic field (H) detected by the horizontal loop antenna, 1,000 feet from detonation.

CHAPTER 3

RESULTS

There is some indication that the signal recorded on the horizontal loop located 1,000 feet from the center of detonation may not be directly associated with the fireball. A second horizontal antenna, 1,300 feet from the burst point, was located on the same approximate radius from the detonation center as the first antenna. The recording channel associated with this second antenna had the same sensitivity as did the recording channel for the near horizontal antenna. There was no signal on this more distant channel.

In the near field zone of a dipole, the field strength is inversely proportional to the cube of the distance. One would, therefore, expect the signal from the far horizontal antenna to be reduced by a factor of $\left(\frac{1300}{1000}\right)^3$ or 2.2 compared with that from the near antenna. The fact that no signal was recorded from the second antenna raises the possibility that the signal received on the near antenna came from a source other than the detonation itself.

Owing to the presence of the Navy transmitter (NSS) at Annapolis, broadcasting at about 18 KC, an extremely high noise level was encountered on all of the vertical loops. As a consequence, it was necessary to reduce the sensitivity on these channels. Failure of the vertical loops, associated with both the near and the far antennas, to detect a component of the signal received by the near horizontal antenna could be the result of the difference in channel sensitivities.

The peak values of the measured magnetic field 1,000 feet from the explosion are about 40 microgauss (see Figure 2). A simple expression giving the field strength at some distance from a magnetic

bubble of given radius is

$$H_r = H_o \left(\frac{a}{r} \right)^3$$

where

H_r is the magnetic field strength, at distance r

H_o is the strength of the earth's magnetic field,
(about 0.5 Gauss)

r is the distance from the source at which H_r is
measured.

and

a is the radius of the magnetic bubble

On the basis of the measured 40 microgauss field at a distance of 1,000 feet, it would appear that the effective radius "a" of the magnetic bubble is 43 feet. This 43-foot value for the effective radius of the conducting sphere is somewhat larger than one would expect from a 500 pound HE charge. Furthermore, the radius of this explosion measured by photographic means, was about 15 feet at 1.5 milliseconds, (D. F. Hansen and G. H. Hetley, Jr., "Streak Photography of Exploding 500 Pound Pentolite Charge", October, 1961, EG&G).

Considering free space EM measurement, an error factor of about 25 in the EM measurement would be required to explain the 3 to 1 ratio between the radius deduced from the EM data and that obtained photographically. The EM system was known to be calibrated to within $\pm 10\%$ so that a 25:1 error in the measured value as a result of an error in system calibration is unlikely. On the other hand, if there were supplemental means for coupling the EM energy from the explosion to the antenna, in addition to the coupling predicted by free-space considerations, it would be possible to

explain the enhanced EM signal on the basis of the improved coupling. This supplemental coupling could conceivably arise from buried pipes or cables running between the EM source and the pickup antenna.

One other feature of the observed EM signal which is difficult to explain by the magnetic bubble model is the polarity reversal of the magnetic field signal detected. Analysis indicates that the initial polarity of the local magnetic field at the pickup antenna is consistent with that which would be generated by the magnetic bubble mechanism. On the other hand, the second half-cycle of the magnetic field signal (see Figure 2) is of the opposite polarity. This polarity is inconsistent with the bubble model which provides only for a unidirectional expulsion of the local field and no polarity reversal in the magnetic field.

BLANK PAGE

CHAPTER 4

CONCLUSIONS

It is extremely difficult to draw any really significant conclusions on the basis of a single field measurement of this type. There are so many uncertainties regarding local conditions, the instrumentation and the like, that any further analysis of this data is probably quite pointless.

To summarize the tentative conclusions drawn from this one shot experiment: there was generated in the vicinity of the pickup antenna located 1,000 feet from the explosion, an EM field whose initial polarity and rise time were consistent with the magnetic bubble model, whose peak amplitude was 25 times greater than that predicted by the model, and whose polarity reversal on the second half-cycle was not consistent with the model.

BLANK PAGE

APPENDIX A
ELECTROMAGNETIC RECORDING SYSTEM

XSY-30

The Electromagnetic Recording (EMR) System is designed to detect and record electromagnetic radiation. This radiation may be the product of any electromagnetic source, the origin of which is immaterial. The system is operated manually during system checkout and during playback. The system may operate, however, either manually or automatically during the recording process.

DESCRIPTION

A.1 General. The EMR system is composed of a Radio Tone Receiver, an Antenna Section, a Recording Rack, a Power Distribution Rack, and interconnecting cables. The major signal paths between the chassis are shown in a block diagram, Figure A.1. Two separate commands are sent to the EMR system, either by conventional connecting wires or by radio signals, from a central timing and firing control system. The first signal received by the EMR system, five minutes before the event to be recorded, initiates a series of events in the EMR which prepares the system for the expected event. For some applications a zero time fiducial marker is also transmitted to the EMR system.

The antenna section receives the electromagnetic signals which are to be monitored and relays these signals to the recording rack. The signals are amplified and recorded on magnetic tape.




Figure A.1 EMR system, block diagram


A.2 Radio Tone Receiver. The Radio Tone Receiver, Model N3620-DI, is the component in the EMR system which receives the radio command signals. The first signal, the operate command, is relayed to the Power Distribution Rack. This signal actuates a programmer which controls the EMR system in a sequential manner. The second signal is the zero fiducial pulse which is relayed through the Power Distribution Rack to the Recording Rack.

A. 3 Power Distribution Rack. The Power Distribution Rack, Figure A. 2, contains a DC to 115 vac inverter, a 15-minute timer, and control circuits which perform the automatic operation of the system. The command signals from the Radio Tone Receiver are detected in the Power Distribution Rack which, in turn, energize various circuits in the system. The duration and programming of the system operation is controlled by a cam timer.

A. 4 Antenna Section. The Antenna Section, Figure A. 3, consists of three loop antennas with their preamplifiers and associated cabling. Each loop antenna is 30 inches in diameter and contains 11 turns of wire within an electrostatic shield. The three antennas are arranged so that their axes are mutually perpendicular. The received electromagnetic energy is resolved into three orthogonal components.

The three preamplifiers and the power connectors were not mounted on the antenna bracket as shown in Figure A. 3 but were placed approximately 25 feet from the antennas. Each preamplifier amplifies the signal from the antenna to which it is connected and then passes the signal through the signal cables to the recording system.

A. 5 Recording Rack. The Recording Rack, Figure A. 4, is composed of a four-track magnetic tape recorder, a distribution panel, a monitor panel, two dual-channel amplifiers, and a power supply chassis mounted on a relay rack. The signals received from the Antenna Section are again amplified and recorded on three separate tracks (channels). Track 4 carries a CW timing wave and a zero time reference signal. The zero fiducial mark is obtained from a type TD-2A Photoelectric Fiducial Marker.



- | | |
|--------------------------|------------------------------------|
| 1. -5 MIN. connector | 5. TAPE RECORDER connector |
| 2. INV. TEST switch | 6. 115 vac INV. connector |
| 3. FIDU connector | 7. 115 VOLTS LINE output connector |
| 4. INV. REMOTE connector | 8. 115 VOLTS LINE input connector |

Figure A. 2 Power distribution rack

The amplitude of the signal level in each channel can be adjusted by the controls on the recorder amplifiers to ensure that each signal is amplified to the correct recording level. The signal in any channel may be visually monitored by connecting an oscilloscope to the channel output.

The power supply, contained in the bottom section of the Recording Rack, provides power for the CW timing oscillator and the three pre-amplifiers in the Antenna Section.





Figure A. 3 Antenna section



- | | |
|---------------------------|----------------------------|
| 1. Magnetic tape recorder | 4. Dual-channel amplifiers |
| 2. Distribution panel | 5. Power supply |
| 3. Monitor panel | 6. Relay rack |

Figure A.4 Recording rack

This page intentionally
left blank



NOTE:
ALL CONNECTOR NOS. PREFIXED
BY "AN-3106-" UNLESS
OTHERWISE INDICATED.




Figure A.6 Functional diagram, Electromagnetic Recording System.

APPENDIX B

FIDUCIAL MARKER

TD-2A

The Type TD-2A Fiducial Marker is a photoelectric device which can be used to synchronize other equipment with the beginning of a fast-rising light pulse. Four parallel-connected outputs are provided. The output is a sharp pulse with a rise time of 0.05 microseconds, a duration of 2 to 12 microseconds when terminated in resistances of from 9 to 50 ohms, and a peak amplitude of 400 volts.

If an impedance of 25 ohms or less is connected to the output of the Fiducial Marker, the marker will reset itself. When using a greater impedance, the Fiducial Marker must be reset manually by pressing the reset button momentarily. A neon lamp indicates when the unit has been triggered.

The Type TD-2A Fiducial Marker is equipped with a 6-power telescope which serves two purposes; to allow the Marker to be directed towards a source of the light pulse, and to divert 50 percent of the intensity of the light pulse to the photocell. The telescope has an adjustable field of view with a maximum total field angle of 7.1° .

The circuit diagram of the unit is shown as Figure B. 1.

Figure B.1 Circuit diagram, Fiducial Marker TD-2A.

DISTRIBUTION LIST

ADDRESSEE	NO. OF COPIES
Defense Documentation Center (DDC), Cameron Station, Alexandria, Virginia Attn: TISIA-21 22314	20
ARMY	
Chief of Research and Development, D/A, Washington, D. C. 20310 Attn: Atomic Division	1
Chief of Engineers, D/A, Washington, D. C. 20310 Attn: ENG CW-NE ENGTE-E ENGMC-E	1 1 1
Commanding General, U. S. Army Materiel Command, Washington, D. C. 20310 Attn: AMCRD-DE-N	2
Commanding General, U. S. Continental Army Command, Ft. Monroe, Virginia 23351	1
President, U. S. Army Air Defense Board, Ft. Bliss, Texas 79906	1
Commandant, Command & General Staff College, Ft. Leavenworth, Kansas 66027 Attn: Archives	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	ARMY (Continued)	NO. OF COPIES
Commandant, U. S. Army Air Defense School, Ft. Bliss, Texas 79906 Attn: Command and Staff Department		1
Director, Special Weapons Development, Hq, CDC, Ft. Bliss, Texas 79906 Attn: Chester I. Peterson		1
Commanding General Aberdeen Proving Ground, Aberdeen, Maryland 21005 Attn: Director BRL		4
Commanding General, The Engineer Center, Ft. Belvoir, Virginia 22060 Attn: Asst. Commandant Engineer School		1
Director, U. S. Army Research and Development Laboratory, Ft. Belvoir, Virginia 22060 Attn: Chief, Tech. Support Branch		1
Commanding Officer, U. S. Army Mobility Command, Center Line, Michigan 48015		1
Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801 Attn: ORDBB-TK Mr. A. Nordio, Engineering Science Laboratory		1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
ARMY (Continued)	
Commanding Officer, Transportation Research Command, Ft. Eustis, Virginia 23604 Attn: Chief, Tech. Info. Div.	1
Commanding General, U. S. A. Electronic R&D Lab., Ft. Monmouth, New Jersey 07703 Attn: Technical Documents Center, Evans Area	1
Commanding General, USA Missile Command, Huntsville, Alabama	1
Commanding General, USA Munitions Command, Dover, New Jersey	1
Commanding Officer, U. S. Army Corps of Engineers, Beach Erosion Board, Washington, D. C. 20315	1
Commanding Officer, U. S. Army Nuclear Defense Laboratory, Edgewood Arsenal, Edgewood, Maryland 21040 Attn: Tech. Library	1
Director, Waterways Experiment Station, U. S. Army Corps of Engineers, Vicksburg, Mississippi Attn: Library	1
Director, U. S. Army Corps of Engineers, Nuclear Cratering Group, Livermore, California	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
NAVY	
Chief of Naval Operations, Navy Department, Washington, D. C. 20350	
Attn: OP-75	2
OP-03EG	1
OP-09B5	1
OP-922G1	1
Director of Naval Intelligence, Navy Department, Washington, D. C. Attn: OP-922V	1
Special Projects Office, Navy Department, Washington, D. C. 20360	
Attn: SP-272	1
Chief, Bureau of Naval Weapons, Navy Department, Washington, D. C. 20360	
Attn: DLI-3	1
Chief, Bureau of Ships, Navy Department, Washington, D. C. 20360	
Attn: Code 372	1
Code 423	1
Code 450	1
Chief, Bureau of Yards and Docks, Navy Department, Washington, D. C. 20370	
Attn: Code D-400	1
Code D-440	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
NAVY (Continued)	
Chief of Naval Research, Navy Department, Washington, D. C. 20390 Attn: Code 811	1
Command-in-Chief, U. S. Pacific Fleet, FPO, San Francisco, California	1
Commander-in-Chief, U. S. Atlantic Fleet, U. S. Naval Base, Norfolk 11, Virginia	1
Commandant of the Marine Corps, Navy Department, Washington, D. C. Attn: Code A03H	4
President, U. S. Naval War College, Newport, Rhode Island	1
Commanding Officer, Nuclear Weapons Training Center, Atlatic, Naval Base, Norfolk 11, Virginia Attn: Nuclear Warfare Department	1
Commanding Officer, U. S. Naval Schools Command, U. S. Naval Station Treasure Island, San Francisco, California	1
Superintendent, U. S. Naval Postgraduate School, Monterey, California	1

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

NAVY (Continued)

Commanding Officer, Nuclear Weapons
Training Center, Pacific, Naval Station,
North Island, San Diego 35, California 2

Commanding Officer, U. S. Naval Damage
Control Training Center, Naval Base,
Philadelphia 12, Pa.
Attn: ABC Defense Course 1

Commander,
U. S. Naval Ordnance Laboratory,
Silver Spring 19, Maryland
Attn: EA 1
EU 1
E 1

Commander, U. S. Naval Ordnance Test
Station,
China Lake, California 1

Commanding Officer & Director,
U. S. Naval Civil Engineering Laboratory,
Port Hueneme, California
Attn: Code L31 1

Director, U. S. Naval Research Laboratory,
Washington, D. C.
20390
Attn: Mrs. Katherine H. Case
Code 2039C 1

Commanding Officer & Director,
Naval Electronics Laboratory,
San Diego 52, California 1

Commanding Officer, U. S. Naval
Radiological Defense Laboratory,
San Francisco, California
94129
Attn: Tech. Info. Division 1

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

NAVY (Continued)

Commanding Officer & Director, David W. Taylor Model Basin, Washington, D. C. 20007 Attn: Library	1
Underwater Explosions Research Division, DTMB, Norfolk Naval Shipyard, Portsmouth, Virginia	1

AIR FORCE

Hq, USAF, Washington, D. C. 20330 Attn: AFRNE	1
AFGOA-1	1
AFROC-AE-1	1
AFRNEA-1	1
Deputy Chief of Staff, Plans and Programs, Hq. , USAF, Washington, D. C. 20330 Attn: War Plans Diviwn	1
Director of Research and Development, DCS/D, Hq. , USAF, Washington, D. C. 20330 Attn: Guidance & Weapons Division	1
Air Force Intelligence Center, Hq. , USAF, ACS/I (AFCIN-301) Washington, D. C. 22212	1

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

AIR FORCE (Continued)

Commander-in-Chief,
Strategic Air Command,
Offutt AFB, Nebraska
68113

Attn: OAWS
DPCBC

1
1

Commander, Tactical Air Command,
Langley AFB, Virginia
23365

Attn: Document Security Branch

1

ASD, Wright-Patterson AFB,
Ohio
45433

1

Commander, Air Force Logistics Command,
Wright-Patterson AFB,
Ohio
45433

2

AFSC, Andrews Air Force Base,
Washington, D. C.
20331

Attn: RDRWA

1

Director, Air University Library,
Maxwell AFB, Alabama
36112

2

AFCRL, L. G. Hanscom Field,
Bedford, Massachusetts
01731

Attn: CRQST-2

1

AFWL, Kirtland AFB,
New Mexico
87117

Attn: Technical Information &
Intelligence Division,
Capt. W. Henderson

4

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

AIR FORCE (Continued)

Commandant, Institute of Technology,
Wright-Patterson AFB,
Ohio

45433

Attn: MCLI-ITRIDL

1

BSD, Norton AFB,
California

92409

1

Director, USAF Project RAND, Via:
Air Force Liaison Office,
The Rand Corporation,
1700 Main Street,

Santa Monica, California

1

Attn: Paul Tamarkin

1

Director of Civil Engineering,
Hq, USAF,
Washington, D. C.

20330

Attn: AFOCE

1

OTHERS

Director of Defense Research &
Engineering

Washington, D. C.

20330

Attn: Tech. Library

1

Atomic Programs

1

Assistant to the Secretary of Defense
(Atomic Energy)

Washington, D. C.

20330

1

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

OTHERS (Continued)

U. S. Documents Officer, Officer of the United States National Military Representative-SHAPE, APO-55, New York, New York	1
Commander-in-Chief, Pacific, Fleet Post Office, San Francisco, California 94129	1
Director, Weapons Systems Evaluation Group, OSD, Room 1E880, The Pentagon, Washington, D. C. 20301	1
Commandant, Armed Forces Staff College, Norfolk 11, Virginia Attn: Library	1
Commander, Field Command, DASA, Sandia Base, Albuquerque, New Mexico 87115	16
Commander, Field Command, DASA, Sandia Base, Albuquerque, New Mexico, 87115 Attn: FCWT	1
FCTG	1
Chief, Defense Atomic Support Agency, Washington, D. C. 20301	5
Commandant, Army War College, Carlisle Barracks, Pennsylvania, Attn: Library	1

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

OTHERS (Continued)

Commandant, The Industrial College of the Armed Forces, Ft. McNair, Washington, D. C. 20310	1
Commandant, National War College, Washington, D. C. Attn: Class Rec. Library	1
Officer-in-Charge, U. S. Naval School, Civil Engineering Corps Officers, U. S. Naval Construction Battalion, Port Hueneme, California	1
Lawrence Radiation Laboratory, Box 808, Livermore, California Attn: Technical Information Division	1
James C. Watson	1
L. F. Wouters	1
Los Alamos Scientific Laboratory, P. O. Box 1663, Los Alamos, New Mexico Attn: Report Librarian	1
B. R. Suqdam	1
John Malik	1
Conrad L. Longmire	1
Administrator, National Aeronautics & Space Administration, 1512 H Street, N. W., Washington, D. C. 20546	1
National Aeronautics & Space Administration, Man-Spacecraft Center, Space Technology Division, Box 1537, Houston, Texas	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Langley Research Center, NASA, Langley Field, Hampton, Virginia 23365 Attn: Mr. Philip Donely	1
Chief, Classified Technical Library, Technical Information Service, U. S. Atomic Energy Commission, Washington, D. C. 20545	1
Manager, Albuquerque Operations Office, U. S. Atomic Energy Commission, P. O. Box 5400, Albuquerque, New Mexico	1
Manager, Nevada Operations Office, USAEC, Las Vegas, Nevada	1
Massachusetts Institute of Technology, Division of Sponsored Research, 77 Massachusetts Avenue, Cambridge, Massachusetts Attn: Dr. Robert J. Hansen	1
University of Michigan, Ann Arbor, Michigan Attn: Dr. Bruce G. Johnston	1
Sandia Corporation, Sandia Base, Albuquerque, New Mexico Attn: Calssified Document Division, For: Dr. M. L. Merritt 87115	1
Dr. Leonard Obert, Applied Physics Laboratory, Bureau of Mines, College Park, Maryland	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
University of Illinois, Civil Engineering Dept. , 111 Talbot Laboratory, Urbana, Illinois Attn: Dr. N. M. Newmark	1
Holmes & Narver, Inc. , 849 S. Broadway, Las Angeles 14, California Attn: Mr. Frank Galbreth	1
Massachusetts Institute of Technology, Division of Sponsored Research, 77 Massachusetts Avenue, Cambridge, Massachusetts, Attn: Professor Robert V. Whitman	1
University of Texas, Structural Mechanics Research Laboratory, Balcones Research Center, Route 4, Box 189, Austin, Texas Attn: Professor J. Neils Thompson	1
United Research Services, 1811 Trousdale, Burlingame, California Attn: Mr. Kenneth Kaplan	1
Stanford Research Institute, Menlo Park, California Attn: Mr. Fred M. Sauer	1
Stanford Research Institute, Menlo Park, California Attn: Dr. George Duvall	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Southwest Research Institute, 8500 Culebra Road, San Antonio, Texas Attn: Dr. Robert C. DeHart	1
General American Transportation Corporation, Mechanix Research Division, 7501 N. Natchez Avenue, Nile, Illinois Attn: Dr. Neidhardt	1
Illinois Institute of Technology Research Institute, 10 West 35th Street, Chicago 16, Illinois	1
United Aircraft Corporation Systems Center, Representative & Engr. Office Room 714-718, Airport Imperial Bldg. 999 Sepulveda Blvd, El Segundo, California	1
Iowa State University of Science and Technology, Ames, Iowa Attn: Professor M. G. Spangler	1
Roland F. Beers, Inc., 813 N. Royal Street, Alexandria, Virginia Attn: Mr. Sherwood Smith	1
Paul Weidlinger, 770 Lexington Avenue, New York 21, New York Attn: Dr. M. Baron	1
Illinois Institute of Technology Research Institute, 10 West 35th Street, Chicago 16, Illinois Attn: Mr. A. Weiderman	1

DISTRIBUTION LIST (Continued)

ADDRESSEE

NO. OF COPIES

OTHERS (Continued)

Engineering Physics Company, 5515 Randolph Road, Rockville, Maryland Attn: Dr. Vincent J. Cushing	1
Aerospace Corporation, P. O. Box 95085, Las Angeles 45, California Attn: Mr. David B. Singer 90012	1
Lockheed Aircraft Corporation, Lockheed Missiles and Space Co. Div., 1111 Lockheed Way, Sunnyvale, California Attn: Dr. R. E. Meyerott Mr. Eugene Perry	2
TRW Space Technology Labs. Inc., Thompson-Ramo Wooldridge, Inc., One Space Park, Redondo Beach, California Attn: Dr. Leon, R. L. Mathews, D. W. Pugsley, F. R. Norton, B. Sussholz	1 1 1 1 1
Aeroneutronic, A Division of Philco Corp., Ford Road, Newport Beach, California Attn: Dr. Arthur J. Ruhlig	1 1
Edgerton, Germeshausen & Grier, Inc., 160 Brookline Avenue, Boston, Massachusetts Attn: Mr. D. F. Hansen 02129	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
General Electric Company, TEMPO, 735 State Street, Santa Barbara, California	
Attn: Dr. W. E. Dudziak	1
Charles P. Hedges	1
General Electric Company, 735 State Street, Santa Barbara, California	
Attn: DASA Data Center for Mr. Warren Chan	1
Paul G. Fischer	1
General Dynamics/Astronautics, 5001 Kearny Villa Road, San Diego, California	
Attn: Dr. D. A. Hamlin	1
Battelle Memorial Institute, 505 King Avenue, Columbus 1, Ohio	
Attn: Mr. R. W. Klingsmith 43215	1
Technical Operations, Inc., South Avenue, Burlington, Massachusetts	
Attn: Dr. Paul I. Richards	1
AVCO Corp, 201 Lowell Street, Wilmington, Massachusetts,	
Attn: Mr. R. E. Cooper	1
The Mitre Corp., Route 62 and Middlesex Turnpike, P. O. Box 208, Bedford, Massachusetts	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Space General Corporation, 9200 E. Flair Drive, El Monte, California Attn: G. L. Brown	1
Bendix Systems Division, 3300 Plymouth Road, Ann Arbor, Michigan Attn: Ted H. Colvin	1
Kaman Aircraft Corporation, Nuclear Division, Garden of the Gods Road, Colorado Springs, Colorado Attn: Burt J. Bittner	1
Federal Aviation Agency, 1711 New York Avenue, N. W., Washington, D. C. 20553 Attn: Lt. Col. James E. Ogle, RD-85	1
Director, National Security Agency, Fort George G. Meade, Maryland 20755 Attn: David L. Sloan, R17	1
Hughes Aircraft Company, Ground Systems Group, 1901 W. Melvern Avenue, Fullerton, California Attn: T. D. Hanscome	1
General Electric Company, Radiation Effects Operation, Electronics Park, Syracuse, New York Attn: Leo H. Dee	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
The Mitre Corporation, Route 62 and Middlesex Turnpike, Bedford, Massachusetts	
Attn: Dr. C. Belote,	1
Dr. Paul E. Grant,	1
Mr. B. Trautman	1
Bell Telephone Laboratories, Inc. Whippany Road, Whippany, New Jersey	
Attn: Jack K. Middaugh,	1
L. S. Inskip	1
University of Denver, Denver Research Institute, University Park, Denver 10, Colorado	
Attn: Howard M. Fowles	1
Northrop Ventura, 1515 Rancho Conejo Blvd. , Newbury Park, California	
Attn: Technical Library for master control	1
International Business Machines, Route 170, Owego, New York	
Attn: Robert M. Kloepper, Dept. 511	1
The Boeing Company, Aero Space Division, 7755 E. Marginal Way, Seattle, Washington	
Attn: Vern E. Bryson,	1
Glenn L. Keister,	1
Robert R. Reed	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
NSS, 3801 Nebraska Avenue, Washington 25, D. C. Attn: Col. Kenneth R. Edwards	1
President, Sandia Corporation, Sandia Base, Albuquerque, New Mexico Attn: Thomas Flanagan, Org. 7251, Ge. Kambourelis, James W. Easley, T.D. Cook	4
Director, Stanford Research Institute, Menlo Park, California Attn: Document Custodian for Edward T. Pierce	1
California Institute of Technology, 1201 East California Blvd. , Pasadena, California Attn: R. F. Christy	1
U. S. Geological Survey, Denver Federal Center, Denver 25, Colorado Attn: Rudolph A. Black	1
Director, Weapons Systems Evaluation Group, Washington, D. C. 20301 Attn: Col. John Swenson, Jack Vorona, Col. James W. Davis, Capt. Joseph A Lovington	1 1 1 1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Director of Military Application, U. S. Atomic Energy Commission, Washington, D. C. Attn: Ben F. Collier	1
Air Technology Corporation, 640 Memorial Drive, Cambridge 39, Massachusetts Attn: Roger E. Clapp	1
Chief, Bureau of Naval Weapons, Navy Department, Washington, D. C. 20360 Attn: W. T. August, RRRE5, C. Lang, RU311	1 1
Mount Auburn Research Associates, Inc., 12 Norfolk Street, Cambridge 39, Massachusetts Attn: Mr. S. L. Kahalas	1
Sylvania Electronic Systems, A Division of Sylvania Electric Products, Inc., 70 Sylvan Road, Waltham 54, Massachusetts Attn: Dr. R. V. Row	1
ITT Kellogg, 500 N. Pulaski Road, Chicago 24, Illinois Attn: Security Officer for Mr. K. D. Swartzel	1
ITT Kellogg Communications Systems, 3700 E. Pontiac Street, Fort Wayne, Indiana Attn: Mr. R. Cotterman Mr. R. Patten	1 1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
IBM Corporation, Route 17C, Owego, New York Attn: Mr. J. Keyser, Dept. 521, 101-2	1
ITT Intelcom Inc. , 5817 Columbia Pike, Bailey's Crossroads, Fairfax County, Virginia Attn: Mr. J.S. Smith	1
Martin Marietta Corporation, Middle River, Baltimore, Maryland Attn: Richard J. Allen, Dr. L. Bittman, Mail Stop T-683	1 1
Aerojet-General Nucleonics, Foot of Fostoria Way, P. O. Box 77, San Ramon, California Attn: Mr. D.I. Gilbert, Supervisor of Research Planning	1
Sperry Rand Corporation, A Division of Sperry Gyroscope, 100 North Road, Sudbury, Massachusetts Attn: Dr. P.H. Klein	1
ACF Electronics Division, Division Headquarters and Plant, 48 Lafayette Street, Riverdale, Maryland	1
Office of Civil Defense, Protective Structures Division, Washington, D. C. Attn: Mr. Pochuta	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Zeus Project Manager, Redstone Arsenal, Huntsville, Alabama Attn: ZEEEX	1
Laboratory for Electronics, Inc., 1079 Commonwealth Avenue, Boston, Massachusetts Attn: Mr. I.G. Versoy	1
Engineering-Physics Company 5515 Randolph Road Pockville, Maryland Attn: Mr. V. Cushing	1
Deputy Chief of Staff for Military Operations, Department of the Army, Washington, D. C. 20310 Attn: Dir of CD	1
Assistant Chief of Staff, Intelligence, Department of the Army, Washington, D. C. 20310	1
Chief of Engineers, Department of the Army, Washington, D. C. 20315 Attn: AMCRD-RS	1
Chief Signal Officer, Department of the Army, Washington, D. C. 20310	1
Commanding General, U. S. Army Combat Development Command, Ft. Belvoir, Virginia 22060	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
President, U. S. Army Artillery Board, Fort Sill, Oklahoma 73503	1
President, U. S. Army Aviation Board, Fort Rucker, Alabama 36362 Attn: ATBG-DG	1
Commandant, U. S. Army Aviation School, Fort Rucker, Alabama 36362	1
Commandant, U. S. Army Signal School, Fort Monmouth, New Jersey 07703	1
Commanding Officer, Army Medical Research Laboratory, Fort Knox, Kentucky 40120	1
Commanding Officer, Harry Diamond Laboratories, Connecticut Avenue and Van Ness Street, N. W., Washington, D. C. 20425 Attn: Ch Nuclear Vulnerability Branch (230)	1
Commanding Officer, U. S. Army Missile Support Agency, White Sands Missile Range, New Mexico 88002 Attn: Technical Library	1
Commanding General, U. S. Army Ammunition Command, Joliet, Illinois	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Commanding General, U. S. Electronics Command, Fort Monmouth, New Jersey 07703	1
Commanding General, U. S. Army Electronic Proving Ground, Fort Huachuca, Arizona 85613 Attn: Technical Library	1
Commanding General, U. S. Army Combat Surveillance Agency, 1124 N. Highland Street, Arlington, Virginia 20315	1
Commandant, U. S. Army Armored School, Fort Knox, Kentucky 40120	1
Commandant, U. S. Army Artillery & Missile School, Fort Sill, Oklahoma 73503 Attn: Combat Dev. Dept.	1
Commandant, U. S. Army Infantry School, Ft. Benning, Georgia 31905 Attn: CDS	1
Commanding General, Chemical Corps Training Command, Ft. McClellan, Alabama 36205	1
Commanding Officer, U. S. Army Missile Support Agency, White Sands Missile Range, New Mexico 88002	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
Director, Research and Analysis Corporation, Waverly Bldg. , 6935 Arlington Road, Bethesda, Maryland	1
Commanding Officer, U. S. Naval Mine Defense Lab, Panama City, Florida	1
HQ. USAF (AFTAC-TD) Washington, D. C. 20333	1
ADC, ADODA, Ent AFB, Colorado 80912 Attn: Operations Analysis Section	1
RADC, Griffiss AFB, New York 13442 Attn: Documents Library, RCSSL-1	1
2AF, Barksdale AFB, Louisiana 71110 Attn: Operations Analysis Office	1
USAESAM, Brooks AFB, Texas 78235	1
ESD, L. G. Hanscom Field, Bedford, Massachusetts 01731	1

DISTRIBUTION LIST (Continued)

ADDRESSEE	NO. OF COPIES
OTHERS (Continued)	
OAR, Bldg. T-D Washington, D. C. 20333 Attn: RROSP	1
HQ USAF (AFORQ), Washington, D. C. 20330	1
Director, Advance Research Projects Agency, Washington, D. C. 20301 Attn: Defender	1
Director, Defense Intelligence Agency, Washington, D. C. 20301	1
Director, Defense Communications Agency, Washington, D. C. 20305	1
Commandant, U. S. Coast Guard, 1300 E Street, N. W., Washington, D. C. Attn: CRD B. E. Kolkhorst	1
Commander, Joint Task Force Eight, Barton Hall, Washington, D. C. 20315	1
Commander-in-Chief, EUCOM, APO 128, New York, New York	1
CINCONAD, Ent AFB, Colorado	1

UNCLASSIFIED

UNCLASSIFIED