

UNCLASSIFIED

AD NUMBER

AD442059

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

**Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; DEC 1963. Other requests shall be referred to Office of Naval Research, Washington, DC 20360.**

AUTHORITY

onr memo, 6 jul 1965

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 442059

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

442059

442059

CATALOGED BY DDC
AS AD No. _____

EASTMAN KODAK COMPANY
APPARATUS AND OPTICAL DIVISION



This research is part of Project DEFENDER under the joint sponsorship of the Advanced Research Projects Agency, the Office of Naval Research and the Department of Defense. Reproduction in whole or in part is permitted for any purpose of the United States Government.

LASER MATERIAL STUDY
Contract Nonr - 3834(00)

Semi-Annual Technical Report
1 July 1963 - 31 December 1963

Order Number 306-62
Project Code Number 7300


Prepared by
EASTMAN KODAK COMPANY
Apparatus and Optical Division
Rochester, New York 14650

For
ADVANCED RESEARCH PROJECTS AGENCY
and
OFFICE OF NAVAL RESEARCH
Department of Navy

Prepared by:


P. B. Mauer

Approved by:


H. F. Hicks, Jr., Acting Manager
Research Laboratories
Apparatus and Optical Division

INTRODUCTION

The previous six month period represented the completion of the bulk of the work of this contract. Our purpose in gaining a time extension and proceeding at a low level of effort and expenditure was twofold: To try to resolve some unanswered technical problems relating the laser efficiencies of different glasses, and to keep in touch with the O.N.R. program systems requirements.

During the period of this report, much of our time was spent in adapting our glass plant procedures to handle silicate glass formulations of large enough size to give good optical quality. We have succeeded and are now producing sufficient quantity to make neodymium-doped silicate glass available commercially.

DISCUSSION

The basic problem of converting optical pumping energy to coherent laser output efficiently is a many sided one. It is in an attempt to shed some light on this problem that the present work is undertaken.

We have previously demonstrated in small rods that fluorescence efficiency is not a sufficient criterion to predict the laser performance of a neodymium doped glass.

Since our facilities for melting, stirring and casting do not allow us to prepare high temperature glasses, we have engaged the services of an outside vendor to prepare a cesium-barium silicate composition to our specifications. We have extended our in-house capability to provide a low melting lithium silicate glass as a second comparison for our standard borate material. This glass has been cast, annealed, ground and polished, but not yet coated and tested. Our next technical report will cover the results of the testing of this material.

So far, only a small melt of the cesium glass has been made for absorption and fluorescence measurements.

Table I summarizes some of the properties of the three glasses whose laser action we plan to investigate.

The rods for test are 12" long and 1/2" diameter, with a fine grind on the cylindrical surface.

Table II is similar to page 7 of our previous technical report (January 1 - June 30, 1963), but has corrected values for the compositions of glasses 2309 and 2310.

TABLE I

Type No.	Composition, Wt. %						Nd, Wt. %	Refractive Index (nD)	Density (gms/cc)	.8μ Absorption (cm ⁻¹)	Life-time (μsec)	.8μ Absorption per ion (10 ⁻²⁰ cm ²)
ND-10	B	La	Si	Th	Sr	Ba	1.0	1.697	4.132	2.80	60	1.9
	36.2	21.4	2.4	19.5	6.2	13.2						
2305	Si	La	Li	Na	Sr	Ba	1.0	1.596	3.130	2.46	360	2.2
	50	12	7	10	10	10						
2311	Si	Cs	Ba				1.0	1.573	3.736	.93	546	.7
	43.4	40.8	14.8									

TABLE II
SILICATES

Glass No.	Composition by Wt. %	$\bar{n}_D$	Refractive Index (nD)	Density (gms/cc)	Peak Absorption Coefficient (cm ⁻¹) at 0.8μ	Life-time (μsec)	Absolute Absorption Cross Section /ion (10 ⁻²⁰ cm ²) at 0.8 microns
2296	Si-La- $\frac{Li-Na-Ba}{40 \ 22 \ 7 \ 10 \ 20}$	1.0	1.6315	3.4471	2.76	336.7	2.240
2297	Si-La-Ce- $\frac{Na-Ba}{42.5 \ 23.9 \ 0.5 \ 10.6 \ 21.3}$	1.0	1.6182	3.5509	2.61	373.1	1.940
2298	Si-La-Ce- $\frac{Li-Na-Zn-Ba}{40 \ 13.5 \ 0.5 \ 5 \ 10 \ 10 \ 20}$	1.0	1.6253	3.4345	2.79	338.5	2.269
2299	Si-La-Ce- $\frac{Li-Na-Cd-Ba}{40 \ 13.5 \ 0.5 \ 5 \ 10 \ 10 \ 20}$	1.0	1.6325	3.5401	2.84	336.7	2.241
2300	Si-Al-Ce- $\frac{Li-Na-Zn-Ba}{40 \ 6.5 \ 0.5 \ 7 \ 10 \ 5 \ 20}$	1.0	1.5962	3.2207	2.43	354.9	2.107
2302	Si-Al-La-Li-Ti- $\frac{Na-Sr-Ba}{50 \ 3 \ 8 \ 7 \ 1 \ 10 \ 10 \ 10}$	1.0	1.5887	3.0817	1.89	359.5	1.711
2303	Si-Al-La-Ce- $\frac{Li-Na-Sr-Ba}{50 \ 3 \ 8.5 \ 0.5 \ 7 \ 10 \ 10 \ 10}$	1.0	1.5858	3.0853	2.01	382.2	1.819
2305	50 - 11.5 0.5 7 10 10 10	1.0	1.5959	3.1298	2.46	359.5	2.200
2309	Si- $\frac{Li-Na-K-Mg-Ca}{49.8 \ 5.3 \ 11.7 \ 16.7 \ 7.1 \ 9.9}$	1.0	1.5829	3.1022	1.60	354.9	1.455
2310	42.7 - 9.5 14.5 - $\frac{Ba}{8.6 \ 23.6}$	1.0	1.5624	2.6422	1.57	336.7	1.676
2311	Si-Cs-Ba- $\frac{Ba}{43.4 \ 40.8 \ 14.8}$	1.0	1.5732	3.7363	0.93	546.0	0.702

FURTHER DEVELOPMENT

Our plan is as follows:

1. To measure output-input energy curves for the ND-10 borate and lithium silicate rods we have.
2. To measure passive absorption at 1.06 microns.
3. To compare efficiency of the rods with different output reflectors.
4. To secure a comparable rod of cesium silicate for similar tests. This will contain 2 wt. percent Nd, to make its absorption more like the other glasses.

UNCLASSIFIED

UNCLASSIFIED