

UNCLASSIFIED

AD NUMBER
AD448884
LIMITATION CHANGES
TO: Approved for public release; distribution is unlimited.
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; MAY 1964. Other requests shall be referred to Frankford Arsenal, Philadelphia, PA.
AUTHORITY
FA ltr 2 Apr 1965

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 4 4 8 8 8 4

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY DDC 448884

AS AD NO. _____

448884

AD

REPORT A64-13


EXPLOSIVE WELDING

by

H. J. ADDISON, Jr.

May 1964

AMCMS Code 5025.11.842



**UNITED STATES ARMY
FRANKFORD ARSENAL
RESEARCH & DEVELOPMENT
DIRECTORATE**

PHILADELPHIA, PA. 19137

DDC AVAILABILITY NOTICE

Qualified requesters may obtain copies of this report from
Defense Documentation Center, Cameron Station, Alexandria, Va. 22314.

DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return
it to the originator.

The findings in this report are not to be construed as an official
Department of the Army position unless so designated by other authorized
documents.

REPORT A64-13

EXPLOSIVE WELDING

by

H. J. ADDISON, Jr.

AMCMS Code 5025.11.842
DA Project 1-A-0-24401-A-110

Research and Development Directorate
FRANKFORD ARSENAL
Philadelphia, Pa. 19137

May 1964

Explosive Welding

H. J. ADDISON, JR.

Metallurgist,
United States Army Munitions Command,
Frankford Arsenal,
Philadelphia, Pa.

Explosive welding occurs when adjacent surfaces of appropriately positioned metals are properly thrust together by energy released from an explosive source. The procedure consists essentially of locating the metal members being welded between an explosive charge and an anvil with the lower member resting on the anvil. Explosive welding can be used for spot and seam welding and cladding. Lap, tee and edge joints (such as is experienced in cladding) have been fabricated. Corner and butt joints are feasible. Tensile-shear strengths approaching that of the base metal have been obtained in various materials in seam-welded lap joints. Explosive spot welds have failed outside the nugget. Explosive welding is feasible and offers possibilities as a future fabrication method.

Contributed by the Machine Design Division and presented at the Design Engineering Conference and Show, Chicago, Ill., May 11-14, 1964, of The American Society of Mechanical Engineers. Manuscript received at ASME Headquarters, April 7, 1964.

Written discussion on this paper will be accepted up to June 15, 1964.

Copies will be available until March 1, 1965.

Explosive Welding

H. J. ADDISON, JR.

Explosive welding is a relatively new joining process that is being studied by an increasing number of organizations. With this process, welding occurs when the adjacent surfaces of the metals to be joined are oriented properly and projected together by energy released from an explosive source. Generally, no effort is made intentionally to provide heat to the welding operation although some heat may be generated in the weld owing to the absorption of energy. In contrast with fusion welding processes, therefore, explosive welding produces little or no melting at the weld interface.

These characteristics suggest several important advantages. These are (a) the ability to weld similar and dissimilar metals that may otherwise be difficult to join by fusion welding processes because of the deterioration of weld or base metal properties, (b) the welding of relatively large surface areas of sheets and plates such as a cladding type of operation, (c) the welding of configurations that may not be readily joined by other more conventional methods, and (d) the possibility of utilizing the process in field fabrications where the location may be inaccessible to other processes.

Most of the published reports on explosive welding have provided information on the dynamic characteristics of the operation, the mechanism of the weld and feasibility of welding various metals and alloys. Also, at least one investigator (1)¹ has reported the influence of certain welding variables on the mechanical properties of welded joints. Although explosive welding can be considered in the early stages of development, attention is being given to a few applications such as the cladding of sheet and plate. At least one organization reportedly is including the explosive cladding of alloys among its commercial activities.

It is likely that explosive welding will be used for many specialized applications as its pos-

¹ Numbers in parentheses designate References at the end of the paper.




Fig. 1 Schematics of explosive welding. A (top): Angular technique; B (bottom): Gap technique

sibilities become more apparent. Designers as well as fabricators, therefore, should have an awareness of the process, its characteristics and its state of development so that its position and capability with respect to other joining processes can be anticipated properly when considering the design and construction of future assemblies. It is the intent of this paper to present this type of information as reflected particularly by the author's work.

WELDING PROCEDURES

The principal features of explosive welding procedures are illustrated in Figs. 1A (1) and 1B. The difference between the two illustrations is the positioning of the base metal members or panels to be welded. In Fig. 1A, the panels are placed at an angle to each other forming a "contact angle". The second technique, Fig. 1B, however, is a setup wherein the panels are positioned parallel to each other. The distance between the members has been called the gap; thus, the name "gap technique".

Other components of the welding setup are essentially the same. The panels are located between an anvil and the explosive charge with the lower panel resting on the anvil. The purpose of the anvil is to absorb energy generated within the panels during the welding operation. A protective or buffer material is placed over the up-




Fig. 2 Angular technique




Fig. 3 Gap technique

per panel to minimize pitting and gouging of the surface. The distance between the explosive and the protective material is usually referred to as the "standoff". When the standoff is zero, that is, when the explosive charge is in contact with the protective material or top panel, the procedure is called a "contact operation". The procedure is referred to as a "standoff operation" when the charge is exploded at a selected distance away from the protective material and panel. In this situation the impulsive force passes through an energy-transmitting medium such as air or water to the top panel. Contact operations usually are used for welding bulk parts and plates whereas standoff operations having a short standoff are suitable for cladding or joining sheet and foil

(2). The angular or the gap technique can be used with either operation.

Two specific welding setups used with these techniques are shown in Figs. 2 and 3. In both instances, lap-welded specimens were prepared by clamping the two panels to the anvil. Primacord consisting of 400 grains of PETN per foot was taped to an iron rod for alignment and positioned parallel to the top panel over the area to be welded. A spacing strip was located as shown in the drawings to prevent the upper panel from being severely deformed or sheared along the edge of the overlap when thrust against the lower panel.

Spacers were used to obtain the proper angle or gap. In the angular technique, the top panel was bent to form an angle slightly greater than




Fig.4 Types of explosive welds. Left: area weld; middle: seam weld; right: spot weld

that which was desired. The spacer was then used to clamp the panel in the correct position. The spacer is displaced in the illustration to show the overlap but was actually over the overlap to assure alignment.

The distance separating the panels in the gap technique was obtained with shims. Dimpling of the top panel also has been used to provide the gap thereby eliminating the need for shims. Although early investigations were performed in water, air has been found to be a satisfactory energy-transmitting medium.

In welding 1/16-in. 2024-T3 aluminum-alloy sheet using the angular setup, a 1/2-deg contact angle and a 1/8-in. standoff produced weldments having tensile-shear strengths approaching the base-metal strengths. When the same material was welded with the gap technique, the best results were obtained using a gap or panel opening of 0.010 in. and a standoff of 1/8 in. It was noted that the gap technique provided somewhat more consistent mechanical properties along the full length of the weld.

Although Primacord was used in the foregoing work, other explosives, such as sheet explosives, in various forms and shapes have been tried using slightly modified procedures. The choice of explosive and shape of the charge is determined, among other factors, by the type of weld that is to be made.

TYPES OF WELDS

Explosive welding, because of the nature of the process, lends itself particularly to the joining of sheet or plate surfaces as in an overlap or cladding situation. Investigators, in studying explosive welding, have made at least three types of welds. These are area, seam, and spot welds. An area weld in this instance, as

opposed to a seam weld, refers to a bond made between the entire mating surfaces of the two members. Fig.4 shows these three welds.

Area Weld

An area weld is represented by the specimen on the left in Fig.4. This specimen was made from two 1/16-in-thick, low-carbon steel panels using the angular technique. The panels are joined essentially throughout their width and length except for an obvious portion along the far edge. This specimen, in view of the separation, conveniently shows the two panels that were joined. Incomplete welding such as is shown can be minimized by changes or refinements in the welding procedure. This type of weld has received more attention by a number of organizations than other explosive welds. Major uses include clad and laminated materials.

Seam Weld

The seam weld represented by the middle specimen in Fig.4 was made down the center of the two panels. Both panels were 1/16-in-thick, 2024-T3 aluminum alloy, which is a high-strength, heat-treatable material. In this specimen, the overall width of the weld interface was approximately 1/2 in. The seam weld can be widened by appropriate changes in procedure without experiencing gross melting at the interface or thermal deterioration of the heat-affected zone often characterized by many other welding processes.

Spot Weld

A spot weld is shown at the right in Fig.4. The base material was 1/16-in-thick, tough pitch copper. Although this material is considered extremely difficult to resistance spot weld, it was explosively spot-welded without difficulty.

The diameter of an explosive spot weld may be




Fig. 5 Weld joints

varied over a wide range by using appropriate explosive charges. This is an important attribute since the load-carrying capacity of a spot weld generally increases with its diameter, provided other factors are held constant.

TYPES OF JOINTS

There are five basic weld joints (3) available to the designer. These are:

- 1 Edge joint.
- 2 Lap joint.
- 3 Tee joint.
- 4 Corner joint.
- 5 Butt joint.

These joints, Fig. 5, have had many variations conceived to satisfy individual requirements of different assemblies.

The selection of a joint is usually done after considering a number of factors including the cost of fabrication, geometry of the weldment, distribution and magnitude of the stresses throughout the assembly and accessibility of the joint. Another important factor is the welding process since it must be capable of making the joint. Recent work has indicated that all of the basic




Fig. 6 Explosively welded lap joints in $1/16$ -in. aluminum alloy 2024-T3. Left: seam weld; right: spot weld

joints in one form or another are at least feasible with the explosive welding process.

Edge Joint

The explosive welding process, using area welding procedures, is particularly suited to the edge type of joint, used in cladding.

Lap Joint

A considerable amount of data has been reported on the mechanical properties of explosively welded lap joints (1) indicating the applicability of the process to this type of joint. Two explosively welded lap joints are shown in Fig. 6. These joints were made using the gap technique. As can be observed, one joint was made with a spot weld. The other, however, is either a seam or area weld depending essentially on whether the entire width of the overlap is intentionally bonded.

Tee and Corner Joints

Very little information has been published on the explosive welding of tee and corner joints, but some work apparently has been conducted. Structural tee shapes reportedly were made in aluminum 6061-T6 (4) and Holtzman (5) has indicated that tee joints can be explosively welded. In view of the apparent success with the tee joint, it is likely that corner joints could also be produced with modified procedures.

Butt Joint

The modified butt joint (scarf joint) shown in Fig. 5 may, more than other butt joint, be explosively weldable since its interface could conceivably be oriented properly with the explosive charge using current techniques. The investigations suggest that joints of this type might be welded, although there has been no information re-




Fig. 7 Explosively seam welded, lap joints in aluminum alloys

ported that butt joints have been successfully made.

EXPLOSIVELY WELDABLE BASE METALS

A number of base metals have been explosively welded. These include aluminum and its alloys, nickel alloys, refractory metals, gold and silver, copper and its alloys, as well as low-carbon and alloy steels in various combinations (1-3, 6-10).

There has been very little information published on the weld properties of these materials and, therefore, the author has been conducting an investigation directed toward obtaining tensile shear data on various metals and alloys. Several lap-welded specimens of different alloys are shown in Figs. 7 through 9. Figs. 7 and 8 are seam welds whereas Fig. 9 shows several spot welds.

The joint strength of the lap-welded alloys employing seam welds, as compared with the ultimate strength of the as-received metal is shown in Table 1. Joint strength was determined in pounds per inch of specimen width rather than pounds per square inch of interfacial area since it was extremely difficult to determine the area of the joint interface in many specimens.

The joint strength of aluminum alloys 2024-T3 and 6061-T6 as well as magnesium alloy AZ31B-0 and copper are essentially equal to the tensile strength of the respective base materials. For these materials, the spread exhibited by the welded joints approximated that exhibited by the base metals.

During the welding operation, plastic deformation occurred in each joint and reduced the thickness of the overlap to some extent. If these reduced cross sectional areas were taken into account, the strength values for lap welds in alu-




Fig. 8 Explosively seam welded, lap joints in four base metals

TABLE 1
COMPARISON BETWEEN STRENGTH OF UNWELDED AND EXPLOSIVE WELDED BASE METALS

Material	Thickness (in.)	Base Metal or Weld	Load (pounds/in.)		
			Average	Maximum	Minimum
2024-T3	0.062	Base Metal Weld	4166 4103	4213 4206	4148 3916
2219-T6	0.090	Base Metal Weld	5660 5149	5685 5573	5647 4888
5083-H24	0.090	Base Metal Weld	4906 4727	4919 4852	4888 4471
6061-T6	0.090	Base Metal Weld	4260 4257	4271 4342	4224 3991
Clad 7075-T6	0.090	Base Metal Weld	6942 5612	6980 6782	6879 3373
1020 Steel	0.020	Base Metal Weld	904 845	909 863	900 819
Mg Alloy AZ31B-0	0.062	Base Metal Weld	2362 2354	2379 2382	2354 2287
Copper	0.040	Base Metal Weld	1260 1283	1263 1289	1259 1264

minum alloy 5083-H24 and 1020 steel may have more nearly approached their base metal strengths. The strength of the clad 7075-T6 weldment, however, varied considerably. All of the tensile shear specimens except those of the clad 7075-T6 alloy failed outside the weld.

JOINT QUALITY

The quality of explosively welded joints has been determined non-destructively by visual examinations, ultrasonic inspection and radiography. Destructive means include the peel test, bend test and tensile-shear test for determining the mechanical strength of joints. Metallography and hardness surveys also have been used to assess the quality of the weld and surrounding area.




Fig. 9 Explosively spot welded, lap joints in three base metals

Non-Destructive Tests

Visual Characteristics. Some measure of quality may be determined visually by observing the continuity of the joint at the edges. Gross irregularities on the surface such as excessive pitting, gouging, surface cracking, and deformation are indicative of poor quality. These defects can be minimized if not entirely eliminated through the use of appropriate welding procedures.

Internal Characteristics. Somewhat limited studies have shown promise that ultrasonic inspection can detect discontinuities or lack of bonding at the weld interface. A correlation was obtained between the amplitude of the ultrasonic signal and the amount of separation at the weld interface (1). The amplitude of the signal decreased as weld quality decreased and as the distance between the panels increased as shown in Fig. 10. The figure shows four zones of the same lap joint with the corresponding signal height for each region.

The study, furthermore, revealed that factors other than weld quality such as the curvature and surface finish of the weldment could influence the ultrasonic signal. It was concluded that if weldments exhibiting severe distortion or varying surface finishes were ultrasonically examined, without compensating for these discrepancies, misleading results might be obtained.

Radiography has been employed to detect defects and has shown some cracking. It has also appeared to have shown the internal contour of spot welds. The existence of surface indentations, however, has partially obscured the image so that the results of radiography appear to be questionable. Radiographic inspection of seam welded joints also disclosed only visible surface irregularities and did not disclose known discontinuities in the joint.

Destructive Tests

Peel Test. The soundness of explosive welds




Fig. 10 Comparison between amplitude of ultrasonic signal and weld quality

- A (top left): amplitude = 1.2
- B (top right): amplitude = 0.7
- C (bottom left): amplitude = 0.2
- D (bottom right): amplitude = 0 X500



Fig. 11 Chisel tested spot weld in 1/16-in-thick, half-hard copper

also has been determined by destructive tests such as the peel or chisel test. These tests are conducted by peeling one member back against the weld or by driving a chisel between the members until failure occurs around the periphery of the weld, through the weld interface, or a combination of both. Any lack of bonding is noted.

The result of a chisel test on a spot weld in 1/16 in. thick, half-hard copper is shown in Fig. 11. Although the weld was separated with diffi-




Fig.12 Microstructures of weld interfaces in explosively welded materials

culty (as evidenced by chisel marks on the panels), its center was not bonded.

Metallography. The weld interface of several explosively bonded materials as revealed at higher magnifications by an optical microscope is shown in Fig.12. These microstructures are representative of joints having good tensile shear strengths. An explosive weld is shown in a high strength, 2000 series aluminum alloy in Fig.12A. In Fig.12B, the interface of the 5000 series aluminum alloy was so well bonded that it was difficult to find. Zones similar to the light areas in Fig.12C have been reported to be solidified melt (10). The interface of an explosively welded magnesium alloy is shown in Fig.12D. A low-carbon steel interface is illustrated in Fig.12E and a copper interface in Fig.12F. Other microstructures also were observed in these specimens indicating considerable variation across the welded interfaces.

The structure of a low strength joint in aluminum alloy 2024-T3 is shown in Fig.13 (1). It can be seen that the weld exhibited cracking and a partially bonded wave shaped interface.

Fine discontinuities which could not be adequately observed with the optical microscope have also been noted in explosively bonded joints. Since it was desirable to know whether the irregularities were microstructure or defects such as




Fig.13 Microstructure observed in low strength explosive welds in 2024-T3 aluminum alloy. A (top): fractured interface; B (bottom): partially bonded, wave-shaped interface; X500

cracking, they were identified with the electron microscope which has a higher resolving power. For example, consider the island-like structure in the cladding of Fig.14A. This photomicrograph shows an explosive weld in 1/16-in-thick alclad aluminum alloy 2024-0. It was not determined with certainty whether the periphery of the island were a crack or solid material when this area was examined up to X1500. The electron microscope, however, revealed that the periphery of the island was composed of solid material. A reproduction of the structure revealed by the electron microscope is shown in Fig.14B. The periphery of the island is the line indicated by the arrows. The microstructure above the line represents cladding outside the island and the structure below the line reveals that the island was composed of clad material.

Tensile Shear Strength. The quality of an explosive welded joint may be evaluated, within limits, by its tensile shear strength and mode of failure. Factors associated with the structure of the joint such as workhardening may increase the strength of the weld above that of the base metal whereas structural discontinuities such as crack-





Fig.14 Structure in explosively welded 1/16-in-thick alclad aluminum alloy 2024-0. A (top): X500
B (bottom): X5600

ing and lack of bonding can lower the base metal properties. The tensile shear strengths of a number of explosively welded materials were discussed previously.

The strength values were obtained from the tensile shear specimen shown in Fig.15A. Mode of failure exhibited by this specimen when seam welded is shown in Fig.15B. The lower specimen sheared through the weld and the middle specimen failed by a combination of tensile and shear within the overlap. The upper specimen failed through the base metal, adjacent to the overlap. This type of failure was characteristic of the higher strength specimens. Although these joints were seam welded, explosive spot welds may also exhibit somewhat similar failures. Two spot welded lap joints which failed outside the weld area are shown in Fig.16.

Hardness. The effects of explosive welding on base metal characteristics may be determined by hardness surveys. Pearson and Hayes (7) have reported base metal combinations such as steel to tantalum and tantalum to itself were hardened ex-





Fig.15 Tensile shear tests of explosive seam welds in lap joints. A (top): tensile shear specimen; B (bottom): mode of failure

tensively at the weld interface due to alloying or the formation of a new phase. It was further reported that some metal systems including copper and monel exhibited interfacial hardnesses lower than that in the rest of the joint. This was attributed to annealing during welding or the formation of dendritic regions.

Hardness changes were also detected in metal systems that appeared similar to the as received material upon being examined with the optical microscope. It was reported that stainless steel, molybdenum and Rene 41 exhibited regions of high hardness in the weld interface without any basic change in the structure of the metal.

The base material away from the interface for all of these materials, however, was reported work hardened by the welding operation. The degree of hardening varied according to the material combination.

Bend. The ductility of a welded joint and defects such as cracking in the weldment can be determined to some extent by bend tests. As an example, a 1-in-wide, longitudinal bend specimen was fabricated from an explosively welded lap joint in 1/16-in. aluminum alloy 2024-T3. The specimen was bent cold around a 3/4-in-dia mandrel for about 36 deg before cracking occurred as shown in Fig.17. Another specimen made with the same welding con-




Fig. 16 Tensile shear tests of explosive spot welds in lap joints No. 423 copper to copper; No. 434 steel to copper




Fig. 17 Guided bend specimens in explosively welded aluminum alloy 2024

ditions was annealed and then bent cold through 180 degrees around the same mandrel, Fig. 17.

APPLICATIONS

The feasibility of explosive welding has been demonstrated and procedures and techniques are being studied by both government and industry with particular reference in some instances to specific applications. This effort to apply the process, of course, does not preclude the need for longer range studies of a research nature but does highlight the interest in exploring its possibilities for satisfying certain immediate joining situations.

As explosive welding is developed, the number and type of applications that might be served will probably grow. At the present time, there are several likely applications. The process appears useful for joining relatively thin sheet to thicker sheet or plate such as is shown in Fig. 18. This type of weldment could represent the joining of attachments to structural members including the




Fig. 18 1/16-in-thick 2024-T3 aluminum-alloy panel explosively welded to 1-in-thick 2024-T-4 aluminum-alloy plate

joining of brackets to pressure vessels or boxes, panels or clips to metal bulkheads, decking or other massive structures.

Laminated materials may be seam or spot welded as shown in Fig. 19. Since explosive welding is one of few welding processes that are capable of making area welds or edge joints it may have a very significant place in the fabrication of items requiring laminated and composite type joints and structures, the fabrication of clad materials, or transition couplings.

Cylindrical components may also be explosively welded as shown in Fig. 20. The specimen on the left was a section from two pieces of aluminum tubing which were welded together. Although the weld is intermittent, the sample does indicate the possibility of explosive welding this type of configuration. The other specimen shows several aluminum tubes bonded inside an aluminum pipe. These results suggest that pipe and tubing can be joined by explosive welding for applications such as gun liners, heat exchangers, filters, casings and sleeves.

Explosive welding may also be useful as a method for fabricating and repairing structures in locations that would be inaccessible or inconvenient for other processes. It might also prove useful for welding a limited number of items which might not warrant the procurement of elaborate, expensive equipment.

CONCLUSIONS

It may be concluded that:

1 Area, spot and seam welds can be produced with the explosive welding process.




Fig. 19 Explosive seam and spot welds in aluminum alloy 2024-T3, multilayer specimens

2 Explosive welding appears capable of producing edge, lap and tee joints and shows promise for making corner and butt joints.

3 Explosive welding can join a variety of metals and alloys in similar and dissimilar combinations.

4 The quality of explosively welded joints may be determined by a number of destructive and nondestructive tests.

5 Explosive welding offers considerable potential for use in a variety of civilian and military applications.

ACKNOWLEDGMENT

The author wishes to express his appreciation to Mr. H. Markus for granting permission to publish this work and to Messrs. F.W. Hussey and I.G. Betz for their technical assistance in the preparation of this paper.

REFERENCES

- 1 "Explosive Welding of Aluminum Alloys", by H. Addison, Jr., W.E. Fogg, I.G. Betz and F.W. Hussey, Welding Journal, American Welding Society, vol. 42, No.8, 1963.
- 2 "Explosive Working of Metals", by J.S. Rinehart and J. Pearson, The Macmillan Company, New York, N.Y., 1963.
- 3 "Welding Handbook, Section One", 5th edi-




Fig. 20 Explosively bonded, cylindrical aluminum components

tion, American Welding Society, New York, N.Y., 1962.

4 "Explosive Weld Trials at P and W Florida Site", Metalworking News, May 27, 1963.

5 Lecture on "Explosive Cladding", by A.H. Holtzman, Drexel Institute, May 1963.

6 "Metallurgical Properties of Some Explosively Welded Metals", by G.A. Hayes and J. Pearson, U.S. Naval Ordnance Test Station Technical Publication 2950, NAVWEPS Report 7925, June 1962.

7 "Research in Explosive Welding", by J. Pearson and G.A. Hayes, Technical paper SP 63-97, American Society of Tool and Manufacturing Engineers, 1963.

8 "Explosive Welding", by D.E. Davenport, Technical paper SP 62-77, American Society of Tool and Manufacturing Engineers, 1962.

9 "Explosive Welding", by V. Philipchuk, Aeronautical Systems Division Technical Report 61-124, Wright-Patterson Air Force Base, Ohio, August 1961.

10 "Flow Configurations in Colliding Plates: Explosive Bonding", by G.R. Cowan and A.H. Holtzman, Journal of Applied Physics, American Institute of Physics, vol. 34, No. 4 (Part I), 1963.

DISTRIBUTION

1 - Hq, U.S.Army Materiel Command Attn: AMCRD-RS-CM-M Washington, D. C. 20313	1 - Commanding General U.S.Army Electronics Command Attn: Mr. H. H. Kedesdy Fort Monmouth, N.J. 07703
5 - Attn: Chief Scientist, AMCSA-SC	
1 - Commanding General U.S.Army Munitions Command Attn: Technical Information Div Dover, New Jersey 07801	1 - Commanding Officer U.S.Army Materials Research Agency Attn: AMXMR-PT, Mr. G. Darcy Watertown Arsenal Watertown, Mass. 02172
1 - Attn: AMSMU-S, Dr. J.V.R.Kaufman	
1 - Attn: AMSMU-I, Mr. R. M. Schwartz	1 - Commanding Officer Picatinny Arsenal Attn: Mr. J. Matlack Plastics & Packaging Lab Dover, N. J. 07801
1 - Attn: AMSMU-E, Mr. C. H. Staley	
1 - Attn: AMSMU-LM, Marine Corps Liaison Officer	1 - Commanding Officer Ammunition Procurement and Supply Agency Attn: SMUAP-Mat'ls Eng Joliet, Ill. 60436
1 - Attn: AMSMU-LC, Combat Development Command Liaison Officer	
1 - Commanding General U.S.Army Test & Evaluation Command Attn: STEAP-DS-TU, Mr. W. Pless Aberdeen Proving Ground, Md. 21005	1 - Commanding Officer USA CDC Ordnance Agency Aberdeen Proving GroundMd. 21005
2 - Attn: Library	
1 - Commanding General U.S.Army Missile Command Attn: Technical Information Div Redstone Arsenal, Alabama 35809	2 - Commanding Officer Rock Island Arsenal Attn: Laboratory Rock Island, Ill. 61202
1 - Attn: Mr. R. Fink, AMSMI-RXX	1 - Attn: Mr. Robt Shaw, Laboratory
1 - Attn: Mr. E. J. Wheelahan, AMSMI-RSM	1 - Commanding Officer Springfield Armory Attn: Mr. E. Abbe, SWESP-TX Springfield,,Mass. 01101
1 - Attn: Mr. R. E. Ely	
1 - Attn: Mr. T. N. L. Purghe	1 - Commanding General U.S.Army Tank-Automotive Center Attn: SMOTA-RCS Warren, Mich. 48089
1 - Attn: Mr. E. Fohrell	
5 - Attn: Mr. C. Martens, AMSMI	2 - Attn: SMOTA-RCM.1

1 - Commanding General Engineering R&D Laboratory Fort Belvoir, Va. 22060	1 - Commander U.S.Naval Ordnance Laboratory Attn: Code WM Silver Spring, Md. 20910
1 - Commanding General Chemical Research & Development Laboratories Attn: Chemical-Biological- Radiological Agency Edgewood Arsenal, Md. 21010	1 - Commandant U.S.Naval Proving Ground Attn: Terminal Ballistics Lab Dahlgren, Va. 22248
1 - Commanding Officer Ballistic Research Laboratory Attn: Mr. E. E. Minor Aberdeen Proving Ground, Md. 21005	1 - Commander U.S.Naval Research Laboratory Attn: Mr. J. E. Scrawley Anacostia Station Washington, D. C. 20390
1 - Commanding Officer U.S.Army Coating & Chemical Laboratories Attn: Dr. C. Pickett Aberdeen Proving Ground, Md. 21005	1 - Hq, Air Research and Development Command Attn: RDIDPA Andrews Air Force Base Washington, D. C. 20331
1 - Commanding Officer Watertown Arsenal Attn: Technical Reference Section Watertown, Mass. 02172	1 - Commanding General Aeronautical Systems Division Attn: Materials Laboratories Wright-Patterson AFB, Ohio 45433
1 - Commanding Officer Lake City Army Ammunition Plant Independence, Mo. 64050	1 - Attn: Aero Research Laboratory
1 - Commanding Officer U.S.Army Research Office-Durham Attn: Metallurgy & Ceramics Div Box CM, Duke Station Durham, N. C. 27706	1 - Commander Arnold Engineering and Develop- ment Center Air Research & Development Center Tullahoma, Tenn. 37389
1 - Commanding Officer Harry Diamond Laboratory Attn: AMXDO-TIB Washington, D. C. 20438	1 - National Aeronautics and Space Administration Attn: Mr. B. G. Achhammer 1512 H St., N.W. Washington, D. C. 20546
1 - Chief, Bureau of Ships Department of the Navy Attn: Code 343 Washington 25, D. C.	1 - Attn: Mr. G. C. Deutsch
1 - Chief, Bureau of Naval Weapons Department of the Navy Attn: RRMA-211 Washington, D.C. 20360	1 - Attn: Mr. R. V. Rhode
	1 - Commander U.S.Naval Ordnance Test Station Attn: Code 5557 China Lake, Calif. 93557

1 - Geo C. Marshall Space Flight Center Attn: Mr. W. A. Wilson, M-ME-M Huntsville, Ala. 35809	1 - Mr. J. B. Hess Department of Metallurgical Research Kaiser Aluminum & Chemical Corp. Spokane 69, Washington
1 - NASA Lewis Flight Propulsion Laboratory Attn: Library 21000 Brookpark Rd Cleveland, Ohio 44135	1 - Dr. Schrade F. Radtke American Zinc Institute 60 E. 42nd St New York 17, N. Y.
1 - Defense Metals Information Center Battelle Memorial Institute Columbus, Ohio	1 - Dr. Thomas A. Read University of Illinois Urbana, Ill
1 - U.S. Atomic Energy Commission Office of Technical Information Ext. P.O. Box 62 Oak Ridge, Tenn. 37831	1 - Dr. Wm. Rostoker Armour Research Foundation Illinois Institute of Technology 10 W. 35th St. Chicago, Ill. 60616
1 - Army Reactor Branch Division of Reactor Development Atomic Energy Commission Washington 25, D. C	1 - Mr. Robert H. Brown Aluminum Company of America Alcoa Research Laboratories P.O. Box 772 New Kensington, Pa.
20 - Defense Documentation Center Cameron Station Alexandria, Va. 22314	1 - Curtiss-Wright Corporation Woodridge, N. J. Attn: A. M. Kettle
1-- Mr. Carson L. Brooks Reynolds Metals Company 4th & Canal Sts. Richmond, Va.	1 - Dr. C. M. Adams, Jr. Division of Sponsored Research Massachusetts Institute of Technology Cambridge, Mass.
1 - Dr. Robert S. Busk Dow Chemical Company Midland, Mich. 48641	
1 - Dr. LaVerne W. Eastwood Olin Mathieson Chemical Corporation Metallurgy Division 400 Park Avenue New York 22, N. Y.	

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
FRANKFORD ARSENAL, Research and Development Directorate Philadelphia, Pa. 19137		Unclassified
		2b. GROUP
		NA
3. REPORT TITLE		
EXPLOSIVE WELDING		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
Research report		
5. AUTHOR(S) (Last name, first name, initial)		
ADDISON, Harry J., Jr.		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
May 1964	15	10
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
AMCMS Code 5025.11.842	FA Report A64-13	
b. PROJECT NO.		
DA Project 1-A-0-24401-A-110		
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.	Paper No.: 64-MD-47 (Amer Soc Mech Eng)	
10. AVAILABILITY/LIMITATION NOTICES		
Qualified requesters may obtain copies of this report from DDC.		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY
		AMCRD-RS-CM-M
13. ABSTRACT		
Explosive welding occurs when adjacent surfaces of appropriately positioned metals are properly thrust together by energy released from an explosive source. The procedure consists essentially of locating the metal members being welded between an explosive charge and an anvil with the lower member resting on the anvil. Explosive welding can be used for spot and seam welding and cladding. Lap, tee, and edge joints (such as is experienced in cladding) have been fabricated. Corner and butt joints are feasible. Tensile-shear strengths approaching that of the base metal have been obtained in various materials in seam-welded lap joints. Explosive spot welds have failed outside the nugget. Explosive welding is feasible and offers possibilities as a future fabrication method.		

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Welding Aluminum Alloys Copper Steel Magnesium Alloys Sheet Alloys Mechanical Properties Nondestructive Testing Explosives Metallography						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.