

UNCLASSIFIED

AD NUMBER
AD451010
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; SEP 1964. Other requests shall be referred to U.S. Naval Ordnance Laboratory, White Oak, Silver Spring, MD.
AUTHORITY
USNOL ltr, 29 Aug 1974

THIS PAGE IS UNCLASSIFIED

NTIS

AD-451 010

NAVORD REPORT

6772

WIND TUNNEL INVESTIGATION OF THE MK 76 PRACTICE BOMB

11 SEPTEMBER 1964



U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

Aerodynamic Research Report 79

WIND TUNNEL INVESTIGATION
OF THE MK 76 PRACTICE BOMB

Prepared by:
Frank J. Regan

ABSTRACT: The MK 76 is a 25 pound, 4 inch diameter Practice Bomb used in large quantities by the U. S. Navy and Air Force. This report gives the results of the static and dynamic wind tunnel tests of the basic body with various combinations of fuzes, lugs and tails.

Originally, the configuration consisted of the basic body with a shrouded cruciform tail. This bomb had an impact fuze and a carrying lug. The effect of the presence of this fuze and lug on the bomb's normal force and pitching moment were investigated in the Mach number range between 0.29 and 1.75. The effect of moving the tail aft slightly was also investigated. The results of these tests indicated a center of pressure 3.2 calibers aft of the nose. Moving the tail aft brought the center of pressure aft to a point 3.8 calibers from the nose.

It was then decided to replace the shrouded tail by two tails of unshrouded design. The first of these was a cruciform tail with a swept leading edge. The basic body was tested with this tail in three positions. The result was a center of pressure location 4.0 calibers aft of the nose, for the forward position of the tail, to 4.5 calibers aft of the nose, for the aft position of the tail. Finally, a cruciform tail of rectangular fins was tested. The result was a center of pressure location of about 4.6 calibers aft of the nose.

Pitch damping tests were carried out on the bomb with both the cruciform swept and cruciform rectangular tails. Drag measurements were made of the bomb with both the shroud and cruciform rectangular tails with combinations of lugs and fuzes.

PUBLISHED NOVEMBER 1964
U. S. NAVAL ORDNANCE LABORATORY
White Oak, Silver Spring, Maryland

NAWORD REPORT 6772

11 September 1964

WIND TUNNEL INVESTIGATION OF THE MK 76 PRACTICE BOMB

The purpose of this investigation was to obtain the static stability (normal force and pitching moment), drag and pitch damping moment data for the MK 76 Practice Bomb.

This project was performed at the request of the Bureau of Naval Weapons under Task Number RMO 42-005/212-1/F008-09-01.

The author wishes to acknowledge the assistance rendered by Mr. P. Ceretta in data acquisition, Miss M. E. Falusi in data reduction and compilation, and Miss A. Evans in report preparation.

R. E. ODENING
Captain, USN
Commander


K. R. ENKENHUS
By direction

NAVORD REPORT 6772

CONTENTS

	Page
Introduction	1
Symbols	1
Nomenclature	2
Description of Bomb Configurations	2
Test Technique	3
Data Reduction	4
Results and Discussion	5
Conclusions	7
References	8

ILLUSTRATIONS

Figure	Title
1	MK 76 Practice Bomb with Impact Fuze and Shroud Tail in Forward Position
2	MK 76 Practice Bomb with Impact Fuze and Shroud Tail in Aft Position
3	MK 76 Practice Bomb with Impact Fuze and Cruciform-Swept Tail in Aft Position
4	MK 76 Practice Bomb with Airburst Fuze and Cruciform-Rectangular Tail
5	MK 76 Practice Bomb with Shroud Tail in Forward Position
6	Shroud Tail for the MK 76 Practice Bomb
7	Cruciform-Swept Tail for MK 76 Practice Bomb
8	Cruciform-Rectangular Tail for MK 76 Practice Bomb
9	Lug for MK 76 Practice Bomb
10	Fuze Designs Used with MK 76 Practice Bomb
11-41	Normal Force, C_N , and Pitching Moment, C_m , Versus Angle of Attack, α
42, 43	Drag Coefficient, C_{D_o} , Versus Mach Number
44	Pitch Damping Coefficient, $C_{m_q} + C_{m_{\dot{\alpha}}}$, Versus Mach Number

TABLES

Table	Title
1	Index of Static Stability, Drag and Pitch Damping Measurements
2	Comparison of the Center of Gravity and the Center of Pressure Among the Various Configurations

NAVORD REPORT 6772

INTRODUCTION

The MK 76 is a 25 pound, 4 inch diameter Practice Bomb used in large quantities by the U. S. Navy and Air Force. This report gives the results of the static and dynamic wind tunnel tests of the basic body with various combinations of fuzes, lugs and tails.

SYMBOLS

A	reference area, $\pi d^2/4$
C_{D_0}	drag force coefficient at zero degrees angle of attack, D/QAd
C_m	static pitching moment coefficient, M_y/QAd
C_{m_α}	derivative of the static pitching moment coefficient with respect to α
$C_{m_q} + C_{m_{\dot{\alpha}}}$	pitch damping coefficient, $(2V/QAd)(\partial L_y/\partial q + \partial M_y/\partial \dot{\alpha})$
C_N	normal force coefficient, N/QA
C_{N_α}	derivative of the normal force coefficient with respect to α
d	maximum body length (2.4 in)
D	drag force
I_{yy}	transverse moment of inertia (about y axis)
l	body length
M	Mach number
M_y	pitching moment (about y axis)
N	normal force
Q	dynamic pressure
q	pitch rate
t	time
V	airspeed

NAVORD REPORT 6772

y	axis normal to bomb's longitudinal axis and in a plane defined by opposing tail fins
α	angle of attack
$\bar{\alpha}$	envelope of plotted pitch damping data
ρ	air density

NOMENCLATURE

B	body
F^1	impact fuze (AN-M146 MTF)
F^2	air burst fuze (XB-125A)
L	body lug
T^1_1	shroud tail in forward position ($l = 13.54$ inches)
T^1_2	shroud tail in aft position ($l = 14.29$ inches)
T^2_1	cruciform-swept tail in forward position ($l = 13.542$ inches)
T^2_2	cruciform-swept tail in mid position ($l = 14.29$ inches)
T^2_3	cruciform-swept tail in aft position ($l = 15.04$ inches)
T_3	cruciform-rectangular tail ($l = 15.04$ inches)

DESCRIPTION OF BOMB CONFIGURATIONS

Table 1 lists the various configurations of the MK 76 Practice Bomb that were tested. Figures 1 through 4 are photographs of all body-tail configurations tested. Figures 5 through 10 are detail drawings of the tails, lugs and fuzes.

All models used in the static tests were 0.6 scale. Since the bomb is 4.0 inches in diameter the wind tunnel models for the static tests were 2.4 inches in diameter.

For brevity all configurations have been represented symbolically by a code which designates the body, lug, fuze, tail and tail position. Combining the symbols listed in the nomenclature, it is possible to represent any configuration by

NAVORD REPORT 6772

a code designation. Thus, the shrouded-tail is represented by the superscript ¹ in the symbol T_j^1 . The subscript j takes on the value 1 or 2 to designate the forward or aft position of the tail. When the shrouded-tail is in the forward or aft position the corresponding body length is 13.54 or 14.29 inches, respectively. The swept cruciform and rectangular cruciform tails are represented by the symbols T^2 and T^3 . The swept cruciform tail was tested in three positions: forward, mid and aft. The corresponding body lengths are 13.54, 14.29 and 15.04 inches, respectively. The symbol T^3 is used with the subscript j taking on the values 1, 2 and 3 to designate the forward, mid and aft positions. The tail T^3 was only tested in one position (with a body of length 15.04 inches). For this reason, no subscript is used. Drawings of tails T^1 , T^2 and T^3 are given in Figures 6, 7 and 8, respectively.

Bombs were tested with a mounting lug and two different fuzes. The lug is represented by the symbol L , and the fuzes by F^1 for the impact fuze and F^2 for the airburst fuze. The absence of L and F indicates that the bomb was tested without that component. Figures 9 and 10 are drawings of the lug and fuzes, respectively.

In the plotted data (Figures 11 through 44) the above code convention has been used to designate the lug, fuze, tail and tail position, where appropriate. Representative configurations have been given in Figures 1 through 4. The codes for these figures are: $BLF^1 T_1^1$, $BLF^1 T_2^1$, $BLF^1 T_3^2$ and $BLF^2 T^3$, respectively.

TEST TECHNIQUE

The wind tunnel tests were carried out in Supersonic Tunnel Number 1. Force and moment data were obtained using a multiple-component internal strain-gage balance. The free oscillation technique was used in the pitch damping tests. The pitch damping model was dynamically balanced about the full scale center of gravity. The model was mounted by means of internal ball bearings to a transverse rod through the center of gravity. Except for a negligible amount of bearing torque the model has complete freedom in pitch.

The pitch damping test technique was as follows: Tunnel flow was established with the model in a non-trimmed condition. From this initial trim displacement the model under-

NAVORD REPORT 6772

went a series of pitch damping oscillations of decreasing amplitude. This oscillatory motion was recorded with a 16 mm movie film speed of 64 frames per second.

DATA REDUCTION

The static wind tunnel data were recorded on IBM cards using the automatic recording system described in reference (2). Using the equations in reference (3), these data were reduced to coefficient form on an IBM 650 digital computer. The data have been corrected for the elastic deflection of the sting support caused by aerodynamic loading.

The moment reference center was taken to be the center of gravity of each wind tunnel model. Table 2 gives the center of gravity location from the nose of the model. The nose of the bomb proper, exclusive of any fuzes present, is the reference point from which the center of gravity and center of pressure are measured.

The pitch damping data reduction method is described in detail in reference (4). Briefly, the method consists of two parts: reading the film and fitting an envelope to the plotted film data. The angle of attack of the model was measured from each frame of film. A time record was obtained from a knowledge of the film speed. A plot of the angular deflection of the model versus time resulted in a damped sinusoidal curve. The logarithmic decrement of the envelope of this curve gave, after non-dimensionalizing the measured quantities, the pitch damping coefficient, $C_{m_q} + C_{m_{\dot{\alpha}}}$. The equation of motion of the

unconstrained pitch oscillations is, in coefficient form,

$$\ddot{\alpha} - \frac{(C_{m_q} + C_{m_{\dot{\alpha}}})QAd^2}{2VI_{yy}} \dot{\alpha} - \frac{C_{m_{\alpha}}QAd}{I_{yy}} \alpha = 0 \quad (1)$$

which has as an approximate solution for the case of light damping:

$$\alpha = \bar{\alpha} \cos \left\{ \sqrt{\frac{-C_{m_{\alpha}}QAd}{I_{yy}}} t \right\} \quad (2)$$

The quantity $\bar{\alpha}$ is an analytic expression for the envelope of the plotted pitch damping data. For the case of linear damping this is given by the following expression:

$$\bar{\alpha} = \alpha_{op} \left(\frac{(C_{m_q} + C_{m_{\dot{\alpha}}}) Q A d^2}{4 V I_{yy}} \right) t \quad (3)$$

where α is the pitch angle at an arbitrarily selected initial time. Thus, for two points on the envelope, $\bar{\alpha}(t)$ and α_0 , separated in time by t seconds, equation (3) may be solved for the pitch damping coefficient, $C_{m_q} + C_{m_{\dot{\alpha}}}$. The result is an expression containing only known or measurable quantities.

RESULTS AND DISCUSSION

Table 1 lists the configurations tested and provides an index to the graphical presentation of wind tunnel results. The static data are presented in Figures 11 through 41. These data are the normal force coefficient, C_N , and the pitching moment coefficient, C_m , versus angle of attack, α . The drag measurements are given in Figures 42 and 43 as drag coefficient at zero degrees angle of attack, C_{D_0} , versus Mach number. The

results of the pitch damping tests are given in Figure 44 as the pitch damping coefficient, $C_{m_q} + C_{m_{\dot{\alpha}}}$ versus Mach number.

These data will now be examined in order to recommend a configuration.

It will be noted in Table 1 that the most comprehensive static wind tunnel data were obtained using the basic body, B, the lug L, the impact fuze, F^1 , and the shrouded tail in the forward position, T^1_1 . These components were combined into configurations BF^1_1 , BLT^1_1 , $BF^1_1 T^1_1$, and $BLF^1_1 T^1_1$. These were tested at Mach numbers of 0.29, 0.42, 0.50 and 0.59. Data were also obtained on the BLT^1_1 and $BLF^1_1 T^1_1$ configurations at Mach numbers of 0.72, 0.85 and 1.75.

NAVORD REPORT 6772

A comparative analysis of the various configurations must involve assessing the relative influence of lugs, fuzes, tail design and tail position. Table 2 was prepared to facilitate this comparison. It presents the center of pressure (in calibers) from the nose for the four configurations at a Mach number of 0.59.

There are certain features of these data that should be emphasized. It will be noted that the addition of a lug moves the center of pressure slightly rearward. The addition of a nose fuze, on the other hand, moves the center of pressure forward. Moving the tail rearward about 0.3 calibers moves the center of pressure rearward about 0.6 calibers.

A limited amount of wind tunnel data was taken using the cruciform swept tail, T^2 , and the cruciform rectangular tail, T^3 . Table 2 gives the center of pressure of the two unshrouded tails and the shrouded tail. The shrouded tail, T^1 , and the cruciform swept tail, T^2 , can be compared using configurations BLT^1_1 and BLT^2_1 . This comparison shows that with the same body length the cruciform swept tail, T^2 , has a center of pressure location further aft than the shrouded tail, T^1 . A similar conclusion is reached in comparing configurations BLT^1_2 , $BLF^1 T^1_2$ with configurations BLT^2_2 , $BLF^2 T^2_2$.

The T^2 tail was tested in a third position. It can be seen that moving the tail about 0.3 calibers further aft results in a rearward displacement of the center of pressure of about 0.5 calibers. It should be noted in passing that as in the case of the T^1 tail the presence of the fuze moves the center of pressure forward.

Finally, a series of tests were conducted of the T^3 tail in a position corresponding to a body length of 6.267 calibers. This is the same body length as when the T^2 tail was used.

Since no tests were conducted on the shrouded tail, T^1 , in this position, direct comparison may be made only between the T^2 and T^3 tails. In spite of the fact that these tails cannot be compared at the same Mach number, it is obvious that the T^3 tail is superior to the T^2 tail, as far as static test results are concerned. Therefore, it was decided to compare the

NAVORD REPORT 6772

effectiveness of the cruciform swept tail, T_s^3 , and the cruciform rectangular tail, T^3 , in pitch damping. The results of these pitch damping tests are given in Figure 44 as a comparison of configurations BLF¹ T^3 , BT³ and BT_s³. It is evident that, while all configurations are similar in pitch damping, the configurations using the cruciform rectangular tail, T^3 , are superior to the configuration using the cruciform swept tail, T^3 . The presence of the fuze increases the pitch damping coefficient.

A series of drag tests were also conducted on configurations using the shrouded tail, T^1 , and the cruciform rectangular tail, T^3 . The results are presented in Figures 42 and 43, respectively. In examining these figures, it can be seen that the presence of lugs increases drag and that the impact fuze, F^1 , results in a higher configurational drag than does the airburst fuze, F^3 .

CONCLUSIONS

The nonshrouded tails, T^2 and T^3 , give a further aft location of the center of pressure than does the shrouded tail, T^1 . Of these nonshrouded tails, the cruciform rectangular tail, T^3 , is superior both statically and dynamically.

NAVORD REPORT 5772

REFERENCES

- (1) Griffin, T., Wind Tunnel Request, WTR 419 (1957)
- (2) Gilbert, B. D., "Automatic Data Processing System (ADAPS) for the Supersonic Wind Tunnels," NAVORD Rpt 2813 (1953)
- (3) Shantz, I., Gilbert, B. D., and White, C. E., "NOL Wind Tunnel Internal Strain-Gage Balance System," NAVORD Rpt 2972 (1953)
- (4) Shantz, I., and Groves, R. T., "Damping and Static Stability in Pitch Measurements of the Ten Caliber Basic Finner at Supersonic Speeds," NAVORD Rpt 4516 (1960)




FIG.1 MK 76 PRACTICE BOMB WITH IMPACT FUZE AND SHROUD TAIL
IN FORWARD POSITION




FIG. 2 MK 76 PRACTICE BOMB WITH IMPACT FUZE AND SHROUD TAIL
IN AFT POSITION




FIG 3 MK 76 PRACTICE BOMB WITH IMPACT FUZE AND CRUCIFORM-SWEPT TAIL
IN AFT POSITION




FIG.4 MK 76 PRACTICE BOMB WITH AIRBURST FUZE AND CRUCIFORM-
RECTANGULAR TAIL




FIG. 5 MK 76 PRACTICE BOMB WITH SHROUD TAIL IN FORWARD POSITION

FIG. 6 SHROUD TAIL FOR THE MK 76 PRACTICE BOMB




FIG. 7 CRUCIFORM-SWEPT TAIL FOR MK 76 PRACTICE BOMB




FIG.8 CRUCIFORM-RECTANGULAR TAIL FOR MK 76 PRACTICE BOMB







FIG 9 LUG FOR MK 76 PRACTICE BOMB



AIR-BURST FUZE (XB-125A)



IMPACT FUZE (AN-M146 MTF)




FIG. 10 FUZE DESIGNS USED WITH MK 76 PRACTICE BOMB




FIG. 11 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1 AT MACH NUMBER 0.29




FIG. 12 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1T1 AT MACH NUMBER 0.20




FIG. 13 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BP-1 AT MACH NUMBER 0.29




FIG. 1. NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION SLF T₁ AT MACH NUMBER 0.29

WATGNO 233027 6772




FIG. 18 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BT₁ AT EACH NUMBER 0.42




FIG. 10 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION RUP AT MACH NUMBER 0.20




FIG. 17 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B5-T1 AT MACH NUMBER 0.42




FIG. 18 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLF T₁ FOR MACH NUMBER 0.42




FIG. 19 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1 AT MACH NUMBER 0.50




FIG. 20 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLT AT MACH NUMBER 0.50




FIG. 21. NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION 31-1 AT MACH NUMBER 0.50




FIG. 22 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLP-T AT MACH NUMBER 0.60




FIG. 23 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BT₁ AT MACH NUMBER 0.59




FIG. 24 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION 8L1 AT MACH NUMBER 0.89




FIG. 23 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION H-1 AT MACH NUMBER 0.59




FIG. 26 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLE-T₁ AT MACH NUMBER 0.59




FIG. 27 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B11 AT MACH NUMBER 0.72




FIG. 28 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1C-1 AT MACH NUMBER 0.72




FIG. 29 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION 5L1 AT MACH NUMBER 0.85




FIG. 30 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1-7 AT MACH NUMBER 0.85




FIG. 31. NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLC AT MACH NUMBER 1.75




FIG. 32 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B11-1 AT MACH NUMBER 1.75




FIG. 33 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION 811 AT MACH NUMBER 0.33




FIG. 34 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION HL-10 AT MACH NUMBER 0.23




FIG. 35 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION SLT₁ AT MACH NUMBER 0.23




FIG. 35 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION A11 AT MACH NUMBER 0.23




FIG. 37. NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLW-1 AT MACH NUMBER 0.23




FIG. 88 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1F-1 AT MACH NUMBER 0.23




FIG. 39 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION B1T9 AT MACH NUMBER 0.79




FIG. 40 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLP-1* AT MACH NUMBER 0.79




FIG. 41 NORMAL FORCE COEFFICIENT AND PITCHING MOMENT COEFFICIENT VERSUS ANGLE OF ATTACK FOR CONFIGURATION BLF¹-1 AT MACH NUMBER 0.79





FIG. 42 DRAG COEFFICIENT VERSUS MACH NUMBER FOR CONFIGURATIONS USING THE T₁ TAIL

C_{D0}
 C_{D0}
 C_{D0}
 C_{D0}
 C_{D0}



Mach Number

FIG. 43 DRAG COEFFICIENT VERSUS MACH NUMBER FOR CONFIGURATIONS USING THE 1° TAIL




FIG. 44 PITCH DAMPING COEFFICIENT VERSUS MACH NUMBER FOR CONFIGURATIONS RLE-1, BT AND BT2

TABLE 1

INDEX OF STATIC STABILITY, DRAG AND
PITCH DAMPING MEASUREMENTS

Figure	Configuration	Mach No.
<u>Index of Static Stability Measurements</u>		
11	BT_1^1	0.29
12	BLT_1^1	0.29
13	$BF^1 T_1^1$	0.29
14	$BLF^1 T_1^1$	0.29
15	BT_1^1	0.42
16	BLT_1^1	0.42
17	$BF^1 T_1^1$	0.42
18	$BLF^1 T_1^1$	0.42
19	BT_1^1	0.50
20	BLT_1^1	0.50
21	$BF^1 T_1^1$	0.50
22	$BLF^1 T_1^1$	0.50
23	BT_1^1	0.59
24	BLT_1^1	0.59
25	$BF^1 T_1^1$	0.59
26	$BLF^1 T_1^1$	0.59
27	BLT_1^1	0.72
28	$BLF^1 T_1^1$	0.72
29	BLT_1^1	0.85

NAVORD REPORT 6772

TABLE 1 (Cont'd)

INDEX OF STATIC STABILITY, DRAG AND PITCH DAMPING MEASUREMENTS

Figure	Configuration	Mach No.
30	$BLF^1 T_1^1$	0.85
31	BLT_1^1	1.75
32	$BLF^1 T_1^1$	1.75
33	BLT_2^1	0.23
34	$BLF^1 T_2^1$	0.23
35	BLT_3^2	0.23
36	BLT_2^2	0.23
37	$BLF^1 T_2^2$	0.23
38	$BLF^1 T_3^2$	0.23
39	BLT^2	0.79
40	$BLF^1 T^2$	0.79
41	$BLF^2 T^2$	0.79
<u>Index of Drag Measurements</u>		
42	$B-T_1^1$	0.40-3.20
43	$B-T^2$	0.40-2.20
<u>Index of Pitch Damping Measurements</u>		
44	$BLF^1 T^2, BT^2, BT_2^2$	0.22-0.70

TABLE 2

COMPARISON OF THE CENTER OF GRAVITY AND THE CENTER
OF PRESSURE AMONG THE VARIOUS CONFIGURATIONS

Configuration	Body Length (calibers)	Mach Number	Center of Gravity from Nose (calibers)	Center of Pressure from Nose (calibers)
BLT ₁ ¹	5.642	0.29	1.600	3.20
BLF ₁ ¹ T ₁ ¹	5.642	0.29	1.542	2.97
BT ₁ ¹	5.642	0.59	1.644	3.19
BLT ₁ ¹	5.642	0.59	1.600	3.20
BF ₁ ¹ T ₁ ¹	5.642	0.59	1.562	2.91
BLF ₁ ¹ T ₁ ¹	5.642	0.59	1.542	3.09
BLT ₂ ¹	5.954	0.23	2.070	3.84
BLF ₁ ¹ T ₂ ¹	5.954	0.23	1.852	3.65
BLT ₁ ²	5.642	0.23	1.507	3.93
BLT ₂ ²	5.954	0.23	1.644	4.17
BLF ₁ ¹ T ₂ ²	5.954	0.23	1.542	4.04
BLF ₁ ¹ T ₃ ²	6.267	0.23	1.646	4.57
BLT ₃ ²	6.267	0.79	1.607	4.68
BLF ₁ ¹ T ₃ ²	6.267	0.79	1.493	4.49
BLF ₂ ² T ₃ ²	6.267	0.79	1.493	4.57

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

No. of
Copies

Chief, Bureau of Naval Weapons
Department of the Navy
Washington, D. C. 20360

Attn: DLI-3

4

Attn: R-14

Attn: RRRE-4

2

Attn: RMGA-811

Attn: RMMO-42

Office of Naval Research
T-3

Washington, D. C.

Attn: Head, Structural Mechanics Branch

Attn: Head, Fluid Dynamics Branch

Director, David Taylor Model Basin
Aerodynamics Laboratory
Washington, D. C.
Attn: Library

Commander, U. S. Naval Ordnance Test Station
China Lake, California
Attn: Technical Library
Attn: Code 406

Director, Naval Research Laboratory
Washington, D. C.
Attn: Code 2027

Commanding Officer
Office of Naval Research
Branch Office
Box 39, Navy 100
Fleet Post Office
New York, New York

NASA
High Speed Flight Station
Box 273
Edwards Air Force Base, California

NASA
Ames Research Center
Moffett Field, California
Attn: Librarian

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

No. of
Copies

NASA
Langley Research Center
Langley Station, Hampton, Virginia
Attn: (Mrs.) Elizabeth R. Gilman, Librarian, Bldg. 1244
Attn: C. H. McLellan
Attn: Adolph Busemann
Attn: Comp. Res. Div.
Attn: Theoretical Aerodynamics Division

NASA
Lewis Research Center
21000 Brookpark Road
Cleveland 11, Ohio
Attn: Librarian
Attn: Chief, Propulsion Aerodynamics Division

NASA
600 Independence Ave., S. W.
Washington, D. C.
Attn: Chief, Division of Research Information
Attn: Dr. H. H. Kurzweg, Director of Research

Office of the Assistant Secretary of Defense (R&D)
Room 3E1065, The Pentagon
Washington 25, D. C.
Attn: Technical Library

Research and Development Board
Room 3D1041, The Pentagon
Washington 25, D. C.
Attn: Library

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314

20

Commander, Pacific Missile Range
Point Mugu, California
Attn: Technical Library

Commanding General
Aberdeen Proving Ground, Maryland
Attn: Technical Information Branch
Attn: Ballistic Research Laboratories

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

No. of
Copies

Commander, Naval Weapons Laboratory
Dahlgren, Virginia

Attn: Library
Attn: Mr. P. Daniels, Code KEM

Director, Special Projects
Department of the Navy
Washington 25, D. C.
Attn: SP-2722

Director of Intelligence
Headquarters, USAF
Washington 25, D. C.
Attn: AFOIN-3B

Headquarters - Aero. Systems Division
Wright-Patterson Air Force Base
Dayton, Ohio
Attn: WWAD
Attn: RRLA-Library

2

Commander
Air Force Ballistic Systems Division
Norton Air Force Base
San Bernardino, California
Attn: BSRVA

2

Chief, Defense Atomic Support Agency
Washington 25, D. C.
Attn: Document Library

Headquarters, Arnold Engineering Development Center
ARO, Inc.
Arnold Air Force Station, Tennessee
Attn: Technical Library
Attn: AEOR
Attn: AEOIM

Commanding Officer, Harry Diamond Laboratories
Washington 25, D. C.
Attn: Library, Room 211, Bldg. 92

Commanding General
U. S. Army Missile Command
Redstone Arsenal, Alabama
Attn: AMSMI-RR (Mr. N. Shapiro)
Attn: AMSMI-RB (Redstone Scientific Information
Center)

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

No. of
Copies

NASA
George C. Marshall Space Flight Center
Huntsville, Alabama
Attn: Dr. E. Geissler
Attn: Mr. T. Reed
Attn: Mr. H. Paul
Attn: Mr. W. Dahm
Attn: Mr. H. A. Connell
Attn: Mr. J. Kingsbury
Attn: ARDAB-DA

APL/JHU (NOW 7386)
8621 Georgia Avenue
Silver Spring, Maryland
Attn: Technical Reports Group
Attn: Mr. D. Fox
Attn: Dr. F. Hill
Attn: Dr. L. L. Cronvich

2

Scientific & Technical Information Facility
P. O. Box 5700
Bethesda, Maryland
Attn: NASA Representative (S-AK/DL)

Commander
Air Force Flight Test Center
Edwards Air Force Base
Muroc, California
Attn: FTOTL

Air Force Office of Scientific Research
Holloman Air Force Base
Alamogordo, New Mexico
Attn: SRLTL

U. S. Army Engineer Research & Development
Laboratories
Fort Belvoir, Virginia
Attn: STINFO Branch

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

University of Minnesota
Minneapolis 14, Minnesota
Attn: Dr. E. R. G. Eckert
Attn: Heat Transfer Laboratory
Attn: Technical Library

Rensselaer Polytechnic Institute
Troy, New York
Attn: Dept. of Aeronautical Engineering

Dr. James P. Hartnett
Department of Mechanical Engineering
University of Delaware
Newark, Delaware

Princeton University
James Forrestal Research Center
Gas Dynamics Laboratory
Princeton, New Jersey
Attn: Prof. S. Bogdonoff
Attn: Dept. of Aeronautical Engineering Library

Defense Research Laboratory
The University of Texas
P. O. Box 8029
Austin 12, Texas
Attn: Assistant Director

Ohio State University
Columbus 10, Ohio
Attn: Security Officer
Attn: Aerodynamics Laboratory
Attn: Dr. J. Lee
Attn: Chairman, Dept. of Aero. Engineering

California Institute of Technology
Pasadena, California
Attn: Guggenheim Aero. Laboratory,
Aeronautics Library
Attn: Jet Propulsion Laboratory
Attn: Dr. H. Liepmann
Attn: Dr. L. Lees
Attn: Dr. D. Coles
Attn: Dr. A. Roshko
Attn: Dr. J. Laufer

Case Institute of Technology
Cleveland 6, Ohio
Attn: G. Kuerti

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

North American Aviation, Inc.
Aerophysics Laboratory
Downey, California
Attn: Chief, Aerophysics Laboratory
Attn: Missile Division (Library)

Department of Mechanical Engineering
Yale University
400 Temple Street
New Haven, Connecticut
Attn: Dr. P. P. Wegener

MIT Lincoln Laboratory
Lexington, Massachusetts

RAND Corporation
1700 Main Street
Santa Monica, California
Attn: Library, USAF Project RAND
Attn: Technical Communications

Mr. J. Lukasiewicz, Chief
Gas Dynamics Facility
ARO, Incorporated
Tullahoma, Tennessee

Massachusetts Institute of Technology
Cambridge 39, Massachusetts
Attn: Prof. J. Kaye
Attn: Prof. M. Finston
Attn: Mr. J. Baron
Attn: Prof. A. H. Shapiro
Attn: Naval Supersonic Laboratory
Attn: Aero. Engineering Library
Attn: Prof. Ronald F. Probstein
Attn: Prof. C. C. Lin

Polytechnic Institute of Brooklyn
527 Atlantic Avenue
Freeport, New York
Attn: Dr. M. Bloom

Attn: Aerodynamics Laboratory

Brown University
Division of Engineering
Providence, Rhode Island
Attn: Librarian

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Air Ballistics Laboratory
Army Ballistic Missile Agency
Huntsville, Alabama

Applied Mechanics Reviews
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas

BUWEPS Representative
Aerojet-General Corporation
6352 N. Irwindale Avenue
Azusa, California

The Boeing Company
Seattle, Washington
Attn: J. H. Russell, Aero-Space Division
Attn: Research Library

United Aircraft Corporation
400 Main Street
East Hartford 8, Connecticut
Attn: Chief Librarian
Attn: Mr. W. Kuhrt, Research Department
Attn: Mr. J. G. Lee

2

Hughes Aircraft Company
Florence Avenue at Teale Streets
Culver City, California
Attn: Mr. D. J. Johnson
R&D Technical Library

McDonnell Aircraft Corporation
P. O. Box 516
St. Louis 3, Missouri

Lockheed Missiles and Space Company
P. O. Box 504
Sunnyvale, California
Attn: Dr. L. H. Wilson
Attn: Mr. M. Tucker
Attn: Dr. R. Smelt

Martin Company
Baltimore, Maryland
Attn: Library
Attn: Chief Aerodynamicist
Attn: Dr. W. Morkovin, Aerophysics Division

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

CONVAIR
A Division of General Dynamics Corporation
Fort Worth, Texas
Attn: Library
Attn: Theoretical Aerodynamics Group

Purdue University
School of Aeronautical & Engineering Sciences
LaFayette, Indiana
Attn: R. L. Taggart, Library

University of Maryland
College Park, Maryland
Attn: Director
Attn: Dr. J. Burgers
Attn: Librarian, Engr. & Physical Sciences
Attn: Librarian, Institute for Fluid Dynamics
and Applied Mathematics
Attn: Prof. S. I. Pai

2

University of Michigan
Ann Arbor, Michigan
Attn: Dr. A. Zuehlke
Attn: Dr. A. Laporte
Attn: Department of Aeronautical Engineering

Stanford University
Palo Alto, California
Attn: Applied Mathematics & Statistics Lab.
Attn: Prof. D. Bershad, Dept. of Aero. Engr.

Cornell University
Graduate School of Aeronautical Engineering
Ithaca, New York
Attn: Prof. W. R. Sears

The Johns Hopkins University
Charles and 34th Streets
Baltimore, Maryland
Attn: Dr. F. H. Clauser

University of California
Berkeley 4, California
Attn: G. Maslach
Attn: Dr. S. A. Schaaf
Attn: Dr. Holt
Attn: Institute of Engineering Research

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Cornell Aeronautical Laboratory, Inc.
4455 Genesee Street
Buffalo 21, New York
Attn: Librarian
Attn: Dr. Franklin Moore
Attn: Dr. J. G. Hall
Attn: Mr. A. Hertzberg

University of Minnesota
Rosemount Research Laboratories
Rosemount, Minnesota
Attn: Technical Library

Director, Air University Library
Maxwell Air Force Base, Alabama

Douglas Aircraft Company, Inc.
Santa Monica Division
3000 Ocean Park Boulevard
Santa Monica, California
Attn: Chief Missiles Engineer
Attn: Aerodynamics Section

CONVAIR
A Division of General Dynamics Corporation
Daingerfield, Texas

CONVAIR
Scientific Research Laboratory
5001 Kearney Villa Road
San Diego, California
Attn: Asst. to the Director of Scientific Research
Attn: Dr. B. M. Leadon
Attn: Library

Republic Aviation Corporation
Farmingdale, New York
Attn: Technical Library

General Applied Science Laboratories, Inc.
Herrick and Stewart Avenues
Westbury, L. I., New York
Attn: Mr. Walter Daskin
Attn: Mr. R. W. Byrne

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Arnold Research Organization, Inc.
Tullahoma, Tennessee
Attn: Technical Library
Attn: Chief, Propulsion Wind Tunnel
Attn: Dr. J. L. Potter

General Electric Company
Missile Space Division
3198 Chestnut Street
Philadelphia, Pennsylvania
Attn: Larry Chasen, Mgr. Library
Attn: Mr. R. Kirby
Attn: Dr. J. Farber
Attn: Dr. G. Sutton
Attn: Dr. J. D. Stewart
Attn: Dr. S. M. Scala
Attn: Dr. H. Lew
Attn: Mr. J. Persh

2

Eastman Kodak Company
Navy Ordnance Division
50 West Main Street
Rochester 14, New York
Attn: W. B. Forman

2

Library
AVCO-Everett Research Laboratory
2385 Revere Beach Parkway
Everett 49, Massachusetts

3

Chance-Vought Corp.
Post Office Box 5907
Dallas, Texas
Library 1-6310/31-2384

National Science Foundation
1951 Constitution Avenue, N. W.
Washington 25, D. C.
Attn: Engineering Sciences Division

New York University
University Heights
New York 53, New York
Attn: Department of Aeronautical Engineering

AERODYNAMICS LABORATORY
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

New York University
25 Waverly Place
New York, New York
Attn: Library, Institute of Math. Sciences

NORAIR
A Division of Northrop Corporation
Hawthorne, California
Attn: Library

Northrop Aircraft, Inc.
Hawthorne, California
Attn: Library

Gas Dynamics Laboratory
Technological Institute
Northwestern University
Evanston, Illinois
Attn: Library

Pennsylvania State University
University Park, Pennsylvania
Attn: Library, Dept. of Aero. Engineering

The Ramo-Wooldridge Corporation
8820 Bellanca Avenue
Los Angeles 45, California

Gifts and Exchanges
Fondren Library
Rice Institute
P. O. Box 1892
Houston, Texas

University of Southern California
Engineering Center
Los Angeles 7, California
Attn: Librarian

The Editor
Battelle Technical Review
Battelle Memorial Institute
505 King Avenue
Columbus, Ohio

Douglas Aircraft Company, Inc.
Long Beach, California
Attn: Library

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Fluidyne Engineering Corporation
5740 Wayzata Boulevard
Golden Valley
Minneapolis, Minnesota

Grumman Aircraft Engineering Corporation
Bethpage, Long Island, New York

Lockheed Missiles and Space Company
P. O. Box 551
Burbank, California
Attn: Library

Marquardt Aircraft Corporation
7801 Havenhurst
Van Nuys, California

Martin Company
Denver, Colorado

Martin Company
Orlando, Florida
Attn: J. Mayer

Mississippi State College
Engineering and Industrial Research Station
Aerophysics Department
P. O. Box 248
State College, Mississippi

Lockheed Missiles and Space Company
3251 Hanover Street
Palo Alto, California
Attn: Library

General Electric Company
Research Laboratory
Schenectady, New York
Attn: Dr. H. T. Nagamatsu
Attn: Library

Fluid Dynamics Laboratory
Mechanical Engineering Department
Stevens Institute of Technology
Hoboken, New Jersey
Attn: Dr. R. H. Page, Director

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Department of Mechanical Engineering
University of Arizona
Tucson, Arizona
Attn: Dr. E. K. Parks

Vitro Laboratories
200 Pleasant Valley Way
West Orange, New Jersey

Department of Aeronautical Engineering
University of Washington
Seattle, Washington
Attn: Prof. R. E. Street
Attn: Library

American Institute of Aeronautics & Astronautics
1290 Avenue of the Americas
New York, New York
Attn: Managing Editor
Attn: Library

Department of Aeronautics
United States Air Force Academy
Colorado

MHD Research, Inc.
Newport Beach, California
Attn: Technical Director

University of Alabama
College of Engineering
University, Alabama
Attn: Head, Dept. of Aeronautical
Engineering

ARDE Associates
100 W. Century Road
Paramus, New Jersey
Attn: Mr. Edward Cooperman

Aeronautical Research Associates of Princeton
50 Washington Road
Princeton, New Jersey
Attn: Dr. C. duP. Donaldson, President

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Daniel Guggenheim School of Aeronautics
Georgia Institute of Technology
Atlanta, Georgia
Attn: Prof. A. L. Ducoffe

University of Cincinnati
Cincinnati, Ohio
Attn: Prof. R. P. Harrington, Head
Dept. of Aeronautical Engineering
Attn: Prof. Ting Yi Li, Aerospace Engineering Dept.

Virginia Polytechnic Institute
Dept. of Aerospace Engineering
Blacksburg, Virginia
Attn: Dr. R. T. Keefe
Attn: Dr. J. B. Eades, Jr.
Attn: Library

IBM Federal System Division
7220 Wisconsin Avenue
Bethesda, Maryland
Attn: Dr. I. Korobkin

Superintendent
U. S. Naval Postgraduate School
Monterey, California
Attn: Technical Reports Section Library

National Bureau of Standards
Washington 25, D. C.
Attn: Chief, Fluid Mechanics Section

North Carolina State College
Raleigh, North Carolina
Attn: Division of Engineering Research
Technical Library

Defense Research Corporation
P. O. Box No. 3587
Santa Barbara, California
Attn: Dr. J. A. Laurmann

Aerojet-General Corporation
6352 North Irwindale Avenue
Box 296
Azusa, California

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Apollo - DDCS
General Electric Company
A&E Building, Room 204
Daytona Beach, Florida
Attn: Dave Hovis

University of Minnesota
Institute of Technology
Minneapolis, Minnesota
Attn: Prof. J. D. Akerman

Guggenheim Laboratory
Stanford University
Stanford, California
Attn: Prof. D. Bershader, Department of Aero.
Engineering

Space Technology Laboratory, Inc.
1 Space Park
Redondo Beach, California 90200
Attn: STL Tech. Lib. Doc. Acquisitions

University of Illinois
Department of Aeronautical and Astronautical Engineering
Urbana, Illinois
Attn: Prof. H. S. Stilwell

Armour Research Foundation
Illinois Institute of Technology
10 West 35th Street
Chicago, Illinois
Attn: Dr. L. N. Wilson

Institute of the Aeronautical Sciences
Pacific Aeronautical Library
7600 Beverly Boulevard
Los Angeles, California

University of California
Department of Mathematics
Los Angeles, California
Attn: Prof. A. Robinson

Louisiana State University
Department of Aeronautical Engineering
College of Engineering
Baton Rouge, Louisiana

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Mathematical Reviews
American Mathematical Society
80 Waterman Street
Providence, Rhode Island

Stanford University
Department of Aeronautical Engineering
Stanford, California
Attn: Library

University of California
Aeronautical Sciences Laboratory
Richmond Field Station
1301 South 46th Street
Richmond, California

University of Denver
Department of Aeronautical Engineering
Denver 10, Colorado

University of Chicago
Laboratories for Applied Sciences
Museum of Science and Industry
Chicago, Illinois
Attn: Librarian

University of Colorado
Department of Aeronautical Engineering
Boulder, Colorado

University of Illinois
Aeronautical Department
Champaign, Illinois

University of Kentucky
Department of Aeronautical Engineering
College of Engineering
Lexington, Kentucky

University of Toledo
Department of Aeronautical Engineering
Research Foundation
Toledo, Ohio

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Aerospace Corporation
P. O. Box 95085
Los Angeles, California
Attn: Advanced Propulsion & Fluid Mechanics Department
Attn: Gas Dynamics Department

Boeing Scientific Research Laboratory
P. O. Box 3981
Seattle, Washington
Attn: Dr. A. K. Sreekanth
Attn: G. J. Appenheimer

Vidya, Inc.
2626 Hanover
Palo Alto, California
Attn: Mr. J. R. Stalder
Attn: Library

General Electric Company
FPD Technical Information Center F-22
Cincinnati, Ohio

Northwestern University
Technological Institute
Evanston, Illinois
Attn: Department of Mechanical Engineering

Harvard University
Cambridge, Massachusetts
Attn: Prof. of Engineering Sciences & Applied Physics
Attn: Library

University of Wisconsin
P. O. Box 2127
Madison, Wisconsin
Attn: Prof. J. O. Hirschfelder

Dr. Antonio Ferri, Director
Guggenheim Aerospace Laboratories
New York University
181st St. and University Ave.
Bronx, New York

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland		UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE		
Wind Tunnel Investigation of the MK 76 Practice Bomb		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
NAVORD REPORT 6772 of 11 September 1964		
5. AUTHOR(S) (Last name, first name, initial)		
Regan, Frank J.		
6. REPORT DATE	7a. TOTAL NO OF PAGES	7b. NO OF REFS
11 September 1964	14 (44 Fig.)	4
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
RMMO 42-005	NAVORD6772	
b. PROJECT NO.		
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.	ARR-79	
10. AVAILABILITY/LIMITATION NOTICES		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY
		BUWEPS - RMMO
13. ABSTRACT		
This report contains static stability, drag and pitch damping moment data for various configurations of the MK 76 Practice Bomb. These configurations are made from a basic body shape to which are attached various combinations of fuzes, tails and lugs. The effects of these components on the static and dynamic aerodynamic coefficients are studied.		

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Wind Tunnel						
2. Static Stability						
3. Drag						
4. Dynamic Stability						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS) (S) (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

Naval Ordnance Laboratory, White Oak, Md. (NAVEDO report 6772) WIND TUNNEL INVESTIGATION OF THE MK 76 PRACTICE BOMB (U), by Frank J. Regan. 14 Sept. 1964. Sp. illus., charts. (Aerodynamics research report 79) BuWeps task RMAO 42-005/212-1/POO8-C9-Q1. UNCLASSIFIED This report contains static stability, drag and pitch damping moment data for various configurations of the MK 76 practice bomb. These configurations are made from a basic body shape to which are attached various combinations of fuzes, tails and lugs. The effects of these components on the static and dynamic aerodynamic coefficients are studied.	1. Bombs, Practice - Mark 76 2. Bombs - Wind tunnel tests I. Regan, J. II. Series III. Project Abstract card is unclassified.
Naval Ordnance Laboratory, White Oak, Md. (NAVEDO report 6772) WIND TUNNEL INVESTIGATION OF THE MK 76 PRACTICE BOMB (U), by Frank J. Regan. 14 Sept. 1964. Sp. illus., charts. (Aerodynamics research report 79) BuWeps task RMAO 42-005/212-1/POO8-C9-Q1. UNCLASSIFIED This report contains static stability, drag and pitch damping moment data for various configurations of the MK 76 practice bomb. These configurations are made from a basic body shape to which are attached various combinations of fuzes, tails and lugs. The effects of these components on the static and dynamic aerodynamic coefficients are studied.	1. Bombs, Practice - Mark 76 2. Bombs - Wind tunnel tests I. Regan, J. II. Series III. Project Abstract card is unclassified.
Naval Ordnance Laboratory, White Oak, Md. (NAVEDO report 6772) WIND TUNNEL INVESTIGATION OF THE MK 76 PRACTICE BOMB (U), by Frank J. Regan. 14 Sept. 1964. Sp. illus., charts. (Aerodynamics research report 79) BuWeps task RMAO 42-005/212-1/POO8-C9-Q1. UNCLASSIFIED This report contains static stability, drag and pitch damping moment data for various configurations of the MK 76 practice bomb. These configurations are made from a basic body shape to which are attached various combinations of fuzes, tails and lugs. The effects of these components on the static and dynamic aerodynamic coefficients are studied.	1. Bombs, Practice - Mark 76 2. Bombs - Wind tunnel tests I. Regan, J. II. Series III. Project Abstract card is unclassified.
Naval Ordnance Laboratory, White Oak, Md. (NAVEDO report 6772) WIND TUNNEL INVESTIGATION OF THE MK 76 PRACTICE BOMB (U), by Frank J. Regan. 14 Sept. 1964. Sp. illus., charts. (Aerodynamics research report 79) BuWeps task RMAO 42-005/212-1/POO8-C9-Q1. UNCLASSIFIED This report contains static stability, drag and pitch damping moment data for various configurations of the MK 76 practice bomb. These configurations are made from a basic body shape to which are attached various combinations of fuzes, tails and lugs. The effects of these components on the static and dynamic aerodynamic coefficients are studied.	1. Bombs, Practice - Mark 76 2. Bombs - Wind tunnel tests I. Regan, J. II. Series III. Project Abstract card is unclassified.