

UNCLASSIFIED

AD 4 5 1 7 2 6

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED


NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

451726

CATALOGED BY DDC 451726

AEROSPACE RESEARCH • AERODYNAMICS • PROPULSION • STRUCTURAL DYNAMICS • ELECTRONIC SYSTEMS AND INSTRUMENTS • COMPUTER MODULES

AS AD No.



RESEARCH
ENGINEERING
PRODUCTION

TECHNICAL REPORT NO. 414

AN APPROXIMATE ANALYSIS OF THE
CONTINUUM LOW DENSITY HYPERSONIC FLOW
OF A CHEMICALLY REACTING AND RADIATING
GAS OVER A BLUNT NOSED BODY

By Massimo Trella
Roberto Vaglio-Laurin

October 26, 1964

GENERAL APPLIED SCIENCE LABORATORIES, INC.
MERRICK and STEWART AVENUES, WESTBURY, L.I., N.Y. (516) ED 8-6960

Project 8010/1220

Total No. of Pages - iii and 34

Copy No. (12) of 100

TECHNICAL REPORT NO. 414

AN APPROXIMATE ANALYSIS OF THE
CONTINUUM LOW DENSITY HYPERSONIC FLOW
OF A CHEMICALLY REACTING AND RADIATING
GAS OVER A BLUNT NOSED BODY*

By Massimo Trella
Roberto Vaglio-Laurin

Prepared for

Advanced Research Projects Agency
Washington 25, D.C.

Under Contract SD-149
ARPA Order No. 396
Project Code 3790

Prepared by

General Applied Science Laboratories, Inc.
Merrick and Stewart Avenues
Westbury, L. I., New York

Approved by:


Antonio Ferri
President

*This research is sponsored by the
Advanced Research Projects Agency

October 26, 1964

SUMMARY

The continuum low density hypersonic flow of a chemically reacting and radiating gas over a blunt body is analyzed by an approximate technique based on a recent alternative formulation of the well-known method of integral relations. Specifically, approximations are introduced for the streamwise variations of several flow properties, while detailed radial profiles, (consistent with the stipulated procedure) are sought by numerical analysis along normals to the body (essentially normals to streamlines); the particular formulation allows careful analysis of the large changes in physico-chemical properties of the gas between body and shock, as are to be encountered at the low Reynolds numbers where viscous effects are important over the entire shock layer. Detailed derivations of the simplified system of ordinary differential equations and of the boundary conditions governing the problem is presented. An outline of numerical procedures for applications is also given.

TABLE OF CONTENTS

<u>SECTION</u>	<u>TITLE</u>	<u>PAGE</u>
I	INTRODUCTION	1
II	GOVERNING EQUATIONS AND BOUNDARY CONDITIONS	5
III	THE INTEGRAL APPROACH	15
IV	OUTLINE FOR NUMERICAL PROCEDURE	27
V	CONCLUSIONS	33
	REFERENCES	34

TECHNICAL REPORT NO. 414

AN APPROXIMATE ANALYSIS OF THE
CONTINUUM LOW DENSITY HYPERSONIC FLOW
OF A CHEMICALLY REACTING AND RADIATING
GAS OVER A BLUNT NOSED BODY

By

Massimo Trella and Roberto Vaglio-Laurin

I. INTRODUCTION

The problem of observables associated with reentry of hypersonic vehicles has received considerable attention in recent years. This problem has strong physico-chemical as well as fluid mechanical overtones. Applications require detailed and accurate quantitative predictions of flow properties; such level of precision can only be obtained by numerical methods. A large body of related literature has recently been set forth; however, most analyses are pertinent to high Reynolds number flows where distinct shock, inviscid and boundary layer regions can be recognized. The range of applicability of those analyses is limited to altitudes below

approximately 220 kft. for typical body dimensions ($R=1$ ft), and hypersonic reentry conditions. At the higher altitudes different flow regimes are encountered, which involve increasingly complex analyses. In an upward sweep of the trajectory, a continuum description of the flow can be applied to study the initial vorticity interaction, viscous layer, and incipient merged layer regimes while the range of lower Reynolds numbers must be analyzed on the basis of either transitional or free molecule flow theory.

The present study is concerned with the first three (continuum) regimes mentioned above. Even within these limits analysis becomes very cumbersome, particularly when effects of chemical reactions and radiation are included. Current state of the art permits detailed numerical investigation of either strictly inviscid flows (Ref. 2) or strictly boundary layer flows (Ref. 3) including coupled chemical reactions and, in preliminary fashion, radiation* (Ref. 4). Low density situations have been studied to limited extent and only in connection with flows of ideal gases; although related analyses rely heavily on extensive machine

* For missile and lunar vehicle reentry, the effect of self absorption can become significant in some part of the shock layer (Ref. 4); however, in this preliminary study we assume the thin gas approximation to be valid over the entire flow field.

calculations results are only available for the stagnation point on a sphere (Ref. 5) and for flows about blunt bodies within the Newtonian approximation (Ref. 6). The limitations of those theories are well known.

The present analysis was undertaken having in mind the strict requirements for prediction of observables, definition of the range of possible observation, and interpretation thereof. However, in view of the exploratory nature of the task an approximate method of analysis has been sought, presumably retaining the essential features of the physical situation.

In the presence of viscous effects and of chemical reaction extending to the entire shock layer careful consideration must be given to distributions of state properties and composition in the direction normal to the body surface; on the basis of this consideration, we have adopted an integral method formulation based on approximate description of the distribution of flow properties in the direction parallel to the body surface (Refs. 7 and 8).


Details of the investigation are presented in the following sequence: Section II) The Governing Partial Differential Equations, Boundary Conditions and the Approximations Based on

Orders of Magnitude Analysis; Section III) The Integral Approximations and the Resulting Ordinary Differential Equations and Boundary Conditions; Section IV) Outline of Numerical Procedure Including Iterative Techniques Successfully Proven in Connection with other Problems.

The present analysis represents the first phase of a research program on reentry observables in low density continuum flows currently under way at GASL.

II. GOVERNING EQUATIONS AND BOUNDARY CONDITIONS

The equations governing the two-dimensional or axisymmetric flow of a viscous, chemically reacting and radiating gas, in a body oriented coordinate system (x, y, Φ) are:



Continuity:

$$\frac{\partial}{\partial x} (r^j \rho u) + \frac{\partial}{\partial y} (x r^j \rho v) = 0 \quad (1)$$

Momentum x:

$$\begin{aligned} \rho \left\{ u \frac{\partial u}{\partial x} + x v \frac{\partial u}{\partial y} + k u v \right\} = & - \frac{\partial p}{\partial x} + \frac{\partial \tau_{xx}}{\partial x} + \frac{\partial}{\partial y} (x \tau_{xy}) \\ & + k \tau_{xy} + j \left\{ \frac{\tau_{xx} - \tau_{\Phi\Phi}}{r} \frac{\partial r}{\partial x} + \frac{x \tau_{xy}}{r} \frac{\partial r}{\partial y} \right\} \end{aligned} \quad (2)$$

Momentum y:

$$\begin{aligned} \rho \left\{ u \frac{\partial v}{\partial x} + \chi v \frac{\partial v}{\partial y} - k u^2 \right\} = & - \chi \frac{\partial p}{\partial y} + \chi \frac{\partial \tau_{yy}}{\partial y} + \frac{\partial \tau_{xy}}{\partial x} + k(\tau_{yy} - \tau_{xx}) \\ & + j \left\{ \frac{\tau_{xy}}{r} \frac{\partial r}{\partial x} + \chi \frac{(\tau_{yy} - \tau_{xx})}{r} \frac{\partial r}{\partial y} \right\} \end{aligned} \quad (3)$$

Energy:

$$\begin{aligned} \rho \left\{ u \frac{\partial H}{\partial x} + \chi v \frac{\partial H}{\partial y} \right\} + \nabla \cdot \hat{q}_r = & \frac{\partial}{\partial x} \left(\frac{1}{\chi} q_x \right) - \frac{\partial}{\partial y} (\chi q_y) + \frac{\partial}{\partial x} (u \tau_{xx} + v \tau_{xy}) \\ & + \frac{\partial}{\partial y} [\chi (u \tau_{xy} + v \tau_{yy})] - \frac{j}{r} \left\{ \left[\frac{1}{\chi} q_x \frac{\partial r}{\partial x} + \chi q_y \frac{\partial r}{\partial y} \right] + \right. \\ & \left. + [(u \tau_{xx} + v \tau_{xy}) \frac{\partial r}{\partial x} + \chi (u \tau_{xy} + v \tau_{yy}) \frac{\partial r}{\partial y}] \right\} \end{aligned} \quad (4)$$

Species:

$$\begin{aligned} \rho \left\{ u \frac{\partial \alpha_i}{\partial x} + \chi v \frac{\partial \alpha_i}{\partial y} \right\} = & \frac{\partial}{\partial x} \left(\frac{\rho D}{\chi} \frac{\partial \alpha_i}{\partial x} \right) + \frac{\partial}{\partial y} \left(\rho D \chi \frac{\partial \alpha_i}{\partial y} \right) \\ & + \frac{j}{r} \left[\frac{\rho D}{\chi} \frac{\partial \alpha_i}{\partial x} \frac{\partial r}{\partial x} + \rho D \chi \frac{\partial \alpha_i}{\partial y} \frac{\partial r}{\partial y} \right] + \rho \chi \dot{w}_i \end{aligned} \quad (5)$$

$$i = 1, 2, \dots, N-1$$

Where:

k = body curvature

$j = \begin{cases} 0 & \text{two-dimensional flow} \\ 1 & \text{axisymmetric flow} \end{cases}$

$\chi = 1 + ky$

Φ = azimuthal angle

$$\left. \begin{aligned} \tau_{xx} &= \frac{2\mu}{\chi} \left(\frac{\partial u}{\partial x} + kv \right) - \frac{2}{3} \mu \left[\frac{1}{\chi} \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{kv}{\chi} \right. \\ &\quad \left. + j \left(\frac{u}{\chi r} \frac{\partial r}{\partial x} + \frac{v}{r} \frac{\partial r}{\partial y} \right) \right] \\ \tau_{yy} &= 2\mu \frac{\partial v}{\partial y} - \frac{2}{3} \mu \left[\frac{1}{\chi} \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{kv}{\chi} + j \left(\frac{u}{\chi r} \frac{\partial r}{\partial x} + \frac{v}{r} \frac{\partial r}{\partial y} \right) \right] \\ \tau_{\Phi\Phi} &= j \left[\frac{2\mu}{r} \left(\frac{u}{\chi} \frac{\partial r}{\partial x} + v \frac{\partial r}{\partial y} \right) - \frac{2}{3} \mu \left(\frac{1}{\chi} \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{kv}{\chi} \right. \right. \\ &\quad \left. \left. + \frac{u}{\chi r} \frac{\partial r}{\partial x} + \frac{v}{r} \frac{\partial r}{\partial y} \right) \right] \\ \tau_{xy} &= \mu \left(\frac{1}{\chi} \frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} - \frac{ku}{\chi} \right) \end{aligned} \right\} (6)$$

Furthermore for $Le = Pr = 1$ and optically thin gas:

$$\left. \begin{aligned}
 q_x &= -\mu \frac{\partial h}{\partial x} \\
 q_y &= -\mu \frac{\partial h}{\partial y} \\
 \nabla \cdot \hat{q}_r &= \chi 4\pi \tilde{\mu} B(T_s) \\
 B(T_s) &= \frac{\sigma T^4}{\pi} \\
 \rho D &= \frac{Le}{Pr} \mu = \mu
 \end{aligned} \right\} (7)$$

The system of $4+N-1$ equations is complemented by an equation of state in the form:

$$h = h(p, \rho, \alpha_i) \quad (8)$$

by a viscosity law:

$$\mu = \mu(p, \rho, \alpha_i) \quad (9)$$

and by the condition:

$$\sum_{i=1}^N \alpha_i = 1 \quad (10)$$

The corresponding unknowns in the original system are the two components of velocity u, v , the pressure p , the density ρ and $(N-1)$ mass fractions.

Two sets of boundary conditions are imposed: one set at the body and one at the "outer edge" of the shock layer; we specify all the boundary conditions in a form appropriate for the "viscous layer regime," namely: 1) no slip and temperature jump phenomena are present at the surface of the body, and 2) the shock can be treated as a surface of discontinuity.

The boundary conditions at the body are:

$$\begin{array}{lcl}
 u_b = v_b = 0 & & \\
 h_b = h_b(x) & & \\
 \text{Surface} & & \\
 \text{catalyticity: 1) if catalytic} & \rightarrow \alpha_i \text{ in equilibrium} & \\
 & 2) \text{ if not catalytic} \rightarrow \text{impermeability conditions for all} & \\
 & & \text{species except surface material}
 \end{array} \quad (11)$$

The boundary conditions at the shock are obtained from the standard Rankine-Hugoniot relations in terms of free stream properties, of local shock inclination, and of a prescribed composition of the mixture on the downstream side; formally

$$\begin{aligned}
 u &= u_s \\
 v &= v_s \\
 \rho &= \rho_s \\
 p &= p_s \\
 \alpha_i &= \alpha_{i_s}
 \end{aligned}
 \quad \left. \vphantom{\begin{aligned} u &= u_s \\ v &= v_s \\ \rho &= \rho_s \\ p &= p_s \\ \alpha_i &= \alpha_{i_s} \end{aligned}} \right\} (12)$$

The total order of the original system is $[7+2(N-1)]$; the $[7+2(N-1)]$ boundary conditions (11) and (12) are however insufficient since the shock geometry is also unknown. The difficulty is removed upon examination of the continuity equation at the body; this provides the additional boundary conditions, namely

$$(v_y)_b = 0 \quad (11a)$$

The original system of Eqs. (1)-(5) may be simplified considerably for specific application to high Mach number flows. Under those conditions the orders of magnitude of the basic properties in the shock layer are:

$$\frac{\rho_\infty}{\rho} \sim \epsilon \ll 1$$

$$v \sim \epsilon U_\infty$$

$$u \sim U_\infty$$

$$y \sim \delta$$

$$\mu \sim \mu_s$$

$$x \sim L \gg \delta$$

$$\chi \sim 1$$

$$k \sim L^{-1}$$

$$\left. \begin{array}{l} \frac{\rho_\infty}{\rho} \sim \epsilon \ll 1 \\ v \sim \epsilon U_\infty \\ u \sim U_\infty \\ y \sim \delta \\ \mu \sim \mu_s \\ x \sim L \gg \delta \\ \chi \sim 1 \\ k \sim L^{-1} \end{array} \right\} (13)$$

Accordingly the following simplified form of the equations is obtained when terms of order higher than $(\epsilon R_e)^{-1}$ are neglected (Ref. 5):

Continuity:

$$\frac{\partial}{\partial x} (x^j \rho u) + \frac{\partial}{\partial y} (x r^j \rho v) = 0$$

Momentum x:

$$\rho \left\{ u \frac{\partial u}{\partial x} + \chi v \frac{\partial u}{\partial y} + k u v \right\} = - \frac{\partial p}{\partial x} + \frac{\partial}{\partial y} \left(\chi \mu \frac{\partial u}{\partial y} \right)$$

Momentum y:

$$\begin{aligned} \rho \left\{ u \frac{\partial v}{\partial x} + \chi v \frac{\partial v}{\partial y} - k u^2 \right\} = & - \chi \frac{\partial p}{\partial y} + \chi \frac{4}{3} \frac{\partial}{\partial y} \left(\mu \frac{\partial v}{\partial y} \right) \\ & - \frac{2}{3} \chi \frac{\partial}{\partial y} \left(\frac{\mu}{\chi} \frac{\partial u}{\partial x} \right) + \frac{\partial}{\partial x} \left(\mu \frac{\partial u}{\partial y} \right) \\ & + j \left\{ \frac{\mu}{r} \frac{\partial r}{\partial x} \frac{\partial u}{\partial y} - \chi \frac{\partial}{\partial y} \left(\frac{\mu}{\chi} \frac{u}{r} \frac{\partial r}{\partial x} \right) \right\} \end{aligned}$$

Energy:

$$\rho \left\{ u \frac{\partial H}{\partial x} + \chi v \frac{\partial H}{\partial y} \right\} = \frac{\partial}{\partial y} \left(\chi \mu \frac{\partial H}{\partial y} \right) - \chi^4 \pi \tilde{\mu} B$$

Species:

$$\rho \left\{ u \frac{\partial \alpha_i}{\partial x} + \chi v \frac{\partial \alpha_i}{\partial y} \right\} = \frac{\partial}{\partial y} \left(\chi \mu \frac{\partial \alpha_i}{\partial y} \right) + \chi \rho \dot{\omega}_i$$

(14)

The system (14) represents the basis of the present analysis.

All subsequent developments are aimed at developing a method of solution. In this connection we begin by introducing new independent variables

$$s = x$$

$$n = y/\delta$$

(15)

with

$$\delta = \delta(s) \quad (16)$$

the shock detachment distance; the domain of integration is thus transformed into a rectangle.

Performing the transformation

$$\left. \begin{aligned} \frac{\partial}{\partial y} &= \frac{1}{\delta} \frac{\partial}{\partial n} \\ \frac{\partial}{\partial x} &= \frac{\partial}{\partial s} - \frac{n}{\delta} \frac{d\delta}{ds} \frac{\partial}{\partial n} \end{aligned} \right\} (17)$$

and recasting the equations in divergence form (desirable for implementation of the integral approach) we obtain:

Continuity:

$$\frac{\partial}{\partial s} (r^j \rho u) - n \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho u \right) + \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \rho v \right) = 0$$

Momentum x:

$$\begin{aligned} \frac{\partial}{\partial s} [r^j (p + \rho u^2)] - n \frac{\partial}{\partial n} \left[\frac{r^j}{\delta} \frac{d\delta}{ds} (p + \rho u^2) \right] + \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \rho u v \right) \\ - k r^j (j p \tan \theta_b - \rho u v) = \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \tau_{xy} \right) \end{aligned}$$

Momentum y:

$$\begin{aligned} \frac{\partial}{\partial s} (r^j \rho_{uv}) - n \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho_{uv} \right) + \frac{\partial}{\partial n} \left[\frac{r^j}{\delta} \chi (p + \rho v^2) \right] \\ - kr^j [(1+j)p + \rho u^2] = \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \tau_{yy} \right) + \frac{\partial}{\partial x} (r^j \tau_{xy}) \\ - n \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \tau_{xy} \right) \end{aligned}$$

Energy:

$$\begin{aligned} \frac{\partial}{\partial s} (r^j \rho u_H) - n \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho u_H \right) + \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \rho v_H \right) \\ = \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \mu \frac{1}{\delta} \frac{\partial H}{\partial n} \right) - \chi r^j 4\pi \tilde{\mu} B \end{aligned} \quad (18)$$

Species:

$$\begin{aligned} \frac{\partial}{\partial s} (r^j \rho u \alpha_i) - n \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho u \alpha_i \right) + \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \rho v \alpha_i \right) \\ = \frac{\partial}{\partial n} \left(\frac{r^j}{\delta} \chi \mu \frac{1}{\delta} \frac{\partial \alpha_i}{\partial n} \right) + \chi r^j \rho \dot{\omega}_i \end{aligned}$$

The boundary conditions are still expressed by (11) and (12) intended to apply at $n=0$ and at $n=1$ respectively.

III. THE INTEGRAL APPROACH

Methodology for solution of the simplified system of partial differential Eqs. (18) is established only for a particular formulation of the problem (the inverse problem where the shock shape is specified and the associated body is determined) and involves considerable labor. The practical problem of analyzing the flow about a given configuration can be solved within practical limits of numerical effort only in approximate fashion. A well known procedure to this effect is represented by the integral method in its various formulations (Refs. 7 and 8). In essence this method reduces the system of governing partial differential equations to an approximating system of ordinary differential equations by introducing assumed distributions of flow properties along one coordinate direction. In the present report we choose to make assumptions about the variation of flow properties in the stream-wise direction since, in the presence of viscous effects and of chemical reactions extending over the entire shock layer, we are particularly interested in assessing the effect of transport phenomena on cross-stream distributions of physico-chemical properties of the gas.

We begin implementation of the aforementioned integral approach by integrating Eqs. (18) between two general stations s_1 and s_2

to obtain the integro-differential equations:

Continuity:

$$\left[r^j \rho u \right]_{s_1}^{s_2} - n \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho u \right) ds + \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \rho v \right) ds = 0 \quad (19a)$$

Momentum x:

$$\begin{aligned} \left[r^j (p + \rho u^2) \right]_{s_1}^{s_2} - n \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left[\frac{r^j}{\delta} \frac{d\delta}{ds} (p + \rho u^2) \right] ds + \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \rho uv \right) ds \\ - \int_{s_1}^{s_2} \left[k r^j (j p \tan \theta_b - \rho uv) \right] ds = \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \tau_{xy} \right) ds \end{aligned} \quad (19b)$$

Momentum y:

$$\begin{aligned} \left[r^j \rho uv \right]_{s_1}^{s_2} - n \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho uv \right) ds + \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left[\frac{r^j}{\delta} \chi (p + \rho v^2) \right] ds \\ - \int_{s_1}^{s_2} k r^j \left[(1+j) p + \rho u^2 \right] ds = \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \tau_{yy} \right) ds \\ + \left[r^j \tau_{xy} \right]_{s_1}^{s_2} - n \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \tau_{xy} \right) ds \end{aligned} \quad (19c)$$

Energy:

$$\begin{aligned}
 \left[r^j \rho u H \right]_{s_1}^{s_2} - n \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho u H \right) ds + \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \rho v H \right) ds \\
 = \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \mu \frac{1}{\delta} \frac{\partial H}{\partial n} \right) ds - \int_{s_1}^{s_2} (\chi r^j 4 \pi \tilde{\mu} B) ds
 \end{aligned} \tag{19d}$$

Species:

$$\begin{aligned}
 \left[r^j \rho u \alpha_i \right]_{s_1}^{s_2} - n \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \frac{d\delta}{ds} \rho u \alpha_i \right) ds + \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \rho v \alpha_i \right) ds \\
 = \frac{\partial}{\partial n} \int_{s_1}^{s_2} \left(\frac{r^j}{\delta} \chi \mu \frac{1}{\delta} \frac{\partial \alpha_i}{\partial n} \right) ds + \int_{s_1}^{s_2} (\chi r^j \rho \dot{w}_i) ds
 \end{aligned} \tag{19e}$$

Reduction of the (3+N) Eqs. (19) to ordinary differential form follows immediately upon stipulation of the s-distribution of certain flow quantities. We point out that only (3+N) quantities can be subject of independent description; of these, two must be velocities, two state properties, and (N-1) species. We assume polynomial laws for the following:

$$\left. \begin{aligned}
 \rho u &= A_1 s + A_3 s^3 + \dots \\
 \rho u^2 &= B_2 s^2 + B_4 s^4 + \dots \\
 \rho uv &= C_1 s + C_3 s^3 + \dots \\
 \rho uh &= D_1 s + D_3 s^3 + \dots \\
 \rho u \alpha_i &= E_{1i} s + E_{3i} s^3 + \dots
 \end{aligned} \right\} (20)$$

where the coefficients A, B, C, D, E are functions of n . The selected quantities are all equal to zero at the axis and the assumed s dependencies satisfy the symmetry conditions; therefore, the number of terms in each polynomial is equal to the number of control stations away from the axis. Consistently with this procedure the properties at the axis are found from ratios of the laws (20) and not from the independent solution of the stagnation point partial differential equations (Ref. 5); for example:

$$\left[v(n) \right]_{\text{axis}} = \left[\frac{uv}{u} \right]_{\text{axis}} = \frac{C_1(n)}{A_1(n)} \quad (21)$$

and so on for all other properties. We also notice that in the case of one control station and one term in the laws (20), the proposed procedure is equivalent to assuming flow similarity.

In addition to the four independent quantities (20) other accessory properties are cast in a polynomial form to permit a more convenient numerical integration of the final system; naturally the degree of these polynomials is determined by the constitutive relations to be satisfied by the quantities on hand [e.g. Eqs. (6)] consistent with the postulated distributions (20). Thus, we set

$$\begin{aligned}
 \rho u \tau_{xy} &= F_1 s + F_3 s^3 + \cdots + F_{m_1} s^{m_1} \\
 \rho u \tau_{yy} &= G_1 s + G_3 s^3 + \cdots + G_{m_2} s^{m_2} \\
 \rho u \mu \frac{\partial H}{\partial n} &= L_1 s + L_3 s^3 + \cdots + L_{m_3} s^{m_3} \\
 \rho u \mu \frac{\partial \alpha_i}{\partial n} &= M_{i1} s + M_{i3} s^3 + \cdots + M_{i m_4} s^{m_4}
 \end{aligned} \tag{22}$$

consistent with symmetry requirements and specific definitions.

Upon substitution of (20) into (19) and (22) one obtains t simultaneous nonlinear ordinary differential equations of the first order which can be cast in the form

$$\sum_{\lambda=1}^t a_{\sigma\lambda} \frac{dP_\lambda}{dn} = F_\sigma \tag{23}$$

where

$$\sigma \lambda = 1, 2, 3 \dots t$$

t is defined in terms of the number z of control stations ($s = \text{const.} = s_1, s_2 \dots$), the number of chemical species N and the magnitude of the highest powers m_i appearing in (22)

$$t = z(3+N) + m_1 + m_2 + m_3 + (N-1)m_4 \quad (23a)$$

$F_\lambda(n)$ denotes the general coefficient (A_i, B_i , etc.) in the stipulated distributions (20) and (22), $a_{\sigma\lambda}$ and F_σ are known functions of s_i , n and P_λ to be determined case by case in accord with the number z of stations considered. Of the t Eqs. (23), $z(3+N)$ follow from the conservation laws (19), while the remaining $[m_1 + m_2 + m_3 + (N-1)m_4]$ are obtained by setting to zero the coefficients of all powers of s in (22). The t boundary conditions for the system (23) may readily be obtained in the following way: $z(3+N)$ conditions are obtained by simultaneous consideration of (11), (12) and (20); $[m_1 + m_2 + m_3 + (N-1)m_4]$ additional conditions are derived therefrom by substitution into (22) and subsequent setting to zero of the coefficients of all powers of s . Recognition of additional z unknowns, namely the z coefficients in the law describing the shock shape, does not alter the order of the

system and merely requires implementation of the conditions (11a) at the z control stations.

In summary, an integral method analysis of the viscous flow of a mixture of N reactant gases over either two-dimensional or axisymmetric bodies, by recognizing z regions (strips) within the domain of interest, involves the solution of a system of t ordinary differential equations of first order (23) plus z algebraic equations, subject to t boundary conditions [t defined by (23a)]. The detailed derivation of expressions for coefficients and forcing functions in the system must be carried out case by case (depending upon the selected number z and the thermodynamic behavior of the mixture); however, some rules of internal consistency must be respected in that process as described below. To be consistent with the stipulation (20) various flow properties of interest must be described by the relations:

$$\rho v = \frac{(\rho u v)(\rho u)}{(\rho u^2)} \quad (24a)$$

$$\rho v^2 = \frac{(\rho u v)^2}{(\rho u^2)} \quad (24b)$$

$$\alpha_i = \frac{(\rho u \alpha_i)}{(\rho u)} \quad (24c)$$

$$h = \frac{(\rho u h)}{(\rho u)} \quad (24d)$$

$$H = h + \frac{1}{2} (u^2 + v^2) = h + \frac{1}{2} \frac{(\rho u^2)}{(\rho u)} \left[(\rho u^2) + (\rho v^2) \right] \quad (24e)$$

$$p = \rho h \pi(s, n) = \frac{(\rho u h)(\rho u)}{(\rho u^2)} \pi(s, n) \quad (24f)$$

The formal expression for the pressure p is suggested by consideration of ideal gas flows wherein $\pi = \text{const}$; in the more general case one has

$$\pi(s, n) = \pi(\rho, h, \alpha_i) \quad (25)$$

As an example of consistent derivation let us examine a complicated term such as that involving the pressure in the x-momentum Eq. (19b):

$$\frac{\partial}{\partial n} \int_{s_1}^{s_2} \frac{r^j}{\delta} \frac{d\delta}{ds} p \, ds \quad (26)$$

The consistent law for the shock is

$$\delta = \delta_0 + \delta_1 s^2 + \delta_2 s^4 + \dots \quad (27)$$

Thus

$$\frac{r^j}{\delta} \frac{d\delta}{ds} = R_0(s) + j n R_1(s) \quad (28)$$

with

$$\left. \begin{aligned} R_0(s) &= \frac{1}{\delta} \frac{d\delta}{ds} \left(\frac{\cos \theta_b}{k} \right)^j \\ R_1(s) &= \frac{d\delta}{ds} \cos \theta_b \end{aligned} \right\} (29)$$

The appropriate sequence of transformations of (26) then proceeds along the following lines:

$$\begin{aligned} \frac{\partial}{\partial n} \int_{s_1}^{s_2} \frac{r^j}{\delta} \frac{d\delta}{ds} p \, ds &= \frac{\partial}{\partial n} \int_{s_1}^{s_2} [R_0(s) + jn R_1(s)] \times \\ &\times \left[\frac{A_1 D_1 + (D_3 A_1 + A_3 D_1) s^2 + D_3 A_3 s^4}{B_2 + B_4 s^2} \right] \pi(s, n) ds \\ &= \frac{\partial}{\partial n} \left\{ A_1 D_1 \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{B_2 + B_4 s^2} \pi(s, n) ds \right. \\ &\quad + (D_3 A_1 + A_3 D_1) \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{B_2 + B_4 s^2} s^2 \pi(s, n) ds \\ &\quad \left. + D_3 A_3 \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{B_2 + B_4 s^2} s^4 \pi(s, n) ds \right\} \\ &= \frac{\partial (A_1 D_1)}{\partial n} \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{B_2 + B_4 s^2} \pi(s, n) ds \end{aligned}$$

$$\begin{aligned}
& + \frac{\partial (D_3 A_1 + A_3 D_1)}{\partial n} \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{B_2 + B_4 s^2} s^2 \pi(s, n) ds \\
& + \frac{\partial (D_3 A_3)}{\partial n} \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{B_2 + B_4 s^2} s^4 \pi(s, n) ds \\
& - \frac{\partial B_2}{\partial n} \left\{ A_1 D_1 \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{(B_2 + B_4 s^2)^2} \pi(s, n) ds \right. \\
& \quad + (D_3 A_1 + A_3 D_1) \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{(B_2 + B_4 s^2)^2} s^2 \pi(s, n) ds \\
& \quad \left. + D_3 A_3 \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{(B_2 + B_4 s^2)^2} s^4 \pi(s, n) ds \right\} \\
& - \frac{\partial B_4}{\partial n} \left\{ A_1 D_1 \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{(B_2 + B_4 s^2)^2} s^2 \pi(s, n) ds \right. \\
& \quad + (D_3 A_1 + A_3 D_1) \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{(B_2 + B_4 s^2)^2} s^4 \pi(s, n) ds \\
& \quad \left. + D_3 A_3 \int_{s_1}^{s_2} \frac{R_0(s) + jn R_1(s)}{(B_2 + B_4 s^2)^2} s^6 \pi(s, n) ds \right\} \\
& + j \int_{s_1}^{s_2} R_1(s) \frac{A_1 D_1 + (D_3 A_1 + A_3 D_1) s^2 + D_3 A_3 s^4}{B_2 + B_4 s^2} \pi(s, n) ds \\
& + \int_{s_1}^{s_2} [R_0(s) + jn R_1(s)] \frac{A_1 D_1 + (D_3 A_1 + A_3 D_1) s^2 + D_3 A_3 s^4}{B_2 + B_4 s^2} \frac{\partial \pi}{\partial n}(s, n) ds
\end{aligned} \tag{30}$$

All the integrals in (30) except the last one may be evaluated in straightforward fashion to obtain associated contributions to the coefficients $a_{\sigma\lambda}$; the last integral is reduced to the desired form by means of the additional relationship:

$$p = \left[R_0(s) + jn R_1(s) \right] \frac{A_1 D_1 + (D_2 A_1 + D_1 A_2) s^2 + D_2 A_2 s^4}{B_2 + B_4 s^2} \quad (31)$$

and transformation:

$$\begin{aligned} \int_{s_1}^{s_2} p \frac{\partial \pi}{\partial n} ds &= \int_{s_1}^{s_2} p \left\{ \frac{\partial(\rho u)}{\partial n} \left[- \frac{(\rho u h)}{(\rho u)^2} \frac{\partial \pi}{\partial h} - \frac{(\rho u \alpha_i)}{(\rho u)^2} \frac{\partial \pi}{\partial \alpha_i} + \frac{(\rho u)}{(\rho u^2)} \frac{\partial \pi}{\partial \rho} \right] \right. \\ &\quad + \frac{\partial(\rho u h)}{\partial n} \frac{1}{\rho u} \frac{\partial \pi}{\partial h} + \frac{\partial(\rho u \alpha_i)}{\partial n} \frac{1}{\rho u} \frac{\partial \pi}{\partial \alpha_i} \\ &\quad \left. - \frac{\partial(\rho u^2)}{\partial n} \frac{(\rho u)^2}{(\rho u^2)^2} \frac{\partial \pi}{\partial \rho} \right\} ds \\ &= \frac{dA_1}{dn} \int_{s_1}^{s_2} p_s \left[- \frac{(\rho u h)}{(\rho u)^2} \frac{\partial \pi}{\partial h} - \frac{(\rho u \alpha_i)}{(\rho u)^2} \frac{\partial \pi}{\partial \alpha_i} + \frac{(\rho u)}{(\rho u^2)} \frac{\partial \pi}{\partial \rho} \right] ds \\ &\quad + \frac{dA_2}{dn} \int_{s_1}^{s_2} p_s^2 \left[- \frac{(\rho u h)}{(\rho u)^2} \frac{\partial \pi}{\partial h} - \frac{(\rho u \alpha_i)}{(\rho u)^2} \frac{\partial \pi}{\partial \alpha_i} + \frac{(\rho u)}{(\rho u^2)} \frac{\partial \pi}{\partial \rho} \right] ds \\ &\quad + \frac{dD_1}{dn} \dots + \end{aligned} \quad (32)$$

All coefficients and forcing functions in (23) may consistently be determined by algebraic transformations as detailed at (26) through (32) above.

Solution of the system (23) may only be sought by numerical means; proper formulation thereof requires a preliminary assessment of the general features of the integral curves to be obtained. In this connection we observe that the integral formulation adopted here does not exhibit critical points of the type present in the standard integral method; hence the integration is straightforward. The absence of singularities follows from the a priori assumed regular behavior at the sonic velocity as manifested either by the prescribed pressure distribution on the body or by the prescribed shock shape (see the alternative procedures in Section IV). The singularity in the standard formulation represents a mathematical manifestation of the continuity requirement; in that case we start by assuming a shock detachment distance δ_0 at the axis and compute increment thereof. Here we do not say anything about δ ; it is completely free to satisfy the continuity requirement consistent with the assumed regular behavior.

Consideration of viscous effects, specifically the no-slip condition at the wall, in the present formulation renders the equations singular at $n=0$; however, this singularity is regular and integration in its neighborhood may readily be performed along the lines detailed in Ref. 5.

IV. OUTLINE FOR NUMERICAL PROCEDURE

In analogy with the inviscid blunt body problem two possibilities are open for the problem on hand: the direct and the inverse method.

Analysis by the direct method proceeds along the following lines: a) the body geometry and the body temperature are given; b) $(N+3)$ distributions of flow properties (polynomials in s) are estimated at $n=0$; these are, for example, the shock geometry $\delta(s)$, the pressure p , the shear stress [whereby a relation between $(\rho u)_n$ and $\left[\frac{(\rho u)^2}{\rho u^3}\right]_n$ is obtained], and either the composition if the wall is not catalytic, or the normal derivative of the N species concentration $\left(\frac{\rho u \alpha_i}{\rho u}\right)_n$ if the wall is catalytic; c) the remaining inputs for the integration are consistently obtained from the study of the equations in the neighborhood of the body; specifically, one requires $v_n=0$ to satisfy continuity and one determines p_n to satisfy the y momentum equation consistent with the prescribed $p(s)^*$; d) numerical integration of (23) is performed from $n=0$ to $n=1$; e) compliance of the results of integration at $n=1$ with the boundary (jump) conditions for ρ , p , u , v and α_i is

* The aforementioned set of inputs is equivalent to prescribing the heat transfer since $h_n = h_n(p_n, \rho_n, \alpha_{in})$.

inspected; and f) if the latter conditions are not satisfied initial estimated values are modified and an iterative solution performed following criteria such as are discussed later in this section.

Analysis by the inverse method proceeds along the following lines: a) the shock geometry is given; b) $(4+N)$ distributions of flow properties (e.g. $\delta, u_n, p_n, h_n, \alpha_{in}$) are estimated and prescribed at the outer edge of the shock layer ($n=1$) and initial values for integration established accordingly; c) integration is carried out from $n=1$ to $n=0$; d) compliance with $(4+N)$ conditions on the body (namely $u=v=v_n=0$, $h=h_b$ and either α_i or α_{in} consistent with surface catalyticity) is inspected; and e) iteration is pursued if not all conditions are satisfied at $n=0$.

It must be concluded that either method exhibits comparable numerical difficulties for the problem on hand; indeed a large number of quantities [either $(3+N)$ or $(4+N)$] must be estimated and iterated upon for either direct or inverse approach.

The required iterations may be carried out in organized fashion by assuming linearization of differences between solutions characterized by change in one input parameter only. To be specific, a first run is performed corresponding to an initial set

of $(3+N)$ estimated quantities; subsequently $(3+N)$ additional runs are performed each characterized by a set of initial conditions differing from the first one for a single quantity. In the hypothesis that the error can be linearized a system of linear algebraic equations in the unknown ΔQ_j [$j=1,2,\dots,(3+N)$] corrections to be imposed on the estimated initial conditions may be constructed; specifically one equates the errors observed in the first run to a weighted linear combination of the errors introduced by each perturbation to obtain

$$P_i = \sum_{j=1}^{3+N} \frac{\partial P_i}{\partial Q_j} \Delta Q_j \quad (33)$$

where P_i indicates the known initial error property for the i^{th} property and the partial derivatives are obtained by differences between the results of each "perturbation" run and the initial one. Obviously the procedure can be repeated until satisfactory convergence is achieved.

A second alternative to the numerical iteration may be sought by extension to the problem on hand of Weil's method for solving a class of ordinary differential equations usually encountered in boundary layer problems. The essence of that

method is the approximate solution of the equations by iteration, satisfying exactly at each iteration the known boundary conditions. Although the characteristics of convergence can not be predicted, an approach along this line is here suggested in view of its simplicity, its adaptability to automatic operation and its capability to provide results to any degree of accuracy. The salient procedural points are clearly illustrated by inspection of the following model solution of a system of two non-linear ordinary differential equations of the first order; extension to the higher order system (25) is immediate. Consider the equations

$$a_{11} \frac{df_1}{dx} + a_{12} \frac{df_2}{dx} = F_1 \quad (34)$$

$$a_{21} \frac{df_1}{dx} + a_{22} \frac{df_2}{dx} = F_2$$

with a_{11} , a_{12} , a_{21} , a_{22} , F_1 , F_2 = known functions of f_1 , f_2 , x , subject to the boundary conditions

$$\begin{array}{lll} \text{at} & x = 0 & f_1 = f_{10} \\ & & \\ \text{at} & x = 1 & f_2 = f_{21} \end{array} \quad (35)$$

Solve the system (34) for the highest order derivatives (in this case first order):

$$\frac{df_1}{dx} = \frac{F_1 - \frac{a_{12}}{a_{22}} F_2}{a_{11} + a_{21} \frac{a_{12}}{a_{22}}} \quad (36)$$

$$\frac{df_2}{dx} = \frac{1}{a_{12}} \left[F_1 - a_{11} \frac{df_1}{dx} \right]$$

At the general n^{th} iteration the properties $(f_1)_{n-1}$ and $(f_2)_{n-1}$ are known (in the initial stage estimated profiles satisfying the known boundary conditions are used as inputs. Write Eq. (36) in the form:

$$\left(\frac{df_1}{dx} \right)_n = \left[\frac{F_1 - \frac{a_{12}}{a_{22}} F_2}{a_{11} + a_{21} \frac{a_{12}}{a_{22}}} \right]_{n-1} \quad (37)$$

$$\left(\frac{df_2}{dx} \right)_n = \left[\frac{1}{a_{12}} \left(F_1 - a_{11} \frac{F_1 - \frac{a_{12}}{a_{22}} F_2}{a_{11} + a_{21} \frac{a_{12}}{a_{22}}} \right) \right]_{n-1}$$

Upon integration

$$[f_1(x)]_n = f_{10} + \int_0^x \left[\frac{F_1 - \frac{a_{12}}{a_{22}} F_2}{a_{11} + a_{21} \frac{a_{12}}{a_{22}}} \right]_{n-1} dx \quad (38)$$

$$[f_2(x)]_n = (f_{20})_n + \int_0^x \left[\frac{1}{a_{12}} \left(F_1 - a_{11} \frac{F_1 - \frac{a_{12}}{a_{22}} F_2}{a_{11} + a_{21} \frac{a_{12}}{a_{22}}} \right) \right]_{n-1} dx$$

The boundary conditions at $x=1$ define

$$(f_{20})_n = f_{21} - \int_0^1 \left[\frac{1}{a_{12}} \left(F_1 - a_{11} \frac{F_1 - \frac{a_{12}}{a_{22}} F_2}{a_{11} + a_{21} \frac{a_{12}}{a_{22}}} \right) \right]_{n-1} dx \quad (39)$$

and, therefore, Eqs. (38) can be used to generate the new profiles. The procedure is with a limit on $\frac{[(f_{20})_n - (f_{20})_{n-1}]}{(f_{20})_n}$. The procedure is amenable to further refinements: in particular when the solution oscillates an over-relaxed iteration or extrapolation can be used to expedite convergence.

V. CONCLUSIONS

A method has been presented for the study of the continuum viscous shock layer about re-entry bodies as it is encountered at altitudes approximately between 300 and 200 kft for vehicles having typical dimensions of the order of feet. An integral approach has been used which permits detailed description of distributions of flow properties along normals to the body surface and, thereby, should lead to reasonable predictions of observables. The present report has been concerned with the initial phase of the investigation, namely the development of the method of analysis. Applications will require extensive numerical work; guide lines therefor have been discussed.

REFERENCES

1. Hayes and Probststein, Hypersonic Flow Theory, Academic Press, Inc., New York, 1959.
2. Hall, J. G., Eschenroeder, A. Q., Marrone, P. V., Blunt-Nose Inviscid Airflows with Coupled Nonequilibrium Processes, J. Aero. Sci., Vol. 29, No. 9, pp. 1038-51, September 1962.
3. Galowin, L. S., Integral Method Solution for a Dissociated Laminar Boundary Layer Applied to a Hypersonic Reentry Body, GASL TR 313, September 1962.
4. Wilson and Hoshizaki, Inviscid Nonadiabatic Flow About Blunt Bodies, AIAA January 1964 meeting, Preprint 64-70.
5. Ho, H. T. and Probststein, R., The Compressible Viscous Layer in Rarefied Hypersonic Flow, Rarefied Gas Dynamics, Academic Press, Inc., New York, 1961, pp. 525-552.
6. Cheng, H. K., The Blunt Body Problem in Hypersonic Flow at Low Reynolds Number, CAL Rept. No. AF-1285-A-10, June 1963.
7. Belotserkovskii, O. M., The Numerical Method of Integral Relations, Journal of Comp. Math. and Math. Physics, Acad. of Sciences, USSR, Vol. 2, No. 5, 1962.
8. Belotserkovskii, O. M., Supersonic Symmetrical Flow of Perfect and Real Gases Around Blunt Bodies, Journal of Comp. Math. and Math. Physics, Acad. of Sciences, USSR, Vol. 2, No. 6, 1962.

DISTRIBUTION LIST
CONTRACT SD-149

<u>Organization</u>		<u>No. of Cys.</u>
Bell Telephone Laboratories Whippany, New Jersey Attn: Dr. C. W. Hoover	(84-8010-1)	1
Institute for Defense Analyses 400 Army-Navy Drive Arlington, Virginia 22202 Attn: Classified Library Dr. J. Menkes		1 1
Weapons Systems Evaluation Group The Pentagon, Washington, D.C. 20301 Attn: Dr. John Daniel	(84-8010-3)	1
Director of Defense Research & Engr. (Strategic Weapons) The Pentagon, Washington, D.C. 20301 Attn: Cdr. R. H. Wertheim	(84-8010-4)	1
Stanford Research Institute Missile Defense Analysis Project 3322 South Memorial Parkway Suite 137 Huntsville, Alabama Attn: Dr. Irving Yabroff	(84-8010-5)	1
Aeronutronic Division Philco Corporation Newport Beach, California Attn: Mr. John Knudsen	(84-8010-6)	1
General Electric Company TEMPO Division 735 State Street Santa Barbara, California Attn: Mr. L. I. Kopeikin	(84-8010-7)	1
Ballistic Systems Division (BSRV) Norton Air Force Base San Bernardino, California Attn: Col. D. C. Middlekauff	(84-8010-8)	10

Project 8010

2

<u>Organization</u>		<u>No. of Cys.</u>
General Electric Company (MSD) Philadelphia, Pennsylvania Attn: Dr. Rowe Chapman	(84-8010-9)	1
Defense Documentation Center Cameron Station Alexandria, Virginia	(34-8010-10)	20
Headquarters Strategic Air Command (OA) Offutt AFB, Nebraska	(34-8010-11)	1
Commander U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Md. Attn: Code BG (V. C. Dawson)	(34-8010-12)	1
Institute of Naval Studies 545 Technology Square Cambridge 39, Massachusetts Attn: George L. Street, Capt., USN	(34-8010-13)	1
Air Force Avionics Laboratory AVWW/ECM Technology Wright-Patterson AFB, Ohio 45433	(34-8010-14)	1
Stanford Research Institute Menlo Park, California Attn: Mr. Ralph Rapp	(34-8010-15)	1
Space Technology Laboratories, Inc. Florida Division P. O. Box 5277 Patrick AFB, Florida 32925 Attn: Technical Library	(84-8010-17)	1
AVCO Corp. Everett Research Laboratories Everett, Massachusetts Attn: Dr. R. Taylor	(34-8010-18)	1

Project 8010

3

<u>Organization</u>	<u>No. of Cys.</u>
Bureau of Weapons Dept. of the Navy Special Projects Office Washington, D.C. Attn: Cdr. A. Julian	(84-8010-19) 5
Kaman Nuclear Garden of the Gods Road Colorado Springs, Colorado Attn: Dr. John Hoffman	(34-8010-21) 1
Battelle Memorial Institute 505 King Avenue Columbus, Ohio Attn: DEFENDER (Ed Ungar)	(34-8010-22) 1
Defense Research Corporation P.O. Box 3587 Santa Barbara, California 93105 Attn: Mr. Ben Alexander	(84-8010-23) 1
AVCO Corporation (RAD) 201 Lowell Street Wilmington, Massachusetts Attn: Mr. Dan Hritzay	(84-8010-24) 1
Sandia Corporation Albuquerque, New Mexico Attn: Mr. Charles Winter	(84-8010-25) 1
Commander U.S. Naval Weapons Laboratory Dahlgren, Virginia Attn: Code: KRT(MODE)	(34-8010-27) 1
Lincoln Laboratory Massachusetts Institute of Technology Lexington, Massachusetts Attn: Dr. C. R. Wieser	(34-8010-28) 1
Dr. A. Nedzel	(34-8010-29) 1
Library	(34-8010-30) 2
Dr. M. Herlin - Group 35	(34-8010-32) 1
Dr. S. Edelberg - Group 35	(34-8010-33) 1
Dr. S. Slattey - Group 35	(34-8010-34) 1
Dr. J. Hermann - Group 35	(34-8010-35) 1
Dr. W. Kornegay - Group 35	(34-8010-36) 1
Dr. B. Bryant - Group 35	(34-8010-37) 1
Dr. G. Pippert - Group 35	(84-8010-38) 1
Dr. M. Balser - Group 35	1

Project 8010

4

<u>Organization</u>		<u>No. of Cys.</u>
Lincoln Laboratory Massachusetts Institute of Technology PRESS Field Station APO 555, Box 58 San Francisco, California 96555		
Attn: Dr. M. Labitt	(104-8010-39)	1
Mr. K. Kressa	(104-8010-41)	1
Commanding General Attn: Mr. E.J. Little/AMSMI-RNR USAMICOM Redstone Arsenal Huntsville, Alabama	(34-8010-42)	1
Institute of Science & Technology The University of Michigan Box 618 Ann Arbor, Michigan Attn: BAMIRAC Library	(34-8010-44)	1
Raytheon Company Attn: Mr. A. Truszanowski Sudbury, Massachusetts	(104-8010-45)	1
R.C.A. Laboratories Moorestown, New Jersey Attn: Mr. Archie Gold	(34-8010-47)	1
Advanced Research Projects Agency Washington, D.C. 20301 Attn: Dr. B. Fisher Dr. C.D. Fitz Mr. R. Zirkind Technical Information Office Mr. C. McLain, Rm. 2B-263	(34-8010-48) (34-8010-49) (34-8010-50) (34-8010-51) (34-8010-52)	1 1 1 3 1
Foreign Technology Division Wright-Patterson Air Force Base, Ohio Attn: TD-FCS (Schmidt)	(64-8010-54)	1
Conductron Corporation 393 S. Main Street Ann Arbor, Michigan Attn: Dr. K. Siegel	(64-8010-55)	1

Project 8010

5

<u>Organization</u>		<u>No. of Cys.</u>
Syracuse University Research Corp. Syracuse, New York Attn: Paul Howells	(64-8010-56)	1
Picatinny Arsenal U. S. Army Dover, New Jersey 07801 Attn: SMUPA-VL	(64-8010-57)	1
General Motors Defense Research Labs. Aerospace Operations Department Santa Barbara, California Attn: Dr. Colin Maiden	(64-8010-58)	1
Aeroelastic and Structures Laboratory Massachusetts Institute of Technology Cambridge, Massachusetts Attn: Dr. Emmitt A. Witmer	(64-8010-59)	1
National Engineering Science Company 711 South Fair Oaks Avenue Pasadena, California Attn: Dr. Richard Tracey	(64-8010-60)	1
Douglas Aircraft Company Missile and Space Systems Division Reentry Systems Advanced Programs Santa Monica, California Attn: V. E. Crosley	(84-8010-61)	1
TRW/Space Technology Laboratories One Space Park Redondo Beach, California Attn: Dr. William S. Carlson	(64-8010-62)	1
Sperry Gyroscope Co. Great Neck, New York Attn: Mr. K. B. Erkenbrack	(84-8010-63)	1

Project 8010

6

<u>Organization</u>		<u>No. of Cys.</u>
Flui Dyne Engineering Corp. 5900 Olson Memorial Highway Minneapolis, Minnesota 55422 Attn: Dr. James S. Holdhusen	(84-8010-64)	1
Aerospace Corporation P.O. Box 1308 San Bernardino, California		
Attn: Mr. K. Pierce	(84-8010-65)	2
Mr. G. Milburn	(84-8010-66)	2
Deputy for Studies and Analyses Research and Technology Division Attn: SESOM (Lt. Col. Greer) Wright-Patterson AFB, Ohio	(84-8010-67)	1

UNCLASSIFIED

UNCLASSIFIED