

UNCLASSIFIED

AD_ 4 5 2 1 0 3

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY DUUC

AS AD No. 452103


EVALUATION STUDY OF
TRANSPORT VEHICLES

D6 - 2067



452103

Final Report for Contract NO w - 63 - 0804C



THE **BOEING** COMPANY
AIRPLANE DIVISION
P. O. BOX 707 · RENTON, WASHINGTON

EVALUATION STUDY OF TRANSPORT VEHICLES

D6-2067

FINAL REPORT FOR CONTRACT NO W -63-0804C

EFFICIENCY DATA *C. H. Spangenberg R. E. Hammons*
OPERATIONAL DATA *C. H. Spangenberg R. E. Hammons*
COST DATA *C. H. Spangenberg R. E. Hammons*
SUPERVISED *C. H. Spangenberg* 6/18/64
APPROVED *R. O. Fitzsimmons* 6/18/64
W. H. COOK (DATE)

FINAL ISSUE NOVEMBER 17, 1964

SUMMARY

This report presents comparative data on a representative group of 47 intercontinental transport vehicles.

Data are shown on efficiency parameters such as vehicle L/D and cruise speed and on a cost parameter defined as the total transport system cost for each of the selected vehicles. A section is presented on operational factors which includes reliability, utilization, useful life and environment. This operational material is generally qualitative and is not necessarily limited to vehicles of this study.

The information is presented in data plots for ease of comparison and is summarized in tables.

Most coverage is given to current and possible future transport aircraft and ships. Covered in less detail are such vehicles as airships, helicopters, ground effect machines, hydrofoils and submarines.

The vehicles were chosen on the basis of being representative of their respective time periods and for showing the effect of changing a major design variable such as type of engine. The data for current vehicles were taken from flight manuals or other operating information. Data for future vehicles were generated in this study or were obtained from published information on selected vehicles.

SUMMARY

This report presents comparative data on a representative group of 47 intercontinental transport vehicles.

Data are shown on efficiency parameters such as vehicle L/D and cruise speed and on a cost parameter defined as the total transport system cost for each of the selected vehicles. A section is presented on operational factors which includes reliability, utilization, useful life and environment. This operational material is generally qualitative and is not necessarily limited to vehicles of this study.

The information is presented in data plots for ease of comparison and is summarized in tables.

Most coverage is given to current and possible future transport aircraft and ships. Covered in less detail are such vehicles as airships, helicopters, ground effect machines, hydrofoils and submarines.

The vehicles were chosen on the basis of being representative of their respective time periods and for showing the effect of changing a major design variable such as type of engine. The data for current vehicles were taken from flight manuals or other operating information. Data for future vehicles were generated in this study or were obtained from published information on selected vehicles.

ACKNOWLEDGEMENTS

This study was done under BuWeps contract NOW-63-0804C. Mr. F. W. Locke and Mr. H. O. Hollenberg of BuWeps served as project officers for the contract.

Organizations which were helpful in supplying information and data for this study were The Maritime Administration, Office of Ship Construction; Military Sea Transportation Service, Office of Maintenance and Repair; Buships, Preliminary Design Section; and Committee of American Steamship Lines, Washington, D. C.

TABLE OF CONTENTS


SUMMARY	1	3.2.5 Takeoff Field Length Comparison	93
		3.2.6 Payload-Range Curves for Study Vehicles	97
ACKNOWLEDGEMENT	11	3.2.7 Marine Innovation Data	100
TABLE OF CONTENTS	111	4.0 OPERATIONAL PARAMETER DATA	103
		4.1 Introduction	103
		4.2 Reliability	103
		4.2.1 General	103
		4.2.2 Transport Aircraft	105
		4.2.2.1 General	105
		4.2.2.2 Specific Data	106
		4.2.3 Transport Ships	110
		4.3 Utilization	112
		4.3.1 General	112
		4.3.2 Operational Utilization	113
		4.3.2.1 Transport Aircraft	113
		4.3.2.1.1 Military Operation	113
		4.3.2.1.2 Commercial Operation	120
		4.3.2.2 Transport Ships	121
		4.3.3 Loading Capability Utilization	124
		4.3.3.1 Transport Aircraft	124
		4.3.3.1.1 Military Operation	124
		4.3.3.1.2 Commercial Operation	124
		4.3.3.2 Transport Ships	127
SYMBOL LIST			
1.0 INTRODUCTION	1		
2.0 DISCUSSION	3		
2.1 Definition of Study Vehicle Characteristics	3		
2.1.1 Transport Aircraft	3		
2.1.2 Transport Ships	5		
2.1.3 Underwater Transport	5		
2.1.4 Innovation Transport Craft	6		
3.0 EFFICIENCY PARAMETER DATA	9		
3.1 Definition of Parameters of Interest	9		
3.2 Plotted Data	18		
3.2.1 Data Plotted vs V_{cru}	19		
3.2.2 Data Plotted vs Year Enter Service	41		
3.2.3 Data Plotted vs $P/L \times V_{cru}$	61		
3.2.4 Data Plotted vs $P/L \times R$	77		

4.4 Useful Life	129	4.6.3.3 Capability Summary and Comparison	153
4.4.1 General	129		
4.4.2 Structural Life	129	5.0 COST PARAMETER DATA	155
4.4.2.1 Transport Aircraft	129	5.1 General	155
4.4.2.1.1 Discussion	129	5.2 Description of Cost Model	156
4.4.2.1.2 Fatigue as a Limiting Factor	130	5.2.1 Transport Aircraft	156
4.4.2.2 Transport Ships	135	5.2.2 Transport Ships	156
4.4.3 Economic Life	136	5.3 Description of Input Assumptions	157
4.4.3.1 Transport Aircraft	136	5.4 Plotted Data	160
4.4.3.2 Transport Ships	137	5.4.1 Program Cost - Dollars/Ton Mile per Day	160
4.5 Operating Environment	138	5.4.2 Industrial Fund Rate - Cents/Ton Nautical Mile	172
4.5.1 Transport Aircraft	139		
4.5.2 Transport Ships	142	5.4.3 Sensitivity Comparisons	176
4.6 Determination of Mission Problem and Fleet Size for Cost Model	146	5.4.4 Program Cost vs Performance Parameters	184
4.6.1 Discussion	146	6.0 CONCLUDING REMARKS AND RECOMMENDATIONS	191
4.6.2 Peacetime Logistics Mission	146		
4.6.2.1 Transport Aircraft	146	7.0 APPENDIX I - SUBSTANTIATING DATA FOR VEHICLES DESIGNED IN THIS STUDY	193
4.6.2.2 Transport Ships	146		
4.6.2.3 Capability Summary and Comparison	147	7.1 Transport Aircraft	193
4.6.3 Thirty Day Deployment of an Armored Division	147	7.1.1 Drag	199
		7.1.2 Weight	199
4.6.3.1 Transport Aircraft	150	7.1.3 Powerplant	202
4.6.3.2 Transport Ships	152	7.2 Transport Ships	203

8.0 APPENDIX II - SUBSTANTIATING DATA FOR

COST MODELS	
8.1 Military Air Transport Costing Method	205
8.1.1 Introduction	205
8.1.2 Program Cost	206
8.1.3 Initial Investment Cost	208
8.1.4 Operation and Maintenance Costs	212
8.1.5 Industrial Funding	215
8.1.6 Personnel Requirements	215
8.2 Military Sea Transport Costing Method	221
8.2.1 Introduction	221
8.2.2 Program Cost	223
8.2.3 Initial Cost	223
8.2.4 Annual Operating Expense	228
9.0 REFERENCES	241

SYMBOL LIST

a	Turbofan engine bypass ratio = Wt flow of air passing fan nozzle <u>46 flow of air passing primary nozzle</u>	LFC	Laminar Flow Control
bb1	Barrel, 6.63 barrels of fuel oil weigh one long ton.	LOBOY	A generic term applied to certain winged aircraft which fly in ground effect to reduce induced drag.
C_f	Equivalent 3-dimensional friction coefficient	L.T.	Long ton = 2,240 lbs
P_H/s	Engine net thrust (lbs)/atmospheric pressure ratio	MAC	Mean Aerodynamic Chord
f	Equivalent drag area, square feet Equal to $C_f \times S_w$	M L/D	The product, Mach No. x L/D
GW	Gross Weight or gross displacement, lbs, short tons, or long tons as noted	M.T.	Measurement ton = 40 cubic feet of cargo volume
HP	Horsepower, brake HP for reciprocating engines; equivalent shaft HP for turboprop engines.	N. Mi./lb	Vehicle nautical mile/lb fuel consumed
h/b	Values quoted for aircraft are maximum dry sea level static rating	O.W.E.	Operating Weight Empty, lbs, short tons, or long tons as noted
L/D	Ratio of height above water to span, measured at aircraft 1/4 MAC Lift/drag ratio		For aircraft see page 200 For ships = weight of steel + weight of machinery + weight of outfit + weight of provisions, stores, crew and effects, and dunnage.
	Values quoted are at the average cruise point. See  , page 11.	P	General symbol to indicate total dry rated power available in terms of HP, ESHP, or thrust for reciprocating, turboprop, or turboprop engines respectively.

P/L	Payload or cargo deadweight, lbs, short tons, or long tons as noted.	W_{STRU}	Structural weight, pounds, short tons, or long tons as noted
POL	Petrol, oil and lubricant		For aircraft see page 200
R	Range, nautical miles		For ships W_{STRU} = Weight of steel unless otherwise noted.
S	Wing area, square feet		Powerplant weight, pounds, short tons or long tons as noted
SHP _N	For marine installations, total normal shaft horsepower.	W_{PP}	For aircraft see page 200
S _v	Airplane wetted area, square feet.		For ships W_{pp} = Weight of machinery unless otherwise noted.
S _{fT.O.}	Takeoff field length, feet.		
sfc/√ σ	Specific fuel consumption/square root of atmospheric temperature ratio	W_{FU}	Weight of fuel used, pounds, short tons or long tons as noted
S.T.	Short ton = 2,000 pounds		W_{FU} = total fuel less reserve fuel
T	Thrust, pounds		
V _{cru}	Cruise speed, knots	$\eta_{overall}$	Efficiency parameter defined as: work/unit time done on vehicle work equivalent fuel input/unit time

1.0 INTRODUCTION

The purpose of this report is to present information in handbook form on selected transport vehicles. It is expected that the report will be useful in providing a background for future comparative studies.

Material is presented in three basic areas:

1. Data related to the vehicle technical efficiency. (Section 3.0)
2. Data related to vehicle operation. (Section 4.0)
3. Data related to vehicle cost and operation on a selected intercontinental mission. (Section 5.0)

Vehicles selected for inclusion in the study include aircraft, ships, underwater craft and several vehicles which are new and different - termed innovations. The vehicles are primarily those used for intercontinental transport. Several aircraft and ships which do not fit this classification are included to provide an end point to the data curves.

The format of the efficiency data presentation is generally similar to that followed by Gabrielli and Von Karman in their paper "What Price Speed?", although a much more comprehensive coverage is given to the selected vehicles.

Operational data are presented in narrative style. Each of the several items categorized as "operational" is discussed and examples are shown, where applicable. Because of the nature of the subject, this section is necessarily less quantitative than either Sections 3 or 5.

Cost data are shown in tables and curves for the study vehicles, each used in a typical intercontinental mission. The intent is more to present engineering data than to complete an operational research study. Because operational costs are connected with mission considerations it was necessary to define a general mission. Ground rules and assumptions are discussed in Sections 4.6 and 5.3.

To provide as complete coverage as possible for transport vehicles in the time period between now and 20 years hence, several classified vehicles have been chosen. Efficiency parameter data on these classified vehicles is contained in a confidential supplement to this report, D6-2068, "Evaluation Study of Transport Vehicles - Supplement."

2.0 DISCUSSION

The most significant problem confronting the designer when evaluating advancements in the state-of-the-art is to separate that which is feasible from that which is desirable.

It is helpful to recognize that successful vehicles are necessarily an integration of technical advancement and economic situation. Viewed in retrospect these historical integrations of technical, operational and economic facts are useful for making comparisons with current engineering possibilities.

The three major sections of this report are presented with this use in mind. The current vehicles for which data are shown were picked on the basis that

1. they were representative of a certain time period or vehicle group and that
2. data were available in sufficient detail to allow adequate description. Future vehicles were chosen on the basis of what is possible if the current state-of-the-art is projected 20 years into the future.

2.1 DEFINITION OF STUDY VEHICLE CHARACTERISTICS

2.1.1 TRANSPORT AIRCRAFT

Aircraft selected for the study are listed in Table 1. They are typical transport aircraft which operate currently, together with some which may operate in the next 20 years. Several of the current aircraft were brought into service as much as 20 years ago. This provides approximately a 40 year spread between the oldest aircraft presented and the most advanced projections.

The current aircraft generally are well known and most readers will be well acquainted with them. For the benefit of other readers the characteristics listed in Table 1 will serve to identify each of the plotted points in Section 3.2

Ten aircraft designed specifically for this study are identified with Boeing model numbers 742-302 through 742-311. These aircraft are typical of state-of-the-art advances which could take place in the next 20 years. Model

Table 1 Aircraft Characteristics

AIRCRAFT	YEAR ENTER SERVICE	GROSS WEIGHT (LB)	WING SPAN (FT)	WING AREA (SQ FT)	NO. ENGINES	ENGINE TYPE	TOTAL INSTALLED POWER OR THRUST	AVG. CRU TOTAL FUEL FLOW (LB/HR)	CRUISE SPEED (KTS)	REMARKS
C-24G	1945	69,000	117.5	1457	4	P & W R-2000-9	5800 HP	1,386	176	
JRM-2	1946	165,000	200.0	3686	4	P & W R-1360-C	12000 HP	2,142	150	
C-118A	1952	107,000	117.5	1463	4	P & W R-2800-62W	8800 HP	1,881	217	
C-124C	1953	165,000	174.1	2508	4	P & W R-4360-63A	13600 HP	3,239	182	
C-133A	1957	275,000	179.7	2973	4	P & W T34-P-7WA	24000 ESHP	8,200	260	
CL-44D-4	1961	205,000	142.3	2075	4	R-R TYNE 12	22920 ESHP	4,668	321	
C-135B	1962	277,500	130.8	2433	4	MARK 515 JT3D-3	72000 LBS	11,132	467	
C-130E	1962	155,000	132.6	1745	4	Allison T58-A-7	16200 LBS	4,253	292	
707-320C L-300	1963	328,000	145.7	2942	4	JT3D-3B	72000 LBS	12,440	466	
	1965	319,000	160.1	3228	4	JT3D-8A	84000 LBS	11,508	435	
742-302	1973	650,000	250.0	5630	4 T'PROP 3 T'PROP	REGEN T'PROP	30000 ESHP	3,627	183	LOBOY - 200,000 lb P/L-8, 800 N.MI.
-303	1973	585,000	232.5	4875	4 T'PROP 2 T'PROP	REGEN T'PROP	69000 ESHP	3,492	189	LOBOY - 200,000 lb P/L-6, 500 N.MI.
-304	1973	830,000	286.0	9750	4 T'PROP + 4 COMP	REGEN T'PROP	58000 LBS	14,950	420	LFC - 200,000 lb P/L-6, 600 N.MI.
-305	1973	672,000	203.0	5185.2	6	A-3 T'PROP	134400 LB	21,645	434	200,000 lb P/L-3, 800 N.MI.
-306	1973	1,340,000	284.0	10307.7	6	A-3 T'PROP	268000 LB	38,558	437	400,000 lb P/L-3, 980 N.MI.
-307	1983	651,000	200.0	5007.7	6	A-3 T'PROP	130200 LB	19,211	430	200,000 lb P/L-3, 960 N.MI.
-308	1983	1,310,000	284.0	10076.9	6	A-3 T'PROP	262000 LB	36,692	430	400,000 lb P/L-4, 200 N.MI.
-309	1973	650,000	266.0	5909.1	6	A-5 T'PROP	22640 LB	14,283	344	200,000 lb P/L-3, 750 N.MI.
-310	1983	588,000	253.0	5345.5	6	A-15 T'PROP	125106 LB	9,676	344	200,000 lb P/L-3, 920 N.MI.
742-311	1973	356,000	148.2	2738.5	4	REGEN T'PROP	75744 LB	11,176	431	100,000 lb P/L-4, 200 N.MI.
748B-15	1968	600,000	206.8	5000	6	P & W JT3D-8B	138000 LB	22,973	448	160,000 lb P/L-2, 735 N.MI.

△ CRUISE; REGEN T'PROP, TAKEOFF; REGEN T'PROP + T'PROP

▽ BYPASS RATIO 5 T'PROP + LFC BLEED & BURN SUCTION COMPRESSOR

748B-15 is also a study aircraft. It is one of many configurations which have been considered for the (now) CX-HIS mission.

Data are presented for these study aircraft not as a prediction of what will occur in the future nor is their presence in this study indicative of particular current interest. Rather, each was chosen as being representative of one or more engineering advances which may be technically feasible. As such, each configuration is worthy of comparison with other current and future aircraft.

A fairly conservative approach was taken in defining these future aircraft. Description of the design method is included in Section 7.

2.1.2 TRANSPORT SHIPS

Transport ships, selected for the study, are listed in Table 2. In line with the nature of the study, they are mostly dry-cargo transports. A few tankers are included for comparison. The selection provides a representative cross-section of vehicles and power plants. It will be noted that most of the current dry-cargo ships were

launched 15 to 20 years ago. Exceptions are, the Mariner Class ships which were introduced in 1952, and the roll-on/roll-off designs seen in the last 4 years.

The increase in ship size and speed with time is characteristically much slower than for aircraft. The 742-320S, -321S ships designed for this study, reflect this conservatism. These ships are described in Section 7.2 and in Ref. 26. The large current tankers included show perfectly the increase in L/D possible with very large (long) ships operated at moderate speeds, do take advantage of the possible reduction in wave making drag.

2.1.3 UNDER WATER TRANSPORT

A number of studies have been completed, in recent years, to evaluate submarine transports. Refs. 31 and 33 are samples of this work. Several study configurations for these submarine transports have been included in the efficiency section of this report. They are defined in Table 3. The actual operational and cost data for submarines, to date, is entirely for Navy strategic or tactical missions. The lack of

Table 2 Ship Characteristics

SHIP	YEAR ENTER SERVICE	GROSS DISPLACEMENT (L. T.)	LENGTH BETWEEN PERP. (FT)	BEAM (FT)	ENGINE TYPE	TOTAL INSTALLED POWER SHP _N	FUEL FLOW @ SHP _N (BBL/DAY)	SEA SPEED (KTS)
C3-S-A2	1942	17615	462.0	69.5	STEAM TURBINE	6500	376	16.5
C1A	1942	11085	390.0	60.0	STEAM TURBINE	4000	176	14.0
C2-S-AJ1	1943	14945	435.0	63.0	STEAM TURBINE	6000	258	15.5
VC2-S-AP3	1944	15210	437.0	62.0	STEAM TURBINE	9500	329	16.5
C1-M-A'71	1944	8265	324.0	50.0	DIESEL	1700	63	10.5
C4-S-11	1952	21093	528.0	76.0	STEAM TURBINE	17500	647	20.3
C3-ST-14a	1958	18286	465.0	78.0	STEAM TURBINE	11220	478	18.0
C4-S-57a	1963	21053	529.0	75.0	STEAM TURBINE	16500	625	20.5
C4-ST-67a	1964	21700	499.5	83.0	STEAM TURBINE	17500	702.5	20.0
T2-SE-A1	1942	21748	510.0	68.0	TURBO-ELEC.	6000	271	14.5
S.S. MANHATTAN MEDIUM TANKER	1962	137068	892.0	132.0	STEAM TURBINE	39000	1440	17.7
	1955	49660	677.0	93.0	STEAM TURBINE	20000	738	18.0
742-320S	1975	24000	598.0	76.0	STEAM TURBINE	24000	852	23.5
742-320S NUC	1975	24000	598.0	76.0	NUCLEAR	24000	---	23.5
742-321B	1985	45000	750.0	106.0	STEAM TURBINE	66000	2215	25.0
742-321S NUC	1985	45000	750.0	106.0	NUCLEAR	66000	---	25.0

any available information for a general logistic mission precluded their use in Sections 4 and 5. In addition, most authoritative writers indicate that the design problems for submarine transport outweigh the operational advantages to such an extent that even in 20 years' time their appearance is doubtful. For the present these vehicles are categorized as engineering possibilities and economic improbabilities.

2.1.4 INNOVATION TRANSPORT CRAFT

From time to time, vehicles are presented which can only be categorized as innovations to the transport field. They are to a greater or lesser extent technically feasible. The economic justification is often less apparent than the engineering feasibility and their development is terminated short of completion.

Vehicles of Table 4 are in part of this kind. The airships are included for their historical interest and to complete the vehicle comparisons against speed and calendar years.

While the helicopter has entrenched itself firmly in certain short range mission areas it does not fit the role of transport aircraft in the same sense as a fixed wing aircraft. For this

Table 3 Submarine Characteristics

SUBMARINE	YEAR ENTER SERVICE	GROSS DISPLACEMENT (L.T.)	BEAM (FT)	ENGINE TYPE	TOTAL INSTALLED POWER SHP _N	SEA SPEED (KTS)
TANKER A	1980	41800	80.0	NUCLEAR	27400	20.0
TANKER B	1980	101400	80.0	NUCLEAR	218000	37.4
TANKER C	1980	48200	78.74	NUCLEAR	40000	22.0

Table 4 Innovation Craft Characteristics

VEHICLE	VEHICLE TYPE	YEAR ENTER SERVICE	GROSS WEIGHT OR DISPLACEMENT	LENGTH BETWEEN PERP. (FT)	BEAM (FT)	ENGINE TYPE	TOTAL INSTALLED POWER	FUEL FLOW	SPEED (KTS)
742-322S	HYDROFOIL	1970	1060 L. T.	235	52	GAS TURBINE	24200 HP	942 bbl/day	40.0
90 TON P/L	GEM	1970	280000 LB	-	-	GE T-64	11200 ESHP	4519 lb/hr	40.0
15 TON P/L	GEM	1970	62270 LB	-	-	GE T-64	5400 ESHP	2564 lb/hr	40.0
VERTOL HC-1B	HELICOPTER	1962	33000 LB	-	-	LYCOMING T-55	5490 ESHP	2338 lb/hr	130.0
ZMC-2	AIRSHIP	1929	11900 LB	-	-	WRIGHT J-5	440 HP	77 lb/hr	40.0
MACON	AIRSHIP	1933	403000 LB	-	-	MAYBACH V12	4480 HP	784 lb/hr	50.0
ZPG-2	AIRSHIP	1954	66800 LB	-	-	WRIGHT R-1300-2A	1600 HP	195 lb/hr	40.0

reason it is included here rather than in
Table 1.

The same comment applies to the hydrofoil ship,
as compared to the displacement ship.

A large number of Ground Effect Machine configurations have been proposed and several are now operating. While many claims have been made, they are still, at best, innovations. In the interest of realism and economy of effort in this study only two GEM's, of Ref. 23, are presented.

Efficiency data, for the airship, helicopter, hydrofoil ship and GEM, are presented as completely as possible. Operational and cost parameter data are omitted because of their paucity or because of the unreasonable effort required to make it compatible with other data.

In addition, a limited amount of efficiency data is presented in Section 3.2.7 for certain marine innovations. These data are less complete than for the other innovations but are shown, in limited form, for their interest.

3.0 EFFICIENCY PARAMETER DATA

3.1 DEFINITION OF PARAMETERS OF INTEREST

The efficiency parameters are defined by the data plots (Figs. 3 through 11) of this section. Tables 5 and 6 are provided to summarize these data and to provide greater accuracy than is possible to read from the plots. In some of the plots, due to the large variation in the parameter value, a compromise had to be made between choosing easily read scale values and omitting, from the plot, the extreme values. This results in some vehicle parameters not appearing in the plotted data.

Taken singly or in combination these parameters define each vehicle's aerodynamic (or hydrodynamic), propulsive, and structural efficiency. The data have been derived from T.O.'s and SAC charts for the military airplanes. Commercial airplane data were taken from manufacturer's performance manuals and detail specifications. Ship data were obtained from MSTs and MarAd documents. Data for vehicles designed in the course of this study were developed using

standard design information and techniques.

Aircraft and ship designers commonly use terms which are unique to their own fields. Insofar as possible, ship building parameters have been defined in aircraft terms for these plots. An explanation is given where common definitions are not possible.

The data are presented in five basic groups:

- I. data plotted vs. V_{cr}
- II. data plotted vs. year enter service
- III. data plotted vs. $P/L \times V_{cr}$ (P/L is taken as the maximum permissible value)
- IV. data plotted vs. $P/L \times R$ (the product is taken as the maximum permissible value)
- V. A comparison of takeoff field length for the aircraft

In Group V, takeoff field length is plotted, together with $\frac{P/L}{GW}$ and L/D , vs. V_{cr} and year entered service. In all cases the field length shown is for military critical field length at maximum takeoff weight.

For Groups I-IV the following parameters are plotted on the ordinate scale:

<u>Parameter</u>	<u>Comment</u>
(1) Year Enter Service	Not Shown for Group II
(2) L/D	1 The value shown is for the average cruise point. It is somewhat less than the maximum value for several of the vehicles.
(3) M L/D	1 Aircraft terminology. Not significant to ship performance and not shown for marine vehicles.
(4) η_{overall}	1 Work done on the vehicle/ unit time = $\frac{\text{Work equivalent fuel}}{\text{input/unit time}}$
(5) $\eta_{\text{overall}} \times L/D$	1 This is a measure of the total vehicle efficiency.
(6) $\frac{\text{N.Mi.}}{\text{LB}} (\text{fuel})$	1 Not shown for Groups III and IV
(7) $P/L \times \frac{\text{N.Mi.}}{\text{LB}}$	1 Not shown for Groups III and IV

(8) $\frac{P/L}{GW}$

For ships, P/L is generally referred to as cargo dead weight.

(9) $\frac{OWE}{GW}$

See the symbol list for the meaning of this term for marine vehicles.

(10) $\frac{P/L}{OWE}$

(11) $\frac{W_{\text{stru}}}{GW}$

This is a reasonable measure of the vehicles' structural efficiency when interpreted in the light of vehicle capability and design load factor.

(12) $\frac{W_{\text{pp}}}{GW}$

(13) $\frac{W_{\text{FU}}}{GW}$

(14) $\frac{W_{\text{pp}} + W_{\text{FU}}}{GW}$

(15) $\frac{W_{\text{pp}} + W_{\text{FU}}}{P/L}$

(16) $\frac{W_{\text{pp}}}{P}$

Not shown for Groups III and IV

(17) $\frac{P}{GW}$

Not shown for Groups III and IV

(18) $\frac{P}{GW} \times V_{\text{cru}}$

Not shown for Groups III and IV

- (19) $\frac{P}{L} \times V \text{ cru}$ Not shown for Groups III and IV
- (20) $\frac{P}{L} \times V \text{ cru}$ 1 Not shown for Groups III and IV
- $\frac{\text{Work equivalent fuel input per unit time}}$

1 This parameter is defined at the average cruise point. For aircraft this is taken to be 1/2 the range at the break in the P/L-Range curve. For ships it is arbitrarily set at 4000 N.Mi. Range does not have a strong influence on this parameter for ships.

2 W_{FU} is defined at the break in the P/L-R curve for aircraft. For ships it is arbitrarily set at 4000 N. Mi.

Most of these parameters will be familiar to the reader. A definition for each is included in the symbol list. Discussion on those which may be ambiguous or unfamiliar is included here.

η_{overall} is defined as the ratio, work done on the vehicle to work equivalent fuel input. The work done per unit time = drag x velocity = $W \times V$.

The work input to the system/unit time = fuel flow x heat content x Joule's constant (778 FT-LB/BTU)

$\eta_{\text{overall}} \times \frac{L}{D}$ reduces to $\frac{W \times V}{\text{Work input/unit time}}$

$\frac{N. Mi.}{LB}$ This aircraft performance parameter varies inversely with vehicle size. It is most useful in comparing vehicles of the same payload and range capability.

$\frac{P}{L} \times \frac{N. Mi.}{LB}$ Dimensionally this parameter is useful work per pound fuel expended. Items (8) through (12) are the usual vehicle weight fractions.

Item (13) is the fuel fraction at design payload and range.

Items (16) through (19) define the power or thrust characteristics for each of the vehicles. The basically different rating systems for turbofan and turboprop or piston aircraft engines preclude the use of common terminology. The respective symbols are defined in the symbol list.

$\frac{P}{L} \times V \text{ cru}$ This parameter compares the useful work output with the work equivalent input per common time unit.

$\frac{\text{Work equivalent fuel input per unit time}}$

Table 5 Aircraft Efficiency Parameter Data

VEHICLE	IDENTIFICATION	YEAR ENTER SERVICE	L/D	M L/D	$\eta_{OVERALL}$	$\eta_{OVERALL} \times L/D$	$\frac{N.M.L.}{lb}$	$\frac{P/L \times N.M.L.}{lb}$	$\frac{P/L}{GW}$	$\frac{OWF}{GW}$	$\frac{P/L}{OWE}$	$\frac{WSTRU}{GW}$
Airplane	C-54G	1945	14.6	3.97	.242	3.33	.1266	1.22	.279	.364	.478	.293
Airplane	JRM-2	1946	17.1	3.91	.262	4.49	.0693	1.61	.285	.317	.553	.299
Airplane	C-118A	1952	17.8	6.08	.268	4.78	.1110	1.59	.267	.509	.525	.243
Airplane	C-124C	1953	17.2	4.83	.241	4.16	.0551	1.52	.299	.568	.526	.304
Airplane	C-133A	1957	17.5	7.37	.189	3.31	.0303	1.47	.353	.427	.823	.285
Airplane	CL-44D-4	1961	18.1	9.71	.289	5.24	.0682	2.19	.314	.442	.709	.295
Airplane	C-135B	1962	17.0	13.41	.242	4.12	.0394	1.71	.312	.391	.793	.236
Airplane	C-130E	1962	15.5	7.51	.257	3.99	.0650	1.46	.290	.371	.616	.254
Airplane	707-320C	1963	17.6	14.18	.250	4.41	.0352	1.68	.291	.410	.710	.249
Airplane	L-300	1965	16.7	12.52	.263	4.39	.0366	1.55	.267	.407	.655	.265
Airplane	742-302	1973	34.8	9.64	.345	12.00	.0503	5.03	.308	.385	.798	.266
Airplane	742-303	1973	32.8	9.35	.351	11.50	.0537	5.37	.354	.402	.891	.275
Airplane	742-304	1973	34.2	24.97	.248	8.49	.0267	2.67	.241	.461	.522	.377
Airplane	742-305	1973	20.3	15.21	.264	5.36	.0205	2.05	.293	.396	.753	.314
Airplane	742-306	1973	21.2	15.05	.266	5.64	.0110	2.20	.299	.400	.746	.330
Airplane	742-309	1973	24.3	14.16	.250	6.07	.0235	2.35	.309	.422	.730	.333
Airplane	742-307	1983	20.4	14.82	.266	5.45	.0218	2.18	.307	.331	.807	.302
Airplane	742-308	1983	21.5	15.55	.266	5.70	.0114	2.25	.303	.379	.805	.320
Airplane	742-310	1983	23.3	13.48	.354	8.26	.0346	3.46	.340	.446	.763	.339
Airplane	742-311	1973	19.2	14.35	.263	5.05	.0375	1.88	.281	.370	.759	.276
Airplane	748B-15	1988	16.8	12.95	.251	4.21	.0192	1.46	.267	.450	.593	.344
Helicopter	VERTOL HC-1B	1962	NA	-	-	-	.0556	.31	.333	.525	.610	.249
Ground effect machine	90 Ton P/L	1970	12.3	0.75	.083	1.02	.0669	.90	.644	.307	2.096	.347
Ground effect machine	15 Ton P/L	1970	8.6	0.52	.045	0.39	.0156	.23	.482	.390	1.236	.382
Airship	ZMC-2	1929	11.2	0.66	.211	2.36	.5159	.34	.109	NA	-	NA
Airship	MACON	1933	39.6	3.01	.245	9.73	.0637	2.91	.227	NA	-	NA
Airship	ZPG-2	1954	25.1	1.83	.208	5.22	.2058	.71	.103	.733	.141	.440

OVERALL	OVERALL x L/D	N.MI. lb	P/L x N.MI. lb	F/L GW	P/L OWE GW	W STRU GW	W PP GW	W FU GV	W L + W FU GW	W PP + W FU P/L	W PP P	P lb	P GW	P GW x V CRU	P ST-KNOT	P P/L x V CRU	P ST-KNOT	P/L x V CRU WORK EQUV. INPUT
.242	3.53	.1266	1.22	.279	.584	.478	.172	.123	.295	1.056	2.039	.084	.951	.951	3.409	3.409	1.053	
.262	4.49	.0623	1.61	.285	.517	.55	.127	.177	.304	1.068	1.752	.073	.970	.970	3.393	3.393	1.447	
.268	4.76	.1110	1.59	.267	.508	.5	.153	.201	.354	1.324	1.860	.082	.757	.757	2.830	2.830	1.437	
.241	4.16	.0551	1.52	.299	.568	.528	.146	.120	.266	.892	1.987	.074	.808	.808	2.704	2.704	1.332	
.189	3.31	.0303	1.47	.353	.427	.828	.070	.198	.298	.759	.804	.087	.671	.671	1.909	1.909	1.310	
.269	5.24	.0682	2.19	.314	.442	.709	.065	.220	.285	.907	.583	.112	.686	.686	2.216	2.216	1.875	
.242	4.12	.0394	1.71	.312	.391	.798	.091	.268	.358	1.148	.350	.259	1.131	1.131	3.636	3.636	1.513	
.257	3.99	.0650	1.46	.290	.471	.616	.109	.215	.324	1.116	1.043	.105	.713	.713	2.464	2.464	1.515	
.250	4.41	.0352	1.68	.291	.410	.710	.074	.269	.343	1.178	.338	.220	.94	.94	3.220	3.220	1.508	
.263	4.39	.0366	1.55	.267	.407	.655	.074	.292	.366	1.37	.279	.264	.214	.214	4.558	4.558	1.399	
.345	12.00	.0503	5.03	.308	.385	.798	.066	.269	.335	1.090	-	-	-	-	-	-	4.303	
.351	11.50	.0537	5.37	.354	.402	.881	.067	.214	.281	.795	-	-	-	-	-	-	4.580	
.248	8.49	.0267	2.67	.241	.461	.522	.036	.271	.307	1.274	.179	.200	.930	.930	3.932	3.932	2.360	
.264	5.36	.0205	2.05	.298	.396	.752	.031	.278	.307	1.031	.151	.200	.922	.922	3.098	3.098	1.892	
.266	5.64	.0110	2.20	.299	.400	.746	.033	.271	.304	1.020	.185	.200	.916	.916	3.066	3.066	1.973	
.250	6.07	.0235	2.35	.308	.422	.730	.032	.244	.276	.897	.174	.189	.897	.897	3.566	3.566	2.165	
.266	5.45	.0218	2.18	.307	.381	.807	.027	.281	.308	1.001	.134	.200	.930	.930	3.028	3.028	1.985	
.266	5.70	.0114	2.26	.305	.379	.805	.028	.284	.312	1.022	.142	.200	.930	.930	3.043	3.043	2.068	
.354	8.28	.0346	3.46	.340	.446	.763	.047	.193	.241	.707	.224	.213	1.237	1.237	3.638	3.638	3.150	
.263	5.05	.0375	1.86	.287	.370	.759	.032	.314	.346	1.232	.149	.213	.987	.987	3.516	3.516	1.720	
.251	4.21	.0182	1.46	.287	.450	.593	.055	.255	.310	1.161	.240	.230	1.030	1.030	3.864	3.864	1.314	
-	-	.0556	.31	.333	.525	.610	.159	.109	.268	.805	.955	.166	1.560	1.560	7.680	7.680	.260	
.083	1.02	.0089	.80	.644	.307	2.096	.037	.051	.087	.136	.915	.040	1.000	1.000	3.100	3.100	.875	
.045	0.39	.0156	.23	.482	.390	1.236	.110	.129	.238	.494	1.263	.087	1.340	1.340	9.090	9.090	.300	
.211	2.36	.5159	.34	.109	NA	-	NA	NA	-	-	-	.037	1.848	1.848	16.920	16.920	.375	
.245	9.73	.0637	2.91	.227	NA	-	NA	NA	-	-	-	.011	.444	.444	1.958	1.958	2.385	
.208	5.22	.2008	.71	.103	.733	.141	.103	.146	.249	2.409	4.312	.024	1.198	1.198	11.594	11.594	.582	

Table 6 Ship Efficiency Parameter Data

VEHICLE	IDENTIFICATION	YEAR ENTER SERVICE	L/D	$\eta_{OVERALL}$	$\eta_{OVERALL} \times L/D$	$\frac{N.M.I.}{lb}$		$\frac{P/L \times \frac{N.M.I.}{lb}}{ST-N.M.I. / lb}$	$\frac{P/L}{GW}$	$\frac{OWE}{GW}$	$\frac{P}{OW}$
						$\frac{N.M.I.}{lb}$	$\frac{N.M.I.}{lb}$				
Surface Dry Cargo Ship	C3-S-A2	1942	290	.184	53.3	3.116×10^{-3}	38.17	.621	.347	1.7	
Surface Dry Cargo Ship	C1A	1942	337	.181	60.8	5.687×10^{-3}	43.25	.613	.359	1.7	
Surface Dry Cargo Ship	C2-S-AJ1	1943	341	.132	62.1	4.303×10^{-3}	46.44	.645	.327	1.3	
Surface Dry Cargo Ship	C1-M-AV1	1944	456	.209	95.1	11.905×10^{-3}	75.11	.683	.300	2.2	
Surface Dry Cargo Ship	VC2-S-AP3	1944	256	.206	52.7	3.579×10^{-3}	38.56	.632	.335	1.8	
Surface Dry Cargo Ship	C4-S-1a	1952	231	.198	45.7	2.238×10^{-3}	29.97	.567	.395	1.4	
Surface Dry Cargo Ship	C3-ST-14a	1958	293	.162	47.5	2.677×10^{-3}	26.35	.481	.483	.9	
Surface Dry Cargo Ship	C4-S-57a	1963	228	.209	47.7	2.328×10^{-3}	31.11	.567	.397	1.4	
Surface Dry Cargo Ship	C4-ST-67a	1964	247	.173	42.7	2.018×10^{-3}	21.17	.432	.528	.8	
Surface Tanker	T2-SE-A1	1942	470	.171	80.3	3.808×10^{-3}	66.61	.718	.260	2.7	
Surface Tanker	Mad. Tanker	1955	440	.180	83.6	1.737×10^{-3}	72.50	.750	.229	3.1	
Surface Tanker	S. S. Manhattan	1962	640	.182	116.7	$.875 \times 10^{-3}$	201.02	.752	.233	3.2	
Surface Dry Cargo Ship	742-320S	1975	230	.199	45.7	1.962×10^{-3}	28.91	.548	.414	1.3	
Surface Dry Cargo Ship	742-321S	1985	175	.201	35.1	$.804 \times 10^{-3}$	18.62	.459	.492	.9	
Surface Dry Cargo Ship	742-320S NUC	1975	230	---	---	---	---	.595	.405	1.4	
Surface Dry Cargo Ship	742-321S NUC	1985	175	---	---	---	---	.521	.479	1.0	
Hydrofoil Dry Cargo	742-322S	1970	18.5	.168	3.1	3.018×10^{-3}	1.432	.400	.461	.8	
Submarine Tanker	TANKER A	1980	292	---	---	---	---	.479	.522	.9	
Submarine Tanker	TANKER B	1980	144	---	---	---	---	.395	.606	.6	
Submarine Tanker	TANKER C	1980	NA	---	---	---	---	.622	.378	1.6	

P/L GW ^L	W STRU GW	W PP GW	W FU GW	W PP + W FU GW	W PP + W FU P/L	W PP lb SHP N	P GW SHP N lb	P GW x V CRU SHP N ST - KNOT	P L x V CRU SHP N ST - KNOT	P/L x V CRU WORK EQUIV. INPUT
1.192	.199	.038	3.25 x 10 ⁻²	7.06 x 10 ⁻²	.114	176.5	.215 x 10 ⁻³	2.613 x 10 ⁻²	4.205 x 10 ⁻²	33.00
1.706	.199	.042	2.83 x 10 ⁻²	7.07 x 10 ⁻²	.116	263.0	.161 x 10 ⁻³	2.300 x 10 ⁻²	3.757 x 10 ⁻²	37.30
1.870	.184	.036	2.78 x 10 ⁻²	6.32 x 10 ⁻²	.098	197.9	.179 x 10 ⁻³	2.315 x 10 ⁻²	3.586 x 10 ⁻²	40.00
2.269	.166	.027	1.82 x 10 ⁻²	4.48 x 10 ⁻²	.066	290.0	.092 x 10 ⁻³	1.750 x 10 ⁻²	2.566 x 10 ⁻²	64.90
1.689	.187	.039	3.28 x 10 ⁻²	7.16 x 10 ⁻²	.113	155.3	.250 x 10 ⁻³	3.023 x 10 ⁻²	4.782 x 10 ⁻²	33.25
1.434	.215	.048	3.78 x 10 ⁻²	8.54 x 10 ⁻²	.151	128.5	.370 x 10 ⁻³	3.650 x 10 ⁻²	6.437 x 10 ⁻²	25.90
.995	NA	NA	3.65 x 10 ⁻²	NA	NA	NA	.274 x 10 ⁻³	3.042 x 10 ⁻²	6.331 x 10 ⁻²	22.75
1.428	.208	.046	3.64 x 10 ⁻²	8.20 x 10 ⁻²	.145	130.2	.350 x 10 ⁻³	3.420 x 10 ⁻²	6.023 x 10 ⁻²	27.05
.818	NA	NA	4.08 x 10 ⁻²	NA	NA	NA	.360 x 10 ⁻³	3.600 x 10 ⁻²	8.340 x 10 ⁻²	18.38
2.152	.175	.021	2.16 x 10 ⁻²	4.27 x 10 ⁻²	.080	171.9	.123 x 10 ⁻³	1.700 x 10 ⁻²	2.366 x 10 ⁻²	57.70
2.279	.169	.021	2.07 x 10 ⁻²	4.13 x 10 ⁻²	.055	114.2	.180 x 10 ⁻³	1.997 x 10 ⁻²	2.662 x 10 ⁻²	62.70
2.227	NA	.015	1.49 x 10 ⁻²	2.98 x 10 ⁻²	.040	117.2	.127 x 10 ⁻³	1.431 x 10 ⁻²	1.903 x 10 ⁻²	87.80
1.325	.232	.058	3.79 x 10 ⁻²	9.54 x 10 ⁻²	.174	129.0	.446 x 10 ⁻³	3.800 x 10 ⁻²	6.930 x 10 ⁻²	25.00
.834	.320	.071	4.93 x 10 ⁻²	12.04 x 10 ⁻²	.262	108.6	.654 x 10 ⁻³	5.240 x 10 ⁻²	11.406 x 10 ⁻²	16.12
1.471	.232	.058	-----	-----	-----	128.8	.446 x 10 ⁻³	3.800 x 10 ⁻²	6.382 x 10 ⁻²	---
1.466	.320	.071	-----	-----	-----	108.6	.654 x 10 ⁻³	5.240 x 10 ⁻²	10.063 x 10 ⁻²	---
.468	.279	.100	13.96 x 10 ⁻²	23.96 x 10 ⁻²	.599	9.8	10.20 x 10 ⁻³	51.00 x 10 ⁻²	127.50 x 10 ⁻²	1.24
.917	NA	NA	-----	NA	NA	NA	.293 x 10 ⁻³	2.930 x 10 ⁻²	6.116 x 10 ⁻²	---
.452	NA	NA	-----	NA	NA	NA	.960 x 10 ⁻³	5.134 x 10 ⁻²	13.011 x 10 ⁻²	---
1.448	.137	.093	-----	-----	-----	252.0	.371 x 10 ⁻³	3.367 x 10 ⁻²	5.411 x 10 ⁻²	---

2

It will be noted that several of the parameters measure the same kind of efficiency in different terms. Recognizing that not all data is available for all vehicles, the complete group is presented for the sake of making easier future comparison studies.

The P/L-R curve for each study vehicle is shown in Section 3.2.6. Because the design range is different for nearly all the vehicles, the parameters involving W_{TU} must be interpreted with care. The fuel fraction is an effective measure of propulsion efficiency between vehicles only when defined at the same range and, particularly for aircraft, when weight and drag are consistent.

The design range, i.e., break point in the P/L-R curve, is taken as the most reasonable point to define the study aircraft's range dependent characteristics. However, there is a certain inconsistency which is impossible to avoid in making these comparisons between aircraft designed for different missions. The two significant items affecting these fractions are:

- (1) The amount of growth left in the structure may be different between aircraft. This is reflected in the shape of the P/L-R curve (Fig. 1). It is particularly apparent when comparing the final model in a series with the first release aircraft. Recognizing this fact is important to the interpretation of weight fraction data.




Fig. 1 Payload Growth for Typical Aircraft P/L~R Curve

- (2) The takeoff field length capability of the respective aircraft may be




Fig. 2 Airplane Model Growth Characteristics

greatly different. This implies a difference in wing loading and power or thrust loading. These items have an effect on fuel consumption and hence on the weight fractions. Understanding of this point is also necessary.

Range performance calculations for marine vehicles are commonly given a wider tolerance than those for aircraft. This is typified by the several power ratings given marine engines which vary according to the RPM chosen. In this study, marine power plants are defined in terms of the installed normal shaft horsepower. This rating is understood to contain a 25 percent power margin over the shaft horsepower required to drive the vessel at its design speed with zero wind, clean bottom, and calm sea. The power margin is to permit the maintenance of sustained sea speed under typical operating conditions with moderate fouling of the hull. Fuel consumption data available for cargo ship operation are quoted in barrels/day. This somewhat coarse measure is consistent with the average power and speed figures commonly used.

4000 N. Mi. was chosen as the distance for defining all range dependent ship parameters. This distance is close to the voyage length for many trade routes. A more rigorous definition of this range would involve consideration of specific missions and is beyond the scope of this study. Inspection of the Payload-Range curves of Section 3.2.6 shows that the slope is much flatter for ships than for aircraft. This means that the rate of change of fuel fraction with range is smaller for ships than for aircraft and substantiates the reasonableness of a single range for all ships.

The hydrofoil craft range dependent parameters are defined at 1000 N. Mi. because of its more limited capability.

3.2 PLOTTED DATA

The data are arranged by Groups I through V as discussed in Section 3.1. Each Group is organized in the order shown for the parameters. The following symbols are used on the plots:

- Reciprocating Engine Airplane
- ⊙ Turboprop Airplane
- Turbofan or Turbojet Airplane
- Non-airplane Aircraft
- ▲ Dry Cargo Surface Ship
- △ Tanker Surface Ship
- Tanker Submarine
- Hydrofoil Ship




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22

3.2.2 DATA PLOTTED vs YEAR ENTER SERVICE

.....






Fig. 23

PL 14




Fig. 24




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 39




Fig. 41



3.2.3 DATA PLOTTED vs P/L x V cru

.....





Fig. 42



(P/L) x VCRU - 1000 SHORT TON - KNOTS

Fig. 43





Fig. 44



(P/L) x VCRU - 1000 SHORT TON - KNOTS

Fig. 45





Fig. 47



(P/L) x VCRU - 1000 SHORT TON - KNCS

Fig. 48




Fig. 49




Fig. 50




Fig. 51




Fig. 54

3.2.4 DATA PLOTTED vs $\frac{P}{L} \times R$

1 2 3 4 5 6 7 8 9 10 11 12




Fig. 56




Fig. 57




Fig. 58






Fig. 59



(P/L) x R - 1000 SHORT TON - N.M.I.

Fig. 60



(P/L) x R - 1000 SHORT TON - N.M.I.

Fig. 61






Fig. 62




(P/L) x R 1000 SHORT TON - N.MI.

Fig. 64




(P/L) x R - 1000 SHORT TON - N.MI.

Fig. 65



(P/L) x R - 1000 SHORT TON - N.M.I.

Fig. 66



(P/L) x R - 1000 SHORT TON - N.M.I.

Fig. 67




Fig. 68




Fig. 69 (P/L) x R - 1000 SHORT TON - N.M.I.







Fig. 70



1940 1945 1950 1955 1960 1965 1970 1975 1980 1985
YEAR INTER SERVICE

Fig. 71

3.2.6 PAYLOAD-RANGE CURVES FOR STUDY VEHICLES

As discussed in Section 3.1 the vehicle's payload-range curve is a significant measure of its performance capability. Curves for the basic vehicles of this study are presented in Figs. 72 and 73. Curves for vehicles which are not included in the cost section are omitted.

The following ground rules are implicit in the curves:

- (1) For aircraft
 - a) Standard day, no wind.
 - b) Reserve fuel equal to 10 percent of initial fuel on board.
 - c) Cruise altitude and speed are defined for maximum payload and maximum range. For the current military airplanes these values were taken from the applicable mission defined in the T. O. (Technical Order) or SAC (Standard Aircraft Characteristics) chart. For current commercial airplanes and the future airplanes it is maximum range cruise speed and altitude. (Except 742-302 and -303 LOBOYS are at sea level at speed for 97 percent maximum

mile per pound.)

- d) The fuel consumption is the actual predicted value. Degradation for compressor bleed and accessory drive is included. Conservatism, such as the 5 percent service tolerance of MIL-C-5011A, is not included.
 - e) Fuel consumption is included for
 - i) ground maneuver and takeoff
 - ii) climb
 - iii) cruise
 - iv) descentExcept for future aircraft, no range credit or fuel penalty for descent is included. At the long ranges of these aircraft this is a very minor item.
 - f) All aircraft weights and performance are based on 2.5 limit maneuver load factor except LOBOY which is 2.0.
- (2) For snips
- a) Average sea conditions and average sustained sea speed at normal power.
 - b) Reserve fuel equal to 25 percent of initial fuel on board, except hydrofoil craft 10 percent of initial fuel.
 - c) Miscellaneous weight on board including




Fig. 72 Study Aircraft Payload/Range Characteristics




Fig. 73 Study Ship Payload/Range Characteristics

- provisions, stores, crew and effects equal to 1/2 percent of total dead weight and dunnage equal to 1 percent of cargo dead weight.
- d) Water on board equal to total capacity.
 - e) Fuel consumption is the actual quoted average at normal power for each current ship. Fuel consumption for future ships includes a 10 percent conservatism.
 - f) Fuel consumption is based on time at sea. Port fuel allowance is not included.

3.2.7 MARINE INNOVATION DATA

Several proposals have been discussed in the recent literature as offering the possibility of improved performance in marine transport. Fig. 74 taken from Ref. 26 summarizes data on four of these configurations. Successful development of these possibilities is necessarily dependent on a significant amount of research being completed and particularly on development of light, compact, high power propulsion machinery.

potential in speed and L/D may be expected from the deep running submarine. This speed potential is purchased at the expense of the most difficulty in practical design and operation.

Inspection of Fig. 74 shows that the largest

- A. SEMI-SUBMERGED SHALLOW RUNNING VESSEL WITH LARGE STRUT EXTENDING ABOVE SURFACE OF THE SEA, 196 FEET LONG.
- B. SEMI-SUBMERGED HULL WITH MINIMUM SIZED STRUT, 186 FEET LONG.
- C. SURFACE VESSEL WITH LARGE BULBS AT EACH END, 258 FEET LONG.
- D. ATOMIC SUBMARINE, DEEP RUNNING, 210 FEET LONG.

NOTE: 60 PERCENT PROPULSION COEFFICIENT ASSUMED




Fig. 74 2000 Ton Displacement Unusual Ship Forms

4.0 OPERATIONAL PARAMETER DATA

4.1 INTRODUCTION

The purpose of this section is to examine the effects of operational influences on transport aircraft and transport ships. Reliability, utilization, useful life, and environment are discussed as they apply to these transport vehicles. Specific data are presented where possible, although the data are necessarily more limited than that of Sections 3 and 5. The primary interest of this study is in cargo rather than passenger transport. Operational data for some passenger aircraft are presented where there is a lack of cargo data and where there is a similarity between passenger and cargo operations.

After comparing general influences of reliability, utilization, useful life, and environment on these aircraft and ships, two representative missions are exercised. The first task is a high density cargo movement to the Far East over a one year period (an example of a weight limited lift). The second is the deployment of an armored

division to the Far East in thirty days (a space-limited example). These missions provide a basis for comparing the capabilities and costs for the various transport vehicles considered in Section 5.

4.2 RELIABILITY

4.2.1 GENERAL

Reliability is defined as the quality of performing as expected, when expected, during the vehicle's specified useful life. In all vehicles, the total reliability is a function of the abilities of all the components, subsystems, and systems of the vehicle.

The reliability of a given mode of transportation may be defined in terms of delays in scheduled operation, in the number and frequency of equipment failures, or in the probability of mission completion. The method used is dependent on the type of equipment involved and the type of information desired.

The following paragraphs discuss general methods by which reliability is affected or improved.

RELIABILITY BY DESIGN

Reliability is dependent on detail design, choice of materials, and specification of fabrication techniques. The reliable performance of sub-systems and systems is dependent on careful selection of components, degree of redundancy, provision of parallel functions, and/or derating of items. Both the vehicle manufacturer and the operator pay for these features, and, thus, reliability is interrelated with safety and economics.

RELIABILITY BY MANUFACTURE

Manufacturing quality control, like reliability, is a matter of statistical analysis. Recognizing that quality control alone cannot prevent all design and manufacturing component failure from appearing in the finished vehicle, manufacturers normally extend a warranty against defective parts and/or labor for a specified length of time or service. These failures are represented graphically by the left hand portion of the curve in Fig. 75.




Fig. 75 Typical Failure Rate Curve

RELIABILITY BY SCHEDULE ADJUSTMENT

With all vehicles, schedule reliability is of considerable significance. This is defined as the ratio of the total trips which are initiated within a specified time of a scheduled departure, divided by the total number of trips planned.

Schedule reliability is dependent on the total number of vehicles available as compared to the number of vehicles scheduled. Where necessary and available, spare vehicles may be used to replace those which are scheduled to depart, but which are out of service because of component failure.

Schedule reliability of vehicles may be drastic-

ally affected by maintainability. Maintainability is defined as the condition describing the relative ease and speed with which deficiencies can be corrected once they are discovered. Factors which influence maintainability are the degree of simplicity or complexity of the equipment involved, its accessibility, the ease with which trouble shooting can be accomplished, and the facility of replacement or repair once the trouble has been isolated. Also affecting schedule reliability are trip duration and turn-around time when considering vehicle substitution or route overlapping techniques.

4.2.2 TRANSPORT AIRCRAFT RELIABILITY

4.2.2.1 GENERAL

In the case of transport airplanes, the most widely used reliability is schedule reliability, or probability of adherence to a predetermined schedule of operation. It is chosen for discussion here.

Factors which affect schedule reliability may be classed as controllable and uncontrollable. The major uncontrollable factor is weather. The delay, cancellation or rerouting of flights

due to weather conditions has customarily not been included in schedule delay studies. However, the advent of equipment and techniques permitting all-weather airplane operation will, in the future, cause greater consideration of weather as a semi-controllable schedule delay cause. Controllable factors which affect schedule reliability include:

- Fleet Size: One method used in commercial fleets to lessen the effects of flight delays and cancellations due to mechanical failures is airplane substitution. Typically 3 to 4 percent of all commercial flights are operated after substitution of an airplane to avoid departure delays.

Economic considerations such as the total number of airplanes in the fleet and the potential revenue loss due to delay dictate the number of "spare" airplanes made available for substitution.

- Flight Duration: The highest equipment failure incidence generally occurs during starting, warmup or some initial phase

of operation appropriate for the equipment involved. It follows that the greater the number of flights conducted per airplane, the greater will be the probability of a delay due to mechanical failure. An airplane operated on a short flight basis will be more likely to experience schedule delays than an airplane assigned to long flights within a given time span.

- Turn-around Time: Turn-around time is defined as the amount of time necessary to airplane passengers, baggage and/or cargo, clean and service the airplane, and reload for new or continued mission. In commercial service, there is normally no provision in this activity to perform any but minor maintenance. Schedule delays may, therefore, be reduced through extension of turn-around time, but this, too, is controlled by economic factors.

- Route Scheduling: Equally important to ensure schedule reliability is flight schedule overlapping to provide standby airplanes in the event malfunctioning air-

planes cannot be repaired in the scheduled time available. All commercial airlines attempt to use the overlapping schedule technique. Where overlapping cannot be provided, a schedule will be particularly vulnerable to delay.

4.2.2.2 RELIABILITY DATA

The data in Table 7 was compiled from operational records of a commercial airline using turbojet, turboprop, turboprop, and reciprocating engine powered transport airplanes. The records covered a period of 27 months (September 1961 through November 1963). Table 7 data does not deal in specific equipment item failures but rather in equipment items which were removed before the scheduled overhaul time. These removals could be the result of erroneous trouble diagnosis, for convenience of maintenance, or because of malfunction.

For purposes of comparison, the information in Table 8 was tabulated from data on regularly scheduled flights by Military Air Transport Service (MATS). It encompasses 12 months of operation (January 1962 through January 1963)

Table 7 Failure and Schedule Data For Transport Airplanes

SYSTEM/EQUIPMENT	TURBOJET AND TURBOFAN TRANSPORTS				TURBOPROP TRANSPORTS			
	Number Unscheduled Removals	Percent of Total Removals	Schedule Interrupt. Caused	Percent of Total Interrupt.	Number Unscheduled Removals	Percent of Total Removals	Schedule Interrupt. Caused	Percent of Total Interrupt.
1. Air Conditioning	1459	6.9	92	6.4	4316	10.3	245	
2. Auto Pilot	757	3.6	23	1.6	1395	3.3	16	
3. Communications	2032	9.7	19	1.3	2672	6.4	65	
4. Electrical	1493	7.1	64	4.4	1530	3.6	326	
5. Fire Protection	340	1.6	44	3.1	283	0.7	42	
6. Flight Controls	578	2.7	79	5.4	731	1.8	146	
7. Fuel	412	2.0	40	2.8	1026	2.5	124	
8. Hydraulic	511	2.4	88	6.1	1744	4.2	220	
9. Ice/Rain Protection	146	.7	15	1.1	930	2.2	51	
10. Instruments	192	.9	-	-	352	0.8	6	
11. Landing Gear	883	4.2	251	17.4	648	1.6	567	
12. Lights	600	2.9	29	2.0	994	2.4	137	
13. Navigation	3719	17.7	115	8.0	4839	11.6	369	
14. Oxygen	1542	7.3	30	2.1	1901	4.6	41	
15. Structures	508	2.4	42	2.9	1315	3.1	224	
16. Cowling	193	.9	6	.4	400	1.0	8	
17. Engines	731	3.5	68	4.7	447	1.1	282	
18. Engine Controls	9	.1	4	.3	42	-	-	
19. Engine Fuel and Controls	603	2.9	59	4.1	1645	3.8	137	
20. Engine Indicating	1139	5.4	18	1.2	3042	7.3	132	
21. Ignition	260	1.2	16	1.1	52	0.1	25	
22. Exhaust	1102	5.2	85	5.9	1238	3.0	12	
23. Oil	516	2.5	68	4.7	2035	4.9	132	
24. Starting	639	3.0	107	7.4	2056	4.9	140	
25. Air	649	3.1	80	5.6	511	1.2	52	
26. Propellers	-	-	-	-	5661	13.6	597	
TOTALS	21,013	100.0	1,442	100.0	41,805	100.0	4044	
TOTAL MISSIONS			42,253				141,558	
TOTAL FLIGHT HOURS			36,760				140,172	
FLIGHT HOURS/MISSION			Avg. .87 hrs with a Min. of .50 hrs. and Max. of 1.30 hrs. in the selected missions				Avg. .99 hrs with a Min. of .90 hrs. and Max. of 1.10 hrs. in the selected missions	

TURBOFAN			TURBOPROP				PISTON ENGINE						
MORTS			TRANSPORTS				TRANSPORTS						
Schedule Interrupt. Caused	Percent of Total Interrupt.	Number Unsched. Removals	Percent of Total Removals	Schedule Interrupt. Caused	Percent of Total Interrupt.	Number Unsched. Removals	Percent of Total Removals	Schedule Interrupt. Caused	Percent of Total Interrupt.	Number Unsched. Removals	Percent of Total Removals	Schedule Interrupt. Caused	Percent of Total Interrupt.
92	6.4	4316	10.3	245	6.0	7402	8.6	324	3.5				
23	1.6	1395	3.3	16	0.4	INCOMPLETE INFORMATION							
19	1.3	2672	6.4	65	1.6	5510	6.4	302	3.3				
64	4.4	1530	3.6	326	8.1	4226	4.9	601	6.5				
44	3.1	283	0.7	41	1.0	1527	1.8	427	4.5				
79	5.4	731	1.8	146	3.6	983	1.2	104	1.1				
40	2.8	1026	2.5	124	3.1	3061	3.6	232	2.5				
88	6.1	1744	4.2	220	5.4	1974	2.3	285	3.1				
15	1.1	930	2.2	51	1.3	1671	1.9	95	1.0				
-	-	352	0.8	6	0.1	INCOMPLETE INFORMATION							
251	17.4	648	1.6	567	14.0	4285	5.0	1511	16.3				
29	2.0	994	2.4	137	3.4	1049	1.2	345	3.7				
115	8.0	4839	11.6	369	9.1	7010	8.2	290	3.1				
30	2.1	1901	3.6	41	1.0	2724	3.2	31	0.3				
42	2.9	1315	3.1	224	5.5	1440	1.7	302	3.3				
6	.4	400	1.0	8	0.2	2533	2.9	127	1.4				
68	4.7	447	1.1	282	5.7	4904	5.7	1397	15.4				
4	.3	42	-	-	-	1132	1.3	81	0.9				
59	4.1	1645	3.8	137	3.4	5272	6.1	231	2.5				
18	1.2	3042	7.3	132	3.3	6389	7.4	133	1.4				
16	1.1	52	0.1	25	0.6	15347	17.9	1227	13.2				
85	5.9	1238	3.0	12	0.3	2809	3.3	170	1.8				
68	4.7	2035	4.9	132	3.3	1978	2.3	234	2.5				
107	7.4	2056	4.9	140	3.5	299	0.3	202	2.2				
80	5.6	511	1.2	52	1.3	-	-	-	-				
-	-	5661	13.6	597	14.8	2392	2.8	621	6.7				
1,442	100.0	41,805	100.0	4044	100.0	85,917	100.0	9273	100.0				
33		141,558		309,950									
20		140,172		409,134									
Avg. .99 hrs with a Min. of .90 hrs. and a Max. of 1.32 hrs with a Min. of .58 hrs. and a Max. of 1.52 hrs. in the selected missions													

Table 8 Schedule Reliability Mats Operation

	TURBOJET TURBOFAN TRANSPORTS	TURBOPROP TRANSPORTS	PISTON ENGINE TRANSPORTS		TURBOJET & TURBOFAN TRANSPORTS
	C-135B	C-133	C-124	C-118	FUTURES
DEPARTURES INTERRUPTED (MAINTENANCE)	6.70%	10.35%	7.51%	5.70%	3%
DEPARTURES INTERRUPTED (ALL CAUSES)	22.10%	28.19%	20.98%	12.34%	10%
PROBABILITY OF ON-SCHEDULE DEPARTURE (MECHANICAL DELAYS ONLY)	93.30%	89.65%	92.49%	94.30%	97%
PROBABILITY OF ON-SCHEDULE DEPARTURE (ALL CAUSE DELAYS)	77.90%	71.81%	79.07%	87.66%	90%
ENGINE PREMATURE REMOVAL RATE PER 1000 ENGINE HRS.	0.642	2.9	0.9	0.8	0.2
FLIGHT HOURS	25,280	32,899	136,696	60,082	
NO. DEPARTURES	3,988	4,814	17,164	11,691	




Fig. 76 Experience Factor In Attaining Schedule Reliability

for which reports were available on similar types of aircraft.

The figures shown in the right hand column are projections for possible future turbojet/turbofan MATS transports. These figures were derived from experience with current commercial transports.

Maintenance facilities and personnel experience will affect the schedule reliability. Characteristically, this is shown in the early operation on any new airplane. Fig. 76 shows that it takes approximately one to two years for operator personnel to become familiar with the airplane, and to learn maintenance of its systems. The data for plotting these curves were derived from operation records of all commercial airlines operating Boeing 707 jet airplanes during a selected 24 month period. The data are based on the ground rule that a schedule delay is 15 minutes or more after schedule takeoff time. The 15 minute period is the same standard for both military and commercial operations. The curves show the difference in the rate that potential schedule reliability will be achieved with and without

prior experience with jet transport airplanes.

Fig. 77 shows the comparative operational reliability of reciprocating engine, turboprop, and turbojet/fan powered airplanes, respectively. These data were taken from the domestic operations of a typical commercial trunk airline operating the above types of airplanes during September, October, and November of 1963.

Using the delays of 15 minutes and over for a one hour flight, as shown on the left hand side of Fig. 77, the operational reliability is 98.15 percent for reciprocating engine airplanes, 98.15 percent for turboprop airplanes and 97.9 percent for turbojet/fan airplanes.




Fig. 77 Comparative Operational Reliability

The above values do not reflect the turbojet/fan airplane work rate capability. Since these airplanes are much larger and faster, the work rate is an important basis for comparison. On the basis of 10,000-ton nautical miles of work for a one hour flight length, the comparable schedule reliability would be 94.5 percent for the reciprocating engine aircraft, 96.1 percent for the turboprop airplanes and 97.5 percent for the turbojet/fan aircraft.

The right hand portion of Fig. 77 shows how the number of delays varies with flight distance and productivity.

4.2.3 TRANSPORT SHIPS

Reliability is viewed and handled by ship operators in a somewhat different fashion from that of aircraft manufacturers and operators. The overall reliability for a ship is kept very high by the carrying of spare parts and maintenance

personnel. Individual component failure rates are probably higher than those for equivalent aircraft parts, although proof of this statement is impossible due to the lack of adequate data.

For this study, the search for part failure rates and reliability data included contacts with commercial and military ship operators and with BuShips. It was determined that operators do not maintain records of part failures in sufficient detail to allow any satisfactory statistical analysis. The point was made that the cost of maintaining such records is not warranted by the potential savings involved. BuShips personnel advised that statistical analyses on large numbers of fleet ship components have been started. However, the cataloging system for these data is still incomplete. In addition, the first interest in these reliability analyses is for electronic systems which are not common to cargo ships. Because of these facts and the obviously large effort involved in gathering BuShips data, it was decided that such an investigation was not warranted in this study.

The nature of transport ship operation is such

that it permits a wide latitude of methods and techniques for assuring reliable operation. Some of these factors, which tend to promote overall ship reliability, are discussed in the following paragraphs.

- **Simplicity of Design:** Compared to aircraft, the systems required for proper ship operation are relatively uncomplicated. This simplicity of design and function helps to ensure the reliability of ship operation by decreasing the number of potential failures, and increasing the ease with which these failures can be corrected if and when they occur.
- **Redundancy of Machinery:** Because a lower power penalty is paid for weight on a ship than in other types of transport vehicles, reserve components and systems are both practical and desirable.
- **Interconnection of Function:** The similarity of machinery in various systems, and the parallel nature of the systems themselves, permit installation so that they

can perform for one another in the event of need or emergency.

- Derating: A common technique for gaining additional usefulness and reliability from an item is to place it into a service environment that is less severe than that for which it was designed. In this way, the item will normally perform reliably for a period far in excess of its rated life, and will be capable of safely assuming higher loads should the need arise.

- Frequency of Servicing and Maintenance: Skilled repair technicians are part of the ship's crew. These personnel are assigned to perform varying degrees of preventive maintenance on a continuing basis.

- Stability of Operation: The nature of ship operation lends itself to stabilized operation over extended periods of time. Since many premature failures may be attributed to stresses incurred in start up and shut down, normal ship operation will tend to minimize these failures.

4.3 UTILIZATION

4.3.1 GENERAL

Utilization as applied to a transport vehicle may be construed to have two meanings - operational utilization and loading utilization. Operational utilization is perhaps the more common, and is defined as being the ratio of the amount of time a vehicle is employed in productive use during a given period, compared to the total time in that period. Loading utilization, or load factor, is the ratio of the amount of cargo which is carried compared to the maximum quantity which can be carried.

The degree of utilization of transport vehicles depends upon the characteristics of the vehicle and the type of service it is required to perform. Characteristics influencing utilization include vehicle dimensions, performance, maintainability, and ease of servicing. Types of usage are divided into the broad classifications of military and commercial. While these factors tend to influence both operational and cargo utilization, for purposes of this discussion it is postulated that vehicle characteristics are more

pertinent to cargo loading utilization, and that the type of service is more pertinent to operational utilization.

4.3.2 OPERATIONAL UTILIZATION

To be utilized operationally a transport vehicle must be capable of departing when called upon with sufficient equipment and supplies to complete its assigned mission. Because of the particular situation, a vehicle may not be able to fulfill this requirement, and the operational utilization will thereby be less than its potential. Factors which affect both the potential utilization, and that which is realized, will be examined.

4.3.2.1 TRANSPORT AIRCRAFT

The two general classifications of transport aircraft service to be considered are military-oriented and commercial-oriented. In military-oriented transport operations, the objective is to operate an aircraft fleet, sufficient in size to meet a specified minimum wartime transport requirement, in the most efficient and economical way; at the same time maintaining the fleet equipment and personnel in a state of readiness.

For commercial operations, the purpose is to operate the minimum number of aircraft required for a given route structure, so as to produce the highest possible revenue. These two basically different objectives have significant effects on utilization figures attained by operators.

Both types of operation are subject to conditions beyond their control which tend to prevent these objectives from being realized. The following sections discuss these factors.

4.3.2.1.1 MILITARY OPERATION

The operation of the Military Air Transport Service (MATC) is used here as an example of military transport aircraft. As a result of their wide experience with transport aircraft, MATC has selected as their annual planning factor a peacetime utilization of 5 hours per day, and 8 hours per day, wartime. The latter factor was used in computing the aircraft fleet size in Sections 4.6.2.1 and 4.6.3.1, and the former for costing purposes in Section 5.

Higher utilizations have been attained and sustained for short periods. As an example Fig. 79




Fig. 78 1948 Berlin Airlift Cumulative Utilization of C-54 Aircraft

shows utilization rates attained by C-54 aircraft during 3 months of the Berlin Airlift in 1948. These side-loading aircraft were called upon to haul unsuitable cargos on short hops in unfavorable weather. Despite these handicaps, the C-54 was able to sustain an approximate 9 hours per day utilization for two months. The first two months of the period show the effects of a surge to high utilization.

Factors which influence operational utilization are listed in Table 9. The most significant factors are perhaps the mission and the maintenance policies.

The size of a military airlift fleet is based on a minimum wartime transport requirement. This fleet is operated in normal peacetime missions, which include a significant amount of training.

Table 9 Operational Utilization Factors

MILITARY AIRCRAFT

1. Missions
2. Routes and Distances
3. Traffic Characteristics
4. Traffic Density
5. Maintenance Facilities
6. Personnel Availability and Training
7. Airplane Characteristics
8. Maintenance Policies
9. Weather
10. Terminal Facilities

The allocation of aircraft to the missions will determine, to a large extent, their operational utilization. Some aircraft, due to scheduling problems, might be inadequate for their assignment, while others would be used only to provide minimum crew proficiency (for which their transport capability would not be used).

OPERATIONAL UTILIZATION METHOD

The following method is an approach to estimating the potential utilization available for short term strategic deployments, based on flight time. The example uses empirical data pertaining to a typical military jet transport. The method may be applied to turboprop and reciprocating engines

powered aircraft by applying appropriate experience factors.

This method shows that deployments with long flight legs may have a high utilization while for deployments with short flight lengths, a much lower utilization may be realized.

DEFINITION OF TERMS

Operationally Ready (Ops Ready): A military aircraft is considered Ops Ready when it is capable of flight and has sufficient equipment, supplies and personnel to carry out its assigned mission.

"Other": Non-flying Ops Ready time such as servicing, minor maintenance, testing, loading, taxiing, etc., is not included in Ops Ready times.

Not Operationally Ready - Supply (NORS): This includes all downtime for supply delays.

Not Operationally Ready - Scheduled Maintenance: Included in this category are periodic (PE), hourly post flight (HPO), special and depot inspections and major modifications. The method

presupposes that these inspections are performed on a flight hour basis rather than on calendar time.

Not Operationally Ready-Time Compliance Technical Order (NOR-TCTO): The time spent in conforming to TCTO's is the only time included in this category.

Downtime: This is the sum of all the applicable elements listed above.

Utilization: For purposes of this method, utilization is defined as the number of total flight hours divided by total aircraft-days of the period being considered.

Average Flight Length: This term is computed by dividing the total flight hours, as above, by the number of sorties, departures, or landings, made. If landings are used, only those involving a full stop and shutdown of engines are to be counted.

MAXIMUM POTENTIAL SUSTAINED UTILIZATION FOR ONE FLIGHT LENGTH

Fig. 79 was constructed using time allocation




Fig. 79 Ops Ready and Nor Elements Typical Jet Transport

factors for a typical military jet transport, shown below. Straight lines through the data points represent an average flight length of 5.2 hours, since all elements except NOR-TCO increase proportionally with utilization. TCOT downtime remains constant since it is a function of aircraft design.

Table 10. Daily Time Allocation Typical Military Jet Transports

(BASED ON AN APPROXIMATELY
2 YEARS OF OPERATION)

	FACTOR PERCENT	DAILY TIME HOURS
NOR-TCO	0.8	0.19
NOR-Sched Maint	6.1	1.46
NOR-Supply	4.2	1.01
NOR-Unsched Maint	12.9	3.10
Operationally Ready	<u>76.0</u>	<u>18.24</u>
TOTALS	100.0	24.00
Operationally Ready		
"Other" Time:		
Loading, Awaiting Maint.,		
Fueling, Inspections,		2.00
Unloading, Etc. *		<u>.33</u>
Taxi Time		2.33
TOTAL		5.2
Average Flight Length		4.46
Average Utilization		

* Varies with aircraft, mission, facilities, etc.

Considering also the time required for "other" non-flying Ops Ready elements, it is assumed that total elapsed time for these functions would be, typically, 2.33 hours. On the basis that half of these functions, except taxiing, could be accomplished simultaneously, the total "other" downtime per flight would be 1.33 hours. This time is plotted at 5.2 hours utilization, since it represents one flight of that duration. Since "other" time also varies with the number of flights, a line drawn through the average utilization shows this relationship. Different circumstances, such as in loading, fueling, maintenance techniques, ground support, etc., could cause this item to vary.

Since this plot represents an aircraft day, if an aircraft flew 5 hours in a day its utilization would be 5 hours/day. This is shown by a line drawn at a 45°-angle from the origin. The intersection of this line with the "other" downtime line represents the maximum potential sustained utilization; in this example, approximately 9.4 hours per aircraft day, at an average flight length of 5.2 hours.

MAXIMUM POTENTIAL UTILIZATION FOR VARYING FLIGHT LENGTHS

To determine this utilization for varying flight lengths, the factors used above may be adjusted based on the following assumptions:

NOR-TCTO: Assumed to remain constant, as above.

NOR-Scheduled Maintenance: Varies with flight length, since it is based on flight hours.

NOR-Supply and Unscheduled Maintenance: Assumed to vary proportionally with the number of failures per flight. For a typical jet transport, the curve labelled "Airplane" in Fig. 80 is used.

Other: Assumed to remain constant.

Fig. 81 is a plot of cumulative downtime per flight per element versus flight length, using the factors of the preceding example and the above assumptions. This information permits Fig. 81b to be drawn by superimposing a 45° line, representing flight time per flight, on the downtime relationships of Fig. 81a.




Fig. 80 Cumulative Failure Rate For Various Mission Times

Fig. 81c is constructed by drawing diagonal lines in Fig. 81b which extend from the origin through the intersection of downtime per flight line to the desired flight time. The intersection of the flight time per flight line and these diagonal lines permits average utilization to be read on the right hand scale. These readings are plotted versus flight length in Fig. 81c to show maximum average potential utilization vs. flight length. For example, if a 5 hour flight length is selected, a proportioning line drawn from the origin through the downtime per flight line for a 5 hour flight intersecting the flight time per flight line, permits reading a maximum potential sustained utilization of 10 hours/day on the right hand scale of Fig. 81b. Fig. 81c allows this to be read directly. Fig. 81a is included to permit, if required, the elimination of certain downtime elements such as TCTO and NOR-Scheduled Maintenance should emergency conditions require. If such were the case, through use of this method a maximum potential sustained utilization of 11.9 hours per day at 5 hours flight length is theoretically possible.

The data used in Figs. 79 through 81 were based




Fig. 81 Method of Developing Maximum Average Utilization Curves

on peacetime operations. Fig. 82 shows how emergency or wartime planning can be used to adjust the elements of downtime mentioned above, and in addition, to account for such contingencies as weather, user policy, operations, etc., which were not included in Fig. 81. This is believed to be a reasonable assessment of the potential available to the military. The dotted line in Fig. 82 represents a composite of airline data, including all delays, for three years of operation.

4.3.2.1.2 COMMERCIAL OPERATION

Higher utilization rates are attained in commercial airline service than in military service. The basic reasons for this can be attributed to their different types of routes, cargos, policies, and to the lower maintenance skill levels available in the military organization.

Commercial utilization of passenger aircraft is most significantly influenced by route structure and passenger convenience scheduling. Other factors which apply are listed in Table 11.

The highest potential utilization is attained




Fig. 82 Projected From Jet Transport Maximum Sustained Utilization

when the route structure and the passenger density allow the airplane to fly fully loaded during the normal traveling period between 7 A. M. and 12 Midnight. Maintenance work is then scheduled for the remaining 7 hours, insofar as is possible. In general, airline maintenance is accomplished on a continuous basis, using if necessary, three working shifts - 24 hours per day - until the work is completed.

The revenue utilization for some twelve airlines flying various types of aircraft during a five

Table 11 Operational Utilization Factors - Commercial Aircraft

1. Traffic Density
2. Routes and Distances
3. Schedule Protection
4. Connecting Flight Requirements
5. Departure/Arrival Times
6. Maintenance Facilities
7. Personnel Availability
8. Airplane Characteristics
9. Maintenance Policies
10. Weather
11. Terminal Facilities

exceeding passenger utilization, since they, presumably, can be scheduled on a 24 hour a day basis. For cargo operations, therefore, maintenance becomes a more limiting factor than for passenger operations.

4.3.2.2 TRANSPORT SHIPS

The operational utilization of a ship is divided into two general categories: ship design and operating characteristics, and situation and circumstance factors.

SHIP DESIGN AND OPERATING CHARACTERISTICS

The ability to obtain high transport ship utilization, from an operational standpoint, depends on the type of vessel and how it is operated in relation to its capabilities. Such vessels may be divided into classifications of cargo, combination, and passenger, depending on the number of passengers carried.

New United States vessels, which are constructed under government subsidy, are designed for the capability to sustain 20 knot speed, for possible use in a military emergency. This high sea speed tends to reduce utilization, by decreasing

year period from 1957-1961 is shown graphically in Fig. 83. Statistics for this plot were obtained from figures published by the Air Transport Association of America. This period was significant to the airline industry in that it marked the transition from reciprocating engine powered aircraft to turbine-powered aircraft, both jet and turboprop. It is believed that the downward trend in reciprocating engine powered aircraft utilization is a result of their being replaced by the turbine craft on the longer routes. This tended to increase the turbine aircraft utilization and decrease the utilization for the piston engine aircraft.

Commercial cargo aircraft have the potential of




Fig. 83 Revenue Utilization - All Domestic Trunks

the amount of time spent at sea in relation to the time spent in port. Port time is the time which a ship spends loading or unloading, undergoing maintenance, awaiting repairs, or awaiting cargo.

Since port time has such an adverse influence on operational utilization, both ship designers and operators are particularly cognizant of factors which affect it. The addition of more hatches, quick-removal hatch covers, faster Burtoning gear, accommodations for containers, and special designs for vehicular loads all tend to increase operational utilization. The effect of speed on productivity of various types of cargo vessels is illustrated in Fig. 84. The space factor (S.F.) is explained in Section 4.3.2.3.

SITUATION AND CIRCUMSTANCE FACTORS

Since a ship is normally producing revenue only while it is at sea, to realize maximum capability port time must be reduced to its practical minimum. For a commercial cargo ship, it may be necessary to strike a compromise between operational utilization and space utilization for reasons of economy.




Fig. 84 Yearly Cargo Delivery Capabilities Of Various Ships For Round Trip Distances

Loading and unloading times are influenced by such factors as dockside cargo handling gear, stevedoring rules, and type(s) of cargo carried.

Repair, maintenance, and reprovisioning are normally accomplished concurrently with load/unload operations. However, insurance underwriters require commercial vessels to undergo a drydocking at approximately one year intervals. These operations require from seven to ten days to complete, during which time scraping, painting, inspection, and major overhaul are performed. For normal ship operation, annual drydocking is the only completely non-operational time. Exceptions do occur as a result of unforeseen or unpredictable events such as accident, weather, or major machinery breakdown.

The type of ports, their number, and distance between them are also of significance in determining operational utilization. The effect of distance between ports is also illustrated in Fig. 84.

4.3.3 LOADING CAPABILITY UTILIZATION

Loading capability utilization of transport

vehicles refers to the effective use of available weight and space. Influential factors include, but are not limited to, cargo characteristics, cargo compartment characteristics, performance of the transport vehicle, facilities, seasons, policies, politics, routes and distances, schedules, availability of vehicles and/or cargo, economics, and safety.

4.3.3.1 TRANSPORT AIRCRAFT

The loading efficiency of transport aircraft is largely a compromise between available cargo and available aircraft space and payload.

4.3.3.1.1 MILITARY OPERATION

Past transport designs have emphasized payload capability, an ineffective criterion for bulky, low density cargo items. As a result, the present day military aircraft have limited capability for carrying such Army equipment. The loading utilization is shown in Table 12 for four current aircraft and four typical military loads.

4.3.3.1.2 COMMERCIAL OPERATION

Passenger Service: Fig. 85 shows revenue pass-

Table 12 Aircraft Loading Efficiency

	AIRBORNE DIVISION	INFANTRY DIVISION	MECHANIZED DIVISION	ARMORED DIVISION
AVERAGE CARGO FLOOR LOADING LBS/SQ FT	73.6	104.5	117.5	140.1
APPROXIMATE PERCENT AIRLIFTABLE BY WEIGHT				
AIRCRAFT TYPE (ALLOWABLE CABIN LOAD, LBS)				
C-124 (39,200)	99	70	69	60
C-130 (44,500)	95	64	64	56
C-133 (77,500)	100	74	72	61
C-141 (89,300)	96	71	64	56

enger load factors for all U. S. domestic trunk carriers over the five year period during which jets were being introduced. The immediate popularity of jets is apparent; however, load factors soon dropped as more of these very productive aircraft were placed into service, and the passenger traffic was unable to increase accordingly. It is interesting to note that the load factors for piston engined aircraft and turbo-prop dropped from roughly 60 percent to 52 percent over this period.

Cargo Service: Whereas commercial aircraft are

space limited in passenger service, cargo service tends toward a weight limited condition although many cargo loads are also space limited. The jets being larger should have a higher weight utilization in cargo use.

Fig. 86 illustrates trends in cargo load factor and revenue productivity as reported by the Air Transport Association. The period subsequent to 1960 shows the same load factor tendencies as were experienced in passenger service a year or so earlier (Fig. 83).




Fig. 85 Revenue Passenger Load Factors




Fig. 86 Cargo Load Factor and Revenue Productivity

Commercial cargo operators are continually incorporating new ideas on loading, many of which were pioneered by the military. Perhaps the most notable such innovation is the 463-L system, which can be instrumental in increasing operational utilization.

4.3.3.2 TRANSPORT SHIPS
 Since most of the remarks applying to loading capability of aircraft also apply in some degree to ships, this discussion will be limited to those items which are peculiar to ships.

Ships, like aircraft, are very dependent on correct weight distribution. In the case of ships, however, there is an additional complicating factor because they must be correctly loaded vertically as well as in the normal longitudinal and lateral directions. This three dimensional distribution, coupled with the wide variety of cargos which a ship may carry, poses a significant planning problem for the load master.

In order to operate safely and efficiently, a ship must be loaded so that it is "full and down" -- "full" in the sense that a maximum of the available space has been used, and "down" meaning carrying a sufficient amount of weight to assure stability and a comfortable ride.

Variations in the type and character of cargo do not always permit a ship to operate full. Each commodity has a stowage factor which represents the cubic feet of space occupied by one long ton (2240 pounds) of that material. When a vessel is loaded, it may not be able to accommodate cargo in the entire space available. There is often additional space lost between individual items of cargo. This loss is referred to as

"broken-stowage". This is at a minimum for bulk cargos such as grain or liquids, and is at its maximum for irregularly shaped items like vehicles, which cannot be easily stacked. The amount of space actually used, divided by the space available for use, gives an overall space factor (S.F.) for the ship. Such representative values for various types of ships were shown in Section 4.3.2.2, Fig. 84.

Efficient cargo loading may also be influenced by the design and construction features embodied in a ship. The allocation of space to living and working areas, machinery, fuel storage, and structural members, as well as the locations of these items, governs to a large extent the amount of cargo capacity and how it may be utilized. The number and size of hatches, winches, and other cargo handling gear are also factors. Specialized developments in the field of maritime transportation are the roll-on/roll-off (RO/RO) vessels, containerships and trailer-ships. These ships are designed for rapid handling of particular types of cargo or cargo packaging, and are significant from a loading capability standpoint in that they often sacri-

five good space utilization for rapidity and ease of loading/unloading (See Section 4.3.2.2).

A cargo ship suitable for military deployment should have the characteristics shown in Table 13.

Table 13 Cargo Ship Requirements For Maximum Military Deployment Utility

1. Minimum of two cargo decks for wheeled or tracked vehicles.
2. Sufficient deck heights to accommodate military cargo.
3. Adequate deck strength to support heavy tanks and loaded vehicles.
4. Facilities to permit ready maneuvering of cargo on each deck, and rapid transfer of cargo between decks.
5. Independence of dockside facilities for loading/unloading military cargo.

4.4 USEFUL LIFE

4.4.1 GENERAL

The useful life of a transport vehicle can be measured in either of two ways - structurally or economically. Both factors depend heavily on when, where, and how the vehicle is operated,

and are mutually related. The vehicle design is governed by principles of economics in the amount of refinement incorporated, in quality of materials and in the projected useful life. Structural considerations are intertwined with economics by governing the frequency and severity of repair, replacement, and maintenance required to keep the vehicle operational.

4.4.2 STRUCTURAL LIFE

The structural life of a transport vehicle is defined as the time period during which the vehicle is operationally useful, taking due account of the design mission and safety standards. It is strongly dependent on many of the elements of Section 4.2, Reliability; Section 4.3, Utilization; and Section 4.5, Environment.

4.4.2.1 TRANSPORT AIRCRAFT

4.4.2.1.1 DISCUSSION

Aircraft structural life is a complex function of economics which is directly dependent on detail design, aircraft performance, and structural maintenance. The requirement to inspect, repair, or replace components after each flight

to assure continued reliability may be restrictive and lead to aircraft replacement.

There are no precise means of determining aircraft structural life; rather, it is a question of how much maintenance is acceptable to the operator. For example, such aircraft as the Ford Tri-Motor, the DC-3, the DC-4, the C-46 and other similar types have been either retired from or continued in service on the basis of economics rather than strictly a structural life limit.

Contributing to the structural maintenance requirements are factors of use such as fatigue, corrosion (chemical, galvanic, stress, fretting), embrittlement, thermal stresses and creep. Each of these phenomena are influenced by detail design, material selection, manufacturing techniques and operating procedures. Of all the factors contributing to structural maintenance requirements, fatigue has been the major focal point. The following paragraphs describe in more detail some of the features which influence structural life or structural reliability as affected by fatigue considerations.

4.4.2.1.2 FATIGUE AS A LIMITING FACTOR

Table 14 gives typical fatigue-free service life goals for three classes of commercial transport aircraft. Actual life is a combination of environment loads and number of flights. Military goals may be identified in a source like Ref. 34. Generally speaking, the fatigue-free life requirement of military aircraft is less than that of commercial airplanes.

Table 14 Typical Fatigue - Free Service Life Goal

COMMERCIAL TRANSPORT AIRCRAFT	
USAGE	TIME
Medium to Long Range	30,000 - 50,000 flight hours
Short to Medium Range	20,000 - 30,000 flight hours
Short Range	15,000 - 20,000 flight hours

The many items affecting fatigue performance can be classified into three categories. These are detail design, natural environment and self-induced environment. Only one of these three categories, detail design, is within the direct control of the aircraft designer.

The elements of detail design considerations can be summed up briefly as follows:

- **Joint Configuration:** The structural geometry, which defines load path and local stress concentrations is most significant in defining fatigue performance. Laboratory tests have shown joints of similar static strength to differ in fatigue characteristics from 10 to 100 times or more.

- **Fasteners:** Both the type and arrangement of fasteners in a joint are important to fatigue performance. Use of increasingly stronger fastener alloys to join structural members causes effects detrimental to fatigue life. Generally, this increased fastener strength means greater load transfer, reduced diameters and increased flexibility with its tendency to localize (i.e., increase) load transfer effects and thereby, shorten fatigue life. Interference fits between holes and fasteners are generally beneficial. Fatigue performance of structures with clearance-fit fasteners may be as little as a third to a tenth that of the interference-fit fasteners.

- **Processes and Manufacturing Techniques:** Fatigue performance is vitally affected by process and manufacturing techniques. Examples of these are: decarburization, plating or cleaning; residual stresses resulting from processes or installation techniques; surface treatment, such as machining effects, protective finish, etc.; or process effects such as forged or cast surfaces, cold working and shot peening.

- **Material:** The selection of material, its grain direction and form, (i.e., wrought, cast, and forged or rolled) are all significant factors in fatigue performance. Notch sensitivity, crack propagation, and residual strength capabilities are important in providing structural safety under fatigue conditions.

- **Fretting:** Structures connected by fasteners generally experience microscopic relative motion under variable loads. By such relative motion, faying surfaces are subject to fretting corrosion with a consequent degradation of fatigue performance.

- **Stress Level:** Stress level is an important key to fatigue performance. Increased stress levels may multiply the deleterious effects of detail features, noted above, as well as being significant in their own right. For example, halving the operating stress levels can increase the fatigue life of a structure by a factor of 10 or more.

Physical environment effects, which may in actual use differ from that estimated during the design stage, include:

- **Corrosion:** The various forms of corrosion are all detrimental to fatigue performance. Pitting corrosion has the same effect on the fatigue performance of a material, particularly the aluminum alloys, as does an open hole. Intergranular types of corrosion will more nearly reflect the severe notch effects of a fatigue crack itself.
- **Temperature:** The more significant effect of temperature is on the creep and rupture characteristics of a material. These, in turn, can create local stress readjustments

that may be significant.

Another general area affecting fatigue performance is variable load environment. Some of these elements are:

- **Gusts:** Turbulence in the atmosphere is probably the most significant fatigue element of the variable load environment. Using the average of all gust data, a difference of over 100:1 can be found between the 5,000 foot altitude and altitudes of 30,000 to 40,000 feet. Gust experience can only be defined in a statistical sense. Fig. 87 reflects a typical variation in gust occurrence due to altitude.
- **Flight Length:** Flight length or profile is a significant factor in the fatigue life evaluation of transport aircraft. Short flights are significant not only in relation to flight structure (wings, pressurized cabins, etc.) but also in their effects on landing gears. Fig. 88 illustrates the variation in fatigue damage, in terms of flights and hours, for structure predominantly




Fig. 88 Estimated Fatigue Variation With Flight Length

dependent upon flight profile.

- Configuration: Such factors as aspect ratio, wing fuel distribution, wing mass distribution due to engines or stores, wing sweep, cabin pressurization, and center of gravity position all have their effect on fatigue performance. The degree and trend is dependent upon the specific configuration. For example, wing sweep, with the resultant re-




Fig. 87 Effect of Altitude on Gust Load Environment

duction in the slope of the lift curve as the sweep increases, causes a reduced response to turbulence. Fig. 89 illustrates the relative fatigue performance of a wing structure as sweep is varied.

Two "design against fatigue" concepts have evolved. These are the "safe life" concept and the "fail safe" concept. The first concept does not tolerate the appearance of fatigue failures. The fail-safe concept strives not only to avoid the appearance of fatigue damage but, should it occur, provides a structural capability to contain the damage until detected and repaired. With the safe-life concept, structure must be retired at an established time. The fail-safe structure has the same goals as a safe-life structure and also has the additional capability for extension of the goals or even meeting the goals in spite of unpredicted or premature fatigue damage. Only the amount of maintenance, not safety or reliability, forms the limit to the potential service life of the fail-safe structure.

The fatigue performance of safe-life structure and fail-safe structure is illustrated, in Fig. 90, in simplified form.




Fig. 89 Approximate Trend of Estimated Wing Fatigue With Wing Sweep Angle

4.4.2.2 TRANSPORT SHIP

Because of the dominant role played by the marine insurance underwriters in establishing design and construction criteria, operating practices, and maintenance requirements, structural longevity of ships is well assured. Moreover, high reliability requirements for ships and the techniques for their realization are less complex than those for aircraft and are more easily attained.

The major obstacle to long structural life of ships is corrosion, either from internal sources or from the operating environment. However, with normal maintenance these problems are successfully circumvented.

In view of these factors, it is concluded that transport ships have an unlimited potential structural life. The major determinants of ship life may be technological considerations as in the case of aircraft, or legislation determined by national policy.




Fig. 90 Fatigue Performance Goals and Limits

4.4.3 ECONOMIC LIFE

In all but wartime or emergency operations, the economics of transport vehicle operation are a significant and underlying factor in the consideration of parameters covered in Section 4.0. A commercial vehicle should be capable of attracting revenue in excess of its expenses, thereby affording an opportunity for profit. A military vehicle should provide the capability to perform its assigned mission at minimum total cost.

4.4.3.1 TRANSPORT AIRCRAFT

The major factor in the economic life of transport aircraft is technological obsolescence.

For commercial vehicles, this creates a situation whereby an aircraft may no longer return maximum profit in the service for which it was designed. This has occurred when some aircraft were comparatively new in terms of use and structural life. The situation is generally determined by competition. It happened to reciprocating engine aircraft when the jets were introduced. The technological spiral may perhaps catch the subsonic passenger jets when supersonic transports

become operational. To counter these economic trends, operators tend to convert the replaced aircraft to service where technological obsolescence is not so important. This, in part, explains the upswing of air cargo service. At the present time, the economic life of a commercial jet aircraft is considered to be from 12 to 14 years, depending on the airline. None of these jet aircraft has reached this age yet and it remains to be seen if they will be used for this full time period.

A similar technological evolution is taking place in the military as the older transport aircraft are being phased out in favor of more productive, newer models. The trend to the newer aircraft is a result not only of advancing technology, but of the changing requirements imposed on airlift capability by the worldwide threat of limited warfare. The current political climate requires aircraft of much larger payload capability than that of piston engine aircraft. This fact contributes to hastening their replacement.

Military transport aircraft are currently considered to have an economic first-line life of approximately 10 years.

4.4.3.2 TRANSPORT SHIPS

National policy dictates that the United States shall have a modern and capable merchant marine which can be employed in the event of international crisis. There are three major economic factors which tend to prevent realization of this goal. One is the almost indefinite life of a well built ship. Second, is the strength and influence of the maritime unions and third is foreign competition. To counteract these, the government provides necessary incentives in the form of subsidy payments, enforced retirement of vessels after a specified period of service, and by passing protective legislation. The economic life of a U.S. flag vessel is artificial; it is controlled by national policy.

The United States transport ship fleet is composed of approximately 1000 major ships. This number is distributed among the subsidized commercial operators, unsubsidized fleet - including coastwise trade and tankers, Military Sea Trans-

portation Service (MSFS) nucleus fleet, and tramp steamers.

Realizing the importance of a healthy ship-building industry and modern maritime capability, the government insures these assets by the Maritime Administration (MARAD). MARAD is empowered to enter into contracts with domestic ship operators whereby a subsidy is paid in return for the authority to dictate certain operating policies and to determine ship economic life.

The subsidies, which are billed to MARAD at the conclusion of each voyage, include partial reimbursement for varying percentages of costs incurred by the operator for such items as wages, repairs, and stores, in order to equalize them with those of foreign operators.

In return for these subsidy payments, the operator must comply with MARAD regulations governing the number of voyages, ports of call, cargos carried, labor practices, etc., and must agree to retire his ships at the end of a specified period. Prior to 1960, this economic life was

20 years; however, Public Law 86-518 enacted in that year increased the life to 25 years for all but World War II ships, which remained as before. During the economic lifetime of a subsidized vessel, payments are made by the operator to an amortization fund to replace the vessel when it is retired. The design specifications for the replacement are normally chosen from MARAD files, and construction of the new vessel is completed in a domestic shipyard which is also under MARAD subsidy.

The government-owned MSTTS nucleus fleet provides a basis for mobilization in the event of national emergency as well as a small fleet which is exclusively in government service. This fleet is capable of operating at a profit, based on industrial funding (the payment to a government agency a rate comparable to that normally paid a commercial operator).

Since MSTTS is non-profit, the excess of revenue, if any, is returned to the using agencies in the form of lower subsequent rates.

The largest U.S. maritime fleet is actually that owned by MARAD. This consists primarily of World War II vessels which have been decommissioned and placed into dead storage as a possible national defense measure.

These vessels are maintained so as to require a minimum of time to outfit if they should be needed. Ships in the dead fleet may be retained, scrapped, or sold, at the discretion of MARAD.

Effectively the economic life of these stored ships is completed on their entering storage. The option to change this condition is exercised only should national interest require it.

4.5. OPERATING ENVIRONMENT

The environment in which a transport vehicle operates has a significant effect on its reliability, utilization and useful life. It imposes a constant and often unpredictable influence on the vehicle throughout its span of use. Environment may be divided into natural environment and induced environment in order to discuss its effects. Each element is so interrelated with

the others and with other aspects of operating criteria that only a qualitative discussion is possible.

4.5.1 TRANSPORT AIRCRAFT NATURAL ENVIRONMENT

Table 15, below, lists major environmental influences for whose extremes aircraft must be designed, and within which they are operated. The right-hand column shows some aircraft characteristics which may be required because of these influences. These considerations may impose restrictions on the operating efficiency and economy of aircraft or may add weight and complexity and must, therefore, be evaluated in the light of their effects on reliability, utilization, and useful life.

The following paragraphs discuss the major impact of these factors on transport aircraft design and performance.

- **Pressurization:** In order that aircraft may fly at altitudes which provide greatest efficiency, it is desirable that at least the crew space be pressurized. For aircraft

Table 15 Natural Environment

Geography	FACTOR	AIRCRAFT DESIGN CONSIDERATION
	Terrain	Pressurization
	Soil	Landing Gear Adequacy
	Location	Self-sufficiency
	Vegetation	Takeoff and Landing Capability
Climate and Weather	Humidity	Ventilation
	Temperature	Air-conditioning
	Winds	Powerplant Efficiency
	Gusts	Structural Criteria
	Rain	Communications
	Fog	Navigation Aids
	Snow and Ice	De-Icing/Anti-Icing
	Dust	Surface Protection

which transport personnel, the entire cabin area is pressurized. This requirement often dictates a circular fuselage cross-section and may impose a structural weight penalty.

- **Landing Gear Adequacy:** The potential limited warfare situations which prevail throughout the world have emphasized the importance of being able to deliver large quantities of military equipment into relatively unsophisticated airfields existing in underdeveloped areas. This implies the ability to withstand severe landing conditions with heavy loads.

and the capability to provide adequate flotation for the aircraft on surfaces with low load-bearing characteristics.

- **Self-Sufficiency:** For both military and commercial aircraft operating into relatively unimproved airfields, it is vital that they be capable of providing a high degree of self-contained equipment. This frees them from dependence on the variety of ground support equipment such as starting units, generators, air conditioning trucks, stairs, and cargo handling gear normally provided at the more highly developed air terminals.
- **Takeoff and Landing Capability:** The same reasons that self-sufficiency and landing gear adequacy are important also influence the requirement for high power, high lift, and deceleration devices to allow operation into and out of short airfields, particularly when these are at high altitude, hot day conditions.
- **Ventilation:** This is essential when conditions of high humidity and fluctuating

temperatures cause condensation on interior surfaces.

- **Air Conditioning:** Aircraft air conditioning units must be adequate to cope with requirements to heat the inhabited areas of the fuselage when the outside air temperature is as low as -65°F , and to cool it from external temperatures as high as 120°F .
- **Powerplant Efficiency:** The effects of temperature, humidity, barometric pressure, icing and foreign object ingestion on powerplants are well known. All contribute to the complexity of the installations and due to this complexity influence operating efficiency.
- **Structural Criteria:** The effect of gusts on the fatigue life of transport aircraft structure is discussed in Section 4.4.2.1.2.
- **Communications and Navigation Aids:** These electronic devices permit transport aircraft to operate more effectively within the existing natural environment by providing use-

ful information on conditions both before and during flight. Factor is particularly useful in extending the visual horizon, and by replacing it when conditions require.

- De- and Anti-Icing: Since transport aircraft often find themselves operating in icing conditions, provisions are made to prevent or remove the formation and accumulation of ice on the structure.

- Surface Protection: The effects of weather elements on the surfaces of aircraft may have a significant bearing on maintenance requirements as discussed in Section 4.4.2. Oxidation, corrosion, and abrasion occur under certain conditions of exposure.

A few of the sometimes drastic, often subtle influences of natural environment on the design, construction, and operation of transport aircraft, have been outlined. By wise use of materials, processes, and techniques, the adverse effects of these influences are, in practice, minimized.

Induced Environment

Induced environment refers to the self-produced effects of design features or operating characteristics discussed in the foregoing section, plus such other elements under the relative influence of control of the operator as are shown in Table 16:

Table 16 Induced Environment Factors

Airport Facilities
Air Traffic Control
Operating Policies
Economic Situation
Mission

The design and operation of aircraft will, in themselves, establish ambient conditions such as temperature and pressure, stress and fatigue, fumes and odors, and corrosion and wear, all of which are relatively independent of natural environment. The major source of these effects is the powerplant, which in addition to the loads imposed by its weight, also generates torque, thrust, heat, and vibration.

The airfield environment is particularly signifi-

cant and may be defined in terms of the number, length, and strength of runways. Fig. 91 gives the free world airfield distribution in terms of numbers of runways and their length. This shows, for example, that an aircraft requiring a runway length of 5000 feet could have a greater operational flexibility in the United States than it would in either Western Europe or Southeast Asia. The potential increases as the required runway decreases below 5000 feet, so that at 2000 feet the available U.S. runways are over 5 times as plentiful as those in Europe. Airports also contribute to the induced environment through the facilities they provide for loading, servicing, storing, and maintaining aircraft.

Navigation and traffic control installations influence utilization of aircraft by permitting safe operation at night, in bad weather, and in areas of heavy air traffic. These facilities include lights and visual beacons, radio navigation aids, radar, voice communication, air traffic control centers, and instrument landing systems. The shorter runways depicted in Fig. 91 tend to have available fewer of these facilities.

4.5.2 TRANSPORT SHIP

Although the same basic environmental factors discussed for aircraft apply also to ships, the influence of these factors is often quite different. This section is intended to show both the similarities and differences.

Natural Environment

Climate and weather are accepted operational considerations for both airplanes and ships; however, the general approach in the maritime industry is to operate despite bad weather, while aircraft operators try to avoid such weather when practical. Once a voyage has been initiated, the ship does not usually try to run from heavy going as an aircraft might, nor does it have significant capability to do this. Climate may be said to have very little influence on marine operations, except in certain special cases such as in areas where persistent fog or ice present a seasonal hazard. However, climate may have a pronounced effect on the efficiency of operating personnel.

With ships, winds are not of great significance except as they affect the speed which may be




Fig. 91 Free World Airfield Distribution

maintained. Fig. 92 shows the approximate speed that a VC2-AP3 vessel can make, depending on the size and direction of wave action. As expected, speed decreases as wave height increases, and as waves move contrary to the direction of the ship's movement.

The effect of wave action on the speed of a ves-

sel have given rise to a system of "optimum track routing" which predicts a course of maximum speed for a given vessel under predicted sea state conditions. This program is especially valuable for military operations which must be conducted at highest practical speed. It also provides a more comfortable crossing and allows lower fuel consumption.

Temperature may affect ship operations by the relation between air temperature and humidity and water temperature, which causes various forms of precipitation: fog, rain, sleet, snow, and hail. As impairments to visibility, these may necessitate a reduction in speed and a constant watch either visually, or on instruments. From a cargo standpoint, humidity and changes in temperature can cause damaging sweating in the holds. Ice floes and bergs are a hazard to navigation. An encrustation of ice on the hull and superstructure imposes additional weight which may impair the stability of a vessel.

Topography is important to ship operation in that it represents the configuration of the ocean floor and thereby the depth of the water. Shallows, shoals and reefs are avoided. Topography also governs the degree of protection afforded by ports and harbors.

Tides and currents play an important role in the environment of a ship by determining the depth of a harbor and speed of movement relative to the water. Currents are responsible for much of the maritime weather, since some form of adverse




Fig. 92 VC2 - AP3 Ship Performance

condition is likely where two such currents join.

The saline content of sea water is responsible for providing ships with a very corrosive environment, both above and below the waterline. The worst corrosion problem on a ship occurs at the waterline, where a constant cycle of submergence and exposure occurs.

Marine organisms, which live in salt water, also provide an environmental problem by attaching themselves to the underwater structure. The buildup of these organisms provides additional frictional resistance to movement through the water, causing a significant decrease in speed and increase in fuel consumption. A yearly downtime is provided for hull cleaning.

Induced Environment

Induced environmental conditions are generally fewer and less severe than for aircraft. Heat from machinery and vibration from the drive train are perhaps the most significant conditions which are self-induced.

Ports and port facilities, bridges and power

lines, locks and canals, navigation aids, and types of cargo are important items in establishing the induced environment. Ports and port facilities such as channels, tugs, docks, wharves, warehouses, cranes, fuel supplies, and ship stores determine, to a great extent, the degree and efficiency of transport ship operation. Man made obstacles like bridges and power lines may dictate the size of vessels which can use a given port.

The draft of a vessel, under given load and water temperature conditions, plus its size may determine whether it can operate in such man made waterways as canals and locks. Table 17 shows the ship characteristics allowed by the three most important of such facilities equipped for ocean-going traffic.

Navigation aids, on both ship and shore govern the conditions under which a vessel may operate in foul weather. The development of radio telephony, radar, shoran, loran, decca, console, direction finders, fathometers, and other devices contribute to the operating capability and safety of transport ships.

Table 17 Limiting Dimensions for Major Inland Passage Facilities

	LENGTH OF LOCKS FEET	BREADTH OF LOCKS FEET	DEPTH OF LOCKS FEET
Panama Canal	1000	110	40
St. Lawrence Seaway	768	80	27
Suez Canal (no locks)			37

4.6.2 PEACETIME LOGISTICS MISSION

A general high-density cargo lift of one million short tons between San Francisco and Singapore is chosen for this study. This is assumed to be the amount moved during a 12-month period. Of the total, 73 percent was assumed to be outbound and 27 percent inbound.

4.6.2.1 TRANSPORT AIRCRAFT

Table 18 shows the number of transport aircraft required to complete the selected mission within one year's time, based on an average utilization rate of 8 hours per day per aircraft. Aircraft were routed so as to provide the greatest weight carrying capability (shortest critical leg).

4.6.2.2 TRANSPORT SHIPS

Transport ship requirements for this mission are given in Table 19. The tonnage given in 4.6.2 was increased by 15 percent to account for extra packaging, packing,

4.6 DETERMINATION OF MISSION PROBLEM AND FLEET SIZES FOR COST MODEL

4.6.1 DISCUSSION

To compare the relative capabilities and costs of aircraft and ships, two missions are exercised. The first mission typifies an annual peacetime logistics mission, while the second represents an emergency military deployment. These cases permit a comparison of the transport vehicles on both a weight-limited and a space-limited basis.

Table 18 Transport Aircraft Requirements - General Cargo Mission

<u>Aircraft Type</u>	<u>Number Required</u>
C-54G	4742
JRM-2	1473
C-118A	1593
C-124C	1260
C-133A	489
CL-44D	462
C-130E	842
C-135B	255
707-320C	222
L-300	263
742-302	247
742-303	261
742-304	114
742-305	112
742-306	56
742-307	112
742-308	56
742-309	140
742-310	139
742-311	222
748B-15	135

and dunnage required for shipment by water. A nominal sea time of 200 days was used for general cargo vessels based on MSTF statistics for cargo operations. Special ship types which are designed specifically to reduce time in port were assigned appropriately higher sea times.

Table 19 Transport Ship Requirements - General Cargo Mission

<u>Ship Type</u>	<u>Number Required</u>
C3-S-A2	17
C1A	31
C2-S-AJ1	20
C1-M-AV1	49
VC2-S-AP3	19
C4-S-1a	13
C3-ST-14a	20
C4-S-57a	11
C4-ST-67a	17
T2-SE-A1	8*
742-320S	9
742-321S	6

* Bulk POL only, equivalent tonnage

4.6.3.3 CAPABILITY SUMMARY AND COMPARISON

Table 20 shows the capabilities of the various aircraft types. Table 21 provides this information for ships. The tables are self-explanatory.

4.6.3 THIRTY-DAY DEPLOYMENT OF AN ARMORED DIVISION

Section 4.6.2 dealt with the performance of aircraft and ships in accomplishing a weight-limited mission; this section examines these same vehicles where space is the limiting factor.

Table 21 Sealift Vehicles - General Cargo Mission

SHIP TYPE	C3-S-A2	C1A	C2-S-AJ1	C1-M-AV1	VC2-S-AP3	C4-S-1a	C3-ST-14a
Payload (Short Tons)	11,592	7,235	10,310	6,133	10,192	12,466	9,061
Total Payload/Round Trip (Short Tons)	15,879	9,895	14,123	8,401	13,962	17,077	12,412
Block Speed (Knots)	16.55	14.04	15.46	10.54	16.55	20.34	18.01
Round Trip/Productivity (Ton-Knots)	262,797	139,150	218,342	88,547	231,071	347,346	223,540
Round Trip Delivery (Short Tons/Ship/Year)	85,905	45,418	71,321	28,899	75,534	113,391	72,983
Sea Time (Days/Year)	200	200	200	200	200	200	200

	C4-S-57a	C4-ST-67a	T2-SE-A1	742-320S	712-321S
Payload (Short Tons)	12,477	9,470	16,934(POL)	13,686	20,574
Total Payload/Round Trip (Short Tons)	17,092	12,972	23,197(POL)	18,748	28,185
Block Speed (Knots)	20.55	20.01	14.50	23.46	25.10
Round Trip/Productivity (Ton-Knots)	351,234	259,572	336,357	439,830	707,433
Round Trip Delivery (Short Tons/Ship/Year)	103,646	112,436	154,028	170,982	274,804
Sea Time (Days/Year)	238	200	280	238	238

The mission selected for this space-limited case was the transport of one ROAD Armored Division from the vicinity of San Francisco to the vicinity of Singapore within thirty days. Table 22 itemizes the particulars of the division being deployed.

4.6.3.1 TRANSPORT AIRCRAFT REQUIRED

The number of aircraft required were calculated from loading simulation studies. Aircraft with front or rear drive-on loading transported both troops and vehicles. Side

loading aircraft carried only personnel and supplies. For defining the fleet size, utilization was assumed to be an average of 8 hours per day per aircraft. Aircraft were limited as to maximum payload by critical leg distance and were further restricted by loading efficiency where applicable.

Table 23 shows the number of aircraft required to carry that percentage of the ROAD Division of which they are capable,

Table 22 ROAD Armored Division

DIVISION MANEUVER BATTALIONS

Div. Major Equip. Wt, lbs	85,753,238
Major Equip. Shadow Area, ft ² (a)	716,664
Vehicles, number	4,098
Personnel Wt, lbs, (b)	3,750,000
Personnel, Number	15,625
Accompanying Supply Wt, lbs	10,868,538
Total Division Wt, lbs	100,371,776 (50,186 Short Tons)

- (a) Division closed-space shadow area with each unit treated as a rectangle (length and width)
 (b) At 240 lbs per man

{ 6 MECHANIZED INFANTRY BATTALIONS 4 TANK BATTALIONS

Table 23 Transport Airlift Requirements - Armored Division Deployment

AIRCRAFT TYPE	NUMBER REQUIRED FOR PERCENT CARRIED	APPROXIMATE WEIGHT PERCENT CARRIED (LOADING LIMITATIONS)	NUMBER REQUIRED FOR 50,186 TONS IN 30 DAYS
C-54G	446	14.6	3,055
JRM-2	146	14.6	1,003
C-118A	172	14.6	1,181
C-124C	523	58.9	888
C-133A	217	65.6	331
CL-44D	76	14.6	522
C-130E	378	56.2	672
C-135B	37	14.6	264
707-320C	31	14.6	213
L-300	147	58.7	250
742-302	154	100.0	154
742-303	163	100.0	163
742-304	81	100.0	81
742-305	76	100.0	76
742-306	37	100.0	37
742-307	76	100.0	76
742-308	38	100.0	38
742-309	93	100.0	93
742-310	92	100.0	92
742-311	156	89.0	175
748B-15	88	100.0	88

the percentage accommodated, and the number required to carry a weight equivalent to that of the Armored Division. This latter number is a device for allowing all aircraft to accomplish the same job. For example, if an aircraft type can only carry 10 percent of an Armored Division, then it is

postulated that it will carry that amount for ten Armored Divisions in thirty days. This permits all aircraft to be costed on the basis of the same total weight. Different percentages carried imply different loading densities. This inconsistency is unavoidable for the Armored Division mission.

4.6.3.2 TRANSPORT SHIPS REQUIRED

Cargo ship requirements are given in Table 24. With the exception of the C1-M-AV1, all ships were capable of completing one, and only one, outbound trip. The C1-M-AV1 is too slow to complete the voyage loading and travel within 30 days. Loading efficiencies were obtained using factors for vehicles and resupply taken from Army Field Manual 101-10. Since the passenger capability of these cargo ships is very limited, it was assumed that no personnel were carried. Inasmuch as all of the POL for the Armored Division is packaged, a bulk carrier like the T2-SE-A1 was not considered part of this exercise.

Table 24 Transport Ship Requirements - Armored Division
Deployment

SHIP TYPE	NUMBER REQUIRED (NO PERSONNEL CARRIED)
C3-S-A2	10
C1A	17
C2-S-AJ1	14
C1-M-AV1	*
VC2-S-AP3	17
C4-S-1a	10
C3-ST-14a	12 ***
C4-S-57a	12
C4-ST-67a	11 ***
T2-SE-A1	**
742-320S	9
742-321S	3

* Because of speed, not responsive in 30 days
** Bulk POL carrier
*** Supplies loaded aboard vehicles

4.6.3.3 CAPABILITY SUMMARY AND COMPARISON

Tables 25 and 26 summarize pertinent data on the airlift and sealift vehicles chosen for this study in accomplishing the emergency military mission.

productivity ratio, which is the product of the percent carried and the number of sorties flown in 30 days, divided by the total sorties required to deploy that percentage. In Table 25 the advanced technology aircraft are shown to be more efficient than the L-300 and the 707-320C.

Aircraft were compared on the basis of a

Table 25 Capabilities of Airlift Vehicles - Armed Division Deployment

AIRCRAFT TYPE	TOTAL WEIGHT CARRIED (SHORT TONS)	SORTIES/30 DAYS	CRITICAL LEG PAYLOAD (SHORT TONS)	AVERAGE FLEET PAYLOAD (SHORT TONS)	SORTIES REQUIRED	PRODUCTIVITY RATIO
Reciprocating Powerplant						
C-54G	7,309	3.16	5.7	5.20	1406	0.033
JRM-2	7,309	2.72	22.0	18.47	396	0.100
C-118A	7,309	3.67	14.3	11.65	628	0.085
C-124C	29,549	3.42	18.6	15.52	1768	0.113
Turboprop Powerplant						
C-133A	32,800	4.22	39.75	36.00	914	0.305
CL-44D	7,309	5.40	32.10	20.08	406	0.194
C-130E	28,183	4.39	22.25	17.00	1637	0.136
Turbosfan Powerplant						
C-135B	7,309	7.37	41.50	37.10	370	0.398
707-320C	7,309	7.37	47.75	32.65	224	0.480
L-300	29,490	6.68	44.65	30.00	971	0.400
Advanced Technology						
742-302	50,186	3.45	100.0	95.0	528	0.655
742-303	50,186	3.54	92.0	87.4	574	0.617
742-304	50,186	2.58	100.0	95.0	528	1.246
742-305	50,186	7.03	100.0	95.0	266	1.330
742-306	50,186	7.05	200.5	189.3	266	2.650
742-307	50,186	7.00	100.0	95.0	528	1.325
742-308	50,186	6.93	200.0	189.3	266	2.603
742-309	50,186	5.68	100.0	95.0	528	1.016
742-310	50,186	5.74	100.0	95.0	528	1.087
742-311	44,650	7.05	50.0	40.63	1099	0.571
749B-15	50,186	7.24	80.0	79.0	635	1.140

The C4-S-1a proved to be the best conventional cargo ship, with the C4-ST-67A Roll-on Roll-off being somewhat better in view of its design for this type service. The 1975 ship proved to be only slightly more productive than current models, but the 1985 ship provided about a three-fold increase in productivity.

Table 26 Capabilities of Sealift Vehicles - Armored Division Deployment

SHIP TYPE	MAXIMUM PAYLOAD (SHORT TONS)	AVERAGE FLEET PAYLOAD (SHORT TONS)	TIME/SORTIE (DAYS)	AVERAGE DELIVERY (SHORT TONS/SHIP/DAY)
C3-S-A2	11,592	4,831	23.40	206.5
C1A	7,235	2,842	24.89	114.2
C2-S-AJ1	10,310	3,451	23.44	147.2
C1-M-AV1	6,133	1,421	31.16	NA*
VC2-S-AP3	10,192	2,842	21.59	131.6
C4-S-1a	12,466	4,831	18.69	258.5
C3-ST-14a	9,061	4,026	17.83	225.8
C4-S-57a	12,477	4,026	17.58	229.0
C4-ST-67a	9,470	4,392	16.20	271.1
T2-SE-A1	16,934**	NA**	24.60	NA**
742-320S	13,686	5,368	16.09	333.6
742-321S	20,571	16,104	16.09	1600.9

* Not responsive within 30 days

** Bulk POL only

5.0 COST PARAMETER DATA

5.1 GENERAL

Ten Year Program Costs were chosen as the economic basis of comparison for the transport vehicles of this study. The Program Costs represent the total dollars required for the acquisition and operation of the several transport systems which have equal wartime transport capabilities. Cost data are presented for two payload capabilities:

- (1) deployment of general cargo with weight limited payloads
- (2) deployment of an Armored Division that results in space limited payloads for B-70 but not all of the transport vehicles.

Tabulations of Program Costs versus Fleet sizes, for equal capabilities, are given in Section 8.1 for transport aircraft and in Section 8.2 for transport ships.

Program dollars per ton mile of wartime deployment capability per day is the specific parameter used to compare transport deployment cost effectiveness. 1964 dollars and short tons are

used as units for both aircraft and ships.

Both MATS and MSTs operate within an Industrial Funding concept. The Industrial Fund provides that a portion of the annual Operation and Maintenance Costs are paid by the agency that uses MATS or MSTs transport services. For MATS, the O&M cost items covered by Industrial Fund are about 80 percent of the total while almost all of the Annual Operating Expense is covered for MSTs.

The level of the Industrial Fund rates are important to the various DOD agencies in that it establishes the payment rate for transport services. The Industrial Fund rates related to the various transport vehicles are plotted versus the year of introduction of the vehicle, to illustrate the cost trends.

Sensitivity comparisons are provided, to show the effects on Program Costs of variations in the major cost inputs or estimates. These effects can be related directly to the deployment capability cost comparisons. Industrial Fund rates

are relatively insensitive to variations in initial cost and wartime utilization. For this reason the sensitivity comparisons are shown for program cost but not for Industrial Fund rate.

Program costs are shown in Section 5.4.4 plotted versus three of the efficiency parameters which were defined in Section 3. The parameters chosen are V_{cru} , $P/L \times V$ and $P/L \times R$. These plots provide a relationship between program costs and technological level.

5.2 DESCRIPTION OF COST MODEL

5.2.1 TRANSPORT AIRCRAFT

Program Costs for the 21 aircraft of this study were computed using the Military Transport System Costing Method, Section 8.1. Program Cost is defined as the total Initial Investment Cost plus ten years of Annual Operations and Maintenance. Expenditures for Design Development, Test, and Evaluation are included in the program cost for future transport aircraft. For transport aircraft, the major items of Initial Investment Cost and Annual Operations and Maintenance are:

<u>Initial Cost</u>	<u>Annual Operations and Maintenance</u>
Basic Fleet Aircraft	Maintenance Material
Command Support Aircraft	Personnel Pay and Allowances
Advanced Attrition	Replacement Training & Personnel Transportation
Buy Aircraft	
Maintenance Spares	
Personnel Training Transportation	Base Maintenance
Aerospace Ground Equipment	Aircraft POL
Stocks POL	Miscellaneous Costs
Non-aircraft Supply	

5.2.2 TRANSPORT SHIPS

Program Costs for the 12 ships were computed using the costing method for the Military Sea Transport System, Section 8.2. As with the aircraft, Program Cost includes Initial Cost plus 10 years Annual Operating Expense. Since MSTTS ships have a 25 year life, by Public Law 86-518 (1960), the ship initial cost is prorated for a ten year period so that the ship time period will be consistent with the time period

assumed for MATS aircraft. Major items of Initial Cost and Annual Operating Expense for ships are:

<u>Initial Cost</u>	<u>Annual Operating Expense</u>
Complete Delivery Price	Maintenance and Repair
	Crew Pay and Subsistence
	Fuel Costs
	Port Charges
	Supplies, Equipage and
	Other Costs
	Overhead Cost
	Cargo Handling Cost

5.3 DESCRIPTION OF INPUT ASSUMPTIONS

The assumptions used in the cost analysis are given in Tables 27 and 28. It is assumed that all aircraft are operated by MATS and all ships are operated by MSTs. Unit flyaway costs for existing aircraft, except for the JRM-2, were estimated using an 85 percent learning curve for airframe production, considering the latest available purchase price and number of aircraft produced. Flyaway costs for the JRM-2 and all future aircraft were estimated, in 1964 dollars,

by the same type of detailed cost estimates that are used to cost aircraft proposals. The DDTCB costs include all basic engineering and development, tooling, five test aircraft (including one static test article and one fatigue test article), structural testing and engine development costs. The production costs include sustaining engineering and tooling, production labor and materials, purchased equipment and direct charges. Costs for engines and electronics for all aircraft are assumed to be independent of fleet size. All costs of existing aircraft have been adjusted to 1964 levels by using an escalation factor of 7 percent per year for airframes and 3 percent per year for engines and equipment. This is an estimate based on review of past costing data. Purchase prices and operational costs of ships were estimated using the method given in Section 8.2.

The required number of production aircraft is obtained by adding command support and advanced attrition buy aircraft to the number of Unit Equipment aircraft determined in Section 4.6. The number of ships required is obtained directly from Section 4.6.

Table 27 Assumptions For Aircraft

AIRCRAFT	JRM-2	C-54G	C-124C	C-118A	C-133A	C-130E	CL-44D4	C-135B	707-320C	L-300	742-303 (LOBOY)
Unit Flyaway Cost (1)	2,138	.993	3,047	1,646	5,085	2,805	3,029	4,339	6,800	6,160	11,739
A/C Production Qty.	1822	5886	1559	1971	805	1042	571	315	275	323	306
Total Cost DDT&E (1)	0	0	0	0	0	0	0	0	0	200	723
Cost of One Engine (1)	.124	.023	.124	.087	.183	.093	.116	.250	.220	.270	.400(2)
No. Engines per A/C	4	4	4	4	4	4	4	4	4	4	4/3
Cost of Electronics	.053	.011	.063	.057	.068	.120	.120	.132	.132	.160	.200
Weight Empty, lbs	80,700	36,700	102,200	65,000	113,800	71,200	86,600	104,900	132,000	127,300	244,000
Wt Electronics, lbs	1,800	800	1,800	1,800	1,800	2,100	2,100	2,100	2,100	2,600	3,250
Max Payload, tons	23.3	9.6	2.5	14.25	48.5	22.5	32	43.25	47.5	48	100
Fuel Cost, \$/Gal.	.171	.171	.171	.171	.10	.10	.10	.10	.10	.10	.10
Fuel Used, Gal./Hr	356	200	480	310	1240	650	690	1680	1940	1750	460
Mission Time (2200 N. Mi.), Hrs	15	12.9	12.5	10.7	8.75	8	7.15	5.1	5.15	5.4	13.3
Crew Composition											
Pilots	3	3	3	3	3	3	3	3	3	3	3
Navigators	2	2	2	2	2	2	2	2	2	2	2
Airmen	3	2	3	3	3	3	3	3	3	3	3
742-303 (LOBOY)	742-303 (LFC)	742-305	742-306	742-307	742-308	742-309	742-310	742-311	748B-15		
Unit Flyaway Cost (1)	11,114	23,336	12,563	25,935	11,908	23,855	11,957	11,610	6,484	12,201	
A/C Production Qty.	323	141	139	69	139	71	173	172	275	167	
Total Cost DDT&E (1)	685	1618	580	1420	535	1220	560	540	305	578	
Cost of One Engine (1)	.400(2)	.750(3)	.300	.750	.300	.750	.250	.250	.250	.300	
No. Engines per A/C	4/2	4/4	6	6	6	6	6	6	4	6	
Cost of Electronics	.200	.200	.160	.200	.160	.200	.160	.160	.132	.160	
Weight Empty, lbs	220,800	377,400	260,500	527,200	242,500	488,200	268,300	256,300	127,900	267,300	
Wt Electronics, lbs	3,250	3,250	2,600	3,250	2,600	3,250	2,600	2,600	2,100	2,600	
Max Payload, tons	100	100	100	100	100	100	100	100	50	90	
Fuel Cost, \$/Gal.	.10	.10	.10	.10	.10	.10	.10	.10	.10	.10	
Fuel Used, Gal./Hr	475	2090	3282	5922	3077	5702	2370	1516	1794	3390	
Mission Time (2200 N. Mi.), Hrs	12.3	5.6	5.25	5.3	5.3	5.45	6.3	6.55	5.23	5.4	
Crew Composition											
Pilots	3	3	3	3	3	3	3	3	3	3	
Navigators	2	2	2	2	2	2	2	2	2	2	
Airmen	3	3	3	3	3	3	3	3	3	3	

The following assumptions are common to all aircraft:

- Utilization 1825 Hr/Yr
- Attrition Rate 1 Aircraft per 100,000 Hours
- Crews/Unit Equipment Aircraft 2.33
- Unit Equipment Aircraft/Wing 48
- Base of Operation Non-Tenant Assume Base Exists

(1) All costs are in millions of dollars unless otherwise noted.
 (2) LOBOY aircraft have 4 regenerative turbo-prop cruise powerplants, plus auxiliary turbofans used for takeoff only.
 (3) Laminar Flow Control (LFC) aircraft has 4 cruise turbofans plus 4 bleed-burn LFC units.

Table 28 Assumptions For Ships

Ship	Prod. Qty.	Outfit Complexity	Machinery	Machinery Location	SHP _N	Sea Speed Knots	Length Bet. Perr. Feet	Beam Feet	Depth to Uppermost Cont. Deck Feet	Cubic No.	Days at Sea Per Yr.	Bale Capacity Cu. Ft.
C4-S-1a	13	Typical (Reefer)	Steam Turbine	Amidships	17,500	20	528	76	44.5	17,857	200	737,000
C4-S-57a(1)	11	Typical (No Reefer)	Steam Turbine	Amidships	16,500	20.5	529	75	42.5	16,862	238	642,897
C3-S-A2	17	Typical (No Reefer)	Steam Turbine	Amidships	8,500	16.5	465	69.5	42.5	13,735	200	736,000
C2-S-AJ1	20	Typical (No Reefer)	Steam Turbine	Amidships	6,000	15.5	435	63	40	10,862	200	543,000
VC2-S-AP3	19	Typical (No Reefer)	Steam Turbine	Amidships	3,500	16.5	436.5	62	38	10,784	200	453,000
C1A	31	Typical (No Reefer)	Steam Turbine	Amidships	4,000	14	390	60	37.5	8,775	200	446,000
742-320S(2)	3	Typical (No Reefer)	Steam Turbine	Amidships	24,000	23.5	598	76	46.5	21,133	238	830,000
742-321S(3)	6	Typical (No Reefer)	Steam Turbine	Amidships	66,000	25	750	106	72	57,240	238	2,770,000
C1-M-AV1	49	Typical (No Reefer)	Diesel	Aft	1,700	10.5	320	50	29	4,640	200	219,754
C4-ST-87a(4)	17	Typical (RO/RO)	Steam Turbine		17,500	20	499.5	83	53	21,973	200	946,800
C3-ST-14a(4)	20	Typical (RO/RO)	Turbine		11,220	18	465	78	48.8	17,682	200	813,116
T2-SE-A1	8	Typical (Tanker)	Turbo Electric	Aft	6,000	14.5	503	68	39.3	13,425	280	---

Attrition for ships is assumed to be negligible

Number of crws per ship = 1

(1) Cargo Ship with Advanced Cargo Handling Gear

(2) 1975 Cargo Ship with Advanced Cargo Handling Gear

(3) 1985 Cargo Ship


(4) Roll on/Roll off Design

5.4 PLOTTED DATA

This section presents the cost comparisons developed for the 21 aircraft transports and the 12 ships considered in the cost section of this study.

5.4.1 PROGRAM COST - DOLLARS/TON MILE OF DEPLOYMENT CAPABILITY PER DAY

Shown, in Fig. 93, is the peacetime cost per ton mile of daily wartime deployment capability for a selected group of aircraft and ships. The selection was made to cover the range of costs for both types of transport vehicles. Considering presently operating and future vehicles, the aircraft costs are 30 to 60 times as high as ship costs depending on range.



RANGE - 1000 N. MI.

Fig. 93 Deployment Capability Cost for General Cargo and Weight-Limited Payloads

Fig. 94 presents the relative costs of 21 aircraft versus range. The superiority of the two LOBOYS (742-302, - 303) and the LFC aircraft (742-304) at ranges greater than 7500 nautical miles should not necessarily be taken as a general conclusion. Refer to Section 3.2.6 for a discussion of the P/L - Range characteristics of each vehicle.




Fig. 94 Aircraft Deployment Capability Cost - General Cargo - Weight Limited Payload

In Fig. 95 the relative costs of 12 ships versus range are presented. In this plot, the program cost of the tanker is much lower than the costs for cargo ships because the tanker has no appreciable cargo handling costs associated with its payload.




Fig. 95 Ship Deployment Capability Cost - General Cargo - Weight Limited Payload

sions is plotted in Fig. 96. It is assumed that an Armored Division is deployed from the West Coast to Singapore within 30 days. Cargo ships and all future aircraft except for the 742-311 have the capability of transporting all equipment associated with Armored Divisions. The C1-M-AV1 cannot load and deliver its cargo within 30 days and the T2-SE-A1 tanker cannot carry Armored Division equipment. Much of the equipment is oversized for existing aircraft and they are not capable of deploying a complete Armored Division. The percentage of total Armored Division weight which can be carried is noted in parentheses after each aircraft designation. For comparison, the fleet sizes of all aircraft are based on deploying a total weight equal to the weight of an Armored Division. Those aircraft which are space limited to carry less than 100 percent of the Armored Division are, in effect, carrying weight limited payloads, each of different loading density. This tends to color the result and the relatively better position of the space limited aircraft curves should be understood as of interest for their qualitative value and should be interpreted with a careful understanding of the mission problem.

The peacetime program cost per ton mile of daily wartime deployment capability for selected aircraft and ships when transporting Armored Divi-




Fig. 96. Deployment Capability Cost Armored Divisions

Fig. 97 shows the distribution of capability costs for the 21 aircraft of the study when deploying Armored Divisions. See the discussion on page 166 for interpretation of the costs for aircraft which are load limited because of size.




Fig. C7 Aircraft Deployment Capability Cost Armored Divisions

The capability costs of 10 ships to deploy an Armored Division are presented in Fig. 98. Two of the 12 ships of Fig. 95 are not included here. They are the C1-M-AV1 and the T2-SE-A1. The C1-M-AV1 cannot meet the requirements for a 30 day mission because of its slow speed. The T2-SE-A1 is not required because it is assumed that the POL required for an Armored Division would be shipped in barrels.




Fig. 98 Ship Deployment Capability Cost Armored Divisions

RANGE - 1000 N. MI.

PROGRAM DOLLARS TON MILE OF DEPLOYMENT CAPABILITY PER YEAR

5.4.2 INDUSTRIAL FUND RATE -- CENTS/TON

NAUTICAL MILE

Industrial Fund rates are established so that certain peacetime operation and maintenance costs are paid by the using agency. For MATS transports, the portion of each O&M cash item charged to the Industrial Fund is given in Section 8.1. Since one Industrial Fund rate for channel traffic is used for the entire MATS fleet, the average operation and maintenance cost per ton mile for the fleet mix is used to determine this rate. In 1962 the MATS load factor on channel traffic was less than 70 percent. For MATS cargo transports, it is assumed that all Annual Operating Expense is charged to the Industrial Fund.

Plotted, in Fig. 99, is the revenue rate possible for each transport vehicle if it carried a full weight limited cargo and was the only transport operated by MATS or MSTTS. Since neither of these conditions existed in 1962, the actual published Industrial Fund Rates were much higher than those shown here. The MATS Special Assignment Airlift rate was 15 cents/ton mile and the equivalent MSTTS rate, including terminal costs, was about 2 cents/ton mile if the cargo density was 25 lbs/cu ft.




Fig. 99 Industrial Fund Rates General Cargo - Weight Limited Payload

Fig. 100 shows a plot of the revenue rates of transport vehicles for the peacetime deployment of Armored Divisions. As in Fig. 96 the percentage of total Armored Division weight which can be carried is noted in parentheses after the aircraft designation. The C1-M-AV1 and the T2-SE-A1 are not included in this plot because the C1-M-AV1 cannot meet the 30 day mission requirement and there is no suitable cargo (bulk POL) for the T2-SE-A1.




Fig. 100 Industrial Fund Rates Percent Deployment Exercise - Armored Division

5.4.3 SENSITIVITY COMPARISONS

Fig. 101 shows the percent change in aircraft program costs for variations in the airframe costs as estimated for the production quantities shown in Table 27 for each aircraft. Airframe cost is the major parameter affecting transport aircraft program cost, especially for production quantities of 200 or less.




Fig. 101 Sensitivity Comparison Airframe Cost versus Program Cost

The percent change in ship program cost for variation in estimated ship delivery price is plotted in Fig. 102. No learning curve has been assumed for ship production quantities and the effect of ship cost is generally much less than the effect of airframe cost.




Fig. 102 Sensitivity Comparison Ship Cost versus Program Cost

Shown, in Fig. 103, is a plot of the percent change in aircraft program costs for variations in wartime utilization. As the wartime utilization decreases from 8 hours/day, the fleet size required to perform the mission increases and unit airframe cost decreases. An increase in daily utilization results in opposite changes. The effect of the change in unit airframe cost is insignificant compared to the major impact on program cost resulting from the change in fleet size.

The cost comparison, shown in Fig. 103, is based on a constant peacetime utilization of 5 hours per day. It is probable that increases in wartime utilization would require increases in crew and maintenance manning above the level required by the 5 hour peacetime utilization. The resulting increase in program cost per wing would somewhat reduce the savings realized by increased wartime utilization and the consequent reductions in fleet size required. This however is a secondary correction and is not included in Fig. 103.




Fig. 103 Sensitivity Comparison Aircraft War Time Utilization versus Program Cost

Fig. 104 shows the percent change in ship Program Cost for changes in assumptions on percent of bale capacity (space load factor) used for cargo handling cost. Analysis of MSTIS data shows that the ratio of actual measurement ton nautical miles to the total measurement ton nautical mile capability is approximately 1 to 3.3. Therefore, a load factor of 0.3 is used in this study for determining the amount of cargo loaded per year. Since the magnitude of cargo handling costs is large, variations in percent bale capacity can have a significant effect on ship program cost.




Fig. 104 Sensitivity Comparison Ship Cargo Handling Cost Factor versus Program Cost

5.4.4 PROGRAM COST VERSUS PERFORMANCE PARAMETERS

Ten Year Program Costs for the various aircraft transports are plotted versus the performance parameters defined in Section 3. Similar plots for ship transports do not show well defined trends and these comparisons are not plotted. However, a tabulation of Program Costs for the various ships, with fleet size determined by two levels of wartime capability, is given in Section 8.2.

In Fig. 105, Ten Year Program Costs for the 21 aircraft fleets are presented versus design cruise speed in knots. Since the program costs are based on fleet sizes for deployment of Armored Divisions (space limited payloads), aircraft with severe space limitations are shown as being less effective, on an economic basis.




Fig. 105 Ten Year Program Cost versus VCRU For Aircraft

In Fig. 106, Ten Year Program Costs, for the aircraft fleets, are presented versus the performance parameter payload (P/L) in short tons multiplied by cruise speed (V_{cru}) in knots. Although fleet sizes are based on the space limited payloads for deployment of Armored Divisions, the payloads used to determine the performance parameters are the maximum weight limited payloads. It is significant that program costs for the Models 742-306 and -308 are higher than might be expected. Since these aircraft have ton-knot capabilities which are double that of the next largest of the remaining aircraft, the required fleet sizes are only about one-half as large. Furthermore, the DDT&E expenditures, which are independent of fleet size, are very large. The small fleet sizes result in high production and DDT&E costs per aircraft. Therefore, for the chosen mission, the Models 742-306 and -308 are more expensive than aircraft of lower productivity. This effect is directly dependent on the choice of the cost problem. A larger transport requirement would reduce, relatively, these large aircraft unit costs and tend to flatten the right hand side of the curve.




Fig. 106 Ten Year Program Cost versus (P/L) x V_{CRU} For Aircraft

The relative Ten Year Program Costs for the aircraft fleets plotted versus the performance parameter payload (P/L) in short tons multiplied by range (R) in nautical miles are presented in Fig. 107. The payload and range used in the performance parameter are the maximum weight limited payload and the maximum range over which that payload can be carried. The Program Costs, however, are based on space limited payloads for the particular range which results in maximum fleet size for the deployment capability required.

The curves of this section (particularly Figs. 93 and 96) compare program costs for several

ships and aircraft, present and future. For these cost values it is shown that a factor of 15 to 60 exists between shipping by sea and shipping by air. Readers with experience in interpreting cost data will recognize that a considerable change in results and conclusions may be had by changing the cost model. This point is mentioned to caution the reader to avoid a too hasty conclusion from a brief scanning of these foregoing curves.

An example of the change to the relative costs and effectiveness of sea and air transport which can be obtained by changing the problem is shown




Fig. 107 Ten Year Program Cost versus (P/L) x Range For Aircraft

in Fig. 108 and Table 29. These data are taken from Ref. 50 which explores movement of a large force to the Far East under wartime conditions. Significant to the conclusions of this referenced study and Fig. 108 is the fact that a complete operations research analysis was done and consideration was given to:

- (1) destination seaport limitations and




Fig. 108 Cost Comparisor for Advanced Capability Aircraft and Roll-on/Roll-off Ships in Wartime Mission

- congestion.
- (2) congestion of ground lines of communication between the port and the area destination.
- (3) consideration of an aircraft design which has intercontinental range and forward area landing capability.
- (4) consideration of the effect on total cost of the speed of deployment.

Other missions of Ref. 50 show the difference in program costs for sea and air transport to be even less than indicated in Fig. 108.

Table 29 Effectiveness for Advanced Capability Aircraft and Roll-on/Roll-off Ship in Wartime Mission

DEPLOYMENT CONDITION	AIRCRAFT OR SHIP TYPE	DEPLOYMENT TIME - DAYS					
		10	15	20	30	45	60
DIRECT ROUTE	GLOBAL TRANSPORT	AB
	RO/RO SHIP	D	D	D	C	.	.

CODE - 1980 Time Period

- .
- A - Deployment complete and realistic
- B - Number of aircraft exceeds production capability or availability
- C - Combat area ground LOC becomes saturated
- D - Ship deployment to Bangkok completed but insufficient time for troops to reach combat area.
- D - Insufficient time (i.e. all ship) to reach Bangkok.

6.C CONCLUDING REMARKS AND RECOMMENDATIONS

A significant measure of the worth of a transport vehicle can be obtained by interpreting its relative position on the efficiency plots of Section 3 and the cost plots of Section 5. Because of the complexity and interaction of the vehicle parameters, it is not possible to devise a single presentation to answer the question - which is the best vehicle? However, by comparing in toto the efficiency and cost data and by considering the relative complexity of the designs as related to the operational considerations of Section 4, a satisfactory conclusion can be reached.

Ships, in other studies, have been shown to be an order of magnitude more effective than aircraft in certain areas. This is apparent in some, but not all, of the parameters of this study. So far as can be seen their relative positions will be maintained in the future with a tendency to close the gap as aircraft are improved. The significance of air transport competition to ships, of course, is in their large speed advantage and relative invulnerability to

wartime losses. This speed advantage for the airplane is shown for one wartime case in Section 5, Fig. 108 where airlift accomplishes missions not attainable by ships.

The data plots of Section 5.4.4 are most significant for an abbreviated comparison of cargo aircraft. The following points should be observed:

- (1) Cruise speed is an important, though not overriding, consideration. Vehicles with higher cruise speeds tend to have lower total program costs. Compressibility drag rise is the limiting factor.
- (2) Large payload capacity is equally important. For the cost problem of this study, an aircraft payload of 200,000 to 300,000 lbs offers minimum total program cost, with the largest reduction achieved below 200,000 lbs.
- (3) Airplane L/D and engine sfc are the two most important single parameters. Large improvements in either or both can, to

a degree, offset the effects of reduced speed and reduced size. For instance, compare on Figs. 105 and 106 742-302 LOBOY (high L/D, low sfc, low speed) with 742-304 LFC airplane (high L/D, higher speed) and with 742-306 (large size, higher speed).

Not shown explicitly in these curves but presented in the c.c.t assumptions, Table 27, is the effect of airplane cost. Because of the steep (initial) learning curve in the industry, the size of the fleet considered is important to any

cost problem. Conclusions can be changed considerably by changing the problem. The mixer chosen for this study is typical for these large aircraft but certainly not the only possibility.

The most promising area for future development appears to be in the powerplant. As always, lighter weight, higher powered engines with lower fuel consumption are highly desirable for both ships and aircraft. Particular interest is seen for the regenerative turbofan aircraft engine of moderately high (10 to 15) bypass ratio.

7.0 APPENDIX I - SUBSTANTIATING DATA FOR
VEHICLES DESIGNED IN THIS STUDY


7.1 TRANSPORT AIRCRAFT

Each of the aircraft identified with Boeing Model No. 748B-15 were designed specifically for this study. Data for Model 748B-15 were taken from one of an early series of design studies completed for the (now) CX-HLS mission. It is included in this study to show the comparison with aircraft designed to other mission requirements.


All study aircraft were completed through the first phase of preliminary design. Three-view layouts were made for each aircraft (Figs. 109 and 110). Drag, weight and balance, and performance estimates are compatible with that stage of development. A summary of the aircraft and their more important characteristics is shown in Table

MODEL 742-	L (FT.)	b (FT.)	h (FT.)	L_c (FT.)
305	233	203	52.1	151
306	289	284	70.3	195
307	233	200	51.3	151
308	289	284	68.3	196
309	225	266	61.0	151
310	225	253	58.5	151
311*	165	148	39.5	100


* (4) ENGINE AIRPLANE




SIDE VIEW



MODELS 742-306, -308



MODELS 742-305, -307, -309, -310



MODEL 742-311

Fig. 109 3 View Drawings For Models 742-305 Through -311




Fig. 110 3 View Drawings For Models 742-302, 303 and 304

Table 30 Aircraft Characteristics

AIRCRAFT	YEAR ENTER SERVICE	DESIGN PAYLOAD LBS	DESIGN GROSS WEIGHT LBS	WING LOADING LBS/SQ FT	WING AREA SQ FT	WING ASPECT RATIO	1/4 CHORD SWEEP DEG	TAPE RATIO	THRUST LOADING	TYPE ENGINE	NUMBER ENGINES	THRUST PER ENGINE
742-302	1973	200,000	650,000	115.	5630	11.1	7°	.35	---	1	4 T'Prop 3 T'Fan	7500 ESHP 23,000*
742-303	1973	200,000	565,000	116.	4875	11.1	7°	.35	---	1	4 T'Prop 2 T'Fan	7000 ESHP 29,000*
742-304	1973	200,000	830,000	85.	9750	8.5	30°	.35	---	2	4 T'Fan -4 Compressor	41,500* -323*/sec 22,400
742-305	1973	200,000	672,000	130.	5170	8.0	30°	.35	5.0	a=3 T'Fan	6	44,670
742-306	1973	400,000	1340,000	130.	10308	8.0	30°	.35	5.0	a=3 T'Fan	6	21,700
742-307	1983	200,000	651,000	130.	5008	8.0	30°	.35	5.0	a=3 T'Fan	6	43,670
742-308	1983	400,000	1310,000	130.	10077	8.0	30°	.35	5.0	a=3 T'Fan	6	20,440
742-309	1973	200,000	650,000	110.	5910	12.0	10°	.38	5.3	a=5 T'Fan	6	20,530
742-310	1983	200,000	588,000	110.	5346	12.0	10°	.38	4.7	a=15 Regen T'Fan	6	18,900
742-311	1973	100,000	356,000	130.	2740	8.0	30°	.35	4.7	a=3 T'Fan	4	23,000
748B-15	1969	160,000	600,000	120.	5000	8.4	35°	.35	4.05	JT3D-8B	6	

△ Cruise: Regen T'Prop
T.O.: Regen T'Prop - T'Fan

2 △ Bypass Ratio T'Fan + LFC
Bleed and Burn Suction Compressor

AIRCRAFT	DESIGN POINT RANGE N. MI.	CRUISE MACH NO.	WFU LBS	(L/D) AVE CRUISE	TOTAL AIRPLANE WETTED AREA SQ FT	AIRPLANE PARASITE AREA SQ FT	O. W. E. LBS	WSTRU LBS	WPP LBS	WFE LBS	W USEFUL LOAD LBS
742-302	8800	.28	175,000	34.8	27,780	83.0	250,500	173,000	43,000	28,000	6300
742-303	6500	.29	121,100	32.8	25,090	84.2	227,000	155,500	37,900	27,400	6200
742-304	6000	.73	225,000	34.2	△	53.5	383,000	312,800	29,700	34,900	5600
742-305	3800	.74	185,400	20.3	25,520	70.7	266,000	211,200	20,800	28,500	5300
742-306	3980	.74	363,600	21.2	46,730	129.0	536,000	442,700	44,300	40,200	8600
742-307	3960	.73	182,700	20.4	24,840	67.3	248,000	196,500	17,500	26,300	5300
742-308	4200	.73	371,700	21.5	45,030	124.0	497,000	410,900	37,100	40,200	8600
742-309	3720	.58	158,400	24.3	29,020	87.9	274,000	217,900	21,000	29,400	5700
742-310	3920	.58	113,400	23.3	26,260	85.2	262,000	199,100	28,000	29,200	5700
742-311	4200	.74	111,900	19.2	13,880	42.2	131,700	96,100	11,300	18,500	3300
748B-15	2785	.77	153,000	16.8	26,950	82.9	270,000	206,000	33,100	28,200	2700

△ 15,340 sq ft turbulent
25,730 sq ft laminar

The ten aircraft designed for this study form five basic groups:

<u>Group</u>	<u>Model Nos.</u>	<u>Payload</u>	<u>Year</u>
I	742-311	100,000	1973
	-305	200,000	1973
	-306	400,000	1973
II	742-307	200,000	1983
	-308	400,000	1983
III	742-309	200,000	1973
	-310	200,000	1983
IV	742-304 (LFC)	200,000	1973
	742-302	200,000	1973
V	-303 (LOBOY)	200,000	1973
		200,000	1973

Groups I and II are larger, newer versions of conventional turbofan aircraft. Group II has the more advanced power plant. The effect of airplane size on the efficiency parameters is seen in a comparison of the three aircraft of Group I.

Group III shows the comparative effect of operating at a reduced design cruise speed with engines of higher bypass ratio.

Group IV is the LFC airplane. The wing and tail surfaces are considered to be effectively all laminar. Because of the probable difficulty of achieving even this much laminar area, the fuselage and the wing and tail root areas are considered turbulent.


Group V has the two LOBOY aircraft. The low specific fuel consumption of the regenerative turboprop engines and the reduced induced drag of the LOBOY operation combine to make a relatively small aircraft which may be attractive at extremely long ranges. They are assumed to operate at an h/b of about 0.06. A discussion of the operational problems associated with these aircraft is beyond the scope of this study. The data are presented with the reservation that these problems will require solution before LOBOYS are accepted as practical.

Use was made of prior studies in determining all the aircraft's wing loadings and aspect ratios. It is believed that the geometry shown in Table 30 is reasonable and not greatly different from what would be chosen should a development program be initiated for any one of the vehicles.

7.1.1 DRAG

The drag polar of each aircraft was built up considering each of the polar components where:

$$C_{D_{TOTAL}} = C_{D_{P_{MIN}}} + \Delta C_{D_P} + \frac{C_L^2}{\pi AR} + \Delta C_{D_M}$$



$$C_{D_{P_{MIN}}} = \frac{f_{total}}{S}$$

$$f_{total} = \Sigma (C_f \times S_w) + \Delta f_{misc}$$

The airplane wetted areas were calculated and a C_f value estimated for each component; i.e., wing, tail, fuselage, nacelle. The sum was found and an increment added, based on information from current airplanes, to account for interference and other miscellaneous items to arrive at the total airplane f .

The items ΔC_{D_P} (that part of the parasite drag coefficient which varies with lift) and ΔC_{D_M} (the increment of drag coefficient which is due to compressibility) were estimated based on information from current airplanes making due allowance for differences in wing geometry. At the cruise condition described in this report both ΔC_{D_P} and ΔC_{D_M} are small. Together they add up to $\Delta C_{D} \leq .0005$. At other operating conditions they will, of course, be larger. The induced drag term,

$C_{D_i} = \frac{C_L^2}{\pi AR}$, is defined in terms of the geometric aspect ratio and the reference wing area.

The polar was used to define the actual drag at each point calculated for the several parts of the mission profile. The parts of the mission are defined in Section 3.2.6.

7.1.2 WEIGHT

The weight for each aircraft was built up by projecting statistical weight data taken from a number of actual airplanes. The basis for the statistical projections included actual group weight statements for the current aircraft of this study. Use was made of data for a number

of other aircraft not included in this study.
 The weight groups are defined as follows:

Total Structure	Wing Group Horizontal Tail Vertical Tail Body Group Main Landing Gear Nose Gear Nacelle or Eng. Sect.
Total Powerplant	Engine (as installed) Engine Accessories Engine Control Fuel System Starting System Lubricating System
Total Fixed Equipment	Instruments Surface Controls Hydraulic System Electrical System Electronics Furnishings Air Conditioning Anti-Icing
WEIGHT EMPTY	Crew and Crew Baggage Unusable Fuel Oil and Unusable Oil Emergency Equipment Cargo Equipment Water - Wash & Drink Galley and Contents
Useful Load	

OPERATING WEIGHT EMPTY (O.W.E.)

The O.W.E. and O.W.E. buildup for each aircraft is shown in Table 30. In making these weight estimates the design load factor was set at 2.5 limit for all aircraft except LOBOY, which was set at 2.0.

A problem shared by all who have occasion to compare and interpret aircraft weights is that of understanding what is included in the weight quoted - considerable latitude being taken in defining the weight groups. The weights quoted in this study for all the aircraft are in accord with the definition above. Table 31 has been prepared to further define the quoted weight characteristics of the several aircraft.

Table 31 Design Features Affecting Aircraft Weight

Model	CARGO HANDLING								OTHER			
	Nose Ramp	Tail Ramp	Side Door	Swing Tail	Prov. for Pallets	Air Drop Ramp	High Cup Floor	Overload Capability	High Flotation Gear	High Lift Devices	Prov. for Personnel	Laminar Flow Control
C-54G			x				x				x	
JRM-2			x**								x	
C-116A			x**								x	
C-124C											x	
C-130E	x*		x		x	x	x				x	
C-133A		x	x		x		x				x	
CL-44D-4			x		x		x				x	
C-135B			x		x		x				x	
707-320C			x		x		x				x	
L-300												
742-302	x	x										
742-303	x	x										
742-304	x	x										
742-305	x	x										
742-306	x	x										
742-307	x	x										
742-308	x	x										
742-309	x	x										
742-310	x	x										
742-311	x	x										
748B-15	x	x			x	x	x				x	

* Loading Elevator in Lower Fuselage

** Two Large Side Cargo Doors

*** Complete Facilities for Commercial Passenger Service Except Seats are not Installed

7.1.1.3 POWERPLANT

Each of the future engines of this study was designed to suit the characteristics of projections to the present state-of-the-art, assuming that sufficient development funding were provided. Data were generated in the form of plots of sfc/\sqrt{D} vs FN/δ for a range of Mach Numbers. Predictions as to basic parameters, such as the optimum engine bypass ratio or compressor pres-

sure ratio and the more detailed parameters, such as engine thrust/weight ratio, T/V_{eng} , were made on the basis of a statistical projection of the latest information available from engine manufacturers. Ref. 24 presents a complete discussion of the engine data used. Table 32 presents a summary of the assumptions on which the future engine data are based.

Table 32 Future Engine Data Assumption

PARAMETER	Used on 742-311 -305 -306	Used on 742-309 -304	Used on 742-307 -308	Used on 742-310	Used on 742-302 -303
Compressor Efficiency (Polytropic)	.91	.91	.92	.92	X
Turbine Efficiency (Adrabatic)	.92	.92	.93	.93	X
Fan Efficiency (Adrabatic)	.88	.88	.90	.97	X
Regenerator Effectiveness	---	---	---	.81	X
Overall Pressure Ratio (at Sea Level Static)	20	20	24	8	8
Fan Pressure Ratio (at Sea Level Static)	1.8	1.55	1.9	1.2	X
Bypass Ratio	3	5	3	15	---
Turbine Inlet Temperature (at Sea Level Static)	2500°R	2500°R	2700°R	2500°R	2500°R

X This parameter was not defined explicitly in the performance prediction of this engine.

7.2 TRANSPORT SHIPS

Four advanced transport ships were designed for this study (Table 33). They are defined as a 1975 conventional ship (742-320S) and a 1985 conventional ship (742-321S). Also shown are nuclear powered versions of these ships. These are identified, respectively, as 742-320S Nuc and 742-321S Nuc.

Detail used in determining these advanced ships compares with that for the future aircraft. Ship design is characterized by standardized determination of design coefficients associated with hull form and ship speed capability and by the conservatism apparent in ship designers' projections to current state-of-the-art.

Table 33 Design Data For Advanced Marine Vehicles

SHIP	YEAR ENTER SERVICE	DESIGN P/L (L.T.)	GROSS WEIGHT (L.T.)	LENGTH BETWEEN PERP. (FT)	TYPE ENGINE	NO. PROPELLERS	NORMAL SHP	DESIGN SEA SPEED (KNOT)	CRUISING RANGE (N.M.I.)	L/D	OWE (L.T.)	WEIGHT STEEL (L.T.)	WEIGHT MACH. (L.T.)	WEIGHT OUTFIT (L.T.)
742-320S	1975	13158	24000	598	STEAM TURBINE	1	24000	23.5	13000	230	9932	5570	1380	2235
742-321S	1985	20665	45000	750	STEAM TURBINE	2	66000	25.0	13000	175	38115	14400	3200	3390
742-320S NUC	1975	14288	24000	598	NUCLEAR STEAM	1	24000	23.5	400000	230	8712	5570	1350	2235
742-321S NUC	1985	28425	45000	750	NUCLEAR STEAM	2	66000	25.0	400000	175	21575	14400	3200	3290
742-322S	1970	423.7	1060	235	GAS TURBINE	2	24200	40.0	1000	18.5	488.4	286	106	64

These factors were taken into account in making these advanced ship preliminary designs. Ref. 26 treats this in detail and defines the data assumptions that were made.

In addition, data are also presented for 742-322S, a large hydrofoil ship designed for 1975 operation. Ref. 26 summarizes and discusses the design characteristics of 742-322S. As discussed in Section 2.1.4, the hydrofoil ship is not an intercontinental transport ship in the same sense as the 742-320S and 742-321S. It is included in this section to avoid an additional section of substantiating data.

8.0 APPENDIX II SUBSTANTIATING DATA FOR COST MODELS

8.1 MILITARY AIR TRANSPORT COSTING METHOD

8.1.1 INTRODUCTION

Total Ten Year Program Costs, for the various fleets The total program cost of an air transport of aircraft considered in this study, are tabulated consists of the expenditures required for Design in Table 34. The method used to estimate these Development, Test, and Evaluation (DITE), the costs is presented following the tabulation. Initial Investment Cost, and Operating and Main-

Table 34 Total Program Costs For Aircraft Fleets (Billions of 1964 Dollars)

AIRCRAFT	WEIGHT LIMITED PAYLOADS						SPACE LIMITED PAYLOADS FOR DEPLOYMENT OF ARMORED DIVISIONS UTILIZATION = 8 HRS/DAY	
	UTILIZATION = 2 HRS/DAY		UTILIZATION = 8 HRS/DAY		UTILIZATION = 14 HRS/DAY		U. E.*	TOTAL Program Cost
	U. E.*	TOTAL Program Cost	U. E.*	TOTAL Program Cost	U. E.*	TOTAL Program Cost		
JRM-2	1964	32.412	1473	24.764	842	14.818	1003	17.370
C-54G	6322	64.019	4742	49.087	2710	28.601	3035	32.101
C-124C	1680	33.209	1260	25.244	720	14.846	388	18.102
C-118A	2124	28.972	1593	21.945	910	12.800	1181	16.457
C-133A	652	16.785	489	12.815	279	7.587	331	8.097
C-130E	1123	19.907	842	15.134	481	8.906	672	12.224
CL-44D4	616	12.128	462	9.218	284	5.415	322	10.356
C-135B	340	8.971	255	6.820	146	4.014	254	6.794
707-320C	296	9.455	222	7.227	127	4.301	213	6.855
L-300	351	11.262	263	8.561	150	5.099	250	8.254
742-302	329	15.076	247	11.742	141	7.250	154	7.895
-303	348	16.524	261	12.012	149	7.378	163	7.941
-304	152	13.269	114	10.583	65	6.977	81	8.138
-305	149	8.468	112	6.817	64	4.167	76	4.779
-306	75	5.487	56	4.629	32	2.829	37	3.593
-307	149	8.119	112	6.354	64	3.985	76	4.580
-308	76	8.094	57	6.468	33	4.381	38	4.826
-309	187	9.659	140	7.517	80	4.689	93	5.308
-310	185	9.077	139	7.079	79	4.388	92	4.993
-311	296	9.719	222	7.444	127	4.530	175	6.010
748B-15	180	9.917	135	7.704	77	4.777	88	5.357

* Number of unit equipment aircraft

tenance Costs for a given period of time. These expenditures are given in 1964 dollars in this study.

The fleet size required to perform any given deployment task is dependent upon wartime utilization, mission profile, and the capability and characteristics of the particular aircraft considered. However, the cost involved in performing the wartime mission is not calculated because the significant budget considerations are peacetime costs for a wartime capability. Also, the costs of a major war are indeterminate because of size, length and location considerations. Occasional limited wars may cost little compared to the year-in year-out costs of peacetime preparedness. The program cost represents the expenditures of acquiring the desired force and operating and maintaining it over a given time period (usually ten years for MATS) under peacetime conditions.

Costing technology is based on the assumption that only one air transport wing will be accommodated per base. Therefore, the total program cost is simply the product of the cost per base including aircraft, times the

number of bases required for the proposed fleet.

8.1.2 PROGRAM COST

There are four basic definitions of program cost. The choice of one over another depends on how the data are to be used.

MARGINAL COSTING

Marginal costing is used for planning purposes. Basically, it is a means of comparing alternate systems by considering only cost elements which can be affected by future decisions. Sunk or committed costs are ignored. DDT&E is charged to the year of program go-ahead. Initial investment is spread uniformly over the useful life of an aircraft. For example, if the program go-ahead for a particular transport system is 1964, first delivery in 1968, last delivery in 1972, and the time period ends in 1977, only the first year delivery aircraft will have served their 10-year useful life. Therefore, for aircraft delivered in 1972, only 5/10 of the initial investment and five years of operation and

Maintenance costs may be included in the marginal program cost.

PROGRAM COSTING BY TOTAL OBLIGATIONAL AUTHORITY (TOA)

This type of program cost involves the total government obligation, by fiscal year, that is required to procure, operate and maintain a given fleet size. For example, on a program go-ahead, DDT&E funds are initially required followed by, or concurrent with, initial investment funds for procurement of aircraft and military bases. As aircraft are delivered, annual O&M funds must also be made available to operate the system. The total program cost is then the sum of funds required each fiscal year for the duration of the program. The funding requirements of competitive transport systems can be compared year by year or by the sum of TOA's starting with initial funding and continuing for a period consistent with the first line life of the transport system. TOA represents the required funds regardless of when they are authorized, appropriated, or expended. This type of cost breakdown is

used by the DOD for program change proposal comparisons.

NEW OBLIGATIONAL AUTHORITY

Another approach to program costing is that used for authorizing the DOD program packages. The funds necessary for DDT&E, procurement of a specified whole number of aircraft plus spares, or annual operation and maintenance cost for a given fleet must be provided for, in advance, by a new obligational authority. This new obligational authority is defined as the full cost of an increment of a program (e.g., DDT&E or a production contract for sixteen aircraft) regardless of the year in which the funds are expended.

TEN YEAR PROGRAM COST

A short-cut method is sometimes used to compare the relative costs of transport systems. The Ten Year Program Cost is the sum of funds required for DDT&E, Initial Investment and 10 years of O&M for the total number of U.E. aircraft considered for equal capability for each transport system

in the comparison study. This method is used for this study.

8.1.3 INITIAL INVESTMENT COST

Program costing can be categorized into two major components, Initial Investment Cost and Annual Operation and Maintenance cost.

The Initial Investment cost consists basically, of two parts: (1) cost for procurement of the required aircraft fleet including spares, and (2) costs for initially establishing a military base of operation.

Aircraft directly involved in performing a given mission are called unit equipment (U.E.) aircraft. To enable a Command to maintain its basic U.E. inventory, additional aircraft (command support) are authorized. In addition to command support aircraft, advanced aircraft purchases are necessary to account for attrition losses. The total production quantity then represents all U.E., command support and attrition aircraft. The unit cost of an airplane is based on the

total production quantity and does not include DDPEE.

The cost of the base includes construction of runways, facilities, training of flight crews and ground personnel, aerospace ground equipment, stocks of petroleum, oil and lubricants (POL) and various other miscellaneous items. Existing bases will be inherited and therefore no cost for modifying or expanding a base, is considered.

A sample calculation of initial investment cost is shown in Table 35. Each cost item is explained on the following pages.

INITIAL INVESTMENT COSTS

• BASIC AIRCRAFT

Basic aircraft represents the total cost of all U.E. aircraft on base. The unit cost of new aircraft is developed by the same type of detailed cost estimates that are used to cost aircraft proposals. The aircraft cost is based on the

Table 35 Initial Investment Cost

INITIAL INVESTMENT COST		AIRCRAFT MODEL	ENGINE MODEL
COST BASED ON PRODUCTION OF 71 A/C - 61 U.F.			
C ₁	TOTAL COST OF AIRPLANE	53,655,000 W _E - WEIGHT EMPTY	488,200
C ₂	COST OF ONE ENGINE	750,000 W _E - WEIGHT U.F. ELECTRONICS	3,250
N ₀	NO. ENGINES/AIRPLANE	6 N ₀ - NO. AIRPLANE/WING	43
C ₃	COST OF ELECTRONICS	200,000 P ₀ - FUEL BURNED GA./HR	5,702
C ₄	C ₁ - C ₂ N ₀ - C ₃	18,955,000 C ₁ - FUEL COST \$/GAL	.10
U	YEARLY UTILIZATION HRS	1,825 H ₀ - ATTRITION RATE	.00001
A. BASIC AIRCRAFT			
I ₀	C ₁ N ₀		1135.4
B. COMMAND SUPPORT			
I ₁	C ₄ U		113.5
C. ADVANCED ATTRITION BUY			
I ₂	I ₀ + I ₁ U ₀ (Program Years)		166.4
D. MAINTENANCE SPARES			
I ₃	Airframe	I ₃ = C ₁ N ₀ (Curve Value)	54.8
I ₄	Electronics	I ₄ = C ₂ N ₀ (Curve Value)	2.2
I ₅	Engines	I ₅ = C ₃ N ₀ (Curve Value)	113.0
E. PERSONNEL TRAINING (Assuming 50% Inertial)			
I ₆	I ₂ + .50 (\$70,000 Pilots + \$42,000 Nav. + \$10,000 Non-Crew Off.)		93.4
F. TRANSPORTATION			
I ₇	I ₆ + \$18 MIL. Pers. + \$697 Off. + \$435 Airm. + \$481 Civ.		8.3
G. BASE - NEW OR: ADDITIONAL CONSTRUCTION (50% for Tenant)			
I ₈	I ₇ + \$10M + (\$3000 Total Base Pers.) + (\$3 W.P. & N.)		-----
H. AIRSPACE GROUND EQUIPMENT - AGE			
I ₉	I ₈ + \$312 Total Base Pers. + .004 I ₁		13.0
I. STOCKS P.O.L.			
I ₁₀	I ₉ + .065 annual P.O.L.		4.2
J. NON AIRCRAFT SUPPLY			
I ₁₁	I ₁₀ + \$178 Total Base Pers.		2.8
K. WAR RESERVE			
I ₁₂	I ₁₁ + (.01 C ₁ + .06 C ₂ N ₀ + .12 C ₃) N ₀		-----
TOTAL INITIAL INVESTMENT COST (IN MILLIONS PER WING)			
TOTAL INITIAL INVESTMENT COST (IN MILLIONS), TOTAL FLEET - 1845.8			1845.8
TOTAL INITIAL INVESTMENT COST (IN MILLIONS), TOTAL FLEET - 1854.4			1854.4
CALC.	REVISED	DATE	
CHECK			
APP.			
			FILE

THE BOEING COMPANY
BOEING AIRCRAFT DIVISION

total production cost excluding DDT&E.

COMMAND SUPPORT
Command support is estimated at ten percent of the basic aircraft and represents additional aircraft authorized to a command to enable it to maintain the basic inventory.

ADVANCED ATTRITION BUY
This cost is dependent on the peacetime attrition rate, unit cost of aircraft, annual utilization and the assumed program years. The attrition rates usually are taken from the "Planning Factors Manual" (AFM 172-3).

MAINTENANCE SPARES
Initial spares are shown separately for airframe, electronics and engines. They are based on the average daily utilization and are estimated as a percentage of the corresponding initial cost in the basic aircraft. (See Fig. 111).




Fig. 111 Aircraft Initial Spares Transport Systems

- **PERSONNEL TRAINING**

This category includes the cost necessary to train military personnel as required for the transport system. This cost is determined by multiplying the number of pilots, navigators, non-crew officers and airmen by a respective average training cost as given in the "Peacetime Planning Factors Manual". Half of these expenses are assumed to be inherited.

- **TRANSPORTATION**

This item includes the cost of transporting military and civilian personnel, their dependents and household goods, and organization equipment. The factors used to compute these costs have been developed from the "Planning Factors Manual" and are directly related to the number of officers and airmen.

- **BASE - NEW OR ADDITIONAL CONSTRUCTION**
Base facilities costs were developed from the 1956 "Peacetime Planning

Factors Manual" for a non-tenant organization. Broken down into three factors, they consist of a basic amount for an entire airplane wing (basic amount & other two factors combined), a cost per man on base, plus a dollar per pound rate of aircraft weight empty times the number of U.E. airplanes. If an existing base can be inherited, this cost item will include allowance for the expansion of the base only.

- **AEROSPACE GROUND EQUIPMENT (AGE)**

This section includes all initial equipment except aircraft, aircraft spares and spare parts. AGE costs are assumed to be proportional to the number of base personnel and the cost for aircraft and personnel facilities.

- **STOCKS POL (PETROLEUM, OIL AND LUBRICANTS)**

This item represents a reserve supply of POL for aircraft and ground equipment requirements. The cost is estimated as a percentage of annual POL.

estimated as a percentage of annual POL.

- **NON-AIRCRAFT SUPPLIES**

Non-aircraft supply costs are based on an average peacetime consumption and are proportional to the number of base personnel.

- **WAR RESERVE**

War reserve costs consists of spare parts for items such as airframes, engines, electronic systems, photographic equipment, fire control and bombing systems, etc., and are shown as percentages of the corresponding initial cost. Normally, war reserves do not apply to MATS transport systems.

8.1.4 OPERATION AND MAINTENANCE COSTS

Operation and Maintenance (O&M) costs represent expenditures directly connected with the peacetime operation and maintenance of a transport wing. Specifically, O&M costs include the cost of maintenance

material (i.e., airframe spares, electronic equipment spares and engine spares), depot labor, personnel pay and allowances, replacement training and personnel transportation, base maintenance, aircraft POL and other miscellaneous expenses. Each of these items is explained on the following pages.

Table 36 shows a sample calculation of annual O&M costs for a 48 U.E. transport wing. The calculation sheet is set up to generate the cost of one wing per base. To determine the annual O&M cost for a given fleet, the cost per base is multiplied by the ratio of U.E. aircraft available each year to the number of U.E. aircraft stationed on one base. The total O&M for the fleet during a programmed time period would be the sum of all annual expenditures during that period.

to actual flying hours. Depot labor costs are assumed to be equal to the cost of base maintenance personnel.

- **PERSONNEL PAY AND ALLOWANCES**

Personnel pay and allowances are based upon standard rates listed in the Planning Factors Manual. The following elements of pay are taken into consideration in deriving a weighted average for MATS personnel: Basic pay, quarters allowances, subsistence allowance, clothing allowance, flight pay, incentive pay and other payments such as re-enlistment bonuses, death gratuities, etc. The manpower requirements, as listed on the personnel calculation sheet Table 38, were derived from actual Air Force unit manning documents.

- **REPLACEMENT TRAINING AND PERSONNEL TRANSPORTATION**

Average annual turnover rates (Planning Factors Manual) were applied to the initial investment cost for personnel

training and transportation to determine both expenses.

- **BASE MAINTENANCE**

Annual base maintenance is assumed to be 5 percent of the initial aircraft and personnel facility costs.

- **AIRCRAFT POL (PETROL, OIL AND LUBRICANTS**

The annual POL costs are defined as the total fuel and lubricants consumed by the basic wing aircraft operating for one year times the average cost per gallon.

- **MISCELLANEOUS COSTS**

This includes all miscellaneous costs not contained in previous items such as POL for ground equipment, heating oil, medical supplies, the cost of the director of supply and services support in Air Materiel Command, etc. It is assumed to be a function of the number of base personnel and the

8.1.6 PERSONNEL REQUIREMENTS

A method has been developed to estimate manpower requirements for any present or proposed air transport systems. Data from Air Force unit manning documents (UMD's) were used to generate the personnel curves shown on Figs. 112 through 116.

weight empty of the aircraft plus a constant based on a full airplane wing (constant ± other two factors combined) and has been developed from RAND Corporation data.

8.1.5 INDUSTRIAL FUNDING

The Industrial Fund is made up of the following items and allows the percentage of cost shown for each item.

Table 37 Factors to O & M Costs to Estimate Industrial Fund Revenues

	PERCENT OF OPERATION AND MAINTENANCE
Maintenance Material	
Airframe	70
Electronics	85
Engines	85
Depot Labor	80
Personnel Pay and Allowances (Civilians Only)	50
Personnel Transportation (Exclud- ing Replacement Training)	50
\$47 Pilots + \$47 Nav. + \$132 Non-Crew Off. + \$97 Airm.	
Base Maintenance	50
Aircraft POL	100
Miscellaneous Costs	80




Fig. 112 Air Transport Squadron Overhead Transport Systems




Fig. 113 Organizational Maintenance - Flight Line Maintenance Squadron - Transport Systems





Fig. 114 Organizational Maintenance - Period Maintenance Squadron - Transport Systems




Fig. 115 Field Maintenance Squadron - Transport Systems




Fig. 116 Service Squadrons - Transport Systems

The number of base personnel required for an air transport system is a function of the aircraft size and type, average mission length, and average utilization. Correction factors were added to allow for variations in mission time, utilization and aircraft type (i.e., reciprocating, turboprop, or jet). Flight crew compositions and crew ratios are determined from actual UMD's or are based on data compiled in Air Force Manual Manpower Policies and Criteria (AFM 26-1).

Table 38 shows a sample calculation of the base personnel required for a 48 U.E. transport wing.

8.2 MILITARY SEA TRANSPORT COSTING METHOD

Total Ten Year Program Costs for the various fleets of ships considered in this study are tabulated in Table 39. The method used to estimate these costs is presented in the pages following the tabulation.

8.2.1 INTRODUCTION

The total program cost for a sea transport system consists of the expenditures required for Initial Cost and Annual Operating Expense for a given time period. These expenditures are given

Table 38 Transport Systems Personnel Per Wing Non-Tenant

MISSION TIME UTILIZATION PAYLOAD BLOCK SPEED	5.45 HRS 3 HRS/DAY 100 TONS 500 KNOTS	AIRPLANE MODEL ENGINE MODEL	142-318
a. Air Transport Squadrons			
Flight Crew - No. of Man/Crew x Crews/Airpl. x Nw			963
Overhead - Curve Value			96
b. Organizational Maintenance Squadrons			
Flight Line Maint. - Curve Value (K ₁ x K ₂)			1827
Periodic Maint. - Curve Value (K ₁ x K ₂)			483
c. Field Maintenance Squadrons			
Aircraft - Engine Maint. - Curve Value (K ₃ x K ₄)			2471
Comm. & Electr. Maint. - Curve Value (K ₅ x K ₆)			479
Maintenance Ldg. Sqds. - 14% of (b + c)			524
d. Base Flight Squadron - 8% of (b + c)			337
e. Air Terminal Squadron - (Max. Payload : 1000) x Block Speed x Nw			3973
f. Operations Squadron - 120 per Base			139
Maintenance Personnel (a through e)			
Line Personnel (a through f)			1441
			10464
h. Civil Engineering Sqds.			
1. Air Police Squadron - Curve Value			1629
2. Service Squadron - Curve Value			316
3. Supply Squadron - Curve Value			549
4. Transportation Sqds. - Curve Value			1143
5. Dispensary - Curve Value			533
6. Air Transp. Wing Command - 80 per Base			346
7. Air Base Group - 8.5% (a through h)			18
			1324
Military Personnel - Base Personnel (a through g) : 1.20			
Pilots - Pilot/Crew x Crew/Airpl. x Nw			13019
Navigation - Nav./Crew x Crew/Airpl. x Nw			329
Non-Crew Officers - 1/23 of (a through g) x 30% Air Transp. Sqds. Onbd.			274
Airmen - Military Pers. - Total Officers			648
			11792
Civilian Personnel - 50% of Total Military Personnel			
			2964
Total Base Personnel (a through g)			
			15823
CHECK			
APPROV			
DATE			
			5000
			THE BENTON COMPANY
			MEMPHIS, TENNESSEE

Table 39 Total Program Costs For Ship Fleets (All Costs in Millions of Dollars)

SHIP	WEIGHT LIMITED PAYLOADS		SPACE LIMITED PAYLOADS FOR DEPLOYMENT OF ARMORED DIVISIONS	
	No. Required	Total 10 Year Program Cost	No. Required	Total 10 Year Program Cost
C4-S-1a	13	312,754	10	240,580
C4-S-57a	11	263,142	12	287,064
C3-S-A2	17	328,984	10	193,520
C2-S-AJ1	20	314,120	14	219,884
VC2-S-AP3	19	311,068	17	278,324
C1A	31	399,280	17	218,960
742-320S	9	264,150	9	264,150
742-321S	6	355,620	3	177,810
C1-M-AV1	49	496,370	-	-
C4-ST-67a	17	439,960	11	284,680
C3-ST-14a	20	424,000	12	254,400
T2-SE-A1	8	102,624	-	-

DAYS AT SEA: Cargo ships with conventional cargo handling gear 200 days
 Cargo ships with advanced cargo handling gear 238 days
 Tankers 280 days

in present dollars since DOD makes cost effectiveness comparisons on this basis.

The fleet size required to perform any given deployment task is dependent on utilization, speed, capability and characteristics of the particular ship. However, the cost involved in performing the wartime deployment is not calculated because the significant budget considerations are the peacetime costs for a wartime capability. Also, the costs of a major war are indeterminate because of size, length and location considerations. Occasional limited wars may cost little compared to the year-in year-out costs of peacetime preparedness. The program cost represents the expenditures of acquiring the desired force and operating and maintaining it over a given time period under peacetime conditions. MSTTS ships are assumed to have a program life of 25 years per Public Law 86-518 (1960).

8.2.2 PROGRAM COST

Since the primary purpose of this document is to compare surface and air deployment costs, a ten year program cost will be used. This is the time period assumed for MATS transports. MSTTS

ships have a 25 year life and, therefore, the ship Initial Cost will be prorated for a ten year period and added to ten years of Annual Operating Expense.

8.2.3 INITIAL COST

The Initial Cost for a ship is taken as the complete delivery price of the ship. For air transport costing, the complete delivery price of the airplane is only 10 percent to 70 percent of the total Initial Investment Cost. The additional aircraft Initial Investment Cost items are listed below with a brief explanation as to why a similar allowance was not made for ship Initial Cost.

Command Support Aircraft - The ship and crew are assumed to have a 10 day lay-up period annually for maintenance and repair, so there is no requirement for command support ships.

Advanced Attrition Buy - Peacetime attrition of ships is assumed to be negligible.

Maintenance Spares - Spare parts for conventional ships are not as specialized as spare parts for

aircraft. For this application, it is assumed that the cost of the initial on board stock of maintenance parts is included in the complete delivery price of the ship.

Personnel Training and Transportation - For MSTs most training is inherited or gained on the job and there are training and travel allowances in the annual Overhead Cost for MSTs.

Base Costs, AGE, Stocks POL, and Non Aircraft Supply - No allowance is made for any of these items because the ship's port is assumed to exist and little, if any, modification is required to accommodate the new conventional ship.

Similarly, it is not considered necessary to purchase special handling equipment (corresponding to AGE), stocks of POL, non-ship supplies or other items which are assumed to be inherited with the port.

The complete delivery price of the ship is estimated as a function of the cubic number (CN) and the normal shaft horsepower (SNP_N). Reference suggests that one of the best measures of overall ship size is CN which is defined as follows: $CN = LBD/100$. L = length between perpendiculars, B = beam or breadth and D = depth (including freeboard).

The hull cost is estimated as a function of CN with variations as to the complexity of the outfitting. See Fig. 117. The cost line labeled TYPICAL - AVERAGE PASSENGER, NO FREEZER is used unless a specific outfitting is requested for cargo ships.




Fig. 187 Hull Cost versus Cubic Number

The machinery cost is estimated as a function of SHPN with machinery located either amidship or aft. See Fig. 118.




Fig. 118 Machinery Cost versus Shaft Horsepower Normal

The Initial Cost is the sum of hull cost and machinery cost. A sample calculation of the Initial Cost of a conventional cargo ship is given in Table 40. The Initial Cost of a ship is assumed to be the construction cost (bid price) plus additional costs for inspection and items added by the owner. Ref. 27 estimates these additional costs as eight percent of the construction cost.

8.2.4 ANNUAL OPERATING EXPENSE

Annual Operating Expense represents the expenditures directly connected with the peacetime operations and maintenance of a ship. The cost categories itemized below conform to the reporting method used in MSTs Financial and Statistical Reports plus the Cargo Handling Costs. Each of these categories is explained on later pages. For comparison, the categories used in estimating Annual Operation and Maintenance Costs for MATS aircraft are also shown.

Table 40

INITIAL COST AND ANNUAL OPERATING EXPENSE OF MATS SHIPS (IN MILLIONS OF \$)	SHIP MODEL LOCATION	CA-8-1A	OUTFIT COMPLEXITY	TYPICAL W/REVIEW
L - LENGTH BET. PERP.	638	SHIP OR BHP		17,500
B - BEAM	76	DAYS AT SEA/YR		300
D - DEPTH TO UPPERMOST CONT. DECK	44.3	DAYS VOYAGE DISTANCE		18,000
CM - CUBIC NUMBER - 100	17,857	N ₁ - NUMBER VOYAGES		24,750-6
V ₆ - SUSTAINED SEA SPEED	30K	WALS CAPACITY, CU FT		127,000
I. INITIAL COST				
A. HULL COST				11,550
B. MACHINERY COST				3,270
DELIVERY PRICE (A+B)				
				14,820
II. ANNUAL OPERATING EXPENSE				
A. MAINTENANCE AND REPAIR				
HULL AND OUTFIT				.041
MACHINERY				.042
B. CREW PAY AND SUBSISTENCE				
				.160
C. FUEL COST, SEA FUEL				
				.378
PORT FUEL				
				.081
D. PORT CHARGES				
				.031
E. SUPPLIES, EQUIPAGE, AND OTHER COSTS				
				.343
F. OVERHEAD COST - .01 (A THROUGH E)				
				.032
G. CARGO HANDLING COST				
CARGO BHP - .3 (BALK CAPACITY/40) (\$9.00/MT (N ₁))				.398
TANKER				NO CHANGE
ANNUAL OPERATING EXPENSE PER SHIP (A THROUGH G)				
				1,183
CALC	REVIEW	DATE		
CHECK				
APPD				
				THE GOALING COMPANY
				SEATTLE, WASHINGTON

Annual Operating Expense

	<u>Ships</u>	<u>Aircraft</u>	<u>CARGO SHIPS</u>	<u>TANKERS</u>
Maintenance and Repair				
Crew Pay and Subsid- ence		Personnel Pay and Allow- ances	Conven- tional	With Adv. Cargo Hand- ling Gear
Fuel Costs	Replacement Training and Personnel Transportation		200	238
Port Charges	Aircraft POL		155	117
Supplies, Equipage and other Costs	Base Maintenance		10	10
Overhead Cost	Miscellaneous Costs		1500	1500
Cargo Handling Costs				
			Days/Year Underway	280
			Days/Year in Port	70
			Days/Year Lay-up Time	15
			Average N.Mi. between Ports	1500

The operating assumptions used for estimating annual costs are given below.

Table 40 shows a sample calculation of Annual Operating Expense for a cargo ship.

- Maintenance and Repair

This item (Figs. 119 and 120) consists of the labor and material necessary for the annual lay-up as well as the material used in routine maintenance. The maintenance and repair costs for the hull are related to the size factor - CN, while the machinery costs are related to the normal shaft horsepower - SHPN.

- Crew Pay and Subsistence

The number in the crew and the average pay is estimated (Fig. 121) as a function of ship size (CN) and its machinery (SHPN). These data were calculated from Ref. 27 for dry cargo ships and Ref. 28 for conventional tankers.

The crew sizes in Fig. 121 do not include the extra crew members required when passengers are carried. One crew member is added for every five passengers and the cost is increased by the ratio of extra crew members over the number in a standard crew.




Fig. 119 Hull Maintenance and Repair versus Cubic Number




Fig. 120 Machinery Maintenance and Repair versus Shaft Horsepower Normal

ANNUAL MAINTENANCE AND REPAIR COST FOR MACHINERY - MILLIONS OF DOLLARS

SHPN
1000




Fig. 121 Crew Pay and Subsistence versus Cubic Number x Shaft Horsepower Normal

- Fuel Costs

The annual cost for fuel (Figs. 122 and 123) is estimated as a function of SHP_N for underway fuel and as the product (CN) (SHP_N) for port fuel necessary to provide hotel services for the crew. The price of Bunker C fuel used was \$2.15 per barrel while diesel fuel was priced at \$3.60 per barrel.

- Port Charges

Port charges (Fig. 124) depend primarily on the registered tonnage of the ship but the standard size factor (CN) was used for estimating these costs. The estimates are based on data from the MSTTS PAC Financial and Statistical Reports. Since MSTTS ships are often berthed at military terminals where port costs do not apply, the estimated cost for port charges will be too low for commercial cargo ships.




Fig. 122 Underway Fuel Costs versus Shaft Horsepower Normal




Fig. 123 Port Fuel Cost versus Cubic Number x Shaft Horsepower Normal




Fig. 124 Port Charges versus Cubic Number

- Supplies, Equipage and Other Costs

These costs depend on ship size, number of crew and amount of ship activity. Therefore, (CN) (SHP_N) is used as the parameter to estimate these costs. (See Fig. 125).




Fig. 125 Supplies, Equipage, and Other Costs versus Cubic Number x Shaft Horsepower Normal

- **Overhead Costs**

This item covers a specific ship's share of the MSIS base operating expenses. It includes salaries, indoctrination costs, training and travel costs, and expenses for supplies, communications and occupancy of premises. Overhead Costs are estimated as 2.7 percent of Annual Operating Expense items A through E.

- **Cargo Handling Costs**

The Terminal Cargo Trans-shipment rates as given in U.S. Army Supply and Maintenance Command SMC PAM No. 55-1 (1963) were averaged for Pacific ports to estimate the average cost for cargo handling per measurement ton. The bale capacity of a ship is divided by 40 to obtain measurement tons and a 30 percent load factor is assumed. The terminal costs for tankers is included in the cost of fuel being transported.

9.0 REFERENCES

1. Flight Handbook, USAF Series C-54D and C-54E Aircraft, T.O. IC-54D-1E, March 22, 1956.
2. Standard Aircraft Characteristics, C-54G Skymaster, Douglas, July 13, 1948.
3. Group Weight Statement, Model JRM-2, Report No. 2388, June 15, 1946.
4. Airplane Characteristics and Performance, Model JRM-2, Bureau of Aeronautics, Navy Dept., August 19, 1944.
5. Flight Manual, USAF Series C-118A Aircraft, T.O. IC-118A-1, June 15, 1962.
6. Standard Aircraft Characteristics, C-118A Liftmaster, Douglas, August 1, 1955.
7. Flight Manual, USAF Series C-124C Aircraft, T.O. IC-124C-1, September 16, 1963.
8. Standard Aircraft Characteristics, C-124C Globemaster, Douglas, January 20, 1955.
9. Flight Manual, USAF Series C-133A & B Aircraft, T.O. IC-133A-1, August 5, 1963.
10. Standard Aircraft Characteristics, C-133A Cargomaster, May 5, 1958 and C-133B Cargomaster, March 2, 1959, Douglas.
11. Summary of Performance Data, CL-44D-4, Canadair Limited, Report OER No. 179,
February 26, 1962.
12. Long Range Cargo Transport, Model CL-44D-4, Canadair Limited, Report No. RAD-44C-100, June 8, 1959.
13. Flight Manual, USAF Series C-130E Aircraft, T.O. IC-130E-1, November 27, 1963.
14. Flight Manual, USAF Series C-135A & B Aircraft, T.O. IC-135A-1-1, December 1, 1962.
15. Lockheed 300, Commercial Turbofan Freighter, The Aeroplane and Commercial Aviation News, January 3, 1963.
16. Lockheed 300, Jet Freighter for the Next Decade, The Aeroplane and Commercial Aviation News, January 17, 1963.
17. Lockheed 300 Data, Lockheed Aircraft Corporation, Report No. AED 553, December 4, 1961
18. C-141A Starlifter, Military Airlift Capability Data, Lockheed - Georgia Co., A Division of Lockheed Aircraft Corporation, ER 5985, November, 1962.
19. Boeing, Vertol Division, The U. S. Army Boeing - Vertol HC-1B Chinook Helicopter, Document 5B-548A, July, 1961.

20. Special Committee on Airships, Review and Analysis of Airship Design and Construction Past and Present, Report No. 2, January 20, 1937.
21. Standard Aircraft Characteristics, ZFG-2 Goodyear, October 1, 1955.
22. Short Group Weight Statement of ZFG-2 Airship.
23. A Study of the Operational Feasibility of the Ground Effect Machine in the Amphibious Support Mission, Office of Naval Research, Report ONR/NAR-26 Appendix I, November, 1962.
24. Randall, J. R., Development of Study Engines for 1973 and 1983, Boeing Document No. D6-7666 TM, February 27, 1964.
25. R. A. Darby, Preliminary Study of LOBOY Airplanes, Boeing Document No. D6-6674 TM, March 10, 1964.
26. J. N. Brion - Evaluation Study of Transport Vehicles - Marine Supplement Boeing Document D2-23214 April, 1964.
27. Benford, Harry, General Cargo Ship Economics and Design, Office of Research Administration, University of Michigan, Report 04465-2-F, July, 1962.
28. Johnson, R. P., and Rumble, H. P., Weight, Cost and Design Characteristics of Tankers and Dry Cargo Ships. Rand Corporation Memorandum RM-3318-FR, April, 1963.
29. Military Sea Transportation Service, Department of the Navy, Merchant Ship Register, MST5 P504, April, 1963.
30. American Bureau of Shipping, The Record, 1950, 1953 and 1962.
31. Russo, V. L., Turner, H. Jr., and Wood, F. W., Submarine Tankers, Presented at the Annual Meeting of The Society of Naval Architects and Marine Engineers, November 17-18, 1960.
32. Arnott, David, (Editor), Design and Construction of Steel Merchant Ships, Society of Naval Architects and Marine Engineers, New York, New York, 1955 Transactions.
33. Shigemitsu, Michiyo, Nuclear - Powered Submarine Tanker, Second United Nations International Conference on the Peaceful Uses of Atomic Energy, Paper A/Conf. 15/P/1320, Geneva 1958.
34. Aeronautical Systems Division, U. S. Air Force, TN 61-141, Detail Requirements and Status Air Force Structure Integrity Program, Part I.
35. A Special Study of Operation "Vittles", Aviation Operations Magazine, April 1949, Vol II, No. 5.

36. Facts and Figures About Air Transportation, Air Transport Association, 24th Edition, 1963.
37. Cargo Grows Despite Rate Turmoil, by Wallace Longstreth, Airlift Magazine, May, 1962.
38. The Impact of Low Cost International Air Freight on Military Reserve Airlift, Aeronautical Research Foundation, Cambridge, Mass., 1956.
39. Can Marine Engineering be Improved by Using the Reliability Theory, John Woodward, Maritime Reporter/Engineering News, March, 1963, Vol 25, No. 6.
40. Optimum Track Routings Speed Ocean Crossings, Navy Management Review, December, 1961, Vol VI, No. 12.
41. Proceedings of a Symposium, Roll on-Roll off Sea Transportation, National Academy of Sciences, National Research Council Publication No. 471, November, 1956.
42. Staff Officers' Field Manual Organizational, Technical, and Logistical Data, Department of the Army Field Manual, FM 101-10, Part I, Unclassified Data, October 1961.
43. Cargo Deadweight Distribution, Martin Heuvelmans, Cornell Maritime Press, New York. 1945.
44. Principles of Water Transportation, Leslie A. Bryan, The Ronald Press, New York, 1939.
45. Conklin, D. L., et. al., Economics of Nuclear and Conventional Merchant Ships, Maritime Reactors Branch, Division of Reactor Development, U. S. Atomic Energy Commission, Contract No. AT(04-3)-109, Directive G., American-Standard, June 30, 1958.
46. Lindsey, W. K., and Doyle, R. C., Transportation For Weapon and Space Systems, Boeing Company Document D2-10732, September 9, 1962.
47. Military Sea Transportation Service, Pacific Area, Financial and Statistical Report, MSTTS Report 7700-2, Fiscal Years 1962 and 1963.
48. Military Sea Transportation Service, Department of the Navy, MSTS Briefing Presentation, CONSTSINST 5000.3A, June 21, 1962, Encl. (1)
49. U. S. Army Supply and Maintenance Command, Transportation and Travel - CONUS Terminal Command Port Handling Rate Structure. SNC PAM No-55-1, February 1963.
50. Military Deployment by Airlift and Sealift, O. Brende, Boeing Document D6-9924, in preparation.

DISTRIBUTION LIST FOR BOEING COMPANY
AIRPLANE DIVISION REPORT D6-2067
"Evaluation Study of Transport Vehicles"
CONTRACT NO. W-63-0804C

1. Chief, Bureau of R-52 (1) RAEV (1)
Naval Weapons Department of the RR-25 (1) RAPP-13 (1)
Navy Washington, D.C. RA-12 (1) DIL-31 (2)
20360 RADD-3 (4) DLI-302 (10)
2. Chief, Bureau of Code 421 (1)
Ships Department of the Technical Librarian (1)
Navy Washington, D.C. 20360
3. Chief of Naval Research
Department of the Navy
Washington, D.C. 20360 Code 461 (1)
4. Office of the Chief of Naval Operations
Department of the Navy
Washington, D.C. 20360 Op-07T5 (1)
5. Commander, Military Sea Transportation
Service
Department of the Navy
Washington, D.C. 20360
Attn: Captain T. M. Davis (1)
6. Commanding Officer and Director,
David Taylor Model Basin
Washington, D.C. 20360
Code 01 (1) Code 601 (1)
7. Director of Naval Warfare Analyses
Institute of Naval Studies
545 Technology Square
Cambridge, Massachusetts 02139 (1)
8. Commanding Officer, Naval Air Development
Center
Air Warfare Research Department
Johnsville, Pennsylvania (1)
9. Commanding Officer
Transportation Research and Development
Command
Fort Eustis, Virginia (1)
10. Headquarters, Research and Technology
Division
Air Force Systems Command
Bolling Field Air Force Base
Washington, D. C. (1)
11. U. S. Department of Commerce
Maritime Administration
Washington, D. C. 20235
Attn: Mr. L. C. Hoffman (1)
12. National Academy of Sciences
2101 Constitution Avenue
Washington, D. C.
Attn: Mr. James Probus (1)
13. Cornell Aeronautical Laboratory, Inc.
P. O. Box 235
Buffalo, New York 14221 (1)
Via: Inspector of Naval Material
1021 Main Street
Buffalo, New York

14. Douglas Aircraft Co.
Aircraft Division
3855 Lakewood Blvd.
Long Beach, California
Attn: Mr. A. M. O. Smith (1)
Via: Bureau of Naval Weapons
Representative
Long Beach, California
15. General Dynamics Corp.
Convair Division
3165 Pacific Highway
San Diego, California (1)
Via: Bureau of Naval Weapons
Representative
San Diego, California
16. General Dynamics Corp.
Electric Boat Division
Groton, Connecticut (1)
Via: Bureau of Naval Weapons
Representative
Bethpage, Long Island, New York
17. Grumman Aircraft Engineering Corp.
South Oyster Bay Road
Bethpage, Long Island, New York (1)
Via: Bureau of Naval Weapons
Representative
Bethpage, Long Island, New York
18. Lockheed California Company
A Division of Lockheed Aircraft Corp.
2555 N. Hollywood Way
Burbank, California (1)
Via: Bureau of Naval Weapons
Representative
Burbank, California
19. LTV Vought Aeronautics Division
P. O. Box 5907
Dallas, Texas 75222 (1)
Via: Bureau of Naval Weapons
Representative
Dallas, Texas 75222
20. McDonnell Aircraft Corp.
Lambert - St. Louis Municipal Airport
P. O. Box 516
St. Louis, Missouri (1)
Via: Bureau of Naval Weapons
Representative
St. Louis, Missouri
21. Martin Marietta Corp.
Middle River
Baltimore, Maryland (1)
Via: Bureau of Naval Weapons
Representative
Westinghouse Corporation
P. O. Box 746
Baltimore, Maryland
22. North American Aviation, Inc.
Columbus Division
4300 East Fifth Avenue
Columbus 16, Ohio (1)
Via: Bureau of Naval Weapons
Representative
Columbus, Ohio
23. Rand Corporation
1700 Main Street
Santa Monica, California (1)
24. Stanford Research Institute
280 Mission Street
South Pasadena, California (1)

25. Stevens Institute of Technology
501 - 711 Hudson Street
Hoboken, New Jersey (1)
Via: Commanding Officer
Office of Naval Research Branch
Office
207 W. 24th Street
New York, New York
26. United Aircraft Corporation
Research Laboratories
400 Main Street
East Hartford, Connecticut (1)
Via: Bureau of Naval Weapons
Representative
East Hartford, Connecticut
27. Committee of American Steamship Lines
1000 Connecticut Avenue
Washington, D. C. 20036
Attn: Mr. R. K. James (1)
28. United States Lines
One Broadway
New York 4, New York
Attn: Mr. Alexander Purdon (1)

The Boeing Company, Airplane Division, Renton, Washington
EVALUATION STUDY OF TRANSPORT VEHICLES
by C. H. Spiegelberg, et al., FINAL REPORT, June, 1964
243 pages, including 110 figures, 29 tables, 50 references,
and two appendices (including 15 figures and 11 tables).
Contract No. NOn-63-0804C, Report No. D6-2087
Unclassified Report

Data are shown for efficiency parameters such as vehicle L/D and for a cost parameter defined as the total transport system cost for each of the selected intercontinental transport vehicles. A section is presented on operational parameters which includes discussion of reliability, utilization, useful life and environment. The information is presented in data plots for ease of comparison and summarized in tables. Most coverage is given to current and possible future transport aircraft and ships. These future vehicles are projected to 1983. Covered in smaller numbers are airships, helicopters, ground effect machines, hydrofoils and submarines.

Descriptors

Transport Vehicles
Efficiency Parameters
Cost Parameters
Operational Parameters
Aircraft
Ships
Submarines

UNCLASSIFIED

UNCLASSIFIED

Descriptors

Transport Vehicles
Efficiency Parameters
Cost Parameters
Operational Parameters
Aircraft
Ships
Submarines

The Boeing Company, Airplane Division, Renton, Washington
EVALUATION STUDY OF TRANSPORT VEHICLES
by C. H. Spiegelberg, et al., FINAL REPORT, June, 1964
243 pages, including 110 figures, 29 tables, 50 references,
and two appendices (including 15 figures and 11 tables).
Contract No. NOn-63-0804C, Report No. D6-2087
Unclassified Report

Data are shown for efficiency parameters such as vehicle L/D and for a cost parameter defined as the total transport system cost for each of the selected intercontinental transport vehicles. A section is presented on operational parameters which includes discussion of reliability, utilization, useful life and environment. The information is presented in data plots for ease of comparison and summarized in tables. Most coverage is given to current and possible future transport aircraft and ships. These future vehicles are projected to 1983. Covered in smaller numbers are airships, helicopters, ground effect machines, hydrofoils and submarines.

Descriptors

Transport Vehicles
Efficiency Parameters
Cost Parameters
Operational Parameters
Aircraft
Ships
Submarines

UNCLASSIFIED

UNCLASSIFIED

Descriptors

Transport Vehicles
Efficiency Parameters
Cost Parameters
Operational Parameters
Aircraft
Ships
Submarines

UNCLASSIFIED

UNCLASSIFIED