

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
REUSE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AD. 4 6 2 3 9 7

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

WT-1661

Line 24
INTEGRAL PART
2/525/65
of the
28 Apr 1960
DEFENSE AGENCY
SANDIA BASE

462397

CATALOGED BY: DDC

Operation

HARDTACK

April - October 1958

Project 6.14

MAY 28 1958

NSA B

PROOF TEST OF AN/TVS-1 (XE-3) FLASH-RANGING EQUIPMENT

Issuance Date: January 24, 1961

HEADQUARTERS FIELD COMMAND
DEFENSE ATOMIC SUPPORT AGENCY
SANDIA BASE, ALBUQUERQUE, NEW MEXICO

QUALIFIED REQUESTERS MAY OBTAIN COPIES OF THIS REPORT FROM D

4 6 2 3 9 7

WT-1661

OPERATION HARDTACK—PROJECT 6.14

PROOF TEST OF AN/TVS-1 (XE-3) FLASH-RANGING EQUIPMENT

G. D. Scarborough, Maj, USA,
Project Officer
J. S. Van Sant

U. S. Army Artillery Board
Fort Sill, Oklahoma

U. S. Army Signal Research and
Development Laboratories
Fort Monmouth, New Jersey

QUALIFIED REQUESTERS MAY OBTAIN COPIES OF THIS REPORT FROM DT

ABSTRACT

The overall objective of this project was to evaluate the Peerless flash-ranging set, AN/TVS-1 (XE-3), prior to its acceptance by the United States Army Signal Research and Development Laboratory (ASRDL).

The specific objectives were to determine the operational capability of two types of automatic shutter-activating units and to compile data on shutter speeds and filter values at different ranges from point of burst of various low-yield nuclear devices.

The project participated in eight detonations at the Nevada Test Site (NTS). Consistent, reliable operation of the equipment tested was obtained at 18 miles from burst. This distance was the maximum line-of-sight range that was available for a suitable observation point.

Although both types of automatic shutter-activating units performed equally well under conditions of high visibility such as existed during the test participations, the modified version was considered most applicable. Camera settings were kept constant, but neutral-density filters of varied transmission factors were experimentally employed.

No recommendation for an overall optimum filtering can be made, because samples included only low-yield detonations and cannot be correlated to higher yields, varying ranges, and changing ambient light conditions.

FOREWORD

This report presents the final results of one of the projects participating in the military-effect programs of Operation Hardtack. Overall information about this and the other military-effect projects can be obtained from ITR-1660, the "Summary Report of the Commander, Task Unit 3." This technical summary includes: (1) tables listing each detonation with its yield, type, environment, meteorological conditions, etc.; (2) maps showing shot locations; (3) discussions of results by programs; (4) summaries of objectives, procedures, results, etc., for all projects; and (5) a listing of project reports for the military-effect programs.

CONTENTS

ABSTRACT-----	5
FOREWORD-----	6
INTRODUCTION-----	9
Objectives-----	9
Background-----	9
Theory-----	9
PROCEDURE-----	10
Instrumentation-----	10
Operations-----	10
RESULTS-----	10
DISCUSSION-----	10
CONCLUSIONS AND RECOMMENDATIONS-----	11
REFERENCES-----	11
TABLES	
1 Neutral-Density Filters, Wratten No. 96-----	11
2 Summary of Shot Participation-----	12
3 Summary of Results-----	12
FIGURES	
1 Peerless flash-ranging set, AN/TVS-1 (XE-3), showing camera with 20-inch lens, automatic actuator, camera mount, leveler, tripod, control box, and battery box-----	13
2 Peerless flash-ranging set, AN/TVS-1 (XE-3), showing camera with 5-inch lens-----	13

PROOF TEST OF AN/TVS-1(XE-3) FLASH-RANGING EQUIPMENT

INTRODUCTION

Objectives. The overall objective of this project was to evaluate the Peerless flash-ranging set, AN/TVS-1(XE-3), prior to its acceptance by the United States Army Signal Research and Development Laboratory (ASRDL).

The specific objectives were to determine the operational capability of two types of automatic shutter-activating units and to compile data on shutter speeds and filter values at different ranges from point of burst of various low-yield nuclear devices.

Background. A Continental Army Command (CONARC) requirement in 1944 that called for a camera capable of locating enemy artillery and rocket firings was abandoned in 1949 because of the technical inadequacy of wet-film-developing processes. Additional studies made in 1950 resulted in a flash recorder utilizing the Polaroid-Land photographic process. Two prototype models were completed and evaluated by the United States Army Artillery Board. Further design recommendations were incorporated into later developments by ASRDL.

In 1953, an additional CONARC requirement called for the capability of determining the location and height of burst of nuclear weapons delivered by friendly forces. An electronic shutter-actuator (Blue Box Mark IV) was procured from Edgerton, Germeshausen and Grier (EG&G). During Operation Upshot-Knothole, ASRDL and CONARC jointly evaluated a system employing this type of shutter actuator; these tests proved the feasibility of the device (Reference 1). The camera unit utilized a pinhole optical system.

During Operation Teapot (Desert Rock V and VI) a version of the AN/TVS-1 flash-ranging set using glass optics was employed tactically by Battery C, 532d Field Artillery Observation Battalion (Reference 2).

The bulk and weight of the actuator led to the design and development of a compact, lightweight, transistorized unit by ASRDL. This device was employed with earlier models of AN/TVS flash-ranging sets by Project 50.8 during Operation Plumbbob (Reference 3).

In the summer of 1955, a contract was let to Peerless Instrument Company for ten service-test models of the AN/TVS-1(XE-3) flash-ranging set with automatic shutter-actuating devices. Peerless attempted to employ vacuum tubes in their first variation of the automatic shutter actuator, but the tubes had an extremely short life and consumed large amounts of power.

Test results of the transistorized, automatic actuator developed by ASRDL indicated that this lightweight and compact unit should be incorporated into the camera being fabricated by Peerless.

Delivery of the first four completed models of the Peerless AN/TVS-1(XE-3) was made to ASRDL in September 1958 for engineer-acceptance tests.

Theory. By using a known baseline and predetermined orientation points, it is possible to detect targets, such as nuclear flashes, by triangulation survey techniques. For accurate data reduction, it is necessary to read to the center of the target's filmed image. The latter should be small—about $\frac{1}{16}$ to $\frac{1}{8}$ inch is considered ideal. To achieve a circumscribed impression of this size, the fireball must be photographed as near to time zero as possible, with filtered lenses. The shutter-actuating system, therefore, must be automatically started with the initial time rise of the nuclear flash.

In order to reduce evenly the amount of light for all wavelengths of the visible spectra that entered the optical system, neutral-density (ND) filters were used. Table 1 describes these filters.

PROCEDURE

Instrumentation. The AN/TVS-1 flash-ranging set is a tripod-mounted, battery-operated, transportable, photographic-recording device (Figures 1 and 2). Immediately in front of the film plane and at right angles to the optical axis is a lined, compensated grid that is superimposed on the film when a picture is exposed through it.

The automatic shutter actuator is a photocell and amplifier combination responding to a fast-time-rise pulse of light that is converted to a usable electrical pulse operating the shutter-tripping mechanism. Two types were used: one (unmodified) in which the electrical pulse output corresponded to the light input pulse in duration, and the other (modified) which had a definite-length output pulse of about 50 msec, regardless of the duration of the light input pulse. Both of these units employed S4 response photocells and time constants that would accept only 50 μ sec or faster, rise-time light pulses.

Operations. Tests were conducted from ranges of 2 to 18 miles from ground zero for fractional-kiloton-yield detonations and from 7 to 60 miles for the larger-yield bursts. For a given shot, specific locations on hilltop sites with line of sight to ground zero were determined by results obtained on a previous participation. Table 2 lists the shot participation.

RESULTS

Data were obtained on the operational ranges of the shutter-activating device and on camera settings compatible with a selected ND filter for best image definition. Camera settings of f:32 at $\frac{1}{200}$ second were used exclusively, a combination that provided the smallest diaphragm opening and fastest shutter speed possible with this camera. Table 3 is a summary of the results attained.

The photographs were analyzed and the data of Table 3 were related to fireball size for a determination of operational ranges for the shutter-activating device and best combinations of filter and camera settings.

DISCUSSION

The flash-ranging equipment functioned properly for all ranges up to 29,000 meters, except during Shot Hamilton, the yield of which was much lower than predicted. At the greater distances, up to 97,000 meters, performance was satisfactory on only one of five occasions. The failures, i.e., nonoperation of the automatic actuators, were attributed to low battery voltages caused by the cold weather that persisted at the selected observation stations. A poor photograph resulted from the first attempt at the longer range, which made clear the need for using a neutral-density filter.

During the first test of the closer (3,600 to 29,000 meters) operations, it was noted that an ND-4 filter proved to be optimum. Subsequent participations at these ranges produced good photographic results. It is considered that these results are valid for the lower yields but are no indication of a capability during larger yield bursts. Previous testing on larger yield weapons as outlined in Reference 3 cannot be correlated with results obtained during this test. It was also noted that the two types of shutter actuators performed equally well. Further evaluation by ASRDL resulted in the conclusion that the modified-type shutter actuator is more reliable than the actuator furnished by the Peerless Instrument Company.

An attempt was made to correlate yield from cloud photography obtained by the AN/TVS cameras used on this series of tests. These results are totally inconclusive and should not be considered because of the limited samples obtained. Graphs in Reference 4 relating yield to cloud measurements were used. Limited picture samples did indicate that cloud stabilization was not uniform and there appeared to be considerable effects from meteorological conditions.

Many minor mechanical deficiencies were found to be present in the equipment during testing. These deficiencies are considered to be correctable and will be enumerated in "Service Test Report" of the United States Army Artillery Board.

CONCLUSIONS AND RECOMMENDATIONS

Under conditions of high visibility such as existed during these test participations, no apparent difference existed in the operation of the shutter actuators. The modified shutter is considered to be more reliable and should be adopted for use on the AN/TVS flash-ranging set.

The camera settings and filters used were satisfactory at the ranges and for the yields involved. Additional testing is required to obtain information on filters, shutter speeds, and lens openings required for larger yield detonations.

REFERENCES

1. R. V. Tiede, D. F. Kelly, and K. C. Burger; "Determination of Height of Burst and Ground Zero"; Project 6.12, Operation Upshot-Knothole, WT-760, May 1955; Army Field Forces Board No. 1, Signal Corps Engineering Laboratories, Fort Monmouth, New Jersey; Secret Restricted Data.
2. "The Location of Atom Bursts by a Field Artillery Observation Battery"; Chapter IV, Report, June 1955; The Artillery and Guided Missile School, Fort Sill, Oklahoma.
3. "Detection of Atomic Burst and Radioactive Fallout"; Project 50.8, Operation Plumbbob, CONARC-56T1, 13 December 1957; Continental Army Command, Fort Monroe, Virginia; Secret Restricted Data.
4. "Capabilities of Atomic Weapons"; Department of the Army Technical Manual, TM 23-200; Department of the Navy, OPNAV Instruction 03400.1B; Department of the Air Force, AFL 136-1; Marine Corps Publications, NAVMC 1104 Rev; Revised Edition November 1957; Headquarters Armed Forces Special Weapons Project, Washington, D. C.; Confidential.

TABLE 1 NEUTRAL-DENSITY FILTERS,
WRATTEN NO. 96

Filter	Percent Transmission
1	10
2	1.0
3	0.1
4	0.01

TABLE 2 SUMMARY OF SHOT PARTICIPATION

Shot	Preliminary Yield	Platform	Area	Time	Date
					1958
Mora	1.9 kt	1,500-ft balloon	7b	0605	29 Sep
Quay	90 tons	100-ft tower	7c	0630	10 Oct
Lea	1.5 kt	1,500-ft balloon	7b	0520	13 Oct
Hamilton	1.17 tons	50-ft tower	FF	0800	15 Oct
Dona Ana	38 tons	500-ft balloon	7b	0620	16 Oct
Rio Arriba	92 tons	70-ft tower	3	0625	18 Oct
Wrangell	115 tons	1,500-ft balloon	FF	0850	22 Oct
Socorro	6.3 kt	1,500-ft balloon	7b	0530	22 Oct

TABLE 3 SUMMARY OF RESULTS

Shot	Observation Post Location	Slant Range meters	Camera Serial Number	ND Filter	Automatic Actuator Type *	Actuator Operated	Image Definition
Observation Post No. 1:							
Mora	736/790	29,000	2	2	M	Yes	Poor
Quay	736/790	29,000	2, 5	3, 4	UM, M	Yes and No	Good
Lea	736/790	29,000	2	4	UM	Yes	Good
Hamilton	736/790	22,000	2, 5	3	UM, M	No	None
Dona Ana	736/790	29,000	2, 5	3, 4	UM, M	Yes	Good
Rio Arriba	736/033	11,000	2, 8, 5	4	UM, M	Yes	Good
Wrangell	736/790	22,000	2	4	M	Yes	Good
Socorro	736/790	29,000	2	4	M	Yes	Good
Observation Post No. 2:							
Mora	854/875	17,000	8	3	UM	Yes	Good
Quay	854/875	17,000	8	4	UM	Yes	Poor
Lea	854/875	17,000	8	4	M	Yes	Good
Hamilton	837/830	15,000	8	4	M	No	None
Dona Ana	854/875	17,000	8	3	M	Yes	Good
Rio Arriba	843/024	3,600	3	4	UM	Yes	Good
Observation Post No. 3:							
Mora	790/940	12,800	3	4	UM	Yes	Good
Quay	843/946	7,500	3	4	UM	Yes	Good
Lea	790/940	12,800	3	4	UM	Yes	Good
Hamilton	880/713	7,000	3	4	UM	No	None
Dona Ana	843/946	7,500	3	4	UM	Yes	Good
Socorro	790/940	12,800	3	4	UM	Yes	Good
Observation Post No. 4:							
Lea	204/175	97,000	5	None	M	Yes	Poor
Wrangell	204/175	77,000	8, 5	1, 2	UM, M	No	None
Socorro	204/175	97,000	8, 5	1, 2	UM, M	No	None

* M, modified actuator; UM, unmodified actuator.




Figure 2 Peerless flash-ranging set, AN/TVS-1 (XE-3), showing camera with 5-inch lens.




Figure 1 Peerless flash-ranging set, AN/TVS-1 (XE-3), showing camera with 20-inch lens, automatic actuator, camera mount, leveler, tripod, control box, and battery box.

DISTRIBUTION

Military Distribution Category 82

ARMY ACTIVITIES

- 1 Deputy Chief of Staff for Military Operations, D/A, Washington 25, D.C. ATTN: Dir. of EM&R
- 1 Chief of Research and Development, D/A, Washington 25, D.C. ATTN: Atomic Div.
- 1 Assistant Chief of Staff, Intelligence, D/A, Washington 25, D.C.
- 2 Chief Chemical Officer, D/A, Washington 25, D.C.
- 1 Chief of Engineers, E/A, Washington 25, D.C. ATTN: ENGB
- 1 Chief of Engineers, D/A, Washington 25, D.C. ATTN: ENGB
- 1 Chief of Engineers, D/A, Washington 25, D.C. ATTN: ENGB
- 2 Office, Chief of Ordnance, D/A, Washington 25, D.C. ATTN: CRODT
- 1 Chief Signal Officer, D/A, Research and Development Div., Washington 25, D.C. ATTN: SIGRD-4
- 1 The Surgeon General, D/A, Washington 25, D.C. ATTN: MEDNE
- 3 Commanding General, U.S. Continental Army Command, Ft. Monroe, Va.
- 1 Director of Special Weapons Development Office, Headquarters COMUSC, Ft. Bliss, Tex. ATTN: Capt. Chester I. Peterson
- 1 President, U.S. Army Artillery Board, Ft. Sill, Okla.
- 1 President, U.S. Army Infantry Board, Ft. Benning, Ga.
- 1 President, U.S. Army Air Defense Board, Ft. Bliss, Tex.
- 1 President, U.S. Army Aviation Board, Ft. Rucker, Ala. ATTN: ATPG-DG
- 1 Commandant, U.S. Army Command & General Staff College, Ft. Leavenworth, Kansas. ATTN: ARCHIVES
- 1 Commandant, U.S. Army Air Defense School, Ft. Bliss, Tex. ATTN: Command & Staff Dept.
- 1 Commanding General, Chemical Corps Training Comd., Ft. McClellan, Ala.
- 1 Commanding Officer, U.S. Army Research Lab., Ft. Monck, Ky.
- 1 Commanding General, QM R&D Comd., QM R&D Cntr., Watich, Mass. ATTN: CBR Liaison Officer
- 1 Commanding General, U.S. Army Chemical Corps, Research and Development Comd., Washington 25, D.C.
- 1 Commanding Officer, Chemical Warfare Lab., Army Chemical Center, Md. ATTN: Tech. Library
- 1 Commanding Officer, Office of Ordnance Research, Box CM, Duke Station, Durham, North Carolina
- 1 Commanding Officer, Picatinny Arsenal, Dover, N.J. ATTN: ORCDBB-TX
- 1 Commanding Officer, Diamond Ord. Fuze Labs., Washington 25, D.C. ATTN: Chief, Nuclear Vulnerability Br. (230)
- 1 Commanding General, Aberdeen Proving Grounds, Md. ATTN: Director, Ballistics Research Laboratory
- 2 Commanding General, U.S. Army Ord. Missile Command, Redstone Arsenal, Ala.
- 1 Commander, Army Rocket and Guided Missile Agency, Redstone Arsenal, Ala. ATTN: Tech Library
- 1 Commanding General, White Sands Missile Range, N. Mex. ATTN: ORDBS-OM-TL
- 1 Commander, Army Ballistic Missile Agency, Redstone Arsenal, Ala. ATTN: ORDAB-HT
- 1 Commanding Officer, USA Signal R&D Laboratory, Ft. Monmouth, N.J.
- 1 Commanding General, USA Combat Surveillance Agency, 1124 N. Highland St., Arlington, Va.
- 1 Commanding Officer, USA, Signal R&D Laboratory, Ft. Monmouth, N.J. ATTN: Tech. Doc. Ctr., Evans Area
- 1 Director, Operations Research Office, Johns Hopkins University, 6935 Arlington Rd., Bethesda 14, Md.
- 1 Commanding General, U. S. ORD Special Weapons-Ammunition Command, Dover, N.J.

NAVY ACTIVITIES

- 2 Chief of Naval Operations, D/N, Washington 25, D.C. ATTN: OP-03EG

- 1 Chief of Naval Operations, D/N, Washington 25, D.C. ATTN: OP-75
- 1 Chief of Naval Operations, D/N, Washington 25, D.C. ATTN: OP-922G1
- 2 Chief of Naval Research, D/N, Washington 25, D.C. ATTN: Code 811
- 3 Chief, Bureau of Naval Weapons, D/N, Washington 25, D.C. ATTN: DLI-3
- 5 Chief, Bureau of Naval Weapons, D/N, Washington 25, D.C. ATTN: RAAD-25
- 1 Chief, Bureau of Ordnance, D/N, Washington 25, D.C.
- 1 Chief, Bureau of Naval Weapons, D/N, Washington 25, D.C. ATTN: SP-43
- 1 Chief, Bureau of Ships, D/N, Washington 25, D.C. ATTN: Code 423
- 1 Chief, Bureau of Yards and Docks, D/N, Washington 25, D.C. ATTN: D-440
- 1 Director, U.S. Naval Research Laboratory, Washington 25, D.C. ATTN: Mrs. Katherine E. Cass
- 2 Commander, U.S. Naval Ordnance Laboratory, White Oak, Silver Spring 19, Md.
- 1 Director, Material Lab. (Code 900), New York Naval Shipyard, Brooklyn 1, N.Y.
- 1 Commanding Officer and Director, Navy Electronics Laboratory, San Diego 52, Calif.
- 2 Commanding Officer, U.S. Naval Radiological Defense Laboratory, San Francisco, Calif. ATTN: Tech. Info. Div.
- 1 Commanding Officer and Director, U.S. Naval Civil Engineering Laboratory, Port Hueneme, Calif. ATTN: Code L31
- 1 Commanding Officer, U.S. Naval Schools Command, U.S. Naval Station, Treasure Island, San Francisco, Calif.
- 1 Superintendent, U.S. Naval Postgraduate School, Monterey, Calif.
- 1 Officer-in-Charge, U.S. Naval School, CMC Officers, U.S. Naval Construction Bn. Center, Port Hueneme, Calif.
- 1 Commanding Officer, Nuclear Weapons Training Center, Atlantic, U.S. Naval Base, Norfolk 11, Va. ATTN: Nuclear Warfare Dept.
- 1 Commanding Officer, Nuclear Weapons Training Center, Pacific, Naval Station, San Diego, Calif.
- 1 Commanding Officer, U.S. Naval Damage Control Tng. Center, Naval Base, Philadelphia 12, Pa. ATTN: AGC Defense Course
- 1 Commanding Officer, Air Development Squadron 5, VFA-5, China Lake, Calif.
- 1 Commanding Officer, Naval Air Material Center, Philadelphia 12, Pa. ATTN: Technical Data Br.
- 1 Commanding Officer, U.S. Naval Air Development Center, Johnsville, Pa. ATTN: NAS, Librarian
- 1 Commanding Officer, U.S. Naval Medical Research Institute, National Naval Medical Center, Bethesda, Md.
- 1 Officer-in-Charge, U.S. Naval Supply Research and Development Facility, Naval Supply Center, Bayonne, N.J.
- 1 Commandant, U.S. Marine Corps, Washington 25, D.C. ATTN: Code AO3H
- 1 Director, Marine Corps Landing Force, Development Center, MCS, Quantico, Va.
- 1 Commanding Officer, U.S. Naval CIC School, U.S. Naval Air Station, Glynco, Brunswick, Ga.
- 9 Chief, Bureau of Naval Weapons, Navy Department, Washington 25, D.C. ATTN: RRL2

AIR FORCE ACTIVITIES

- 1 Air Force Technical Application Center, HQ. USAF, Washington 25, D.C.
- 1 Hq. USAF, ATTN: Operations Analysis Office, Official Vice Chief of Staff, Washington 25, D. C.

- 11 HQ. USAF, Washington 25, D.C. ATTN: AFCIN-3D1,
Rm. 4B137, Pentagon
- 1 Director of Research and Development, DCS/D, HQ. USAF,
Washington 25, D.C. ATTN: Guidance and Weapons Div.
- 1 The Surgeon General, HQ. USAF, Washington 25, D.C.
ATTN: Bio.-Def. Pres. Med. Division
- 1 Commander, Tactical Air Command, Langley AFB, Va. ATTN:
Doc. Security Branch
- 1 Commander, Air Defense Command, Ent AFB, Colorado.
ATTN: Operations Analysis Section, ADOOA
- 1 Commander, Hq. Air Research and Development Command,
Andrews AFB, Washington 25, D.C. ATTN: RDRWA
- 1 Commander, Air Force Ballistic Missile Div. Hq. ARDC, Air
Force Unit Post Office, Los Angeles 45, Calif. ATTN: WDSOT
- 2 Commander, AF Cambridge Research Center, L. G. Hanscom
Field, Bedford, Mass. ATTN: CRQST-2
- 5 Commander, Air Force Special Weapons Center, Kirtland AFB,
Albuquerque, N. Mex. ATTN: Tech. Info. & Intel. Div.
- 2 Director, Air University Library, Maxwell AFB, Ala.
- 1 Commander, Lowry Technical Training Center (TW),
Lowry AFB, Denver, Colorado.
- 1 Commandant, School of Aviation Medicine, USAF, Aerospace
Medical Center (ATC), Brooks Air Force Base, Tex.
ATTN: Col. G. L. Hekhuis
- 1 Commander, 1009th Sp. Wpns. Squadron, HQ. USAF, Washington
25, D.C.
- 3 Commander, Wright Air Development Center, Wright-Patterson
AFB, Dayton, Ohio. ATTN: WCACT (For WCOSI)
- 2 Director, USAF Project RAND, VIA: USAF Liaison Office,
The RAND Corp., 1700 Main St., Santa Monica, Calif.
- 1 Chief, Ballistic Missile Early Warning Project Office,
L. G. Hanscom AFB, Bedford, Mass. ATTN: Col. Leo V.
Skinner, USAF
- 1 Commander, Air Technical Intelligence Center, USAF,
Wright-Patterson AFB, Ohio. ATTN: AFCIN-4B1a, Library
- 1 Assistant Chief of Staff, Intelligence, HQ. USAF, APO
633, New York, N.Y. ATTN: Directorate of Air Targets
- 1 Commander-in-Chief, Pacific Air Forces, APO 953, San
Francisco, Calif. ATTN: PFCIE-MB, Base Recovery
- OTHER DEPARTMENT OF DEFENSE ACTIVITIES
- 1 Director of Defense Research and Engineering, Washington 25,
D.C. ATTN: Tech. Library
- 1 Director, Weapons Systems Evaluation Group, Room 1E880,
The Pentagon, Washington 25, D.C.
- 4 Chief, Defense Atomic Support Agency, Washington 25, D.C.
ATTN: Document Library
- 1 Commander, Field Command, DASA, Sandia Base, Albuquerque,
N. Mex.
- 1 Commander, Field Command, DASA, Sandia Base, Albuquerque,
N. Mex. ATTN: FCFO
- 2 Commander, Field Command, DASA, Sandia Base, Albuquerque,
N. Mex. ATTN: FCWT
- 1 Commander-in-Chief, Strategic Air Command, Offutt AFB,
Nebr. ATTN: OAMS
- U.S. Documents Officer, Office of the United States
National Military Representative - SHAPE, APO 55,
New York, N.Y.
- 1 SAC (SUP3.1), Offutt AFB, Nebr.
- ATOMIC ENERGY COMMISSION ACTIVITIES
- 3 U.S. Atomic Energy Commission, Technical Library, Washing-
ton 25, D.C. ATTN: For DMA
- 2 Los Alamos Scientific Laboratory, Report Library, P.O.
Box 1663, Los Alamos, N. Mex. ATTN: Helen Redman
- 5 Sandia Corporation, Classified Document Division, Sandia
Base, Albuquerque, N. Mex. ATTN: H. J. Smyth, Jr.
- 10 University of California Lawrence Radiation Laboratory,
P.O. Box 808, Livermore, Calif. ATTN: Clovia G. Craig
- 1 Weapon Data Section, Office of Technical Information
Extension, Oak Ridge, Tenn.
- 31 Office of Technical Information Extension, Oak Ridge,
Tenn. (Surplus)

UNCLASSIFIED

UNCLASSIFIED