

UNCLASSIFIED


AD NUMBER
AD465132
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; APR 1965. Other requests shall be referred to Office of Naval Research, 800 North Quincy Street, Arlington, VA 22217-5660.
AUTHORITY
ONR ltr, 4 May 1977

THIS PAGE IS UNCLASSIFIED

CATALOGED BY: DDC

AS AD NO.

AD 465132



HYDRONAUTICS, incorporated research in hydrodynamics

Research, consulting, and advanced engineering in the fields of NAVAL and INDUSTRIAL HYDRODYNAMICS. Offices and Laboratory in the Washington, D. C., area: Pindell School Road, Howard County, Laurel, Md.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

HYDRONAUTICS, Incorporated

TECHNICAL REPORT 231-7

ON THE SURFACE WAVE PATTERN OF
SUBMERGED BODIES
STARTED FROM REST

By

C. C. Hsu

April 1965

Prepared Under
Office of Naval Research
Department of the Navy
Contract No. Nonr 3688(00)
NR 220-016

HYDRONAUTICS, Incorporated

-1-

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT.....	1
INTRODUCTION.....	2
GENERAL FORMULATION.....	2
SURFACE WAVE PROFILES.....	7
NUMERICAL RESULTS AND DISCUSSION.....	12
REFERENCES.....	17

HYDRONAUTICS, Incorporated

-11-

LIST OF FIGURES

- Figure 1 - Definition Sketch
- Figure 2 - Surface Wave Pattern of a Submerged Body Started Impulsively From Rest
- Figure 3 - Amplitude of the Initial Unsteady Disturbance With t as a Varying Parameter
- Figure 4 - Amplitude of the Initial Unsteady Disturbance With x as a Varying Parameter
- Figure 5 - Comparison of Theoretical and Experimental Centerline Wave Profiles Due to a Submerged 9 Feet Long, 7 to 1, Rankine Ovoid Started from Rest

NOTATION

f	depth of submergence measured from the centerline of the body
g	gravitational acceleration
M	strength of point source
$\vec{q}$	velocity vector
R	radial distance from source or sink
t	time
U	forward speed
x, y, z	rectangular cartesian coordinates
φ	velocity potential
ζ	wave height
ζ_r	regular wave height
ζ_l	local disturbance
ζ_s	steady wave height
ζ_1	unsteady disturbance
$\bar{\zeta}_s, \bar{\zeta}_1$	amplitude of the steady wave and unsteady disturbance, respectively

ABSTRACT

The initial surface wave pattern due to a submerged body started from rest with uniform speed in a perfect fluid is studied. The mean surface elevations may, in general, be separated into three parts: (i) A steady local disturbance which travels both upstream and downstream and diminishes as the distance from the body increases, (ii) a group of steady regular waves which travel downstream from the origin $x = x - x_0 = 0$ to $x = 1/2 Ut$ with group velocity $1/2 U$, and (iii) a time-dependent cylindrical disturbance which travels both upstream and downstream and diminishes rapidly as time increases. For sufficiently long time t , the general expression for the unsteady disturbance can be obtained by the method of stationary phase. It is found that for a given finite value of t , the effect of the unsteady disturbance becomes more serious as the downstream distance from the body increases. It is also shown that the initial unsteady effect is, at lower Froude numbers, more persistent and therefore takes a longer time to subside. A comparison of the predicted centerline wave profile due to a submerged 9 feet long, 7 to 1, Rankine ovoid started from rest with DTMB data has been made; the results are in very good agreement.

INTRODUCTION

The problem of submerged bodies or ships in accelerated motion is primarily of interest in connection with towing-tank experiments. No matter how quickly the final desired speed is attained by the model, the question always arises as to how long it takes before the effect of the starting conditions becomes inappreciable. This question has been discussed by Havelock (1), (2), Maruo (3) and Wehausen (4) in dealing with the wave resistance of submerged bodies or of thin ships. The effect of the initial acceleration upon the wave pattern of submerged bodies has received, however, very little attention. It is the purpose of this report to investigate the surface wave pattern of simple submerged bodies started from rest. The result is of practical importance in connection with the experimental determination in towing tanks of the surface waves made by submarine models. The theoretical results for the particular case of a Rankine body are compared with experiments conducted at the David Taylor Model Basin.

GENERAL FORMULATION

The governing equation for submerged bodies moving through an incompressible, inviscid fluid in irrotational motion may be shown to be

$$\nabla^2 \varphi = \frac{\partial^2 \varphi}{\partial x^2} + \frac{\partial^2 \varphi}{\partial y^2} + \frac{\partial^2 \varphi}{\partial z^2} = 0 \quad [1]$$

where

x, y, z are the cartesian coordinates and the origin is taken on the mean free surface with $O-z$ vertically upwards,

φ is the perturbation velocity potential and is assumed to be small.

The perturbed fluid velocity $\vec{q}(u, v, w)$ is given by

$$\vec{q} = -\nabla\varphi = -\text{grad } \varphi \quad [2]$$

The linearized boundary conditions at the free surface may be expressed as

$$\left. \begin{aligned} \frac{\partial\varphi}{\partial t} - g\zeta &= \text{const.} && (\text{dynamical condition}) \\ \frac{\partial\varphi}{\partial z} + \frac{\partial\zeta}{\partial t} &= 0 && (\text{kinematic condition}) \end{aligned} \right\} \text{at } z = 0 \quad [3]$$

where ζ is the free surface elevation,
 g the gravitational acceleration, and
 t the time variable.

At the rigid submerged body surface it is evident that the condition

$$\frac{\partial(\varphi + Ux)}{\partial n} = 0 \quad [4]$$

must hold, in which $\frac{\partial}{\partial n}$ represents differentiation along the normal to the boundary surface and where U is the free stream velocity.

Boundary condition [4] can generally be satisfied by distributing appropriate singularities inside or on the surface of the body. In order to satisfy boundary conditions [3] and [4] simultaneously, a complementary function, in addition to the prescribed singularities, is needed. It can be shown, Reference 3, that the total velocity potential must have the form

$$\varphi = \varphi_0 + \varphi_1$$

$$= \varphi_0 - \bar{\varphi}_0 + \frac{1}{\pi} \int_0^t d\tau \int_{-\pi}^{\pi} d\theta \int_0^{\infty} G(\kappa, \theta, \tau) e^{\kappa(z-1\tilde{w})} \sin\{\sqrt{g\kappa}(t-\tau)\} \sqrt{g\kappa} d\kappa \quad [5]$$

where

φ_0 is the velocity potential due to the prescribed singularities and depends mainly on the body shape

$\bar{\varphi}_0$ is the image of φ_0

$$G(\kappa, \theta, \tau) = -\frac{1}{4\pi} \int_{S'} \left(\frac{\partial \varphi_0}{\partial n} - \varphi_0 \frac{\partial}{\partial n} \right) e^{\kappa(z+1\tilde{w})} dS$$

S' is an arbitrary surface enclosing the singularities

$$\tilde{w} = x \cos \theta + y \sin \theta.$$

Consider now the special case of a Rankine body (ovoid) submerged in water at a given depth, as shown in Figure 1, suddenly started from rest with a given velocity U and maintaining that speed. For a first order approximation, the fluid motion may be taken to be that due to a point source and a point sink of strength $|M|$ distributed at the points $(0,0,-f)$ and $(C,t,-f)$ respectively. The velocity potential φ_o due to an impulsive point source or sink at (x_n, y_n, z_n) is given by

$$\varphi_o = \frac{M_n}{R_n} \quad [6]$$

where

$$M_n(t) = 0 \quad t \leq 0$$

$$M_n(t) = M_n = \text{constant} \quad t > 0$$

$$R_n = \sqrt{(x-x_n)^2 + (y-y_n)^2 + (z-z_n)^2}$$

The function G of Equation [5] in this case is simply

$$G = M_n e^{\kappa[z_n + 1(x_n \cos \theta + y_n \sin \theta)]} \quad [7]$$

Substituting Equation [7] into Equation [5] gives

HYDRONAUTICS, Incorporated

-6-

$$\varphi = \frac{M_n}{R_n} - \frac{M_n}{R_n} + \frac{1}{\pi} \int_0^t M_n(\tau) d\tau \int_{-\pi}^{\pi} d\theta \int_0^{\infty} e^{\kappa(z+z_n)} \cos \kappa \tilde{w}_n' \sin \left\{ \sqrt{g\kappa}(t-\tau) \right\} \sqrt{g\kappa} d\kappa \quad [8]$$

where

$$\bar{R}_n = \sqrt{(x-x_n)^2 + (y-y_n)^2 + (z+z_n)^2}$$

$$\tilde{w}_n' = (x-x_n) \cos \theta + (y-y_n) \sin \theta$$

The total velocity potential for a Rankine ovoid started impulsively from rest with uniform velocity can then be shown to be

$$\varphi = \varphi_{\text{source}} + \varphi_{\text{sink}}$$

$$\begin{aligned} &= M \left[\frac{1}{\sqrt{x^2+y^2+(z+f)^2}} - \frac{1}{\sqrt{x^2+y^2+(z-f)^2}} + \frac{1}{\sqrt{(x+l)^2+y^2+(z-f)^2}} - \frac{1}{\sqrt{(x+l)^2+y^2+(z+f)^2}} \right] \\ &+ \frac{1}{\pi} \int_0^t M(\tau) d\tau \int_{-\pi}^{\pi} d\theta \int_0^{\infty} e^{-\kappa f + \kappa z} \left[\cos \kappa \tilde{w}_1' - \cos \kappa \tilde{w}_2' \right] \sin \left\{ \sqrt{g\kappa}(t-\tau) \right\} \sqrt{g\kappa} d\kappa \end{aligned} \quad [9]$$

with

$$\tilde{w}_1' = x \cos \theta + y \sin \theta$$

$$\tilde{w}_2' = (x+l) \cos \theta + y \sin \theta$$

l = distance between the point source and sink

SURFACE WAVE PROFILES

It is seen from Equation [3] that the mean free surface elevations can be expressed as

$$\zeta \approx \left. \frac{1}{g} \frac{\partial \varphi}{\partial t} \right|_{z=0}$$

$$= \frac{1}{g} \frac{\partial}{\partial t} (\varphi_0 - \bar{\varphi}_0) + \frac{1}{\pi} \int_0^t d\tau \int_{-\pi}^{\pi} d\theta \int_0^{\infty} \kappa G(\kappa, \theta, \tau) e^{\kappa(z-i\tilde{w})} \cos \left\{ \sqrt{g\kappa} (t-\tau) \right\} d\kappa \Big|_{\text{at } z=0}$$

[10]

Consider first the case of an impulsive point source started from rest with velocity U which is maintained constant; the mean surface wave height can then be expressed as

$$\zeta = \frac{1}{\pi} \operatorname{Re} \int_0^t M(\tau) d\tau \int_{-\pi}^{\pi} d\theta \int_0^{\infty} \kappa e^{-\kappa f} e^{i\kappa \tilde{w}} \cos \sqrt{g\kappa} (t-\tau) d\kappa \quad [11]$$

with

$$\tilde{w} = [(x-x_0) + U(t-\tau)] \cos \theta + y \sin \theta$$

Re denotes the real part of

Integrating with respect to τ , Equation [11] becomes

$$\begin{aligned}
\zeta = & \frac{1}{2\pi} \left(\frac{M}{U} \right) R_L \int_{-\pi}^{\pi} d\theta \int_0^{\infty} \left\{ 1 \frac{2\kappa \sec \theta}{\kappa - \frac{g}{U^2} \sec^2 \theta} e^{-\kappa f + i\kappa[(x-x_0)\cos\theta + y\sin\theta]} \right. \\
& + \frac{\kappa}{1} e^{-\kappa f + i\kappa[(x-x_0)\cos\theta + y\sin\theta]} \left[\frac{e^{\frac{1}{\kappa}(\kappa U \cos\theta - \sqrt{g\kappa})t}}{\kappa \cos\theta - \sqrt{\frac{g}{U^2}} \kappa} + \frac{e^{\frac{1}{\kappa}(\kappa U \cos\theta + \sqrt{g\kappa})t}}{\kappa \cos\theta + \sqrt{\frac{g}{U^2}} \kappa} \right] \Bigg\} d\kappa d\theta \\
= & \zeta_s + \zeta_1
\end{aligned} \tag{12}$$

The limiting value of the regular wave ζ_r as t becomes infinite may be derived from the principle values of the integrals in Equation [12]. The steady local disturbance ζ_l arises from the first integral in Equation [12]. The steady surface wave pattern ($\zeta_s = \zeta_r + \zeta_l$) due to a point source has been discussed in detail in a previous report by Yim (5). The primary interest here is to evaluate approximately the effect the initial time-dependent disturbances have on the general wave profiles.

For sufficiently large positive values of t , the surface wave heights due to the initial disturbances may be evaluated from the following double integral by applying the method of stationary phase twice in succession:

$$\zeta_1 = \frac{1}{\pi} \frac{M}{U} R \ell \left\{ \int_{-\pi/2}^{\pi/2} d\theta \int_0^{\infty} \frac{\kappa e^{-\kappa f}}{1} \left[\frac{e^{1(\kappa \bar{w}_1 - \sqrt{g\kappa}t)}}{\kappa \cos \theta - \sqrt{\frac{g}{U^2}} \kappa} + \frac{e^{1(\kappa \bar{w}_1 + \sqrt{g\kappa}t)}}{\kappa \cos \theta + \sqrt{\frac{g}{U^2}} \kappa} \right] d\kappa \right\} \quad [13]$$

with

$$\bar{w}_1 = [(x - x_0) + Ut] \cos \theta + y \sin \theta = R_1 \cos(\theta - \delta_1) > 0$$

$$R_1 = \sqrt{(x - x_0 + Ut)^2 + y^2}$$

$$\delta_1 = \tan^{-1} \left(\frac{y}{x - x_0 + Ut} \right)$$

Evaluating first with respect to κ , Equation [13] has the form

$$\zeta_1 \approx \frac{1}{\sqrt{\pi}} \frac{M}{U} R \ell \left\{ \frac{1}{1} \int_{-\pi/2}^{+\pi/2} \frac{\exp \left[\frac{gt^2 f}{4R_1^2 \cos^2(\theta - \delta_1)} - 1 \left(\frac{gt^2}{4R_1 \cos(\theta - \delta_1)} - \frac{\pi}{4} \right) \right] d\theta}{\sqrt{\frac{R_1^2 \cos^2(\theta - \delta_1)}{gt^2}} \left(\cos \theta - \frac{2R_1 \cos(\theta - \delta_1)}{Ut} \right)} \right\} \quad [14]$$

The initial wave heights ζ_1 for sufficiently large time t , may then be shown to be

$$\zeta_1 \approx \frac{M}{U} R_l \left\{ \frac{1}{1} \frac{\exp \left[\frac{-gt^2}{4R_1^3} f - 1 \frac{gt^2}{4R_1} \right]}{\left(\sqrt{\frac{1}{8} \left| \frac{-gt^2}{R_1} \right|} \right) \sqrt{\frac{R_1^3}{gt^2} \left(\cos \delta_1 - \frac{2R_1}{Ut} \right)}} \right\}$$

$$= -2 \sqrt{2} \frac{M}{U} \frac{e^{\frac{-gt^2}{4R_1^3} f}}{R_1 \left(\cos \delta_1 - \frac{2R_1}{Ut} \right)} \sin \frac{gt^2}{4R_1} \quad [15]$$

This formula however is not valid in the neighborhood of $R_1 = 0$ and $R_1 = Ut/2 \cos \delta_1$ since in these regions the non-circular part of the integrand in Equation [14] varies rather rapidly and the method of stationary phase therefore fails to apply. The correct evaluation of ζ_1 around these points, which is generally very tedious and has little bearing on the outcome, will not be pursued further.

The mean water free surface elevation due to a Rankine ovoid started impulsively from rest with constant velocity U can be obtained by superposing the values due to a point source and sink with distance l apart. The resulting disturbance may be separated into three parts as Havelock did in (1) for the two-dimensional case (see Figure 2).

(1) A steady local disturbance (ζ_l) which traveled both upstream and downstream and diminishes as the distance from the body increases.

(ii) A group of steady regular waves (ζ_r) which travel downstream from the origin $x-x_0=x=0$ only to $x = -1/2 Ut$ with group velocity $1/2 U$, and behave like $x^{-1/2}$ far downstream ($1 \ll x/\lambda < Ut/2\lambda$).

(iii) A time-dependent cylindrical disturbance (ζ_1) which travels both upstream and downstream and diminishes rapidly as time increases.

The first two parts have been studied in (5). The last part, for sufficiently long time t , is simply

$$\zeta_1 \approx -2/2 \frac{M}{U} \left\{ \frac{e^{\frac{-gt^2}{4R_1^2}} f \sin \frac{gt^2}{4R_1}}{R_1 \left(\cos \delta_1 - \frac{2R_1}{Ut} \right)} - \frac{e^{\frac{-gt^2}{4R_2^2}} f \sin \frac{gt^2}{4R_2}}{R_2 \left(\cos \delta_2 - \frac{2R_2}{Ut} \right)} \right\} \quad [16]$$

where

$$R_1 = \sqrt{(x+Ut)^2 + y^2}, \quad R_2 = \sqrt{(x+l+Ut)^2 + y^2} \quad \text{respectively.}$$

$$\delta_1 = \tan^{-1} \left(\frac{y}{x+Ut} \right), \quad \delta_2 = \tan^{-1} \left(\frac{y}{x+l+Ut} \right)$$

In order to assess quantitatively the initial unsteady disturbance on the overall wave motion, simple numerical calculations are made in the following section.

NUMERICAL RESULTS AND DISCUSSION

For simplicity only the waves on the centerline of the mean water free surface due to a Rankine ovoid started impulsively from rest are to be discussed in detail here. From Equation [16], taking $y = 0$, the unsteady cylindrical wave pattern ζ_1 for sufficiently long time takes the form

$$\zeta_1 = +2\sqrt{2} \left(\frac{M}{U} \right) \left(\frac{1}{Ut} \right) \left\{ \frac{e^{-\frac{gf}{4U^2 \left(1 + \frac{x}{Ut}\right)^2}} \sin \left[\frac{gt}{4U \left(1 + \frac{x}{Ut}\right)} \right]}{\left(1 + \frac{x}{Ut}\right) \left(1 + \frac{2x}{Ut}\right)} - \frac{e^{-\frac{gf}{4U^2 \left(1 + \frac{x+l}{Ut}\right)^2}} \sin \left[\frac{gt}{4U \left(1 + \frac{x+l}{Ut}\right)} \right]}{\left(1 + \frac{x+l}{Ut}\right) \left[1 + \frac{2(x+l)}{Ut}\right]} \right\}$$

$$= \bar{\zeta}_1 \left\{ \sin \left[\frac{gt}{4U \left(1 + \frac{x}{Ut}\right)} \right] - A_1 \sin \left[\frac{gt}{4U \left(1 + \frac{x+l}{Ut}\right)} \right] \right\} \quad [17]$$

where

$$\bar{\zeta}_1 = 2\sqrt{2} \left(\frac{M}{U} \right) \left(\frac{1}{Ut} \right) \frac{e^{-\frac{1}{4F^2 \left(1 + \frac{x}{Ut}\right)^2}}}{\left(1 + \frac{x}{Ut}\right) \left(1 + \frac{2x}{Ut}\right)}$$

is defined as the amplitude of the cylindrical unsteady disturbance,

$$A_1 = \frac{\left(1 + \frac{x}{Ut}\right) \left(1 + \frac{2x}{Ut}\right)}{\left(1 + \frac{x+l}{Ut}\right) \left[1 + \frac{2(x+l)}{Ut}\right]} \exp \left\{ -\frac{1}{4F^2} \left[\frac{1}{\left(1 + \frac{x+l}{Ut}\right)^2} - \frac{1}{\left(1 + \frac{x}{Ut}\right)^2} \right] \right\} \text{ is,}$$

in general, of $O(1)$,

$F = \frac{U}{\sqrt{gf}}$ is the Froude number based on depth.

It can be seen that the amplitude of the unsteady cylindrical wave, $\bar{\zeta}_1$, for a fixed value of x , diminishes rapidly like $1/t$ with increasing t . At a given time t , the value of $\bar{\zeta}_1$ decreases upstream but increases downstream as the distance from the body increases. It is, therefore, to be expected, that the effect of the unsteady cylindrical disturbance on the general steady wave pattern would be more serious far downstream. To illustrate, it is assumed that the distance from the body downstream is sufficiently large so that the steady local disturbance is negligibly small and the regular wave can be evaluated by the method of stationary phase, i.e.,

$$\zeta_s = \zeta_l + \zeta_s \approx \zeta_s$$

$$\begin{aligned} &\approx 4 \frac{M}{U} \left(\frac{2\pi g}{U^2} \right)^{\frac{1}{2}} e^{-\frac{1}{F^2}} \left[\frac{1}{|x|^{\frac{1}{2}}} \cos \left(\frac{g|x|}{U^2} + \frac{\pi}{4} \right) - \frac{1}{|x+l|^{\frac{1}{2}}} \cos \left(\frac{g|x+l|}{U^2} + \frac{\pi}{4} \right) \right] \\ &= \bar{\zeta}_s \left[\cos \left(\frac{g|x|}{U^2} + \frac{\pi}{4} \right) - A_s \cos \left(\frac{g|x+l|}{U^2} + \frac{\pi}{4} \right) \right] \end{aligned} \quad [18]$$

where

$$\zeta_s = \pi \frac{M}{U} \left| \frac{1}{\lambda x} \right|^{\frac{1}{2}} e^{-\frac{1}{F^2}} \quad \text{is the amplitude of the steady wave profile far downstream} \\ (1 \ll x/\lambda < Ut/2\lambda)$$

$$A_s = \left| \frac{x}{x+l} \right|^{\frac{1}{2}} \sim 1 \quad (1)$$

$$\lambda = \frac{2\pi U^2}{g} \quad \text{is the centerline wave length}$$

From Equations [17] and [18], the amplitude ratio of the unsteady disturbance and the steady wave is found to be

$$\frac{\bar{\zeta}_1}{\bar{\zeta}_s} = \frac{1}{2\sqrt{2\pi}} \frac{|\lambda x|}{Ut} e^{-\frac{1}{F^2} \left[\frac{1}{4 \left(1 + \frac{x}{Ut}\right)^2} - 1 \right]} \\ = \frac{1}{2\sqrt{2\pi}} \left| \frac{1}{x\lambda} \right|^{\frac{1}{2}} \left| \frac{x}{Ut} \right| e^{-\frac{1}{F^2} \left[\frac{1}{4 \left(1 + \frac{x}{Ut}\right)^2} - 1 \right]} \quad [19]$$

The non-dimensional value of $\bar{\zeta}_1/\bar{\zeta}_s$, at $x/\lambda = 4$, versus Ut/λ for various Froude numbers F is shown in Figure 3. It can be seen that the value of $\bar{\zeta}_1$ diminishes very rapidly with increase in t .

In Figure 4 the amplitude ratio $\bar{\zeta}_1/\bar{\zeta}_s$, at $Ut/\lambda = 10$, is plotted against x/λ for various F . It is evident that the effect of the unsteady disturbance on the steady wave profile becomes more prominent (since the value of $\bar{\zeta}_1/\bar{\zeta}_s$ gets bigger) as the wave moves further downstream. It is also of interest to note from Figures 3 and 4, that the value of $\bar{\zeta}_1/\bar{\zeta}_s$ at a given x and t increases with decreasing F . This would seem to suggest the fact that the unsteady disturbance takes a much longer time to subside at the lower Froude numbers.

A preliminary experimental study of the Kelvin wake produced by submerged bodies has been made at the David Taylor Model Basin, (6). In those tests, a 9 feet long, 7 to 1, Rankine ovoid was towed at several submergence depths, and wave height measurements were made at various points in the basin. In Figure 5 the center-line wave pattern in a test run, at $U = 10$ ft/sec, $t = 13.22$ sec., and $F = 1.016$, together with the corresponding calculated values are shown. Since at distances very far downstream ($> 1/2 Ut$) the wave profile is entirely contributed by the unsteady disturbance as discussed in the previous section and is of no practical interest, the comparison between the theoretical calculations and experimental data is, therefore, made only from $x = 0$ (near the nose of the ovoid) extending downstream to the neighborhood of $1/2 Ut$. It is seen that the theory and experiment are in quite good agreement. The value of F , for the particular case studied, is rather large and the effect of unsteady disturbance on the steady surface wave profile is, in general, small as can be seen from Figure 3 or 4; the measured and the steady surface profiles

HYDRONAUTICS, Incorporated

-16-

are quite similar. At lower Froude numbers, say $F = 1/2$, however, the unsteady effect is considerably larger; it is to be expected then that the true steady surface wave pattern may have quite a departure from the measured values in this latter case.

HYDRONAUTICS, Incorporated

-17-

REFERENCES

1. Havelock, T. H., "The Wave Resistance of a Cylinder Started From Rest," Quarterly Journal of Mechanics and Applied Mathematics, Vol. II, pp. 325-334, 1949.
2. Havelock, T. H., "The Resistance of a Submerged Cylinder in Accelerated Motion," *ibid.*, Vol. II, pp. 419-427, 1949.
3. Maruo, H., "Modern Developments of the Theory of Wave-Making Resistance in the Non-Uniform Motion," The Society of Naval Architects of Japan, 60th Anniversary series, Vol. II, pp. 1-87, 1957.
4. Wehausen, J. V., "Effect of the Initial Acceleration Upon the Wave Resistance of Ship Models," Journal of Ship Research, Vol. 7, No. 3, 1964.
5. Yim, B., "Waves Due to a Submerged Body," HYDRONAUTICS, Incorporated Technical Report 231-3, May 1963.
6. "Preliminary Kelvin Wake Study," DTMB Test Report 039-H-01, December 1964

HYDRONAUTICS, INCORPORATED




FIGURE 1 - DEFINITION-SKETCH

HYDRONAUTICS, INCORPORATED




FIGURE 2--SURFACE WAVE PATTERN OF A SUBMERGED BODY STARTED IMPULSIVELY FROM REST




FIGURE 3 - AMPLITUDE OF THE INITIAL UNSTEADY DISTURBANCE
WITH t AS A VARYING PARAMETER




FIGURE 4 - AMPLITUDE OF THE INITIAL UNSTEADY DISTURBANCE
WITH x AS A VARYING PARAMETER




FIGURE 5 - COMPARISON OF THEORETICAL AND EXPERIMENTAL CENTERLINE WAVE PROFILES DUE TO A SUBMERGED 9 FEET LONG, 7 TO 1, RANKINE OVOID STARTED FROM REST

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) HYDRONAUTICS, Incorporated, Pindell School Rd. Howard County, Laurel, Maryland		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE ON THE SURFACE WAVE PATTERN OF SUBMERGED BODIES STARTED FROM REST			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Technical Report			
5. AUTHOR(S) (Last name, first name, initial) Hsu, C. C.			
6. REPORT DATE April 1965		7a. TOTAL NO. OF PAGES 26	7b. NO. OF REFS 6
8a. CONTRACT OR GRANT NO. Nonr 3688(00) NR220-016		9a. ORIGINATOR'S REPORT NUMBER(S) Technical Report 231-7	
b. PROJECT NO.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.			
d.			
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Office of Naval Research Department of the Navy	
13. ABSTRACT The initial surface wave pattern due to a submerged body started from rest with uniform speed in a perfect fluid is studied. The mean surface elevations may, in general, be separated into three parts: (i) A steady local disturbance which travels both upstream and downstream and diminishes as the distance from the body increases, (ii) a group of steady regular waves which travel downstream from the origin $x=0$ to $x=1/2 U t$ with group velocity $1/2 U$, and (iii) a time-dependent cylindrical disturbance which travels both upstream and downstream and diminishes rapidly as time increases. For sufficiently long time t , the general expression for the unsteady disturbance can be obtained by the method of stationary phase. It is found that for a given finite value of t , the effect of the unsteady disturbance becomes more serious as the downstream distance from the body increases. It is also shown that the initial unsteady effect is, at lower Froude numbers, more persistent and therefore takes a longer time to subside. A comparison of the predicted centerline wave profile due to a submerged 9 feet long, 7 to 1, Rankine ovoid started from rest with DTMB data has been made; the results are in very good agreement.			

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Submerged body						
2. Velocity potential						
3. Impulsive motion						
4. Surface waves						
5. Unsteady disturbance						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive S200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

DD FORM 1473 (BACK)

1 JAN 64

UNCLASSIFIED

Security Classification