

UNCLASSIFIED

AD NUMBER

AD467451

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

**Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 30 APR 1965.
Other requests shall be referred to Office of Naval Research, 875 North Randolph Street, Arlington, VA 22203-1995.**

AUTHORITY

ONR ltr dtd 4 May 1977

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

ARPA Order No. 306
Project Code No. 4730

THE PERKIN-ELMER CORPORATION
(Report No. 8011)

Absorption of Light in Gases

First Semiannual Technical Summary Report
through March 31, 1965

Submitted by

J. G. Atwood, Project Scientist

Phone No. (203) 847-0411


to the

OFFICE OF NAVAL RESEARCH

"Reproduction in Whole or in Part of this Report is Permitted for any Purpose of The United States Government."

This Research is part of Project DEFENDER under the joint sponsorship of the Advance Research Projects Agency, the Office of Naval Research, and the Department of Defense.

Contract No. Nonr-4661(00)
1 November, 1964 to 31 July, 1965
Amount of Contract - \$48,858.00



CATALOGED BY: DDC
AS AD NO. 467451

THE PERKIN-ELMER CORPORATION
E-O RESEARCH DEPARTMENT

Absorption of Light in Gases

First Semiannual Technical Summary Report
through March 31, 1965

Background and Objective

Our goal in this work is to study, optimize, and experimentally demonstrate acoustic detection of absorption of laser beams in gases. The outcome of the work will be a critical evaluation of the technique to determine whether it is suitable for a survey of extremely weak absorptions in the atmosphere, and as a sampling method for detection of trace constituents. We expect that in the course of the work, quantitative measurements in at least one laser wavelength region for air and some test gases will also be made.

Overall Plan

Apparatus for generating, detecting, and measuring acoustic pulses from absorbed laser light in gases is being designed, constructed, and calibrated. The overall equipment layout as we are planning it is shown in Figure 1. The pulsed laser fires through a gas sample contained in the acoustic chamber. Laser wavelength is varied by cooling the pulsed laser with the temperature control system. An energy monitor system records the relative energy of each laser burst.

Light absorption causes the gas in the laser beam to expand suddenly. The resulting sound wave is captured by the parabolic cylindrical reflector and focused by the paraboloidal reflector onto the microphone diaphragm. See Figure 2 for a back view of the acoustic chamber.

The diaphragm is a thin collodion membrane supported by a spider frame. It forms one end of the optical resonator associated with the single mode gas laser. See Figure 3 for details of the resonator. As in Figure 4, vibrations

of the membrane in response to the acoustic pulses cause the resonant beam of the laser to shift position on the nose of the sensing prism. The resulting signal imbalance from the photodetectors is amplified and displayed on the oscilloscope for photographically recording the amplitude of the acoustic pulse. The imbalance or difference signal is also fed back to piezoelectric drivers on the gas laser's resonant mirror for maintaining single mode operation.

Calibration equipment for recording the pulsed laser wavelength is shown to the right in Figure 1 and in more detail in Figure 5. The grating and etalon together provide high resolution, and the hollow cathode lamp gives a stable wavelength reference.

The acoustic calibrator is not shown in the overall layout. It is a cylindrical device for generating acoustic pulses of known amplitude in the pulsed laser beam path. This is necessary for making quantitative measurements.

Design of Acoustic System

We studied the factors bearing on the efficiency and signal to noise of the acoustic focusing system. The laser beam diameter sets the sound's average wavelength. This was chosen as 2 mm, as a compromise between greater efficiency of conversion for small beams and greater absorption coefficient for the propagated sound for short acoustic wavelengths.

The maximum sound frequencies present will be about 3×10^5 cycles/sec. Here air attenuates at 12 db/meter. Thus, a short acoustic path is essential. A "clamshell" arrangement was chosen with an aperture of 30 cm. The total air path is 50 cm, giving attenuation of 6 db at the highest frequencies.

Since the sound mirrors have a figure tolerance of the order of the shortest sound wavelength they are made of aluminum. Cams for controlling the machining are being designed in the Perkin-Elmer Scientific Computer Facility.

Optical-Thermal Relaxation Time

Since it is essential that the absorbed energy be released as heat in a time short compared to the transit time of sound across the beam, (which is

less than 3 microseconds), we had some concern about the speed of the thermal relaxation process, as it is known that slow relaxations are a cause of anomalous acoustic attenuation. Study indicates that for the optical energy levels we excite, the relaxation will be extremely fast, usually less than 10^8 seconds at 1 atmospheric pressure. It will be comparable to the lifetime associated with the pressure broadened linewidth of the optical bands observed.

Acoustic Detection System

The problem of building a microphone capable of reaching the Brownian noise limit at 100 to 300 kc requires a highly unconventional solution. First, in order to match the acoustic impedance of a transducer to the air so that acoustic noise energy will be freely transferred, we require a compliant diaphragm or ribbon so thin that it weighs less per unit area than a slab of air that is 1/10 of a sound wavelength in thickness. Acoustic waves of the Brownian noise pressure will then make this membrane move a few angstroms, or less than 1/1000 wavelength of light.

We will solve the problem by using a membrane mirror of the order of 1000 Angstroms thick as in a Golay infrared detector. Its motion will be measured by making it one reflector in an optical resonator illuminated by a frequency stabilized CW neon helium laser. (See Figure 3).

The frequency control system will keep the laser tuned to one mode of the mirror-membrane resonant cavity. Acoustic pulses will detune the resonator faster than the laser frequency control loop can follow. The acoustic signals will therefore be seen on the error signal of the frequency control loop. (See Figure 4).

The frequency controlled laser, a new single-mode unit designed on another project for very good short term stability and tight servo control, is almost complete.

Absorption Sensitivity

We reviewed the calculations of absorption sensitivity to determine a reasonable goal in this first experiment. The gas sample will be outside the

pulsed laser resonant cavity for simplicity. Also, the laser output power will be reduced somewhat by cooling. For a 0.05 joule pulse and a 2 mm diameter beam, it should be possible to measure absorptivities as small as 10^{-6} cm^{-1} , when the limiting noise is due to Brownian motion of the air. Measuring an absorptivity as small as 10^{-6} cm^{-1} will be a significant demonstration of the usefulness of the method, and probably will not require elaborate refinements.

Absolute Acoustic Calibration

Several methods of calibrating the acoustic chamber and detector have been conceived and studied. The plan is to generate a cylindrical acoustic pulse of known amplitude in the acoustic chamber by some device or physical process. We have estimated the performance of an electrically pulsed hot wire stretched in the laser beam path. We have also considered an electromagnetically expanded tube. The final method has not been chosen yet.

Pulsed Laser Construction

Design and construction of the pulsed laser has been deferred temporarily, because current research on another project at Perkin-Elmer on single mode lasers using cryptocyanine dyes appears to be very promising for this experiment. When this method of making single mode pulses has been thoroughly worked out on the other project, we will build a breadboard temperature scannable single mode laser for this project.

First Measurements

Some data on the fine structure of atmospheric attenuation is now available. In the wavelength region between $6941\overset{\circ}{\text{A}}$ and $6943\overset{\circ}{\text{A}}$ there are several weak absorptions, as shown in Figure 6. This region may be scanned by cooling the laser from 300°K down to 250°K approximately. We are planning to measure atmospheric absorptivity here as a first experiment. It will be necessary to measure the wavelength of each laser pulse with a resolution of 133. An etalon and grating have been chosen to do this. The etalon will provide resolving power, and the grating will separate the orders. A wavelength reference lamp has also been chosen for absolute calibration.




Figure 1. OVERALL LAYOUT




Figure 2. ACOUSTIC CHAMBER




Figure 3. ACOUSTIC DETECTOR AND LASER RESONATOR




Figure 4.
DIAGRAM OF FREQUENCY STABILIZED LASER SYSTEM AND ACOUSTIC DETECTOR





Figure 5. WAVELENGTH CALIBRATION

Figure 6. ATMOSPHERE ATTENUATION



DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Perkin-Elmer Corporation Electro-Optical Division, Norwalk, Conn.		2a. REPORT SECURITY CLASSIFICATION Unclassified		
		2b. GROUP		
3. REPORT TITLE ABSORPTION OF LIGHT IN GASES				
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) First Semiannual Technical Summary Report - 1 Nov. 64 - 31 Mar. 1965				
5. AUTHOR(S) (Last name, first name, initial) Atwood, John G.				
6. REPORT DATE 30 April 1965		7a. TOTAL NO. OF PAGES 10		7b. NO. OF REFS 0
8a. CONTRACT OR GRANT NO. Nonr-4661(00)		9a. ORIGINATOR'S REPORT NUMBER(S) PE Engineering Report No. 8011		
b. PROJECT NO. 4730				
c. TASK ARPA Order 306		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) None		
d.				
10. AVAILABILITY LIMITATION NOTICES "Qualified requestors may obtain copies of this report from DDC."				
11. SUPPLEMENTARY NOTES None		12. SPONSORING MILITARY ACTIVITY "Project Defender" Advance Research Projects Agency, Office of Naval Research, Department of Defense Washington, D. C.		
13. ABSTRACT Evaluation of a method for measuring molecular absorptivities as small as 10^{-6} cm^{-1} is being conducted. Sound pulses generated by the absorption of ruby laser light are to be focused on a collodian membrane microphone: Membrane motion of as little as 5Å will be detected by making the membrane one reflector of an optical resonator illuminated by a frequency stabilized CW helium-neon laser. Signals will be observed in the frequency control loop. Wavelength scanning of the ruby laser will be done by temperature control over a 2Å region. Optical-thermal relaxation times have been studied. They are less than 10^{-8} seconds, too short to disturb the acoustic pulse. Ruby laser wavelength will be calibrated with a wavelength reference lamp, an etalon, and a grating, to provide resolving power.				

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Weak absorption of light Pulsed laser applications CW laser applications Acoustic detectors Molecular absorption						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedure, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.