

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

A 473562

BRLM 1681

BRL

AD

MEMORANDUM REPORT NO. 1681

THE ZERO-YAW DRAG COEFFICIENT FOR PROJECTILE, 8-INCH: HE, M106

by

Elizabeth R. Dickinson

September 1965

DDC

NOV 12 1965

NSA B

U. S. ARMY MATERIEL COMMAND
BALLISTIC RESEARCH LABORATORIES
ABERDEEN PROVING GROUND, MARYLAND

Destroy this report when it is no longer needed.
Do not return it to the originator.

DDC AVAILABILITY NOTICE

Qualified requesters may obtain copies of this report from DDC.

Release or announcement to the public is not authorized

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1681

SEPTEMBER 1965

THE ZERO-YAW DRAG COEFFICIENT
FOR
PROJECTILE, 8-INCH: HE, M106

Elizabeth R. Dickinson

Computing Laboratory

RDT & E Project No. 1P523801A287

ABERDEEN PROVING GROUND, MARYLAND

Previous page was blank, therefore not filmed.

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1681

ER Dickinson/vc
Aberdeen Proving Ground, Md.
September 1965

THE ZERO-YAW DRAG COEFFICIENT
FOR
PROJECTILE, 8-INCH: HE, M106

ABSTRACT

This report presents an analytical fit of experimentally determined drag coefficients for the howitzer shell designated as Projectile, 8-Inch: HE, M106. Both a tabular and a graphical representation of the fitted coefficients are included.

Previous page was blank, therefore not filmed.

INTRODUCTION

In 1941, the first firing table for the 8-inch M106 howitzer projectile was published. This firing table (FT 8-J-1) was based on data, obtained from firings in 1940, reduced with the G_5 drag coefficient. In 1958, FT 8-J-2 was published. The data for this table were based on the 1940 firings plus some supplementary firings conducted in 1955. All of the data (1940 and 1955) were reduced, on the EDVAC and the ORDVAC, using a drag coefficient based on radio doppler measurements ⁽¹⁾. In 1960, standard firing table format was changed; thus it became necessary to rework the data of FT 8-J-2 and publish it as FT 8-J-3.

Since 1960 and the publication of FT 8-J-3, firing table format has again changed: all tabulations are now in terms of meters per second, and a table of fuze setting factors has been added. Also, more probable error data for this projectile have become available. Since the advent of BRLESC, computing techniques for the production of firing tables have become more sophisticated. Hence the Artillery requested that a new 8-inch firing table be published (FT 8-J-4).

All of the data available since 1940 were to be reanalysed by modern methods. In addition, when the new self-propelled 8-inch howitzer became available, firings were conducted (1962-1963) to determine whether or not the same firing table could be used for firing the M106 projectile from both this vehicle and the towed vehicle. Reduction of the data from these firings showed a wide variation in ballistic coefficient for rounds fired in the low zones (charges 1, 2 and 3). Hence it was decided to investigate the drag coefficient of the M106 projectile at subsonic velocities.

DRAG COEFFICIENT

The experimental data used for determining the Mach number-drag coefficient relationship for the 8-inch M106 projectile (Fig. 1) were obtained from firings conducted by the Exterior Ballistics Laboratory in the large free flight range ⁽²⁾. These data were fitted analytically in the Computing Laboratory.

It was assumed that in the subsonic region, the drag coefficient is independent of Mach number. Hence, the zero-yaw drag coefficient, C_{D_o} , was determined by the following relationship.

$$C_{D_o} = C_D - C_{D_\delta} \overline{\delta^2}$$

where C_{D_o} = zero-yaw drag coefficient

C_{D_δ} = yaw drag coefficient (deg^{-2})

$\overline{\delta^2}$ = mean squared yaw (deg^2)

It became immediately apparent that in this subsonic region there existed two distinct levels of drag. C_{D_o} for each level was determined independently (Fig. 2), resulting in slightly different yaw-drag coefficients for each level.

High level: $C_{D_o} = .1227$; $C_{D_\delta} = .000911/\text{deg}^2$

Low level: $C_{D_o} = .1054$; $C_{D_\delta} = .001123/\text{deg}^2$

Examination of the photographic plates from the range gave a possible explanation of this phenomenon. This examination showed that the flow going over the rotating bands of the high drag rounds differed from that going over the low drag rounds. Because the resolution on the plates is not adequate for detailed study, it is not possible to pinpoint the cause of this difference in flow. It might be due to a difference in the depth of body undercut, to a malformation of the rotating band or to a combination of both.

The wake patterns of two rounds, one typical of the high drag rounds and one typical of the low drag rounds, were measured (Table I). Whatever the cause of the difference in flow over the rotating bands, it resulted in a decrease in effectiveness of the boattail thus increasing base drag.

Although no definite explanation of the two levels of drag can be stated at this time, the fact of their existence does explain the variations in ballistic coefficient. Nevertheless, a two-level drag coefficient is not practical for the purpose of producing a firing table. The artilleryman in the field does not know whether he is about to fire a high drag round or a low drag round. Therefore all of the rounds below $M = .84$ were grouped together with the following results.

$$C_{D_o} = .11098065; C_{D_\delta} = .0010386852/\text{deg}^2$$

The use of this combined drag coefficient in the computation of the firing table could result in range errors. The greatest errors would be in zones 1 and 2, where the entire flight of the projectile is in the subsonic region. In order to determine the magnitude of the range errors in these two zones, trajectories were computed using the high, low and combined subsonic drag coefficients. At the maximum ranges (where maximum error would be encountered) there is a possibility of an error in range of +58, -28 meters in zone 1; +79, -39 meters in zone 2.

Because the new subsonic drag coefficients differed appreciably from the subsonic drag coefficient determined by the doppler measurements ⁽¹⁾ (Fig. 2), it was deemed advisable to fire additional rounds in the free flight range to check the drag coefficient in the transonic and supersonic regions. The data from these firings (Table II), corrected for yaw [$C_{D_0}(M > .84) = .001017$] and fitted analytically, resulted in the Mach number-drag coefficient curve shown in figure 3. Although the curve differs significantly from the old one in the subsonic region, it is in fair agreement with the old curve throughout the remaining range of Mach numbers (Fig. 4).

Following are the expressions for the Mach number-drag coefficient relationship being used in the production of the firing table, FT 8-J-4. Subsonically, the drag is a constant; through a portion of the transonic rise, the drag coefficient is a linear function of Mach number. The remainder of the experimental data was fitted by several polynomial functions of Mach number, with the requirement that C_{D_0} and its first derivative should be equal at the points of juncture. The tabulated values are given in Table III, the graphical representation in figure 3.

Interval	C_{D_0}
$0.0 \leq M \leq .860$	.11098065
$.860 \leq M \leq .95197594$	$10.094889 - 23.218392M + 13.499065M^2$
$.95197594 \leq M \leq .96784380$	$-2.1387491 + 2.4831784M$
$.96784380 \leq M \leq 1.10$	$-11.547651 + 21.926195M - 10.044501M^2$
$1.10 \leq M \leq 2.00$	$.67467570 - .29621652M + .056594850M^2$

TABLE I

WAKE CONVERGENCE PATTERNS

Calibers behind base	Diameter of wake/Diameter of base	
	Low drag round	High drag round
.5	.96	
1.0	.90	1.12
2.0	.72	1.06
2.5	.60	
3.0		1.00

TABLE II

EXPERIMENTAL DATA FROM FREE FLIGHT MEASUREMENTS

Round No.	M	C _D	$\overline{\delta^2}$ (deg ²)
7009	.706	.1094	3.6
6987	.719	.1644	52.6
6879	.743	.1220	.5
6986	.789	.1049	1.1
6876	.793	.1116	2.5
6877	.830	.1071	3.1
7007	.830	.1285	5.5
6985	.839	.2052	90.2
6983	.868	.1270	.4
6880	.869	.1284	.4
6878	.870	.1172	.6
6989	.906	.1514	.4
7008	.910	.1453	1.7
6875	.915	.1566	3.1
6990	.934	.1795	3.3
7003	.985	.3282	3.9
6994	1.003	.3403	1.0
7004	1.068	.4157	5.0
7006	1.180	.4104	5.1
7323	1.284	.3894	.5
7322	1.388	.3760	.4
7005	1.421	.3632	1.1
7324	1.588	.3465	.4
7325	1.598	.3480	1.9
7002	1.695	.3413	2.6
7326	1.926	.3106	.5
7327	1.941	.3168	1.1

TABLE III

TABLE OF DRAG COEFFICIENTS

M	C _{Do}	M	C _{Do}	M	C _{Do}
0.855	.1110	0.895	.1275	0.935	.1869
0.856	.1110	0.896	.1285	0.936	.1890
0.857	.1110	0.897	.1295	0.937	.1910
0.858	.1110	0.898	.1305	0.938	.1931
0.859	.1110	0.899	.1315	0.939	.1952
0.860	.1110	0.900	.1326	0.940	.1974
0.861	.1110	0.901	.1337	0.941	.1995
0.862	.1110	0.902	.1348	0.942	.2017
0.863	.1111	0.903	.1359	0.943	.2040
0.864	.1112	0.904	.1371	0.944	.2062
0.865	.1113	0.905	.1383	0.945	.2085
0.866	.1115	0.906	.1395	0.946	.2108
0.867	.1116	0.907	.1408	0.947	.2132
0.868	.1118	0.908	.1421	0.948	.2155
0.869	.1121	0.909	.1434	0.949	.2179
0.870	.1123	0.910	.1447	0.950	.2203
0.871	.1126	0.911	.1461	0.951	.2228
0.872	.1129	0.912	.1475	0.952	.2252
0.873	.1133	0.913	.1489	0.953	.2277
0.874	.1136	0.914	.1503	0.954	.2302
0.875	.1140	0.915	.1518	0.955	.2327
0.876	.1144	0.916	.1533	0.956	.2352
0.877	.1149	0.917	.1548	0.957	.2377
0.878	.1154	0.918	.1564	0.958	.2401
0.879	.1159	0.919	.1580	0.959	.2426
0.880	.1164	0.920	.1596	0.960	.2451
0.881	.1169	0.921	.1612	0.961	.2476
0.882	.1175	0.922	.1629	0.962	.2501
0.883	.1181	0.923	.1646	0.963	.2526
0.884	.1188	0.924	.1663	0.964	.2550
0.885	.1194	0.925	.1680	0.965	.2575
0.886	.1201	0.926	.1698	0.966	.2600
0.887	.1208	0.927	.1716	0.967	.2625
0.888	.1216	0.928	.1734	0.968	.2650
0.889	.1223	0.929	.1752	0.969	.2674
0.890	.1231	0.930	.1771	0.970	.2699
0.891	.1240	0.931	.1790	0.971	.2723
0.892	.1248	0.932	.1810	0.972	.2747
0.893	.1257	0.933	.1829	0.973	.2771
0.894	.1266	0.934	.1849	0.974	.2795
0.895	.1275	0.935	.1869	0.975	.2818

TABLE OF DRAG COEFFICIENTS


M	C _{Do}	M	C _{Do}	M	C _{Do}
0.975	.2818	1.015	.3593	1.055	.4047
0.976	.2842	1.016	.3609	1.056	.4054
0.977	.2865	1.017	.3624	1.057	.4061
0.978	.2888	1.018	.3639	1.058	.4068
0.979	.2910	1.019	.3653	1.059	.4075
0.980	.2933	1.020	.3668	1.060	.4081
0.981	.2955	1.021	.3682	1.061	.4087
0.982	.2977	1.022	.3696	1.062	.4093
0.983	.2999	1.023	.3710	1.063	.4099
0.984	.3021	1.024	.3723	1.064	.4105
0.985	.3042	1.025	.3737	1.065	.4110
0.986	.3064	1.026	.3750	1.066	.4115
0.987	.3085	1.027	.3763	1.067	.4120
0.988	.3106	1.028	.3776	1.068	.4125
0.989	.3126	1.029	.3789	1.069	.4130
0.990	.3147	1.030	.3801	1.070	.4134
0.991	.3167	1.031	.3813	1.071	.4138
0.992	.3187	1.032	.3825	1.072	.4143
0.993	.3207	1.033	.3837	1.073	.4146
0.994	.3227	1.034	.3849	1.074	.4150
0.995	.3246	1.035	.3860	1.075	.4153
0.996	.3265	1.036	.3872	1.076	.4157
0.997	.3284	1.037	.3883	1.077	.4160
0.998	.3303	1.038	.3894	1.078	.4162
0.999	.3322	1.039	.3904	1.079	.4165
1.000	.3340	1.040	.3915	1.080	.4167
1.001	.3359	1.041	.3925	1.081	.4170
1.002	.3377	1.042	.3935	1.082	.4172
1.003	.3395	1.043	.3945	1.083	.4173
1.004	.3412	1.044	.3954	1.084	.4175
1.005	.3430	1.045	.3964	1.085	.4176
1.006	.3447	1.046	.3973	1.086	.4178
1.007	.3464	1.047	.3982	1.087	.4179
1.008	.3481	1.048	.3991	1.088	.4179
1.009	.3498	1.049	.3999	1.089	.4180
1.010	.3514	1.050	.4008	1.090	.4180
1.011	.3530	1.051	.4016	1.091	.4180
1.012	.3546	1.052	.4024	1.092	.4180
1.013	.3562	1.053	.4032	1.093	.4180
1.014	.3578	1.054	.4040	1.094	.4180
1.015	.3593	1.055	.4047	1.095	.4179

TABLE OF DRAG COEFFICIENTS

M	C _{Do}	M	C _{Do}	M	C _{Do}
1.095	.4179	1.135	.4114	1.175	.4048
1.096	.4178	1.136	.4112	1.176	.4046
1.097	.4177	1.137	.4110	1.177	.4044
1.098	.4176	1.138	.4109	1.178	.4043
1.099	.4175	1.139	.4107	1.179	.4041
1.100	.4173	1.140	.4105	1.180	.4039
1.101	.4171	1.141	.4104	1.181	.4038
1.102	.4170	1.142	.4102	1.182	.4036
1.103	.4168	1.143	.4100	1.183	.4035
1.104	.4166	1.144	.4099	1.184	.4033
1.105	.4165	1.145	.4097	1.185	.4031
1.106	.4163	1.146	.4095	1.186	.4030
1.107	.4161	1.147	.4094	1.187	.4028
1.108	.4159	1.148	.4092	1.188	.4026
1.109	.4158	1.149	.4090	1.189	.4025
1.110	.4156	1.150	.4089	1.190	.4023
1.111	.4154	1.151	.4087	1.191	.4022
1.112	.4153	1.152	.4085	1.192	.4020
1.113	.4151	1.153	.4084	1.193	.4018
1.114	.4149	1.154	.4082	1.194	.4017
1.115	.4148	1.155	.4080	1.195	.4015
1.116	.4146	1.156	.4079	1.196	.4014
1.117	.4144	1.157	.4077	1.197	.4012
1.118	.4142	1.158	.4075	1.198	.4010
1.119	.4141	1.159	.4074	1.199	.4009
1.120	.4139	1.160	.4072	1.200	.4007
1.121	.4137	1.161	.4071	1.210	.3991
1.122	.4136	1.162	.4069	1.220	.3975
1.123	.4134	1.163	.4067	1.230	.3960
1.124	.4132	1.164	.4066	1.240	.3944
1.125	.4131	1.165	.4064	1.250	.3928
1.126	.4129	1.166	.4062	1.260	.3913
1.127	.4127	1.167	.4061	1.270	.3898
1.128	.4126	1.168	.4059	1.280	.3882
1.129	.4124	1.169	.4057	1.290	.3867
1.130	.4122	1.170	.4056	1.300	.3852
1.131	.4120	1.171	.4054	1.310	.3838
1.132	.4119	1.172	.4052	1.320	.3823
1.133	.4117	1.173	.4051	1.330	.3808
1.134	.4115	1.174	.4049	1.340	.3794
1.135	.4114	1.175	.4048	1.350	.3779

TABLE OF DRAG COEFFICIENTS

M	C_{Do}	M	C_{Do}
1.350	.3779	1.700	.3347
1.360	.3765	1.710	.3336
1.370	.3751	1.720	.3326
1.380	.3737	1.730	.3316
1.390	.3723	1.740	.3306
1.400	.3709	1.750	.3296
1.410	.3695	1.760	.3286
1.420	.3682	1.770	.3277
1.430	.3668	1.780	.3267
1.440	.3655	1.790	.3258
1.450	.3642	1.800	.3249
1.460	.3628	1.810	.3239
1.470	.3615	1.820	.3230
1.480	.3602	1.830	.3221
1.490	.3590	1.840	.3212
1.500	.3577	1.850	.3204
1.510	.3564	1.860	.3195
1.520	.3552	1.870	.3187
1.530	.3539	1.880	.3178
1.540	.3527	1.890	.3170
1.550	.3515	1.900	.3162
1.560	.3503	1.910	.3154
1.570	.3491	1.920	.3146
1.580	.3479	1.930	.3138
1.590	.3468	1.940	.3130
1.600	.3456	1.950	.3123
1.610	.3445	1.960	.3115
1.620	.3433	1.970	.3108
1.630	.3422	1.980	.3100
1.640	.3411	1.990	.3093
1.650	.3400	2.000	.3086
1.660	.3389		
1.670	.3378		
1.680	.3368		
1.690	.3357		
1.700	.3347		



Projectile , 8-INCH: HE, M 106
with Fuze , PD, M 51A5

Fig. 1

Two Levels of Drag in Subsonic Region




Fig. 2




Fig. 3

C_{D0} vs M 8-inch M106




Fig. 4

REFERENCES

1. Charles T. Odom. A Revised Drag Coefficient, K_D , Based on the 8-inch Howitzer Shell, HE, M106 BRL MR-1065, April 1957.
2. Walter K. Rogers, Jr. The Transonic Free Flight Range BRL R-1044, June 1958.

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) U. S. Army Ballistic Research Laboratories Aberdeen Proving Ground, Maryland		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE THE ZERO-YAW DRAG COEFFICIENT FOR PROJECTILE, 8-INCH: HE, M106		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial) Dickinson, Elizabeth R.		
6. REPORT DATE September 1965	7a. TOTAL NO. OF PAGES 21	7b. NO. OF REFS 2
8a. CONTRACT OR GRANT NO. b. PROJECT NO. 1P23801A287 c. d.	9a. ORIGINATOR'S REPORT NUMBER(S) Memorandum Report No. 1681	
		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC. Release or announcement to the public is not authorized.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY U. S. Army Materiel Command Washington, D. C.	
13. ABSTRACT This report presents an analytical fit of experimentally determined drag coefficients for the howitzer shell designated as Projectile, 8-Inch: HE, M106. Both a tabular and a graphical representation of the fitted coefficients are included.		

DD FORM 1473
1 JAN 64

Unclassified
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Projectile, 8-Inch: HE, M106 Drag coefficient						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.