

UNCLASSIFIED

AD NUMBER
AD473746
LIMITATION CHANGES
TO: Approved for public release; distribution is unlimited. Document partially illegible.
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; OCT 1965. Other requests shall be referred to Army Electronic Research and Development Activity, White Sands Missile Range, NM. Document partially illegible.
AUTHORITY
USAERDA per ltr, 26 Sep 1966

THIS PAGE IS UNCLASSIFIED

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

9723246

ECOM-5018

AD

ATMOSPHERIC SOUND PROPAGATION NEAR THE EARTH'S SURFACE

By


RICARDO PENA

and

MARVIN DIAMOND

DA TASK 1P620901A198-02

OCTOBER 1965



U.S. ARMY
ELECTRONICS RESEARCH & DEVELOPMENT ACTIVITY
WHITE SANDS MISSILE RANGE

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND • FORT MONMOUTH, N.J.

DDC AVAILABILITY NOTICE

Qualified requesters may obtain copies of this report from DDC.

DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed.
Do not return it to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

ATMOSPHERIC SOUND PROPAGATION NEAR THE EARTH'S SURFACE

By

RICARDO PENA

and

MARVIN DIAMOND

DA TASK 1P620901A198-02

OCTOBER 1965

ENVIRONMENTAL SCIENCES DIRECTORATE
U. S. ARMY ELECTRONICS RESEARCH AND DEVELOPMENT ACTIVITY
WHITE SANDS MISSILE RANGE
NEW MEXICO

ABSTRACT

A study of sound propagation near the earth's surface under relatively calm meteorological conditions showed considerable variation in the pressure of detected waves. This variation was shown to be due to atmospheric effects between the source and detector. The accuracy of determining the elevation angle of the sound source was found to be highly dependent upon the surface temperature.

CONTENTS

	Page
ABSTRACT-----	ii
INTRODUCTION-----	1
INSTRUMENTATION-----	1
RESULTS-----	3
CONCLUSIONS-----	9

INTRODUCTION

The detection of pressure waves generated by high-altitude explosions on previous experiments has been accompanied by considerable pressure variations between microphones of a surface array. Since the pressure waves travelled nearly vertically over paths greater than 250,000 feet the array can be considered as a single point relative to the acoustic source. Thus the portions of each wave which were detected at each microphone propagated along essentially the same path through the atmosphere. This would indicate that molecular absorption processes are the same for all parts of each wave and that absorption cannot be a cause of the observed pressure variations. However, atmospheric conditions such as temperature, wind, and turbulence near the surface are probably different at the various microphone locations of the array and might affect the wave pressure in that area.

The purpose of this report is to present the results of an experiment which was performed to study atmospheric effects on the pressure of incident acoustic waves in the air layer near the earth's surface. Information was also obtained on the accuracy with which the azimuth and elevation angle of a sound ray can be determined.

INSTRUMENTATION

The locations of the sound source and the array, which was a square 1500 feet on a side, are shown in Figure 1. The sound source consisted of an automatic device which could remotely detonate as many as thirteen 10-gauge shotgun shells at five-second intervals. The device was placed near the top of a tower, 190 feet above the surface with the barrel pointing toward the ground. Two salvos of thirteen and nine shells, respectively, were fired within a few minutes.


General Radio (GR) sound level meters (Model 1551C) at the base of the tower and at each corner of the array were used to monitor the generated sound. All the sound level meters were calibrated with a two-volt RMS 400-cycle source at a 120-db level prior to and after the test period.

The sound meter at the base of the tower was used to correlate variations in source intensity with variations in measured outputs of the array sound meters. If a correlation was obtained between these sensors this would establish the variations as being caused by the source.

Data were obtained between 1800 and 1900 MST on 24 February 1965. During this time surface winds were less than 2 MPH and skies were clear. The temperature was 8°C at the surface and 7°C at 1000 feet above the surface, indicating nearly isothermal conditions within this layer of air.

FIGURE 1

LOCATION OF SOUND SOURCE AND
MICROPHONE ARRAY



The output of the sound meters was recorded on magnetic tape at 30 inches per second during the test period and reproduced at 1-7/8 inches per second to decrease the frequency by a factor of 16. This frequency decrease provided an accurate visual representation on the oscillograph chart of the predominant 200 cps signal detected by the sound meters. A recording of the pressure wave at the base of the tower and at an array position is shown in Figure 2.

RESULTS

PRESSURE

The mean incident pressure, standard deviation, and coefficient of variation for each position in the array and at the base of the tower are listed in Table I.

TABLE I

STATISTICS OF PRESSURE MEASUREMENTS


n = 22

	TOWER	<u>ARRAY POSITIONS</u>			
		NW	NE	SE	SW
Mean Incident Peak Pressure ($\bar{X}$) dynes/cm ²	31.3	.61	.38	.38	.67
Standard Deviation (σ)	.41	.31	.08	.08	.12
Coefficient of Variation %	1.2	20	21	16	18

The higher pressure obtained at the NW and SW microphone positions would be expected since they were closer to the sound source than those at the SE and SW locations. If the decrease in amplitude between tower and array was due only to spherical divergence, the pressure at the center of the array as estimated from

$$\frac{P_{\text{Tower}}}{P_{\text{Array}}} = \frac{d_{\text{Array}}}{d_{\text{Tower}}}$$

FIGURE 2
PRESSURE WAVES



would have been about $1.2 \text{ dynes cm}^{-2}$ which is larger than the measured values. The difference between this pressure and the ones measured at the array positions is largely due to scattering or absorption phenomena. Some energy is also lost due to the source not being isotropic with respect to the array positions.

The much larger coefficients of variation at the array positions than at the tower position indicate that the atmosphere caused pressure variations in the propagating wave; therefore, what may be described meteorologically as "calm" conditions (0-2 mph) was not the case with respect to acoustic propagation. Due to variations in temperature, humidity and wind, slight turbulence and eddies, in seemingly calm air, can produce rapid changes in the speed of sound. Such changes can result in varying focusing patterns that can cause rapid temporal fluctuations in the pressure of waves at any location. These pressure fluctuations indicate that measurements of the atmospheric parameters obtained with the usually sluggish meteorological instruments are incapable of disclosing the fine structure of the distribution of temperature, humidity, or wind.

AZIMUTH AND ELEVATION ANGLE

The determination of azimuth and elevation angle is based on the assumption that the detected sound is a plane wave front that undergoes no distortion or change of direction as the wave crosses the array. The direction of wave propagation is considered as the direction of the normal to the wave front. The possibilities of introducing an error in assuming plane wave instead of spherical wave propagation were investigated. It was found that the maximum possible error in wave arrival, which occurs at the SW microphone and decreases as the radius of curvature increases, is 0.035 second. Comparing the time interval ($t_4 - t_1$) of a plane and spherical wave respectively, the error reduces to 0.005 second, which when applied to the azimuth equation below will not influence the results appreciably.

In Figure 3, ABCD represents a microphone array showing microphones 1, 2, 3, 4 and W_1, W_2, W_3, W_4 are the intersections of the wave front with the horizontal plane at times t_1, t_2, t_3 and t_4 , respectively. From the geometry of Figure 3 the azimuth with reference to the center of the array is obtained from

$$\tan \theta = \frac{t_4 - t_1 + t_3 - t_2}{t_4 - t_3 + t_2 - t_1}$$

Figure 4 shows the vertical plane containing the horizontal line AF. The angle (ϵ) which the ray path (JF) forms with the horizontal is the elevation angle of the normal to the wave front. AJ is normal to the ray path and represents the plane wave front.

FIGURE 3

GEOMETRY OF WAVE FRONT CROSSING ARRAY





FIG. 4

GEOMETRY OF ELEVATION ANGLE COMPUTATION



The elevation angle (ϵ) may then be obtained from

$$\cos \epsilon = \frac{V_s (t_4 - t_2)}{AC \cos \beta}$$

where V_s is the local speed of sound as obtained from local temperature and wind conditions, AC is the diagonal of the square array and β is the angle between the diagonal and the ray path (from Figure 3).

The above calculations assume that all the microphones lie in the same horizontal plane, which was true for the microphones in this experiment.

The results of the azimuth and elevation angle computations summarized in Table II show that the azimuth angle as computed from the microphone data agrees quite well with the geometric values, which indicates that the variations in pressure due to atmospheric conditions had little or no effect on the trajectory of any portion of the wave front.

Three values of elevation angles, computed from microphone data, are listed to show the effect of a one-degree error in surface temperature. The results indicate that at low elevation angles slight temperature errors can cause large errors in the computed elevation angle.

TABLE II

SUMMARY OF AZIMUTH AND ELEVATION ANGLE COMPUTATIONS

GEOMETRIC AZIMUTH	COMPUTED AZIMUTH	GEOMETRIC ELEVATION ANGLE	COMPUTED ELEVATION ANGLE
250° 04'	258° 32' ± 0.13° *	1° 55'	5° 12' - 7°C 3° 54' - 8°C 1° 49' - 9°C

*Standard deviation

CONCLUSION

Acoustic waves travelling in the air layer near the earth's surface are greatly influenced by atmospheric conditions. It has been shown that even under relatively calm conditions, atmospheric conditions can cause variations of as much as 20 per cent in the measured pressure of sound waves. This variation was observed under assumed isothermal conditions in a surface air layer about 1000 feet thick.

Under stable meteorological conditions, the azimuth of detected sound was determined with considerable accuracy; however, the accuracy of the elevation angle was found to be highly dependent upon the surface temperature.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) U. S. Army Electronics Command Fort Monmouth, New Jersey		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE ATMOSPHERIC SOUND PROPAGATION NEAR THE EARTH'S SURFACE		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial) Pena, Ricardo Diamond, Marvin		
6. REPORT DATE October 1965	7a. TOTAL NO. OF PAGES 9	7b. NO. OF REFS None
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S) ECOM-5018	
b. PROJECT NO. c. DA Task 1P620901A198-02 d.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY U. S. Army Electronics Command U. S. Army Electronics R&D Activity White Sands Missile Range, New Mexico	
13. ABSTRACT A study of sound propagation near the earth's surface under relatively calm meteorological conditions showed considerable variation in the pressure of detected waves. This variation was shown to be due to atmospheric effects between the source and detector. The accuracy of determining the elevation angle of the sound source was found to be highly dependent upon the surface temperature.		

DD FORM 1473

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
1. Acoustics 2. Sound Propagation 3. Meteorological Conditions 4. Atmospheric Effects 5. Surface Temperature						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification