

UNCLASSIFIED

AD NUMBER
AD475565
LIMITATION CHANGES
TO: Approved for public release; distribution is unlimited.
FROM: Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; DEC 1965. Other requests shall be referred to Arnold Engineering Development Center, Arnold AFB, TN 37389. This document contains export-controlled technical data.
AUTHORITY
AEDC ltr, 2 Nov 1971

THIS PAGE IS UNCLASSIFIED

eg,



**STATIC STABILITY CHARACTERISTICS
OF THE ALARR PAYLOAD AND THE EFFECT OF
THE WAKE ON THE BALLUTE DECELERATOR
CHARACTERISTICS AT TRANSONIC SPEEDS**

Warren E. White and Travis R. Brice

ARO, Inc.

December 1965

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with the prior approval of
Arnold Engineering Development Center.

DISTRIBUTION UNLIMITED, APPROVED FOR PUBLIC
RELEASE (PER AF LETTER 2 NOV 71, XON)

**PROPULSION WIND TUNNEL FACILITY
ARNOLD ENGINEERING DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
ARNOLD AIR FORCE STATION, TENNESSEE**

AEDC TECHNICAL LIBRARY



6102 1E000 0220 5

NOTICES

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

STATIC STABILITY CHARACTERISTICS
OF THE ALARR PAYLOAD AND THE EFFECT OF
THE WAKE ON THE BALLUTE DECELERATOR
CHARACTERISTICS AT TRANSONIC SPEEDS

Warren E. White and Travis R. Brice
ARO, Inc.

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with prior approval of
Arnold Engineering Development Center.

DISTRIBUTION UNLIMITED, APPROVED FOR PUBLIC
RELEASE (PER AF LETTER 2 NOV 71, XON)

FOREWORD

The work reported herein was done at the request of the Air Force Special Weapons Center (AFSWC), Air Force Systems Command (AFSC), Kirtland Air Force Base, New Mexico, under System 921A.

The results of the test presented were obtained by ARO, Inc. (a subsidiary of Sverdrup and Parcel, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The test was conducted from September 20 through October 4, 1965, under ARO Project No. PA0612, and the manuscript was submitted for publication on November 19, 1965.

This technical report has been reviewed and is approved.

Francis M. Williams
Major, USAF
AF Representative, PWT
DCS/Test

Jean A. Jack
Colonel, USAF
DCS/Test

ABSTRACT

Drag data were obtained at Mach numbers 0.5, 0.8, and 1.2 for the Goodyear Aerospace Corporation ballute decelerator in the wake of the payload of the Air Launch Air Recovery Rocket (ALARR). Two model sizes of the ALARR payload were tested at angles of attack of 0 and 20 deg placed at 2, 3, 4, 5, and 6 payload diameters forward of the decelerator. The decelerator remained at zero angle of attack. The wake influence of the larger payload reduced the drag of the decelerator, both at 0- and 20-deg angles of attack. In addition, static stability characteristics were obtained on the ALARR payload for a Mach number range from 0.5 to 1.5 and an angle-of-attack range from -4 to +22 deg. To maintain static stability the center of gravity cannot move more than 29 percent of the model length aft of the nose.

CONTENTS

	<u>Page</u>
ABSTRACT.	iii
NOMENCLATURE.	vi
I. INTRODUCTION	1
II. APPARATUS	
2.1 Wind Tunnel	1
2.2 Test Articles.	2
III. TEST DESCRIPTION	
3.1 Test Procedure.	2
3.2 Precision of Measurements	3
IV. RESULTS AND DISCUSSION	
4.1 Decelerator Drag.	3
4.2 Payload Static Stability	4

ILLUSTRATIONS

Figure

1. Schematic of Tunnel 1T with a Typical Decelerator-Payload Installation.	5
2. Decelerator-Payload Configurations Installed in the Test Section	6
3. Static Stability Model Installed in the Test Section	7
4. Details and Dimensions of Models	8
5. Test Reynolds Number per Foot as a Function of Mach Number	9
6. Effect of Mach Number Variation on the Decelerator Drag Coefficient for Decelerator-Payload Separation Distances	
a. Separation Distance of Two Payload Diameters.	10
b. Separation Distance of Three Payload Diameters.	10
c. Separation Distance of Four Payload Diameters.	10
d. Separation Distance of Five Payload Diameters.	11
e. Separation Distance of Six Payload Diameters.	11

Figure		Page
7.	Effect of Decelerator-Payload Separation Distances on the Decelerator Drag Coefficient	
a.	$M_\infty = 0.50$	12
b.	$M_\infty = 0.80$	12
c.	$M_\infty = 1.2$	12
8.	Schlieren Photographs of Decelerator	13
9.	Effect of Angle of Attack on the C_N , C_m , x_{xp} , $C_{A,F}$, and $C_{A,b}$ Characteristics of the Static Stability Model	
a.	C_N , $M_\infty = 0.50$ to 0.90	14
b.	C_N , $M_\infty = 1.00$ to 1.50	15
c.	C_m , $M_\infty = 0.50$ to 0.90	16
d.	C_m , $M_\infty = 1.00$ to 1.50	17
e.	x_{cp} , $M_\infty = 0.50$ to 0.90	18
f.	x_{cp} , $M_\infty = 1.00$ to 1.50	19
g.	$C_{A,F}$, $M_\infty = 0.50$ to 0.90	20
h.	$C_{A,F}$, $M_\infty = 1.00$ to 1.50	21
i.	$C_{A,b}$, $M_\infty = 0.50$ to 0.90	22
j.	$C_{A,b}$, $M_\infty = 1.00$ to 1.50	23
10.	Effect of Mach Number Variation on C_{N_α} and x_{np} for the Static Stability Model, $\alpha = 0$ deg	24
11.	Effect of Mach Number Variation on the $C_{A,F}$ and $C_{A,b}$ for the Static Stability Model, $\alpha = 0$ deg	25

NOMENCLATURE

A_B	Decelerator cross-sectional area based on maximum decelerator diameter without fence, 0.01502 sq ft
A_b	Stability payload model base area, 0.01173 sq ft
C_A	Axial-force coefficient, axial force/ $q_\infty S$
$C_{A,b}$	Base axial-force coefficient, $\frac{p_\infty - p_b}{q_\infty} \cdot \frac{A_b}{S}$
$C_{A,F}$	Forebody axial-force coefficient, $C_A - C_{A,b}$
C_D	Decelerator drag coefficient, drag/ $q_\infty A_B$

C_m	Pitching-moment coefficient referenced to the model nose, measured pitching moment/ $q_\infty S D_S$
C_N	Normal-force coefficient, normal force/ $q_\infty S$
C_{N_α}	Rate of change of normal-force coefficient with angle of attack $(dC_N/d\alpha)_{\alpha=0}$, per deg
D	Payload diameters, 0.07933 ft and 0.1088 ft
D_S	Stability model reference diameter, 0.125 ft
L	Model length (see Fig. 4), in.
M_∞	Free-stream Mach number
p_b	Stability model base pressure, psf
p_∞	Free-stream static pressure, psf
q_∞	Free-stream dynamic pressure, $0.7 p_\infty M_\infty^2$, psf
R	Radial coordinate of model (see Fig. 4), in.
Re/ft	Reynolds number per foot
S	Stability model reference area, 0.01227 sq ft
X	Longitudinal coordinate of model (see Fig. 4), in.
x	Payload and decelerator separation distance, in.
x_{cp}	Center-of-pressure location in model reference diameters, negative aft of model nose (C_m/C_N)
x_{np}	Neutral-point location in model reference diameters, negative aft of model nose $(dC_m/dC_N)_{\alpha=0}$
α	Payload model angle of attack, positive nose up, deg

SECTION I INTRODUCTION

The Air Launch Air Recoverable Rocket (ALARR) is an air sampling rocket designed to take atmospheric samples at altitudes above 60,000 ft. To recover the payload, Goodyear Aerospace Corporation is developing a ballute decelerator to decelerate the payload to a desired velocity before deploying the recovery parachute. A test program was initiated to simulate a 22-in. -diam and a 30-in. -diam ballute decelerator in the wake of the ALARR payload. This was accomplished by placing payload models of two sizes forward of the ballute decelerator model. Drag data for the decelerator at Mach numbers 0.5, 0.8, and 1.2 were obtained by placing the payloads at 2, 3, 4, 5, and 6 payload diameters forward of the ballute. The payloads were set at angles of attack of 0 and 20 deg. The decelerator remained at zero angle of attack.

In addition, static stability of the ALARR payload was obtained at a Mach number range from 0.5 through 1.5 for an angle-of-attack range from -4 to +22 deg.

SECTION II APPARATUS

2.1 WIND TUNNEL

The Aerodynamic Wind Tunnel, Transonic (1T) is an open-circuit, continuous flow wind tunnel capable of operating at Mach numbers from 0.50 to 1.50. The total pressure is approximately 1.4 atm throughout the operating range. The test section is 12 in. square, 37.5 in. long, and has perforated walls as shown in Fig. 1. A more detailed description of the tunnel may be found in the Test Facilities Handbook.¹ Photographs showing typical model installations are presented in Figs. 2 and 3. The sidewalls with 8- by 12-in. glass inserts were used only for the schlieren photography phase of the test.

¹Test Facilities Handbook (5th Edition). "Propulsion Wind Tunnel Facility, Vol. 3." Arnold Engineering Development Center, July 1963.

2.2 TEST ARTICLES

The dimensions of the models are presented in Fig. 4. A 0.075-scale payload was tested with a 0.075-scale model of a 22-in. -diam decelerator, and the same decelerator model was tested with a 0.055-scale payload, in which case the decelerator model represented a 30-in. -diam decelerator at 0.055-scale. The payloads were mounted on a strut at 0- and 20-deg angles of attack and were placed 2, 3, 4, 5, and 6 payload diameters forward of the decelerator. The decelerator was sting mounted and remained at zero angle of attack. No simulation was made of the riser line connecting the decelerator to the payload. The decelerator model was also tested alone. In addition, a 0.086-scale payload stability model was tested. This model was sting mounted.

The decelerator was mounted on an internal strain-gage load cell which measured drag force. The static stability model was mounted on an internal strain-gage balance which measured normal force, pitching moment, and axial force. Base pressures were measured on the stability model only and were obtained from two static pressure orifices located at the base of the model.

SECTION III TEST DESCRIPTION

3.1 TEST PROCEDURE

The decelerator was tested alone and in the wake of the payloads at Mach numbers 0.50, 0.80, and 1.2. The decelerator was translated vertically to determine strut influences and the vertical position which would give minimum drag. The centerline of the test section was used as reference zero, and translation above the centerline was termed positive. The decelerator was translated ± 2.5 in. The static stability model was tested at Mach numbers from 0.5 to 1.5 and at angles of attack from -4 to +22 deg. The tunnel was operated at stagnation pressures which ranged from approximately 2765 to 2897 psf, and stagnation temperatures which varied from 142 to 208°F. The temperature variation was used to alleviate moisture condensation. The slight variation in tunnel conditions caused a change in Reynolds number which is presented in Fig. 5 as a function of Mach number.

3.2 PRECISION OF MEASUREMENTS

The estimated uncertainties in the data are given in the following table and are based on a 95-percent probability.

<u>UNCERTAINTIES</u>				
<u>Symbol</u>	<u>$M_\infty = 0.5$</u>	<u>$M_\infty = 0.8$</u>	<u>$M_\infty = 1.2$</u>	<u>$M_\infty = 1.5$</u>
M_∞	± 0.003	± 0.003	± 0.015	± 0.015
α , deg	± 0.10	± 0.10	± 0.10	± 0.10
q_∞ , psf	± 3	± 3	± 3	± 3
C_D	± 0.010	± 0.006	± 0.005	-
C_N	± 0.017	± 0.008	± 0.006	± 0.005
C_m	± 0.036	± 0.018	± 0.013	± 0.012
$C_{A,b}$	± 0.016	± 0.008	± 0.006	± 0.005
$C_{A,F}$	± 0.015	± 0.015	± 0.011	± 0.010

Angle of attack was corrected for sting and balance deflections. No corrections have been made for the test section flow inclination or tunnel wall interference. The uncertainty in Mach number given above is the deviation from the mean value in the test region. The uncertainty in setting and maintaining Mach number is estimated to be less than ± 0.004 .

SECTION IV RESULTS AND DISCUSSION

4.1 DECELERATOR DRAG

The effects of the wake of the ALARR payload on the ballute decelerator are presented in Figs. 6 and 7 in terms of the variation of the drag coefficient with free-stream Mach number and separation distance, respectively. The decelerator was translated vertically to determine strut influences and the vertical position which would give minimum drag. Generally, the center of the payload wake, as determined from schlieren photographs, correlated with the position of minimum drag. The drag data presented are for the center-of-wake positions. For the payloads at $\alpha = 0$ deg, the wake center corresponded to the tunnel centerline. The strut influences on the position of the wake center and on the decelerator drag were considered to

be small. The curves for the decelerator alone are included in Figs. 6 and 7 to allow a comparison with payload and decelerator configurations. The wake influences of the larger payloads produced a generally lower drag on the decelerator at corresponding payload angles of attack of both 0 and 20 deg. The drag of the decelerator in the wake of either payload at $\alpha = 20$ deg was less than that for either payload at $\alpha = 0$ deg except at low values of x/D at $M_\infty = 1.2$. For all payload and decelerator configurations at Mach numbers 0.5 and 0.8, the drag remained essentially the same when the separation distance was increased from 2 to 6 payload diameters. For Mach number 1.2, the drag increased as separation distance increased except at large separation distances for the 0.075-scale payload at $\alpha = 0$ deg. For the 0.055-scale payload ($\alpha = 0$ deg) at all separation distances and the 0.075-scale payload ($\alpha = 0$ deg) at small separation distances, the decelerator drag coefficient was equal to or greater than the decelerator-alone value for subsonic Mach numbers. This is not thoroughly understood; however, some difference is noted in the flow pattern over the decelerator. In particular, the flow appears to be separated ahead of the burble fence in the decelerator-alone case, but not in the decelerator-payload case. This suggests that the drag on the burble fence may be higher in the wake of the payload for the cited conditions. Different types of flow pattern can be seen in Fig. 8.

4.2 PAYLOAD STATIC STABILITY

Presented in Fig. 9 are the curves of C_N , C_m , x_{cp} , $C_{A,F}$, and $C_{A,b}$ obtained with the ALARR payload static stability model. The normal-force coefficient and pitching-moment coefficient exhibited a nonlinear variation for the angle-of-attack range tested; however, the curves exhibited an almost linear variation within the limits from -4 to +8 deg angle of attack. The pitching moment was referenced to the nose of the model. On the x_{cp} plots, the neutral-point locations are also presented since x_{cp} is indeterminate near zero angle of attack.

The normal-force curve slope, C_{N_α} , and the neutral-point location, x_{np} , are presented in Fig. 10, and the $C_{A,F}$ and $C_{A,b}$ curves are presented in Fig. 11 as a function of Mach number for $\alpha = 0$ deg. In the absence of the decelerator, the payload stability cannot be maintained if the center of gravity is more than 29 percent of the model length aft of the nose.







Fig. 1 Schematic of Tunnel 1T with a Typical Decelerator-Payload Installation




0.075-Scale Payload,
 $x/D = 2, \alpha = 0$ deg



0.075-Scale Payload,
 $x/D = 2, \alpha = 20$ deg



0.055-Scale Payload,
 $x/D = 2, \alpha = 0$ deg



0.055-Scale Payload,
 $x/D = 2, \alpha = 20$ deg

Fig. 2 Decelerator-Payload Configurations Installed in the Test Section




Fig. 3 Static Stability Model Installed in the Test Section

PAYLOAD COORDINATES FOR THREE PAYLOADS			
PERCENT OF MODEL LENGTH	0.055-SCALE L = 2.230 in.	0.075-SCALE L = 3.041 in.	STABILITY L = 3.496 in.
X/L	R	R	R
0	0.174	0.240	0.275
6	0.219	0.299	0.344
19	0.302	0.411	0.473
31	0.367	0.501	0.576
43	0.414	0.565	0.649
56	0.451	0.616	0.708
64	0.467	0.636	0.731
68	0.471	0.642	0.738
72	0.474	0.646	0.743
77	0.477	0.650	0.747
86	0.478	0.652	0.750
90	0.451	0.615	0.707
100	0.467	0.638	0.733

DECELERATOR COORDINATES	
PERCENT OF MODEL LENGTH	0.075-SCALE L = 2.03 in.
X/L	R
0	0
13	0.23
26	0.46
39	0.65
52	0.77
65	0.82
73	0.83
78	0.98
85	0.98
90	0.68
91	0.64
98	0.42
100	0

ALL DIMENSIONS IN INCHES
 SCALED DIMENSIONS ARE BASED ON
 THE 22-in. FULL-SCALE BALLUTE




Fig. 4 Details and Dimensions of Models







Fig. 5 Test Reynolds Number per Foot as a Function of Mach Number



a. Separation Distance of Two Payload Diameters




b. Separation Distance of Three Payload Diameters




c. Separation Distance of Four Payload Diameters

Fig. 6 Effect of Mach Number Variation on the Decelerator Drag Coefficient for Decelerator-Payload Separation Distances



d. Separation Distance of Five Payload Diameters



e. Separation Distance of Six Payload Diameters

Fig. 6 Concluded






Fig. 7 Effect of Decelerator-Payload Separation Distances on the Decelerator Drag Coefficient




Decelerator Alone

$M_{\infty} = 0.8$




Payload $x/D = 2, \alpha = 0$ deg



Decelerator Alone

$M_{\infty} = 0.5$



Payload $x/D = 2, \alpha = 0$ deg

Fig. 8 Schlieren Photographs of Decelerator






Fig. 9 Effect of Angle of Attack on the C_N , C_m , x_{cp} , C_A , F , and $C_{A,b}$ Characteristics of the Static Stability Model




b. C_N , $M_\infty = 1.00$ to 1.50

Fig. 9 Continued



c. C_m , $M_\infty = 0.50$ to 0.90

Fig. 9 Continued



d. C_m , $M_\infty = 1.00$ to 1.50

Fig. 9 Continued

FLAGGED SYMBOLS INDICATE NEUTRAL-POINT LOCATIONS



e. x_{cp} , $M_\infty = 0.50$ to 0.90


Fig. 9 Continued

FLAGGED SYMBOLS INDICATE NEUTRAL - POINT LOCATIONS




f. x_{cp} , $M_\infty = 1.00$ to 1.50

Fig. 9 Continued




g. $C_{A,F}$, $M_\infty = 0.50$ to 0.90

Fig. 9 Continued




h. $C_{D,F}$, $M_\infty = 1.00$ to 1.50

Fig. 9 Continued



i. $C_{A, b}, M_\infty = 0.50$ to 0.90

Fig. 9 Continued



j. $C_{A,b}$ for $M_\infty = 1.00$ to 1.50

Fig. 9 Concluded




Fig. 10 Effect of Mach Number Variation on C_{N_α} and x_{np}
for the Static Stability Model, $\alpha = 0^\circ$




Fig. 11 Effect of Mach Number Variation on the $C_{A,F}$ and $C_{A,b}$ for the Static Stability Model, $\alpha = 0^\circ$

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center ARO, Inc. Operating Contractor Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3 REPORT TITLE STATIC STABILITY CHARACTERISTICS OF THE ALARR PAYLOAD AND THE EFFECT OF THE WAKE ON THE BALLUTE DECELERATOR CHARACTERISTICS AT TRANSONIC SPEEDS			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5 AUTHOR(S) (Last name, first name, initial) White, Warren E. and Brice, Travis R., ARO, Inc.			
6 REPORT DATE December 1965		7a TOTAL NO OF PAGES 33	7b NO OF REFS 1
8a CONTRACT OR GRANT NO AF 40(600)-1200		9a ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-65-265	
b System 921A			
c		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
d			
10 AVAILABILITY/LIMITATION NOTICES Qualified users may obtain this report from the following sources: <u>DISTRIBUTION UNLIMITED, APPROVED FOR PUBLIC RELEASE (PER AF LETTER 2 NOV 71, XON)</u> to foreign governments, or by other means, without the prior approval of AEDC.			
11 SUPPLEMENTARY NOTES N/A		12 SPONSORING MILITARY ACTIVITY Air Force Special Weapons Center Air Force Systems Command, Kirtland Air Force Base, New Mexico	
13 ABSTRACT Drag data were obtained at Mach numbers 0.5, 0.8, and 1.2 for the Goodyear Aerospace Corporation ballute decelerator in the wake of the payload of the Air Launch Air Recovery Rocket (ALARR). Two model sizes of the ALARR payload were tested at angles of attack of 0 and 20 deg placed at 2, 3, 4, 5, and 6 payload diameters forward of the decelerator. The decelerator remained at zero angle of attack. The wake influence of the larger payload reduced the drag of the decelerator, both at 0- and 20-deg angles of attack. In addition, static stability characteristics were obtained on the ALARR payload for a Mach number range from 0.5 to 1.5 and an angle-of-attack range from -4 to +22 deg. To maintain static stability the center of gravity cannot move more than 29 percent of the model length aft of the nose.			

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
ALARR						
scientific rockets						
static stability characteristics						
ballute decelerators						
drag data						
transonic flow						
wind tunnel tests						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.