

UNCLASSIFIED

AD NUMBER

AD480606

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; APR 1966. Other requests shall be referred to Arnold Engineering Development Center, Arnold AFB, TN.

AUTHORITY

AFFDL ltr 24 Jan 1973

THIS PAGE IS UNCLASSIFIED

AEDC-TR-66-83

a.6

MAY 9 1966

NOV 1 1966

JUN 30 1967



INVESTIGATION OF THE EFFECTS OF AIR INJECTION UPON THE HYPERSONIC LAMINAR BOUNDARY LAYER

R. L. Palko and A. D. Ray
ARO, Inc.

April 1966

This document is subject to special export controls
and each transmittal to foreign governments or foreign
nationals may be made only with prior approval of
AFFDL.

PROPERTY OF U. S. AIR FORCE
AEDC LIBRARY
AF 40(600)1200

**VON KÁRMÁN GAS DYNAMICS FACILITY
ARNOLD ENGINEERING DEVELOPMENT CENTER
AIR FORCE SYSTEMS COMMAND
ARNOLD AIR FORCE STATION, TENNESSEE**

NOTICES

When U. S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

INVESTIGATION OF THE EFFECTS
OF AIR INJECTION UPON THE
HYPERSONIC LAMINAR BOUNDARY LAYER

R. L. Palko and A. D. Ray
ARO, Inc.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFFDL.

FOREWORD

The work reported herein was conducted for The Boeing Company, Seattle, at the request of the Air Force Flight Dynamics Laboratory (AFFDL), Research and Technology Division (RTD), Air Force Systems Command (AFSC), under Program Element 62405334, Project 1366, Task 136606.

The results of the tests were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The tests were conducted from September 20, 1965, to January 27, 1966, under ARO Project No. VT0510, and the manuscript was submitted for publication on March 24, 1966.

This technical report has been reviewed and is approved.

Donald E. Beitsch
Major, USAF
AF Representative, VKF
DCS/Test

Jean A. Jack
Colonel, USAF
DCS/Test

ABSTRACT

An experimental study was conducted to obtain boundary-layer pitot pressure profile data on a sharp and a blunt leading edge rectangular plate and a sharp leading edge delta wing at Mach 6, 8, and 10. Effects of Reynolds number, angle of attack, and mass injection were studied. Selected results are presented to illustrate the effect of air injection upon the sharp rectangular plate boundary layer at Mach 8 and zero angle of attack.

CONTENTS

	<u>Page</u>
ABSTRACT	iii
NOMENCLATURE	vi
I. INTRODUCTION	1
II. APPARATUS	
2.1 Wind Tunnels	1
2.2 Models	1
2.3 Survey Probe	2
2.4 Instrumentation	2
III. PROCEDURE	3
IV. RESULTS AND DISCUSSION	3
REFERENCES	4

ILLUSTRATIONS

Figure

1. Wind Tunnels	5
2. Model Details	
a. Rectangular Model	6
b. Delta Model	7
3. Effect on Boundary-Layer Pitot Pressure Profiles of Mass Injection on a Sharp Rectangular Plate at Mach 8	8
4. Effect on Boundary-Layer Pitot Pressure Profiles of Mass Injected at Different Locations on a Sharp Rectangular Plate at Mach 8	9
5. Effect of Variations in Free-Stream Reynolds Number on Boundary-Layer Pitot Pressure Profiles for a Sharp Rectangular Plate at Mach 8	10

TABLE

I. Test Conditions	11
------------------------------	----

NOMENCLATURE

M_{∞}	Free-stream Mach number
p_o	Stagnation pressure, psia
p_o'	Total pressure behind a normal shock, psia
P_{tp}	Probe total pressure, psia
p_w	Model surface pressure, psia
p_{∞}	Free-stream static pressure, psia
Re_{∞}	Free-stream unit Reynolds number, in.^{-1}
T_o	Stagnation temperature, °R
T_w	Model surface temperature, °R
x	Longitudinal distance along model surface, in.
y	Vertical distance above model surface, in.
z	Lateral distance along model surface, in.

SECTION I INTRODUCTION

Pitot and surface pressure and surface temperature measurements were made on a flat rectangular plate and a flat delta plate at Mach numbers of 6, 8, and 10. The tests were performed in the 50-in. hypersonic tunnels (Gas Dynamic Wind Tunnels, Hypersonic (B) and (C)). The objective of the tests was to obtain boundary-layer pitot pressure profile data to help verify an analytical method under development by The Boeing Company for predicting minimum critical Reynolds number (below which boundary-layer transition cannot occur) in hypersonic flow.

To supply comparison data for use in the analytical method, small amounts of air were injected into the boundary layer to produce very small magnitude artificial disturbances. Boundary-layer pitot pressure profile data, measured near the downstream end of the plate, were used to determine the extent to which the boundary layer was disturbed. Some other parameters which were studied were the effects of free-stream Reynolds number and angle of attack.

SECTION II APPARATUS

2.1 WIND TUNNELS

Tunnels B and C are axisymmetric, continuous flow, variable density wind tunnels with 50-in. -diam test sections (Fig. 1 and Ref. 1). Tunnel B has interchangeable throat sections which produce nominal Mach numbers of 6 and 8. The tunnel operates at stagnation pressures from 20 to 300 psia at Mach 6 and from 50 to 900 psia at Mach 8. Stagnation temperatures up to 1350°R are utilized to prevent liquefaction of the air in the test section.

Tunnel C operates at a nominal Mach number of 10 at stagnation pressures from 200 to 1800 psia. Stagnation temperatures up to 1900°R are utilized to prevent air liquefaction.

2.2 MODELS

The models, furnished by The Boeing Company, consisted of two flat stainless steel plates (Fig. 2), one rectangular in shape (20 x 28 in.)

and the other delta in shape (34 in. long). The rectangular model had interchangeable leading edges of 0.002- and 0.25-in. diameter, whereas the delta model had fixed 0.002-in. -diam leading edges. The instrumented surfaces of the models were 1/4-in. stainless steel plates. Both models were instrumented with surface pressure taps and thermocouples and were sting mounted in the tunnels. The Chromel[®]-Alumel[®] thermocouples were tack welded to the back of the 1/4-in. surface plate. Ports for air injection were located at several places along the centerline of both models to artificially disturb the boundary layer.

2.3 SURVEY PROBE

The pitot survey probe was capable of traversing in the x, y, and z planes. The outer diameter of the probe tip used during the surveys was 0.032 in.

A fouling light was used to indicate contact between probe and model surface for determining the "y" zero. The "y" zero was repeatable within 0.002 in.

2.4 INSTRUMENTATION

Model surface pressures were measured in Tunnel B with 15-psid transducers, whereas in Tunnel C, 1- and 15-psid transducers were switched in and out of the system automatically to allow measuring to better precision. The estimated precision of the Tunnel B measurements is ± 0.003 psia or 1 percent, and in Tunnel C is ± 0.001 psia or 1 percent, whichever is larger.

The probe pressure was measured with a 5-psid transducer, using a variable reference pressure, which allowed measurements within a precision of ± 0.002 psia or 1 percent, whichever is larger.

The reference junction of the surface temperature thermocouples was maintained at 132°F. The temperature measurements are estimated to be accurate within ± 2 deg.

The mass flow for the injection ports was measured using calibrated orifices in a flowmeter. The pressure upstream of the orifice and the differential pressure across the orifice were measured with a 100- and a 50-psid FM transducer, respectively. The supply air to the flowmeter was maintained at room temperature. Based upon calibrations of the flowmeter and upstream-pressure transducer, the precision of the mass flow measurement is estimated to be ± 5 percent.

SECTION III PROCEDURE

The tests were conducted at nominal Mach numbers of 6, 8, and 10 at stagnation pressures of 20 to 285 psia, 100 to 900 psia, and 600 to 1800 psia, respectively. A complete tabulation of the test conditions is given in Table I.

References 2 and 3 were used to determine preliminary tunnel and model conditions to ensure that laminar flow existed over the model for the mass injection tests. To verify the condition of the flow, the probe was traversed along the surface of the model in the "x" direction and stopped at selected intervals to measure pitot-probe pressure.

SECTION IV RESULTS AND DISCUSSION

To obtain comparison data for the Boeing analytical method, it was necessary to obtain pitot pressure profiles under conditions of an artificial disturbance. The use of air injection was chosen in order that the method of disturbing the boundary layer could be closely controlled and the exact conditions could be used in the analytical program.


Data were obtained for two variations in the air injection procedure. One was to inject air at different mass flow rates from one location and measure boundary-layer pitot pressure profiles at each mass flow rate (Fig. 3). As shown in the figure, the lower mass injection rate ($10 \times 10^{-6} \text{ lb}_m\text{-sec}^{-1}$) had little or no effect on the profile measured near the rear of the sharp rectangular plate. However, deviations did occur when the flow rate was increased to 20×10^{-6} and $50 \times 10^{-6} \text{ lb}_m\text{-sec}^{-1}$. Surface pressure and temperature distributions are shown at the bottom of the figure to illustrate typical levels of these data recorded at Mach 8.

The second variation (Fig. 4) was to inject at the same mass flow rate from different injection ports. As illustrated in Fig. 4, the location of the injection port has little influence upon the boundary-layer pitot pressure profile measured at a station near the end of the plate. Injecting air at a rate of $6.7 \times 10^{-6} \text{ lb}_m\text{-sec}^{-1}$ from ports located 2 and 11 in. aft of the leading edge had no effect upon the profile, and injection at a rate of $14 \times 10^{-6} \text{ lb}_m\text{-sec}^{-1}$ from either port produced about the same effect.


The effect of unit Reynolds number at Mach 8 on the sharp rectangular model is shown in Fig. 5. Here the trends are as expected, with the lower Reynolds number data, which was the base condition for the two figures previously discussed, showing a laminar profile and the higher Reynolds number data showing that transition has begun.

REFERENCES

1. Test Facilities Handbook (5th Edition). "von Kármán Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, July 1963.
2. Palko, R. L., Burt, R. H., and Ray, A. D. "An Experimental Investigation of Boundary-Layer Transition on Flat Plates at Mach Numbers 5, 8, and 10." AEDC-TDR-64-167 (AD444368), August 1964.
3. Deem, R. E., Erickson, C. R., and Murphy, J. S. "Flat-Plate Boundary-Layer Transition at Hypersonic Speeds." FDL-TDR-64-129, October 1964.




Tunnel Assembly




Tunnel Test Section

Fig. 1 Wind Tunnels




a. Rectangular Model

Fig. 2 Model Details



All Dimensions in Inches

○ Pressure Tap
 △ Mass Injection Port
 + Thermocouple



Instrument Number	x, in.	Type Instrument
1	8.5	Pressure
2	11.0	
3	16.0	
4	21.0	
5	25.0	
6	31.0	
7	21.0	
8	21.0	
9	25.0	
10	25.0	
11	31.0	
12	31.0	
A	9.0	Injection Port
B	13.0	
C	18.0	
D	23.0	
A ₁	9.5	Thermocouple
B ₁	12.0	
C ₁	14.5	
D ₁	17.0	
E ₁	19.5	
F ₁	22.0	
G ₁	24.5	
H ₁	27.0	
J ₁	29.5	
K ₁	32.0	
L ₁	19.5	
M ₁	22.0	
N ₁	22.0	
O ₁	24.5	
P ₁	24.5	
Q ₁	27.0	
R ₁	27.0	
S ₁	29.5	
T ₁	29.5	
U ₁	32.0	
V ₁	32.0	

b. Delta Model
 Fig. 2 Concluded




Fig. 3 Effect on Boundary-Layer Pitot Pressure Profiles of Mass Injection on a Sharp Rectangular Plate at Mach 8




Fig. 4 Effect on Boundary-Layer Pitot Pressure Profiles of Mass Injected at Different Locations on a Sharp Rectangular Plate at Mach 8

Sym	M_∞	p_0 , psia	T_0 , °R	Re_∞ , in. ⁻¹ x 10 ⁻⁵
○	7.88	100	1190	0.45
△	7.92	200	1240	0.85
◇	7.95	300	1265	1.22





Fig. 5 Effect of Variations in Free-Stream Reynolds Number on Boundary-Layer Pitot Pressure Profiles for a Sharp Rectangular Plate at Mach 8

TABLE I
TEST CONDITIONS

	Model Configuration		
	Sharp Rectangular	Blunt Rectangular	Delta
<u>Nominal Mach 6</u>			
Unit Reynolds, $\text{in.}^{-1} \times 10^{-5}$	0.29 to 2.42	0.29 to 4.25	0.60 to 4.25
Angle of attack, deg	-5 to +15	-5 to +15	-5 to +15
Trip location, in.	2 to 7	2 to 7	9 to 18
Trip mass flow, $\text{lb}_m\text{-sec}^{-1} \times 10^6$	3.6 to 15.0	2.5 to 73.0	3.0
Profile locations, in.	6 to 24	6 to 24	9 to 33
<u>Nominal Mach 8</u>			
Unit Reynolds, $\text{in.}^{-1} \times 10^{-5}$	0.45 to 3.20	0.45 to 3.20	0.98 to 3.20
Angle of attack, deg	-5 to +15	-5 to +15	-5 to +10
Trip location, in.	2 to 11	2 to 5	9 to 18
Trip mass flow, $\text{lb}_m\text{-sec}^{-1} \times 10^6$	6.7 to 50.0	6.7 to 50.0	10.0 to 20.0
Profile locations, in.	6 to 24	6 to 24	7 to 30
<u>Nominal Mach 10</u>			
Unit Reynolds, $\text{in.}^{-1} \times 10^{-5}$	1.27 to 1.80	0.68 to 1.80	0.68 to 1.80
Angle of attack, deg	-5 to +10	+10	-5 to +10
Trip location, in.	2 to 7	2 to 11	9 to 23
Trip mass flow, $\text{lb}_m\text{-sec}^{-1} \times 10^6$	100.0	60.0	340.0
Profile locations, in.	12 to 24	16 to 24	4 to 30

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center, ARO, Inc., Operating Contractor Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3 REPORT TITLE INVESTIGATION OF THE EFFECTS OF AIR INJECTION UPON THE HYPERSONIC LAMINAR BOUNDARY LAYER			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5 AUTHOR(S) (Last name, first name, initial) Palko, R. L. and Ray, A. D., ARO, Inc.			
6 REPORT DATE April 1966		7a TOTAL NO OF PAGES 17	7b NO OF REFS 3
8a CONTRACT OR GRANT NO AF40(600)-1200		9a ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-66-83	
b PROJECT NO. 1366		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A	
c Program Element 62405334			
d Task 136606			
10 AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC and transmittal to foreign governments and foreign nationals must have prior approval of AFFDL.			
11 SUPPLEMENTARY NOTES N/A		12 SPONSORING MILITARY ACTIVITY Air Force Flight Dynamics Laboratory (AFFDL)(RTD) Air Force Systems Command (AFSC) Wright-Patterson Air Force Base, Ohio	
13 ABSTRACT An experimental study was conducted to obtain boundary-layer pitot pressure profile data on a sharp and a blunt leading edge rectangular plate and a sharp leading edge delta wing at Mach 6, 8, and 10. Effects of Reynolds number, angle of attack, and mass injection were studied. Selected results are presented to illustrate the effect of air injection upon the sharp rectangular plate boundary layer at Mach 8 and zero angle of attack.			

14	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT

air injection
 boundary layer
 hypersonic flow
 laminar

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S)** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER.** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).
10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.
12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.
13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.