

AD 621658

AFCRL-65-649
SEPTEMBER 1965
ENVIRONMENTAL RESEARCH PAPERS, NO. 134



METEOROLOGY LABORATORY PROJECT 3850

AIR FORCE CAMBRIDGE RESEARCH LABORATORIES

L. G. HANSCOM FIELD, BEDFORD, MASSACHUSETTS

Project Sand Storm—An Experimental Program in Atmospheric Diffusion

JOHN H. TAYLOR, LT COLONEL, USAF
EDITOR

OFFICE OF AEROSPACE RESEARCH
United States Air Force



Best Available Copy

Abstract

A series of field experiments in atmospheric diffusion was conducted at Edwards Air Force Base, California, in 1963. The primary feature which distinguished this series from similar experimental investigations was that instantaneous sources were studied. Puffs of tracer material were generated quasi-instantaneously by short bursts of small, horizontally fired, solid propellant rocket motors. Tracer samples were collected on a horizontal grid that had 350 sampling positions. All of the 43 experiments were conducted under thermally unstable atmospheric conditions.

Analyses of the data identified the region of the turbulent energy spectrum which contains the eddies that are effective in diffusing the clouds. Eulerian measurements of turbulence are shown to be correlated with lateral rates of cloud growth. Downwind distributions of peak inhalation-level dosages were found to be quite irregular, with the anomalies unpredictable on the basis of measurable meteorological parameters. It was, nevertheless, possible to develop an operationally useful estimating equation relating peak dosages to distance from the source.

Contents

I. INTRODUCTION by John H. Taylor, Lt. Colonel, USAF	1
II. DIFFUSION EXPERIMENT DESIGN FACTORS by John H. Taylor, Lt. Colonel, Gordon L. Tucker, Captain, and Frederick J. Fowler, Captain, USAF	5
III. DESCRIPTION OF THE DIFFUSION EXPERIMENTS by Juri V. Nou, Captain, USAF	9
IV. METEOROLOGICAL INSTRUMENTATION by Francis H. Miller, Major, USAF	19
V. THE TRACER ASSESSMENT TECHNIQUE by Einar J. Enwall	23
VI. METEOROLOGICAL DATA REDUCTION AND PROCESSING by Robert L. Noblin, Clayton E. Graham, and William E. Mayer	29
VII. AN OPERATIONS-ORIENTED ANALYSIS by John H. Taylor, Lt. Colonel, USAF	35
APPENDIX A, Dosage and Source Data	A1
APPENDIX B, Phototheodolite Data	B1
APPENDIX C, Variance of Wind Direction Fluctuations	C1

PROJECT SAND STORM—AN EXPERIMENTAL PROGRAM IN ATMOSPHERIC DIFFUSION

I. Introduction

John H. Taylor, Lt. Colonel, USAF
Air Force Cambridge Research Laboratories

A field test program in atmospheric diffusion was carried out at Edwards Air Force Base, California, over a 9-month period in 1963. For ease of reference the program was nicknamed Project Sand Storm. It was designed primarily to provide operationally useful statements of dilution rates of pollutant clouds from small-volume, quasi-instantaneous sources. Motivation for the program arose from the necessity for using existing test facilities at the Air Force Rocket Propulsion Laboratory to static fire rocket motors whose exhausts contained substantial amounts of toxic materials, and the inability to estimate with any degree of confidence the magnitude of the resulting toxicological hazard.

Although recent studies of a similar nature had yielded the technical information needed to solve related Air Force problems (Barad, 1958; Barad and Fuquay, 1962; Haugen and Fuquay, 1963; Haugen and Taylor, 1963), there were significant differences which made the previous studies inapplicable to the current problem. The basic difference was in the character of the pollutant cloud. The short burst of a rocket motor can be likened to a quasi-instantaneous source that generates a puff. All the previous studies had been concerned with plumes generated by continuously emitting sources. While it is generally accepted that the behavior of

(Received for publication 8 April 1965)

puffs in the atmosphere differs from that of plumes, the laws governing the diffusion of puffs were not well substantiated. Theoretical investigations of the behavior of puffs, important as they might be for guiding the field studies, were not sufficient for solving the operational problem. Further, the few experimental studies that had been conducted had had very limited objectives and were of little use for determining the diffusion rates of clouds generated by static-fired rocket motors.

A preliminary analysis of the problem at Edwards indicated that a substantial field test program would be required to produce the data needed to solve the immediate operational problem. Even a minimal program for measuring the horizontal distributions of dosages downwind of the motor-firing point called for a densely instrumented sampling grid. Meteorological support requirements included wind and temperature profiles from near the surface to 200 feet and a sufficient number of surface wind measurements to define significant features, if any, in the horizontal flow patterns over the sampling grid. Supplemental information on the initial cloud size and height was considered essential because of the unknown source configurations. The latter requirement was satisfied at least partially by double phototheodolite measurements.

The design and direction of Project Sand Storm were undertaken by the Air Force Cambridge Research Laboratories at the request of the Air Force Rocket Propulsion Laboratory which, in turn, provided funding, logistic support, and technical services. Logistic support included construction of the sampling grid, provision of trucks for service, and facilities for maintaining the equipment. Technical services included the reduction and processing of meteorological and tracer sampling data.

Personnel of the 6th Weather Squadron, 4th Weather Group, Air Weather Service, installed, maintained, and operated the sampling equipment. Personnel of Detachment 21, 4th Weather Group, maintained and operated the meteorological equipment. The Air Force Flight Test Center provided the personnel and equipment for making phototheodolite observations. Coordination of the varied activities of all participating units was provided by AFCRL.

The following is a list of the personnel who participated in the field test program:

6th Weather Squadron (Mobile), 4th Weather Group, Air Weather Service

- MSgt R. B. Eis
- TSgt J. C. Copeland
- TSgt P. Zerbecki
- SSgt D. L. Hanson
- A1C L. M. Acker
- A2C J. B. Braden
- A2C W. F. Burns
- A2C S. L. Carkin
- A2C H. A. Clifton, Jr.
- A2C B. W. Connolly, Jr.

A2C A. Farley, Jr.
 A2C T. P. Kerbein
 A2C M. L. Prince
 A2C M. P. Tulledge
 A2C D. E. Wagner
 A3C T. K. Ingoldsby
 A3C W. J. Marino
 A3C R. L. Metzendorf
 A3C R. A. Mocre
 A3C W. M. Warschell
 A3C L. N. Young

Detachment 21, 4th Weather Group, Air Weather Service

SSgt P. W. Persian
 A1C M. E. Thompson
 A2C A. L. Fleenor
 A2C B. S. Muelman

Air Force Rocket Propulsion Laboratory

E. J. Enwall
 CPT F. J. Fowler*
 C. E. Graham
 W. F. Mayer
 MSgt D. A. Miller
 R. L. Noblin

*Captain Fowler was Staff Meteorologist to AFRPL from Det. 21, 4th Weather Group.

Air Force Flight Test Center

W. G. Ogle
 TSgt J. W. Morgan
 C. D. Wood

Hanford Atomic Products Operation, General Electric Company

M. F. Scoggins

Air Force Cambridge Research Laboratories

LTC J. H. Taylor
 MAJ F. H. Miller*
 CPT J. V. Nou*
 CPT G. L. Tucker*

*4th Weather Group attached to AFCRL

The three objectives of this report are: (1) to describe the program, (2) to present some findings of an operationally oriented analysis, and (3) to present some of the test data. The first objective is accomplished in Chapters II through VI which deal with the design and description of the field experiments and include discussions of tracer-dosage measurements, meteorological measurements, and the procedures used in data reduction and processing. The second objective is met in Chapter VII in which an analysis of the Sand Storm data is directed toward the solution of a specific operational problem. The third objective is completed in the appendices, where one will find tabulations of tracer sampling and source data in Appendix A, phototheodolite data in Appendix B, and intensity of turbulence measurements in Appendix C.

References

- Barad, M. L., ed. (1958) Project Prairie Grass, A Field Program in Diffusion, AFCRL, Geophysic Research Paper No. 58
- Barad, M. L., and Fuquay, J. J., eds. (1962) Green Glow Diffusion Studies, AFCRL, Geophysics Research Paper No. 73
- Haugen, D. A., and Fuquay, J. J., eds. (1963) The Ocean Breeze and Dry Gulch Diffusion Programs, AFCRL Research Report 63-791(I)
- Haugen, D. A., and Taylor, J. H., eds. (1963) The Ocean Breeze and Dry Gulch Diffusion Programs, II, AFCRL Research Report 63-791(II)

II. Diffusion Experiment Design Factors

John H. Taylor, Lt. Colonel, and Gordon L. Tucker, Captain*
Air Force Cambridge Research Laboratories

and Frederick J. Fowler, Captain**
Air Force Rocket Propulsion Laboratory

The primary objective of the Sand Storm field program was to collect data that could be used to develop operationally useful statements of diffusion rates of puffs released from static-fired rocket motors. The design of the experiments was directed solely toward the accomplishment of this objective, within the framework of constraints imposed by operational limitations and practical considerations. At the outset the following operational limitations were imposed:

- a. The sources were to be the short bursts of small rocket motors static-fired in a horizontal position.
- b. The tracer material was to be the beryllium contained in the propellant grain and expelled as particulate compounds of beryllium. It is extremely toxic and necessitated elaborate precautions for safeguarding the health of personnel participating in field activities.
- c. The source point was preselected.

*Currently assigned to Detachment 21, 4th Weather Group, Air Weather Service.

**During the period of field test, Captain Fowler was assigned as Staff Meteorologist to AFRPL from Detachment 21, 4th Weather Group. He is currently assigned to the University of Washington.

Based on the first two operational constraints and the requirement for a timely solution, a proven air-sampling technique utilizing readily available sampling equipment was to be used. The assay procedure selected to complement the sampling technique is described in Chapter IV. It has the following significant features which further influenced the design of the experiments:

- a. The detection threshold of tracer in the sample was about $0.05 \mu\text{g Be}$, but accurate assays were possible only for amounts equal to or greater than $0.5 \mu\text{g}$.
- b. In practice the range of assessment extended over about 5 orders of magnitude.
- c. The assessment procedure was lengthy, costly, and destroyed the sample.

Because of economic and logistic limitations on the number of sampling units that could be supported in the field, and the rate at which sample assessments could be made, a maximum of about 350 samples could be collected per experiment. In addition, the climatology of low-level winds at the site revealed that in order to achieve a reasonable expectance of winds favorable to a test, the angular width of the sampling array had to be at least 90 degrees. Therefore, in order to adequately define lateral and downwind distributions of dosages, the sampling array had to be limited to a horizontal plane. This—together with the uncertainty of the extent of the toxicological hazard associated with the intentional releases of toxic materials, the desire to obtain a statistically significant set of experiments, and the desirability of conducting rocket motor tests during daylight conditions—led to the decision to conduct all experiments under thermally unstable meteorological conditions.

The remaining feature of the basic design was the specification of sampler density in the downwind and lateral directions. Essentially, the problem was that of finding the best compromise, one which permitted an adequate definition of the lateral dosage distribution at as many distances from the source as required to define the downwind distribution of dosages. In making the decision as to the adequacy of lateral, or arcwise, spacing of sampling units, we utilized the statistics of Gaussian distributions. To be wholly adequate, the distribution should be defined by three standard deviations on either side of the mean and have one to two significant samples per standard deviation (Haugen, 1959). This means that the peak should be about 100 times the minimum significant dosage and there should be 7 to 12 samples with significant dosages. With our assay technique yielding a minimum significant dosage of $0.5 \mu\text{g}$, the peak would have to be at least $50 \mu\text{g Be}$, a factor which also influenced our decision concerning the maximum distance downwind from the source that sampling would be practical.

Arcwise sampler spacing then became a problem of estimating the expected lateral dimensions and growth rates of puffs. Some theoretical (Smith and Hay,

1961; Sutton, 1947) and empirical (Cramer et al, 1958; Aerojet-General Nucleonics, 1962; General Electric Co., 1962) works were used in making these estimates. Our estimates were of necessity crude, but they revealed that we would not be able to include a safety factor in arcwise sampling density if we instrumented a sufficient number of arcs to adequately define downwind distributions. We wished to sample to the maximum downwind distance permitted by source strengths and assay techniques, and at the same time show the effect of source height on close-in surface dosages. It was decided to instrument 10 arcs, giving priority to downwind sampler density at the expense of arcwise density. However, the grid design was made flexible enough to allow changes if during the course of the experiments such changes became necessary. After the fourteenth experiment we concluded that we could eliminate four of the arcs near the source without degradation of the experiments. The sampling units from the discontinued arcs were then allotted to the remaining six arcs, giving a more nearly acceptable arcwise sampling density.

Specifications of the tracer sampling grid are given in Chapter III, Table 2.

Acknowledgments

The authors wish to emphasize that they did not design the experiments alone. Among those who provided valuable guidance and assistance are: Dr. Morton L. Barad, Dr. Duane A. Haugen, and Captain Juri V. Nou of Air Force Cambridge Research Laboratories, and Mr. James J. Fuquay and Mr. Max F. Scoggins of the General Electric Company.

References

- Aerojet-General Nucleonics (1962) Unpublished preliminary results of three rocket motor tests, San Ramon, Calif.
- Cramer, H.E., Record, F.A., and Vaughan, H.C. (1958) The Study of the Diffusion of Gases or Aerosols in the Lower Atmosphere, AFCRC-TR-58-239, Bedford, Mass.
- General Electric Company (1962) Unpublished data of diffusion from elevated sources, Hanford, Wash.
- Haugen, D.A. (1959) The Effect of Sampler Spacing on Basic Analyses of Concentration Data, GRD Research Note No. 7, GRD, AFCRL, Bedford, Mass.
- Smith, F.B., and Hay, J.S. (1961) The expansion of clusters of particles in the atmosphere, Quart. J. Roy. Met. Soc. 87.
- Sutton, O.G. (1947) The theoretical distribution of airborne pollution from factory chimneys, Quart. J. Roy. Met. Soc. 73.

III. Description of the Diffusion Experiments

Juri V. Nou, Captain*
Air Force Cambridge Research Laboratories

1. INTRODUCTION

From March through November 1963, 43 diffusion experiments were conducted at Edwards Air Force Base, California. All experiments were conducted under thermally unstable atmospheric conditions with westerly or southwesterly winds of sufficient strength (over 5 knots) to assure that the tracer material was carried downwind within the confines of the sampling grid.

2. THE SOURCE

Small, solid propellant rocket motors were static-fired in short bursts to produce the tracer clouds. The horizontally fired motors were aligned approximately with the wind so that the exhaust was expelled in a downwind direction and remained close to the ground for a distance of 75 to 150 feet before blossoming into a puff. However, since the puff had initial finite dimensions, the effective source point for an equivalent point source lay somewhere upwind. Crude estimates, based on ob-

*Currently assigned to Detachment 10, 4th Weather Group, Air Weather Service.

served initial puff dimensions and growth rates over the shorter travel distances, indicated that the effective source point was very close to the actual firing point.

The relatively large amounts of thermal energy liberated during firings caused the puffs to rise immediately after they were formed. Although it was not possible to accurately determine the effective source heights (because phototheodolite measurements proved to be inadequate for that purpose in most cases), they appeared to vary considerably, depending on the amount of propellant expended and on the wind speed. Based on a limited amount of phototheodolite data and on visual observations, the effective source heights were estimated to vary from a few feet, perhaps 10 to 20 feet, when small motors were fired in strong winds, to 100 feet or slightly more when large motors were fired under light wind conditions.

Firing durations ranged from about 2 to 8 seconds. Propellant grains varied in weight from about 8 to 70 pounds and produced clouds whose visible dimensions were initially 50 to 150 feet in diameter. Source data are tabulated in Appendix A.

3. THE TRACER

Finely divided metallic beryllium, an ingredient of the rocket motor propellant grains, was used as the tracer material. When the motors were fired, compounds of beryllium were expelled and distributed throughout the exhaust cloud. The motors were weighed before and after firing to determine the amount of propellant expended. This, with a precise measure of the percentage by weight of beryllium in the grain, provided an accurate measure of the source strength.

4. TRACER SAMPLING

Sampling techniques and sampling equipment were similar to those used in the Green Glow, Ocean Breeze, and Dry Gulch diffusion programs. In fact, the basic sampling units used in Project Sand Storm were those which had been used previously at Vandenberg AFB and Cape Kennedy in supporting Projects Ocean Breeze and Dry Gulch. The only significant change to the units was the addition of a remote-control shutdown capability, a capability necessitated by the toxic nature of the tracer.

The tracer material was collected on molecular membrane filters mounted 4.5 feet above the ground. Air, drawn through the filter, was metered at a constant flow rate of 3.94 cubic feet per minute by means of a critical flow orifice mounted in the filter head assembly. Aspiration was provided by a Gast, Model 2565V, heavy-duty, vane-type vacuum pump driven by a Clinton, Series 290, Model TBA,

air-cooled, four-cycle, one-cylinder gasoline engine (Scoggins, 1962).^{*} One engine-pump assembly was required to aspirate each filter. Figures 1 and 2 show sampling units with typical exposures.

Since the particle-size distribution of the tracer was not accurately known, it was necessary to test the efficiency of the membrane filters to be sure that tracer particles were not lost through the filter. The Gelman Type AM-1 filters, which were used throughout the series of experiments, are rated virtually 100 percent effective in retention of airborne particles of 1 micron diameter and greater.



Figure 1. A Member of the Field Crew, Wearing Protective Clothing and Respirator, is Manually Starting One of the Sampling Units

^{*}Scoggins, M. F. (1962) The field sampling grid, Chap. VI in Geophysics Research Paper No. 73 (I), Bedford, Mass., 1962.



Figure 2. A Sampling Unit With Typical Exposure is Shown. The source point is located near the meteorological profile tower in the background about 300 meters away

These filters were mounted side by side with another type of filter (Millipore Type AA) similarly rated for particles 0.1 micron diameter and greater. Dual samples were collected at 30 sampling positions 200 and 300 meters from the source. Of the 41 pairs of samples so obtained with tracer amounts equal to or greater than 0.5 microgram, no statistically significant difference could be found in the exposures (mass collected normalized for sampling rate) for the 2 types of filter. It was therefore assumed that the particle-size distribution was centered well above 1.0 micron and that the Gelman AM-1 filter was adequate for the experiments.




Figure 3. Distribution of the Ratios of Exposures Obtained From Two Types of Filters Mounted Side by Side

Figure 3 shows the frequency distribution of the ratios of exposures obtained from the Gelman AM-1 filter to those obtained from the Millipore AA filter. The mean of the logarithms of the ratios is -0.0117 , corresponding to a ratio of 0.973 . The standard deviation of the logarithms is 0.1202 , corresponding to a factor of 1.32 . For comparative purposes, the straight line shown in Figure 3 represents a log-normal distribution with a mean of zero and standard deviation of 0.1202 .

In addition to providing information concerning the statistical significance of the departure of the mean ratio from the assumed mean of 1.0 , the distribution provides some insight into the reliability of the tracer techniques as applied in the Sand Storm field test program. Since the dual samples were obtained from independent sampling units (a separate engine, vacuum pump, vacuum gauge, and critical-flow orifice were used to aspirate each filter), and the amount of material on each filter was determined independently for each sample, the differences between amounts collected on filters mounted side by side is an indication of the combined error introduced by the sampling and assay techniques. There is of course the implicit assumption that the two adjacent filters were exposed to equal amounts of tracer material. The standard deviation of 0.1202 places the 90 percent confidence limits at a factor of 1.58 ; that is, measured exposures could be expected to be within the range 63 to 158 percent of an

assumed true value 90 percent of the time. Obviously, this is an upper limit of accuracy attained during the Sand Storm experiments. Systematic errors in assay techniques, such as a change in assay instrument calibration curves occurring over a period of weeks, could cause measured values to depart from true values by a slightly greater amount.

5. THE SAMPLING GRID

The tracer sampling units were arrayed on circular arcs concentric on the firing point. As explained in the preceding chapter, during the first experiments measurements of the arcwise distributions of tracer material were given a lower priority than measurements of the axial distributions. Samplers were placed along 10 arcs ranging from 100 to 2400 meters from the source. After a preliminary analysis of 14 experiments, we found that: (1) a greater arcwise sampler density was required to adequately define arcwise distributions, and (2) the density of samplers in the downwind direction could be decreased without significantly degrading the quality of the experiments. The grid configuration was then modified to include six arcs with a greater arcwise sampler density, the total number of sampling units remaining approximately the same. Originally the grid was 90 degrees in width, extending from 17 through 107 degrees true azimuth from the firing point. However, during the course of the experiments it became apparent that wind directions were invariably such that the cloud was never carried toward the northern boundary of the grid. The grid width was then reduced to the 72-degree sector, 035 to 107 degrees. Table 1 shows the various sampling grid configurations.

The motors were fired from Pad C of AFRPL's Test Area 1-16, which was situated near the col of a gentle saddle in the terrain. The land sloped gently downward from the firing point in both the upwind and downwind directions, and rose gently in both crosswind directions. The region upwind 8 miles from the firing point and downwind over the entire diffusion grid was rather regular, sandy, desert floor sparsely covered with sage brush and dotted with Joshua trees. See Figures 4 and 5. Figure 6 shows the general location and layout of the sampling grid.

Table 1. Sand Storm Sampling Grid Configurations

Arc No.	Distance From Source (meters)	Experiments No. 1-14 (17° to 107°)			Experiments No. 16-27 (17° to 107°)			Experiments No. 28-44 (35° to 107°)		
		Sampler Spacing		No. of Samplers	Sampler Spacing		No. of Samplers	Sampler Spacing		No. of Samplers
		Degrees	Meters		Degrees	Meters		Degrees	Meters	
1	100	4	6.98	23	-	-	0	-	-	0
2	150	4	10.47	23	-	-	0	-	-	0
3	200	4	13.96	23	2	6.98	46	2	6.98	37
4	250	4	17.45	23	-	-	0	-	-	0
5	300	3	15.71	31	-	-	0	-	-	0
6	400	3	20.94	31	2	13.96	46	2	13.96	37
7	600	3	31.42	31	2	20.94	46	2	20.94	37
8	800	3	41.89	31	1.5	20.94	61	1.5	20.94	49
9	1200	2	41.89	46	1.5	31.41	61	1.5	31.41	49
10	2400	1	41.89	91	1	41.89	91	1	41.89	73
			Totals	353			351			282




Figure 4. Photograph of a Portion of the Sampling Grid. Access roads along the first seven sampling arcs are visible. The sandy desert floor on which the grid is located is sparsely covered with clumps of sage brush and dotted with Joshua trees



Figure 5. Haystack Butte Rises to a Height of About 400 Feet Above the Desert Floor. Located about 1-1/2 miles southeast of the firing pad, it is the nearest prominent terrain feature




Figure 6. The General Configuration of the Sand Storm Sampling Grid, Meteorological Instrument Locations, and Phototheodolite Camera Positions

IV. Meteorological Instrumentation

Francis H. Miller, Major*
Air Force Cambridge Research Laboratories

Primary meteorological support was provided by instruments mounted on a 204-foot profile tower located 200 feet upwind from the rocket-motor firing pad. The tower, manufactured by Upright Scaffolds, was an open-frame tubular-aluminum structure, 4 by 6 feet in cross section, assembled from basic units 6 feet high. All wind sensors were mounted on retractable booms extending 12 feet from the tower in a direction perpendicular to the centerline of the tracer sampling grid. The temperature sensors were mounted on 6-foot booms extending in the opposite direction. Wind speed and directions were measured at 12, 50, 100, and 200 feet, wind azimuth and elevation angles at 18 and 150 feet, and temperature differences between 6 and 50, 6 and 100, and 6 and 200 feet. All data were recorded on strip charts.

The requirement that winds be closely monitored prior to firing the motor and during the passage of the cloud through the diffusion course necessitated installing recorders in the central control blockhouse about 1/4 mile from the tower. Unfortunately, there was not sufficient space in the control room to allow installation of all the recorders, so only two were installed in the blockhouse; the remaining seven were installed in a shelter near the foot of the profile tower.

*4th Weather Group, attached to AFCRL.

Through a switching system, signals from any of the four standard wind sets and either of the two bivane sets could be selected for display on the recorders in the blockhouse. In addition, the operation of the chart drive motors for all recorders could be controlled from the blockhouse.

The tower-mounted wind sets were standard Beckman and Whitley instruments (Figure 1). The direction transmitters, Model 1565, were lightweight airfoil vanes attached to a low-torque potentiometer. The wind speed transmitters, Model 1564, were lightweight three-cup anemometers attached to a chopper disc which produced a pulsed signal on a phototransistor. Signals from both transmitters were fed to a multichannel translator, Model 1750, and then to a Texas Instrument Company Rectiwriter dual-channel recorder. The manufacturers' specifications indicate that: (1) over an 80-degree-azimuth range the combined tolerances produced a relative error of less than 1.4 degrees, and (2) above 0.65 knot the wind speed error was less than 1.5 percent or 0.15 knot, which-




Figure 1. Beckman and Whitley Wind Set Consisting of Lightweight Airfoil Wind Vane and Three-Cup Anemometer

ever was greater. Calibration checks and adjustments for zero and full scale were performed prior to each diffusion experiment.

The bivane equipment was the standard Gelman-Gill rapid response instrument. It consisted of a lightweight bidirectional vane connected to two potentiometers, one for azimuth and one for elevation angle; a power supply translator; and a Texas Instrument Company Rectiwriter dual-channel recorder. A relative error of no more than 1.2 degrees over a range of 80 degrees in both azimuth and elevation was indicated for the system. Unfortunately the bivane sets were not operating until after the tenth experiment, and it was still later in the test series before we were satisfied with the reliability of the data. For these reasons the bivane data are incomplete.

Each of the temperature difference sets consisted of two Leeds and Northrup copper thermohms, Model No. 8195, mounted in Climet Company aspirated temperature shields, Model No. 0.6-1. The thermohms were connected into a self-balancing bridge of a suitably modified Leeds and Northrup Speedomax H recorder. The modification consisted of a variable resistance connected across one arm of the bridge to balance out inequalities in the resistances of the thermohms and interconnecting cable leads. The range of the set was -10°F to $+20^{\circ}\text{F}$. System accuracy was better than $\pm 0.3^{\circ}\text{F}$ over the ambient temperature range of -50°F to $+150^{\circ}\text{F}$. System response time for 90 percent of a step temperature change was 40 seconds. This slow response was selected to provide a smoothed recording of temperature difference so that mean values over the periods of interest could be interpolated directly from the chart record.

In addition to the meteorological instrumentation on the profile tower, three wind sets were positioned on the diffusion grid. These sets were basically Belfort Type C wind sets which were modified by Control Equipment Corporation to provide greater reliability of operation. The sets are battery powered and record on Esterline-Angus 20-pen operations recorders (see Figure 2). Their use in Project Sand Storm was primarily to determine if there were systematic differences between low-level winds recorded at the profile tower and those observed on the sampling grid. No differences were found.




Figure 2. A Modified Belfort Type C Wind Set Consisting of Lightweight Vane and Three-Cup Anemometer and an Esterline-Angus 20-Pin Operations Recorder. The sets are battery powered and were used in remote locations of the test site

V. The Tracer Assessment Technique

Einar J. Enwall
Air Force Rocket Propulsion Laboratory

1. GENERAL

Prior to beginning the diffusion experiments, several methods of beryllium assessment (Smythe and Whitem, 1961) were evaluated to determine which was best suited for the routine assay of tracer samples to be collected during the experiments. It was predetermined that the tracer material would be collected on molecular membrane filters that showed no trace of beryllium. It was understood that the samples would be highly contaminated; therefore, the chemical analysis should be specific for beryllium. Operational considerations dictated that the procedure be capable of handling about 400 samples per week on a continuing basis. Additional requirements were:

- a. The detection threshold should be no greater than $0.001 \mu\text{g}$ of Be and the assay procedure adaptable to as much as $500 \mu\text{g}$ of Be on the sample.
- b. The root-mean-square error should be not greater than 5 percent on samples of $1.0 \mu\text{g}$ or more, and no greater than 10 percent on samples of 0.05 to $1.0 \mu\text{g}$ Be.

Spectrophotometric and colorimetric techniques were quickly eliminated from

further consideration because of their inadequate sensitivity and precision. A neutron activation technique that was tested had the same deficiencies, but not to the same extent; it would have been useful as a scanning device, had there not been technical difficulties that were corrected too late for the technique to be of value in the Sand Storm experiments. Emission spectrographic methods were not considered feasible because they proved to be too time-consuming for the highly contaminated samples.

The morin-fluorometric method (Sill et al, 1961), although a lengthy procedure requiring considerable skill and care, was modified and adapted to provide the required sensitivity and production volume while approaching the stated precision requirements. When tested on samples containing known amounts of beryllium, the modified morin-fluorometric method achieved the precision shown in Table 1.

Table 1. Precision of Morin-Fluorometric Method of Beryllium Determination

Be on Filter	Number of Samples	RMS Error	
(μg)		(μg)	(%)
0.1	23	.0139	13.9
0.5	23	.0224	11.2
1.0	24	.0851	8.5
5.0	21	.3351	6.7
10.0	25	.5852	5.9
20.0	22	1.414	7.1
80.0	21	5.083	6.4

The fluorometric determination of beryllium using morin as a reagent has been reported in great detail elsewhere (Sill et al, 1961). Therefore, only the briefest description is given here, followed by notes on the instrumentation and procedures used for Project Sand Storm assays.

Beryllium reacts with morin (2', 4', 3, 5, 7 pentahydroxy flavone) in an alkaline solution to produce a compound that fluoresces when energized by ultraviolet radiation. Interferences from fluorescent compounds of other metals, such as lithium, scandium, zinc, calcium, and others, are eliminated by addition of a complexing agent (EDTA), making the morin reaction nearly specific for beryllium. A second interference is produced by elements such as copper, silver, and manganese which oxidize morin and destroy the fluorescence. This is eliminated by separating insoluble beryllium hydroxide from the soluble oxidizers before morin is

added. Silica is excluded as an interference by precipitation and filtration.

Particular attention was directed to factors affecting the precision of measurements. The temperature of the fluorescing compound was controlled to $\pm 0.1^{\circ}\text{C}$ to lessen the effect of changes in temperature on the intensity of fluorescence. A buffer system was employed to stabilize alkalinity which also affects the intensity of fluorescence. Other procedures were adopted so that the assay technique would be consistently reliable and more efficient when applied to a large number of samples. Still other procedures were adopted to allow the technique to be applied by personnel with varying degrees of skill in laboratory methods.

A special laboratory with all the equipment necessary for beryllium assays was set aside in AFRPL's Laboratory Services Division and was staffed with four technicians. After a few weeks the laboratory could handle some 80 to 100 samples daily. Its operations were continuously monitored during the entire course of the diffusion program. Every reasonable precaution was taken to prevent contamination of glassware. Instrument calibrations were frequently checked. Reagent solutions were meticulously prepared with best grade chemicals. In short, every effort was made to insure that laboratory standards were maintained at a peak level.

2. OUTLINE OF THE ASSAY PROCEDURE

This section is devoted to a descriptive outline of the laboratory procedure used for determining the amount of beryllium in Sand Storm tracer samples. Instrumentation, reagents, and laboratory methods differ somewhat from any previously reported work on beryllium determinations, but the procedure closely parallels the morin-fluorometric method reported by Sill et al (1961).

2.1 Instrumentation

A Turner fluorometer Model No. 111 with General Electric mercury lamp No. F4T4/BL was used. The major emission was at 360 m μ . Filters used in the fluorometer were Wratten (2 in. x 2 in.) numbers 2A, 47B, 2A-12, 58, 1-60, and 2 ND. The cuvettes were 12 x 75 mm round pyrex tubes.

2.2 Reagents

Phenol Red. Dilute 0.1 g of the sodium salt of phenolalulphothalein, certified A. C. S. grade, to 250 ml with distilled water.

Morin Solution, 0.008 percent. Dissolve 8 mg of morin (purchasable from L. Light Co., Ltd., Pyle Estate, Colabrook Near Slugh Bucks, England; imported by Leonard Elion, Ph. D., 2 Concord Avenue, Larchmont, New York) in 250 ml of absolute ethyl alcohol. Dilute to 1000 ml with distilled water. Mix. Store in actinic bottle.

Ammonium Chloride Solution, 25 percent. Add 250 g of A. R. grade ammonium chloride to 750 ml of distilled water.

EDTA and TEA Solution. Place 5 g of A. R. grade (ethylene dinitrilo) tetra acetic acid, disodium salt, and 2 g of refined 2, 2' 2'' nitrilo triethanol in 100-ml volumetric flask and dilute to volume with distilled water.

Buffer Solution. 156 g of A. R. grade sodium hydroxide, 63 g A. R. grade citric acid, and 37 g A. R. grade boric acid. Make up to 2 liters with distilled water.

Aluminum Nitrate Solution, 0.05 M. Dissolve 37.5 g of $\text{Al}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$ A. R. grade in 200 ml of distilled water and make up to 2000 ml.

Beryllium Sulfate Solution, 1 μg Be/ml. Dissolve 0.9820 g $\text{BeSO}_4 \cdot 4\text{H}_2\text{O}$, purified, Fisher Scientific Co., in 10 ml of concentrated sulfuric acid. Heat if necessary. Cool. Transfer solution to 1000-ml volumetric flask containing 200 ml of distilled water. Dilute to volume. Mix. Take 10 ml of this solution and dilute to 500 ml, using 0.1 N sulfuric acid as diluent.

Beryllium Sulfate Solution, 0.1 μg Be/ml. Pipette 10 ml of 1 μg Be/ml into a 100-ml volumetric flask. Dilute to volume with 0.1 N sulfuric acid.

2.3 Procedure

Place filter in 125-ml narrow-neck Erlenmeyer flask. (Use hood.) Wet filter paper with 1 ml of concentrated sulfuric acid. Heat filter until it chars. Cool. Add 10 ml of concentrated nitric acid. Place flask on hot plate that is hot enough to vaporize the sulfuric acid. Heat to dense fumes. Cool. If solution is a yellow to brown color, add 10 ml more of concentrated nitric acid. Add a small amount of potassium perchlorate (0.2 to 0.4 g). Heat until solution becomes colorless and volume of solution is approximately 1 ml. Cool. Dilute solution with 10 ml of water. Filter solution through No. 40 Whatman paper into a 100-ml volumetric flask. Dilute to volume and mix.

Pipette a suitable aliquot (not over 10 ml) into a 15-ml centrifuge tube. Add 1 ml of 25 percent ammonium chloride solution, 1 ml of 0.05 M aluminum nitrate solution, and two drops of phenol red indicator. Mix. Neutralize solution with 1:3 ammonium hydroxide solution to red color. Dilute to 10 ml and mix. Centrifuge at 1200 $\times$ gravity for 15 minutes, or sufficient time and speed, to compact beryllium and aluminum hydroxides at bottom of centrifuge tube. Discard filtrate. Add two

drops of phenol red solution to the centrifuge tube. Acidify contents of centrifuge tube with 0.05 N sulfuric acid. Add 0.5 N sulfuric acid. Add 0.5 ml of EDTA and TEA solution. Neutralize with buffer solution. Add 2 ml more of buffer solution and mix. Centrifuge at 1200 x gravity for 5 minutes. If a precipitate is present, decant the solution to clean centrifuge tube. Place tube in water bath maintained at $25 \pm 0.1^\circ\text{C}$. When sample temperature is 25°C , add 1 ml of morin solution. Mix and transfer solution to a cuvette and place cuvette in fluorometer. Set the fluorometer slit opening, and place suitable filters in primary and secondary position, as called for in curves No. 1, 2, or 3, to obtain readings on fluorometer previously zeroed against a reagent blank. The reagent blank is prepared the same way as the sample. Obtain the beryllium content from standardization curves.

2.4 Standardization

Three calibration curves are prepared.

Curve No. 1 for 0 to 0.08 $\mu\text{g Be}$

Place millipore filters in fourteen 100-ml narrow-mouthed Erlenmeyer flasks. With a microburet, transfer volumes of 0.1 $\mu\text{g Be/ml}$ solution to the flasks to give the following concentrations: 0, 0.005, 0.01, 0.02, 0.03, 0.05, and 0.07 $\mu\text{g Be}$. Treat these standards in the same way as the samples. Set slit at 3 X. Place filters 2A and 47B in the primary position, and filters 58 and 2A-12 in the secondary position. Adjust fluorometer to zero on 0 $\mu\text{g Be}$ sample. Obtain fluorometer readings on each standard. Plot straight-line curve of amount of Be versus fluorometer readings.

Curve No. 2 for 0 to 0.7 $\mu\text{g Be}$

Place millipore filters in fourteen 100-ml narrow-mouthed Erlenmeyer flasks. Transfer to the flasks, by means of a microburet, volumes of 0.10 $\mu\text{g Be/ml}$ solution to give the following concentrations: 0, 0.05, 0.1, 0.2, 0.3, 0.5, and 0.7 $\mu\text{g Be}$. Treat these standards in the same way as the samples. Set slit at 1 X. Place filters 2A and 47B in the primary position and filters 2A-12, 58, and 1-60 in the secondary position. Adjust fluorometer to zero on the 0.0 $\mu\text{g Be}$ sample. Obtain fluorometer readings on standards. Set up a straight-line curve based on amount of Be versus fluorometer readings.

Curve No. 3 for 0.7 to 5 $\mu\text{g Be}$

This curve is prepared in the same manner as curves 1 and 2, except that it is non-linear. The slit is set at 10 X. The primary filters are 2A and 47B, and the secondary filters are 58 and 2ND. The curve is used to obtain an approximate beryllium concentration in samples containing large amounts of beryllium, so that an appropriate dilution factor can be made for subsequent assays using curve 2.

References

- Sill, C.W., Willis, C.P., and Flygare, K., Jr. (1961) Improvements in the fluorometric determination of submicrogram quantities of beryllium, Anal. Chem., 33:1671.
- Smythe, L.E., and Whitem, R.N. (1961) Analytical chemistry of beryllium, Analyst 86:83-94.

VI. Meteorological Data Reduction and Processing

Robert L. Noblin, Clayton E. Graham
and William E. Mayer
Air Force Rocket Propulsion Laboratory

Personnel of the Air Force Rocket Propulsion Laboratory reduced and processed the wind data obtained from the Sand Storm profile tower. Wind azimuth-angle measurements made at four tower levels and wind elevation-angle measurements made at two levels were recorded on strip charts at a chart speed of 6 inches per minute for 40-minute periods during each experiment. These analog records were reduced to 1-second digital values using a Benson-Lehner "Oscar J" chart reader that re-recorded the information on punched cards. Each 40-minute record was reduced to digital form but, in general, only the first 10 minutes of each record was processed in the computer routines. Occasionally, however, more than 10 minutes of record was required to adequately define the spectral curve. In these cases the entire 40-minute record was processed.

Two separate computer routines were used to process the digitized wind data. Although one expanded program could have provided the desired information, it was more economical to use two independent programs, each designed to satisfy a specific requirement.

The first and by far the simpler of the two programs, the one whose results were used to estimate the shape of the spectral curve, provided calculations of the amount of energy contained in various regions of the low-frequency end of the one-dimensional turbulent energy spectrum. Elimination of the energy contributed

by high-frequency (small) eddies was achieved by averaging data points continuously over overlapping intervals of length s before computing the variance of wind fluctuations. This is equivalent (in electrical terms) to low-pass filtering. The shape and efficiency of this filter and its application in turbulent diffusion analyses are discussed by Smith (1962) and Pasquill (1962).

The input data for the low-pass filter program were the 1-second digitized values of wind data:

$$A_r; \quad r = 1, 2, 3, \dots, n.$$

For each smoothing interval, s , of the group:

$$s = 2^{m-1}; \quad m = 1, 2, 3, \dots, 10.$$

A set of averaged data points was found from:

$$(\bar{A}_s)_i = \frac{1}{s} \sum_{j=i}^{s+i-1} A_j; \quad i = 1, 2, 3, \dots, n_s$$

where the number of averaged data points in the record of length n is:

$$n_s = n - s + 1.$$

The variances are:

$$\sigma^2(\bar{A}_s) = \frac{\sum_{i=1}^{n_s} (\bar{A}_s)_i^2 - \frac{1}{n_s} \left[\sum_{i=1}^{n_s} (\bar{A}_s)_i \right]^2}{n_s - 1}.$$

The second computer program was used to determine the amount of energy contained in various bands of the turbulent energy spectra. The high-frequency energy was eliminated in exactly the same way as in the case of low-pass filtering; that is, the record was smoothed by averaging data points. Low-frequency energy was eliminated by limiting the interval over which the variances were computed. In practice this was accomplished by sampling the smoothed record over overlapping intervals of length T corresponding to a frequency below which energy is to be excluded. The variance was computed for each sampling interval, T , in the

period of record, and these variances were averaged. The average was taken as a measure of the energy contributed by periods greater than $2.25 T$ and less than 2.25 times s (Pasquill, 1962).

As in the previous example, the input data were 1-second samples taken over the period of record:

$$A_r; r = 1, 2, 3, \dots, n.$$

The smoothing intervals were:

$$s = 2^{m-1}; m = 1, 2, 3, 4, 5,$$

and the sampling intervals:

$$T = 2^{m+3}; m = 1, 2, 3, 4, 5, 6.$$

The sets of averaged data points for the various combinations of T and s are:

$$(\bar{A}_{T,s})_{k,i} = \frac{1}{s} \sum_{j=i}^{s+i-1} A_j; \quad \text{for } k = 1, 2, 3, \dots, n_T$$

and $i = k, k+1, k+2, \dots, T-s+k,$

where the number of sampling intervals, T , in the period of record is:

$$n_T = n - T + 1.$$

This process results in $n_r (= T - s + 1)$ values of $(\bar{A}_{T,s})$ in an interval of length T . The variances of the $(\bar{A}_{T,s})$ values are:

$$\sigma^2(A_{T,s}) = \frac{\sum_{i=k}^{T-s+k} (A_{T,s})_{k,i}^2 - \frac{1}{n_r} \left[\sum_{i=k}^{T-s+k} (A_{T,s})_{k,i} \right]^2}{n_r - 1}.$$

Averaging the n_T variances over the entire record:

$$\overline{\sigma^2(A_{T,s})} = \frac{1}{n_T} \sum_{k=1}^{n_T} \left\{ \frac{\sum_{i=k}^{T-s+k} (\bar{A}_{T,s})_{k,i} - \frac{1}{n_r} \left[\sum_{j=k}^{T-s+k} (\bar{A}_{T,s})_{k,i} \right]^2}{n_r - 1} \right\}.$$

The 29 nontrivial values of $\overline{\sigma^2(A_{T,s})}$ for the combinations of $s = 1, 2, 4, 8, 16$ and $T = 16, 32, 64, 128, 256, 512$ represent the intensity of turbulence in various portions of the one-dimensional energy spectrum. These values are shown in Appendix C for azimuth data taken at four levels during each of the Sand Storm experiments. Because of incomplete data and instrument difficulties experienced with the bivanes, similar computations for elevation angles are not included.

References

- Pasquill, F. (1962) Atmospheric Diffusion, Van Nostrand Co. Ltd., London.
- Smith, F. B. (1962) The Effect of sampling and averaging of turbulence,
Quart. J. Roy. Met. Soc. 88.

VII. An Operations-Oriented Analysis

John H. Taylor, Lt. Colonel
Air Force Cambridge Research Laboratories

1. INTRODUCTION

The objective of this chapter is to present an analysis that was directed toward obtaining an operationally useful solution for the specific problem facing AFRPL test range officials—namely, the ability to estimate the toxicological hazard associated with open-air firings of small, solid propellant rocket motors whose exhaust products are highly toxic. Except for the specific problem at hand, no attempt was made to evaluate theoretical works or to advance the knowledge of diffusion from instantaneous sources; such investigations are left for further analyses where the Sand Storm data may prove useful.

Before beginning the discussion of the analysis, it might be well to define, at least in an intuitive sense, what we mean by diffusion since it can be viewed in several ways. For example, a diffusing puff embedded in an air current is subject to the variations in speed and direction of the current and will be observed to take a meandering, undulating trajectory if viewed from a fixed frame of reference. If viewed from a reference point moving with the cloud, only the growth and dilution of the puff will be observed. When one thinks of diffusion it is ordinarily only the latter process that is considered, and theoretical and experimental work has been limited largely to this concept of diffusion. It is obvious, however, that

inhalation-level dosages are to some degree influenced by both the rate of growth of the puff and the height of its center of mass relative to the plane in which dosage observations are made. In the case of a plume, time-averaging virtually eliminates the effect of instantaneous displacements of the plume above or below the time-mean axis. This obviously is not so for a puff. Irregularities in the downwind distribution of dosages are to be expected. However, prior to the Sand Storm experiments it was not known to what extent those influences would be exhibited. If the irregularities caused by variations in the height of the puff above the sampling grid were small compared with tracer dilution rates, an estimating equation could be developed in a form suggested by traditional theoretical work. If they were not, some other approach would have to be taken.

It will be shown in the following discussion that downwind distributions were quite irregular and that the influence of the irregularities was sufficiently strong to severely limit the ability of measurable meteorological parameters to explain the variance of dilution rates observed near the surface. This precluded the development of an operationally useful estimating equation relating downwind dosages to meteorological parameters. In the final analysis, inhalation-level dosages are related by means of probability statements to distances from the source.

2. GENERAL CONSIDERATIONS

The concentration of a pollutant cloud with Gaussian distribution released as an instantaneous point source was shown by Pasquill (1962) to be:

$$\chi(x, y, z, t) = \frac{Q}{(2\pi)^{3/2} \sigma_x \sigma_y \sigma_z} \exp \left[-1/2 \left(\frac{x^2}{\sigma_x^2} + \frac{y^2}{\sigma_y^2} + \frac{z^2}{\sigma_z^2} \right) \right]$$

where:

χ = the concentration at time t found at distance x in the direction of travel, at lateral distance y and vertical distance z , relative to the center of the puff,

Q = the amount of pollutant released, and

σ_x , σ_y , and σ_z = the standard deviations of the material about the mean.

If the material is transported with a speed $\bar{u} = \frac{x}{t}$, the dosage, $E = \int_0^\infty \chi dt$, can be shown to be:

$$E = \frac{Q}{2\pi \sigma_y \sigma_z \bar{u}} \exp \left[-1/2 \left(\frac{y^2}{\sigma_y^2} + \frac{z^2}{\sigma_z^2} \right) \right]$$

and at a given downwind distance the ground-level point passed by the center of the puff receives a dosage:

$$E_p = \frac{Q}{\pi \sigma_y \sigma_z \bar{u}} \quad (1)$$

From theoretical considerations of turbulent flow, which incorporate several assumptions that are only approximated in the real atmosphere, Smith and Hay (1961) show that for a puff:

$$\sigma_y \propto \sigma^2(\theta) X$$

and

$$\sigma_z \propto \sigma^2(\phi) X$$

where $\sigma^2(\theta)$ and $\sigma^2(\phi)$ are the variances of the azimuth and inclination angles, respectively, of wind fluctuations and X is the distance from the source.

Equation (1) then becomes:

$$\frac{E_p}{Q} = \frac{k}{\pi \sigma^2(\theta) \sigma^2(\phi) X^2 \bar{u}} \quad (2)$$

where k is a constant of proportionality.

The equation suggests that with a knowledge of the variance of wind direction fluctuations and of the mean wind speed we could predict the peak dosage, normalized for source strength, as a function of downwind distance. One of the first problems that arises is selecting the values for $\sigma^2(\theta)$ and $\sigma^2(\phi)$, inasmuch as it is possible to obtain any number of values of variance from a single wind

record simply by changing the range of frequencies over which the variances are computed.

Consider the puff that grows in size under the influence of turbulent diffusion. As the puff grows, larger eddies become more and more effective in distributing the material, while smaller eddies become less important. Therefore, for a given cloud size there exists a range of eddy sizes which is important in diffusing the cloud. Eddies much larger merely move the cloud in an irregular trajectory (horizontal and vertical) as it travels downwind; eddies much smaller ineffectively nibble at the edges of the cloud. However, for an initially small cloud that eventually grows large, all eddies up to those comparable in size to the dimensions of the large cloud play a role in distributing the material. Therefore, it is to be expected that the range of eddy sizes effective in diffusing initially small puffs extends over the high-frequency end of the energy spectrum. The problem is to determine which portion of the turbulent energy spectrum it is that contains the productive eddies. To do so in a deterministic manner is virtually impossible when it is remembered that wind observations taken at a point fixed in space do not adequately define the energy spectrum as observed from a frame of reference traveling with the cloud, the one which is the more relevant in the diffusion of puffs. The shapes of the spectra may be similar, but there is a relative displacement of the spectrum observed from the fixed point toward higher frequencies. The magnitude of this displacement has for some time been a matter of conjecture. Indeed, whether it is a constant or a function of meteorological parameters has not been settled. In this analysis we shall not attempt an investigation of those problems. Rather, we shall content ourselves with determining, empirically, the range of eddy sizes (frequencies) which is effective in diffusing puffs of the size and character under consideration.

By applying various smoothing intervals, s , to serially recorded wind data (that is, averaging the recorded values over time intervals of length s) before computing the variance of wind direction fluctuations, the energy contributed by high-frequency (small) eddies can be eliminated. This is commonly referred to as low-pass filtering. By limiting the period of record over which the variance is taken, the energy contributed by low-frequency (large) eddies can be eliminated. In practice the period of record is not necessarily restricted, but a number of variances are computed, each for a sampling interval of length T . The average of these variances taken over the entire period of record is given as a measure of the energy in the high-frequency end of the spectrum. This is in effect high-pass filtering. Both filters can be applied in computing the variance, thus obtaining the energy within a band of frequencies. The technique used in applying the filters to the Sand Storm wind data is described

in Chapter VI.

Assuming that the material within the cloud is distributed normally, the standard deviation of the material observed at inhalation-level is the same as would be observed at any other height. Therefore, for a puff whose center may rise and fall as it is carried downwind, thus causing irregularities in the downwind distribution of ground-level dosages, the most coherent measure of the puff's growth is not the rate of change of magnitude of observed dosages but the change of lateral distributions.

Smith and Hay (1961) hypothesized that the growth rate, $\Delta\sigma_y/\Delta X$, of the initially small puff is approximately constant and proportional to the energy contained in the high-frequency end of the turbulent-energy spectrum. This raises several questions. Is the puff generated by firing a rocket motor "initially small"? What is the appropriate portion of the turbulent-energy spectrum?

For purposes of this investigation, "initially small" means that the initial dimensions of the puff are small when compared with eddies containing significant amounts of energy. By convention (Smith and Hay, 1961) we will define a small puff as one whose initial standard deviation, σ_{y_0} , is less than one-tenth the length-scale of turbulence as estimated by the formula (Pasquill, 1962):

$$l(\theta) = \frac{\bar{u}}{4\pi n_{\max}}$$

where $l(\theta)$ = length-scale based on wind-azimuth fluctuations,

$\bar{u}$ = mean wind speed,

and $n_{\max}$ = the frequency at which $nG(n)$ is maximum
on the curve of
 $nG(n)$ versus $\log n$. $\sigma^2(\theta) = \int_0^\infty nG(n) d \log n$.

Figure 1 shows plots of $nG(n)$ vs. $\log n$ for wind-azimuth fluctuations at three heights taken during a 20-minute wind run during Experiment No. 14. Here $n_{\max}$ occurs at about 5×10^{-3} cycles per second at all levels. The 12-foot mean-wind speed was 5.3 meters per second, giving a length-scale of 84.8 meters. Examination of σ_y values at 100 meters from the source and phototheodolite data correlated with motor size provided an estimate of σ_{y_0} , the initial standard deviation of the cloud. For Experiment No. 14, σ_{y_0} was estimated to be 4.6 meters. By definition the cloud is initially small.




Figure 1. One-Dimensional Turbulent Energy Spectrum Computed for Three Levels of Wind-Azimuth Observations Taken During Experiment No. 14. Computations were based on 20 minutes of data reduced to 1-second readings.

The length-scale for each experiment was compared with estimates of σ_{y0} . It was found that with one exception (Experiment No. 13) the tests produced "initially small" clouds.

To determine which measure of the turbulent energy, $\sigma^2(\theta)_{T,s}$, was best correlated with the rate of growth of the tracer cloud, $\Delta\sigma_y/\Delta X$, correlation coefficients between the two were computed. For each experiment, 87 values of $\sigma^2(\theta)_{T,s}$ ($T = 16, 32, 64, 128, 256, 512$ seconds and $s = 1, 2, 4, 8, 16$ seconds) were computed, using the azimuth data recorded by the Beckman-Whitley wind sets. Not all of the measurements of σ_y could be considered valid for various reasons, the chief one being that an insufficient number of samples was exposed to significant amounts of tracer material. A substantial number of measurements were eliminated, even when the criterion for selection was relaxed to the point that: (1) an acceptable distribution be defined by 5 samples having 0.5 microgram or more of the tracer and (2) the peak be at least 10 times as

great. After eliminating unreliable measurements, based on these criteria, there were 32 experiments for which $\Delta\sigma_y/\Delta X$ could be computed for the distance interval 200 to 400 meters, 24 experiments for the interval 200 to 1200 meters, 14 experiments for the 200- to 2400-meter interval, and 14 for the 1200- to 2400-meter interval.

The matrices of correlation coefficients obtained by comparing four measurements of $\Delta\sigma_y/\Delta X$ with 87 measurements of $\sigma^2(\theta)_{T,s}$ per experiment are shown in Table 1. There are four observations which immediately suggest themselves. First, the 12-foot wind record provides the best correlations. Second, there is little, if any, advantage gained by smoothing the wind record. This is in accord with the intuitively drawn conclusion that for initially small clouds all eddies in the high-frequency end of the spectrum are effective in the distribution of the material. Third, examining only the 12-foot level, there is a trend for the maximum value of the correlation coefficient to occur at greater sampling intervals, T , as the travel distance (and cloud-size) is extended. This is shown graphically in Figure 2, and is in accord with our intuitive reasoning that larger eddies begin more and more to exert their influence as the cloud grows in size. Fourth, it appears that over the range of travel distances involved there would be but little error introduced if T were selected as 128 seconds and s as 1 second.

One more comment needs to be made about the values of the correlation coefficients in Table 1. Examining only the 12-foot-level correlation coefficients, one notes for $s = 1$ that the highest value for the distance increment 200 to 400 meters is 0.89; for the increment 200 to 1200 meters it is 0.90; for 200 to 2400 meters it is 0.84; and for 1200 to 2400 meters it is 0.87. None of these values is significantly different, statistically, from a true correlation coefficient of, say, 0.87. Therefore, it is probably not valid to conclude that the correlation decreases with increasing distance.

It was not possible to make a comparison of $\Delta\sigma_z/\Delta X$ with measured values of $\sigma^2(\phi)_{T,s}$ since no measurements of the vertical distribution of the tracer were made. However, since all the experiments were conducted under thermally unstable conditions, it is reasonable to suppose that the vertical rate of growth was positively correlated with the lateral rate of growth. It should then be possible to use measured values of $\sigma^2(\theta)$ and $\bar{u}$ to develop an estimating equation similar to Eq. (1) for obtaining expected values of E_p/Q .

Table 1. Correlation Coefficients for $\frac{\Delta\sigma_y}{\Delta X}$ vs. $\sigma^2(\theta)_T, s$

12-ft wind

50-ft wind

200-ft wind

s	T	16	32	64	128	256	512
1		.87	.89	.88	.86	.85	.75
2		.87	.89	.88	.86	.85	.75
4		.87	.89	.88	.85	.85	.75
8		.88	.89	.88	.86	.84	.74
16		.89	.88	.86	.84	.74	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_1$$

s	T	16	32	64	128	256	512
1		.88	.89	.90	.89	.88	.79
2		.89	.89	.90	.89	.88	.79
4		.89	.89	.90	.89	.88	.79
8		.89	.89	.90	.89	.88	.79
16		.90	.90	.89	.88	.79	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_2$$

s	T	16	32	64	128	256	512
1		.66	.72	.76	.82	.84	.72
2		.66	.72	.76	.82	.84	.72
4		.67	.71	.75	.82	.83	.72
8		.65	.70	.74	.82	.83	.72
16		.66	.72	.82	.83	.72	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_3$$

s	T	16	32	64	128	256	512
1		.73	.78	.81	.85	.87	.75
2		.72	.77	.85	.85	.87	.76
4		.72	.76	.85	.85	.86	.76
8		.72	.74	.85	.84	.86	.76
16		.71	.84	.84	.86	.75	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_4$$

s	T	16	32	64	128	256	512
1		.82	.84	.83	.78	.76	.65
2		.80	.83	.82	.78	.76	.64
4		.78	.82	.82	.77	.76	.63
8		.78	.81	.82	.77	.75	.63
16		.83	.83	.76	.74	.61	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_1$$

s	T	16	32	64	128	256	512
1		.83	.86	.86	.82	.81	.71
2		.82	.85	.86	.83	.80	.70
4		.81	.85	.86	.82	.80	.69
8		.81	.85	.86	.82	.80	.69
16		.87	.87	.82	.80	.68	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_2$$

s	T	16	32	64	128	256	512
1		.63	.73	.71	.70	.69	.70
2		.64	.73	.71	.70	.69	.70
4		.65	.74	.71	.70	.69	.70
8		.66	.73	.70	.69	.69	.70
16		.70	.67	.66	.69	.70	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_3$$

s	T	16	32	64	128	256	512
1		.80	.77	.76	.75	.76	.76
2		.80	.79	.76	.75	.76	.76
4		.82	.79	.76	.74	.76	.76
8		.82	.78	.74	.73	.76	.76
16		.74	.70	.70	.75	.75	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_4$$

s	T	16	32	64	128	256	512
1		.58	.56	.54	.49	.44	.34
2		.57	.54	.54	.48	.43	.33
4		.55	.53	.53	.48	.42	.32
8		.53	.50	.52	.47	.42	.31
16		.50	.53	.47	.41	.29	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_1$$

s	T	16	32	64	128	256	512
1		.55	.52	.51	.45	.40	.30
2		.53	.50	.50	.44	.39	.30
4		.51	.48	.49	.43	.38	.29
8		.48	.55	.48	.42	.37	.27
16		.55	.49	.43	.39	.25	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_2$$

s	T	16	32	64	128	256	512
1		.60	.63	.61	.55	.46	.46
2		.60	.62	.61	.54	.46	.46
4		.58	.61	.61	.54	.45	.45
8		.59	.59	.61	.53	.44	.45
16		.63	.65	.53	.44	.44	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_3$$

s	T	16	32	64	128	256	512
1		.67	.67	.66	.60	.57	.54
2		.67	.67	.65	.59	.55	.54
4		.69	.66	.65	.58	.54	.53
8		.60	.63	.64	.56	.53	.52
16		.66	.66	.56	.52	.52	

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_4$$

$$\left(\frac{\Delta\sigma_y}{\Delta X}\right)_1 = \frac{\sigma_{y400} - \sigma_{y200}}{200} \left(\frac{\Delta\sigma_y}{\Delta X}\right)_2 = \frac{\sigma_{y1200} - \sigma_{y200}}{1000} \left(\frac{\Delta\sigma_y}{\Delta X}\right)_3 = \frac{\sigma_{y2400} - \sigma_{y200}}{2200} \left(\frac{\Delta\sigma_y}{\Delta X}\right)_4 = \frac{\sigma_{y2400} - \sigma_{y1200}}{1200} \left(\frac{\Delta\sigma_y}{\Delta X}\right)_4$$




Figure 2. Correlation Coefficients Between Rate of Cloud Growth and the Intensity of Turbulence for Various Travel Distances as a Function of the Sampling Interval. The rates of growth, $\Delta \sigma_y / \Delta X$, are for travel distances 200 to 400 meters, 200 to 1200 meters, 200 to 2400 meters, and 1200 to 2400 meters. N is the number of experiments for which the correlation coefficients could be computed

3. REGRESSION ANALYSIS

A multiple-regression analysis was carried out using an estimating equation of the form:

$$\frac{E_p}{Q} = a X^b [\sigma^2(\theta)_{128,1}]^c \bar{u}^d \quad (3)$$

where $\frac{E_p}{Q}$ = the peak dosage normalized for source strength,

X = distance from the source,

$\sigma^2(\theta)_{128,1}$ = variance of wind direction fluctuations with 1-second smoothing interval and 128-second sampling interval,

$\bar{u}$ = mean wind speed, and

a , b , c , and d are the coefficients of the estimating equation.

This form is suggested by Eq (2) but allows for empirical determination of the estimating equation coefficients, a desirable feature since many simplifying assumptions implicit in Eq (2) are not met in this series of experiments.

The equation is designed to estimate the downwind distribution of E_p/Q in that region which is not influenced to a significant degree by the effective height of the source, that is, in a region that is distant enough from the source so that the inhalation-level dosages resulting from the elevated source are substantially the same as would be observed from a ground-level source. Examination of downwind distributions of E_p for individual experiments indicated that this region on occasion did not include measurements taken within 300 meters of the source. Therefore, the regression analysis was performed on data collected on the five arcs from 400 meters to 2400 meters from the source. Data for the 38 experiments for which we have reliable measurements of E_p at all 5 travel distances are included. The regression analysis yielded:

$$\frac{E_p}{Q} = 2.91 X^{-1.59} [\sigma^2(\theta)_{128,1}]^{-.530} \bar{u}^{-.230} \quad (4)$$

where $\frac{E_p}{Q}$ = peak dosage normalized for source strength in units of seconds per cubic meter,

X = downwind distance in meters,

$\sigma^2(\theta)_{128,1}$ = variance of wind-direction fluctuations (with smoothing intervals of 1 second and sampling interval of 128 seconds) in units of degrees squared, and

$\bar{u}$ = mean wind speed in units of meters per second.

The analysis also shows that there is very little reduction of variance contributed by $\bar{u}$. This is not surprising since it was noted that: (1) $\bar{u}$ is not well correlated with E_p/Q , and (2) there is a high correlation between $\bar{u}$ and $\sigma^2(\theta)$. (See Table 2.) Nothing is lost in the way of prediction accuracy when $\bar{u}$ is eliminated from the equation. It then becomes:

$$\frac{E_p}{Q} = 1.25 X^{-1.59} [\sigma^2(\theta)_{128,1}]^{-.415} \quad (5)$$

where the variables and units are the same as in Eq (4).

Table 2. Correlation Coefficients Between the Logarithms of Variables in Equations (4), (5), and (6)

	$\log X$	$\log \sigma^2(\theta)_{128,1}$	$\log \bar{u}$
$\log \frac{E_p}{Q}$	-0.67	-0.21	0.14
$\log \sigma^2(\theta)_{128,1}$			-0.80

Again, Table 2 shows that $\sigma^2(\theta)$ is not well correlated with E_p/Q . The precision gained by its inclusion in the estimating equation is insignificant. When it is eliminated, the equation becomes:

$$\frac{E_p}{Q} = .180 X^{-1.59} \quad (6)$$

It can be seen from Table 3, which shows several measures of the accuracy of estimate of Eqs. (4), (5), and (6), that there is really nothing to be gained by the inclusion of the meteorological parameters. The multiple correlation coefficients between logarithms of the observed values of the dependent and independent variables are shown in the second column of Table 3. They are shown here for the reader who is accustomed to using them as a measure of the precision of an estimating equation. However, the multiple correlation coefficient is not as meaningful a measure as those shown in the remaining columns, because we wish to know the accuracy of estimate of E_p/Q , not the logarithm of E_p/Q . The third column shows the reduction of variance achieved by regression equations containing the various combinations of independent variables. It can be seen that the reduction of variance, while statistically significant, is not high, and that little improvement is realized by

Table 3. Efficiency of Equations (4), (5), and (6)

Independent variables	Multiple correlation coefficient for log $\frac{E_p}{Q}$ and log of independent variables	Percent estimated of variance*	Percent reduction within a factor of 2 of observed $\frac{E_p}{Q}$	Percent reduction within a factor of 4 of observed $\frac{E_p}{Q}$
X	.67	24	45	83
X and $\sigma^2(\theta)_{128,1}$	.70	31	54	82
X, $\sigma^2(\theta)_{128,1}$ and $\bar{u}$	.70	31	53	81

$$* \text{ Percent reduction of variance} = 100 \left\{ 1 - \frac{\sum \left[\left(\frac{E_p}{Q} \right) - \left(\frac{E_p}{Q} \right)' \right]^2}{\sum \left[\left(\frac{E_p}{Q} \right) - \left(\frac{E_p}{Q} \right) \right]^2} \right\}$$

the introduction of meteorological parameters. Here again, this standard measure of the accuracy of the estimating equation has a serious deficiency when applied to data such as these which extend over several orders of magnitude. It tends to weight too heavily the larger values, in this case E_p/Q values measured

close to the source, at the expense of the lower values, or those at the most distant arcs. Another "yardstick" for measuring the accuracy of the prediction equations is the percentage of estimated values which are within a given range of the observed values. In this particular case we have chosen factors of 2 and 4 for two different ranges. The fourth column of Table 3 shows that a slight, but not statistically significant, gain is shown by the inclusion of $\sigma^2(\theta)$, when the percentage within a factor of 2 is used as the measure of prediction accuracy. No improvement in accuracy is shown when the factor of 4 is the measurement criterion.

It is not particularly surprising that the accuracy of the estimating equation is so low, even when tested on dependent data. The reason is that the behavior of a diffusing puff is very erratic, subject to low-frequency lifting and descending motions. A close examination of a few of the experiments will illustrate the erratic behavior and will show the futility of attempting to develop concise, accurate, quantitative statements of inhalation-level dosages resulting from diffusing puffs of the character under consideration here.

Figure 3 shows, for three experiments, the downwind distribution of peak dosages normalized for source strength. Each experiment was conducted under thermally unstable and relatively strong wind conditions, yet the downwind distributions are decidedly different. There is nothing in the meteorological statistics of the three to suggest that one should be any different from the other. Yet we see in one case, Experiment 23, a much greater decrease of dosage than would be expected after the puff has traversed about 1/3 the length of the sampling grid. In another, Experiment 31, the observed dilution rate is much less than would be expected. In Experiment 19 the dosages actually increase with distance over the outer half of the grid. The normalized arcwise integrated dosages shown in Figure 4 for the same experiments have similar downwind distributions. It is not likely that any prediction scheme based on measured meteorological parameters will ever be able to explain these anomalies. Unless they are adequately defined by meteorological measurements, there is little chance that inhalation-level dosages, observed under conditions prevailing for the Sand Storm experiments, can be predicted except on a statistical basis with but little reduction of variance gained through the use of meteorological measurements.




Figure 3. Downwind Distribution of Peak Dosages Normalized for Source Strength for Three Sand Storm Experiments Conducted Under Similar Meteorological Conditions

It should be recalled that all the Sand Storm experiments were conducted under thermally unstable conditions, which tends to limit the range of meteorological parameters. This is perhaps a partial explanation of the low correlations between the meteorological parameters and E_p/Q . Had tests also been conducted at night when thermally stable conditions prevailed, a greater range of meteorological parameters would have been observed. Correlations with E_p/Q most likely would have been greater, yielding a greater reduction of variance. Even then it is doubtful that operational applications of estimating equations could be made without resorting to some form of probability statement.




Figure 4. Downwind Distributions of Arcwise Integrated Dosages Normalized for Source Strength for Three Sand Storm Experiments Conducted Under Similar Meteorological Conditions

4. PROBABILITY ANALYSIS

Since most of the explained variance has been shown to be a function of distance from the source, we will develop a scheme for relating peak downwind exposures to travel distance as a function of probability of occurrence. No meteorological measurements are required, except to establish that thermally unstable conditions prevail over the region that the cloud is to travel and that a mean wind speed of at least 6 knots exists over the area (the general conditions prevailing during Sand Storm experiments).

Figure 5 shows a plot of E_p/Q vs. downwind distance for the 38 experiments for which we had reliable measurements of the peak dosage at all 5 of the outermost arcs. (See exception noted in Figure 5.) The E_p/Q values extend over about




Figure 5. Normalized Peak Dosages Plotted as a Function of Distance for 38 Sand Storm Experiments. The lowest three values at the 2400-meter arc have been omitted. Those were for Experiment Nos. 18, 34, and 49 in which the amount of tracer collected was so low (< 0.5 microgram) that an accurate assay was not possible. The curves, $P = .50$, $P = .75$, $P = .90$, and $P = .95$, represent the probabilities (0.50, 0.75, 0.90, and 0.95, respectively) of not exceeding the indicated values

2 orders of magnitude at each travel distance. At each travel distance they appear to have a distribution not unlike the Gaussian when only the upper 70 percent of E_p/Q values are examined. Figure 6 shows, for the 800-meter arc, a plot on probability paper of E_p/Q values vs. the cumulative percentage of occurrence. The more closely the points are collinear the more closely the distribution approaches the Gaussian form. Fitting a straight line to the points yields a mean and a standard deviation for the Gaussian distribution approximated by the points. This was done by the method of least squares for all E_p/Q values exceeding the 30th percentile at each of the five travel distances. Regression analysis was then used to relate the computed mean and standard deviation to distance from the source, thus allowing the computation of regression lines relating E_p/Q to downwind distances for various probabilities of occurrence.

The regression line representing the 50th percentile was found to be:

$$\left(\frac{E_p}{Q}\right)_{50} = .116 X^{-1.50} \quad (7)$$




Figure 6. Distribution of Measured Values of E_p/Q at a Distance of 800 Meters from the Source

where $\left(\frac{E_p}{Q}\right)_{50}$ = the 50th percentile value of E_p/Q in units of seconds per cubic meter (Gaussian distribution assumed),

and X = the distance from the source in units of meters.

The standard deviation of the distribution of E_p/Q values, also a function of downwind travel distance, was found to be:

$$\sigma\left(\frac{E_p}{Q}\right) = .0626 X^{-1.34} \quad (8)$$

where $\sigma\left(\frac{E_p}{Q}\right)$ = the standard deviation of E_p/Q values about their mean, in units of seconds per cubic meter,

and X = distance from the source in meters.

The curves in Figure 5 represent the 0.50, 0.75, 0.90, and 0.95 probability levels. This, of course, is no more than a quantitative description of the distribution of normalized peak dosages for the ensemble of Sand Storm diffusion experiments. However, it provides a simple procedure for evaluating the potential hazard associated with firing rocket motors of the type under consideration during thermally unstable atmospheric conditions.

Acknowledgments

The work reported in this chapter was conducted by a number of people. Among those especially active in the task were: Captain Juri V. Nou (AWS), Miss Joan Dwyer (AFCRL), and Miss Patricia Kelly (Regis College) who developed the computer routines used in the analyses and processed much of the data. Dr. M. L. Barad and Dr. D. A. Haugen devoted many hours of their time to discussions covering all aspects of the analyses. The author gratefully acknowledges the opportunity to document this effort.

References

- Pasquill, F. (1962) Atmospheric Diffusion, Van Nostrand Company Ltd., London.
- Smith F. B., and Hay, J. S. (1961) The expansion of clusters of particles in the atmosphere, Quart. J. Roy. Met. Soc. 87.

Appendix A

Dosage and Source Data

This appendix consists of three tables. Table A1 presents normalized dosage data for all valid Sand Storm experiments and a limited amount of meteorological data. Table A2 contains explanatory notes supplementing information shown in Table A1. Table A3 presents information concerning the tracer source.

In the heading of each tabulation in Table A1, U-BAR is the wind speed taken at 12 feet on the profile tower and averaged over a 10-minute period beginning 3 minutes before motor firing. DELTA T [1], DELTA T [2], and DELTA T [3] are the temperature differences between 6 feet and 50, 100, and 200 feet respectively. A negative value indicates a temperature decrease with height, thus an "unstable" condition. Also given in the headings are arc numbers and the distance in meters of the arc from the source. Azimuths are degrees (true) from the source point. Values shown in the body of the tabulations are dosage values normalized for source strength (sometimes referred to as normalized exposures) in units of 10^{-6} seconds per cubic meter. These values are derived by dividing the amount of tracer material collected at each sampling position by the aspiration rate of the sampling unit and by the amount of tracer released. Starred values indicate that there is some doubt as to the exact value shown, and a brief note explaining the circumstances of each starred dosage value is given in Table A2. At the foot of each tabulation in Table A1 the arcwise standard deviation is shown in degrees (SIGMA DEG;) and in meters (SIGMA M;) for all arcs with at least five significant measurements (that is, with five dosage

measurements equal to or greater than $0.5\mu\text{g Be}$) and a peak value of at least $5\mu\text{g Be}$. For A.c 10 the peak dosage requirement was relaxed to $2.5\mu\text{g Be}$.

Table A3 give information on motor size and firing duration. The times shown are for ballistic burn time which does not include a fraction of a second at the beginning and end of the firing sequence.

Table A1. Normalized Dosage Data

NORMALIZED DOSAGES										
SAND STORM NO. 02										
DATE 27 MAR 1963										
TIME 1130 PST										
		E/Q								
		[10 ⁻⁶ SEC/CU METER]								
		U-BAR: 10.33 METERS/SEC								
		DELTA T [1]: -1.4 DEG F								
		DELTA T [2]: -1.6 DEG F								
		DELTA T [3]: -2.7 DEG F								
ARC NO:	1	2	3	4	5	6	7	8	9	10
DIST[M]:	100	150	200	250	300	400	600	800	1200	2400
AZIMUTH										
45			0.374							
46										
47					0.374					
48										
49	2.32	1.47	1.02	1.12						
50					3.64	4.65				
51										0.524
52										0.449
53	46.2	49.4	44.9*	14.5	16.5	28.0	15.0	7.00	1.38	0.913
54										0.644
55									1.84	0.823
56					39.7	22.4	17.2	1.02		0.823
57	147.0	154.0	95.2	48.9					0.733	1.29
58										0.913
59					15.9	18.7	1.29	2.14	1.29	1.12
60										1.75
61	304.0	53.9	18.9	13.9						1.57
62					4.21	2.24	0.823	0.823		1.47
63										
64										
65	84.4	3.64	4.65							
66										
67										
68										
69	12.7	5.33								
70										
71										
72										
73	0.913									
SIGMA										
DEG:	3.53	3.18	2.91	**	2.74	2.91	**	**	**	**
M:	6.1	8.3	10.1	**	14.3	20.3	**	**	**	**

Table A1 (contd)

NORMALIZED DOSAGES									
E/Q									
[10 ⁻⁶ SEC/CU METER]									
SAND STORM NO. 03									
DATE 8 APR 1963									
TIME 1040 PST									
ARC NO: 1	2	3	4	5	6	7	8	9	10
DIST[M]: 100	150	200	250	300	400	500	600	1200	2400
AZIMUTH									
65			0.504	0.280*					
66									
67									
68					0.371	0.422	0.694		
69	16.8	2.63	1.23	0.586					
70									
71					0.616	1.43	0.828	0.151	
72									
73	161.0	38.9	15.4	10.0				0.259*	
74					6.64	10.5	2.48	0.422	
75								0.647*	
76									0.211
77	168.0	79.0	55.8	27.8	12.5*	11.2	6.90	2.16	0.259*
78									0.345*
79								3.13	0.478
80					19.9	19.7	6.90	3.40	0.293
81	49.4	47.1	34.2	30.0				0.862*	0.129
82									
83					14.3	16.8	14.0	3.32	0.431*
84									
85	25.3	23.7	22.7	19.0				0.293	
86					5.52	2.26	2.07	0.108	
87									
88									
89	3.10	1.05	1.51	1.13	0.560	0.884	0.586		
90									
91									
92						0.293			
93		0.884		0.586					
SIGMA									
DEG: 3.84	4.05	3.91	4.24	3.83	3.93	4.05	**	**	**
IN: 8.6	10.5	13.6	18.5	20.0	27.4	42.3	**	**	**

DATA REPORT

SAND STORM NO. 05
DATE 24 APR 1963
TIME 1531 PST

NORMALIZED DOSAGES

E/Q

[10⁻⁶ SEC/CM METER]

U-BAR: 5.86 METERS/SEC
DELTA T [1]: -2.0 DEG F
DELTA T [2]: -2.3 DEG F
DELTA T [3]: -3.0 DEG F

ARC NO:	1	2	3	4	5	6	7	8	9	10
DIST(M):	100	150	200	250	300	400	600	800	1200	2400

AZIMUTH

49	7.09	0.695	0.425							
50							2.13			
51										
52										
53	39.0	7.09*	22.3	17.0	9.70		2.84*			
54										
55									1.39	
56					19.1	9.92	3.90	0.964		
57	63.7	36.7	43.2	21.3					2.13	
58										
59					33.5	19.7	6.73	5.40	4.13	
60										
61	115.0	52.5	55.7	32.5					11.4	
62					35.2	25.0	17.6	13.8		
63									2.88	0.284*
64										0.354
65	216.0	203.0	104.0	43.2	49.6	41.1	43.2	24.1	4.25*	0.964
66										2.37
67									5.67*	2.13
68					74.6	45.4	43.2	20.7		1.66
69	373.0	140.0	68.1	58.4					10.8	1.39
70										2.55
71					32.9	15.9	17.0*	14.2	13.5	0.964
72										2.64
73	352.0	36.7	33.5	8.15					8.86	3.19
74					3.63	2.28	2.20	1.84		3.71
75									4.11	2.84*
76										2.13*
77	15.9				0.496	0.610	1.06		2.13*	1.57
78										1.22
79									1.53	2.03
80										0.496
81									1.18	1.30
82										0.142
83										0.142
84										0.865
85										1.22

SIGMA

DEG:	5.58	4.31	5.52	5.56	5.06	4.32	4.55	3.83	5.94	5.30
M:	9.7	11.2	19.2	24.2	26.4	30.1	47.6	53.4	124.3	222.1

Table A1 (contd)

SAND STORM NO. 06		NORMALIZED DOSAGES								U-BAR: 3.86 METERS/SEC	
DATE 6 MAY 1963		E/Q								DELTA T [1]: -2.4 DEG F	
TIME 1420 PST		[10 ⁻⁶ SEC/CU METER]								DELTA T [2]: -2.8 DEG F	
										DELTA T [3]: -3.9 DEG F	
ARC NO:	1	2	3	4	5	6	7	8	9	10	
DIST[M]:	100	150	200	250	300	400	600	800	1200	2400	
AZIMUTH											
59											0.351
60											0.974
61											0.351
62						1.15					0.974
63									1.07		1.51
64											0.308
65			0.537	0.394	0.537	1.79			0.881		0.179
66											0.215
67									0.881		0.0358
68					0.394	0.881	0.351				0.537
69	3.98		0.115	0.702					2.10		0.616
70											0.351
71					2.59	3.58	5.26	2.23	2.15		0.573
72											0.573
73	22.4	14.7	1.38	3.80					1.88		0.437
74					9.67	14.2	2.69	0.702			0.437
75									0.881		
76											
77	35.5	37.1	10.2	8.60	5.95	8.88	0.351	0.537	0.974		
78											
79									0.931		
80					19.1	8.31	0.394	0.179			
81	153.0	57.3	31.9	31.6							
82											
83					15.1*	1.25	0.351				
84											
85	240.0	139.0	34.9	24.6							
86					3.58		0.659				
87											
88											
89	106.0	12.2	0.215	0.115	0.659						
90											
91											
92					0.179						
93	5.16			0.351							
94											
95					0.251						
SIGMA											
DEG:	4.20	3.90	3.39	3.82	4.49	4.50	4.46	**	4.51	**	
M:	7.3	10.2	11.8	10.6	23.5	31.4	40.6	**	94.4	**	

Table A7 (cont'd)

NORMALIZED DOSAGES										
SAND STORM NO. 07				E/Q		U-BAR: 7.58 METERS/SEC				
DATE 8 MAY 1963						DELTA T [1]: -2.2 DEG F				
TIME 0939 PST						DELTA T [2]: -2.5 DEG F				
[10 ⁻⁶ SEC/CU METER]										
						DELTA T [3]: -3.6 DEG F				
ARC NO:	1	2	3	4	5	6	7	8	9	10
DIST[M]:	100	150	200	250	300	400	600	800	1200	2400
AZIMUTH										
47					0.179	0.394				
48										
49	5.11	1.07	0.537	0.251						
50					0.251	0.537	0.251	0.487		
51										
52										
53	17.2	15.0	1.15	3.04	1.97	2.05	4.65	2.23	1.25	
54										
55									2.51	
56					12.2	17.2	5.66	5.66		
57	93.1*	29.5	23.5	22.9					3.04	
58										
59					21.5*	21.8	14.7	6.94	3.94	0.838
60										0.537
61	139.0	63.0	41.0	26.5					5.42	0.974
62					17.5	14.0	11.0	7.16		0.795
63									4.12	0.394
64										0.251
65	111.0	36.8	28.9	15.8	16.4	9.95	11.2	6.16	4.57	1.15
66										0.179
67									3.79	0.638
68					2.59	2.51	2.55	5.51		
69	44.4	8.31	5.66	2.19					3.76	
70										
71					0.308		0.537	0.437		
72										
73	2.86	0.881	2.77							
74					0.179					
75										
76										
77	0.881	0.251	0.659		0.179					
SIGMA										
DEG:	4.50	4.33	4.19	**	3.86	3.78	4.20	4.77	4.53	**
M:	7.8	11.3	14.6	**	20.2	26.3	43.9	66.6	94.9	**

Table A1 (cont'd)

NORMALIZED DOSAGES									
E/Q									
[10 ⁻⁶ SEC/CU METER]									
SAND STORM NO. 09	U-BAR: 9.14 METERS/SEC								
DATE 23 MAY 1963	DELTA T [1]: -3.1 DEG F								
TIME 1311 PST	DELTA T [2]: -3.8 DEG F								
	DELTA T [3]: -4.8 DEG F								
ARC NO: 1	2	3	4	5	6	7	8	9	10
DIST(M): 100	150	200	250	300	400	600	800	1200	2400
AZIMUTH									
73	0.511	0.357							
74									
75									
76									
77	28.4	0.255	0.314		0.255				
78									
79								0.255	
80					0.445	0.810			
81	233.0	26.1	8.17	0.117				0.496	
82									
83					5.99	0.897		0.117	0.314
84									0.445
85	156.0	217.0	47.9	34.5				0.547	0.547
86					37.8	4.75	22.0	4.15	0.715
87								3.23	0.854
88									1.46
89	309.0	150.0	68.6	73.3	97.4	73.3	22.8	16.7	1.46
90								5.25	1.82
91								6.57	1.09
92					103.0	67.1	19.5	6.86	0.854
93	150.0	134.0	78.8	124.0				3.01	0.992
94									0.255
95					32.0	28.8	11.7	2.55	0.401
96									0.445
97	26.1	16.1	15.8	16.1				0.182	0.401
98					3.87	1.46	0.182		
99									
100									
101	0.496	0.897	1.84						
102									
103									
104									
105			0.584						
SIGMA									
DEG:	4.85	3.90	4.15	**	2.96	2.62	**	**	2.92 3.41
M:	8.4	10.2	14.4	**	15.5	18.2	**	**	61.2 142.9

Table A1 (contd)

NORMALIZED DOSAGES									
E/Q									
[10 ⁻⁶ SEC/CM METER]									
SAND STORM NO. 10									
DATE 29 MAY 1963									
TIME 1352 PST									
	U-BAR: 6.16 METERS/SEC								
	DELTA T [1]: -2.5 DEG F								
	DELTA T [2]: -3.1 DEG F								
	DELTA T [3]: -4.2 DEG F								
ARC NO: 1	2	3	4	5	6	7	8	9	10
DIST[M]: 100	150	200	250	300	400	600	800	1200	2400
AZIMUTH									
41	0.568								
42									
43									
44									
45	0.501								
46									
47									
48									
49	1.62	0.501							
50									
51									
52									
53	2.39	0.824							
54									
55									
56									
57	1.50	1.41		0.312					
58									
59					0.312		0.696		
60									
61	3.26	1.44	0.537	1.44					0.179
62					0.824	0.128	0.568		0.384
63									0.220
64									0.179
65	18.5	2.65	3.68	4.25	6.34	1.28	0.251	0.501	0.179
66									0.153
67									0.179
68					7.88	1.37	1.79	0.629	0.251
69	125.0	11.7	6.34	9.77					0.384
70									0.471
71					15.6	3.53	1.15	1.21	1.02
72									0.384
73	81.9	1.41	11.3	12.9					2.05
74					6.75	7.11	1.02	1.66	0.153
75									0.384
76									0.220
77	0.895	1.24	4.40	1.66	3.33	1.59	0.885	1.11	0.348
78									0.128
79									0.568
80					1.11	1.46	0.225		0.767
81	0.629	0.854	0.537	0.312					0.312
82									
83					0.696	0.409			
84									
85	0.501		0.179						
86						0.128			
SIGMA									
DEG:	4.22	6.44	4.28	4.12	4.26	4.28	5.72	**	**
M:	7.3	16.8	14.9	17.9	22.2	29.8	59.9	**	**

Table A1 (contd)

NORMALIZED DOSAGES									
E/Q									
[10 ⁻⁶ SEC/CU METER]									
SAND STORM NO. 11									
DATE 10 JUN 1963									
TIME 0914 PST									
	U-BAR: 12.51 METERS/SEC								
	DELTA T [1]: -2.4 DEG F								
	DELTA T [2]: -2.5 DEG F								
	DELTA T [3]: -4.0 DEG F								
ARC NO: 1	2	3	4	5	6	7	8	9	10
DIST[M]: 100	150	200	250	300	400	600	800	1200	2400
AZIMUTH									
45	0.127	0.178	0.249	0.437					
46									
47									
48									
49	0.467	0.0812	0.178	0.508				0.249	
50									
51								0.279	
52									
53	1.52	0.249	0.279	0.762*				0.249	
54									
55								0.234*	
56					0.624	0.249			
57	50.8	13.8	5.89	3.59				0.218	
58									
59					5.89	1.88	1.14	0.406	
60									
61	160.0	87.8	23.0	14.0				1.02	
62					15.3	9.34	3.87	0.660	0.127
63								2.16	0.249
64									0.624
65	321.0	265.0	101.0	55.1	31.0	16.7	6.60	4.57	2.28
66									1.23
67									1.40
68								1.90	1.14
69	353.0	25.2	7.82	2.63	9.90	9.14*	2.88	2.38	1.33
70									1.78
71					2.31	1.52	0.0508	0.127	0.127
72									0.152*
73	8.94	2.10	0.127	0.249					0.178
74						0.564	0.127		0.127
75								0.152	0.310
76								0.178	
77	1.36	0.817	0.178	0.127			0.310		
78									
79									
80							0.178		
81	0.624	0.0812	0.249						
82									
83							0.127		
84									
85	0.594	0.127							
86							0.178		
87									
88									
89	0.381	0.0508					0.249		
90									
91									
92							0.310		
93	0.624	0.178							
SIGMA									
DEG:	3.87	2.77	2.77	3.69	2.89	4.73	**	**	5.07
M:	6.7	7.2	9.6	16.1	15.1	33.0	**	**	106.9

Table A1 (contd)

SAND STORM NO. 12			NORMALIZED DOSAGES							U-BAR: 2.33 METERS/SFC	
DATE 12 JUN 1963			E/Q							DELTA T [1]: -1.3 DEG F	
TIME 1018 PST			[10 ⁻⁶ SEC/CM METER]							DELTA T [2]: -1.7 DEG F	
										DELTA T [3]: -2.2 DEG F	
ARC NO:	1	2	3	4	5	6	7	8	9	10	
DIST(M):	100	150	200	250	300	400	600	800	1200	2400	
AZIMUTH											
17							0.127				
18											
19											
20							0.498				
21											
22							0.279				
23											
24							0.406				
25											
26							0.178				
27											
28											
29											
30											
31											
32			0.152	0.975	0.762	0.178	0.345				
33											
34					4.14	0.345	0.467				
35											
36		0.310	3.05	3.31	3.84	0.564	0.817				
37											
38		0.127	3.08	5.13	4.33	1.45	0.762				
39											
40											
41					10.7	2.34	0.533				
42		3.05	1.14	18.1							
43					14.4	9.90	0.762				
44											
45	2.10	1.20	1.58	22.6	11.2	1.55	0.564				
46											
47											
48											
49											
50											
51											
52											
53	3.24	1.17	3.76	33.5	15.9	1.07	0.381				
54											
55											
56					10.1	1.40	0.533				
57	7.11*	0.975	28.9	81.2							
58					6.45	3.81	0.467		0.249		
59											
60											
61	11.4	2.89	5.13	4.26	7.31	2.85	2.79	0.533	0.249		
62											
63									0.381		
64										0.218	
65	47.2	15.1	2.89	15.1	10.3	1.84	2.69	1.61	0.406	0.127	
66										0.279	
67									0.888	0.437	
68					16.3	1.75	2.59	1.14		0.533	
69	215.0	8.83	15.5	17.3					1.52	0.345	
70										0.660	
71					9.90	2.34	1.96	0.178	1.88	0.406	
72										0.564	
73	166.0	18.5	19.6	26.6					1.71	0.690	
74					2.72	2.47	1.07	0.0508		0.624	
75									0.406	0.660	
76										0.467	

Table A1 (contd)

SAND STORM NO. 12 [CONT.]

ARC NO:	1	2	3	4	5	6	7	8	9	10
DIST[M]:	100	150	200	250	300	400	600	800	1200	2400
AZIMUTH										
77	30.3	11.6	11.6	19.5	2.44	3.40	1.02	0.345		0.660
78										0.467
79										0.848
80					0.888	1.78	0.690	0.127		0.564
81	27.2	8.12	24.2	12.0						0.624
82										0.762
83					0.564	1.45	0.381	0.279		0.178
84										
85	27.2	11.6	15.5	5.33						
86					0.437	1.04	0.498	0.0508		
87										
88										
89	6.85	4.26	9.04	0.690		0.726	0.381	0.381		
90										
91										
92						0.690	0.553	0.249		
93	7.72	2.16	8.12	0.381						
94										
95						0.660	0.249			
96										
97	20.9			0.152						
98						0.467	0.564			
99										
100										
101	15.9					1.02	0.594			
102										
103										
104						1.07	0.594			
105	0.624									
106										
107						0.564	0.345			
SIGMA										
DEG:	9.07	10.6	13.6	11.5	11.2	17.8	20.1	**	17.9	**
M:	15.8	27.8	47.5	50.1	53.7	124.3	210.9	**	375.3	**

SAND STORM NO. 13
DATE 14 JUN 1963
TIME 1057 PST

NORMALIZED DOSAGES

E/Q
[10⁻⁶ SEC/CU METER]

U-BAR: 2.91 METERS/SEC
DELTA T [1]: -1.7 DEG F
DELTA T [2]: -2.1 DEG F
DELTA T [3]: -2.8 DEG F

ARC NO:	1	2	3	4	5	6	7	8	9	10
DIST[M]:	100	150	200	250	300	400	600	800	1200	2400
AZIMUTH										
44						0.108				
45										
46										
47						0.130				
48										
49				2.22						
50					0.698	0.373				
51										
52										
53				2.74	2.77	0.867	0.108			
54										
55										
56					2.82	1.27	0.152			
57		0.590		1.14						
58										
59					1.63	1.68	0.672	0.130	0.238	
60										
61		1.33	0.130	0.373					0.507	
62					1.08	3.59	1.63	0.915		
63									0.806	0.212
64										0.186
65		**	0.455	2.49	2.63	4.77	2.82	4.38	0.425	0.108
66										0.0434
67									0.295	**
68					5.16	4.03	6.24	3.64		0.108
69	1.57	**	2.19	3.18					0.650	0.130
70										**
71					2.43	5.51	7.72	4.21	0.832	0.108
72										0.130
73	6.24	0.186	8.45	6.24					1.30	0.212
74					3.31	6.24	7.54	2.22		0.347
75									1.19	0.373
76										
77	3.04	0.325	4.77	1.68	2.28	5.33	8.63	1.68	1.95	
78										
79									1.52	
80					1.24	3.25	9.93	2.93		
81		0.590	1.95	0.780					1.37	
82										
83					0.915	3.01	5.51	3.72	1.44	
84										
85		0.533	2.28	0.425					1.95	
86					0.698	1.95	2.93	2.00		
87									1.89	
88										
89			0.186	0.915	0.212	0.212	0.325	1.41	2.11	
90										
91									2.60	
92					0.425	0.152	0.264	0.533		
93			0.152	0.832					1.98	
94										
95					0.325	0.212	0.212	0.373	2.17	
96										
97				0.698					1.68	
98					0.264	0.186				
99									1.46	
100										
101				0.481	0.425				0.425	
102										
103										
104					0.264					
105				0.186						
106										
107					0.238					
SIGMA										
DEG:	**	**	5.37	13.4	12.0	8.90	6.74	8.46	10.3	**
M:	**	**	18.7	58.4	63.0	62.1	70.6	118.1	215.7	**

Table A1 (contd)

[illegible]

Table A1 (contd)

SAND STORM NO. 16 DATE 9 JUL 1963 TIME 0950 PST		NORMALIZED DOSAGES					U-BAR: 4.47 METERS/SEC	
		E/Q					DELTA T [1]: -1.6 DEG F	
		(10 ⁻⁶ SEC/CM FILTER)					DELTA T [2]: -2.2 DEG F	
							DELTA T [3]: -2.7 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST (M):	200	400	600	800	1200	2400		
AZIMUTH								
85.0	2.01*							
85.5								
86.0						0.518		
86.5								
87.0	5.56	0.140				1.34		
87.5								
88.0						3.27		
88.5								
89.0	5.93	1.22	0.285			2.74		
89.5								
90.0						2.10*		
90.5								
91.0	4.72	0.374	0.350			1.57		
91.5								
92.0						0.117		
92.5								
93.0	8.87	0.490	1.55					
93.5								
94.0								
94.5								
95.0	11.1	1.45	4.72	1.48				
95.5								
96.0								
96.5				3.97*	0.934			
97.0	14.5	2.57	10.7					
97.5								
98.0				10.3	0.934			
98.5								
99.0	17.5	5.75*	19.8					
99.5				6.91	0.518			
100.0								
100.5								
101.0	33.1	12.5	23.6	15.2	0.575			
101.5								
102.0								
102.5				11.4	0.514*			
103.0	23.0	6.54*	2.66					
103.5								
104.0				0.668	0.458			
104.5								
105.0	16.6	3.92	0.701					
105.5								
106.0								
106.5								
107.0	5.93	0.897						
SIGMA								
DEG:	**	**	2.45	2.13	**	1.42		
M:	**	**	25.6	29.6	**	59.5		

Table A1 (contd)

SAND STORM NO. 17		NORMALIZED DOSAGES				U-BAR: 5.37 METERS/SEC	
DATE 11 JUL 1963		E/Q				DELTA T [1]: -1.7 DEG F	
TIME 0933 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]: -2.2 DEG F	
						DELTA T [3]: -3.0 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST [M]:	200	400	600	800	1200	2400	
AZIMUTH							
74.0						0.234	
74.5							
75.0						0.263	
75.5							
76.0						0.234	
76.5							
77.0							
77.5							
78.0							
78.5							
79.0	0.358						
79.5							
80.0					0.234		
80.5							
81.0	32.2		0.530				
81.5				0.292	0.134*		
82.0							
82.5							
83.0	12.1	1.08	2.60	1.01			
83.5							
84.0							
84.5				2.32			
85.0	13.8	0.889	3.80				
85.5							
86.0				2.18			
86.5							
87.0	4.83	1.22	7.46				
87.5				2.60			
88.0							
88.5							
89.0	3.78	2.93	2.44	2.39			
89.5							
90.0							
90.5				1.70			
91.0		0.741	1.08				
91.5							
92.0							
92.5							
93.0		0.143					
SIGMA							
DEG:	2.45	**	2.30	2.46	**	**	
N:	8.5	**	24.0	34.3	**	**	

Table A1 (contd)

SAND STORM NO. 18		NORMALIZED DOSAGES				U-BAR: 8.65 METERS/SEC	
DATE 15 JUL 1963		E/Q				DELTA T [1]: -2.2 DEG F	
TIME 1030 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]: -2.7 DEG F	
						DELTA T [3]: -0.0 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
56.0					0.453		
56.5							
57.0	42.3	0.913					
57.5					0.371*		
58.0							
58.5							
59.0	50.6	1.71	2.12	2.60	0.312*		
59.5							
60.0							
60.5				1.20	0.260		
61.0	51.2	23.3	2.87				
61.5							
62.0				1.20	1.30		
62.5							
63.0	88.0	25.3*	4.79				
63.5				1.43	0.557		
64.0							
64.5							
65.0	57.9	10.0	3.24	1.06	0.646		
65.5							
66.0							
66.5					0.728		
67.0	20.8*	2.69					
67.5							
68.0							
68.5							
69.0	7.20	1.00*					
69.5							
70.0							
70.5							
71.0		0.364					
71.5							
72.0							
72.5							
73.0		0.201*					
SIGMA							
DEG:	3.10	2.26	**	**	**	**	**
M:	10.8	15.7	**	**	**	**	**

A18

Table A1 (contd)

SAND STORM NO. 19		NORMALIZED DOSAGES					U-BAR: 12.60 METERS/SEC	
DATE 17 JUL 1963		C/Q					DELTA T [1]: -2.1 DEG F	
TIME 0936 PST		(10 ⁻⁶ SEC/CMETER)					DELTA T [2]: -2.6 DEG F	
							DELTA T [3]: -3.9 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST(M):	200	400	600	800	1200	2400		
AZIMUTH								
67.0	0.270							
67.5								
68.0								
68.5								
69.0	4.73							
69.5								
70.0								
70.5								
71.0	17.0	5.56	0.378		1.20			
71.5								
72.0								
72.5				1.82	1.88			
73.0	53.6	17.3	5.22			0.579		
73.5								
74.0				1.78	1.74	3.71		
74.5								
75.0	84.9	7.80	2.51			3.94		
75.5				1.00	1.29	3.19		
76.0								
76.5								
77.0	17.3	3.86	0.471	0.811	0.525	1.54		
77.5								
78.0								
78.5				0.332	0.378			
79.0	3.90	0.949	0.193					
79.5								
80.0					0.193			
SIGMA								
DEC:	1.92	1.92	**	**	2.39	**		
M:	6.7	13.4	**	**	50.0	**		

Table A1 (contd)

SAND STORM NO. 20		NORMALIZED DOSAGES					U-BAR: 3.86 METERS/SEC	
DATE 26 JUL 1963		E/Q					DELTA T [1]: -0.7 DEG F	
TIME 1018 PST		[10 ⁻⁶ SEC/CM METER]					DELTA T [2]: -2.3 DEG F	
							DELTA T [3]: -2.8 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
54.0						0.0836		
54.5								
55.0						0.142		
55.5								
56.0						0.140		
56.5								
57.0						0.201		
57.5								
58.0						0.435		
58.5								
59.0						0.414		
59.5								
60.0						0.414		
60.5								
61.0						0.418*		
61.5								
62.0						0.421		
62.5								
63.0	1.35					0.304		
63.5								
64.0						0.496*		
64.5								
65.0	6.30					0.836		
65.5								
66.0						0.659		
66.5								
67.0	0.02*					0.949		
67.5								
68.0						0.797		
68.5								
69.0	5.66					1.42		
69.5								
70.0					0.204	1.59		
70.5								
71.0	15.0				0.358	0.949		
71.5								
72.0						1.35		
72.5					0.230			
73.0	24.4					1.57		
73.5								
74.0					0.262	1.61		
74.5								
75.0	1.50					1.72		
75.5					0.179			
76.0						1.50		
76.5								
77.0	0.659				0.122	0.974		
77.5								
78.0						1.24		
78.5					0.708*			
79.0	0.531					0.995		
79.5								
80.0				2.61	2.65	0.347		
80.5								
81.0	0.443	0.244	1.95			0.995		
81.5				15.6	2.40			
82.0						1.33		
82.5								
83.0	0.372	1.27	1.63	13.4	3.29*	0.974		
83.5								

Table A1 (contd)

SAND STORM NO. 20 [CONT.]						
ARC NO:	3	6	7	8	9	10
DIST[M]:	200	400	600	800	1200	2400
AZIMUTH						
84.0						0.570
84.5				12.6	4.50	
85.0		0.297	1.35			0.241
85.5						
86.0				6.37*	4.21	0.188
86.5						
87.0		0.297	2.08			0.146
87.5				3.43	1.95	
88.0						0.104
88.5						
89.0		0.177	4.50	3.72	1.45*	0.0797
89.5						
90.0						0.0482
90.5				2.14	1.14	
91.0			2.26			0.0531
91.5						
92.0				1.73	1.05	0.0747
92.5						
93.0			0.673			
93.5				0.974	0.867	
94.0						
94.5						
95.0				0.705	0.811	
95.5						
96.0						
96.5				1.04	0.464	
97.0						
97.5						
98.0				0.779	0.110	
98.5						
99.0						
99.5				1.27		
SIGMA						
DEG:	3.37	**	3.56	4.30	5.13	7.32
M:	11.7	**	37.2	60.0	107.5	306.7

Table A1 (contd)

SAND STORM NO. 21		NORMALIZED DOSAGES					U-BAR: 7.57 METERS/SEC	
DATE 30 JUL 1963		E/Q					DELTA T [1]: -1.2 DEG F	
TIME 1256 PST		[10 ⁻⁶ SEC/CM METER]					DELTA T [2]: -3.6 DEG F	
							DELTA T [3]: -4.6 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
65.0	0.110		0.117	0.106				
65.5								
66.0								
66.5				0.163				
67.0	0.203	0.152	0.256					
67.5								
68.0				0.156				
68.5								
69.0	1.94	0.579	0.448					
69.5				0.241	0.156			
70.0								
70.5								
71.0	7.17	1.59*	0.833	0.459*	0.297	0.0766		
71.5								
72.0						0.141		
72.5				0.858	0.777			
73.0	11.7	4.48	5.79			0.191*		
73.5								
74.0				1.54	1.38*	0.259		
74.5								
75.0	71.7	17.7	9.28			0.833		
75.5				3.25*	2.44			
76.0						1.65		
76.5								
77.0	126.0	25.7	11.8	6.71	2.47	0.826		
77.5								
78.0						0.851		
78.5				9.43	4.48			
79.0	82.6	32.8	13.8			0.971		
79.5								
80.0				12.4	4.62	1.09		
80.5								
81.0	14.4	11.7	13.3			1.11*		
81.5				9.14	5.65			
82.0						1.14		
82.5								
83.0	2.82	4.06*	5.08	2.29	4.20	0.717		
83.5								
84.0						0.191*		
84.5				0.865	0.865			
85.0	0.636*	1.47	0.826					
85.5								
86.0				0.0946	0.177*			
86.5								
87.0		0.0812	0.177					
SIGMA								
DEG:	2.24	2.74	3.36	2.88	3.22	2.95		
N:	7.8	19.1	35.1	40.2	67.3	123.7		

A22

Table A1 (contd)

SAND STORM NO. 22		NORMALIZED JOGAGES				U-BAR: 4.33 METERS/SEC	
DATE 9 AUG 1963		E/Q				DELTA T [1]: -2.0 DEG F	
TIME 1458 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]: -2.7 DEG F	
						DELTA T [3]: -3.5 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
80.0				0.0894			
80.5							
81.0	2.08		0.223				
81.5				0.210			
82.0							
82.5							
83.0	1.51		1.31	0.622			
83.5							
84.0							
84.5				0.217			
85.0	1.10		1.62			0.0733	
85.5							
86.0				0.199		0.105	
86.5							
87.0	2.26	0.321	2.79			0.168	
87.5				0.531			
88.0						0.105	
88.5							
89.0	2.47	1.48	5.31	0.499	0.0915	0.0936	
89.5							
90.0						0.0824	
90.5				0.562	0.0562		
91.0	4.16	12.9	5.59			0.0716	
91.5							
92.0				0.849	0.0349	0.0611	
92.5							
93.0	4.30	3.32*	7.09			0.0524	
93.5				1.31	0.0559		
94.0						0.109	
94.5							
95.0	3.53*	0.824	8.56	2.44	0.0821	0.102	
95.5							
96.0						0.0737	
96.5				4.16	0.122		
97.0	2.93	2.32	10.1			0.0524	
97.5							
98.0				6.46	0.894	0.138	
98.5							
99.0	2.71	2.27	10.7			0.175	
99.5				6.81	1.75		
100.0						0.102	
100.5							
101.0	1.99	2.98	8.28	8.87	1.59	0.131	
101.5							
102.0							
102.5				11.2	1.92		
103.0	2.68	1.64*	6.64				
103.5							
104.0				4.16	0.279		
104.5							
105.0	8.87	0.786	7.37				
105.5				3.39	0.262		
106.0							
106.5							
107.0	10.4	1.70	8.73	1.63			
SIGMA							
DEC:	**	**	**	**	**	**	**
II:	**	**	**	**	**	**	**

SAND STORM NO. 23		NORMALIZED DOSAGES				U-BAR: 7.45 METERS/SEC	
DATE 16 AUG 1963		E/Q				DELTA T [1]: -2.6 DEG F	
TIME 1558 PST		[10 ⁻⁶ SEC/CM METER]				DELTA T [2]: -2.7 DEG F	
						DELTA T [3]: -3.6 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
55.0		0.100					
55.5							
56.0							
56.5							
57.0	0.139	0.562	0.474				
57.5				0.386			
58.0							
58.5							
59.0	1.09	2.02	1.01	0.909			
59.5							
60.0							
60.5				0.966	0.386		
61.0	2.79	2.32	2.32				
61.5							
62.0				1.86	0.997		
62.5							
63.0	18.8	3.86	3.86				
63.5				3.27	1.60		
64.0							
64.5							
65.0	22.1	9.83	5.34	6.25	1.76		
65.5							
66.0							
66.5				7.90	1.55		
67.0	34.1	13.1	17.3				
67.5							
68.0				10.3	2.70		
68.5							
69.0	106.0	17.7	17.1				0.134
69.5				12.4	5.34		
70.0							0.239
70.5							
71.0	121.0	37.7	10.7	10.1	2.97		0.418
71.5							
72.0							0.171
72.5				7.72	2.02		
73.0	104.0	23.7	10.6				0.284
73.5							
74.0				3.86	1.40		0.266
74.5							
75.0	69.9	20.0	7.41				0.244
75.5				5.34	1.47		
76.0							0.279
76.5							
77.0	53.4	13.2	9.23	7.13	1.71		0.177
77.5							
78.0							
78.5				0.702	0.474		
79.0	14.9	6.35	1.18				
79.5							
80.0				0.0702			
80.5							
81.0	7.72	0.302	0.421				
81.5							
82.0							
82.5							
83.0	2.51		0.151				
83.5							
84.0							
84.5							
85.0	0.0878						
SIGMA							
DEG:	3.96	4.36	4.55	4.36	4.27	**	
M:	13.8	30.4	47.6	60.8	89.5	**	

Table A1 (contd)

SAND STORM NO. 24			NORMALIZED DOSAGES			U-BAR: 5.82 METERS/SEC	
DATE 19 AUG 1963			E/Q			DELTA T [1]: -1.3 DEG F	
TIME 1542 PST			[10 ⁻⁶ SEC/CU METER]			DELTA T [2]: -1.4 DEG F	
						DELTA T [3]: -2.3 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
75.0	0.252	0.291	0.257				
75.5				0.0809			
76.0							
76.5							
77.0	0.989	0.647	0.608	0.0848			
77.5							
78.0							
78.5				0.193			
79.0	2.20	1.57	0.442				
79.5							
80.0				0.428			
80.5							
81.0	5.00	3.78	0.899				
81.5				0.324*	0.0719		
82.0							
82.5							
83.0	11.9	6.08	2.82	0.219	0.0899		
83.5							
84.0							
84.5				0.539	0.112		
85.0	19.6	8.05	3.63				
85.5							
86.0				1.77	0.264	0.261	
86.5							
87.0	37.8	5.14	4.85			0.360*	
87.5				2.23	0.608		
88.0						0.485	
88.5							
89.0	42.8	9.20	6.08	2.37	1.19	0.205	
89.5							
90.0							
90.5				5.32	2.02		
91.0	36.0*	3.31	7.73				
91.5							
92.0				7.59	1.74		
92.5							
93.0	30.2	6.29	6.65				
93.5				10.1	1.83		
94.0							
94.5							

Table A1 (contd)

SAND STORM NO. 24 [CONT.]						
ARC NO:	3	6	7	8	9	10
DIST[M]:	200	400	600	800	1200	2400
AZIMUTH						
95.0	42.3	5.75	8.99	7.91	0.640	
95.5						
96.0						
96.5				4.85		
97.0	25.3	11.3	4.10			
97.5						
98.0				4.28		
98.5						
99.0	13.7	11.0	2.73			
99.5				1.30		
100.0						
100.5						
101.0	2.05	2.70	2.19			
101.5						
102.0						
102.5						
103.0	0.759	0.0942	1.04			
103.5						
104.0						
104.5						
105.0	0.0848	0.243	0.182			
105.5						
106.0						
106.5						
107.0			0.103			
SIGMA						
DEG:	4.81	6.48	5.57	4.03	**	**
ft:	16.7	45.2	58.3	56.3	**	**

Table A1 (contd)

SAND STORM NO. 25		NORMALIZED DOSAGES				U-BAR: 7.82 METERS/SEC	
DATE 21 AUG 1963		E/Q				DELTA T [1]: -2.7 DEG F	
TIME 1334 PST		(10 ⁻⁶ SEC/CM METER)				DELTA T [2]: -3.2 DEG F	
						DELTA T [3]: -4.5 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
63.0	0.0327						
63.5							
64.0							
64.5							
65.0	0.141						
65.5							
66.0							
66.5							
67.0	0.345						
67.5							
68.0							
68.5							
69.0	0.851*	0.0450					
69.5							
70.0							
70.5							
71.0	3.75	0.327	0.0450		0.0419		
71.5							
72.0							
72.5					0.0878		
73.0	8.92	0.593	0.860				0.0796
73.5							
74.0				0.583	0.180		
74.5							
75.0	15.9	4.58	1.65				
75.5				1.00	0.786		
76.0							
76.5							
77.0	24.9	6.06	2.55	0.565	0.876		
77.5							
78.0							
78.5				0.442*	0.933		
79.0	21.4	8.37	1.95				
79.5							
80.0				0.377	0.548		
80.5							
81.0	44.4	11.4	1.59				
81.5				0.0409	0.416		
82.0							
82.5							
83.0	33.2	6.55	0.123		0.262		
83.5							
84.0							
84.5					0.138		
85.0	14.6	1.35	0.0532				
85.5							
86.0					0.0429		
86.5							
87.0	6.19	0.0450	0.0480				
87.5							
88.0							
88.5							
89.0	0.612						
89.5							
90.0							
90.5							
91.0	0.0542						
SIGMA							
DEG:	3.89	2.92	2.71	**	2.88	**	
11:	13.5	20.4	28.3	**	60.2	**	

Table A1 (contd)

SAND STORM NO. 26		NORMALIZED DOSAGES				U-BAR: 9.66 METERS/SEC	
DATE 22 AUG 1963		E/Q				DELTA T [1]: -2.7 DEC F	
TIME 1430 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]: -3.0 DEC F	
						DELTA T [3]: -4.5 DEC F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
49.0	0.214						
49.5							
50.0							
50.5							
51.0	4.11						
51.5							
52.0							
52.5							
53.0	12.6	0.0424					
53.5							
54.0							
54.5							
55.0	17.0	0.648	0.139				
55.5							
56.0				0.534			
56.5							
57.0	34.2	9.49	2.06				
57.5				0.939			
58.0							
58.5							
59.0	48.1	44.5	12.1	1.24	1.78		
59.5							
60.0						0.0818	
60.5				5.77	1.46*		
61.0	61.9	42.6	17.8			0.259	
61.5							
62.0				7.13*	1.25	0.246	
62.5							
63.0	54.3	41.1	21.9			0.468	
63.5				8.66	3.56		
64.0						0.426*	
64.5							
65.0	64.8	30.0	12.8	5.34	2.92*	0.494	
65.5							
66.0						0.591	
66.5				6.87	2.59		
67.0	66.7	21.9	10.7			0.494	
67.5							
68.0				5.51	2.40	0.632	
68.5							
69.0	34.8	17.8	9.23			0.518*	
69.5				2.74	1.51		
70.0						0.411	
70.5							
71.0	28.8	15.7	5.04	2.06	1.21	0.219	
71.5							
72.0						0.246	
72.5				2.59	0.546		
73.0	20.6	9.23	4.34			0.178	
73.5							
74.0				2.11	0.850	0.164	
74.5							
75.0	8.60	4.53	3.29			0.113	
75.5				1.78	0.454*		
76.0						0.0923	
76.5							
77.0	6.80	2.88	0.769	0.453	0.233	0.0424	
77.5							
78.0							
78.5				0.121	0.0504		

Table A1 (contd)

SAND STORM NO. 26 [CONT.]

ARC NO:	3	6	7	8	9	10
DIST[M]:	200	400	600	800	1200	2400
AZIMUTH						
79.0	0.769	0.382	0.139			
79.5						
80.0				0.206	0.0486	
80.5						
81.0	0.546	0.0850	0.0567			
81.5				0.0445		
82.0						
82.5						
83.0	0.121	0.0688		0.274		
83.5						
84.0						
84.5				0.121		
85.0	0.211	0.0424				
85.5						
86.0				0.0583		
86.5						
87.0	0.0794					
87.5						
88.0						
88.5						
89.0	0.0909					
89.5						
90.0						
90.5						
91.0	0.0342					
SIGMA						
DEG:	5.59	4.76	4.57	4.95	4.38	3.86
M:	19.5	33.2	47.9	69.0	91.6	161.6

Table A1 (contd)

SAND STORM NO. 27		NORMALIZED DOSAGES					U-BAR: 6.35 METERS/SFC	
DATE 27 AUG 1963		E/Q					DELTA T [1]: -1.8 DEG F	
TIME 1538 PST		[10 ⁻⁶ SEC/CM METER]					DELTA T [2]: -2.1 DEG F	
							DELTA T [3]: -2.9 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
51.0	0.0863							
51.5								
52.0								
52.5								
53.0	0.263	0.202						
53.5								
54.0								
54.5								
55.0	1.29	0.452	0.113					
55.5								
56.0				0.0822		0.0470		
56.5								
57.0	2.78	2.63	0.986			0.352		
57.5				0.265	*0.0493	0.846		
58.0								
58.5								
59.0	13.3	8.79	4.03	2.09	0.353	1.22*		
59.5								
60.0						1.66		
60.5				5.16	0.838			
61.0	29.3	9.04	7.61			1.25		
61.5								
62.0				0.799	1.01	0.855*		
62.5								
63.0	93.7	4.70	3.76			0.600		
63.5				0.689	0.115			
64.0						0.417		
64.5								
65.0	57.2	2.55	*0.0616	0.197*		0.565		
65.5								
66.0						0.536		
66.5				0.0616				
67.0	51.6	0.0717				0.475		
67.5								
68.0						0.304		
68.5								
69.0	26.3					0.109		
69.5								
70.0								
70.5								
71.0	1.08							
71.5								
72.0								
72.5								
73.0	0.0657							
73.5								
74.0								
74.5								
75.0	0.0544							
75.5								
76.0								
76.5								
77.0	0.0431							
77.5								
78.0								
78.5								
79.0	0.0329							
SIGMA								
DEG:	2.83	2.41	**	1.57	**	3.07		
M:	9.8	16.8	**	21.8	**	128.6		

Table A1 (contd)

SAND STORM NO. 28		NORMALIZED DOSAGES					U-BAR: 8.49 METERS/SEC	
DATE 30 AUG 1963		E/Q					DELTA T [1]: -2.5 DEG F	
TIME 1439 PST		(10 ⁻⁶ SEC/CU METER)					DELTA T [2]: -2.8 DEG F	
							DELTA T [3]: -3.7 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST(M):	200	400	600	800	1200	2400		
AZIMUTH								
55.0	0.0555							
55.5								
56.0								
56.5								
57.0	0.0905							
57.5								
58.0								
58.5								
59.0	0.132							
59.5								
60.0								
60.5								
61.0	0.202							
61.5								
62.0								
62.5								
63.0	0.782							
63.5								
64.0								
64.5								
65.0	2.50	0.0411						
65.5								
66.0								
66.5								
67.0	4.61*	0.142						
67.5								
68.0								
68.5								
69.0	8.97	2.70	0.0782					
69.5								
70.0								
70.5								
71.0	18.1	47.6	0.123	0.0329				
71.5								
72.0								
72.5					0.0388			
73.0	22.2	18.8	0.161					
73.5								
74.0					0.209			
74.5								
75.0	47.6	12.3	0.471					
75.5				0.181	0.0668			
76.0								
76.5								
77.0	72.6	0.576	0.476	0.222	0.181			
77.5								
78.0								
78.5				0.173	0.0400			
79.0	12.3	0.141	0.107					
79.5								
80.0				0.0964				
80.5								
81.0	4.61							
SIGMA								
DEG:	3.32	1.68	2.83	2.69	**	**		
M:	11.5	11.6	29.6	37.5	**	**		

Table A1 (contd)

SAND STORM NO. 29		NORMALIZED DOSAGES				U-BAR: 7.69 METERS/SEC	
DATE 10 SEP 1963		E/Q				DELTA T [1]: -1.2 DEG F	
TIME 1611 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]: -1.4 DEG F	
						DELTA T [3]: -2.6 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
65.0	0.111						
65.5							
66.0							
66.5							
67.0	0.131						
67.5							
68.0							
68.5							
69.0	0.918	0.234	0.375				
69.5							
70.0							
70.5							
71.0	2.62	1.33	0.746	0.0509			
71.5							
72.0							
72.5				0.125	*0.0509		
73.0	5.33	1.23	0.654*				
73.5							
74.0				0.332	0.981		
74.5							
75.0	13.7	3.32	0.551				
75.5				1.37	2.36		
76.0						1.44	
76.5							
77.0	23.6	4.25*	2.01	3.88	2.76	3.32	
77.5							
78.0						3.03	
78.5				5.82	3.32		
79.0	13.1*	5.48	12.3			2.14	
79.5							
80.0				10.2	3.27*	1.23	
80.5							
81.0	7.44	8.19	7.51			0.150	
81.5				5.27	3.19		
82.0						0.124	
82.5							
83.0	1.95	1.80	0.777	2.08	0.491*		
83.5							
84.0							
84.5				0.509	0.0736		
85.0	0.442*	0.124	0.0676				
85.5							
86.0				0.0572			
86.5							
87.0	0.106						
87.5							
88.0							
88.5							
89.0	0.0429						
SIGMA							
DEG:	2.96	3.27	2.61	2.14	2.43	**	
IN:	10.3	22.7	27.3	29.8	50.9	**	

SAID STORM NO. 30		NORMALIZED DOSAGES				U-BAR: 2.90	METERS/SEC
DATE 11 SEP 1963		E/Q				DELTA T [1]:	-1.4 DEG F
TIME 1526 PST		[10 ⁻⁶ SEC/CM METER]				DELTA T [2]:	-1.8 DEG F
						DELTA T [3]:	-2.4 DEG F
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
77.0	0.0469						
77.5							
78.0							
78.5							
79.0	0.103	0.0346					
79.5							
80.0							
80.5							
81.0	0.151	0.0510					
81.5							
82.0							
82.5							
83.0	2.43	0.100					0.0655
83.5							0.0202
84.0							
84.5				0.0634			
85.0	11.6	0.0574					*0.0328
85.5							
86.0				0.107			0.0574
86.5							
87.0	26.9	0.346	0.0410				*0.0492
87.5				0.0634	*0.0492		*0.0426
88.0							
88.5							
89.0	21.3*	0.796	0.287	0.0469	0.0714		0.0387
89.5							0.0305
90.0							
90.5				0.320	0.115		*0.0737
91.0	18.0	1.80	0.860				
91.5							
92.0				0.852	0.159		0.180
92.5							
93.0	23.6	2.85	0.960				0.134
93.5				0.934	0.292		0.195
94.0							
94.5							
95.0	9.70	5.98	1.44	1.04	0.361		0.333
95.5							0.215
96.0							
96.5				1.24	0.401		0.249
97.0	4.65	2.92	2.08				
97.5							
98.0				1.52	0.346		0.500
98.5							
99.0	0.964	0.387	0.541				0.246*
99.5				1.66	0.878		0.123
100.0							
100.5							
101.0	0.152	0.136	0.459	0.860	0.819		0.361
101.5							0.108
102.0							
102.5				0.410	0.387		0.0451
103.0	0.0533	0.0429	0.136				
103.5							
104.0				0.0410	0.221		0.0778
104.5							0.0755
105.0							
105.5					*0.0410		0.0346
106.0							
SIGMA							
DEC:	3.55	3.04	3.24	3.63	3.82	5.28	
11:	12.4	21.2	33.9	50.7	80.0	221.1	

Table A1 (contd)

SAND STORM NO. 31		NORMALIZED DOSAGES					U-BAR: 8.89		MFTERS/SEC		
DATE 12 SEP 1963		E/Q					DELTA T [1]:		-0.8 DEG F		
TIME 1501 PST		(10 ⁻⁶ SEC/CU METER)					DELTA T [2]:		-1.4 DEG F		
							DELTA T [3]:		-2.2 DEG F		
ARC NO:	3	6	7	8	9	10					
DIST(M):	200	400	600	800	1200	2400					
AZIMUTH											
75.0	0.0713										
75.5											
76.0											
76.5											
77.0	0.290										
77.5											
78.0											
78.5											
79.0	0.204	0.0332									
79.5											
80.0											
80.5											
81.0	4.93	0.194									
81.5				0.0373							
82.0											
82.5											
83.0	54.7	2.24	0.673	0.0664							
83.5											
84.0											
84.5				0.581	0.0664						
85.0	64.7	3.30	0.829								
85.5											
86.0				0.299	0.521	0.197					
86.5											
87.0	69.0	15.4	4.99			0.627					
87.5				5.21	2.80						
88.0						0.0946					
88.5											
89.0	36.5	23.9	8.87	6.20	4.56	0.204					
89.5											
90.0						1.02					
90.5				7.13*	7.46						
91.0	26.5	25.9	11.4			2.39					
91.5											
92.0				8.31	6.70	3.07					
92.5											
93.0	6.64	8.26	8.46			4.79					
93.5				9.32	6.27						
94.0						6.20					
94.5											
95.0	1.14	4.30	4.50	6.20	4.79	3.37					
95.5											
96.0						2.52					
96.5				0.954	0.904						
97.0	0.380	0.239	0.400			0.591					
97.5											
98.0				0.0705	0.125	0.295					
98.5											
99.0	0.110	0.0498									
99.5											
100.0											
100.5											
101.0	0.0664										
SIGMA											
DEG:	2.91	2.65	2.76	2.68	2.50	2.15					
IN:	10.1	18.4	28.9	37.4	52.3	90.0					

Table A1 (contd)

		NORMALIZED DOSAGES						
SAND STORM NO. 32		E/Q					U-BAR: 3.80	METERS/SEC
DATE 16 SEP 1963		[10 ⁻⁶ SEC/CU METER]					DELTA T (1):	-2.1 DEG F
TIME 1413 PST							DELTA T (2):	-2.6 DEG F
							DELTA T (3):	-3.7 DEG F
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
71.0	0.228							
71.5								
72.0								
72.5								
73.0	2.36	0.0593	0.0492					
73.5								
74.0					0.125			
74.5								
75.0	27.9*	0.202	0.410*					
75.5				0.474	4.74			
76.0								
76.5								
77.0	90.8	3.67	3.33	1.33	5.41			
77.5								
78.0								0.816
78.5				4.74	6.26			
79.0	54.9	11.9	32.0					0.991
79.5								
80.0				7.37	10.6			1.27
80.5								
81.0	0.934	5.70	11.2					1.38
81.5				9.83	11.4			
82.0								4.59
82.5								
83.0	0.614	4.80	7.80	10.7	7.80			2.95*
83.5								
84.0								1.95
84.5				15.2	6.88			
85.0	0.429	7.23	8.52					1.80
85.5								
86.0				7.52	2.95*			1.44
86.5								
87.0	0.356	0.287	4.31					0.934
87.5				3.46	1.23			
88.0								0.508
88.5								
89.0	0.254		0.292	1.24	1.20			0.474
89.5								
90.0								0.243
90.5				0.444	0.787			
91.0	0.192							0.138
91.5								
92.0				0.0878	0.292			0.0655
92.5								
93.0	0.0574							0.0492
93.5					0.159			
94.0								0.0369
94.5								
95.0	0.0510				0.0410			
SIGMA								
DEG:	1.92	2.84	2.82	2.85	3.53	2.88		
M:	6.6	19.7	29.5	39.8	73.8	120.4		

Table A1 (contd)

SAND STORM NO. 33		NORMALIZED DOSAGES				U-BAR: 4.51 METERS/SEC	
DATE 8 OCT 1963		E/Q				DELTA T [1]: -0.3 DEG F	
TIME 1543 PST		(10 ⁻⁶ SEC/CM METER)				DELTA T [2]: -0.8 DEG F	
						DELTA T [3]: -1.5 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
68.0					0.0663		
68.5							
69.0	1.46						
69.5					0.673		
70.0							
70.5							
71.0	2.46	0.182	0.232	0.124	1.92		
71.5							
72.0						0.0995	
72.5				0.561	1.59*		
73.0	9.58	1.32	0.949			0.249	
73.5							
74.0				3.08	1.37	0.663	
74.5							
75.0	25.5	10.9	6.47			1.21	
75.5				5.31	0.431		
76.0						1.29*	
76.5							
77.0	76.0	9.12	3.95	7.00	0.124	1.38	
77.5							
78.0						1.58	
78.5				3.98*			
79.0	27.9	8.72	2.49			1.86	
79.5							
80.0				2.29		0.786	
80.5							
81.0	9.59	1.33	0.663			0.395	
81.5				0.746			
82.0						*0.0829	
82.5							
83.0	3.35	0.199	0.434	0.663			
SIGMA							
DEC:	2.30	2.06	2.32	2.29	1.84	2.10	
M:	8.0	14.3	24.2	31.9	38.5	88.0	

Table A1 (contd)

SAND STORM NO. 34 DATE 9 OCT 1963 TIME 1408 PST		NORMALIZED DOSAGES					U-BAR: 6.57 METERS/SEC	
		E/Q					DELTA T [1]:	-1.7 DEG F
		[10 ⁻⁶ SEC/CU METER]					DELTA T [2]:	-1.9 DEG F
							DELTA T [3]:	-2.8 DEG F
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
69.0			0.0871					
69.5				0.0785				
70.0								
70.5								
71.0		0.250	0.562	0.125				
71.5								
72.0								
72.5				0.225				
73.0	0.0831	0.562	0.615					
73.5								
74.0				0.0934				
74.5								
75.0	6.48	1.90	0.475					
75.5				0.266	0.0831			
76.0								
76.5								
77.0	8.65	0.997	0.389		0.748			
77.5								
78.0								
78.5					0.326			
79.0	11.7	0.535						
79.5								
80.0								
80.5								
81.0	0.997	0.349						
81.5								
82.0								
82.5								
83.0	0.0997							
SIGMA								
DEG:	**	2.56	**	**	**	**		
M:	**	17.9	**	**	**	**		

Table A1 (contd)

		NORMALIZED DOSAGES					U-BAR: 10.76 METERS/SEC	
SAND STORM NO. 35		E/Q					DELTA T [1]: -1.3 DEG F	
DATE 11 OCT 1963		[10 ⁻⁶ SEC/CU METER]					DELTA T [2]: -1.6 DEG F	
TIME 1447 PST							DELTA T [3]: -2.5 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
91.0	2.68	0.0572						
91.5								
92.0								
92.5								
93.0	11.4	0.111						
93.5								
94.0								
94.5								
95.0	25.5	0.234						
95.5								
96.0								
96.5								
97.0	40.0	0.409	0.181					
97.5								
98.0								
98.5								
99.0	63.8	3.04	0.294					
99.5								
100.0								
100.5								
101.0	38.3	22.1	0.490	0.0817	*0.0490			
101.5								
102.0								
102.5				0.245	0.0927			
103.0	18.0	27.6	2.01					
103.5								
104.0				0.508	0.164*	0.0695		
104.5								
105.0	6.11	13.7	1.37			0.214		
105.5				1.20	0.302			
106.0						0.291		
106.5								
107.0	0.319	4.58	0.508	1.86	0.948	0.165		
SIGMA								
DEG:	2.96	**	**	**	**	**		
M:	10.3	**	**	**	**	**		

Table A1 (contd)

SAND STORM NO. 36		NORMALIZED DOSAGES				U-BAR: 6.65	METERS/SFC
DATE 15 OCT 1963		E/Q				DELTA T [1]:	-0.5 DEG F
TIME 1608 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]:	-0.8 DEG F
						DELTA T [3]:	-1.6 DEG F
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
77.0	0.0823						
77.5							
78.0							
78.5							
79.0	1.96						
79.5							
80.0							
80.5							
81.0	6.85	0.247	0.0412				
81.5							
82.0							
82.5							
83.0	13.8	4.46	1.88	0.202			0.138
83.5							
84.0							0.390
84.5				2.78	0.145		
85.0	44.6	9.38	6.37				0.698
85.5							
86.0				3.34	3.05		0.769
86.5							
87.0	84.0	12.3	6.58				0.988
87.5				4.89	3.34		
88.0							1.38
88.5							
89.0	62.9	26.3	7.84	5.10	4.33		1.96
89.5							
90.0							1.30
90.5				6.16	4.61		
91.0	9.81	5.76*	8.25				0.0576
91.5							
92.0				1.21	1.23		0.105
92.5							
93.0	4.18	1.22	1.96				0.0329
93.5				0.0905	0.0708		
94.0							
94.5							
95.0	0.658	0.0947	0.0412				
95.5							
96.0							
96.5							
97.0	0.202						
SIGMA							
DEG:	2.48	2.35	2.72	2.23	1.91	1.96	
M:	8.6	16.4	28.5	31.0	40.1	81.9	

Table A1 (contd)

SAND STORM NO. 37		NORMALIZED DOSAGES					U-BAR: 6.40 METERS/SEC
DATE 22 OCT 1963		C/Q					DELTA T [1]: -0.4 DEG F
TIME 1534 PST		110 ⁻⁶ SEC/CU METER					DELTA T [2]: -0.6 DEG F
							DELTA T [3]: -1.1 DEG F
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
65.0	0.0406						
65.5							
66.0							
66.5							
67.0	0.593						
67.5							
68.0							
68.5							
69.0	4.70						
69.5							
70.0							
70.5							
71.0	14.3	0.390*	0.483	0.101			
71.5							0.0383
72.0							
72.5				0.801	0.226		
73.0	12.2	6.21	3.30				
73.5							
74.0				2.34	0.461		
74.5							
75.0	4.06	4.96	2.66				
75.5				1.14	0.608		
76.0							
76.5							
77.0	3.30	3.17	1.28	0.926	0.0790		
77.5							
78.0							
78.5				0.171			
79.0	1.36	0.343	0.634				
79.5							
80.0							
80.5							
81.0	0.232	0.0333	0.0343				
81.5							
82.0							
82.5							
83.0	0.0426						
SIGMA							
DEG:	2.64	1.80	**	1.67	**	**	**
11:	9.2	12.5	**	23.3	**	**	**

Table A1 (contd)

SAND STORM NO. 38		NORMALIZED DOSAGES					U-BAR: 9.26 METERS/SEC	
DATE 23 OCT 1963		E/Q					DELTA T [1]: -1.4 DEG F	
TIME 1335 PST		[10 ⁻⁶ SEC/CJ METER]					DELTA T [2]: -1.7 DEG F	
							DELTA T [3]: -2.6 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST[M]:	200	400	600	800	1200	2400		
AZIMUTH								
67.0	0.0388							
67.5								
68.0								
68.5								
69.0	0.0558							
69.5								
70.0								
70.5								
71.0	0.196	0.0439						
71.5								
72.0								
72.5								
73.0	2.70	0.0782	0.0782					
73.5								
74.0				0.0319				
74.5								
75.0	7.45	0.456	0.128			0.0518		
75.5				0.0550	0.0448			
76.0						0.0917		
76.5								
77.0	28.4	1.34	1.03	0.196	1.28	0.156		
77.5								
78.0						0.187		
78.5				2.03	1.61			
79.0	48.7	5.82	5.01			0.257		
79.5								
80.0				5.82	4.05	0.877		
80.5								
81.0	67.6	28.4	11.3			0.696		
81.5				8.63	4.53			
82.0						1.12		
82.5								
83.0	47.4	31.1	21.5	10.7	6.64	2.84		
83.5								
84.0						1.75		
84.5				9.65	6.51			
85.0	25.5	30.3	16.0*			2.84		
85.5								
86.0				10.5	4.26	1.34		
86.5								
87.0	14.0	9.25	14.0			1.12		
87.5				7.32	4.39			
88.0						1.05		
88.5								
89.0	5.97	4.47	5.25	6.45	4.87	1.05		
89.5								
90.0						0.317		
90.5				3.78	1.05			
91.0	4.95	0.337	0.555			0.124		
91.5								
92.0				0.555	0.772			
92.5								
93.0	0.597		0.134					
93.5				0.0909	0.190			
SIGMA								
DEG:	3.53	2.59	2.91	3.29	3.58	2.92		
M:	12.3	18.0	30.4	45.8	74.9	122.3		

Table A1 (contd)

		NORMALIZED DOSAGES				U-BAR: 6.83 METERS/SEC	
		E/Q				DELTA T (1): -1.8 DEG F	
		[10 ⁻⁶ SEC/CU METER]				DELTA T (2): -2.7 DEG F	
						DELTA T (3): -3.0 DEG F	
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
65.0	0.668	0.248					
65.5							
66.0							
66.5							
67.0	2.37	1.03	0.180				
67.5							
68.0				0.278			
68.5							
69.0	20.8	2.52	0.618				
69.5				0.970	0.198		
70.0							
70.5							
71.0	41.7	9.42	3.23	2.26	2.01		
71.5							
72.0							
72.5				2.75	1.33		
73.0	52.0	10.9	8.55				
73.5							
74.0				3.48			
74.5							
75.0	31.7	14.0	2.74				
75.5							
76.0							
76.5							
77.0	25.2*	2.70					
77.5							
78.0							
78.5							
79.0	20.4						
79.5							
80.0							
80.5							
81.0	5.51						
81.5							
82.0							
82.5							
83.0	1.40						
83.5							
84.0							
84.5							
85.0	0.242						
SIGMA							
DEG:	3.39	2.38	**	**	**	**	**
M:	11.8	16.6	**	**	**	**	**

A42

Table A1 (contd)

SAND STORM NO. 41		NORMALIZED DOSAGES				U-BAR: 8.96		MFTERS/SFC	
DATE 4 NOV 1963		C/Q				DELTA T [1]:		-1.8 DEG F	
TIME 1208 PST		[10 ⁻⁶ SEC/CJ METER]				DELTA T [2]:		-2.0 DEG F	
						DELTA T [3]:		-3.1 DEG F	
ARC NO:	3	6	7	8	9	10			
DIST(M):	200	400	600	800	1200	2400			
AZIMUTH									
59.0	0.181	0.0821	0.304	0.361	0.166				
59.5									
60.0									
60.5				0.594	0.640				
61.0	0.474	1.17	1.09						
61.5									
62.0				2.28	0.697	0.0944			
62.5									
63.0	3.12	3.33	2.36			0.181			
63.5				3.76	1.53				
64.0						0.208			
64.5									
65.0	5.71	5.91	5.84	4.17	2.08	0.333			
65.5									
66.0						0.781			
66.5				4.74	3.46				
67.0	18.1	18.1	7.94			1.02			
67.5									
68.0				7.30	4.10	0.757			
68.5									
69.0	46.0	20.8	10.5			0.389			
69.5				9.29	5.01				
70.0						0.208			
70.5									
71.0	55.8	17.2	11.5	7.60	2.56	0.130			
71.5									
72.0						0.0903			
72.5				7.81	1.27				
73.0	36.1	24.9	14.4			0.0369			
73.5									
74.0				2.92	0.430				
74.5									
75.0	23.6	27.7	4.66						
75.5				1.38	0.0903				
76.0									
76.5									
77.0	43.2	17.2	3.33	1.44	0.222				
77.5									
78.0									
78.5				2.08	0.128				
79.0	19.5	7.30	2.92						
79.5									
80.0				1.08					
80.5									
81.0	6.33	1.08	0.0410						
81.5				0.0328					
82.0									
82.5									
83.0	0.648								
83.5									
84.0									
84.5									
85.0	0.0356								
SIGMA									
DEG:	4.09	4.18	4.15	4.33	3.32	2.21			
M:	14.2	29.1	43.4	60.5	69.6	92.5			

Table A1 (contd)

SAND STORM NO. 42		NORMALIZED DOSAGES				U-BAR: 10.18	METERS/SEC
DATE 5 NOV 1963		E/Q				DELTA T [1]:	-1.3 DEG F
TIME 1425 PST		[10 ⁻⁶ SEC/CU METER]				DELTA T [2]:	-1.5 DEG F
						DELTA T [3]:	-2.4 DEG F
ARC NO:	3	6	7	8	9	10	
DIST[M]:	200	400	600	800	1200	2400	
AZIMUTH							
57.0	0.0416						
57.5							
58.0							
58.5							
59.0	0.0457						
59.5							
60.0							
60.5							
61.0	0.366						
61.5							
62.0				*0.0832	0.0665		
62.5							
63.0	0.665	0.0707	0.0644				0.101
63.5				0.273	0.183		
64.0							0.211
64.5							
65.0	1.98	0.216	0.665	0.665	0.253		0.198
65.5							0.225
66.0							
66.5				0.873	0.536		
67.0	7.7	3.24	2.66				0.0915
67.5							
68.0				1.16	1.16		0.0205
68.5							
69.0	24.0	5.99	4.16*				0.110
69.5				2.96	0.948		
70.0							*0.0965
70.5							
71.0	42.3	7.05	6.22	4.08			0.0832
71.5							
72.0							
72.5				2.05			
73.0	25.3	8.12	12.7				
73.5							
74.0				0.183			
74.5							
75.0	19.8	4.01	1.38				
75.5							
76.0							
76.5							
77.0	1.75	0.374	0.0499				
77.5							
78.0							
78.5							
79.0	0.0333						
SIGMA							
DEG:	2.64	2.62	2.40	2.41	1.90		**
M:	9.2	18.2	25.1	33.6	39.7		**

A44

Table A1 (contd)

SAND STORM NO. 43		NORMALIZED DOSAGES				U-BAR: 7.34	METERS/SEC
DATE 7 NOV 1963		E/Q				DELTA T [1]:	-1.2 DEG F
TIME 1422 PST		[10 ⁻⁶ SEC/CU METER]				DFLTA T [2]:	-1.6 DEG F
						DELTA T [3]:	-2.2 DEG F
ARC NO:	3	6	7	8	9	10	
DIST(M):	200	400	600	800	1200	2400	
AZIMUTH							
65.0	0.264						
65.5							
66.0							
66.5							
67.0	1.27						
67.5							
68.0							
68.5							
69.0	2.02	0.894	0.202				
69.5				0.0410			
70.0						0.0677	
70.5							
71.0	9.64	1.41	0.0902	0.100	0.0451	0.101	
71.5							
72.0						0.221	
72.5				0.246	0.246		
73.0	9.35	0.866	0.640			0.123	
73.5							
74.0				0.820	0.287		
74.5							
75.0	15.3	2.92	0.894				
75.5				2.21	1.80		
76.0							
76.5							
77.0	11.9	2.36	0.553	1.23	1.08		
77.5							
78.0							
78.5				0.877			
79.0	4.02	1.53	0.738				
79.5							
80.0				0.208			
80.5							
81.0	0.202	0.109	0.0510				
81.5				0.0553			
SIGMA							
DEG:	2.93	3.08	**	2.02	**	**	
M:	10.2	21.5	**	28.1	**	**	

Table A1 (contd)

SAND STORM NO. 44		NORMALIZED USAGES					U-BAR: 4.48 METERS/SEC	
DATE 13 NOV 1963		E/Q					DELTA T [1]: -1.0 DEG F	
TIME 1408 PST		[10 ⁻⁶ SEC/CU METER]					DELTA T [2]: -1.3 DEG F	
							DELTA T [3]: -1.9 DEG F	
ARC NO:	3	6	7	8	9	10		
DIST(M):	200	400	600	800	1200	2400		
AZIMUTH								
54.5				0.410				
55.0	0.0363	0.0847	0.115					
55.5								
56.0				0.389				
56.5								
57.0	1.92	0.462	0.363					
57.5				0.169	*0.0404			
58.0								
58.5								
59.0	8.09	0.0404	0.220	0.0865	0.0888			
59.5								
60.0								
60.5				0.0404	0.0565			
61.0	2.45	0.0161	0.242					
61.5								
62.0				0.0494	0.0381			
62.5								
63.0	0.936	0.199	0.0775					
63.5				0.0544	*0.0387			
64.0						0.0605		
64.5								
65.0	0.520	0.218	0.0815		0.0404	0.0565		
65.5								
66.0								
66.5					*0.0533			
67.0	0.444	0.0686	0.0605					
67.5								
68.0					0.0704			
68.5								
69.0	0.0625	0.0784	0.0161					
69.5								
70.0								
70.5								
71.0			0.0350					
SIGMA								
DEG:	2.30	**	**	**	**	**		
II:	8.0	**	**	**	**	**		

Table A2. Remarks Concerning Table A1

Run	Position	Remarks
2	3-53	Interpolated; dead engine, gas 2/3 full.
3	5-65	Interpolated; dead engine, gas full.
	5-77	Estimated; 1/2 filter missing.
	9-73	Interpolated; dead engine, gas full, cock closed.
	9-75	Interpolated; dead engine, gas full, cock closed.
	9-81	Interpolated; dead engine, gas full, cock closed.
	9-83	Interpolated; dead engine, gas full, cock closed.
	10-77	Interpolated; sample lost.
	10-78	Interpolated; filter torn.
5	2-53	Interpolated; dead engine, gas 3/4 full.
	7-53	Interpolated; dead engine, gas 2/3 full.
	7-71	Interpolated; sample lost.
	9-65	Interpolated; sample lost.
	9-67	Interpolated; sample lost.
	9-77	Interpolated; sample spilled.
	10-62	Interpolated; filter damaged.
	10-75	Interpolated; sample lost.
	10-76	Interpolated; sample lost.
6	5-83	Interpolated; filter lost.
7	1-57	Interpolated; extremely low assay, no explanation.
	5-59	Interpolated; filter lost.
11	4-53	Interpolated; filter lost.
	6-68	Interpolated; filter damaged.
	9-55	Interpolated; engine dead, gas full, cock closed.
	10-71	Interpolated; filter lost.
12	1-57	Interpolated; engine dead, gas 3/4 full.
	7-77	Interpolated; engine dead, gas full.
14	7-89	Interpolated; dead engine, gas full, cock closed.
	10-90	Interpolated; dead engine, gas full, cock closed.
16	3-85	Interpolated; dead engine, gas 3/4 full.
	6-99	Interpolated; dead engine, gas 3/4 full, engine seized.
	6-103	Interpolated; dead engine, gas 3/4 full, engine seized.
	8-96.5	Interpolated; dead engine, gas full, cock closed.
	9-102.5	Interpolated; dead engine, gas 3/4 full, engine seized.
	10-90	Interpolated; no sample collected.

Table A2 (contd)

Run	Position	Remarks
17	9-81.5	Interpolated; low vacuum.
18	3-67	Interpolated; engine dead, gas full.
	6-63	Interpolated; engine dead, gas 3/9, engine seized.
	6-69	Interpolated; low vacuum.
	6-73	Interpolated; orifice plugged.
	9.57.5	Interpolated; engine dead, fuel cap off.
	9-59	Interpolated; engine dead, fuel cap off.
20	3-67	Interpolated; dead engine, gas 1/2 full.
	8-86	Interpolated; filter torn.
	9-78.5	Interpolated; dead engine, gas 1/2 full.
	9-83	Interpolated; sample spilled.
	9-89	Interpolated; low vacuum.
	10-61	Interpolated; filter lost.
	10-64	Interpolated; dead engine, gas 3/4 full.
21	3-85	Interpolated; dead engine, gas 3/4 full, engine seized.
	6-71	Interpolated; dead engine, fuel cap off.
	6-83	Interpolated; dead engine, fuel cap off.
	8-71	Interpolated; dead engine, gas full.
	8-75.5	Interpolated; sample spilled.
	9-74	Interpolated; low vacuum.
	9-86	Interpolated; dead engine, gas full.
	10-73	Interpolated; dead engine, gas 3/4 full.
	10-81	Interpolated; filter torn.
	10-84	Interpolated; dead engine, gas 3/4 full.
22	3-95	Interpolated; dead engine, gas full.
	6-93	Interpolated; dead engine, gas 1/2 full.
	6-103	Interpolated; filter lost.
24	3-91	Interpolated; dead engine, gas 3/4 full.
	8-81.5	Interpolated; dead engine, gas 3/4 full.
	10-87	Interpolated; damaged filter.
25	3-69	Interpolated; low vacuum.
	8-78.5	Interpolated; damaged filter.
26	8-62	Interpolated; damaged filter.
	9-75.5	Interpolated; lost filter.
	9-60.5	Interpolated; sample spilled.

Table A2 (contd)

Run	Position	Remarks
26	9-65	Interpolated; dead engine, gas full.
	10-64	Interpolated; filter lost.
	10-69	Interpolated; dead engine, gas 3/4 full, seized engine.
27	7-65.0	Interpolated; damaged filter.
	8-65.0	Interpolated; damaged filter.
	9-57.5	Interpolated; dead engine, gas 3/4 full.
	10-59	Interpolated; filter lost.
	10-62	Interpolated; low vacuum.
28	3-67	Interpolated; dead engine, gas 1/2 full.
29	3-79	Interpolated; damaged filter.
	3-85	Interpolated; dead engine, gas 3/4 full.
	6-77	Interpolated; dead engine, gas full.
	7-73	Interpolated; damaged filter.
	9-72.5	Interpolated; spilled sample.
	9-80	Interpolated; dead engine, gas 3/4 full.
	9-83	Interpolated; dead engine, gas 3/4 full.
30	3-89	Interpolated; dead engine, gas full.
	9-87.5	Interpolated; dead engine, gas 1/2 full.
	9-105.5	Interpolated; dead engine, gas 1/2 full.
	10-85	Interpolated; damaged filter.
	10-87	Interpolated; damaged filter.
	10-88	Interpolated; damaged filter.
	10-91	Interpolated; dead engine, gas full.
	10-99	Interpolated; dead engine, gas 1/2 full.
31	8-90.5	Interpolated; dead engine, gas full.
32	3-75	Interpolated; dead engine, gas 3/4 full.
	7-75	Interpolated; dead engine, gas 3/4 full.
	9-86	Interpolated; dead engine.
	10-83	Interpolated; lost filter.
33	8-78.5	Interpolated; damaged filter.
	9-72.5	Interpolated; damaged filter.
	10-76	Interpolated; spilled sample.
	10-82	Interpolated; damaged filter.
35	9-101	Interpolated; damaged filter.
	9-104	Interpolated; damaged filter.

Table A2 (c ntd)

Run	Position	Remarks
36	6-91	Interpolated; dead engine, fuel line off.
37	6-71	Interpolated; damaged filter.
38	7-85	Interpolated; spilled sample.
40	3-77	Interpolated; dead engine, gas 3/4 full.
42	7-69	Interpolated; lost filter.
	8-62	Interpolated; dead engine, gas 3/4 full.
	10-70	Interpolated; dead engine, gas 3/4 full.
44	9-57.5	Interpolated; lost filter.
	9-63.5	Interpolated; damaged filter.
	9-66.5	Interpolated; dead engine, gas 3/4 full.

Table A3. Source Data

Experiment Number	Date (1963)	Weight of Expended Propellant (pounds)	Firing Duration (seconds)
2	27 March	7.20	5.4
3	8 April	25.00	5.0
4	19 April	Unknown	Unknown
5	24 April	7.60	5.1
6	6 May	15.04	3.9
7	8 May	15.05	8.0
8	22 May	14.90	4.9
9	23 May	14.77	5.0
10	29 May	25.74	2.5
11	10 June	25.95	2.4
12	12 June	25.95	2.5
13	14 June	24.90	8.0
14	19 June	15.00	4.7
16	9 July	23.07	6.3
17	11 July	22.54	7.5
18	15 July	14.51	4.2
19	17 July	13.96	5.3
20	26 July	30.43	7.8
21	30 July	30.52	8.1
22	9 August	30.85	8.5
23	16 August	30.69	7.7
24	19 August	29.97	7.7
25	21 August	65.81	7.1
26	22 August	66.53	7.2
27	27 August	65.56	7.1
28	30 August	65.47	7.1
29	10 September	65.88	7.3
30	11 September	65.75	7.2
31	12 September	64.95	7.8
32	16 September	65.75	7.3
33	8 October	39.71	5.3
34	9 October	39.60	5.9
35	11 October	65.92	7.6
36	15 October	65.45	7.3
37	22 October	66.31	7.9
38	23 October	67.53	7.5
39	29 October	22.54	8.2
40	30 October	15.00	5.0
41	4 November	65.66	6.8
42	5 November	64.78	7.0
43	7 November	65.68	8.1
44	13 November	66.75	7.7

Appendix B

Phototheodolite Data

The data presented in this appendix were taken from three phototheodolite cameras, Model KTH 53. The cameras were pulsed simultaneously at a rate of four frames per second and recorded the azimuth and elevation of the aiming point as well as the time. One camera was positioned approximately one-third mile upwind of the firing pad. The other two were positioned approximately one mile from the firing pad on a line normal to the centerline of the sampling grid. Camera locations relative to the firing pad and sampling grid are shown in Figure 6 of Chapter III in the report. Triangulation with the camera closest to the firing pad and either of the other two cameras sufficed to fix the position in space and time of any portion of the cloud observed by the two cameras.

For many of the experiments it was possible to identify only the top of the cloud from two camera positions simultaneously. Consequently the height, rate of rise, and the rate of transport of the top of the cloud was the only information obtained from those experiments. For others it was possible to determine the crosswind dimension from the angular width taken from pictures made by the upwind camera. For a few experiments the dimension in the direction of travel was determined from the angular spread of the cloud in pictures made by one or both of the other two cameras. It was never possible, however, to identify both the top and the base of the visible cloud simultaneously, so that estimates of the height of the cloud's center were not possible; hence, we were unable to determine the effective source height with reasonable accuracy.

Adverse weather conditions, such as blowing sand which could damage camera lenses and haze which made cloud definition poor, as well as priority commitments of camera crews, reduced the number of diffusion experiments supported by phototheodolite measurements to 32. Of these, some were of less than 20 seconds duration.

The tabulations which follow present the position of the cloud top and the cloud width and length as a function of time after the cloud was first observed by one of the cameras. This time can be taken to be about 1 to 2 seconds after ignition. The X coordinate is oriented along the centerline of the 90-degree sampling grid, that is, the 062-degree true azimuth from the firing pad. The Y coordinate is normal to the X coordinate, with positive values to the south and negative values to the north.

Table B1. Phototheodolite Data

SAND STORM NO. 2

DATE: 27 Mar 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
3	15.9	- 6.5	146.1		
4	18.2	- 5.2	179.3		
5	21.5	- 6.8	214.4		
6	23.0	-10.1	251.1		
7	25.5	- 9.1	288.3		
8	22.5	-17.9	316.8		
9	23.6	-24.5	350.3		
10	25.3	-13.8	401.3		
11	25.5	-17.9	433.6		
12	27.4	-28.0	462.6		
13	26.5	-32.9	510.8		
14	29.5	-38.6	537.7		
15	29.9	-41.4	562.9		
16	35.3	-56.8	580.7		

SAND STORM NO. 3

DATE: 8 Apr 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
2	18.5	17.0	99.2	13.8	
3	23.2	26.1	133.4	26.6	
4	24.8	28.9	150.9	31.8	
5	29.2	32.8	183.3	35.9	
6	34.9	42.0	214.4	45.4	
7	39.0	44.6	244.9	51.9	
8	43.8	46.2	272.8	61.1	
9	49.8	58.0	299.7	68.0	
10	53.6	57.2	338.2	71.8	
11	63.8	65.0	360.8	75.7	
12	73.5	71.7	396.5	79.4	
13	83.2	77.8	427.3	77.4	
14	95.4	86.2	463.4	85.3	
15	103.1	85.2	496.7	96.6	
16	110.8	96.6	534.6	104.0	
17	118.4	106.1	564.1		
18	133.8	109.5	606.3		
19	139.5	121.2	651.0	106.5	
20	152.3	135.3	691.6	106.3	
24	177.6	180.1	848.3	134.6	

B4

Table B1 (contd)

SAND STORM NO. 4

DATE: 19 Apr 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
2	23.3	1.2	106.1		
3	29.6	13.0	151.8		
4	41.4	5.6	196.3		
5	48.8	5.6	240.6		
6	54.8	4.2	286.9		
7	61.0	5.3	331.6		
8	71.4	.2	374.1		
9	73.7	13.3	420.9		
10	80.0	11.7	465.1		
11	86.9	15.8	510.1		
12	95.3	23.5	554.9		

Table B1 (contd)

SAND STORM NO. 6

DATE: 6 May 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	4.9	2.2	14.8	4.6	
1	16.1	20.3	74.4	31.0	
2	31.9	35.3	110.5	38.3	
3	39.4	44.6	128.5	55.0	
4	46.9	52.4	146.8	59.7	
5	52.2	61.0	171.5	67.2	
6	51.5	69.5	194.0	72.4	
7	59.2	76.8	214.7	76.4	
8	54.9	85.5	242.0	77.7	
9	56.6	99.9	283.5	85.8	
10	61.5	99.8	301.3	87.0	
11	64.0	106.1	326.2	92.4	
12	73.4	113.0	351.4	89.5	
13	84.8	128.0	374.3	89.1	
14	89.0	129.9	400.4	93.4	
15	97.1	134.3	427.5	90.7	
16	102.4	135.0	453.4	94.9	
17	108.9	140.7	477.0	96.8	
18	112.0	148.9	498.7	99.5	
19	108.5	155.5	526.7	101.9	
20	115.8	164.6	551.6	106.4	
25	144.9	196.4	686.0	113.5	
30	153.3	215.3	788.9		
31	164.3	231.9	840.1		

Table B1 (contd)

SAND STORM NO. 7

DATE: 8 May 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	10.6	6.5	43.2		
1	19.7	12.7	85.7		
2	28.1	25.7	131.4		
3	40.3	23.4	165.4		
4	46.2	18.5	179.7		
5	52.3	19.4	219.2		
6	58.4	15.9	242.9		
7	64.8	16.8	271.6		
8	73.7	18.0	294.6		
9	77.5	15.9	341.4		
10	80.3	7.2	374.6		

Table B1 (contd)

SAND STORM NO. 10

DATE: 27 May 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	17.2	8.9	77.7		
1	30.1	28.2	106.9		
2	31.8	31.9	127.8		
3	33.8	46.0	164.6		
4	44.5	48.9	174.2		
5	52.0	66.3	225.6		
6	62.1	75.2	234.7		
7	71.6	76.1	246.3		
8	75.7	77.1	251.3		
9	78.0	75.8	249.7		
10	89.8	80.0	268.3		
11	92.2	82.9	276.0		
12	95.0	84.2	288.7		
13	98.2	90.3	303.5		
14	101.0	91.4	306.9		
15	110.2	92.5	319.1		
16	117.5	94.0	326.0		
17	120.1	100.1	337.5		
18	123.8	103.3	351.9		
19	131.1	105.9	358.9		
20	138.8	105.4	374.1		
25	175.0	106.3	447.1		
30	210.4	98.8	531.8		
35	244.9	105.7	608.2		
36	252.8	109.1	624.1		

Table B1 (contd)

SAND STORM NO. 13

DATE: 14 June 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	8.2	2.1	20.7		
1	18.2	10.0	65.0		
2	24.9	14.7	86.3	44.0	
3	27.9	21.4	126.0	51.4	
4	38.7	24.8	142.9	60.1	
5	49.3	21.2	151.2		
6	55.7	21.2	159.6	66.4	
7	60.1	19.8	170.3	68.3	
8	64.5	18.9	176.0		
9	69.8	20.7	186.7		
10	74.0	29.0	217.8		
11	83.5	26.8	221.7	80.8	
12	91.8	24.9	225.7		
13	96.3	19.5	231.6	82.3	
14	104.8	18.6	237.4		
15	114.1	18.5	246.0	88.7	
16	119.5	19.9	250.6		
17	128.4	21.7	259.5		
18	136.4	23.4	261.2		
19	139.7	27.2	271.2		
25	162.4	70.0	374.0		
30	196.1	91.1	417.9		
35	225.4	110.5	463.5		
40	240.9	147.8	491.3		

Table B1 (contd)

SAND STORM NO.14

DATE: 19 June 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	12.0	9.9	38.6		
1	19.1	28.7	76.5	36.5	
2	18.8	37.6	91.6	47.0	
3	19.8	50.9	137.3	61.2	
4	28.4	63.7	166.1	65.9	
5	31.7	60.6	181.4		
6	39.4	67.4	194.4	67.3	
7	43.1	66.0	204.7	68.3	
8	44.9	76.1	225.8	68.9	
9	50.2	84.9	243.0		
10	55.6	92.8	254.5	69.6	
11	57.7	93.7	261.6		
12	59.7	107.0	282.4	72.8	
13	65.7	106.8	300.9	74.4	
14	67.5	118.2	310.5		
15	70.0	122.5	318.2		
16	81.5	116.9	332.8	78.5	
17	83.0	129.2	346.0	76.9	
18	87.4	133.0	357.1	81.0	
19	89.4	132.1	372.8		
20	93.7	143.1	391.2		
25	112.5	173.0	456.6		

Table B1 (contd)

SAND STORM NO. 16

DATE: 9 July 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	3.8	3.8	16.6		
1	18.6	25.4	81.3		
2	25.4	23.7	107.6		
3	30.5	33.1	119.5		
4	33.3	42.5	131.1		
5	34.1	45.8	135.6		
6	36.5	56.5	168.4		
7	43.6	60.7	188.0		
8	47.6	62.1	192.2		
9	49.1	67.0	203.0		
10	55.8	72.8	215.8		
11	59.3	83.7	234.5		
12	66.4	87.7	250.3		
13	70.0	87.7	267.6		
14	69.7	96.0	278.4		
15	76.4	100.4	304.9		
16	81.7	104.2	313.7		
17	88.8	110.2	328.1		
18	88.7	119.4	335.0		

SAND STORM NO. 17

DATE: 11 July 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	7.1	1.1	.3	6.7	
1	12.8	6.0	26.9	21.8	
2	23.1	24.9	72.9	41.5	
3	32.0	30.6	108.7	51.4	
4	35.4	32.4	129.4	62.5	
5	39.2	39.5	154.2	71.9	
6	41.7	34.5	169.0	78.1	
7	47.1	39.3	177.0	83.9	
8	48.1	47.3	188.6		
9	53.0	54.5	218.4	91.2	
10	58.2	61.1	229.7	91.5	
11	65.8	66.9	248.6	91.9	
12	68.4	74.0	259.4	92.4	

Table B1 (contd)

SAND STORM NO. 18

DATE: 15 July 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
1	18.8	11.3	65.6		
2	19.9	8.8	106.2		
3	26.0	8.5	138.5		
4	29.9	11.2	166.4		
5	35.4	9.3	194.4		
6	40.0	6.1	223.0		
7	45.2	8.9	250.9		
8	49.2	6.9	276.0		
9	53.0	9.9	295.9		
10	57.4	7.2	318.1		
11	63.6	21.0	339.8		
12	71.2	22.3	366.2		
13	78.6	25.3	388.5		
14	83.6	23.4	413.2		
15	87.9	24.5	447.0		
16	93.0	25.1	467.7		
17	98.9	20.0	496.5		
18	103.8	18.5	522.4		
19	109.2	18.2	547.2		
20	112.6	18.6	573.0		
25	127.6	14.3	691.4		
30	142.7	9.1	822.7		
34	153.5	- 7.7	887.3		

Table B1 (contd)

SAND STORM NO.19

DATE: 17 July 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	6.8	6.6	17.7		
1	14.1	22.5	71.5	29.8	
2	20.6	31.2	108.7	41.1	
3	25.5	41.0	147.7	51.5	
4	23.9	41.5	154.0	56.1	
5	26.5	48.5	170.3	60.3	
6	28.1	57.9	196.6	67.7	
7	30.6	64.5	216.8	68.0	
8	39.4	80.8	263.6	74.5	
9	45.1	91.3	287.0	79.2	
10	45.9	101.5	311.4		
11	54.2	120.0	335.7	92.1	
12	62.9	135.3	354.2		
13	74.1	151.4	398.3	98.2	
14	78.2	157.9	419.6		
15	88.9	169.2	460.3		
16	92.7	179.1	494.4	109.0	

Table B1 (contd)

SAND STORM NO. 20

DATE: 26 July 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	13.1	11.5	55.2		
1	21.0	21.5	95.9		
2	25.8	27.7	126.2		
3	29.7	32.3	150.1		
4	33.5	36.2	178.0		
5	38.7	39.1	199.3		
6	45.7	47.9	225.3		
7	54.7	49.3	244.4		
8	64.0	54.1	264.5		
9	72.6	56.3	278.8		
10	80.0	54.6	291.1		
11	87.0	57.5	307.9		
12	92.6	62.3	322.6		
13	97.9	67.7	338.3		
14	103.9	71.1	352.6		
15	108.1	74.8	368.5		
16	113.7	77.8	385.4		
17	116.9	75.8	400.8		
18	123.5	74.9	410.2		
19	131.5	82.0	433.9		
20	135.9	83.7	449.9		
25	169.0	98.2	519.3		
30	199.4	120.5	587.6		
35	233.0	142.4	676.6		
40	268.5	175.8	722.3		
45	297.5	238.7	783.6		
48	307.5	263.3	797.8		

Table B1 (contd)

SAND STORM NO. 21

DATE: 30 July 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	4.2	2.0	22.3	5.9	
1	19.2	16.6	81.5	44.9	
2	24.5	12.4	124.8	57.0	
3	28.6	20.5	176.6	65.4	
4	34.9	69.1	206.6	65.9	
5	40.2	83.4	237.3	69.9	
6	45.8	91.5	273.1	76.5	
7	51.8	100.8	307.1	80.3	
8	57.3	111.5	340.1	86.7	
9	61.4	122.8	383.9	94.4	
10	63.5	129.9	402.7		
11	70.3	137.6	435.7		
12	74.3	149.8	465.9		
13	82.0	157.1	501.2		
14	87.3	171.4	531.7		
15	93.6	180.0	562.5		
16	98.3	187.5	584.7		
17	104.6	198.0	621.4		
18	110.1	201.1	654.4		
19	114.7	209.0	684.4		
20	120.0	216.3	715.5		
25	137.7	240.8	850.5		
30	159.5	284.8	1010.1		
35	190.9	319.8	1157.7		
40	208.1	330.5	1299.4		
45	222.2	387.2	1453.5		
48	231.0	367.4	1530.7		

Table B1 (contd)

SAND STORM NO. 22

DATE: 9 Aug 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	4.9	4.0	19.2		
1	18.9	24.3	66.2		
2	21.8	37.6	100.1		
3	20.4	42.8	130.7		
4	28.2	63.2	150.2		
5	33.0	75.3	168.7		
6	35.6	85.9	185.0		
7	44.2	93.3	200.9		
8	48.3	103.0	217.5		
9	55.4	104.8	240.5		
10	62.6	117.4	261.5		
11	68.0	127.7	275.2		
12	70.6	135.9	284.1		
13	74.5	136.9	298.7		
14	80.4	142.9	308.0		
15	87.0	150.1	315.0		
16	92.5	155.8	326.1		
17	99.5	162.6	340.5		
18	104.8	173.9	351.6		
19	109.0	182.7	362.7		
20	116.5	194.0	386.5		
25	117.4	250.7	457.5		
30	133.8	307.8	522.0		
35	145.6	353.2	610.8		
40	153.6	395.7	666.4		
45	166.7	440.0	762.2		
50	162.3	543.2	823.6		
54	165.3	562.1	871.9		

Table B1 (contd)

SAND STORM NO. 23

DATE: 16 Aug 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	9.9	8.7	28.5	11.2	
1	23.2	28.2	84.5	35.9	
2	37.7	33.9	110.5	47.0	
3	45.1	38.6	136.1	47.3	
4	49.7	43.6	160.5	54.6	
5	51.3	47.0	182.9	53.7	
6	50.5	61.8	252.7	58.2	
7	53.4	64.5	275.4	63.2	
8	55.8	72.1	302.7	60.5	
9	56.0	75.3	326.5	72.6	
10	57.6	80.6	356.0	79.6	
11	56.5	84.3	371.9	86.3	
12	57.0	93.0	410.4	84.5	
13	57.1	96.6	439.1	94.8	
14	58.8	101.6	472.4	96.7	
15	60.6	104.4	481.8	107.4	
16	62.2	106.4	517.1	112.4	
17	61.7	108.9	537.2	118.3	
18	63.7	117.3	567.7		
19	64.2	119.4	593.1		
20	64.4	126.9	619.4		
25	69.8	107.0	740.6		
27	75.0	119.2	811.4		

Table B1 (contd)

SAND STORM NO. 25

DATE: 21 Aug 63

TIME	POSITION OF TOP			WIDTH	LENGTH
	Z	Y	X		
(seconds)	(feet)	(feet)	(feet)	(feet)	(feet)
0	3.6	2.9	5.8	5.8	
1	17.1	28.9	91.3	43.9	
2	28.4	25.0	120.6	65.3	
3	36.1	48.6	145.3	71.0	
4	44.1	58.0	165.6	86.5	
5	47.0	61.5	184.5	87.4	
6	52.6	72.4	203.7	101.6	
7	53.7	80.1	225.8	111.3	
8	55.0	85.1	247.3	118.0	
9	57.2	89.4	268.0		
10	63.9	93.2	285.6		
11	67.2	100.7	302.2		
12	69.3	111.5	321.2		
13	71.3	118.9	341.5		
14	74.0	127.9	360.0		
15	77.0	155.3	406.9		
16	83.9	168.8	440.9		
17	89.5	177.8	455.9		
18	97.1	192.1	478.2		
19	105.7	203.7	500.1		
20	113.6	210.4	521.6		
25	160.1	260.3	623.9		
30	201.5	300.5	730.3		

Table B1 (contd)

SAND STORM NO. 26

DATE: 22 Aug 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
1	21.4	10.3	81.0		
2	30.8	6.6	163.2		
3	43.5	8.8	199.8		
4	54.0	10.0	249.8		
5	64.1	12.6	288.5		
6	71.4	9.3	324.7		
7	72.4	14.9	364.5		
8	76.5	19.2	416.2		
9	78.1	3.3	440.7		
10	77.2	4.4	478.8		
11	86.2	-3.5	519.7		
12	89.0	.0	550.7		
13	93.4	.8	583.2		
14	94.8	-2.2	618.5		
15	98.2	1.4	656.1		
16	97.7	4.5	689.2		
17	101.4	7.5	727.5		
18	104.1	25.1	829.6		
19	110.9	25.1	873.0		
20	111.2	28.3	913.2		
25	124.4	39.8	1120.1		
29	135.6	40.2	1263.4		

Table B1 (contd)

SAND STORM NO. 27

DATE: 27 Aug 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	8.0	8.3	45.4	13.7	
1	20.7	19.8	100.2	38.5	
2	34.1	24.5	127.8	64.3	
3	41.2	26.0	147.6	80.4	
4	43.5	31.1	164.0	93.3	
5	46.1	30.4	179.1	101.3	
6	47.2	38.5	245.2	110.0	
7	51.0	41.8	310.8	121.9	
8	57.7	45.5	334.4	138.1	
9	62.0	46.8	358.7	146.5	
10	67.2	44.4	399.7	151.8	
11					
12					
13	84.5	38.6	463.7	167.8	
14	87.9	46.6	488.5	160.6	
15	92.7	51.3	512.0	174.2	
16	96.9	44.1	539.0	181.1	
17	101.3	40.9	563.6	189.5	
18	106.4	44.0	587.5	190.2	
19	110.4	38.1	606.5		
20	114.8	44.2	630.6		
25	131.7	23.3	771.4		
30	147.7	15.6	844.3		
35	164.8	26.1	965.2		
40	188.9	-18.8	1087.7		
45	217.4	-22.7	1198.0		
50	238.2	-19.9	1307.9		
55	260.2	-6.5	1439.1		
60	271.0	-10.5	1558.4		
65	278.6	.6	1687.9		
70	289.9	-1.7	1816.2		
75	304.4	3.8	1959.5		
80	307.5	10.5	2099.7		
85	312.5	19.8	2196.4		
90	321.3	19.8	2313.2		
95	331.1	13.1	2451.6		
98	341.4	21.9	2529.3		

Table B1 (contd)

DAND STORM NO. 28

DATE: 30 Aug 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	11.2	6.6	34.7	18.5	
1	20.5	10.7	89.0	37.6	
2	29.7	23.1	132.3	62.3	
3	30.2	35.8	168.5	71.1	
4	38.5	40.5	209.2	77.9	
5	46.1	45.0	234.7	90.0	
6	53.2	49.4	266.1	96.0	
7	60.1	56.6	284.4	104.1	
8	65.6	62.8	316.9	112.6	
9	73.5	64.3	342.3		
10	78.9	67.9	368.6		
11	85.8	74.7	388.2	115.0	
12	94.0	76.7	417.7	118.5	
13	95.9	87.1	438.2	120.7	
14	101.5	92.7	461.6	125.2	
15	106.0	98.1	488.1	130.0	
16	113.9	103.9	515.6		
17	119.0	111.3	540.5		
18	119.9	116.8	566.7		
19	127.4	120.2	591.8	138.9	
20	136.6	124.3	613.9	139.7	
25	164.5	145.4	722.6	155.7	
30	208.3	170.5	828.2		
35	254.7	107.0	964.3		

Table B1 (contd)

SAND STORM NO. 29

DATE: 10 Sept 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	6.2	7.2	28.7		
1	26.8	15.4	78.1		
2	35.3	21.8	139.9		
3	47.8	25.4	160.5		
4	55.3	32.4	183.8		
5	60.4	38.5	207.6		
6	63.7	45.2	230.0		
7	67.4	54.1	260.7		
8	71.1	64.3	307.5		
9	79.4	82.8	328.3		
10	87.8	84.7	352.9		
11	94.4	102.6	376.6		
12	102.5	98.8	406.4		
13	108.8	114.4	440.4		
14	120.3	120.0	474.4		
15	125.7	130.0	506.1		
16	124.3	144.5	539.7		
17	130.5	155.9	563.2		
18	139.3	170.8	600.2		
19	148.6	179.8	632.8		
20	152.0	193.3	665.5		
25	181.2	227.9	812.2		

Table B1 (contd)

SAND STORM NO. 30

DATE: 11 Sept 1963

TIME (seconds)	POSITION OF TOF			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	2.6	5.5	21.1		
1	23.5	24.6	88.4		
2	34.0	35.2	106.8		
3	38.1	47.7	143.5		
4	41.9	56.2	174.2		
5	48.2	63.7	194.7		
6	59.0	72.5	213.2		
7	68.1	77.4	226.9		
8	77.0	86.7	238.1		
9	64.3	94.2	248.5		
10	68.1	100.9	261.7		
11	67.5	107.9	279.7		
12	72.6	113.3	297.4		
13	77.0	121.6	311.2		
14	81.0	129.9	327.6		
15	81.0	140.0	350.7		
16	85.6	145.0	367.1		
17	93.2	145.0	377.8		
18	100.8	165.0	398.9		
19	106.1	170.5	412.3		
20	111.9	181.8	424.9		
25	134.6	209.0	494.8		
30	162.8	240.0	559.7		
35	193.2	301.5	620.4		
40	218.9	335.1	666.0		
45	235.8	367.5	725.0		
50	254.3	409.3	807.8		
55	273.8	452.9	871.3		
60	293.6	497.8	937.7		
65	312.0	534.3	1004.2		
70	327.3	558.9	1082.2		
75	339.3	585.6	1159.6		

Table B1 (contd)

SAND STORM NO. 31

DATE: 12 Sept 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	5.3	6.8	25.9	6.4	
1	21.7	19.4	84.3	37.5	
2	29.2	40.8	146.3	55.5	
3	38.5	50.8	184.2	68.1	
4	48.2	67.7	224.6	81.3	
5	57.0	78.4	250.7	94.7	
6	66.4	88.5	276.0	103.3	
7	71.0	102.0	309.5	111.9	
8	77.2	112.9	337.7	126.5	
9	84.9	127.2	366.2	129.7	
10	89.0	173.8	385.5	138.2	
11	96.4	175.1	421.6	139.0	
12	102.9	188.5	451.9	144.1	
13	110.5	210.9	482.8	150.9	
14	119.5	232.7	513.3	160.5	
15	126.2	254.7	548.0	169.1	
16	135.7	285.9	617.1	181.5	
17	135.5	288.6	609.8	184.9	
18	141.9	313.1	642.7	200.4	
19	147.3	329.1	632.5	210.1	
20	149.3	347.6	706.4	222.4	
25	166.0	435.3	866.7		
30	177.8	498.9	1042.3		
35	196.3	628.2	1180.3		
40	219.8	734.6	1338.9		

Table B1 (contd)

SAND STORM NO. 32

DATE: 16 Sept 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	12.0	8.0	37.3		
1	25.0	22.6	88.3		
2	32.0	37.9	142.1		
3	39.2	45.4	175.5		
4	47.0	54.0	205.3		
5	51.4	65.5	239.9		
6	58.2	76.1	267.5		
7	65.4	84.3	297.6		
8	70.2	88.8	319.0		
9	75.0	98.9	342.8		
10	79.3	111.7	378.2		
11	85.3	121.8	404.1		
12	93.6	135.9	432.2		
13	99.0	145.6	457.3		
14	104.4	153.0	474.9		
15	111.2	167.9	505.0		
16	117.0	180.5	530.1		
17	122.2	192.7	554.5		
18	127.7	203.1	589.2		
19	133.6	213.9	611.3		
20	139.5	222.1	639.0		
25	175.9	283.4	771.3		
30	198.6	327.5	898.1		
35	230.8	382.7	1048.2		
40	245.6	422.4	1181.1		
42	246.6	449.1	1234.9		

Table B1 (contd)

SAND STORM NO. 34

DATE: 9 Oct 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	17.0	18.8	76.5	29.4	23.5
1	32.3	26.8	103.2	42.3	33.6
2	33.5	34.2	143.7	65.5	60.6
3	39.1	39.2	151.3	69.8	78.0
5	48.4	47.6	192.6	81.6	111.3
6	54.3	62.2	228.1	90.6	
7	61.5	66.1	251.1		127.4
8	65.0	66.7	275.7	96.3	
9	69.5	73.9	297.2	102.8	133.4
10	77.3	78.9	310.2		139.1
11	83.0	82.0	327.2		151.5
12	92.4	89.2	347.4		
13	99.5	90.7	366.3		
14	107.4	97.0	383.6		
15	115.7	105.2	396.3		
16	124.8	111.0	416.5		
17	132.4	116.3	432.5		
18	140.8	122.7	448.9		
19	148.7	131.2	468.9		
20	157.4	134.4	485.7		
25	210.2	159.1	585.5		
30	255.5	161.2	670.6		
35	293.1	190.1	762.1		
40	332.9	216.2	852.9		
45	368.2	252.4	958.7		
50	397.1	268.0	1008.7		
60	468.8	330.7	1229.2		
65	504.6	342.2	1261.6		
70	558.9	359.6	1365.3		
73	596.0	382.1	1418.9		

Tabl B1 (cont.)

SAND STORM NO. 37

DATE: 22 Oct 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	15.4	10.3	32.7		38.3
1	22.8	30.1	98.5		108.6
2	30.2	46.1	151.0		151.4
3	37.9	54.4	177.2		182.1
5	51.4	58.6	234.7		252.1
6	62.6	60.9	243.9		289.3
7	71.9	75.0	292.5		320.6
8	69.8	88.0	331.3		329.7
9	75.4	102.7	345.2		339.2
10	82.8	109.2	367.0		
11	89.4	76.8	383.3		
12	92.9	78.0	407.2		
13	99.5	82.9	439.9		
14	106.6	94.6	463.2		
15	114.9	94.7	458.2		
16	125.6	100.0	491.3		
17	130.5	107.5	534.9		
18	112.9	144.1	538.4		
19	114.7	152.0	566.3		
20	123.4	158.2	574.7		
25	151.8	177.2	696.5		
29	180.5	207.8	792.6		

TABLE 10 (Cont.)

SAND STORM NO. 39

DATE: 23 Oct 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
1	44.9	50.3	183.3	77.0	
2	36.5	57.6	216.1	96.1	
3	42.7	66.7	249.6	108.2	
4	58.2	75.7	285.1	112.6	
5	45.0	89.8	317.0	117.1	
6	65.0	103.7	348.0	120.4	
7	72.9	112.8	380.8	126.5	
8	81.1	131.9	412.4	132.0	
9	87.3	142.7	442.4	139.5	
10	93.2	156.9	472.2	151.6	
11	99.6	166.6	501.2	156.2	
12	106.4	183.0	532.5	168.1	
13	111.4	198.5	563.0	175.5	
14	116.1	211.8	591.9	179.6	
15	118.8	225.3	623.2	175.1	
16	125.4	236.5	650.5	177.0	
17	127.9	244.6	684.5	178.0	
18	130.4	255.9	711.8		
19	132.9	262.7	752.9		
20	137.3	271.7	781.4	188.2	
25	146.7	340.4	938.2	222.5	
30	160.0	398.3	1105.6	252.0	
35	168.4	463.8	1258.0		
40	180.0	525.5	1394.0		

Table B1 (contd)

SAND STORM NO. 39

DATE: 29 Oct 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	13.8	6.6	28.7	23.1	21.5
1	20.9	10.9	77.2	40.9	35.3
2	21.8	19.8	104.9	49.0	63.8
3	27.7	25.2	149.0	58.3	71.8
4	37.2	35.9	165.2	61.8	81.2
5	44.8	36.7	180.1	66.4	76.9
6	49.7	39.0	188.0	70.5	102.4
7	56.8	42.9	198.0	74.2	108.6
8	60.9	45.0	210.4	80.7	114.6
9	66.2	47.8	223.1	81.5	121.4
10	70.7	50.4	233.3	86.2	142.0
11	75.5	52.5	244.1	90.4	151.9
12	78.2	53.7	264.1		164.1
13	75.6	60.0	268.9		166.5
14	78.7	55.4	280.5		173.9
15	85.2	59.5	292.5		181.0
16	91.1	64.3	317.1		184.6
17	96.3	69.7	354.3		184.7
18	101.5	71.1	372.8		191.5
19	105.9	69.5	385.2		
20	111.1	70.5	396.8		195.2
25	133.9	64.8	499.6		
30	162.0	80.2	579.4		
35	184.2	82.2	661.9		
40	207.5	91.6	738.2		
45	226.3	67.8	804.3		
50	248.5	49.9	870.3		
55	275.6	72.3	929.9		
60	298.0	62.1	999.5		
65	322.4	65.5	1079.7		
69	342.6	43.8	1125.3		

Table B1 (contd)

SAND STORM NO. 40

DATE: 30 Oct 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	10.7	7.7	44.1	17.5	
1	19.2	19.4	98.0	29.5	
2	30.7	33.8	128.2	42.6	
3	37.1	43.5	164.4	49.6	
4	44.7	52.5	195.0	54.5	
5	49.6	56.2	223.4	56.0	
6	54.5	61.1	252.1		
7	56.5	72.2	278.3	63.3	
8	59.6	79.7	306.7	69.5	
9	66.4	84.1	327.6		
10	70.2	82.7	353.0	73.4	
11					
12					
13	81.6	90.7	430.5	78.6	
14	89.0	97.6	457.8		
15	95.8	97.2	484.7	82.7	
16	101.9	103.1	512.4		
17	105.3	108.7	541.4		
18	113.7	117.4	569.2	85.4	
19					
20	118.9	131.2	617.6	89.1	
25					
29	151.3	207.1	889.6	99.6	

Table B1 (contd)

SAND STORM NO. 41

DATE: 4 Nov 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	24.0	20.8	80.0	27.8	
1	25.3	34.8	130.6	44.7	
2	30.9	49.0	177.8	53.3	
3	37.4	57.7	218.5	59.0	
4	41.3	63.8	256.2	74.6	
5	45.6	69.6	288.7	81.8	
6	48.7	71.0	296.9	94.9	
7	53.0	73.4	329.0	98.5	
8	57.2	81.0	358.5	105.0	
9	58.1	84.4	393.5	119.7	
10	66.2	93.1	424.8		
11	70.5	101.2	458.3	131.1	
12	76.1	103.7	485.6	133.7	
13	80.3	103.7	510.6	135.1	
14	87.3	108.0	538.1	139.1	
15	92.6	117.4	566.1		
16	97.1	122.7	598.7	140.5	
17	101.7	126.6	630.1		
18	107.7	130.5	654.7		
19	113.3	133.4	689.7		
20	120.8	140.9	719.6		
25	145.6	139.7	878.4		
30	153.6	159.7	1051.1		
35	166.8	148.0	1211.4		
40	173.9	160.1	1377.9		
45	181.1	169.4	1541.8		
50	191.7	179.4	1713.6		
52	198.7	182.7	1768.3		

Table B1 (contd)

SAND STORM NO. 42

DATE: 5 Nov 1963

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	13.6	10.9	40.0	18.8	
1	24.4	21.1	92.4	39.1	
2	34.4	26.9	119.6	53.1	
3	45.7	44.5	167.5	68.6	
4	42.1	54.8	217.9	76.3	
5	55.2	55.4	249.4	89.0	
6	78.2	58.5	279.8	96.4	
7	72.6	62.2	294.8	110.6	
9	81.9	66.6	362.0	126.7	
10	90.5	70.8	385.2		
11	98.3	68.7	425.0	134.5	
12	103.9	73.9	455.0	144.6	
13	112.0	82.4	493.1	147.1	
14	119.4	98.9	541.9	159.4	
15	125.0	93.1	579.1	166.4	
16	127.3	91.5	607.7	167.0	
17	132.7	95.0	644.0	168.5	
18	140.7	90.9	670.7		
19	150.8	97.4	713.3	179.9	
20	151.9	106.5	747.6		
25	181.1	133.9	957.1	185.7	
30	210.1	143.9	1144.0		
35	223.4	162.6	1347.7		
40	248.9	161.1	1481.5		
43	265.4	177.3	1611.8		

Table B1 (contd)

SAND STORM NO. 43

DATE: 7 Nov 63

TIME (seconds)	POSITION OF TOP			WIDTH (feet)	LENGTH (feet)
	Z	Y	X		
	(feet)	(feet)	(feet)		
0	17.4	10.7	42.6	19.1	
1	27.1	21.0	89.4	34.9	
2	34.0	27.7	128.5		
3	44.2	26.1	148.4	47.9	
4	55.6	29.5	165.6	54.2	
5	65.3	36.4	194.2	63.4	
6	74.4	41.3	228.5	70.1	
7	82.2	46.6	253.8	78.9	
8	90.3	46.5	277.2	86.7	
9	96.8	56.6	305.6	92.3	
10	103.7	57.5	325.6	101.0	
11	108.5	60.7	346.3	111.3	
12	113.8	65.7	373.0	122.6	
13	116.6	73.4	395.4	133.8	
14	119.8	74.9	428.1	147.0	
15	123.4	75.7	452.1	153.3	
16	128.9	81.1	482.7	157.4	
17	129.9	85.7	503.2	160.5	
18	136.6	95.1	540.4	164.8	
19	141.8	102.2	565.3	175.7	
20	144.6	114.3	597.4	187.0	
25	169.8	137.3	715.3	221.0	
30	195.3	149.4	819.5	260.2	
35	213.3	171.4	946.5	304.7	
40	238.3	209.3	1071.9	338.7	

Appendix C

Variance of Wind Direction Fluctuations

The tabulations contained in this appendix show the variances of wind azimuth fluctuations for various smoothing and sampling intervals. The mathematical filters used to obtain the data are explained in Chapter VI of the report. The instrumentation used to collect the data is described in Chapter IV. The variances, shown in units of degrees squared, are computed from 10 minutes of record beginning 3 minutes before firing. The wind direction and speed are mean values for the same period and are in units of degrees true azimuth and meters per second.

Table C1. Variance of Wind Direction Fluctuations

$\sigma^2(\theta)_{T, \theta}$
(degrees)

SAND STORM NO. 2
DATE 27 Mar 1963
TIME 1130 PST

		12 Feet				50 Feet									
		T (sec)				T (sec)									
s	(sec)	16	32	64	128	256	512	s	(sec)	16	32	64	128	256	512
1	1	24.5	30.6	38.6	48.7	49.6	64.6	1	1						
2	2	20.1	26.5	34.6	44.8	45.8	60.7	2	2						
4	4	13.3	20.4	28.7	39.0	40.2	54.9	4	4						
8	8	4.7	12.5	21.2	31.9	33.2	47.6	8	8						
16	16	0	3.7	12.3	23.6	25.0	39.1	16	16						
M I S S I N G															

M I S S I N G

MEAN DIRECTION AND SPEED 226/10.3

100 Feet						200 Feet											
		T (sec)				T (sec)											
s	(sec)	16	32	64	128	256	512	s	(sec)	16	32	64	128	256	512		
1	1	9.1	13.5	18.4	25.1	26.4	40.0	1	1	5.0	8.2	12.0	15.9	18.6	33.4		
2	2	8.1	12.7	17.6	24.4	25.7	39.3	2	2	4.5	7.8	11.6	15.5	18.3	33.1		
4	4	5.9	10.7	15.8	22.7	24.1	37.6	4	4	3.3	6.8	10.7	14.8	17.6	32.3		
8	8	2.2	7.2	12.5	19.5	21.0	34.6	8	8	1.3	4.8	8.9	13.2	16.2	30.6		
16	16	0	2.4	7.8	15.1	17.0	30.1	16	16	0	1.7	5.8	10.4	13.7	27.6		
												MEAN DIRECTION AND SPEED				253/11.7	

MEAN DIRECTION AND SPEED 253/11.7

$$\sigma^2(\theta)_{T,s}$$
(degrees)

SAND STORM NO. 3
DATE 8 Apr 1963
TIME 1040 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	15.5	20.2	27.1	37.0	46.5	46.3	1	13.0	18.1	24.4	32.2	39.8	39.5
2	12.7	17.6	24.5	34.5	44.0	44.0	2	11.0	16.3	22.7	30.6	38.3	38.0
4	8.5	13.7	20.8	30.8	40.6	40.7	4	7.6	13.2	19.9	28.0	36.0	35.5
8	2.9	8.4	15.6	25.8	36.2	36.3	8	2.7	8.5	15.5	23.9	32.2	31.9
16	0	2.7	9.7	20.2	31.4	31.7	16	0	2.7	9.6	18.3	27.1	27.2
MEAN DIRECTION AND SPEED 277/11.0													
100 Feet							200 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	10.2	14.2	19.4	27.7	35.1	35.3	1	5.3	8.8	12.8	18.4	23.4	25.1
2	8.7	12.8	18.1	26.4	33.9	34.2	2	4.7	8.2	12.4	18.0	23.0	24.7
4	6.0	10.3	15.6	24.1	31.9	32.1	4	3.4	7.1	11.4	17.1	22.3	24.0
8	2.1	6.5	11.9	20.7	29.1	29.2	8	1.3	4.9	9.4	15.3	20.8	22.5
16	0	2.1	7.4	16.4	25.9	25.9	16	0	1.8	6.3	12.5	18.5	20.1
MEAN DIRECTION AND SPEED 274/12.6													
MEAN DIRECTION AND SPEED 265/13.5													

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 4
DATE 19 Apr 1963
TIME 1314 PST

12 Feet									
T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	19.2	28.8	40.4	53.8	64.6	80.3	1	12.5	19.2
2	16.1	26.0	37.8	51.2	62.2	77.9	2	10.6	17.5
4	11.1	21.3	33.6	47.1	58.3	74.3	4	7.4	14.5
8	3.9	13.9	27.0	40.8	52.3	68.8	8	2.8	9.8
16	0	5.1	18.2	32.5	44.4	62.0	16	0	3.5

MEAN DIRECTION AND SPEED 253/13.7

100 Feet									
T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	11.6	19.2	27.9	36.4	48.6	61.3	1	6.2	10.7
2	10.0	17.6	26.5	35.1	47.2	60.2	2	5.4	9.9
4	7.0	14.8	24.1	32.7	44.8	58.2	4	3.9	8.5
8	2.7	10.1	20.1	28.8	40.8	55.0	8	1.6	6.0
16	0	3.7	13.9	23.0	34.9	50.2	16	0	2.2

MEAN DIRECTION AND SPEED 248/14.8

50 Feet									
T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	12.5	19.2	26.0	31.0	39.6	60.5	1	6.2	10.7
2	10.6	17.5	24.5	29.6	38.1	59.1	2	5.4	9.9
4	7.4	14.5	22.0	27.1	35.6	56.8	4	3.9	8.5
8	2.8	9.8	18.1	23.5	32.0	53.5	8	1.6	6.0
16	0	3.5	12.2	18.1	26.7	48.6	16	0	2.2

MEAN DIRECTION AND SPEED 264/17.2

$$\sigma^2(\theta)_{T,u}$$
(degrees)

SAND STORM NO. 5

DATE 24 Apr 1963

TIME 1531 PST

12 Feet					50 Feet								
T (sec)					T (sec)								
θ (sec)	16	32	64	128	256	512	θ (sec)	16	32	64	128	256	512
1	24.7	33.2	48.6	68.0	74.5	101.2	1	13.5	22.2	39.1	60.9	65.8	88.9
2	20.6	29.1	44.6	64.4	71.2	97.8	2	11.5	20.2	37.1	59.3	64.3	87.4
4	13.9	22.6	38.2	58.9	66.2	92.5	4	8.1	16.9	33.7	56.5	62.0	85.1
8	8.5	13.2	28.7	50.8	59.1	85.0	8	3.1	11.5	28.1	52.0	58.7	81.3
16	5.0	8.4	18.6	35.3	52.1	77.9	16	0	4.2	15.4	44.8	53.6	75.4

MEAN DIRECTION AND SPEED 253/5.9

100 Feet				200 Feet			
T (sec)				T (sec)			
s	16	32	64	128	256	512	128
(sec)							
1	8.4	16.3	32.1	54.3	56.9	74.8	48.8
2	7.3	15.2	31.0	53.4	56.3	74.1	47.7
4	5.4	13.2	29.0	51.8	55.2	73.0	45.4
8	2.2	9.4	25.0	48.6	53.0	70.8	41.5
16	0	3.6	17.8	42.2	48.8	66.4	35.7
MEAN DIRECTION AND SPEED				MEAN DIRECTION AND SPEED			
269/9.5				265/9.8			

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 6
DATE 6 May 1963
TIME 1420 PST

		12 Feet				50 Feet			
		T (sec)				T (sec)			
s	(sec)	16	32	64	128	256	512	s	(sec)
1	42.4	60.1	82.1	123.8	169.9	270.2		1	
2	33.9	52.1	74.3	115.3	163.2	262.9		2	
4	23.1	42.0	64.7	107.1	155.3	254.2		4	
8	8.2	27.1	50.7	93.3	144.0	241.5		8	
16	0	3.4	33.0	75.3	130.6	225.2		16	

MISSING

MEAN DIRECTION AND SPEED 246/3.9

		100 Feet				200 Feet			
		T (sec)				T (sec)			
s	(sec)	16	32	64	128	256	512	s	(sec)
1	24.5	39.4	59.8	91.7	133.5	241.7		1	
2	21.1	36.2	56.8	88.8	130.7	238.8		2	
4	15.0	30.5	51.4	83.5	125.7	233.5		4	
8	5.6	20.8	42.1	74.3	117.3	224.3		8	
16	0	7.6	23.4	60.9	105.5	210.4		16	

MEAN DIRECTION AND SPEED 256/5.9

MEAN DIRECTION AND SPEED 236/7.2

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 7
DATE 8 May 1963
TIME 0939 PST

		12 Feet					50 Feet								
		T (sec)					T (sec)								
s	(sec)	16	32	64	128	256	512	s	(sec)	16	32	64	128	256	512
1	22.3	28.3	33.7	37.4	40.1	38.5	35.3	1	15.4	20.3	25.4	31.0	37.4	35.3	35.3
2	18.3	24.6	30.2	34.1	36.5	35.2	33.6	2	13.2	18.3	23.6	29.3	35.8	33.6	33.6
4	12.3	19.1	25.3	29.3	32.1	30.5	30.7	4	9.0	14.6	20.3	26.2	32.7	30.7	30.7
8	4.1	11.5	18.6	23.0	26.1	24.5	26.4	8	3.2	9.2	15.4	21.6	28.4	26.4	26.4
16	0	3.7	11.6	16.6	20.0	18.6	21.3	16	0	2.9	9.4	15.8	23.1	21.3	21.3

MEAN DIRECTION AND SPEED 253/7.6

		100 Feet					200 Feet											
		T (sec)					T (sec)											
s	(sec)	16	32	64	128	256	512	s	(sec)	16	32	64	128	256	512			
1	18.2	22.0	26.4	32.1	40.5	36.9	32.9	1	14.1	9.2	14.1	19.2	21.4	25.3	22.9			
2	15.0	20.0	24.6	30.4	38.8	35.2	32.1	2	13.2	8.1	13.2	17.3	20.7	24.5	22.1			
4	11.6	16.2	21.0	27.1	35.4	31.9	29.7	4	11.2	5.3	11.2	5.7	19.1	22.8	20.7			
8	4.2	9.8	14.8	21.1	29.1	26.1	26.1	8	7.5	2.2	7.5	12.7	16.2	19.7	17.9			
16	0	2.4	7.5	13.8	21.3	19.5	19.5	16	2.7	0	2.7	8.2	11.9	15.0	13.1			
		MEAN DIRECTION AND SPEED					244/13.4						MEAN DIRECTION AND SPEED					246/15.7

MEAN DIRECTION AND SPEED 246/15.7

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 8
DATE 22 May 1963
TIME 1332 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	37.3	55.4	82.7	126.8	189.5	332.6	1	39.1	65.9	100.3	155.0	200.7	341.0
2	30.8	49.3	77.0	121.3	184.5	327.3	2	33.8	61.2	95.9	150.6	196.3	336.8
4	21.4	40.6	68.8	113.5	177.2	320.0	4	24.6	53.2	88.4	143.0	188.9	329.7
8	8.2	27.5	56.7	102.0	166.7	309.4	8	10.2	38.6	74.7	129.3	175.7	316.6
16	0	9.9	38.2	84.6	151.2	293.1	16	0	14.0	49.7	104.2	152.8	291.7

MEAN DIRECTION AND SPEED 250/6.6

100 Feet							200 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	22.2	35.6	51.1	76.1	118.6	221.6	1	13.2	20.6	29.2	40.5	62.3	138.5
2	19.6	33.2	49.0	74.0	116.6	219.8	2	11.6	19.1	27.8	39.2	61.0	137.3
4	14.2	28.4	44.7	69.7	112.4	216.0	4	8.4	16.0	25.2	36.6	58.5	134.8
8	5.6	19.6	36.9	61.7	104.6	208.9	8	3.2	10.6	20.5	31.8	53.9	130.2
16							16	0	3.7	13.8	24.8	47.1	123.5

MEAN DIRECTION AND SPEED 265/7.6

MEAN DIRECTION AND SPEED 243/10.6

$$\sigma^2(\theta)_{T,s}$$

 (degrees)

SAND STORM NO. 9
DATE 23 May 1963
TIME 1311 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	20.3	26.3	33.9	39.5	45.9	47.9	1	11.2	14.8	18.6	19.9	22.3	23.9
2	16.0	22.3	30.2	35.9	42.3	44.3	2	9.3	13.2	17.1	18.5	20.9	22.5
4	10.3	17.0	25.2	31.1	37.5	39.6	4	6.5	10.5	14.8	16.4	18.8	20.3
8	3.5	10.6	19.2	25.7	32.2	34.3	8	2.2	6.5	11.3	13.2	15.6	17.1
16	0	3.5	12.2	19.9	26.6	28.6	16	0	2.1	7.2	9.8	12.4	13.5

MEAN DIRECTION AND SPEED 267/9.1

100 Feet				200 Feet			
T (sec)				T (sec)			
s	16	32	64	128	256	512	1024
1	11.1	15.0	19.0	18.7	17.0	21.7	20.1
2	9.4	13.4	17.6	17.5	15.9	20.4	18.8
4	6.5	10.8	15.3	15.7	14.1	18.4	16.9
8	2.4	7.0	11.9	13.1	11.5	15.5	14.3
16	0	2.3	7.5	9.8	8.4	11.9	11.2
MEAN DIRECTION AND SPEED				MEAN DIRECTION AND SPEED			
272/13.6				270/16.0			

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 10
DATE 29 May 1963
TIME 1352 PST

12 Feet										50 Feet																													
T (sec)										T (sec)																													
s	16	32	64	128	256	512	s	16	32	64	128	256	512	s	16	32	64	128	256	512																			
(sec)							(sec)							(sec)																									
1	31.0	47.2	67.0	88.0	94.6	105.9	1	24.6	31.3	41.5	55.3	57.6	70.7	1	24.6	31.3	41.5	55.3	57.6	70.7																			
2	26.5	43.7	64.1	85.5	92.3	103.5	2	20.9	28.1	38.6	52.9	55.6	68.4	2	20.9	28.1	38.6	52.9	55.6	68.4																			
4	19.2	37.7	58.9	81.1	88.4	99.5	4	14.6	22.7	33.7	48.9	52.1	64.5	4	14.6	22.7	33.7	48.9	52.1	64.5																			
8	7.6	26.6	49.3	72.7	80.8	92.2	8	5.3	14.5	26.2	42.7	46.9	58.8	8	5.3	14.5	26.2	42.7	46.9	58.8																			
16	0	9.4	32.6	57.4	67.2	79.2	16	0	4.5	16.6	34.3	39.8	51.9	16	0	4.5	16.6	34.3	39.8	51.9																			
MEAN DIRECTION AND SPEED										251/6.2																													
100 Feet										200 Feet																													
T (sec)										T (sec)																													
s	16	32	64	128	256	512	s	16	32	64	128	256	512	s	16	32	64	128	256	512																			
(sec)							(sec)							(sec)																									
1	26.2	37.9	45.3	54.1	69.5	82.0	1	25.9	35.6	48.7	64.6	89.0	110.1	1	25.9	35.6	48.7	64.6	89.0	110.1																			
2	22.4	34.7	42.6	51.3	66.8	79.5	2	22.2	32.2	45.5	61.5	85.8	107.3	2	22.2	32.2	45.5	61.5	85.8	107.3																			
4	15.8	29.1	38.1	46.6	62.1	75.2	4	15.8	26.5	40.0	56.1	80.5	102.5	4	15.8	26.5	40.0	56.1	80.5	102.5																			
8	6.0	19.9	30.5	39.0	54.8	68.3	8	5.8	17.0	31.0	47.2	71.6	94.7	8	5.8	17.0	31.0	47.2	71.6	94.7																			
16	0	6.8	18.8	27.7	43.9	58.0	16	0	5.4	19.0	35.6	60.0	85.0	16	0	5.4	19.0	35.6	60.0	85.0																			
MEAN DIRECTION AND SPEED										267/6.4										MEAN DIRECTION AND SPEED										257/missing									

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 11

DATE 10 June 1963

TIME 0914 PST

		12 Feet				50 Feet			
		T (sec)				T (sec)			
s	(sec)	16	32	64	128	256	512	s	(sec)
1	11.1	15.8	20.4	24.7	30.0	30.3	30.3	1	15.3
2	9.4	14.3	19.0	23.3	28.6	29.0	29.0	2	12.8
4	6.5	11.8	16.8	21.1	26.4	26.9	26.9	4	8.8
8	2.4	7.9	13.3	17.7	23.0	23.8	23.8	8	3.2
16	0	2.7	8.3	13.0	18.3	19.5	19.5	16	0

MEAN DIRECTION AND SPEED 234/12.5

		100 Feet				200 Feet			
		T (sec)				T (sec)			
s	(sec)	16	32	64	128	256	512	s	(sec)
1	11.1	15.1	18.1	21.1	27.1	29.7	29.7	1	6.1
2	9.5	13.7	16.8	19.9	25.9	28.5	28.5	2	5.2
4	6.6	11.3	14.5	17.8	23.8	26.4	26.4	4	3.5
8	2.4	7.3	11.0	14.5	20.5	23.1	23.1	8	1.2
16	0	2.4	6.4	10.2	16.0	19.0	19.0	16	0

MEAN DIRECTION AND SPEED 255/14.2

Table C1 (contd)

$$\sigma^2(\theta)_{T,0}$$

SAND STORM NO. 13
DATE 14 June 1963
TIME 1057 PST

12 Feet				50 Feet			
T (sec)				T (sec)			
s	16	32	64	128	256	512	s
(sec)							(sec)
1	69.9	122.3	208.1	264.8	305.2	316.8	1
2	58.5	111.2	197.9	255.7	295.1	308.0	2
4	40.3	93.1	181.2	241.6	279.3	294.4	4
8	16.3	65.8	155.4	221.6	258.0	274.6	8
16	0	25.5	110.5	187.2	223.8	240.2	16

MEAN DIRECTION AND SPEED 275/2.9

100 Feet				200 Feet			
T (sec)				T (sec)			
s	16	32	64	128	256	512	1024
1	54.6	80.9	110.1	132.5	155.2	181.0	207.5
2	45.0	71.9	101.9	124.3	145.9	173.1	198.5
4	32.5	60.5	92.0	114.8	135.6	163.7	187.8
8	12.7	40.9	74.6	98.5	118.2	147.5	172.1
16	0	13.7	47.7	74.1	92.5	122.5	146.0

MEAN DIRECTION AND SPEED 295/3.4

MEAN DIRECTION AND SPEED 283/4.0

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 14
DATE 19 June 1963
TIME 1018 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	26.1	46.5	84.5	155.3	173.1	216.8	1	15.5	28.1	53.0	104.4	112.5	147.5
2	22.3	42.8	80.9	152.0	170.3	214.1	2	13.5	26.1	51.0	102.5	111.1	146.0
4	15.9	36.3	74.6	146.1	165.4	209.4	4	9.8	22.4	47.1	98.9	108.4	143.1
8	6.2	25.3	63.4	135.7	157.2	201.2	8	3.9	15.7	40.0	92.2	103.7	137.8
16	0	9.7	45.1	117.7	144.1	187.2	16	0	6.0	28.1	80.0	96.0	128.0

MEAN DIRECTION AND SPEED 275/5.3

100 Feet							200 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	15.9	24.5	52.9	106.9	110.6	153.4	1	10.6	18.3	32.8	59.4	64.9	97.1
2	14.1	24.6	50.9	105.1	109.3	152.0	2	9.2	17.0	31.5	58.2	63.9	95.9
4	10.5	21.1	47.1	101.8	107.1	149.2	4	6.6	14.5	29.0	55.9	62.1	93.8
8	4.1	14.3	39.4	94.7	102.4	143.4	8	2.6	10.1	24.6	51.9	58.9	90.0
16	0	5.0	27.0	82.2	94.6	133.1	16	0	3.7	17.2	44.6	53.9	83.1
MEAN DIRECTION AND SPEED							MEAN DIRECTION AND SPEED						
285/5.3							275/5.6						

MEAN DIRECTION AND SPEED 285/5.3

MEAN DIRECTION AND SPEED 275/5.6

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 16

DATE 9 July 1963

TIME 0950 PST

12 Feet					50 Feet				
T (sec)					T (sec)				
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	44.9	82.4	134.0	205.0	254.2	281.4	1	34.1	50.0
2	38.8	76.7	128.9	201.4	250.2	277.9	2	29.5	46.1
4	28.2	66.3	119.8	193.1	243.4	272.0	4	21.5	39.4
8	11.7	47.7	103.1	178.1	231.5	261.5	8	8.7	27.4
16	0	18.6	72.7	150.7	209.7	242.7	16	0	9.2

MEAN DIRECTION AND SPEED 270/4.5

100 Feet					200 Feet				
T (sec)					T (sec)				
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	23.8	35.3	51.0	70.6	96.0	136.2	1	14.7	26.8
2	20.4	32.0	48.2	67.9	93.2	133.8	2	12.9	25.2
4	14.5	26.4	43.4	63.3	88.7	129.9	4	9.5	22.1
8	5.3	17.1	35.4	55.8	81.6	123.7	8	3.9	16.0
16	0	6.3	24.4	45.5	72.0	115.8	16	0	6.2

MEAN DIRECTION AND SPEED 284/5.6

MEAN DIRECTION AND SPEED 293/6.1

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 17
DATE 11 July 1963
TIME 0933 PST

12 Feet					50 Feet				
T (sec)					T (sec)				
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	32.9	51.4	87.6	129.5	153.1	153.9	1	22.8	35.9
2	28.9	47.7	84.0	126.6	150.8	151.0	2	18.9	32.0
4	21.4	40.8	77.4	121.3	146.5	145.9	4	12.5	25.5
8	8.4	27.8	64.5	111.0	138.0	136.1	8	4.3	16.4
16	0	9.5	44.0	94.2	124.9	121.0	16	0	6.3
MEAN DIRECTION AND SPEED					267/5.4				

100 Feet					200 Feet				
T (sec)					T (sec)				
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	23.7	38.8	62.3	79.8	87.0	96.9	1		
2	20.7	36.2	59.9	77.9	85.3	94.8	2		
4	14.8	30.9	55.1	74.0	81.7	90.4	4		
8	5.9	21.9	46.7	66.8	74.8	82.7	8		
16	0	8.0	32.0	54.5	63.0	69.5	16		
MEAN DIRECTION AND SPEED					278/6.6				

MISSING

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 18

DATE 15 Jul 1963

TIME 1030 PST

12 Feet									
T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	27.9	40.1	53.7	68.5	100.8	145.4	1	21.5	29.5
2	24.1	36.7	50.7	65.5	97.8	142.8	2	17.6	26.0
4	17.2	30.7	45.3	60.1	92.4	138.3	4	11.9	20.9
8	6.6	20.8	36.6	51.5	83.4	131.3	8	4.2	13.5
16	0	5.8	23.2	38.6	69.7	121.1	16	0	4.5
MEAN DIRECTION AND SPEED 262/8.7									

100 Feet										200 Feet						
T (sec)										T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512			
(sec)							(sec)									
1	13.3	19.9	27.7	40.4	72.3	112.8	1									
2	11.5	18.4	26.3	39.1	71.0	111.8	2									
4	8.3	15.7	22.9	36.8	68.7	110.1	4									
8	3.3	11.1	19.8	32.8	64.8	107.5	8									
16	0	3.9	12.7	25.9	57.5	103.1	16									
MEAN DIRECTION AND SPEED										MISSING					MEAN DIRECTION AND SPEED	
275/10.0																

MEAN DIRECTION AND SPEED

50 Feet

T (sec)

s

(sec)

16

32

64

128

256

512

200 Feet

T (sec)

s

(sec)

16

32

64

128

256

512

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 13
DATE 17 JULY 1963
TIME 0936 PST

12 Feet										50 Feet										
T (sec)										T (sec)										
s	16	32	64	128	256	512	s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)							(sec)						
1	15.9	23.7	29.7	35.3	39.1	37.9	1	13.7	20.4	27.1	35.5	40.2	39.0	1	13.7	20.4	27.1	35.5	40.2	39.0
2	13.6	21.7	28.0	33.6	37.5	36.3	2	11.7	18.6	25.5	33.9	38.6	37.5	2	11.7	18.6	25.5	33.9	38.6	37.5
4	9.5	18.1	24.8	30.5	34.4	33.3	4	8.2	15.3	22.7	31.1	35.9	34.9	4	8.2	15.3	22.7	31.1	35.9	34.9
8	3.6	12.3	20.0	25.9	29.8	28.9	8	3.1	10.2	18.3	26.9	32.0	31.1	8	3.1	10.2	18.3	26.9	32.0	31.1
16	0	4.3	12.9	19.2	23.5	22.6	16	0	2.6	12.4	21.4	27.2	26.2	16	0	2.6	12.4	21.4	27.2	26.2

MEAN DIRECTION AND SPEED 251/12.6

100 Feet										200 Feet										
T (sec)										T (sec)										
s	16	32	64	128	256	512	s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)							(sec)						
1	8.8	14.8	22.2	32.9	38.7	37.3	1	8.2	12.4	17.0	22.6	24.5	25.3	1	8.2	12.4	17.0	22.6	24.5	25.3
2	7.7	13.8	21.4	32.2	38.0	36.6	2	7.1	11.5	16.3	22.0	24.0	24.7	2	7.1	11.5	16.3	22.0	24.0	24.7
4	5.6	11.8	19.8	30.7	36.9	35.5	4	5.2	9.9	14.9	20.8	23.0	23.6	4	5.2	9.9	14.9	20.8	23.0	23.6
8	2.3	8.5	17.1	28.2	34.8	33.5	8	2.0	6.9	12.5	18.8	21.3	21.8	8	2.0	6.9	12.5	18.8	21.3	21.8
16	0	3.2	12.1	23.6	30.3	30.0	16	0	2.5	8.5	15.4	18.3	18.9	16	0	2.5	8.5	15.4	18.3	18.9
MEAN DIRECTION AND SPEED										MEAN DIRECTION AND SPEED										
258/14.6										253/16.1										

MEAN DIRECTION AND SPEED 253/16.1

258/14.6

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 20
DATE 26 July 1963
TIME 1018 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	42.6	65.5	113.0	194.0	315.5	389.2	1	47.8	65.9	94.9	137.4	223.7	314.8
2	36.0	59.2	106.7	188.0	309.8	383.5	2	40.8	59.6	88.8	131.4	218.6	303.7
4	25.9	49.7	97.1	179.0	300.3	375.1	4	29.2	49.3	78.8	121.6	210.3	301.6
8	10.3	34.0	80.7	163.4	283.6	361.0	8	10.7	31.8	61.5	104.5	196.0	287.9
16	0	11.8	54.1	137.8	255.9	338.5	16	0	10.1	38.1	79.9	174.6	264.8

MEAN DIRECTION AND SPEED 280/3.9

100 Feet					200 Feet								
T (sec)					T (sec)								
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1							1	23.9	36.8	50.0	84.6	98.4	99.0
2							2	20.2	33.3	46.9	61.5	95.2	96.2
4							4	14.1	27.6	41.7	56.3	89.8	91.7
8							8	5.0	18.1	33.4	47.9	81.1	84.6
16							16	0	5.7	22.7	37.9	70.8	75.3
M I S S I N G													

MEAN DIRECTION AND SPEED

270/3.8

MISSING

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 21
DATE 30 July 1963
TIME 1130 PST

12 Feet										50 Feet									
T (sec)										T (sec)									
s	16	32	64	128	256	512	s	(sec)		s	16	32	64	128	256	512	s	(sec)	
1	20.7	29.3	36.0	41.5	50.5	79.1	1			18.1	25.3	37.2	52.7	67.7	82.7		1		
2	17.7	26.8	33.8	39.5	48.5	76.0	2			15.3	22.6	34.6	50.4	65.5	80.5		2		
4	12.6	22.3	30.0	35.8	45.0	72.4	4			10.6	18.2	30.6	46.9	62.3	77.3		4		
8	4.7	14.9	23.5	29.6	38.9	66.5	8			3.9	11.6	24.3	41.6	57.5	72.6		8		
16	0	4.9	14.5	21.2	30.6	58.5	16			0	3.8	16.0	34.5	51.3	66.9		16		
MEAN DIRECTION AND SPEED										MEAN DIRECTION AND SPEED									
262/7.6										254/9.0									

100 Feet										200 Feet									
T (sec)										T (sec)									
s	16	32	64	128	256	512	s	(sec)		s	16	32	64	128	256	512	s	(sec)	
1	17.8	29.1	48.2	71.2	90.4	96.6	1			18.1	28.3	43.7	59.7	71.2	78.0		1		
2	15.4	26.8	46.0	63.4	88.7	95.1	2			15.4	26.0	41.4	58.0	69.5	76.6		2		
4	11.1	22.8	42.3	56.6	86.1	92.6	4			11.0	21.9	37.6	53.0	66.7	73.9		4		
8	4.4	16.0	35.3	61.5	81.5	88.5	8			4.3	15.3	31.2	50.0	61.9	69.6		8		
16	0	5.8	24.5	52.6	73.6	81.9	16			0	5.4	20.6	41.6	54.2	62.7		16		
MEAN DIRECTION AND SPEED										MEAN DIRECTION AND SPEED									
264/9.4										254/9.0									

$\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 22
DATE 9 August 1963
TIME 1458 PST

12 Feet		50 Feet					
s (sec)	T (sec)						T (sec)
	16	32	64	128	256	512	
1	40.8	62.4	93.9	147.8	198.5	308.3	39.5
2	34.5	56.6	88.9	142.9	194.1	304.3	34.5
4	23.7	46.8	80.2	134.6	186.8	297.8	25.1
8	9.2	31.9	66.9	121.7	175.8	288.0	9.8
16	0	11.7	46.0	101.2	158.6	272.8	0
							11.8
							47.7
							106.9
							175.1
							258.9
							159.6
							155.2
							148.6
							121.1
							220.4
							305.8
							224.5
							512

MEAN DIRECTION AND SPEED 260/4.3

100 Feet						200 Feet						
s (sec)	T (sec)					s (sec)	T (sec)					
	16	32	64	128	256		512	16	32	64	128	256
1	33.3	54.6	90.1	153.6	227.9	297.0	21.4	35.4	55.2	79.1	113.4	134.6
2	29.6	51.4	87.0	150.7	225.1	294.2	17.7	31.8	51.9	75.8	109.7	131.3
4	22.2	44.9	80.7	144.9	219.6	288.5	12.2	26.3	46.9	70.8	104.4	126.4
8	9.1	31.8	67.6	132.4	208.2	276.4	4.5	17.8	39.3	63.5	96.7	119.1
16	0	11.0	44.5	110.0	188.0	254.0	0	6.8	27.9	52.9	85.5	108.3

MEAN DIRECTION AND SPEED 250/5.3

MEAN DIRECTION AND SPEED 259/5.0

$\sigma^2(\theta)_{T,s}$ (degrees)

SAND STORM NO. 23
DATE 16 August 1963
TIME 1558 PST

12 Feet				50 Feet			
T (sec)				T (sec)			
s (sec)	16	32	64	128	256	512	s (sec)
1	17.6	29.5	44.1	57.1	72.1	93.5	1
2	14.9	27.0	42.0	55.2	70.2	91.5	2
4	10.4	22.7	38.4	51.9	67.0	88.0	4
8	4.1	15.9	32.7	46.8	62.0	82.5	8
16	0	6.0	23.1	38.1	53.5	72.9	16

MEAN DIRECTION AND SPEED 265/7.5

		100 Feet				200 Feet									
		T (sec)				T (sec)									
s (sec)		16	32	64	128	256	512	s (sec)		16	32	64	128	256	512
1	13.4	18.6	24.6	32.5	37.4	54.2		1		9.6	15.9	21.0	26.5	29.4	43.9
2	11.4	16.9	23.1	31.2	36.2	52.9		2		8.3	14.8	20.1	25.7	28.7	43.1
4	7.8	13.6	20.4	29.0	34.1	50.5		4		6.0	12.7	18.3	24.3	27.5	41.7
8	2.8	8.8	16.4	25.5	30.9	46.9		8		2.4	9.0	15.2	22.0	25.6	39.2
16	0	3.0	11.0	20.8	26.6	42.1		16		0	3.3	10.3	18.1	22.5	35.2
MEAN DIRECTION AND SPEED		243/9.5				MEAN DIRECTION AND SPEED				252/9.3					

MEAN DIRECTION AND SPEED 243/9.5

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 24
DATE 19 August 1963
TIME 1542 PST

12 Feet					50 Feet				
T (sec)					T (sec)				
s	16	32	64	128	s	16	32	64	128
(sec)					(sec)				
1	53.2	73.3	84.4	103.2	1	50.3	62.9	78.1	95.5
2	45.1	66.4	78.7	98.4	2	42.3	56.6	72.5	91.2
4	31.9	55.1	69.4	90.3	4	29.2	46.4	63.5	84.2
8	11.7	36.2	54.2	76.8	8	17.6	30.8	50.3	73.4
16	0	12.1	33.9	58.8	16	0	10.2	32.0	57.9
MEAN DIRECTION AND SPEED					271/5.8				

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 25
DATE 21 August 1963
TIME 1334 PST

12 Feet									
T (sec)									
s (sec)	16	32	64	128	256	512	s (sec)	16	32
1	28.2	41.6	62.0	91.2	99.3	138.8	1	16.8	24.8
2	24.3	38.0	58.5	88.0	96.3	135.9	2	14.2	22.4
4	17.0	31.1	52.0	82.0	90.5	130.5	4	9.8	19.4
8	6.1	20.3	41.5	72.3	81.1	122.1	8	3.7	12.3
16	0	7.0	27.3	59.0	69.3	111.6	16	0	4.2
MEAN DIRECTION AND SPEED 263/7.8									

100 Feet									
T (sec)									
s (sec)	16	32	64	128	256	512	s (sec)	16	32
1							1		
2							2		
4							4		
8							8		
16							16		
MEAN DIRECTION AND SPEED									

200 Feet

T (sec)									
s (sec)	16	32	64	128	256	512	s (sec)	16	32
1							1		
2							2		
4							4		
8							8		
16							16		
MEAN DIRECTION AND SPEED									

MISSING

MISSING

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 26
DATE 22 August 1963
TIME 1430 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	25.4	40.2	64.3	94.2	135.6	165.9	1	21.1	34.4	58.9	88.2	125.9	139.4
2	21.8	36.8	61.2	91.3	132.9	163.4	2	17.9	31.3	56.0	85.7	123.5	137.3
4	15.4	30.6	55.3	86.1	126.0	159.0	4	12.6	26.1	51.1	81.7	119.7	134.1
8	5.7	20.4	45.5	77.3	119.6	151.7	8	4.8	17.7	43.1	75.4	113.9	129.3
16	0	7.6	31.3	64.9	107.9	142.5	16	0	6.7	30.5	65.4	104.8	122.7

MEAN DIRECTION AND SPEED 256/9.7

100 Feet										200 Feet																					
T (sec)										T (sec)																					
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512											
1	15.4	25.0	42.1	63.3	96.0	116.1	1	14.7	26.0	43.6	62.1	90.9	113.4	1	14.7	26.0	43.6	62.1	90.9	113.4											
2	13.5	23.2	40.5	61.8	94.7	114.9	2	12.7	24.0	41.9	60.5	89.5	112.1	2	12.7	24.0	41.9	60.5	89.5	112.1											
4	9.6	19.6	37.1	58.8	92.1	112.7	4	9.2	20.7	38.8	57.8	87.3	110.1	4	9.2	20.7	38.8	57.8	87.3	110.1											
8	3.8	13.3	31.0	53.4	87.4	108.6	8	3.8	14.7	33.2	52.8	83.1	106.3	8	3.8	14.7	33.2	52.8	83.1	106.3											
16	0	4.7	21.2	44.7	80.1	102.4	16	0	5.4	23.1	43.7	75.6	99.3	16	0	5.4	23.1	43.7	75.6	99.3											
MEAN DIRECTION AND SPEED										255/11.4										MEAN DIRECTION AND SPEED										247/11.0	

MEAN DIRECTION AND SPEED 255/11.4

MEAN DIRECTION AND SPEED 247/11.0

$$\sigma^2(\theta)_{T,s}$$

(degrees)

SAND STORM NO. 27
DATE 27 August 1963
TIME 1538 PST

12 Feet					50 Feet								
T (sec)					T (sec)								
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	30.5	54.3	93.4	122.0	146.4	150.3	1	34.3	55.3	93.3	139.1	214.9	205.3
2	25.9	49.8	89.4	118.5	142.3	147.2	2	28.9	50.2	88.4	134.5	209.5	201.5
4	18.7	42.7	83.1	113.4	136.9	142.8	4	19.9	41.7	80.1	126.7	200.8	195.2
8	7.4	29.9	71.3	104.1	127.5	134.7	8	7.7	28.8	67.2	115.2	188.3	186.3
16	0	11.4	50.7	88.8	112.7	121.4	16	0	10.4	45.9	96.4	168.1	172.2

MEAN DIRECTION AND SPEED 249/6.4

100 Feet							200 Feet						
		T (sec)							T (sec)				
n	16	32	64	128	256	512	n	16	32	64	128	256	512
(sec)													(sec)
1	41.1	63.9	96.7	161.3	304.1	286.7	1	31.1	43.8	64.6	111.6	216.9	219.9
2	34.4	57.9	90.7	154.7	296.6	281.6	2	27.3	40.6	61.3	108.1	213.0	217.2
4	23.7	48.3	81.3	144.5	285.1	274.0	4	19.6	34.2	54.4	100.8	205.0	211.8
8	9.5	34.1	67.7	129.8	268.8	263.9	8	7.5	23.2	42.8	88.3	191.2	202.7
16	0	12.3	44.6	104.3	240.9	247.2	16	0	7.3	25.4	69.0	169.5	189.5
MEAN DIRECTION AND SPEED						249/5.9	MEAN DIRECTION AND SPEED						239/6.8

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 28
DATE 30 August 1963
TIME 1439 PST

12 Feet									
T (sec)									
s (sec)	16	32	64	128	256	512	s (sec)	16	32
1	19.4	34.0	54.9	83.2	100.0	123.5	1	16.8	26.3
2	16.7	31.4	52.7	81.2	98.1	121.8	2	14.2	23.8
4	11.9	26.8	48.8	77.6	94.7	118.9	4	9.8	19.8
8	4.7	18.9	41.9	71.2	88.6	113.8	8	3.8	13.6
16	0	7.2	29.6	59.3	77.0	104.5	16	0	4.8

MEAN DIRECTION AND SPEED 255/8.5

200 Feet									
T (sec)									
s (sec)	16	32	64	128	256	512	s (sec)	16	32
1	11.0	18.7	30.7	48.4	60.5	72.2	1	10.4	16.2
2	9.6	17.5	29.6	47.5	59.7	71.5	2	9.0	14.9
4	6.9	15.2	27.4	45.6	58.0	70.0	4	6.5	12.6
8	2.9	11.1	23.5	42.1	55.0	67.4	8	2.5	8.7
16	0	4.0	15.7	35.0	49.1	62.6	16	0	3.0

MEAN DIRECTION AND SPEED 262/8.3

MEAN DIRECTION AND SPEED 250/8.3

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 29
DATE 10 September 1963
TIME 1611 PST

12 Feet									
T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	27.5	41.5	54.1	80.2	79.7	106.5	1	26.2	39.3
2	24.2	38.5	61.2	77.7	77.5	103.9	2	22.6	36.0
4	17.5	32.6	55.4	72.8	73.0	98.9	4	16.1	30.1
8	6.6	21.9	45.0	64.0	65.1	89.8	8	6.1	20.2
16	0	7.6	29.5	51.4	54.2	76.8	16	0	6.9

MEAN DIRECTION AND SPEED 261/7.7

100 Feet									
T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	19.1	30.1	47.2	56.1	59.2	74.2	1	13.6	24.7
2	16.8	28.2	45.5	54.6	57.9	72.7	2	11.9	23.1
4	12.4	24.5	42.1	51.8	55.4	70.0	4	8.8	20.0
8	5.1	17.5	35.6	46.9	51.3	65.1	8	3.5	14.1
16	0	6.1	24.0	38.5	44.8	56.8	16	0	5.4

MEAN DIRECTION AND SPEED 265/9.5

200 Feet

T (sec)									
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	13.6	24.7	42.4	51.6	64.2	72.8	1	13.6	24.7
2	11.9	23.1	41.1	50.4	63.1	71.7	2	11.9	23.1
4	8.8	20.0	39.4	48.0	61.0	69.6	4	8.8	20.0
8	3.5	14.1	33.1	43.5	57.2	65.3	8	3.5	14.1
16	0	5.4	23.6	35.7	50.4	58.1	16	0	5.4

MEAN DIRECTION AND SPEED 250/10.5

Table C1 (contd)

$$\sigma^2(\theta)_{T, \theta}$$

(degrees)

SAND STORM NO. 30
DATE 11 September 1963
TIME 1526 PST

12 Feet					50 Feet				
T (sec)					T (sec)				
s (sec)	16	32	64	128	s (sec)	16	32	64	128
1	60.2	37.2	139.2	200.1	1	50.0	73.3	104.2	170.6
2	49.5	87.1	129.7	191.1	2	41.6	65.8	96.9	163.5
4	34.1	72.5	116.1	178.2	4	28.9	54.5	85.9	152.8
8	13.2	50.1	95.6	158.7	8	10.8	36.6	68.6	135.7
16	0	10.0	64.1	128.7	16	0	13.2	44.5	111.3

MEAN DIRECTION AND SPEED 261/2.9

100 Feet					200 Feet				
T (sec)					T (sec)				
s (sec)	16	32	64	128	s (sec)	16	32	64	128
1	28.4	37.8	52.5	94.9	1	35.8	53.1	76.3	108.1
2	23.5	33.6	48.4	90.8	2	31.1	49.0	72.4	104.3
4	16.8	27.8	42.7	85.0	4	22.5	41.4	65.3	97.4
8	6.2	18.1	33.1	75.0	8	8.4	27.7	52.5	85.0
16	0	5.6	20.6	60.9	16	0	9.7	34.2	67.6

MEAN DIRECTION AND SPEED 244/3.4

Table C1 (contd)

 $\sigma^2(\theta)_{T,\theta}$
(degrees)

SAND STORM NO. 31
DATE 12 Sep 1963
TIME 1501 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	13.0	16.2	19.8	24.7	33.6	36.7	1	8.4	10.7	14.0	19.8	32.3	38.1
2	10.6	14.0	17.8	22.7	31.6	34.8	2	6.9	9.4	12.7	18.5	31.1	37.0
4	6.7	10.0	14.4	19.5	28.4	31.8	4	4.7	7.3	10.7	16.6	29.4	35.3
8	2.2	6.1	10.4	15.6	24.8	28.2	8	1.6	4.4	7.9	14.0	27.0	33.1
16	0	1.9	6.2	11.6	21.1	24.8	16	0	1.3	4.8	10.8	24.1	30.9
MEAN DIRECTION AND SPEED							266/8.9						

100 Feet							200 Feet								
T (sec)							T (sec)								
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512		
1	4.5	6.7	9.8	16.3	34.3	44.9	1	2.9	4.6	6.5	10.3	21.7	29.5		
2	3.8	6.1	9.2	15.7	33.7	44.5	2	2.5	4.2	6.2	10.0	21.3	29.0		
4	2.6	5.0	8.1	14.6	32.6	43.7	4	1.7	3.4	5.5	9.2	20.7	28.6		
8	0.9	3.3	6.5	12.5	31.0	42.7	8	0.6	2.3	4.6	8.3	19.6	27.9		
16	0	1.1	4.2	10.3	28.2	41.3	16	0	0.8	3.1	6.7	17.8	27.0		
MEAN DIRECTION AND SPEED							MEAN DIRECTION AND SPEED							257/10.6	
279/11.2															

$$\sigma^2(\theta)_{T, \theta}$$

SAND STORM NO. 32
DATE 16 Sep 1963
TIME 1413 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	16.5	24.9	40.2	72.8	97.0	145.3	1	12.1	17.7	25.3	39.8	60.1	115.5
2	14.1	22.6	37.9	70.6	95.0	143.6	2	10.2	15.9	23.5	38.0	58.4	113.8
4	9.9	18.6	33.9	66.6	91.5	140.8	4	6.7	12.6	20.3	34.6	55.4	110.9
8	5.6	12.1	27.5	60.2	86.0	136.5	8	2.3	8.1	16.0	30.4	51.1	107.3
16	0	4.4	18.7	50.8	78.6	131.4	16	0	2.9	10.6	24.8	45.7	102.9

MEAN DIRECTION AND SPEED 264/8.8

		100 Feet				200 Feet									
		T (sec)				T (sec)									
s	(sec)	16	32	64	128	256	512	s	(sec)	16	32	64	128	256	512
1	11.6	18.1	40.6	59.3	95.5	11.2	17.4	25.8	33.8	43.7	63.5				
2	10.2	16.9	39.4	58.2	94.6	9.7	16.2	22.7	32.7	42.6	62.5				
4	7.5	14.5	37.2	56.0	92.7	6.9	13.9	20.6	30.6	40.6	60.6				
8	2.3	10.1	32.9	51.6	89.2	2.7	9.8	15.9	26.8	37.0	57.3				
16	0	3.5	25.9	44.4	83.4	0	3.5	10.9	20.7	31.3	51.7				
MEAN DIRECTION AND SPEED		266/9.6				MEAN DIRECTION AND SPEED				258/10.4					

Table C1 (contd)

 $\theta^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 33

DATE 8 Oct 1963

TIME 1543 PST

12 Feet										50 Feet				
T (sec)										T (sec)				
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512	
1	22.0	25.8	27.9	31.1	34.7	40.0	1	14.0	17.2	21.2	26.9	33.8	41.6	
2	18.9	23.2	25.4	28.5	32.1	37.4	2	12.0	15.4	19.5	25.2	32.1	39.9	
4	13.3	18.3	20.7	23.8	27.4	32.9	4	8.3	12.3	16.5	22.2	29.0	37.1	
8	4.6	10.7	13.6	16.7	20.0	25.0	8	3.0	7.6	11.9	17.7	24.5	32.9	
16	0	2.8	6.5	9.8	13.5	18.8	16	0	2.1	6.3	12.2	19.1	27.9	

MEAN DIRECTION AND SPEED 258/4.5

100 Feet										200 Feet				
T (sec)										T (sec)				
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512	
1	7.5	11.4	14.4	17.0	20.4	23.5	1	5.7	9.1	11.8	14.6	20.5	27.5	
2	6.4	10.6	13.7	16.2	19.6	22.7	2	5.0	8.5	11.3	14.2	20.0	27.0	
4	4.6	9.1	12.4	14.9	18.3	21.4	4	3.7	7.4	10.5	13.3	19.2	26.2	
8	1.8	6.4	10.1	12.9	16.3	19.3	8	1.5	5.2	8.8	11.7	17.4	24.4	
16	0	2.2	6.4	9.6	12.9	15.8	16	0	1.8	5.9	8.2	14.2	21.4	

MEAN DIRECTION AND SPEED 249/5.2

MEAN DIRECTION AND SPEED 252/6.0

$\theta^2(\theta)_{T,c}$
(degrees)

SAND STORM NO. 34
DATE 9 Oct 1963
TIME 1408 PST

12 Feet							30 Feet								
		T (sec)							T (sec)						
s		16	32	64	128	256	512	s		16	32	64	128	256	512
(sec)								(sec)							
1		32.3	53.4	88.5	131.1	137.2	156.2	1		37.4	68.8	112.1	168.8	198.5	216.1
2		27.7	49.2	84.5	127.6	134.3	153.2	2		32.2	64.0	107.7	164.9	195.0	212.9
4		19.7	41.7	77.5	121.4	129.4	148.0	4		23.3	55.5	100.2	158.3	189.2	207.6
8		8.0	29.4	65.7	110.8	121.6	139.6	8		9.7	40.2	86.4	146.3	178.9	198.0
16		0	10.7	45.1	92.2	109.1	125.6	16		0	15.5	60.9	122.9	159.0	179.8

MEAN DIRECTION AND SPEED 263/6.6

100 Feet				200 Feet			
T (sec)				T (sec)			
s (sec)	16	32	64	128	256	512	512
1	15.8	27.3	50.0	80.0	90.9	101.5	85.9
2	13.3	24.9	47.7	78.0	89.1	99.8	84.2
4	9.3	20.8	43.6	74.8	86.0	96.9	80.9
8	3.5	14.2	36.9	69.5	81.3	92.4	75.3
16	0	5.5	26.0	60.5	73.6	85.1	66.5
MEAN DIRECTION AND SPEED							244/8.1
253/6.8							

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 35
DATE 11 Oct 1963
TIME 1447 PST

12 Feet						50 Feet							
T (sec)						T (sec)							
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	14.2	18.1	20.8	24.1	24.1	24.8	1						
2	11.9	16.1	18.9	22.2	22.2	23.0	2						
4	8.0	12.7	15.7	19.1	19.2	20.1	4						
8	2.8	7.9	11.4	14.9	15.0	16.1	8						
16	0	2.5	6.5	10.1	10.5	11.8	16						
MEAN DIRECTION AND SPEED						292/10.8						MISSING	

100 Feet							200 Feet								
T (sec)							T (sec)								
s	16	32	64	128	256	512	s	16	32	64	128	256	512		
(sec)							(sec)								
1	5.5	6.8	9.3	11.4	9.7	12.2	1	2.3	3.4	4.9	6.6	5.9	8.8		
2	4.7	6.1	8.6	10.8	9.1	11.7	2	1.9	3.0	4.5	6.3	5.6	8.5		
4	3.3	4.9	7.4	9.7	8.1	10.6	4	1.2	2.4	4.0	5.8	5.2	8.1		
8	1.2	2.9	5.5	7.9	6.6	9.0	8	0.4	1.6	3.2	5.2	4.7	7.5		
16	0	0.8	3.3	6.0	5.0	7.2	16	0	0.5	2.2	4.3	4.0	6.8		
MEAN DIRECTION AND SPEED							289/12.7	MEAN DIRECTION AND SPEED							279/13.7

$$\sigma^2(\theta)_{T,2}$$

(degrees)

SAND STORM NO. 36
DATE 15 Oct 1963
TIME 1608 PST

[illegible]

100 Feet							200 Feet						
		T (sec)							T (sec)				
s (sec)	16	32	64	128	256	512	s (sec)	16	32	64	128	256	512
1	5.2	6.9	10.6	21.2	30.2	60.5	1	4.1	6.1	10.1	19.2	22.6	39.5
2	4.6	6.3	10.1	20.6	29.7	59.9	2	3.5	5.6	9.6	18.7	22.3	38.9
4	3.3	5.2	8.9	19.5	28.9	58.6	4	2.5	4.7	8.6	17.8	21.6	37.9
8	1.2	3.3	7.0	17.6	27.4	56.4	8	0.9	3.1	7.0	16.3	20.4	36.1
16	0	0.9	4.4	14.7	25.3	52.8	16	0	1.1	4.7	13.8	18.7	33.0
MEAN DIRECTION AND SPEED						274/7.2	MEAN DIRECTION AND SPEED						262/7.5

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 37
DATE 22 Oct 1963
TIME 1534 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	16.8	24.1	35.6	43.1	48.6	67.7	1	12.9	18.1	25.5	29.4	36.9	62.0
2	14.3	21.8	33.5	41.2	46.6	65.7	2	10.8	16.2	23.8	27.8	35.3	60.5
4	10.0	17.9	29.8	37.9	43.1	62.3	4	7.3	13.0	20.9	25.1	32.5	57.9
8	3.7	11.8	23.8	32.6	37.4	57.0	8	2.7	8.5	16.8	21.4	28.7	54.4
16	0	3.8	15.3	25.3	29.2	49.5	16	0	2.9	11.0	16.5	23.6	49.6
MEAN DIRECTION AND SPEED 235/6.4							200 Feet						
							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	10.2	15.3	18.0	18.4	21.1	44.4	1	9.3	15.6	22.3	25.6	25.6	51.7
2	8.8	14.1	17.1	17.6	20.4	43.5	2	8.0	14.4	21.3	24.8	24.8	50.7
4	6.3	11.8	15.3	16.2	19.0	41.8	4	5.7	12.2	19.4	23.2	23.4	48.8
8	2.3	7.8	12.3	13.9	16.9	39.0	8	2.2	8.5	16.2	20.7	21.0	45.4
16	0	2.7	7.9	10.8	14.0	35.1	16	0	3.1	11.0	16.8	17.3	39.8
MEAN DIRECTION AND SPEED 257/6.8							MEAN DIRECTION AND SPEED 245/7.1						

$\sigma^2(\theta)_{T,0}$
(degrees)

SAND STORM NO. 38

DATE 23 Oct 1963

TIME 1335 PST

12 Feet				50 Feet			
T (sec)				T (sec)			
s	16	32	64	128	256	512	1024
(sec)	1	2	4	8	16	32	64
1	19.4	26.0	35.1	46.2	51.3	56.6	61.9
2	16.5	23.4	32.6	43.9	49.2	54.4	59.7
4	11.5	19.0	28.3	40.0	45.6	50.6	55.7
8	4.2	12.3	22.0	34.3	40.6	45.0	49.4
16	0	4.0	13.5	26.6	33.6	37.4	41.3

MEAN DIRECTION AND SPEED 246/9.3

100 Feet				200 Feet			
T (sec)				T (sec)			
θ (sec)	16	32	64	128	256	512	1024
1	6.0	9.1	15.1	22.7	27.0	31.3	35.6
2	5.1	8.2	14.2	22.0	26.3	30.5	34.8
4	3.5	6.7	12.7	20.6	25.0	29.3	33.6
8	1.3	4.3	10.3	18.4	22.8	27.3	31.7
16	0	1.5	7.0	15.6	20.2	24.7	29.1
MEAN DIRECTION AND SPEED				MEAN DIRECTION AND SPEED			
265/11.0				256/11.1			

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 39
DATE 29 Oct 1963
TIME 1445 PST

12 Feet							50 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	39.1	58.9	86.2	112.4	152.2	323.4	1	37.8	65.1	95.6	118.0	167.7	356.5
2	33.5	53.9	82.0	108.7	149.0	319.4	2	31.6	59.6	91.5	114.5	164.6	352.9
4	23.8	45.4	74.8	102.4	143.4	312.6	4	22.6	51.1	85.1	109.1	159.5	347.3
8	15.4	31.6	62.8	92.2	134.3	301.5	8	9.0	36.1	73.5	99.5	150.4	337.5
16	0	11.5	43.2	76.2	120.4	284.0	16	0	13.8	52.5	82.5	134.9	320.5

MEAN DIPECTION AND SPLED 228/3.5

100 Feet							200 Feet						
T (sec)							T (sec)						
s	16	32	64	128	256	512	s	16	32	64	128	256	512
(sec)							(sec)						
1	37.2	60.2	71.9	92.2	164.5	349.0	1	45.8	83.2	81.9	71.1	70.0	131.4
2	31.0	55.0	68.1	88.8	161.2	345.7	2	40.4	79.0	78.8	68.5	67.6	128.4
4	21.5	46.8	62.0	83.1	155.6	340.3	4	30.4	70.4	73.0	63.8	63.3	122.6
8	8.8	33.3	51.6	73.0	145.5	331.0	8	12.9	51.8	61.2	54.6	55.2	111.3
16	0	12.2	34.0	56.6	129.0	315.9	16	0	19.6	39.8	38.7	42.1	91.6

MEAN DIPECTION AND SPEED 236/4.1

MEAN DIPECTION AND SPEED 227/4.2

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 40
DATE 30 Oct 1963
TIME 1131 PST

12 Feet										50 Feet				
T (sec)										T (sec)				
s	16	32	64	128	256	512	s	16	32	64	128	256	512	
(sec)							(sec)							
1	25.6	35.1	48.8	73.4	103.3	111.6	1	26.4	34.3	44.5	62.9	88.0	106.2	
2	21.7	31.7	45.5	70.5	100.7	108.8	2	23.1	31.4	41.9	60.5	85.6	103.9	
4	15.2	25.9	40.1	65.5	96.4	104.2	4	16.5	25.9	36.9	55.9	81.3	99.4	
8	5.7	17.1	31.4	57.8	89.7	97.0	8	6.2	17.0	28.6	49.5	74.5	92.0	
16	0	5.8	19.7	47.0	80.5	87.5	16	0	5.4	17.2	38.3	65.1	81.9	

MEAN DIRECTION AND SPEED 232/6.8

100 Feet										200 Feet				
T (sec)										T (sec)				
s	16	32	64	128	256	512	s	16	32	64	128	256	512	
(sec)							(sec)							
1	15.2	19.9	28.5	43.2	58.2	82.1	1	13.7	18.6	24.0	35.8	55.0	85.7	
2	13.1	18.1	26.8	41.8	56.9	80.7	2	12.0	17.1	22.6	34.3	53.6	84.3	
4	9.3	14.8	23.8	39.2	54.6	78.2	4	8.6	14.2	19.9	31.7	50.9	81.8	
8	3.3	9.3	18.6	34.7	50.5	73.9	8	3.2	9.3	15.2	27.0	46.2	77.3	
16	0	3.1	11.7	28.6	45.5	68.2	16	0	2.8	8.9	20.8	40.4	71.1	

MEAN DIRECTION AND SPEED 256/8.1

MEAN DIRECTION AND SPEED 246/7.1

Table C1 (contd)

 $\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 41
DATE 4 Nov 1963
TIME 1208 PST

12 Feet					50 Feet				
T (sec)					T (sec)				
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	18.3	25.2	32.8	44.0	56.9	55.7	1	18.6	24.0
2	15.0	22.3	30.1	41.4	54.5	53.2	2	15.5	21.1
4	9.9	17.5	25.7	37.1	50.4	49.3	4	10.5	16.5
8	3.3	10.9	19.8	31.3	45.0	44.2	8	3.5	9.8
16	0	3.9	13.0	24.6	38.7	38.9	16	0	3.3

MEAN DIRECTION AND SPEED 235/9.0

100 Feet					200 Feet				
T (sec)					T (sec)				
s	16	32	64	128	256	512	s	16	32
(sec)							(sec)		
1	9.3	11.9	15.5	20.4	26.4	25.3	1	8.3	12.0
2	8.0	10.8	14.5	19.6	25.7	24.5	2	7.2	11.0
4	5.7	8.9	12.9	18.1	24.4	23.1	4	5.2	9.2
8	2.1	5.8	10.3	15.9	22.5	21.0	8	2.0	6.2
16	0	1.8	6.6	12.5	19.5	18.1	16	0	2.0

MEAN DIRECTION AND SPEED 259/11.2

MEAN DIRECTION AND SPEED

252/9.8

$$\sigma^2(\theta)_{T,0}$$
(degrees)

SAND STORM NO. 42
DATE 5 Nov 1963
TIME 1425 PST

12 Feet						
T (sec)						
	16	32	64	128	256	512
1 (sec)	16.3	22.5	29.9	34.9	39.7	40.8
2	13.5	19.8	27.3	32.3	37.3	38.3
4	8.8	15.3	23.1	28.3	33.3	34.2
8	2.9	9.5	17.0	23.2	28.4	29.1
16	0	3.3	11.8	17.8	22.7	23.6
MEAN DIRECTION AND SPEED 228/10.2						
100 Feet						
T (sec)						
	16	32	64	128	256	512
1 (sec)	5.5	7.9	11.0	16.5	20.9	22.9
2	4.7	7.2	10.4	15.9	20.3	22.3
4	3.3	6.0	9.2	14.7	19.1	21.3
8	1.3	4.1	7.3	12.8	17.2	19.7
16	0	1.3	4.5	9.8	14.6	17.0
MEAN DIRECTION AND SPEED 251/12.1						
50 Feet						
T (sec)						
	16	32	64	128	256	512
1 (sec)	11.8	18.9	19.1	26.6	34.3	35.7
2	9.9	13.1	17.4	24.8	32.6	34.1
4	6.8	10.0	14.6	22.0	29.8	31.5
8	2.5	6.5	10.8	18.1	25.8	27.8
16	0	1.8	5.1	13.2	21.1	23.4
MEAN DIRECTION AND SPEED 242/12.4						
200 Feet						
T (sec)						
	16	32	64	128	256	512
1 (sec)	4.7	6.6	10.1	14.6	18.0	21.5
2	4.1	6.0	9.5	14.2	17.5	21.1
4	3.0	5.1	8.6	13.3	16.7	20.3
8	1.1	3.3	5.9	11.7	15.1	18.9
16	0	1.0	4.3	9.3	13.0	16.8
MEAN DIRECTION AND SPEED 242/12.4						

SAND STORM NO. 43
DATE 7 Nov 1963
TIME 1422 PST

MEAN DIRECTION AND SPEED 232/7.3

MEAN DIRECTION AND SPEED 246/8.4

$\sigma^2(\theta)_{T,s}$
(degrees)

SAND STORM NO. 44
DATE 13 Nov 1963
TIME 1408 PST

		12 Feet					50 Feet								
		T (sec)					T (sec)								
s	(sec)	16	32	64	128	256	512	s	(sec)	16	32	64	128	256	512
1	33.3		51.6	79.3	120.2	143.7	156.9	1	21.9		34.7	55.6	93.4	128.8	149.7
2	28.7		47.5	74.5	116.8	140.7	153.9	2	18.5		31.5	52.6	90.5	126.1	147.3
4	20.7		40.2	67.9	110.6	135.4	148.8	4	12.9		26.3	47.5	85.4	121.6	143.5
8	8.0		27.5	56.1	93.6	125.9	140.0	8	4.9		17.9	39.4	77.2	114.5	137.6
16	0		9.7	37.7	81.8	111.0	126.6	16	0		6.5	26.8	64.5	103.6	129.1

MEAN DIRECTION AND SPEED 241/4.5

100 Feet				200 Feet			
T (sec)				T (sec)			
s (sec)	16	32	64	128	256	512	s (sec)
1	15.0	22.9	38.1	59.5	102.5	119.7	1
2	12.9	20.9	36.1	57.4	100.6	115.2	2
4	9.2	17.1	32.4	63.5	97.0	115.4	4
8	3.2	10.8	26.0	56.7	90.7	110.7	8
16	0	3.2	17.5	47.7	83.2	105.5	16
MEAN DIRECTION: AND SPEED				266/4.6			
MEAN DIRECTION: AND SPEED				251/4.8			

ENVIRONMENTAL RESEARCH PAPERS

- No. 1. Examination of a Wind Profile Proposed by Swinbank, *Morton L. Barad, March 1964 (REPRINT).*
- No. 2. Wind and Temperature Variations During Development of a Low-Level Jet, *Yutaka Izumi, Morton L. Barad, March 1964 (REPRINT).*
- No. 3. Radiation Pattern of Surface Waves From Point Sources in a Multi-Layered Medium, *V. A. Haskell, March 1964 (REPRINT).*
- No. 4. Photoelectric Emission Phenomena in LiF and KCl in the Extreme Ultraviolet, *R. G. Newburgh, February 1964 (REPRINT).*
- No. 5. Equatorial Loci of the Earth's Magnetic Field and Cosmic Ray Parameters, *E. J. Chernosky, J. M. Collins, M. P. Hagan, March 1964.*
- No. 6. Helium and Argon Emission Continua and Their Use in Absorption Cross-Section Measurements in the Vacuum Ultraviolet, *R. E. Huffman, Y. Tanaka, J. C. Larrabee, March 1964 (REPRINT).*
- No. 7. Airflow and Structure of a Tornadoic Storm, *K. A. Browning, R. J. Donaldson, Jr., March 1964 (REPRINT).*
- No. 8. Automatic Digital Radar Reflectivity Analysis of a Tornadoic Storm, *David Atlas, Keith A. Browning, Ralph J. Donaldson, Jr., Hugh J. Sweeney, March 1964 (REPRINT).*
- No. 9. Indications of a Lunar Synodical Period in the Sunshine Observations for Boston, Massachusetts, and Columbia, Missouri, *Iver A. Lund, March 1964.*
- No. 10. A Search for Rainfall Calendaricities, *Glenn W. Brier, Ralph Shapiro, Norman J. MacDonald, March 1964 (REPRINT).*
- No. 11. Lee Wave Clouds Photographed From an Aircraft and a Satellite, *John H. Conover, April 1964 (REPRINT).*
- No. 12. Diurnal Variation of the Atmosphere Around 190 Kilometers Derived From Solar Extreme Ultraviolet Absorption Measurements, *L. A. Hall, W. Schweizer, H. E. Hinteregger, April 1964 (REPRINT).*
- No. 13. Absorption Coefficients of Oxygen in the 1060-580-A Wavelength Region, *R. E. Huffman, J. C. Larrabee, and Y. Tanaka, May 1964 (REPRINT).*
- No. 14. Sunrise Effects on East-West Ionospheric Propagation Paths, *Thomas D. Conley and David Blood, May 1964.*
- No. 15. Project Firefly 1962-1963, *N.W. Rosenberg, Ed., May 1964.*
- No. 15. (Appendix), Project Firefly 1962-1963—Classified Appendix (U), *N.W. Rosenberg, Ed., June 1964.*
- No. 16. Small-Scale Wind Structure Above 100 Kilometers, *Samuel P. Zimmerman, May 1964, (REPRINT).*
- No. 17. Resonance Radiation of AlO From Trimethyl Aluminum Released Into the Upper Atmosphere, *N.W. Rosenberg, D. Golomb, E.F. Allen, Jr., May 1964, (REPRINT).*
- No. 18. Possibility of a 26- or 27-Month Periodicity in the Equatorial Geomagnetic Field, *Ralph Shapiro and Fred Ward, May 1964, (REPRINT).*
- No. 19. Crater Frequency and the Interpretation of Lunar History, *Robert T. Dodd, Jr., John W. Salisbury, and Vern G. Smalley, May 1964, (REPRINT).*
- No. 20. Altitude Variation of Rayleigh, Aerosol, and Ozone Attenuating Components in the Ultraviolet Region, *L. Elterman, May 1964.*
- No. 21. Long Line Azimuths From Optical Observations of the ANNA Flashing Satellite, *Armando Mancini, June 1964.*
- No. 22. Ionospheric Perturbations, Solar Flares, and Geomagnetic Storms—Correlations Observed by Oblique Long-Range High-Frequency Probing, *Helen R. Baker and Alfred E. Reilly, June 1964.*
- No. 23. Laser-Satellite Reflection Parameters, *Robert L. Hiff, June 1964.*
- No. 24. The Infrared Telluric Absorption Spectrum Introductory Report, *J.N. Howard, and J.S. Garing, June 1964 (REPRINT).*
- No. 25. Be⁷, P³², P³³, and S³⁵: Stratospheric Concentrations and Artificial Production, *P.J. Drevinsky, J.T. Wasson, E.C. Couble and N.A. Dimond, July 1964 (REPRINT).*
- No. 26. Generation and Properties of High Altitude Chemical Plasma Clouds, *N.W. Rosenberg and D. Golomb, July 1964 (REPRINT).*
- No. 27. The Statistics of Satellite Scintillations at a Subauroral Latitude, *Jules Aarons, John Mullen and Sunanda Basu, July 1964 (REPRINT).*
- No. 28. The Mathematical Equivalence of Multi-Level and Vertically Integrated Numerical Forecasting Models, *Louis Berkofsky, July 1964 (REPRINT).*
- No. 29. Low Energy Charge Exchange and Ion-Molecule Reactions, *J.F. Paulson, July 1964 (REPRINT).*

ENVIRONMENTAL RESEARCH PAPERS (Continued)

- No. 30. Shear Deformation of Upper Mantle Mineral Analogues: Tests to 55 kb at 27°C, R.E. Riecker, 1/Lt, USAF and K.E. Seifert, 1/Lt, USAF, July 1964.
- No. 31. Some Numerical Results of a Model Investigation of the Atmospheric Response to Upper-Level Heating, Louis Berkofsky and Ralph Shapiro, July 1964 (REPRINT).
- No. 32. Electrical Processes in the Nighttime Exosphere, R.C. Sagalyn and M. Smiddy, July 1964 (REPRINT).
- No. 33. Radioactivity in Sputnik 4 Fragment, John T. Wassen, July 1964 (REPRINT).
- No. 34. Falling Sphere Measurements of Atmospheric Density Temperature and Pressure up to 115 km, A.C. Faire and K.S.W. Champion, July 1964.
- No. 35. Geodetic Positioning From Simultaneous Optical Observations of the ANNA I-B Satellite, Lyndon L. Sheldon, Capt, USAF and Donald H. Eckhardt, July 1964.
- No. 36. The Evolution of Temperature and Velocity Profiles During Breakdown of a Nocturnal Inversion and a Low-Level Jet, Yutaka Izumi, July 1964 (REPRINT).
- No. 37. A Test for the Period of 18 Cycles per Year in Rainfall Data, Glenn W. Brier, Ralph Shapiro and Norman J. MacDonald, July 1964 (REPRINT).
- No. 38. Ozone-sonde Observations Over North America, Volume 2, Wayne S. Hering and Thomas R. Borden, Jr., Editors, July 1964.
- No. 39. Radar Reflectivity of Storms Containing Spongy Hail, David Atlas, Kenneth R. Hardy and Jurg Joss, August 1964 (REPRINT).
- No. 40. Radio Star Scintillation Over Canada During the 20 July 1963 Eclipse, R.S. Allen, J.A. Klobuchar, W.C. Kidd and H.E. Whitney, August 1964.
- No. 41. Tropopause Definition and Hourly Fluctuations, Arthur J. Kantor, August 1964.
- No. 42. Olivine Shear Strength at High Pressure and Room Temperature, R.E. Riecker and K.E. Seifert, August 1964 (REPRINT).
- No. 43. An Observation of a Large, Sudden Ionospheric Total Electron Content Decrease, J.A. Klobuchar, H.E. Whitney and R.S. Allen, August 1964 (REPRINT).
- No. 44. The Height Variation of Vertical Heat Flux Near the Ground, W.P. Elliott, September 1964, (REPRINT).
- No. 45. A Mid-Latitude Biennial Oscillation in the Variance of the Surface-Pressure Distribution, R. Shapiro, September 1964 (REPRINT).
- No. 46. Atmospheric Attenuation Model, 1964, in the Ultraviolet, Visible, and Infrared Regions for Altitudes to 50 km, L. Elterman, September 1964.
- No. 47. A Study of Auroral Echoes at 19.4 Megacycles per Second, Chester Malik and Jules Aarons, September 1964 (REPRINT).
- No. 48. Notes on Wright's Interpretation of Temporal Variation of O/N₂ Ratio in the Thermosphere, H.E. Hinteregger, September 1964 (REPRINT).
- No. 49. A Study of the Fine Structures in the Solar Chromosphere, Jacques M. Beckers, September 1964.
- No. 50. Observations of Ionospheric Wind Patterns Through the Night, N.W. Rosenberg and H.D. Edwards, September 1964 (REPRINT).
- No. 51. Ionospheric Temperatures Obtained From Photography of Shock Waves, N.W. Rosenberg, September 1964 (REPRINT).
- No. 52. Mutually Consistent Magnetic Charts Based on Orthogonal Functions, Paul F. Fougere, September 1964, (REPRINT).
- No. 53. Hourly Variability of Density at Radiosonde Heights, Paul F. Vee, September 1964 (REPRINT).
- No. 54. Solar XUV-Spectrum From 310 Å to 55 Å, H.E. Hinteregger, L.A. Hall, and W. Schweizer, September 1964 (REPRINT).
- No. 55. The Identification and Significance of Orographically Induced Clouds Observed by TIROS Satellites, John H. Conover, September 1964 (REPRINT).
- No. 56. Rocket Measurements With Electron and Ion Probes in an Aurora, J.C. Ulwick, W. Pfister, O.C. Haycock, and K.D. Baker, September 1964.
- No. 57. A Dynamical Model for Investigating the Effects of Periodic Heat Sources on the Equatorial Stratosphere, L. Berkofsky and R. Shapiro, September 1964 (REPRINT).
- No. 58. Neutral Hydrogen Near the North Galactic Pole, Nannielou H. Dieter, October 1964 (REPRINT).
- No. 59. Parameters for Attenuation in the Atmospheric Windows for Fifteen Wavelengths, Louis Elterman, October 1964 (REPRINT).
- No. 60. A Detailed Study of a Brief Period of Radio Star and Satellite Scintillations, Sunanda Basu, Richard S. Allen, and Jules Aarons, October 1964 (REPRINT).

ENVIRONMENTAL RESEARCH PAPERS (Continued)

- No. 61. Rocket Investigation of the Electrical Structure of the Lower Ionosphere, *R.C. Sagalya and M. Smiddy, October 1964 (REPRINT).*
- No. 62. On the Origin of Hurricane Spiral Bands, *D. Atlas, K.R. Hardy, R. Wexler, and R.J. Boucher, October 1964 (REPRINT).*
- No. 63. Formation of an Electron Depleted Region in the Ionosphere by Chemical Releases, *D. Golomb, N.W. Rosenberg, J.W. Wright, and R.A. Barnes, October 1964 (REPRINT).*
- No. 64. High-altitude Minimum Wind Fields and Balloon Applications, *George F. Nolan and Ralland A. Smith, October 1964.*
- No. 65. The Effect of Solar Flares on the (OI) Green Line of the Nightglow, *B.S. Dandekar and S.M. Silverman, October 1964 (REPRINT).*
- No. 66. Atmospheric Aerosol Observations with Searchlight Probing, *Louis Elterman and Allan B. Campbell, October 1964 (REPRINT).*
- No. 67. Ionospheric Winds: Motions Into Night and Sporadic E Correlations, *N.W. Rosenberg, H.D. Edwards, and J.W. Wright, November 1964 (REPRINT).*
- No. 68. Solar X Rays From 3 to 12 Angstroms as Measured With a Proportional Counter Spectrometer, *James E. Manson, November 1964.*
- No. 69. The Cosmic-Ray Equator at 170° West Longitude, *M.A. Shea, D.F. Smart, and J.F. Kenney, November 1964 (REPRINT).*
- No. 70. Radar Observations of Ice Spheres in Free Fall, *J.T. Willis, K.A. Browning, and D. Atlas, November 1964 (REPRINT).*
- No. 71. Very Low Frequency Envelope Spectra of Solar Radio Bursts, *Santima Basu, November 1964.*
- No. 72. A Collation Study of a Highly Magnetic Period (September 29-23, 1963), *Herbert M. Silverman and Barbara A. Rumsey, December 1964.*
- No. 73. Infrared Stellar Irradiance, *Russell G. Walker and Anthony D'Agati, December 1964 (REPRINT).*
- No. 74. Direct Satellite Probe Measurements of Ionospheric Irregularities in the F Region and the Polar Cap, *J.C. Ulwick, W. Pfister, and R.E. McInerney, December 1964.*
- No. 75. Winter Space Correlations of Pressure, Temperature, and Density to 16 km, *Eugene A. Bertoni and Iver A. Lund, December 1964.*
- No. 76. Lunar Surface Features: Mid-Infrared Spectral Observations, *Graham R. Hunt and John W. Salisbury, December 1964 (REPRINT).*
- No. 77. Evolution of a Graphical Prediction Technique Incorporating Ageostrophic Effects, *H. Stuart Muench, January 1965 (REPRINT).*
- No. 78. Measurements of Radio Star and Satellite Scintillations at a Subauroral Latitude, *R.S. Allen, J. Aarons, and H. Whitney, January 1965 (REPRINT).*
- No. 79. The Fall-Off with Height of Terrain-Induced Vertical Motions, *Louis Berkofsky, January 1965 (REPRINT).*
- No. 80. A Case Study Using Ozone to Determine Structure and Air Motions at the Tropopause, *Samuel Penn, January 1965 (REPRINT).*
- No. 81. Analysis and Interpretation of TIROS II Infrared Radiation Measurements, *R.S. Hawkins, February 1965 (REPRINT).*
- No. 82. Mass Spectrometry in the D-Region Ionosphere—Apparatus, Techniques, and First Measurements, *R.S. Narcis and A.D. Bailey, February 1965.*
- No. 83. Investigations of Noctilucent Cloud Particles, *C.L. Hemmaway, R.K. Soberman, and G. Witt et al., February 1965 (REPRINT).*
- No. 84. General Circulation of the Solar Atmosphere from Observational Evidence, *Fred Ward, February 1965 (REPRINT).*
- No. 85. An Investigation Into the Use of Temperature Gradients as an In-Flight Warning of Impending Clear-Air Turbulence, *George McLean, February 1965.*
- No. 86. Total Energy and Energy Spectral Density of Elastic Wave Radiation from Propagating Faults, *A. I. Haskell, February 1965 (REPRINT).*
- No. 87. Improved Extreme Ultraviolet Absorption Measurements in the Upper Atmosphere, *L.A. Hall, W. Schweizer, and H.E. Hinteregger, February 1965 (REPRINT).*
- No. 88. Sunspot Cycle and Ionospheric Storms, *Raymond J. Cormier and K.L. Smallwood, TSGT, USAF, February 1965.*
- No. 89. Ionospheric and Tropospheric Scintillations of a Radio Star at Zero to Five Degrees of Elevation, *John P. Castelli, Jules Aarons, and Herbert M. Silverman, March 1965 (REPRINT).*
- No. 90. A Demonstration of Antenna Beam Errors in Radar Reflectivity Patterns, *Ralph J. Donaldson, Jr., March 1965 (REPRINT).*
- No. 91. Coupling of Magnetohydrodynamic Waves in Stratified Media, *H. Loeferlein, March 1965 (REPRINT).*

ENVIRONMENTAL RESEARCH PAPERS (Continued)

- No. 92. Project ANNA Optical Observations, *Paul H. Dishong and George Hadgigeorge, March 1965.*
- No. 93. Airflow and Precipitation Trajectories Within Severe Local Storms Which Travel to the Right of the Winds, *Keith A. Browning, April 1965 (REPRINT).*
- No. 94. A Synoptic Study of Scintillations of Ionospheric Origin in Satellite Signals, *J. Aarons, and J. Mullen (and other members of the Joint Satellite Studies Group), April 1965 (REPRINT).*
- No. 95. Stratospheric Energy Processes and Associated Atmospheric Long-Wave Structure in Winter, *H. Stuart Muench, April 1965.*
- No. 96. Geology, Mineralogy, and Hydrology of U.S. Playas, *J.T. Neal, Capt, USAF, April 1965.*
- No. 97. Solar XUV Radiation and Neutral Particle Distribution in July 1963 Thermosphere, *H.E. Hinteregger, L.A. Hall, and G. Schmidtke, April 1965 (REPRINT).*
- No. 98. Investigation of Geomagnetic Duct Propagation of High-Frequency Radio Signals, *G.J. Gassman, T.B. Barrett, and B. Pratt, April 1965 (REPRINT).*
- No. 99. Satellite Measurements of the Diurnal Variation of Electron Temperatures in the F Region, *R.C. Sagalyn, M. Smiddy, and Y.V. Bhargava, April 1965 (REPRINT).*
- No. 100. Analysis of Ionospheric Winds and Turbulence Over Puerto Rico with a Correlation Method-I, *T.J. Keneshea, M.E. Gardner, and W. Pfister, April 1965 (REPRINT).*
- No. 101. The Evolution of an Ionospheric Hole, *Malcolm A. MacLeod and Dan Golomb, April 1965.*
- No. 102. Ionospheric Electron Content Measurements During a Solar Eclipse, *J.A. Klobuchar and H.E. Whitney, May 1965 (REPRINT).*
- No. 103. Evaporation of the Solar Corona into Interplanetary Space, *Hari K. Sen, May 1965.*
- No. 104. Data Previous to the International Geophysical Year 1: 5577 (OI) Line at Sacramento Peak, New Mexico, *G.J. Hernandez, May 1965.*
- No. 105. Auroral Zone Emissions Centered at 700 Cycles per Second, *Alv Egeland, Georg Gustafsson, Sven Olsen, Jules Aarons, and William Barron, May 1965 (REPRINT).*
- No. 106. Measurements in the Radiation Belts From Hitch-Hiker I, *F.R. Paolini, R. Giacconi, J.R. Waters, L. Katz, and D. Smart, June 1965 (REPRINT).*
- No. 107. Oxygen Atom Determination in the Upper Atmosphere by Chemiluminescence of Nitric Oxide, *Dan Golomb, N.W. Rosenberg, Carol Aharonian, J.A.F. Hill, and H.L. Alden, June 1965 (REPRINT).*
- No. 108. Indications of a Lunar Synodical Period in United States Observations of Sunshine, *Iver A. Lund, June 1965 (REPRINT).*
- No. 109. Photometry of the Solar Chromosphere, *Richard B. Dunn, June 1965.*
- No. 110. A Measure of Skill in Forecasting a Continuous Variable, *Irving I. Gringorten, June 1965 (REPRINT).*
- No. 111. Long-Term Variation of Solar Extreme Ultraviolet Fluxes, *L.A. Hall, W. Schweizer, and H.E. Hinteregger, June 1965 (REPRINT).*
- No. 112. The Inherent Smoothing of Whole-Disk Solar Indices, *Ralph Shapiro, June 1965 (REPRINT).*
- No. 113. A Catalogue of ARCAS-ROBIN Soundings, *Robert W. Lenhard and Arthur J. Kantor, June 1965.*
- No. 114. Spherical Harmonic Analysis, 2. A New Model Derived from Magnetic Observatory Data for Epoch 1960.0, *Paul F. Fougere, June 1965 (REPRINT).*
- No. 115. Seasonal Atmospheric Attenuation Measurements at 3.27 cm Wavelength, *John P. Castelli, June 1965.*
- No. 116. Rocket Optical Observation of a Day-time Aurora, *S.M. Silverman, John W.F. Lloyd, B.L. Cochran, and L.J. Nardone, July 1965 (REPRINT).*
- No. 117. Origin of Linear Elements on Mare Humorum, *John W. Salisbury, Vern G. Smalley, and Luciano B. Ronca, July 1965 (REPRINT).*
- No. 118. Infrared Spectral Emission and Its Application to the Detection of Organic Matter on Mars, *Graham R. Hunt, July 1965 (REPRINT).*
- No. 119. Chemical Release and Missile Exhaust Studies, *N.W. Rosenberg, Editor, July 1965 (SECRET).*
- No. 120. Molecular Oxygen Distribution in the Upper Atmosphere, 2, *A.S. Jursa, M. Nakamura, and Y. Tanaka, August 1965 (REPRINT).*
- No. 121. Jet-Stream Structure over the Central United States Determined from Aircraft Observations, *R.M. Endlich and G.S. McLean, August 1965 (REPRINT).*
- No. 122. Radio Star Scintillation During the July 20, 1963 Eclipse, *R.S. Allen, J.A. Klobuchar, W.C. Kidd, and H.E. Whitney, August 1965 (REPRINT).*
- No. 123. Giant Desiccation Polygons of Great Basin Playas, *James T. Neal, Capt, USAF, August 1965.*
- No. 124. Angels in Focus, *David Atlas, August 1965 (REPRINT).*
- No. 125. Solar Plasma Wind, Earth Currents and Diurnal Magnetic-field Variation, *H. Poeverlein, August 1965 (REPRINT).*
- No. 126. Ozone and Temperature Structure in a Hurricane, *Samuel Penn, August 1965 (REPRINT).*
- No. 127. N_2^+ Ions at Twilight, *William Swider, Jr., August 1965 (REPRINT).*
- No. 128. A Note on Density Variability at Constant Altitude vs. Constant Pressure, *P. Nee, A.E. Cole, I.I. Gringorten, and N. Sissenevine, August 1965 (REPRINT).*
- No. 129. Turbulent Atmospheric Parameters by Contaminant Deposition, *S.P. Zimmerman, August 1965 (REPRINT).*
- No. 130. Observational Study of Macroscopic Inhomogeneities in the Solar Atmosphere VI. Photospheric Oscillations and Chromospheric Structure, *Frank Q. Orrall, August 1965 (REPRINT).*

ENVIRONMENTAL RESEARCH PAPERS (Continued)

- No. 131. Monthly Atmospheric Structure, Surface to 80 km, *Arthur J. Kantor and Allen E. Cole, August 1965 (REPRINT).*
- No. 132. Empirical Relationships Between Gust Intensity in Clear-Air Turbulence and Certain Meteorological Quantities, *R.M. Endlich and G.S. McLean, August 1965 (REPRINT).*
- No. 133. Ozonesonde Observations Over North America, Volume 3, *Wayne S. Hering and Thomas R. Borden, Jr., Editors, August 1965.*
- No. 134. Project Sand Storm—An Experimental Program in Atmospheric Diffusion, *John H. Taylor, Lt. Colonel, USAF, Editor, September 1965.*

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY <i>(Corporate author)</i> Hq AFCRL, OAR (CRH) United States Air Force Bedford, Massachusetts		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP -
3. REPORT TITLE Project Sand Storm--An Experimental Program in Atmospheric Diffusion		
4. DESCRIPTIVE NOTES <i>(Type of report and inclusive dates)</i> Scientific Report. State of the art.		
5. AUTHOR(S) <i>(Last name, first name, initial)</i> TAYLOR John H., Lt. Colonel, Editor		
6. REPORT DATE September 1965	7a. TOTAL NO. OF PAGES 196	7b. NO. OF REFS 16
8a. CONTRACT OR GRANT NO. (AFSC) b. PROJECT AND TASK NO. 3850-01 c. DOD ELEMENT Basic Field 650 d. DOD SUBELEMENT Subfield 650A		9a. ORIGINATOR'S REPORT NUMBER(S) ERP No. 134 9b. OTHER REPORT NO(S) <i>(Any other numbers that may be assigned this report)</i> AFCRL-65-649
10. AVAILABILITY LIMITATION NOTICES Qualified requestors may obtain copies of this report from DDC. Other persons or organizations should apply to the Clearinghouse for Federal Scientific and Technical Information (CFSTI), Sills Building, 5285 Port Royal Road, Springfield, Virginia 22151.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Hq AFCRL, OAR (CRH) United States Air Force Bedford, Massachusetts	
13. ABSTRACT A series of field experiments in atmospheric diffusion was conducted at Edwards Air Force Base, California, in 1963. The primary feature which distinguished this series from similar experimental investigations was that instantaneous sources were studied. Puffs of tracer material were generated quasi-instantaneously by short bursts of small, horizontally fired, solid propellant rocket motors. Tracer samples were collected on a horizontal grid that had 350 sampling positions. All of the 43 experiments were conducted under thermally unstable atmospheric conditions. Analyses of the data identified the region of the turbulent energy spectrum which contains the eddies that are effective in diffusing the clouds. Eulerian measurements of turbulence are shown to be correlated with lateral rates of cloud growth. Downwind distributions of peak inhalation-level dosages were found to be quite irregular, with the anomalies unpredictable on the basis of measurable meteorological parameters. It was, nevertheless, possible to develop an operationally useful estimating equation relating peak dosages to distance from the source.		

Unclassified
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Atmospheric diffusion Turbulence Micrometeorology						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of link, rules, and weights is optional.