

AD 623836

AD

TECHNICAL REPORT ECOM-01377-1

DATA PROCESSING PLANS FOR

BALLISTIC WINDS STUDY

QUARTERLY REPORT NO. 1

CLEARINGHOUSE FOR FEDERAL SCIENTIFIC AND TECHNICAL INFORMATION			
Hardcopy	Microfiche		
\$ 1.00	\$ 0.50	12 pp	2
ARCHIVE COPY			

Code 1

By

FREDERICK P. OSTBY, JR.

OCTOBER 1965

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND • FORT MONMOUTH, N.J.

CONTRACT NO. DA 28-043 AMC-01377(E)

THE TRAVELERS RESEARCH CENTER, INC.
250 CONSTITUTION PLAZA, HARTFORD, CONNECTICUT 06103

DATA PROCESSING PLANS
FOR
BALLISTIC WINDS STUDY

Quarterly Report

Report No. 1

1 June 1965 to 31 August 1965

CONTRACT NO. DA 28-043 AMC-01377(E)

DA PROJECT NO. 1V0-25001-A-126-01

Prepared By

F. P. Ostby

THE TRAVELERS RESEARCH CENTER, INC.

HARTFORD, CONNECTICUT 06103

For

U. S. ARMY ELECTRONICS COMMAND,

FORT MONMOUTH, N. J.

ABSTRACT

Detailed computer program specifications were written for a preprocessor to perform various editing and minor calculating functions on a basic set of rawinsonde data. These functions are described.

A formulation was made of the several parts of the Conditional Relaxation Analysis Method (CRAM) program that will be used to analyze the data. The procedures for the initial guess, correction, solution of Poisson's Equation by relaxation, and smoothing are discussed.

1.0 INTRODUCTION

Contract DA 28-043 AMC-01377 (E) is for the development of an improved, automated technique for computing ballistic winds, temperature and density in mountainous terrain.

The initial effort under this contract has been the development of data processing procedures. Two computer programs are being written for the IBM 7094. A preprocessor program will perform various editing and preliminary calculating functions on the basic data (as supplied) to yield a set of data in a format acceptable to the subsequent objective analysis program. The analysis program will then yield virtual temperature, density, and wind analyses necessary for the various ballistic calculations. These two programs are described in more detail in the following section.

2.0 DESCRIPTION OF COMPUTER PROGRAMS

2.1 The Preprocessor

Basic meteorological data, to be supplied by the sponsor, will comprise rawinsonde reports for a network of twelve stations in the Ft. Huachuca, Arizona area taken several times a day during January and February of 1965. Before this data can be fed into an objective analysis program, editing, converting and calculating must be performed. The preprocessor program now being written will first perform any conversion necessary to make the data, generated by a Burroughs B-5000, acceptable to the IBM 7094. The horizontal coordinates of the balloon at each recorded altitude are given in relative terms as horizontal northward and eastward displacements from the launch site for each tenth of a minute for the first three minutes and every minute thereafter. The next function of the preprocessor will be to convert these displacements to absolute locations in the objective analysis grid system. This grid system will be based on the Universal Transverse Mercator (UTM) grid system with a grid interval of 10 km.

At the same time, the vertical coordinate of the balloon, given in height above sea level, will be converted to height above ground along its trajectory. For this purpose, a gridded terrain map is being constructed from maps prepared by The Army Map Service, Corps of Engineers, U.S. Army, Washington, D.C. with a basic grid interval of 2.5 km. This map will be placed on magnetic tape to use in these height determinations.

The next step is to compute zone wind components for each rawinsonde flight. The horizontal coordinates of the balloon and the elapsed time are computed for the base and top of each specified artillery zone. This computation is performed by interpolation using the previously-computed horizontal and vertical coordinates. The u- and v-zone wind components for each artillery zone are then computed from the horizontal distance travelled from the base to the top of the zone and the elapsed time within the zone.

The preprocessor will also compute the mean virtual temperature and mean density for each of the zones using the significant-level data supplied. For these determinations the zones are computed, not from height above ground, but rather, by reference to the height of the firing position.

In both the zone wind computations and the temperature and density computations, the location of the meteorological information for each zone is assigned the horizontal

coordinates of the midpoint of the particular zone taken along the balloon trajectory, thereby taking into account the drift of the balloon.

The final role of the preprocessor is to write an output tape which will contain the zone winds, temperature and density for each station along with its grid locations. This information will be used as input to the objective analysis program.

2.2 The Objective Analysis Program

Objective analysis is concerned with defining the spatial distribution of a variable at a set of regularly spaced grid points, given an irregularly spaced set of observations. The analysis technique to be used in this study is one developed and applied by Thomasell and Welsh¹ called CRAM (Conditional Relaxation Analysis Method). CRAM is based on a generalized version of Carstensen's relaxation method.² We are modifying an existing two-dimensional CRAM program to extend it to three dimensions. The horizontal grid length will be 10 km while the vertical grid interval will be a function of the artillery zone heights.

We begin with an initial guess of the variable to be analyzed over an evenly spaced field of grid points, $\phi(i, j, k)$. The horizontal coordinates are represented by i and j and the vertical coordinate by k . There are several ways to generate the initial guess. One, which we are considering, is to employ a surface-fitting technique to the data. That is, we wish to find the three-dimensional polynomial surface which best fits the observed field of data where the equation for the surface is of the form

$$\phi(x, y, z) = a_0 + a_1x + a_2y + a_3z + a_4x^2 + a_5y^2 + a_6z^2 \quad (2-1)$$

We will do this by using a screening regression technique to select those "predictors", x, y, z , etc., which significantly explain the variability of the "predictand", ϕ . The screening regression technique is outlined as follows.

From an array of possible predictors, the screening procedure selects first the one that has the highest linear correlation with the predictand in question. This predictor is

¹Thomasell, A., and J. G. Welsh, 1963: Studies of Techniques for the Analysis and Prediction of Temperature in the Ocean. Part I: The Objective Analysis of Sea-surface Temperature, Interim Report 7046-70, The Travelers Research Center, Inc.

²Progress Report, Fleet Numerical Weather Facility, U.S. Naval Postgraduate School, Monterey, Calif., April 1962.

then held constant, and partial-correlation coefficients between the predictand and each of the remaining predictors are examined; the predictor now associated with the highest coefficient is the second one selected. Additional predictors are chosen similarly until a selected predictor fails to explain a significant additional percentage of the remaining variance of the predictand.

The technique also gives the coefficients (a_0, a_1 , etc.) for each of the selected "predictors". The initial guess field is now generated from the derived equation.

The initial guess field is then "corrected". For each observation, the difference between the observed value and value computed for that location by interpolating among the initial guess values at the surrounding grid points is computed. This difference is then translated to the nearest grid point and added to that grid point as a correction to the initial guess. If more than one difference is translated to the same grid point an average correction is applied. These modified grid-point values are then "flagged". Also initial-guess grid-point values on the six perimeter surfaces of the analysis volume are considered to have fixed values and are also "flagged". For all "flagged" grid points, ϕ does not change during the subsequent relaxation process. (see Fig. 2-1)

The next step is to compute for all non-flagged grid points new values which satisfy the Poisson Equation,

$$\nabla^2 \phi(i, j, k) = F(i, j, k) \quad (2-2)$$

where ϕ is the analyzed value of the variable in question at grid point (i, j, k) , F is a forcing function defining some specified feature of the field of ϕ , and ∇^2 is the finite-difference Laplacian operator in three dimensions. The forcing function, F , is generally computed from the initial guess field as

$$\begin{aligned} F(i, j, k) = & \phi(i+1, j, k) + \phi(i-1, j, k) + \phi(i, j+1, k) + \phi(i, j-1, k) \\ & + \phi(i, j, k+1) + \phi(i, j, k-1) - 6\phi(i, j, k) \end{aligned} \quad (2-3)$$

The solution of Eq. (2-2) is accomplished by relaxation methods, as follows:

For each of the non-flagged grid points

(a) Compute the residual, R , for iteration n from




Fig. 2-1. Typical two dimensional field of $\phi(i, j)$. Grid points which have been flagged are denoted by $+$ and those not flagged are denoted by O . Station observations are denoted by $\textcircled{S}$ with an arrow pointing to the grid points for which values of ϕ are modified.

$$\begin{aligned}
R^n(i, j, k) = & \phi^n(i+1, j, k) + \phi^n(i, j+1, k) + \phi^n(i, j, k+1) \\
& + \phi^{n+1}(i-1, j, k) + \phi^{n+1}(i, j-1, k) \\
& + \phi^{n+1}(i, j, k-1) - 6\phi^n(i, j, k) - F(i, j, k).
\end{aligned} \tag{2-4}$$

(b) If $|R^n(i, j, k)| \leq \epsilon$ (where ϵ is the tolerance) proceed to the next grid point and return to (a) above.

(c) If $|R^n(i, j, k)| > \epsilon$, compute the (n+1) estimate of $\phi(i, j, k)$ from

$$\phi^{n+1}(i, j, k) = \alpha R^n(i, j, k) + \phi^n(i, j, k) \tag{2-5}$$

where α , the relaxation coefficient, is an input parameter. Then proceed to the next grid point and return to (a) above.

(d) When the first pass through the non-fixed grid points has been completed, return to (a) for a second pass if any residuals remain that exceed ϵ . Repeat passes as often as is required to reduce all residuals to ϵ or less.

The last phase of the analysis program is the application of a smoothing operator to eliminate from the analysis undesirable small-scale features introduced by small errors or by the analysis technique itself.

A simplified version of CRAM has been written for the IBM 1620 to compare the fields analyzed two-dimensionally with those analyzed three-dimensionally and to study the number of passes required as a function of the relaxation coefficient. We feel that three-dimensional CRAM analyses should be superior to the two-dimensional CRAM analyses as well as being computationally more efficient.

3.0 CONCLUSIONS

A preprocessing program has been coded to convert basic meteorological data into a form that can be processed efficiently by the objective analysis program.

The objective analysis program is a three-dimensional adaptation of the Conditional Relaxation Analysis Method (CRAM). This will be our principal analysis tool for studying ballistic corrections in mountainous terrain.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1 ORIGINATING ACTIVITY (Corporate author) The Travelers Research Center, Inc. 250 Constitution Plaza Hartford, Connecticut 06103		2 a. REPORT SECURITY CLASSIFICATION NA 2 b GROUP NA
3 REPORT TITLE Data Processing Plans for Ballistic Winds Study		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Quarterly Report No. 1, 1 June 1965 to 31 August 1965		
5. AUTHOR(S) (Last name, first name, initial) Ostby, Frederick P.		
6. REPORT DATE October 1965	7 a. TOTAL NO. OF PAGES 6	7 b. NO. OF REFS
8 a. CONTRACT OR GRANT NO DA 28-043 AMC-01377(E) b. PROJECT NO. 1V0-25001-A-126-01 c. d.	9 a. ORIGINATOR'S REPORT NUMBER(S) 9 b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) Technical Report ECOM 01377-1	
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC. This report has been released to CFSTI.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Atmospheric Sciences Laboratory U.S. Army Electronics Command Fort Monmouth, New Jersey	
13. ABSTRACT Detailed computer program specifications were written for a preprocessor to perform various editing and minor calculating functions on a basic set of rawinsonde data. These functions are described. A formulation was made of the several parts of the Conditional Relaxation Analysis Method (CRAM) program that will be used to analyze the data. The procedures for the initial guess, correction, solution of Poisson's Equation by relaxation, and smoothing are discussed.		

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Meteorology, Ballistic Winds, Artillery Metro Station						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER. If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, &c, & 8d. PROJECT NUMBER. Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY. Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification