

AFCRL-65-768
OCTOBER 1965
INSTRUMENTATION PAPERS, NO. 86



AIR FORCE CAMBRIDGE RESEARCH LABORATORIES

L. G. HANSCOM FIELD, BEDFORD, MASSACHUSETTS

The Short-Backfire Antenna

H. W. EHRENSPECK

CLEARINGHOUSE FOR FEDERAL SCIENTIFIC AND TECHNICAL INFORMATION			
Hardcopy	Microfilm		
\$ —	\$ —	//	
ARCHIVE COPY			

Code 1, 20

DDC
JAN 12 1966
DDC-IRA B

OFFICE OF AEROSPACE RESEARCH
United States Air Force



AFCL-65-768
OCTOBER 1965
INSTRUMENTATION PAPERS, NO. 86

MICROWAVE PHYSICS LABORATORY PROJECT 5635

AIR FORCE CAMBRIDGE RESEARCH LABORATORIES

L. G. HANSCOM FIELD, BEDFORD, MASSACHUSETTS

The Short-Backfire Antenna

H. W. EHRENSPECK

Reprinted from the PROCEEDINGS OF THE IEEE, Vol. 53, No. 8, pp. 1138-1140, August 1965

OFFICE OF AEROSPACE RESEARCH
United States Air Force



The Short-Backfire Antenna

Backfire antennas discussed, [1] to [6], are characterized by the multiple reflection of electromagnetic waves between two plane reflectors of different size, with the energy being bound to the longitudinal antenna axis by a slow wave structure. A sketch of a typical backfire antenna is shown in Fig. 1; M marks the larger, R the smaller of the two plane reflectors that are arranged parallel to each other and transverse to the longitudinal antenna axis. The D 's indicate a row of dipole elements that

constitutes the slow wave structure. The spacing L between the plane reflectors M and R is also the total axial length of the backfire antenna.

The open region between the plane reflectors acts similarly to a laser cavity [5], [6], with a standing-wave field distribution along the axis. The energy is radiated off through the aperture plane VV which passes through reflector R . Optimized conditions, which include optimum adjustment of height and spacing of the dipole elements D as well as of the size of the reflectors M and R , yield a gain increase of 6 dB above an

equal-length endfire antenna. For larger backfire antennas an even higher increase in gain is possible if stacked reflectors are used [5], [6].

Until very recently, only backfire antennas that were at least one wavelength long had been investigated. As a result of more recent work, however, an even shorter backfire antenna—in fact, the shortest one at all conceivable (approximately 0.5λ long)—has awakened an interest all its own. This "short-backfire" antenna is so com-




Fig. 1. Backfire antenna structure.

fact that practically all of the energy radiated into the cavity is intercepted by reflectors M and R . Over such a short distance, a slow-wave structure would be of no help in trapping the energy, and is therefore not used. The new antenna thus consists of only the plane reflectors M and R , spaced approximately half a wavelength apart, and the feed between them. Although its basic structure is still recognizably that of the backfire antenna, the short-backfire antenna differs so noticeably in design principles and specific constructions described, [1] to [6], as to justify a special name.


A photograph of an S-band short-backfire antenna model for 3000 MHz ($\lambda = 10.0$ cm) is shown in Fig. 2(a). The diameter of

the larger reflector (M) is 2.0λ ; the smaller reflector (R) is a circular metal disk 0.4λ in diameter, spaced 0.5λ from the larger reflector. It offers the advantage of being insensitive to the polarization of the feed, which may consequently be linear in any direction, circular or crossed. The width of the rim surrounding reflector M is 0.25λ . Either reflector could be made from solid or perforated sheet material, or any other structural design equivalent in reflectivity.



The configuration of the short-backfire antenna seems to be somewhat similar to that of the "reflex" antenna developed by G. v. Trentini [7]. However, the two antennas are based on quite different principles and also differ essentially in structure. The reflex antenna applies multiple reflection between a total reflector and a partial one of equal area that usually consists of a number of parallel metal rods or strips, the radiating aperture being defined by the structure and reflectivity of the partial reflector. In contrast the two reflectors of the short-backfire antenna (M and R) differ radically in area (area ratio between 15-to-1 and 30-to-1), with the smaller reflector (R) in its simplest form consisting of a solid metal disk; the radiating aperture forms in the area surrounding the smaller reflector and extends—undisturbed by metal rods or strips—even beyond the cross-sectional area of the larger reflector, as an experimental nearfield study has shown.

The gain of the short-backfire antenna of Fig. 2(a) was measured to be 13.1 dB above a dipole, or 15.2 dB above isotropic at 3000 MHz. Its 360° patterns in E and H plane are presented in Fig. 2(b). Rather remarkably, all sidelobes in the patterns are at least 20 dB below the maximum in the E as well as in the H plane, and the backlobe is far below 25 dB, the lowest level that shows in these patterns; further measurements indicated that it is in fact more than 30 dB below the maximum. These "clean" patterns were obtained over a frequency range of 1-to-1.4. Because the relatively high gain of the short-backfire is mainly due to the higher directivity in the H plane, this antenna type is especially suitable for the reception of horizontally polarized fields on or near ground.

The progress achieved with the new antenna structure can best be demonstrated by comparing it with the Yagi as the most frequently used endfire. A conventional Yagi with a gain of 15 dB isotropic has to be about 4.0λ long, and needs 15 to 20 dipole elements. The patterns of gain-optimized Yagis have relatively high sidelobes, however, especially in their H -plane patterns. To obtain patterns comparable to the low side—and backlobe patterns of the short-backfire, the number of reflectors and the axial length of the Yagi (number of directors) would have to be markedly increased, and the directors would require tapering to lower heights toward the radiating antenna termination. In Fig. 3 the short-backfire antenna (a) and Yagi (b), both constructed to have the same gain and about the same pattern quality, are shown to the same scaling factor so that they can be directly compared in size and material requirements. Although the reflector area of the short-backfire antenna is larger than that of the Yagi, and in addition a second small reflector is needed, the antenna length is less than one-tenth that of



(a)



(b)

Fig. 2. S-band model of short-backfire antenna. (a) Antenna structure. (b) E - and H -plane pattern for 3000 MHz.




Fig. 3. Comparison of the physical structures of a short-backfire antenna and a Yagi with approximately the same patterns and gain (15 dB above isotropic). (a) Short-backfire antenna. (b) Yagi antenna.

the Yagi and the number of dipole elements is only 1 in contrast to 27 elements for the Yagi (including 5 reflector dipoles not shown).

H. W. EHRENSPECK
Air Force Cambridge Research Labs.
L. G. Hanscom Field,
Bedford, Mass.

REFERENCES

- [1] H. W. Ehrenspeek, "The Backfire Antenna, a New Type of Directional Line Source," *Proc. IRE (Correspondence)*, vol. 48, pp. 109-110, January 1960.
- [2] F. J. Zucker, "Surface and Leaky-Wave Antennas," in *Antenna Engineering Handbook*, H. Jasik, Ed. New York: McGraw-Hill, 1961, ch. 16.
- [3] H. W. Ehrenspeek, "Reflection Antenna Employing Multiple Director Elements and Multiple Reflection of Energy to Effect Increased Gain," U. S. Patent No. 3,122,745, February 1964. (Additional patents applied for.)

- [4] J. A. Strom and H. W. Ehrenspeek, "Backfire Antennas for SHF, UHF, and VHF Bands," AFCRL-63-114, AF Cambridge Research Lab., Bedford, Mass., April 1963.
- [5] H. W. Ehrenspeek, "The Backfire Antenna: New Results," *Proc. IEEE (Correspondence)*, vol. 53, pp. 639-641, June 1965.
- [6] F. J. Zucker, "The Backfire Antenna: A Qualitative Approach to Its Design." To be published shortly.
- [7] G. v. Trentini, "Partially Reflecting Sheet Arrays," *IRE Trans. on Antennas and Propagation*, vol. AP-4, pp 66-671, October 1956.

Reprinted from the PROCEEDINGS OF THE IEEE

VOL. 53, NO. 8, AUGUST, 1965

pp. 1138-1140

Copyright 1965, and reprinted by permission of the copyright owner

PRINTED IN THE U.S.A.

INSTRUMENTATION PAPERS
(Formerly: Instrumentation for Geophysics and Astrophysics)

- No. 1. A Digital Electronic Data Recording System for Pulse-Time Telemetry, *Gilbert O. Hall, Feb 1953.*
- No. 2. A Rocket-Borne Equipment for the Measurement of Infrared Radiation, *R. M. Slavin, Feb 1953.*
- No. 3. Balloon-Borne Conductivity Meter, *S. C. Coroniti, A. Nazarek, C. S. Stergis, D. E. Kotas, D. W. Seymour and J. V. Werne, Dec 1954.*
- No. 4. Magnetic Compensation of Aircraft, *J. McClay and B. Schuman, Aug 1955.*
- No. 5. Lovotron-A Low Voltage Triggered Gap Switch, *E. H. Cullington, W. G. Chace and R. L. Morgan, Sep 1955.*
- No. 6. Balloon-Borne Air Sampling Device, *Charles W. Chagnon, Apr 1957.*
- No. 7. Instrumentation for Studies of the Exploding Wire Phenomenon, *W. G. Chace and E. H. Cullington, Aug 1957.*
- No. 8. Device for Lowering Loads from High-Altitude Balloons, *W. C. Wagner and F. X. Doherty, Jul 1958.*
- No. 9. Equipment and Techniques for In-Flight Deployment of Long Train Instrumentation Packages from High Altitude Balloons, *Arlo E. Gilpatrick and Romain C. Fruge, Sep 1958.*
- No. 10. Study of a Phosphor Light Pulsar, *Michael R. Zatzick, Sep 1960.*
- No. 11. Study of a Pulsed Logarithmic Photometer, *Michael R. Zatzick, Sep 1960.*
- No. 12. Theoretical Analysis of the PAR-Scope: An Oscilloscope Display for Weather Radars, *Edwin Kessler, III, Jul 1959.*
- No. 13. Evaluation of Visual Distance Computer, CP-384(XD-1), *P. I. Hershberg, Apr 1960.*
- No. 14. Hypsometer for Constant Level Balloon, *W. C. Wagner, Jun 1960.*
- No. 15. Magnetic Photomultiplier with Large Cathode for Extreme Ultraviolet, *L. A. Hall and H. E. Hinteregger, Dec 1960.*
- No. 16. AIDE - Altitude Integrating Device, Electronic, *P. I. Hershberg, J. R. Griffin and R. H. Guenther, Dec 1960.*
- No. 17. Switching Devices for Very High Currents, *E. H. Cullington and W. G. Chace, April 1961.*
- No. 18. Cedar Hill Meteorological Research Facility, *D. W. Stevens, Jun 1961.*
- No. 19. Evaluation of Control Monitor AN/QGA 11 Prototype, *R. S. Menchel, Aug 1961.*
- No. 20. A Microwave Refractometer with Fast Response and Absolute Digital Recording, *R. H. Shaw and R. M. Cunningham, Mar 1962.*
- No. 21. Superpressure Balloon for Constant Level Flight, *L. Gruss, Jul 1962.*
- No. 22. Measurement Range Required of Meteorological Equipment, *A. Court and H. Salmela, Aug 1962.*
- No. 23. Proportional Counter Spectrometer for Solar X-Rays Between 1 and 10 Angstroms, *L. Heroux, J. E. Manson, and R. Smith, Dec 1962.*
- No. 24. A Simplified Sonic Anemometer for Measuring the Vertical Component of Wind Velocity, *J. Chandran Kaimal, Jan 63.*
- No. 25. Evaluation of Modification to Antenna of Rawin Set AN/GMD-2, *Konstantin Pocs, Jan 63.*
- No. 26. Evolution of the Design of the Anna I Satellite Optical Beacon, *T. Wirtanen, Feb 63.*
- No. 27. Seismic Model Impactor, *K. C. Thomson and J. A. Hill, Aug 63.*
- No. 28. Error Analysis of the Modified Humidity-Temperature Measuring Set AN/TMQ-11, *R. W. Lenhard, Jr., Major, USAF, and B. D. Weiss, Aug 63.*
- No. 29. Evaluation of a Varactor Diode Parametric Amplifier for Rawin Set AN/GMD-2, *Konstantin Pocs, Sep 1963.*
- No. 30. The Hydromagnetic Wave Tube, *R. E. Murphy and M. H. Bruce, Sep 1963.*
- No. 31. A Time-of-Flight Mass Spectrometer Adapted for Studying Charge Transfer, Ion Dissociation, and Photoionization, *W. Hunt, Jr., et al., Sep 1963.*
- No. 32. Moire Fringe Measuring System for Far Infrared Interferometric Spectrometer, *E. V. Loewenstein, Sep 1963.*
- No. 33. Opposed Anvil Basic Design Considerations, *R. E. Riecker, 1/Lt USAF, Dec 1963.*
- No. 34. New Shear Apparatus for Temperatures of 1000°C and Pressures of 50 kb, *R. E. Riecker, 1/Lt USAF, K. E. Seifert, 1/Lt USAF, Nov 1963.*
- No. 35. Accuracy of Meteorological Data Obtained by Tracking the ROBIN With MPS-19 Radar, *Robert W. Lenhard, Jr., Major, USAF, Margaret P. Doody, Dec 1963.*
- No. 36. An Application of Induction Heating to Rock Deformation Apparatus, *R. E. Riecker, 1/Lt, USAF, Mar 1964.*
- No. 37. A Monopole Phased-Array Feed for Spherical Reflectors, *W. G. Mavroides, L. S. Dorr, April 1964.*
- No. 38. Equipment and Techniques for Low Temperature Electron Irradiations, *L.F. Lowe, C. Jimenez, and E.A. Burke, April 1964 (REPRINT).*
- No. 39. Lunar Thermal Emission Measurements and Related Antenna Considerations, *John P. Castelli, April 1964 (REPRINT).*
- No. 40. Continuous Zone-Refining Apparatus, *John K. Kennedy, April 1964 (REPRINT).*

INSTRUMENTATION PAPERS (Continued)

- No. 41. Improved Closed-System Evaporation Crystallizer, *John L. Sampson and Mary A. DiPietro*, May 1961 (REPRINT).
- No. 42. Calibration of a Flyable Mass Spectrometer for N and O Atom Sensitivity, *R.S. Narcisi, H.J. Schiff, J.E. Morgan and H.A. Cohen*, June 1961 (REPRINT).
- No. 43. A Preliminary Evaluation of the Cricketsonde Rocket System, *Konstantins Pocs*, June 1964.
- No. 44. New Shear Apparatus for Temperatures of 1000°C and Pressures of 50 Kilobars, *R.E. Riecker*, August 1964 (REPRINT).
- No. 45. Reflection Correction for Thermal Neutron Spectra Derived from Transmission Data, *E.A. Burke and L.F. Lowe*, August 1964 (REPRINT).
- No. 46. A Prototype Lunar Transponder, *Mahlon S. Hunt*, August 1964 (REPRINT).
- No. 47. Automatic Plotting of Spin-Wave Instability Threshold Data, *Tom G. Purnhagen, Capt, USAF*, August 1964 (REPRINT).
- No. 48. Logical Techniques for Glottal Source Measurements, *John L. Ramsey, 1/Lt, USAF*, August 1964.
- No. 49. An Ultrastable Microwave Radiometer, *William B. Goggins, Jr., Capt, USAF*, September 1964.
- No. 50. Impurities in a Vacuum, *Jerome H. Bloom, Charlotte E. Ludington, and Robert L. Phipps*, May 1964.
- No. 51. Digital Readout of Oscilloscope Sweep Delay Times, *K.E. McGee and W.W. Hunt, Jr.*, October 1964 (REPRINT).
- No. 52. High Pressure Thrust Bearings: An Application, *R.E. Riecker and D.L. Pendleton*, November 1964.
- No. 53. A Method for Electrocutting Single Crystals of Metals and Electropolishing the Exposed Crystalline Face, *Bernard Rubin and John J. O'Connor*, December 1964.
- No. 54. Comparison of Bivane and Sonic Techniques for Measuring the Vertical Wind Component, *J.C. Kaimal, H.E. Cramer, F.A. Record, J.E. Tillman, J.A. Businger, and M. Miyake*, December 1964 (REPRINT).
- No. 55. Experiences with the Impedance Probe on Satellites, *O.C. Haycock, K.D. Baker and J.C. Ulwick*, January 1965 (REPRINT).
- No. 56. Silicon Current Amplifier for Microampere Current Levels, *B. Buchanan, S. Roosild, and R. Dolan*, February 1965 (REPRINT).
- No. 57. A Multi-Level Radar Storm Contour Mapper, *William E. Lamkin and David Atlas*, April 1965.
- No. 58. Nanosecond Pulses of Very Low Impedance, *Heinz J. Fischer*, April 1965.
- No. 59. An Operational Amplifier Circuit for Characterization of Negative-Conductance Devices, *Virgil E. Vickers*, April 1965 (REPRINT).
- No. 60. Multiband Spectral System for Reconnaissance, *Carlton E. Molineux*, April 1965 (REPRINT).
- No. 61. Operating Characteristics of a Commercial Resistance-Strip Magnetic Electron Multiplier, *W.W. Hunt, Jr., K.E. McGee, and M.J. Kennedy*, May 1965 (REPRINT).
- No. 62. Frequency Stability in Dielectric Resonators, *M.R. Stiglitz and J.C. Sethares*, May 1965 (REPRINT).
- No. 63. ANNA Satellite Yields Photogrammetric Parameters, *Owen W. Williams*, June 1965 (REPRINT).
- No. 64. Heat Transfer Considerations in the Temperature Control of Instrumentation Packages at High Altitudes, *Arnold Piacentini, Kenneth H. Lindenfelser, 1/Lt, USAF, and Darrel E. Dube, 1/Lt, USAF*, June 1965.
- No. 65. Vacuum Ultraviolet Light Sources: New Excitation Unit for the Rare Gas Continua, *R.E. Huffman, J.C. Larrabee, and Derek Chambers*, June 1965.
- No. 66. The Compensation of Two-Beam Interferometers, *W.H. Steel*, June 1965.
- No. 67. A Laser Fog Disdrometer, *Bernard A. Silverman, Brian J. Thompson, and John H. Ward*, June 1965 (REPRINT).
- No. 68. Radiochemical Procedures for Selected Radionuclides in Environmental Samples, *Joseph Pecci, Peter J. Drevinsky, Edward Couble, Noreen A. Dimond, Marvin I. Kalkstein, and Anahid Thomasian*, June 1965.
- No. 69. Evaluation of the T-755/GMQ-20 Wind Speed and Direction Transmitter, *Russell M. Peirce, Jr.*, June 1965.
- No. 70. A Laser for an Earth-Based Satellite Illuminator, *Robert L. Hiff*, June 1965.
- No. 71. A Unique Scintillation Rate Counter for Ionospheric Studies, *Frederick F. Slack and John P. Mullen*, June 1965.
- No. 72. Differential Thermal Analysis (DTA) of Oxide Systems in Air to 1620°C at Atmospheric Pressure, *Cortland O. Dugger*, June 1965.
- No. 73. Automatic Camera System for Solar Corona Photography, *D.J. Davis, Jr., W.R. McCann, V.A. Remillard, P. Beaudoin, and A. Thomas*, July 1965 (REPRINT).
- No. 74. A Direct Calibration of a Birefringent Photometer, *G.J. Hernandez and E.L. Layman*, August 1965 (REPRINT).
- No. 75. A Ray-Tracing Program for Birefringent Filters, *J.M. Beckers, and R.B. Dunn*, August 1965.

INSTRUMENTATION PAPERS (Continued)

- No. 76. Vocal-Response Synthesizer, *Caldwell P. Smith, August 1965 (REPRINT).*
- No. 77. The Backfire Antenna: New Results, *Hermann W. Ehrenspeek, September 1965 (REPRINT).*
- No. 78. A Method for Accurately Measuring the Vertical Electric Field Strength of a Propagating VLF Wave.
R.P. Harrison and E.A. Lewis, September 1965 (REPRINT).
- No. 79. A System for the Determination of the Vertical Wind Profile From an Aircraft, *James F. Morrissey, September 1965.*
- No. 80. A Parapropagation Pattern Classifier, *Herbert A. Glucksman, September 1965 (REPRINT).*
- No. 81. Pressure Gradients in Bridgman Anvil Devices, *L.C. Toule and R.E. Riecker, September 1965.*
- No. 82. New Excitation Unit for Rare Gas Continua in the Vacuum Ultraviolet. *R.E. Huffman, J.C. Larrabee,
and D. Chamber, October 1965 (REPRINT).*
- No. 83. Photographing Satellite-Reflected Laser Pulses for Geodetic Stereo Triangulation, *Robert L. Hiff,
October 1965 (REPRINT).*
- No. 84. An Attempt to Reduce the Gas Load in an Ultrahigh-Vacuum Chamber. *Joel E.M. Adler, October 1965 (REPRINT).*
- No. 85. High Temperature Furnace System B-208-R, *Robert C. Marshall, Charles E. Ryan, Dennis P. Considine, and
John J. Hawley, October 1965.*
- No. 86. The Short-Backfire Antenna, *H.W. Ehrenspeek, October 1965 (REPRINT).*

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) Hq AFCRL, OAR (CRD) United States Air Force Bedford, Massachusetts		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE The Short-Backfire Antenna		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Scientific Report. Interim.		
5. AUTHOR(S) (Last name, first name, initial) EHRENSPECK, H. W.		
6. REPORT DATE October 1965	7a. TOTAL NO. OF PAGES 12	7b. NO. OF REFS 7
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S) AFCRL-65-768	
b. PROJECT AND TASK NO. 5635-02		
c. DOD ELEMENT 61445014	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) AFCRL-65-768	
d. DOD SUBELEMENT 681305		
10. AVAILABILITY/LIMITATION NOTICES Requests for additional copies by Agencies of the Department of Defense, their contractors, and other government agencies should be directed to DDC. Limitation: Reproduction in whole or in part is permitted for any purpose of the U. S. Government.		
11. SUPPLEMENTARY NOTES Reprinted from the Proceedings of the IEEE, Vol. 53, No. 8, pp. 1138-1140, August 1965		12. SPONSORING MILITARY ACTIVITY Hq AFCRL, OAR (CRD) United States Air Force Bedford, Massachusetts
13. ABSTRACT A new type of antenna, the "Short Backfire," consists of two plane reflectors, spaced approximately half a wavelength apart, and the feed between them. It develops a high gain and its patterns have a very low sidelobe level.		

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	Directional Antenna High-gain Low Sidelobe Level						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoI Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.