

ESD-TR-66-95

MTR-160

ESD RECORD COPY

RETURN TO
SCIENTIFIC & TECHNICAL INFORMATION DIVISION
(ESTI), BUILDING 1211

ESD ACCESSION LIST

ESTI Call No. **AL 51135**

Copy No. 1 of 1 cys.

HIGH-ALTITUDE REENTRY DRAG EFFECTS

JUNE 1966

S. Sharensen

Prepared for

DEPUTY FOR ENGINEERING & TECHNOLOGY
DIRECTORATE OF RADAR & OPTICS
ELECTRONIC SYSTEMS DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
L. G. Hanscom Field, Bedford, Massachusetts



Advanced Research Projects Agency
Project Defender
ARPA Order No. 596

Distribution of this document is unlimited.

Project 8090

Prepared by

THE MITRE CORPORATION
Bedford, Massachusetts

Contract AF19(628)-5165

AD0634390

CSRRR

This document may be reproduced to satisfy official needs of U.S. Government agencies. No other reproduction authorized except with permission of Hq. Electronic Systems Division, ATTN: ESTI.

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Do not return this copy. Retain or destroy.

HIGH-ALTITUDE REENTRY DRAG EFFECTS

JUNE 1966

S. Sharensen

Prepared for

DEPUTY FOR ENGINEERING & TECHNOLOGY
DIRECTORATE OF RADAR & OPTICS
ELECTRONIC SYSTEMS DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
L. G. Hanscom Field, Bedford, Massachusetts



Advanced Research Projects Agency
Project Defender
ARPA Order No. 596

Distribution of this document is unlimited.

Project 8090

Prepared by

THE MITRE CORPORATION
Bedford, Massachusetts
Contract AF19(628)-5165

FOREWORD

This research was supported by the Advanced Research Projects Agency (Project Defender), and was monitored by ESD under Contract No. AF 19(628)-5165.

REVIEW AND APPROVAL

Publication of this technical report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

R. G. McConnell
for H. M. BYRAM
Project Officer

ABSTRACT

The effect of atmospheric drag on the trajectory of a reentry body is considered. The analysis is valid in the high altitude regime. Results are presented as the differential displacement and velocity from the vacuum trajectory for various values of ballistic coefficient.

LIST OF ILLUSTRATIONS

<u>Figure Number</u>		<u>Page</u>
1	ΔS vs. Altitude	6
2	$\frac{d(\Delta S)}{dt}$ vs. Altitude	7
3	$\frac{d^2(\Delta S)}{dt^2}$ vs. Altitude	8
4	Atmospheric Density - $\rho(h)$	9
5	$\int_{h_o}^h \rho(h) dh \frac{LBS}{FT^2}$	10
6	$\int_{h_o}^h dh' \int_{h_o}^{h'} \rho(h') \frac{LBS}{FT}$	11

TABLE OF SYMBOLS AND UNITS

h = altitude - feet

$\rho(h)$ = atmospheric density - pounds per cubic foot

S = distance along trajectory - feet

v = velocity along trajectory - feet per second

β = ballistic coefficient - pounds per square foot


θ_E = reentry angle

t = time - seconds

The differential displacement of a re-entering body due to atmospheric drag is considered in this report. The situation considered is shown below. The body enters the atmosphere at an angle θ_E from the horizontal with an initial velocity v_0 . The altitude, measured from the earth's surface, is h . The altitude h_0 is chosen large enough such that:

$$\rho(h_0) \approx 0 \quad (1)$$

where $\rho(h)$ is the atmospheric density as a function of altitude.



Neglecting the earth's curvature, the effect of earth gravity and atmospheric drag, the trajectory of the re-entering body is a straight line and the displacement along the trajectory is given by:

$$S = \frac{h_0 - h}{\sin \theta_E} \quad (2)$$

where

$$S = v_o t \quad (3)$$

Including, now, the effect of drag (but not lift), the classical equation for deceleration due to drag is:

$$- \frac{dv}{dt} = \frac{1}{2\beta} \rho(h) v^2 \quad (4)$$

Here v is the instantaneous velocity of the vehicle and β the ballistic coefficient.

Constraining the analysis to the high altitude re-entry regime where changes in v are small, the drag force can be calculated by assuming $v \approx v_o$ in this regime.

From equations (2) and (3):

$$dt = - \frac{dh}{v_o \sin \theta_E} \quad (5)$$

Substituting equation (4) for dt , and setting $v \approx v_o$:

$$\int_{v_o}^v dv = \int_{h_o}^h \frac{v_o}{2\beta \sin \theta_E} \rho(h) dh \quad (6)$$

$$v - v_o = \frac{v_o}{2\beta \sin \theta_E} \int_{h_o}^h \rho(h) dh \quad (7)$$

$$v = v_o + \frac{v_o}{2\beta \sin \theta_E} \int_{h_o}^h \rho(h) dh \quad (8)$$

But:

$$v = \frac{dS}{dt} \quad (9)$$

Therefore:

$$dS = v_o dt + \frac{v_o dt}{2\beta \sin \theta_E} \int_{h_o}^h \rho(h) dh \quad (10)$$

from equation (8). Substituting from equation (5):

$$dS = v_o dt - \frac{dh}{2\beta(\sin \theta_E)^2} \int_{h_o}^h \rho(h) dh \quad (11)$$

Integrating equation (11):

$$\int_{S_o}^S dS = v_o \int_{t_o}^t dt - \frac{1}{2\beta(\sin \theta_E)^2} \int_{h_o}^h dh' \int_{h_o}^{h'} \rho(h') dh' \quad (12)$$

But:

$$S_o = 0 \quad (13)$$

at $h = h_o$. Thus

$$S = v_o(t - t_o) - \frac{1}{2\beta(\sin \theta_E)^2} \int_{h_o}^h dh' \int_{h_o}^{h'} \rho(h') dh' \quad (14)$$

Now, in the absence of the atmosphere, equation (4) reduces to:

$$\frac{dv}{dt} = 0 \quad (15)$$

and the displacement is simply:

$$S' = v_o (t - t_o) \quad (16)$$

Subtracting (14) from (16) gives the differential displacement ΔS :

$$\Delta S = S' - S = \frac{1}{2\beta(\sin \theta_E)^2} \int_{h_o}^h dh' \int_{h_o}^{h'} \rho(h') dh' \quad (17)$$

For comparison the velocity, $\frac{d(\Delta S)}{dt}$, and the deceleration, $\frac{d^2(\Delta S)}{dt^2}$, are derived:

$$\frac{d(\Delta S)}{dt} = \frac{1}{2\beta(\sin \theta_E)^2} \frac{dh}{dt} \int_{h_o}^h \rho(h) dh \quad (18)$$

From equations (2) and (3):

$$\frac{dh}{dt} = - \sin \theta_E \frac{dS}{dt} \quad (19)$$

or

$$\frac{dh}{dt} = - \sin \theta_E v_o \quad (20)$$

Therefore:

$$\frac{d(\Delta S)}{dt} = - \frac{v_o}{2\beta \sin \theta_E} \int_{h_o}^h \rho(h) dh \quad (21)$$

But:

$$\int_{h_o}^h \rho(h) dh < 0 \quad (22)$$

Therefore:

$$\frac{d(\Delta S)}{dt} = \frac{v_o}{2\beta \sin \theta_E} \left| \int_{h_o}^h \rho(h) dh \right| \quad (23)$$

The deceleration is found from a second differentiation:

$$\frac{d^2(\Delta S)}{dt^2} = \frac{v_o}{2\beta \sin \theta_E} \frac{dh}{dt} \rho(h) \quad (24)$$

or:

$$\frac{d^2(\Delta S)}{dt^2} = - \frac{v_o^2}{2\beta} \rho(h) \quad (25)$$

The results of this analysis are presented in Figure 1, as ΔS vs. h for three different values of β . For comparison, $\frac{d(\Delta S)}{dt}$ and $\frac{d^2(\Delta S)}{dt^2}$ are presented in Figures 2 through 3. Since this analysis applies only in the region where the velocity change is small, the curves are terminated at the appropriate lowest altitude for the particular value of β . The atmospheric density profile used is known in Figure 4*. The first and second integrals of the density profile are given in Figures 5 and 6.

S. Sharensen
S. Sharensen

SS/rjs

* P. J. Nawrocki and R. Papa, Atmospheric Processes, Prentice-Hall, Inc., New Jersey, 1963.




Figure 1
 ΔS VS ALTITUDE θ = REENTRY ANGLE β = BALLISTIC COEFF. - PSF




Figure 2

$\frac{d(\Delta S)}{dt}$ VS. ALTITUDE θ_E = REENTRY ANGLE
 5500 NM TRAJECTORY β = BALLISTIC COEFF. - PSF

1B-17.746




Figure 3

$\frac{d^2(\Delta S)}{dt^2}$ VS ALTITUDE θ_E = REENTRY ANGLE

1B-17.745

5500 NM TRAJECTORY β = BALLISTIC COEFF. - PSF




Figure 4
ATMOSPHERIC DENSITY - $\rho(h)$

IB-17,744




Figure 5

1B-17.743

$$\int_{h_0}^h \rho(h) dh \frac{\text{LBS}}{\text{FT}^2}$$




Figure 6

$$\int_{h_0}^h \int_{h_0}^{h'} \rho(h') \frac{\text{LBS}}{\text{FT}}$$

IB-17.742

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) The MITRE Corporation Bedford, Massachusetts		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE High-Altitude ReEntry Drag Effects			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5. AUTHOR(S) (Last name, first name, initial) Sharensen, Stanley			
6. REPORT DATE June 1966		7a. TOTAL NO. OF PAGES 16	7b. NO. OF REFS 1
8a. CONTRACT OR GRANT NO. AF 19(628)-5165		9a. ORIGINATOR'S REPORT NUMBER(S) ESD-TR-66-95	
b. PROJECT NO. 8090		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) MTR-160	
c.			
d.			
10. AVAILABILITY/LIMITATION NOTICES Distribution of this document is unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Advanced Res. Proj. Agency, Proj. Defender, ARPA Order No. 596; Deputy for Eng. & Tech., Dir. of Radar and Optics, Elec. Sys. Div., L. G. Hanscom Fld., Bedford, Mass.	
13. ABSTRACT The effect of atmospheric drag on the trajectory of a reentry body is considered. The analysis is valid in the high altitude regime. Results are presented as the differential displacement and velocity from the vacuum trajectory for various values of ballistic coefficient.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Satellites Reentry, at High Altitudes Atmospheric Drag, Effects on Trajectory						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.