

NOLC REPORT 670

10 AUGUST 1966

NOLC REPORT 670

AD 633303

ATTENUATION OF Ka-BAND ENERGY BY SNOW AND ICE

J. W. BATTLES

D. E. CRANE

CLEARINGHOUSE FOR FEDERAL SCIENTIFIC AND TECHNICAL INFORMATION			RESEARCH DEPARTMENT
Hardcopy	Microfiche		
\$ 1.00	\$ 0.50	13 pp	50
ARCHIVE COPY			

code 1

Distribution of this document
is unlimited.



NAVAL ORDNANCE LABORATORY CORONA
CORONA, CALIFORNIA

NAVAL ORDNANCE LABORATORY CORONA

E. B. JARMAN, CAPT., USN
Commanding Officer

F. S. ATCHISON, Ph. D.
Technical Director

FOREWORD

The study described in this report is part of a continuing effort to obtain data that will be valuable for radiometer mapping at millimeter frequencies. The work was funded by WEP-TASK R360-FR-104/211-1/R011-01-01 and AIR 360-016/211-1/S061.

C. J. HUMPHREYS
Head, Research Department

ABSTRACT

Measurements of the attenuation of electromagnetic energy by snow and the reflection of radiation from snow and ice were made by using an interferometer and manufactured snow and ice in an environmental chamber under closely controlled conditions. The ambient temperature was held at -14°F for all measurements. Snow and ice attenuation and reflection measurements are tabulated for various snow densities covering the range from 32 to 39 GHz. Results show that packed snow and greater density produce less attenuation.

CONTENTS

	<u>Page</u>
Introduction	1
Description of Apparatus	1
Description of Snow	3
Results	3
Conclusions	9
References	10

INTRODUCTION

The measurements described herein are a continuation of the work reported in Reference 1. The earlier report describes how the transmission and reflection properties of snow are affected by a change in temperature. It was the object of the study described in this report to determine how these same properties are affected by the variation of the snow density at a fixed temperature. The results of these measurements can be used in evaluating the effects of snow or ice coverings on radar backscatter or radiometer measurements.

DESCRIPTION OF APPARATUS

The design of the interferometer used to obtain the measurements is based on the one described in References 1 and 2. However, to prevent the cold temperature from affecting the calibration of the attenuators, the system was redesigned so that the standing-wave detector, the phase shifter, and the attenuators were outside the Tenney walk-in cold chamber. Figure 1 shows the arrangement of the interferometer with respect to the cold chamber.

The radiation from the klystron is divided into two waveguide paths by means of a directional coupler, and the waveguide with the most power is used to transmit the radiation into the chamber. The radiation is then collimated by a horn-lens system and transmitted through the snow sample to a horn and propagated out of the chamber through the waveguide connected to the other branch of the directional coupler. Between the waveguide horn and the directional coupler are an isolator, a hybrid T standing-wave detector, an attenuator, and a phase shifter. The isolator prevents any radiation from the branch of the coupler from entering the chamber; the attenuator matches the amplitude of the radiation coming directly from the klystron with that transmitted through the snow sample; and the phase shifter is used to adjust the phase of the radiation from the klystron so that a null condition can be set up in the detector arm of the hybrid T.

This null condition is set up both with the sample of snow in place and with the snow removed. The difference in readings on the attenuator under the two conditions gives the amount of attenuation loss caused by the snow sample. The reflection loss is measured by replacing the




FIGURE 1. Setup for Attenuation Measurements

mirror with a smooth snow sample of an equivalent size. The difference between the attenuator readings with the snow and with the mirror gives the reflection loss.

DESCRIPTION OF SNOW

The snow was made by first cooling the cold chamber to below freezing and then spraying a fine mist of water into it. Figure 2 shows a microphotograph of a sample of the crystals formed on the chamber floor and in the air when the chamber was cooled to about 20° F before being sprayed with cold water. Figures 3-6 are microphotographs of the samples of snow formed when the chamber was cooled to -50° F and sprayed with water. Cold water was used to produce the snow shown in Figure 4, and hot water was used to obtain that shown in Figures 3, 5, and 6. The dimensions of the largest sphere in this group of figures is of the order of a hundredth of an inch, whereas some of the crystals in Figure 2 were as large as one-sixteenth of an inch. It is obvious from these microphotographs that the man-made snow used for the measurements more closely resembles very small hail or sleet than it does natural snow flakes.

RESULTS

All measurements were taken at -14° F. The attenuation measured for the different densities and types of snow are given in Table 1.

TABLE 1. Attenuation Caused by Snow and Ice

Type	Thickness, in.	Density, g/in. ³	Loss, dB	Fig. No.
Fine loose snow	5.5	3.35	2.5	3
Fine snow with local packed areas	5.5	5.35	7.2	4
Large ice crystals	5.5	6.42	9.2	2
Packed snow (of type shown in Fig. 3 & 4)	5.5	7.77	1.4	5
Slab of ice ^a	2	15.05	1.2	-

^aMade from distilled water.




FIGURE 2. Ice Crystals Formed by Spraying Cold Water into 20° F Chamber




FIGURE 3. Snow Formed by Spraying Hot Water into -50°F Chamber




FIGURE 4. Snow Formed by Spraying Cold Water into -50°F Chamber




FIGURE 5. Packed Snow (of type shown in Figures 3 and 4) Formed by Spraying
Hot Water into -50°F Chamber

Handwritten mark



FIGURE 6. Particle of Snow Formed by Spraying Hot Water into -50°F Chamber

In all cases the reflection was about 7.9 percent. The error in measurement is within ± 0.5 db for all measurements of attenuation and reflection.

The table shows that the loss in transmitted signal is highest for fine snow with local packed areas and for the large ice crystals. Because the fine loose snow and the packed snow apparently caused less scattering of the radiation, these two types were believed to be more homogeneous than the other samples. The measurements given for the snow sample were consistent from 32 to 39 GHz. The ice sample was measured only at 39 GHz.

CONCLUSIONS

Since the snow samples used in Reference 1 were not photographed, it is not known if the previous samples were identical with those shown here. However, the fact that the results obtained in both cases appear to be comparable indicates that the samples were at least similar. One cannot conclude, however, that the results thus obtained are identical with those that would be obtained from natural snow. Although the densities are very similar to those reported in Reference 3 for natural snow, it is not known whether the transmission characteristics would remain the same for the packed artificial snow spheres and the packed natural snow flakes. It must be concluded, therefore, that these measurements cannot be meaningful until a comparison is made with similar measurements taken on naturally formed snow.

REFERENCES

1. J. W. Battles and D. E. Crane, NAVWEPS Report 8816, Millimeter Wave Attenuation Through Snow, Naval Ordnance Laboratory, Corona, California, 15 July 1965.
2. J. W. Battles and D. E. Crane, NAVWEPS Report 8201, Millimeter Interferometer, Naval Ordnance Laboratory, Corona, California, 1 August 1964.
3. Ice and Snow; Properties, Processes, and Applications (Proceedings of a conference held at the Massachusetts Institute of Technology, February 12-16, 1962), Ed. by W. D. Kingery. M. I. T. Press, Cambridge, Mass., 1963.

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1 ORIGINATING ACTIVITY (Corporate author) Naval Ordnance Laboratory Corona, California		2a REPORT SECURITY CLASSIFICATION Unclassified
		2b GROUP
3 REPORT TITLE ATTENUATION OF Ka-BAND ENERGY BY SNOW AND ICE		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5 AUTHOR(S) (Last name, first name, initial) Battles, James W., and Crane, Delbert E.		
6 REPORT DATE 10 August 1966	7a. TOTAL NO. OF PAGES 12	7b. NO. OF REFS 3
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S) NOLC Report 670	
b. PROJECT NO WEPTASK R360-FR-104/ 211-1/R011-01-01 and c AIR 360-016/211-1/S061 d.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10 AVAILABILITY/LIMITATION NOTICES Distribution of this report is unlimited		
11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY Naval Air Systems Command Navy Department	
13 ABSTRACT Measurements of the attenuation of electromagnetic energy by snow and the reflection of radiation from snow and ice were made by using an interferometer and manufactured snow and ice in an environmental chamber under closely controlled conditions. The ambient temperature was held at -14° F for all measurements. Snow and ice attenuation and reflection measurements are tabulated for various snow densities covering the range from 32 to 39 GHz. Results show that packed snow and greater density produce less attenuation.		

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Mapping, Radiometer Radiation Electromagnetic Snow-reflected Snow-attenuated						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY.** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION.** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S).** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE.** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES.** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES.** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S).** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES.** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS) (S) (C) or (U)

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.