

AD 680791

MEASUREMENTS OF THE STATIC PRESSURE DISTRIBUTIONS AND SHOCK SHAPE ON AN OBLATE SPHEROID AT MACH NUMBERS OF 3 and 6

NOL

5 JULY 1966

UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOLTR 66-138

| | | | |
|--|------------|----|----|
| CLEARINGHOUSE FOR FEDERAL SCIENTIFIC AND TECHNICAL INFORMATION | | | |
| Hardcopy | Microfiche | 23 | AD |
| \$ 1.00 | \$.50 | pp | |
| / ARCHIVE COPY | | | |

DDG
 SEP 26 1966
 C

Distribution of this document is unlimited.

Aerodynamics Research Report No. 265

MEASUREMENTS OF THE STATIC PRESSURE DISTRIBUTIONS AND
SHOCK SHAPE ON AN OBLATE SPHEROID AT MACH
NUMBERS OF 3 AND 6

by

Lionel Pasiuk

ABSTRACT: The results of experimental measurements of the static pressure distribution and bow shock shape on an oblate spheroid are presented. This experiment was conducted at nominal Mach numbers of 3 and 6 and a free stream Reynolds number range of 2.3×10^5 to 5.8×10^6 per foot. Comparisons are made with the calculated values of several different laboratories.

U. S. Naval Ordnance Laboratory
White Oak, Silver Spring, Maryland

5 July 1966

Measurements of the Static Pressure Distribution and Shock Shape
on an Oblate Spheroid at Mach Numbers of 3 and 6

This report presents the results of an experimental project at the request of the Office of Naval Research. In a separate program the Office of Naval Research had found that analytical results, performed at various laboratories, gave widely different results for the pressure distribution and shock shape on a blunt body in supersonic flow. The purpose of the present experiments was to identify which analytical prediction was correct.

The experiments were carried out in Supersonic Tunnel No. 2 and the hypersonic Tunnel at the U. S. Naval Ordnance Laboratory.

J. A. DARE
Captain, USN
Commander

K. R. ENKENDES
by direction

CONTENTS

| | Page |
|--------------------------------|------|
| INTRODUCTION..... | 1 |
| EXPERIMENTS..... | 1 |
| Model..... | 1 |
| Test Facilities..... | 2 |
| Instrumentation..... | 2 |
| Experimental Procedure..... | 3 |
| Possible Sources of Error..... | 3 |
| Data Reduction..... | 4 |
| Pressure..... | 4 |
| Shock Shape..... | 4 |
| RESULTS..... | 4 |
| Pressure..... | 4 |
| Shock Shape..... | 5 |
| CONCLUSIONS..... | 5 |
| REFERENCE..... | 6 |

ILLUSTRATIONS

- Figure 1 Sketch of the oblate spheroid showing pressure tap locations.
- Figure 2 Photograph of the oblate spheroid model.
- Figure 3 Schematic diagram of the test setup.
- Figure 4 Comparison between the experimental and calculated values of the surface pressure on the oblate spheroid model at $M \approx 3$.
- Figure 5 Comparison between the experimental and calculated values of the surface pressure on the oblate spheroid model at $M \approx 6$.
- Figure 6 Schlieren photograph of the shock wave and model at $M \approx 3$.
- Figure 7 Schlieren photograph of the shock wave and model at $M \approx 6$.
- Figure 8 Comparison between the experimental and calculated values of the shock wave produced by the oblate spheroid model at $M \approx 3$.

TABLES

- Table 1 Comparison Between Measured and Desired Model Contour
- Table 2 Experimental Pressure Distribution on an Oblate Spheroid

SYMBOLS

| | |
|-----------------|--|
| a | major axis of the oblate spheroid |
| B | bluntness parameter of the oblate spheroid, $B = (a/b)^2$ |
| b | minor axis of the oblate spheroid |
| D | model base diameter |
| M | Mach number |
| P | dimensionless pressure, $P = p/\rho_\infty u_\infty^2$ |
| p | pressure |
| P ₀ | supply pressure |
| R | coordinate normal to the flow |
| R _c | model radius of curvature at the stagnation point |
| Re _D | Reynolds number based on model diameter, $Re_D = \rho_\infty u_\infty D / \mu_\infty$ |
| r | nondimensional coordinate normal to the flow, $r = R/R_c$ |
| T ₀ | supply temperature |
| u _∞ | free stream velocity |
| Z | coordinate in the flow direction |
| Z _M | measured Z coordinate of the model |
| z | nondimensional coordinate in the flow direction, $z = Z/R_c$ |
| μ _∞ | absolute viscosity in the free stream |
| ρ _∞ | density in the free stream |
| φ | roll angle |

INTRODUCTION

Comparisons of various numerical calculations of the detached shock flow field about a series of blunt bodies were made at the Naval Weapons Laboratory under the sponsorship of the Office of Naval Research. Calculations were performed by several government and private laboratories on ellipsoids of revolution of various degrees of bluntness. Details of these methods and the results of the calculations are given in reference (1). This report contains the results of surface pressure and detailed shock wave measurements on one of these bodies and compares the experimental results with the corresponding numerical calculations

EXPERIMENTS

Model

The model is an oblate spheroid. A sketch is given in Figure 1 and a photograph in Figure 2. To make the photograph a mirror was placed behind the model so that both its front and back may be seen. Its degree of bluntness B , is defined as the ratio of its major to minor axis squared,

$$B = (a/b)^2$$

and for this model $B = 4$. Both the maximum diameter D , and the radius of curvature at the stagnation point R_c , have values of 4 inches. The contour is given by the following equation,

$$r = 2[z(2-z)]^{\frac{1}{2}}$$

when the origin is taken as the stagnation point. This contour is continued in the base region.

There are 24 pressure orifices on the model, each with a diameter of 0.030 inches. The location of these orifices is given in the table in Figure 1.

The model's original surface finish was 32 microinches, and this finish remained the same through the $M \approx 3$ test in Supersonic Tunnel No. 2. But during the test in the Hypersonic Tunnel at $M \approx 6$, the surface finish became very rough on the windward half of the model and this roughness is now measured to be from 60 to 85 microinches.

Both the model and pressure tubing are made from stainless steel. The tubes are connected to the model with high temperature silver solder.

Test Facilities

These tests were made in Supersonic Tunnel No. 2 and the Hypersonic Tunnel of the Naval Ordnance Laboratory. The boundary layer on the model was laminar in all cases. The tunnel running conditions were as follows:

Supersonic Tunnel No. 2:

| | |
|-----------------------------------|--|
| Mach Number | = 3.04 |
| Supply Pressure | = 15.7 to 34.7 lb/in ² abs. |
| Supply Temperature | = 59 to 68 ^o F |
| Reynolds Number per foot | = 2.6×10^6 to 5.8×10^6 |
| Reynolds number based on diameter | = 0.87×10^6 to 1.93×10^6 |

Hypersonic Tunnel:

| | |
|-----------------------------------|--|
| Mach Number | = 5.98 |
| Supply Pressure | = 177 to 444 lb/in ² abs. |
| Supply Temperature | = 631 to 667 ^o F |
| Reynolds Number per foot | = 2.3×10^6 to 5.5×10^6 |
| Reynolds Number based on diameter | = 0.77×10^6 to 1.83×10^6 |

Instrumentation

Figure 3 is a schematic diagram of the pressure instrumentation setup. Each pressure tap is connected to a pressure transducer by stainless steel tubing. The transducer is mounted is a pressure switch capable of holding 48 transducers and switching each one from model to calibration pressures. The electrical signal from the transducer is recorded on magnetic tape by the DARE data readout system. This system is capable of continuously recording 100 inputs per second. At the same time two pressure taps are monitored on plotters. These two pressure taps are at the same r location 180 degrees apart and are used to aerodynamically align the model.

Two brands of transducers are used. They are the CEC 312 and the Statham 130. For the pressures on the windward half of the model, 0 to 15 psia transducers are used, whereas the pressures on the leeward half were read on 0 to 5 psia transducers.

Experimental Procedure

The experimental procedure was essentially the same for both wind tunnel tests. The model was oriented in the test section so that all of the pressure taps lie in the same pitch plane. Then all pressure tube connections were made and the pressure measuring system was checked for leaks. Immediately before each data run was made, each transducer was calibrated at values of 0, 0.5, 1.0, 10.0 and 15.0 lb/in² absolute.

During each data run the following steps were followed:

1. Supply pressure and temperature were stabilized at the desired value.
2. Pressures recorded on the two plotters were observed. If the model is aligned with the flow these pressures will be equal.
3. The data were continuously recorded on magnetic tape for approximately 10 seconds giving 10 data points for each tap.
4. While the pressure data were being recorded, schlieren pictures of the flow field were photographed.

Possible Sources of Error

Measurements of the model contour were made after the tests and these measurements were not identical to the design values. Table I gives the measured and design values of the contours. As can be seen, the error in the contour becomes greater as r increases and the maximum absolute error in z is 0.007 inches. These small errors give a model that is a little more blunt. Based on a Newtonian pressure distribution, the error is less than 1.5 percent.

The sensitivity of the data readout system was better than one percent.

The transducers used were stable with time. Drift from calibration to calibration was no more than 0.5 percent for 95 percent of the transducers and none drifted more than 2.0 percent.

The gages used to read the calibration pressures are less than 0.5 percent in error.

The model was not in exact alignment with the flow. For the $M = 3$ and $M = 6$ data the percent pressure difference due to misalignment was up to 1.0 percent and 2.0 percent, respectively.

Therefore, the pressure error due to misalignment is not more than 0.5 percent and 1.0 percent for the M = 3 and M = 6 data, respectively.

The schlieren photographs of the shock shape were made with 70 millimeter black and white film. The expected dimensional change of this film is less than 0.2 percent. This is well below the measurement errors. Quantitative measurements of the shock shape were obtained by reading the negatives on a tele-reader. The tele-reader gave from 100 to 125 counts between the shock and the body, and a measurement between two clearly defined points could be made to within one count. The degree of scatter of these measurements is caused by the poor definition of the shock.

Data Reduction

Pressure

Before reducing the data the pressure calibrations of each transducer were plotted and found to be linear in the range of pressures encountered during the tests. Then each pressure measurement was reduced by linear interpolation between the two nearest calibration points.

Shock Shape

The shock shape was measured on a telereader. This instrument projects the negative on a frosted screen through an optical system. Superimposed over the negative's image were vertical and horizontal cross-hairs. The negative was adjusted so that the model was aligned with the cross-hairs and the telereader was zeroed at the stagnation point. The z position of the shock model was measured for various values of r and the corresponding count readings were punched on data cards. Then these counts were reduced to inches on the IBM 7090 computer.

RESULTS

Pressure

Table 2 contains a list of the pressure measurements for both M = 3.04 and M = 5.98 data. The pressure data are ratioed to ∞^2 and the model coordinates are made dimensionless with respect to the radius of curvature at the stagnation point (4 inches for this model).

Figure 4 is a plot of the M = 3 pressure data along with several calculated curves. As can be seen, the curves generated by MIT, AVCO, NASA, and NWL are in best agreement with the

experimental data. The curve labeled DOUGLAS 1 follows the experimental data for $0 \leq r \leq 0.35$, then falls slightly below. NORTHROP's calculations are in agreement for $0 \leq r \leq 0.3$.

Presented in Figure 5 is the data for $M \approx 6$. Again the NASA and NWL curves are in best agreement along with the DOUGLAS 1 and DOUGLAS 2 curves. The calculated values of NORTHROP are in good agreement in the range $0 \leq r \leq 0.325$. Here the MIT and AVCO curves fall somewhat below the experimental data.

The direct method of calculating the flow field is used by MIT, AVCO, and NWL, whereas NASA and DOUGLAS 1 use the inverse method. For a more complete description of the calculated values, see reference (1).

Shock Shape

Figures 6 and 7 are schlieren photographs of the bow wave and model at Mach numbers of 3.04 and 5.98, respectively. The $M = 3.04$ shock shape measurements are compared with the calculated values in Figure 8. The shock shapes generated by NASA, DOUGLAS 1, NWL, NORTHROP, MIT, and AVCO are in best agreement with the experimental data. For the most part, these agreements are consistent with the pressure results.

Due to the increase in the scatter of the shock measurements at $M = 5.98$, the comparisons with calculated values are not as certain as those made with the $M = 3.04$ data. It appears that the results at Mach 5.98 are very similar to those at Mach 3.04.

CONCLUSIONS

The results of experimental static pressure and shock shape measurements on an oblate spheroid have been presented. These results show that the calculations of NASA, DOUGLAS 1, and NWL are consistently in good agreement with the experimental data. Also, the predictions of NORTHROP are in good agreement with experiments from the stagnation point to $r = 0.3$.

REFERENCE

- (1) Perry, J., "A Comparison of Solutions to Some Blunt Body Problems," to be published as a report by the U. S. Naval Weapons Laboratory, Dahlgren, Virginia

TABLE 1

COMPARISON BETWEEN MEASURED AND DESIRED MODEL CONTOUR

| R (in.) | Measured Z_m (in.) | Design Z (in.) | $Z - Z_m$ (in.) |
|------------|----------------------------|------------------------|--------------------|
| 0 | 0 | 0 | 0 |
| .1 | .0010 | .0010 | 0 |
| .2 | .0046 | .0040 | -.0006 |
| .3 | .0107 | .0110 | .0003 |
| .4 | .0169 | .0200 | .0004 |
| .5 | .0308 | .0320 | .0012 |
| .6 | .0449 | .0460 | .0011 |
| .7 | .0617 | .0630 | .0013 |
| .8 | .0818 | .0840 | .0022 |
| .9 | .1048 | .1060 | .0012 |
| 1.0 | .1316 | .1340 | .0024 |
| 1.1 | .1622 | .1640 | .0018 |
| 1.2 | .1969 | .2000 | .0031 |
| 1.3 | .2366 | .2400 | .0034 |
| 1.4 | .2824 | .2860 | .0036 |
| 1.5 | .3349 | .3380 | .0031 |
| 1.6 | .3953 | .4000 | .0074 |
| 1.7 | | .4980 | |
| 1.8 | .5585 | .5640 | .0055 |
| 1.9 | .6807 | .6880 | .0073 |
| 2.0 | | 1.0000 | |

TABLE 2

EXPERIMENTAL PRESSURE DISTRIBUTION ON AN OBLATE SPHEROID

Bluntness Parameter $B = 4$
 Radius of Curvature at Stagnation Point, $R_c = 4$ inches
 Maximum Diameter = 4 inches

$M = 5.98$
 $p_o = 443.6 \text{ lb/in}^2 \text{ abs.}$
 $T_o = 631^\circ\text{F}$
 $Re_D = 1.92 \times 10^6$

$M = 3.04$
 $p_o = 31.1 \text{ lb/in}^2 \text{ abs.}$
 $T_o = 68^\circ\text{F}$
 $Re_D = 1.70 \times 10^6$

| r | P | | | r | P | | |
|-------|----------------|------------------|---------------------------|-------|----------------|------------------|---------------------------|
| | $\phi=0^\circ$ | $\phi=180^\circ$ | Leeward $\phi=0^\circ$ | | $\phi=0^\circ$ | $\phi=180^\circ$ | Leeward $\phi=0^\circ$ |
| 0 | .930 | | | 0 | .956 | | |
| 0.050 | .928 | | | 0.050 | .955 | | |
| 0.100 | .914 | .910 | | 0.100 | .943 | | |
| 0.150 | | | | 0.150 | .919 | | |
| 0.200 | .868 | .874 | .0169 | 0.200 | .882 | | .0374 |
| 0.250 | .821 | | | 0.250 | | | |
| 0.300 | .764 | .780 | .0163 | 0.300 | .794 | .801 | .0355 |
| 0.325 | .720 | | | 0.325 | .757 | | |
| 0.350 | .675 | | .0167 | 0.350 | .708 | | .0398 |
| 0.375 | .626 | | | 0.375 | .661 | | |
| 0.400 | .558 | .568 | .0163 | 0.400 | .598 | .596 | .0381 |
| 0.425 | .475 | | | 0.425 | .514 | | |
| 0.450 | .378 | | .0164 | 0.450 | .405 | | .0372 |
| 0.500 | .043 | .043 | | 0.500 | .052 | .050 | |




FIG. 1 SKETCH OF THE OBLATE SPHEROID SHOWING PRESSURE TAP LOCATIONS



FIG. 2 PHOTOGRAPH OF THE OBLATE SPHEROID MODEL




FIG. 2 SCHEMATIC DIAGRAM OF THE TEST SET-UP




FIG. .





FIG. 4 COMPARISON BETWEEN THE EXPERIMENTAL AND CALCULATED VALUES OF THE SURFACE PRESSURE ON THE OBLATE SPHEROID MODEL AT $M \approx 3$.



A




FIG. 5 COMPARISON BETWEEN THE EXPERIMENTAL AND CALCULATED VALUES OF THE SURFACE PRESSURE ON THE OBLATE SPHEROID MODEL AT $M = 6$

B




FIG. 6 SCHLIEREN PHOTOGRAPH OF THE SHOCK WAVE AND MODEL AT $M = 3$




FIG. 1. SCHEMATIC PHOTOGRAPH OF THE SHOCK WAVE AND MODEL AT $M =$




FIG. 8 COMPARISON BETWEEN THE EXPERIMENTAL AND CALCULATED VALUES OF THE SHOCK WAVE PRODUCED BY THE OBLATE SPHEROID MODEL AT $M = 3$.

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

| | <u>No. of Copies</u> |
|--|--------------------------|
| Commander, Naval Ordnance Systems Command Department of the Navy Washington, D. C. 20360 Attn: ORD 034 Attn: ORD 03211 Attn: ORD 0351 | 2 |
| Commander, Naval Air Systems Command Department of the Navy Washington, D. C. 20360 Attn: AIR 604 Attn: AIR 03C Attn: AIR 320 | 2 |
| Office of Naval Research T-3 Washington, D. C. 20390 Attn: Head, Structural Mechanics Branch Attn: Head, Fluid Dynamics Branch | |
| Director, David Taylor Model Basin Aerodynamics Laboratory Washington, D. C. 20007 Attn: Library | |
| Commander, U. S. Naval Ordnance Test Station China Lake, California 93557 Attn: Technical Library Attn: Code 406 | |
| Director, Naval Research Laboratory Washington, D. C. 20390 Attn: Code 2027 | |
| Commanding Officer Office of Naval Research Branch Office Box 39, Navy 100 FPO, New York, New York 09510 | |
| NASA High Speed Flight Station Box 273 Edwards Air Force Base, California 93523 | |
| NASA Ames Research Center Moffett Field, California 94035 Attn: Librarian | |

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

No. of
Copies

NASA
Langley Research Center
Langley Station, Hampton, Virginia 23362
Attn: (Mrs.) Elizabeth R. Gilman, Librarian, Bldg. 1244
Attn: C. H. McLellan

Attn: Comp. Res. Div.
Attn: Theoretical Aerodynamics Division

NASA
Lewis Research Center
21000 Brookpark Road
Cleveland 11, Ohio 44135
Attn: Librarian
Attn: Chief, Propulsion Aerodynamics Division

NASA
600 Independence Ave., S. W.
Washington, D. C. 20546
Attn: Chief, Division of Research Information
Attn: Dr. H. H. Kurzweg, Director of Research

Office of the Assistant Secretary of Defense (R&D)
Room 3E1065, The Pentagon
Washington 25, D. C. 20301
Attn: Technical Library

Research and Development Board
Room 3D1041, The Pentagon
Washington 25, D. C. 20301
Attn: Library

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314

20

Commander, Pacific Missile Range
Point Mugu, California 93041
Attn: Technical Library

Commanding General
Aberdeen Proving Ground, Maryland 21005
Attn: Technical Information Branch
Attn: Ballistic Research Laboratories

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)

No. of
Copies

Commander, Naval Weapons Laboratory
Dahlgren, Virginia 22448
Attn: Library

Director, Special Projects
Department of the Navy
Washington 25, D. C. 20360
Attn: SP-2722

Director of Intelligence
Headquarters, USAF
Washington 25, D. C. 20330
Attn: AFOIN-3B

Headquarters - Aero. Systems Division
Wright-Patterson Air Force Base
Dayton, Ohio 45433
Attn: WWAD
Attn: RRLA-Library

2

Commander
Air Force Ballistic Systems Division
Norton Air Force Base
San Bernardino, California 92409
Attn: BSRVA

2

Chief, Defense Atomic Support Agency
Washington 25, D. C. 20360
Attn: Document Library

Headquarters, Arnold Engineering Development Center
ARO, Inc.
Arnold Air Force Station, Tennessee 37389
Attn: Technical Library
Attn: AEOR
Attn: AEOIM

Commanding Officer, Harry Diamond Laboratories
Washington 25, D. C. 20438
Attn: Library, Room 211, Bldg. 92

Commanding General
U. S. Army Missile Command
Redstone Arsenal, Alabama 35808
Attn: AMSMI-RR (Mr. N. Shapiro)
Attn: AMSMI-RB (Redstone Scientific Information
Center)

**AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A1)**

No. of
Copies

NASA

**George C. Marshall Space Flight Center
Huntsville, Alabama 35812**

**Attn: Dr. E. Geissler
Attn: Mr. T. Reed
Attn: Mr. H. Paul
Attn: Mr. W. Dahm
Attn: Mr. H. A. Connell
Attn: Mr. J. Kingsbury
Attn: ARDAB-DA**

APL/JHU (NOw 7386)

**8621 Georgia Avenue
Silver Spring, Maryland 20910**

**Attn: Technical Reports Group
Attn: Mr. Richard Suess
Attn: Dr. F. Hill
Attn: Dr. L. L. Cronvich**

2

Scientific & Technical Information Facility

**P. O. Box 5700
Bethesda, Maryland 20014**

Attn: NASA Representative (S-AKAKL)

Commander

**Air Force Flight Test Center
Edwards Air Force Base
Muroc, California 93523**

Attn: FTOTL

Air Force Office of Scientific Research

**Holloman Air Force Base
Alamogordo, New Mexico 88310**

Attn: SRLTL

**U. S. Army Engineer Research & Development
Laboratories**

Fort Belvoir, Virginia 22060

Attn: STINFO Branch

Aerospace Research Laboratories

**Wright-Patterson Air Force Base
Ohio 45433**

**Attn: Thermo-Mechanics Research
Laboratory (ARN)**

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

University of Minnesota
Minneapolis 14, Minnesota 55455
Attn: Dr. E. R. G. Eckert
Attn: Heat Transfer Laboratory
Attn: Technical Library

Rensselaer Polytechnic Institute
Troy, New York 12180
Attn: Dept. of Aeronautical Engineering

Dr. James P. Hartnett
Department of Mechanical Engineering
University of Delaware
Newark, Delaware 19711

Princeton University
James Forrestal Research Center
Gas Dynamics Laboratory
Princeton, New Jersey 08540
Attn: Prof. S. Bogdonoff
Attn: Dept. of Aeronautical Engineering Library

Defense Research Laboratory
The University of Texas
P. O. Box 8029
Austin 12, Texas 78712
Attn: Assistant Director

Ohio State University
Columbus 10, Ohio 43210
Attn: Security Officer
Attn: Aerodynamics Laboratory
Attn: Dr. J. Lee
Attn: Chairman, Dept. of Aero. Engineering

California Institute of Technology
Pasadena, California 91109
Attn: Guggenheim Aero. Laboratory,
Aeronautics Library
Attn: Jet Propulsion Laboratory
Attn: Dr. H. Liepmann
Attn: Dr. L. Lees
Attn: Dr. D. Coles
Attn: Dr. A. Roshko

Case Institute of Technology
Cleveland 6, Ohio 44106
Attn: G. Kuerti

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

North American Aviation, Inc.
Aerophysics Laboratory
Downey, California 90241
Attn: Chief, Aerophysics Laboratory
Attn: Missile Division (Library)

Department of Engineering
and Applied Sciences
Yale University
400 Temple Street
New Haven, Connecticut 06520
Attn: Dr. P. P. Wegener

MIT Lincoln Laboratory
Lexington, Massachusetts 02173

RAND Corporation
1700 Main Street
Santa Monica, California 90401
Attn: Library, USAF Project RAND
Attn: Technical Communications

Mr. J. Lukasiewicz, Chief
Gas Dynamics Facility
ARO, Incorporated
Tullahoma, Tennessee 37389

Massachusetts Institute of Technology
Cambridge 39, Massachusetts 02139
Attn: Prof. J. Kaye
Attn: Prof. M. Finston
Attn: Mr. J. Baron
Attn: Prof. A. H. Shapiro
Attn: Naval Supersonic Laboratory
Attn: Aero. Engineering Library
Attn: Prof. Ronald F. Probststein
Attn: Prof. C. C. Lin

Polytechnic Institute of Brooklyn
527 Atlantic Avenue
Freeport, New York 11735
Attn: Dr. M. Bloom
Attn: Aerodynamics Laboratory

Brown University
Division of Engineering
Providence, Rhode Island 02912
Attn: Librarian

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Air Ballistics Laboratory
Army Ballistic Missile Agency
Huntsville, Alabama 35809

Applied Mechanics Reviews
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas 78228

BUWEPS Representative
Aerojet-General Corporation
6352 N. Irwindale Avenue
Azusa, California 91702

The Boeing Company
Seattle, Washington 98124
Attn: J. H. Russell, Aero-Space Division
Attn: Research Library

United Aircraft Corporation
400 Main Street
East Hartford 8, Connecticut 06118
Attn: Chief Librarian
Attn: Mr. W. Kuhrt, Research Department
Attn: Mr. J. G. Lee

2

Hughes Aircraft Company 90230
Florence Avenue at Teale Streets
Culver City, California
Attn: Mr. D. J. Johnson
R&D Technical Library

McDonnell Aircraft Corporation
P. O. Box 516
St. Louis 3, Missouri 63166

Lockheed Missiles and Space Company
P. O. Box 504
Sunnyvale, California 94086
Attn: Dr. L. H. Wilson
Attn: Mr. M. Tucker
Attn: Dr. R. Smelt

Martin Company
Baltimore, Maryland 21220
Attn: Library
Attn: Chief Aerodynamicist
Attn: Dr. W. Morkovin, Aerophysics Division

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

CONVAIR
A Division of General Dynamics Corporation
Fort Worth, Texas 76101
Attn: Library
Attn: Theoretical Aerodynamics Group

Purdue University
School of Aeronautical & Engineering Sciences
LaFayette, Indiana 47907
Attn: R. L. Taggart, Library

University of Maryland
College Park, Maryland 20742
Attn: Director
Attn: Dr. J. Burgers
Attn: Librarian, Engr. & Physical Sciences
Attn: Librarian, Institute for Fluid Dynamics
and Applied Mathematics
Attn: Prof. S. I. Pai

2

University of Michigan
Ann Arbor, Michigan 48104
Attn: Dr. A. Kuethe
Attn: Dr. A. Laporte
Attn: Department of Aeronautical Engineering

Stanford University
Palo Alto, California 94305
Attn: Applied Mathematics & Statistics Lab.
Attn: Prof. D. Bershader, Dept. of Aero. Engr.

Cornell University
Graduate School of Aeronautical Engineering
Ithaca, New York 14850
Attn: Prof. W. R. Sears

The Johns Hopkins University
Charles and 34th Streets
Baltimore, Maryland 21218
Attn: Dr. F. H. Clauser

University of California
Berkeley 4, California 94720
Attn: G. Maslach
Attn: Dr. S. A. Schaaf
Attn: Dr. Holt
Attn: Institute of Engineering Research

**AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)**

**No. of
Copies**

Cornell Aeronautical Laboratory, Inc.
4455 Genesee Street
Buffalo 21, New York 14225
Attn: Librarian
Attn: Dr. Franklin Moore
Attn: Dr. J. G. Hall
Attn: Mr. A. Hertzberg

University of Minnesota
Rosemount Research Laboratories
Rosemount, Minnesota 55068
Attn: Technical Library

Director, Air University Library
Maxwell Air Force Base, Alabama 36112

Douglas Aircraft Company, Inc.
Santa Monica Division
3000 Ocean Park Boulevard
Santa Monica, California 90405
Attn: Chief Missiles Engineer
Attn: Aerodynamics Section

CONVAIR
A Division of General Dynamics Corporation
Daingerfield, Texas 75638

CONVAIR
Scientific Research Laboratory
5001 Kearney Villa Road
San Diego, California 92123
Attn: Asst. to the Director of Scientific Research
Attn: Dr. B. M. Leadon
Attn: Library

Republic Aviation Corporation
Farmingdale, New York 11735
Attn: Technical Library

General Applied Science Laboratories, Inc.
Herrick and Stewart Avenues
Westbury, L. I., New York 11590
Attn: Mr. R. W. Byrne

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Arnold Research Organization, Inc.
Tullahoma, Tennessee 37389
Attn: Technical Library
Attn: Chief, Propulsion Wind Tunnel
Attn: Dr. J. L. Potter

General Electric Company
Missile Space Division
3198 Chestnut Street
Philadelphia, Pennsylvania 19104
Attn: Larry Chasen, Mgr. Library 2
Attn: Mr. R. Kirby
Attn: Dr. J. Farber
Attn: Dr. G. Sutton
Attn: Dr. J. D. Stewart
Attn: Dr. S. M. Scala
Attn: Dr. H. Lew
Attn: Mr. J. Persh

Eastman Kodak Company
Navy Ordnance Division
50 West Main Street
Rochester 14, New York 14614
Attn: W. B. Forman 2

Library 3
AVCO-Everett Research Laboratory
2385 Revere Beach Parkway
Everett 49, Massachusetts 02149

Chalce-Vought Corp.
Post Office Box 5907
Dallas, Texas 75222
Library 1-6310/3L-2884

National Science Foundation
1951 Constitution Avenue, N. W.
Washington 25, D. C. 20550
Attn: Engineering Sciences Division

New York University
University Heights
New York 53, New York 10453
Attn: Department of Aeronautical Engineering

AERODYNAMICS LABORATORY
EXTERNAL DISTRIBUTION LIST (12)

No. of
Copies

New York University
25 Waverly Place
New York, New York 10003
Attn: Library, Institute of Math. Sciences

NORAIR
A Division of Northrop Corporation
Hawthorne, California 90250
Attn: Library

Northrop Aircraft, Inc.
Hawthorne, California 90250
Attn: Library

Gas Dynamics Laboratory
Technological Institute
Northwestern University
Evanston, Illinois 60201
Attn: Library

Pennsylvania State University
University Park, Pennsylvania 16802
Attn: Library, Dept. of Aero. Engineering

The Ramo-Wouldridge Corporation
8820 Bellanca Avenue
Los Angeles 45, California 90045

Gifts and Exchanges
Fondren Library
Rice Institute
P. O. Box 1892
Houston, Texas 77001

University of Southern California
Engineering Center
Los Angeles 7, California 90007
Attn: Librarian

The Editor
Battelle Technical Review
Battelle Memorial Institute
505 King Avenue
Columbus, Ohio 43201

Douglas Aircraft Company, Inc.
Long Beach, California 90801
Attn: Library

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Fluidyne Engineering Corporation
5740 Wayzata Boulevard
Golden Valley
Minneapolis, Minnesota 55416

Grumman Aircraft Engineering Corporation
Bethpage, Long Island, New York 11714

Lockheed Missiles and Space Company
P. O. Box 551
Burbank, California 91503
Attn: Library
Attn: M. Laden

Marquardt Aircraft Corporation
7801 Havenhurst
Van Nuys, California 91406

Martin Company
Denver, Colorado 80201

Martin Company
Orlando, Florida 32805
Attn: J. Mayer

Mississippi State College
Engineering and Industrial Research Station
Aerophysics Department
P. O. Box 248
State College, Mississippi 39762

Lockheed Missiles and Space Company
3251 Hanover Street
Palo Alto, California 94304
Attn: Library

General Electric Company
Research Laboratory
Schenectady, New York 12301
Attn: Dr. H. T. Nagamatsu
Attn: Library

Fluid Dynamics Laboratory
Mechanical Engineering Department
Stevens Institute of Technology
Hoboken, New Jersey 07030
Attn: Dr. R. H. Page, Director

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Department of Mechanical Engineering
University of Arizona
Tucson, Arizona 85721
Attn: Dr. E. K. Parks

Vitro Laboratories
200 Pleasant Valley Way
West Orange, New Jersey 07052

Department of Aeronautical Engineering
University of Washington
Seattle, Washington 98105
Attn: Prof. R. E. Street
Attn: Library

American Institute of Aeronautics & Astronautics
1290 Avenue of the Americas
New York, New York 10019
Attn: Managing Editor
Attn: Library

Department of Aeronautics
United States Air Force Academy
Colorado 80840

MHD Research, Inc.
Newport Beach, California 92660
Attn: Technical Director

University of Alabama
College of Engineering
University, Alabama 35486
Attn: Head, Dept. of Aeronautical
Engineering

ARDE Associates
100 W. Century Road
Paramus, New Jersey 07652
Attn: Mr. Edward Cooperman

Aeronautical Research Associates of Princeton
50 Washington Road
Princeton, New Jersey 08540
Attn: Dr. C. duP. Donaldson, President

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Daniel Guggenheim School of Aeronautics
Georgia Institute of Technology
Atlanta, Georgia 30332
Attn: Prof. A. L. Ducoffe

University of Cincinnati
Cincinnati, Ohio 45221
Attn: Prof. R. P. Harrington, Head
Dept. of Aeronautical Engineering
Attn: Prof. Ting Yi Li, Aerospace Engineering Dept.

Virginia Polytechnic Institute
Dept. of Aerospace Engineering
Blacksburg, Virginia 24061
Attn: Dr. R. T. Keefe
Attn: Dr. J. B. Eades, Jr.
Attn: Library

IBM Federal System Division
7220 Wisconsin Avenue
Bethesda, Maryland 20014
Attn: Dr. I. Korobkin

Superintendent
U. S. Naval Postgraduate School
Monterey, California 93940
Attn: Technical Reports Section Library

National Bureau of Standards
Washington 25, D. C. 20234
Attn: Chief, Fluid Mechanics Section

North Carolina State College
Raleigh, North Carolina 27607
Attn: Division of Engineering Research
Technical Library

Defense Research Corporation
P. O. Box No. 3587
Santa Barbara, California 93015
Attn: Dr. J. A. Laurmann

Aerojet-General Corporation
6352 North Irwindale Avenue
Box 296
Azusa, California 91702

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Apollo - DDCS
General Electric Company
A&E Building, Room 204
Daytona Beach, Florida 32014
Attn: Dave Novis

University of Minnesota
Institute of Technology
Minneapolis, Minnesota 55455
Attn: Prof. J. D. Akerman

Guggenheim Laboratory
Stanford University
Stanford, California 94305
Attn: Prof. D. Bershader, Department of Aero.
Engineering

Space Technology Laboratory, Inc.
1 Space Park
Redondo Beach, California 90278
Attn: STL Tech. Lib. Doc. Acquisitions

University of Illinois
Department of Aeronautical and Astronautical Engineering
Urbana, Illinois 61801
Attn: Prof. H. S. Stilwell

Armour Research Foundation
Illinois Institute of Technology
10 West 35th Street
Chicago, Illinois 60616
Attn: Dr. L. N. Wilson

Institute of the Aeronautical Sciences
Pacific Aeronautical Library
7600 Beverly Boulevard
Los Angeles, California 90036

University of California
Department of Mathematics
Los Angeles, California 90024
Attn: Prof. A. Robinson

Louisiana State University
Department of Aeronautical Engineering
College of Engineering
Baton Rouge, Louisiana 70803

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Mathematical Reviews
American Mathematical Society
80 Waterman Street
Providence, Rhode Island 02906

Stanford University
Department of Aeronautical Engineering
Stanford, California 94305
Attn: Library

University of California
Aeronautical Sciences Laboratory
Richmond Field Station
1301 South 46th Street
Richmond, California 94804

University of Denver
Department of Aeronautical Engineering
Denver 10, Colorado 80210

University of Chicago
Laboratories for Applied Sciences
Museum of Science and Industry
Chicago, Illinois 60601
Attn: Librarian

University of Colorado
Department of Aeronautical Engineering
Boulder, Colorado 80302

University of Illinois
Aeronautical Department
Champaign, Illinois 61820

University of Kentucky
Department of Aeronautical Engineering
College of Engineering
Lexington, Kentucky 40506

University of Toledo
Department of Aeronautical Engineering
Research Foundation
Toledo, Ohio 43606

AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)

No. of
Copies

Aerospace Corporation
P. O. Box 95085
Los Angeles, California 90045
Attn: Advanced Propulsion & Fluid Mechanics Department
Attn: Gas Dynamics Department

Boeing Scientific Research Laboratory
P. O. Box 3981
Seattle, Washington 98124
Attn: Dr. A. K. Sreekanth
Attn: G. J. Appenheimer

Vidya, Inc.
2626 Hanover
Palo Alto, California 94304
Attn: Mr. J. R. Stalder
Attn: Library

General Electric Company
FPD Technical Information Center F-22
Cincinnati, Ohio 45201

Northwestern University
Technological Institute
Evanston, Illinois 60201
Attn: Department of Mechanical Engineering

Harvard University
Cambridge, Massachusetts 02138
Attn: Prof. of Engineering Sciences & Applied Physics
Attn: Library

University of Wisconsin
P. O. Box 2127
Madison, Wisconsin 53706
Attn: Library

Dr. Antonio Ferri, Director
Guggenheim Aerospace Laboratories
New York University
181st St. and University Ave.
Bronx, New York 10453

**AERODYNAMICS DEPARTMENT
EXTERNAL DISTRIBUTION LIST (A2)**

**No. of
Copies**

Department of Aerospace & Mechanical
Engineering Sciences
University of California-San Diego
La Jolla, California 92037
Attn: Dr. P. A. Libby

University of New Mexico
Albuquerque, New Mexico 87106
Attn: Dr. Theodore Sparks

Notre Dame University
Southbend, Indiana 46556
Attn: Dr. John D. Nicolaides
Department of Aerospace Engineering

Dr. John Laufer, Chairman
University of Southern California
Graduate Department of Aerospace Studies
University Park
Los Angeles, California 90007

North American Aviation, Inc.
Los Angeles Division
International Airport
Los Angeles, California 90045
Attn: Library

Mr. Walter Jaskin, Consulting Engineer
Reentry Systems Dept., Systems and Technologies
General Electric Company
P. O. Box 8555
Philadelphia, Pennsylvania 19101

| DOCUMENT CONTROL DATA - R&D | | |
|---|---|--|
| <i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i> | | |
| 1 ORIGINATING ACTIVITY (Corporate author) U. S. Naval Ordnance Laboratory White Oak, Silver Spring, Maryland | | 2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED |
| | | 2b GROUP |
| 3 REPORT TITLE MEASUREMENTS OF THE STATIC PRESSURE DISTRIBUTIONS AND SHOCK SHAPE ON AN OBLATE SPHEROID AT MACH NUMBERS OF 3 AND 6 | | |
| 4 DESCRIPTIVE NOTES (Type of report and inclusive dates) FINAL | | |
| 5 AUTHOR(S) (Last name, first name, initial) PASIUK, LIONEL | | |
| 6 REPORT DATE 5 July 1966 | 7a TOTAL NO OF PAGES 21 | 7b NO OF REFS 1 |
| 8a CONTRACT OR GRANT NO | 9a ORIGINATOR'S REPORT NUMBER(S) | |
| b PROJECT NO NOL-936/CNR | NOLTR 66-138 | |
| c | 9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report) | |
| d | ARR - 265 | |
| 10 AVAILABILITY/LIMITATION NOTICES "Distribution of this document is unlimited." | | |
| 11 SUPPLEMENTARY NOTES | 12 SPONSORING MILITARY ACTIVITY Office of Naval Research | |
| 13 ABSTRACT <p>The results of experimental measurements of the static pressure distribution and bow shock shape on an oblate spheroid are presented. This experiment was conducted at nominal Mach numbers of 3 and 6 and a free stream Reynolds number range of 2.3×10^6 to 5.8×10^6 per foot. Comparisons are made with the calculated values of several different laboratories.</p> | | |

| 14 KEY WORDS | LINK A | | LINK B | | LINK C | |
|----------------------------|--------|----|--------|----|--------|----|
| | ROLE | WT | ROLE | WT | ROLE | WT |
| 1. pressure distributions | | | | | | |
| 2. shock wave | | | | | | |
| 3. experimental | | | | | | |
| 4. supersonic flow | | | | | | |
| 5. blunt body | | | | | | |
| 6. ellipsoid of revolution | | | | | | |
| 7. re-entry body | | | | | | |

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
4. **DESCRIPTIVE NOTES.** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).
10. **AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.